

Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
Rating Over Front of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements

LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and do not exceed 75% of a static tipping load over front of machine with crawlers blocked. Capacities based on structural competence are denoted by an asterisk (*).

Upper boom point capacity for liftcrane service with single part whip line is 13 610 kg or 27 220 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of jib, all load blocks, hooks, weight ball, slings, hoist lines, etc. beneath boom and jib point sheaves is considered part of main boom load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up and front tumbler properly blocked so that centerline of idler tumbler becomes tipping fulcrum. Travel drive must be to rear of machine. Swing is limited to that sector shown on Operating Range Diagram **No. 8029-A**. Refer to boom rigging

No. 192054, Wire Rope Specification chart **No. 8033-A**, and Counterweight Arrangement chart **No. 8026-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 9 373 mm crawlers, 1 219 mm treads, 8 534 mm retractable gantry, 12 part boom hoist reeving, boom support straps, and 76 750 kg counterweight.

Maximum Boom and Jib Lengths Lifted Unassisted Over Front of Blocked Crawlers			
WITHOUT BOOM CATWALKS		WITH BOOM CATWALKS	
Boom Length	Jib No. 132	Boom Length	Jib No. 132
(a)(b)100.6m	---	(a)(b) 97.5m	---
(a)(b) 97.5m	---	94.5m	---
94.5m	---	91.4m	---
91.4m	---	88.4m	---
88.4m	---	85.3m	12.2m
85.3m	12.2m	82.3m	24.4m
(b) 85.3m	18.3m	79.2m	30.5m
82.3m	24.4m	76.2m	36.6m
79.2m	30.5m		
(b) 79.2m	36.6m		

Load block, hook and weight ball on ground at start.

(a) Upper boom point cannot be used.

(b) Machine must be equipped with optional upperworks jacking cylinders.

Deduct From Capacities When Jib Is Attached	
Jib Length	Jib No. 132
12.2m	2 900 kg
18.3m	3 720 kg
24.3m	4 670 kg
30.5m	5 810 kg
36.6m	6 940 kg

Boom Catwalks Deduct
Deduct 300 kg from capacities when boom catwalks are attached.

Consult jib chart for jib capacities.

Upper boom point cannot be used when jib is attached.



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
Rating Over Front of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
57.9m (190 Ft.) BOOM			
9.8	82.7	59.8	95 200 *
10.0	82.4	59.8	95 200 *
11.0	81.4	59.6	95 200 *
12.0	80.4	59.5	95 200 *
13.0	79.4	59.3	95 200 *
14.0	78.4	59.1	92 800
15.0	77.4	58.9	83 700
16.0	76.4	58.6	75 900
18.0	74.3	58.1	63 900
20.0	72.3	57.5	54 900
22.0	70.2	56.8	47 900
24.0	68.0	56.0	42 300
26.0	65.9	55.1	37 800
28.0	63.7	54.2	34 000
30.0	61.5	53.1	30 800
32.0	59.2	52.0	28 100
34.0	56.8	50.7	25 700
36.0	54.4	49.3	23 600
38.0	51.9	47.8	21 800
40.0	49.4	46.1	20 200
42.0	46.7	44.3	18 700
44.0	43.9	42.3	17 400
46.0	40.9	40.1	16 200
48.0	37.8	37.6	15 100
50.0	34.4	34.8	14 100
52.0	30.7	31.6	13 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
61.0m (200 Ft.) BOOM			
9.8	83.0	62.9	95 200 *
10.0	82.8	62.9	95 200 *
11.0	81.9	62.7	95 200 *
12.0	80.9	62.6	95 200 *
13.0	80.0	62.4	95 200 *
14.0	79.0	62.2	92 600
15.0	78.0	62.0	83 400
16.0	77.1	61.8	75 700
18.0	75.1	61.3	63 600
20.0	73.2	60.7	54 600
22.0	71.2	60.0	47 600
24.0	69.2	59.3	42 100
26.0	67.2	58.5	37 500
28.0	65.1	57.6	33 700
30.0	63.0	56.6	30 500
32.0	60.9	55.5	27 800
34.0	58.7	54.3	25 400
36.0	56.4	53.0	23 300
38.0	54.2	51.6	21 500
40.0	51.8	50.1	19 800
42.0	49.3	48.4	18 400
44.0	46.8	46.6	17 100
46.0	44.1	44.6	15 900
48.0	41.4	42.4	14 800
50.0	38.4	40.0	13 800
52.0	35.2	37.3	12 900
54.0	31.8	34.2	12 100
56.0	28.0	30.7	11 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
64.0m (210 Ft.) BOOM			
10.4	82.8	65.9	95 200 *
11.0	82.3	65.8	95 200 *
12.0	81.3	65.7	95 200 *
13.0	80.4	65.5	95 200 *
14.0	79.5	65.3	92 500
15.0	78.6	65.1	83 300
16.0	77.7	64.9	75 600
18.0	75.9	64.4	63 500
20.0	74.0	63.9	54 500
22.0	72.1	63.2	47 500
24.0	70.2	62.5	41 900
26.0	68.3	61.8	37 400
28.0	66.4	60.9	33 600
30.0	64.4	60.0	30 400
32.0	62.4	59.0	27 700
34.0	60.3	57.9	25 300
36.0	58.2	56.7	23 200
38.0	56.1	55.4	21 400
40.0	53.9	53.9	19 700
42.0	51.7	52.4	18 300
44.0	49.3	50.7	17 000
46.0	46.9	48.9	15 800
48.0	44.4	46.9	14 700
50.0	41.7	44.8	13 700
52.0	39.0	42.4	12 800
54.0	36.0	39.7	12 000
56.0	32.8	36.8	11 200
58.0	29.3	33.4	10 500



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
Rating Over Front of Blocked Crawlers
No Travel - Limited Swing

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
67.1m (220 Ft.) BOOM			
11.0	82.6	68.9	95 200 *
12.0	81.7	68.7	95 200 *
13.0	80.9	68.6	95 000 *
14.0	80.0	68.4	92 300
15.0	79.1	68.2	83 100
16.0	78.3	68.0	75 400
18.0	76.5	67.6	63 300
20.0	74.7	67.0	54 300
22.0	73.0	66.4	47 300
24.0	71.2	65.8	41 700
26.0	69.3	65.0	37 100
28.0	67.5	64.2	33 300
30.0	65.6	63.4	30 100
32.0	63.7	62.4	27 400
34.0	61.8	61.4	25 000
36.0	59.9	60.2	22 900
38.0	57.8	59.0	21 100
40.0	55.8	57.7	19 400
42.0	53.7	56.2	18 000
44.0	51.5	54.7	16 700
46.0	49.3	53.0	15 500
48.0	47.0	51.2	14 400
50.0	44.6	49.2	13 400
52.0	42.1	47.1	12 500
54.0	39.5	44.8	11 700
56.0	36.7	42.2	10 900
58.0	33.7	39.3	10 200
60.0	30.4	36.1	9 600
62.0	26.8	32.3	8 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
70.1m (230 Ft.) BOOM			
11.0	83.0	72.0	89 000 *
12.0	82.1	71.8	87 500 *
13.0	81.3	71.7	86 100 *
14.0	80.5	71.5	84 800 *
15.0	79.6	71.3	82 400
16.0	78.8	71.1	76 100
18.0	77.1	70.7	63 100
20.0	75.4	70.2	54 000
22.0	73.7	69.6	47 000
24.0	72.0	69.0	41 400
26.0	70.3	68.3	36 900
28.0	68.5	67.5	33 100
30.0	66.8	66.7	29 900
32.0	65.0	65.8	27 100
34.0	63.1	64.8	24 700
36.0	61.3	63.7	22 600
38.0	59.4	62.6	20 800
40.0	57.5	61.3	19 200
42.0	55.5	60.0	17 700
44.0	53.5	58.6	16 400
46.0	51.4	57.0	15 200
48.0	49.3	55.3	14 200
50.0	47.1	53.5	13 100
52.0	44.8	51.6	12 300
54.0	42.4	49.4	11 400
56.0	39.9	47.1	10 600
58.0	37.3	44.6	9 900
60.0	34.5	41.8	9 300
62.0	31.4	38.7	8 700
64.0	28.1	35.1	8 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
73.2m (240 Ft.) BOOM			
11.6	82.8	75.0	85 300 *
12.0	82.4	74.9	84 700 *
13.0	81.6	74.8	83 400 *
14.0	80.9	74.6	82 300 *
15.0	80.1	74.4	81 100 *
16.0	79.3	74.2	76 800
18.0	77.7	73.8	62 800
20.0	76.0	73.3	53 800
22.0	74.4	72.8	46 800
24.0	72.8	72.2	41 200
26.0	71.1	71.5	36 600
28.0	69.5	70.8	32 800
30.0	67.8	70.0	29 600
32.0	66.1	69.1	26 800
34.0	64.4	68.2	24 400
36.0	62.6	67.2	22 300
38.0	60.8	66.1	20 500
40.0	59.0	64.9	18 900
42.0	57.1	63.7	17 400
44.0	55.3	62.3	16 100
46.0	53.3	60.9	14 900
48.0	51.3	59.3	13 800
50.0	49.3	57.6	12 800
52.0	47.2	55.8	11 900
54.0	45.0	53.9	11 100
56.0	42.7	51.8	10 300
58.0	40.3	49.5	9 600
60.0	37.8	47.0	9 000
62.0	35.2	44.3	8 300
64.0	32.3	41.2	7 800
66.0	29.2	37.8	7 200



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
Rating Over Front of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
76.2m (250 Ft.) BOOM			
12.2	82.6	78.0	81 100 *
13.0	82.0	77.8	80 100 *
14.0	81.2	77.7	79 000 *
15.0	80.5	77.5	77 700 *
16.0	79.7	77.3	74 200
18.0	78.2	76.9	62 900
20.0	76.6	76.5	53 600
22.0	75.1	76.0	46 600
24.0	73.5	75.4	41 000
26.0	71.9	74.8	36 500
28.0	70.3	74.1	32 600
30.0	68.7	73.3	29 400
32.0	67.1	72.5	26 700
34.0	65.4	71.6	24 300
36.0	63.8	70.6	22 200
38.0	62.1	69.6	20 400
40.0	60.4	68.5	18 700
42.0	58.6	67.3	17 300
44.0	56.8	66.0	16 000
46.0	55.0	64.6	14 800
48.0	53.1	63.2	13 700
50.0	51.2	61.6	12 700
52.0	49.3	59.9	11 800
54.0	47.2	58.1	11 000
56.0	45.2	56.2	10 200
58.0	43.0	54.1	9 500
60.0	40.7	51.8	8 800
62.0	38.3	49.4	8 200
64.0	35.8	46.7	7 600
66.0	33.1	43.8	7 100
68.0	30.3	40.5	6 600
70.0	27.1	36.8	6 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
79.2m (260 Ft.) BOOM			
12.2	82.9	81.0	78 200 *
13.0	82.3	80.9	77 400 *
14.0	81.6	80.8	75 800 *
15.0	80.8	80.6	73 700 *
16.0	80.1	80.4	71 500
18.0	78.6	80.1	62 900
20.0	77.1	79.6	53 400
22.0	75.7	79.1	46 400
24.0	74.2	78.6	40 800
26.0	72.6	78.0	36 200
28.0	71.1	77.3	32 400
30.0	69.6	76.6	29 100
32.0	68.0	75.8	26 400
34.0	66.5	74.9	24 000
36.0	64.9	74.0	21 900
38.0	63.3	73.0	20 100
40.0	61.6	72.0	18 400
42.0	60.0	70.8	16 900
44.0	58.3	69.6	15 600
46.0	56.5	68.3	14 400
48.0	54.8	67.0	13 400
50.0	53.0	65.5	12 400
52.0	51.1	63.9	11 500
54.0	49.3	62.2	10 700
56.0	47.3	60.4	9 900
58.0	45.3	58.5	9 200
60.0	43.2	56.4	8 500
62.0	41.1	54.2	7 900
64.0	38.8	51.8	7 300
66.0	36.4	49.2	6 800
68.0	33.9	46.3	6 300
70.0	31.2	43.1	5 800
72.0	28.2	39.6	5 400

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
82.3m (270 Ft.) BOOM			
12.8	82.7	84.0	70 000 *
13.0	82.6	84.0	69 900 *
14.0	81.9	83.9	69 300 *
15.0	81.2	83.7	68 500 *
16.0	80.5	83.5	67 200 *
18.0	79.1	83.2	61 800
20.0	77.6	82.7	53 100
22.0	76.2	82.3	46 100
24.0	74.8	81.7	40 500
26.0	73.3	81.2	35 900
28.0	71.8	80.5	32 100
30.0	70.4	79.8	28 900
32.0	68.9	79.1	26 100
34.0	67.4	78.3	23 700
36.0	65.9	77.4	21 600
38.0	64.3	76.4	19 800
40.0	62.8	75.4	18 200
42.0	61.2	74.4	16 700
44.0	59.6	73.2	15 400
46.0	57.9	72.0	14 200
48.0	56.3	70.7	13 100
50.0	54.6	69.3	12 100
52.0	52.8	67.8	11 200
54.0	51.1	66.2	10 400
56.0	49.2	64.5	9 600
58.0	47.4	62.7	8 900
60.0	45.4	60.8	8 200
62.0	43.4	58.7	7 600
64.0	41.4	56.5	7 000
66.0	39.2	54.2	6 500
68.0	36.9	51.6	6 000
70.0	34.5	48.8	5 500
72.0	32.0	45.7	5 100
74.0	29.2	42.3	4 700
76.0	26.2	38.4	4 300



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
Rating Over Front of Blocked Crawlers
No Travel - Limited Swing

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
85.3m (280 Ft.) BOOM			
12.8	83.0	87.1	64 800 *
13.0	82.8	87.1	64 700 *
14.0	82.2	86.9	64 200 *
15.0	81.5	86.8	63 700 *
16.0	80.8	86.6	63 000 *
18.0	79.4	86.3	60 300 *
20.0	78.1	85.9	52 900
22.0	76.7	85.4	45 800
24.0	75.3	84.9	40 200
26.0	73.9	84.3	35 600
28.0	72.5	83.7	31 800
30.0	71.1	83.1	28 600
32.0	69.7	82.3	25 800
34.0	68.2	81.6	23 500
36.0	66.8	80.7	21 300
38.0	65.3	79.8	19 500
40.0	63.8	78.8	17 800
42.0	62.3	77.8	16 400
44.0	60.8	76.7	15 100
46.0	59.2	75.6	13 900
48.0	57.6	74.3	12 800
50.0	56.0	73.0	11 800
52.0	54.4	71.6	10 900
54.0	52.7	70.1	10 100
56.0	51.0	68.5	9 300
58.0	49.2	66.8	8 600
60.0	47.4	65.0	7 900
62.0	45.6	63.1	7 300
64.0	43.7	61.1	6 700
66.0	41.7	58.9	6 200
68.0	39.6	56.5	5 700
70.0	37.4	54.0	5 200
72.0	35.1	51.2	4 800
74.0	32.7	48.2	4 400
76.0	30.1	44.9	3 900
78.0	27.3	41.2	3 600

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
88.4m (290 Ft.) BOOM			
13.4	82.8	90.1	60 100 *
14.0	82.4	90.0	59 800 *
15.0	81.8	89.9	59 300 *
16.0	81.1	89.7	58 800 *
18.0	79.8	89.4	57 100 *
20.0	78.5	89.0	52 900
22.0	77.2	88.5	45 600
24.0	75.8	88.0	40 000
26.0	74.5	87.5	35 500
28.0	73.1	86.9	31 600
30.0	71.8	86.3	28 400
32.0	70.4	85.6	25 700
34.0	69.0	84.8	23 300
36.0	67.6	84.0	21 200
38.0	66.2	83.2	19 300
40.0	64.8	82.2	17 700
42.0	63.3	81.3	16 200
44.0	61.9	80.2	14 900
46.0	60.4	79.1	13 700
48.0	58.9	77.9	12 600
50.0	57.4	76.7	11 700
52.0	55.8	75.3	10 700
54.0	54.2	73.9	9 900
56.0	52.6	72.4	9 100
58.0	50.9	70.8	8 400
60.0	49.2	69.1	7 700
62.0	47.5	67.3	7 100
64.0	45.7	65.4	6 600
66.0	43.8	63.4	6 000
68.0	41.9	61.2	5 500
70.0	39.9	58.9	5 100
72.0	37.9	56.4	4 600
74.0	35.7	53.7	4 200
76.0	33.4	50.8	3 800
78.0	30.9	47.5	3 400
80.0	28.3	44.0	3 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
91.4m (300 Ft.) BOOM			
14.0	82.7	93.1	54 300 *
15.0	82.1	92.9	53 800 *
16.0	81.4	92.8	53 200 *
18.0	80.2	92.5	50 900 *
20.0	78.9	92.1	48 500 *
22.0	77.6	91.7	45 500
24.0	76.3	91.2	39 800
26.0	75.0	90.7	35 200
28.0	73.7	90.1	31 400
30.0	72.4	89.5	28 100
32.0	71.1	88.8	25 400
34.0	69.7	88.1	23 000
36.0	68.4	87.3	20 900
38.0	67.0	86.5	19 000
40.0	65.7	85.6	17 300
42.0	64.3	84.7	15 900
44.0	62.9	83.7	14 600
46.0	61.5	82.6	13 400
48.0	60.0	81.5	12 300
50.0	58.6	80.3	11 300
52.0	57.1	79.0	10 400
54.0	55.6	77.6	9 600
56.0	54.0	76.2	8 800
58.0	52.5	74.7	8 100
60.0	50.9	73.1	7 400
62.0	49.2	71.4	6 800
64.0	47.5	69.6	6 200
66.0	45.8	67.7	5 700
68.0	44.0	65.7	5 200
70.0	42.2	63.6	4 700
72.0	40.3	61.3	4 300
74.0	38.3	58.8	3 900
76.0	36.2	56.1	3 400
78.0	34.0	53.3	3 100
80.0	31.7	50.1	2 700
82.0	29.2	46.7	2 400



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
Rating Over Front of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
94.5m (310 Ft.) BOOM			
14.0	82.9	96.2	48 900 *
15.0	82.3	96.0	48 300 *
16.0	81.7	95.9	47 000 *
18.0	80.5	95.6	44 600 *
20.0	79.2	95.2	42 500 *
22.0	78.0	94.8	40 700 *
24.0	76.8	94.3	38 900
26.0	75.5	93.8	34 900
28.0	74.3	93.3	31 100
30.0	73.0	92.7	27 800
32.0	71.7	92.0	25 100
34.0	70.4	91.3	22 700
36.0	69.1	90.6	20 600
38.0	67.8	89.8	18 700
40.0	66.5	88.9	17 100
42.0	65.2	88.0	15 600
44.0	63.8	87.1	14 300
46.0	62.5	86.0	13 100
48.0	61.1	85.0	12 000
50.0	59.7	83.8	11 000
52.0	58.3	82.6	10 100
54.0	56.8	81.3	9 300
56.0	55.4	80.0	8 500
58.0	53.9	78.5	7 800
60.0	52.4	77.0	7 100
62.0	50.8	75.4	6 500
64.0	49.2	73.7	5 900
66.0	47.6	71.9	5 400
68.0	45.9	70.0	4 900
70.0	44.2	68.0	4 400
72.0	42.4	65.9	4 000
74.0	40.6	63.6	3 500
76.0	38.7	61.2	3 200
78.0	36.7	58.6	2 800
80.0	34.6	55.7	2 400
82.0	32.4	52.7	2 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
97.5m (320 Ft.) BOOM			
14.6	82.8	99.2	45 200 *
15.0	82.6	99.1	44 700 *
16.0	82.0	99.0	43 600 *
18.0	80.8	98.7	41 400 *
20.0	79.6	98.3	39 200 *
22.0	78.4	97.9	37 300 *
24.0	77.2	97.5	35 600 *
26.0	76.0	97.0	34 000
28.0	74.8	96.4	31 000
30.0	73.5	95.9	27 600
32.0	72.3	95.2	24 900
34.0	71.1	94.6	22 500
36.0	69.8	93.9	20 400
38.0	68.6	93.1	18 500
40.0	67.3	92.3	16 900
42.0	66.0	91.4	15 400
44.0	64.7	90.5	14 100
46.0	63.4	89.5	12 900
48.0	62.1	88.4	11 800
50.0	60.7	87.3	10 800
52.0	59.4	86.2	9 900
54.0	58.0	84.9	9 100
56.0	56.6	83.7	8 300
58.0	55.2	82.3	7 600
60.0	53.7	80.8	6 900
62.0	52.3	79.3	6 300
64.0	50.7	77.7	5 700
66.0	49.2	76.0	5 200
68.0	47.6	74.2	4 700
70.0	46.0	72.3	4 200
72.0	44.4	70.3	3 700
74.0	42.6	68.2	3 300
76.0	40.9	66.0	2 900
78.0	39.0	63.6	2 500
80.0	37.1	61.0	2 200
82.0	35.1	58.2	1 800

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
100.6m (330 Ft.) BOOM			
14.6	83.0	102.2	39 800 *
15.0	82.8	102.2	39 400 *
16.0	82.2	102.0	38 300 *
18.0	81.1	101.7	36 000 *
20.0	79.9	101.4	34 100 *
22.0	78.7	101.0	32 400 *
24.0	77.6	100.6	30 800 *
26.0	76.4	100.1	29 500 *
28.0	75.2	99.6	28 200 *
30.0	74.1	99.0	27 000 *
32.0	72.9	98.4	25 200
34.0	71.7	97.8	22 800
36.0	70.5	97.1	20 800
38.0	69.2	96.4	18 900
40.0	68.0	95.6	17 200
42.0	66.8	94.7	15 800
44.0	65.5	93.8	14 500
46.0	64.3	92.9	13 300
48.0	63.0	91.9	12 200
50.0	61.7	90.8	11 200
52.0	60.4	89.7	10 300
54.0	59.1	88.5	9 400
56.0	57.7	87.3	8 700
58.0	56.4	86.0	7 900
60.0	55.0	84.6	7 300
62.0	53.6	83.2	6 700
64.0	52.2	81.6	6 100
66.0	50.7	80.0	5 500
68.0	49.2	78.3	5 000
70.0	47.7	76.5	4 600
72.0	46.1	74.7	4 100
74.0	44.5	72.7	3 700
76.0	42.8	70.5	3 300
78.0	41.1	68.3	2 900
80.0	39.4	65.9	2 600
82.0	37.5	63.4	2 200