



Liftcrane Jib Capacities

2250 SERIES 1

**Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating**

Maximum Operating Wind Speeds (all Jib Lengths) 10 m/s

LIFTING CAPACITIES: Chart supplements boom capacity chart **No. 8016-AM**. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and are calculated to comply with EN 13000, ISO 4305 and include factors based on a 4.0 degree tipping angle. Capacities based on structural competence are denoted by an asterisk (*). Capacities indicated by (b) require 2 010 kg minimum block weight with 4 part hoist line reeving on 12.2m jib and 3 part on 18.3m jib.

76.2m thru 91.4m boom lengths require only the middle 3 sheaves to be used on the lower boom point. All other sheaves must be removed from the lower boom point.

Weight of all load blocks, hooks, weight ball, slings, etc., beneath boom and jib point sheaves, is considered part of jib load. Reeved hoist line included in jib weight. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging **No. 179809**, jib assembly **No. 192352**, Wire Rope Specification chart **No. 8030-A**, and Counterweight Arrangement chart **No. 8026-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

WIND CONDITIONS: Machine may be operated in winds stated in Maximum Operating Wind Speed table provided crane operator judgment is used to allow for wind effect on lifted load and other considerations noted on capacity chart are followed. Wind will have a considerable effect on load with a large "sail area" and must be compensated for accordingly by reducing load ratings, reducing operating speeds or by a combination of both. Wind speed to be measured at boom point elevation. **Operation is not permitted when wind is above conditions stated in Maximum Operating Wind Speed table.** Park crane (upper inline with crawlers) with load block on ground or secured and position boom at 70 degrees. Lower boom onto blocking at ground level when wind is above 22 m/s.

MACHINE TRAVEL: Machine to travel on a firm, level and uniformly supporting surface and boom within boom angle range shown in capacity chart. *Travel with 100 percent of rated load prohibited.* Travel restricted to 90 percent of rated capacity with speed not to exceed 0.4 m/s. Refer to Maximum Allowable Travel Specification chart **No. 8998-A**.

MAX PERMISSIBLE SLEWING SPEED: Slewing operation with working load shall not exceed 0.4 m/s as measured at the operating radius. The amount of time to brake or start slewing a working load shall not be less than 2.5 seconds.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

JIB POINT ELEVATION: Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with 9 373 mm crawlers, 1 219 mm treads, 8 534 mm retractable gantry, 12 part boom hoist reeving, boom support straps, and 76 750 kg counterweight.

Maximum capacity on 29 mm wire rope is 13 610 kg per line.

BoomCatwalks Deduct
Deduct 300 kg from capacities when boom catwalks are attached.

Liftcrane Jib Capacities

2250 SERIES 1

**Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating**

**Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s**

Maximum Boom and Jib Lengths Lifted Unassisted					
Over Front of Blocked Crawlers		Over Rear of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 132	Boom Length	Jib No. 132	Boom Length	Jib No. 132
(a)(b)(c)(d) 91.4m	—	(a)(b)(c)(d) 88.4m	—	(a)(b)(c) 79.2m	—
(a)(b)(c)(d) 88.4m	—	(a)(b)(c) 85.3m	—	(b) 76.2m	—
(a) 85.3m	—	(a) 82.3m	—	73.2m	—
82.3m	—	79.2m	—	70.1m	(d)12.2m
79.2m	(b)(d)(e) 18.3m	76.2m	(d)(e) 18.3m	67.1m	(b)(d) 24.4m
79.2m	(b)(d) 12.2m	76.2m	(d) 12.2m	67.1m	(d) 18.3m
76.2m	(d)(e) 24.4m	73.2m	(d)(e) 18.3m	64.0m	(d) 30.5m
76.2m	(d) 18.3m	73.2m	(d) 12.2m	61.0m	(d) 36.6m
73.2m	(b)(d)(e) 30.5m	70.1m	(b)(d) 30.5m	57.9m	36.6m
73.2m	(d) 24.4m	70.1m	(d) 24.4m		
73.2m	(d) 18.3m	67.1m	(d) 36.6m		
70.1m	(d)(e) 36.6m	67.1m	(d) 30.5m		
70.1m	(d) 30.5m	64.0m	36.6m		
67.1m	(d) 36.6m				
64.0m	36.6m				
Load block, hook and weight ball on ground at start. (a) Upper boom point and third line sheave assembly on boom top must be removed. (b) Machine must be equipped with optional upperworks jacking cylinders. (c) Boom <i>must</i> be rigged with one hoist lead line. (d) Raising reserve is less than 10% tip weight. (e) When equipped with boom catwalks, length cannot be raised.					

Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
12.2	80.5	53.9	45 300 *b							12.2
14.0	78.4	53.5	42 300 *b							14.0
16.0	76.2	53.0	39 800 *b	78.6	52.7	32 900 *b				16.0
18.0	73.9	52.4	37 600 *b	76.3	52.1	31 600 *b	78.7	51.3	25 300 *	18.0
20.0	71.6	51.7	35 700 *b	74.0	51.4	30 300 *	76.3	50.6	24 200 *	20.0
22.0	69.2	50.9	33 900 *b	71.6	50.6	29 200 *	73.9	49.8	23 200 *	22.0
24.0	66.9	50.1	32 400 *b	69.2	49.7	28 200 *	71.5	48.9	22 300 *	24.0
26.0	64.4	49.1	31 000 b	66.7	48.7	27 300 *	69.0	47.9	21 400 *	26.0
28.0	61.9	48.0	28 700	64.2	47.6	26 500 *	66.4	46.8	20 700 *	28.0
30.0	59.4	46.8	25 700	61.7	46.4	25 800 *	63.8	45.6	20 000 *	30.0
32.0	56.8	45.5	23 200	59.0	45.1	23 900	61.1	44.2	19 400 *	32.0
34.0	54.1	44.0	21 100	56.3	43.6	21 700	58.3	42.7	18 800 *	34.0
36.0	51.3	42.4	19 200	53.5	42.0	19 700	55.4	41.0	18 300 *	36.0
38.0	48.3	40.6	17 500	50.5	40.2	18 000	52.4	39.2	17 800 *	38.0
42.0	42.0	36.4	14 700	44.1	35.9	15 100	45.8	34.8	15 500	42.0
46.0	34.6	31.0	12 400	36.6	30.4	12 800				46.0
42.7m (140 Ft.) BOOM										
12.2	81.0	57.0	45 300 *b							12.2
14.0	79.1	56.6	43 100 *b							14.0
16.0	77.0	56.2	40 600 *b	79.2	55.8	33 300 *b				16.0
18.0	74.8	55.6	38 400 *b	77.1	55.3	32 000 *b	79.3	54.5	25 600 *	18.0
20.0	72.6	55.0	36 500 *b	74.9	54.6	30 800 *b	77.1	53.8	24 500 *	20.0
22.0	70.4	54.2	34 800 *b	72.7	53.9	29 700 *	74.9	53.1	23 500 *	22.0
24.0	68.2	53.4	33 200 *b	70.4	53.1	28 700 *	72.6	52.3	22 600 *	24.0
26.0	65.9	52.5	31 700 b	68.1	52.1	27 800 *	70.3	51.3	21 800 *	26.0
28.0	63.6	51.5	28 200 b	65.8	51.1	27 000 *	67.9	50.3	21 100 *	28.0
30.0	61.3	50.4	25 300	63.4	50.0	25 900	65.5	49.2	20 400 *	30.0
32.0	58.9	49.1	22 800	61.0	48.8	23 500	63.0	47.9	19 800 *	32.0
34.0	56.4	47.8	20 600	58.5	47.4	21 300	60.4	46.5	19 200 *	34.0
36.0	53.8	46.3	18 700	55.9	45.9	19 400	57.8	45.0	18 700 *	36.0
38.0	51.1	44.7	17 100	53.2	44.3	17 600	55.1	43.3	18 100	38.0
42.0	45.5	40.9	14 200	47.5	40.5	14 700	49.2	39.4	15 200	42.0
46.0	39.1	36.3	12 000	41.0	35.7	12 400				46.0
50.0	31.7	30.3	10 100	33.5	29.7	10 400				50.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
13.7	79.9	59.8	44 200 *b							13.7
14.0	79.7	59.8	43 800 *b							14.0
16.0	77.7	59.3	41 400 *b	79.8	59.0	33 700*b				16.0
18.0	75.6	58.8	39 200 *b	77.8	58.4	32 400*b				18.0
20.0	73.6	58.2	37 300 *b	75.7	57.8	31 200*b	77.8	57.1	24 800*	20.0
22.0	71.5	57.5	35 600 *b	73.6	57.1	30 200*	75.7	56.3	23 900*	22.0
24.0	69.4	56.7	34 100 *b	71.5	56.4	29 200*	73.6	55.6	23 000*	24.0
26.0	67.3	55.9	31 300 b	69.4	55.5	28 300*	71.4	54.7	22 200*	26.0
28.0	65.1	54.9	27 800 b	67.2	54.5	27 500*	69.2	53.7	21 500*	28.0
30.0	62.9	53.9	24 900	65.0	53.5	25 900	66.9	52.7	20 800*	30.0
32.0	60.7	52.7	22 400	62.7	52.4	23 200	64.6	51.5	20 200*	32.0
34.0	58.4	51.5	20 200	60.4	51.1	21 000	62.3	50.2	19 600*	34.0
36.0	56.0	50.1	18 400	58.0	49.7	19 000	59.8	48.8	19 100*	36.0
38.0	53.5	48.6	16 700	55.5	48.2	17 300	57.3	47.3	17 900	38.0
42.0	48.4	45.2	13 900	50.3	44.8	14 400	52.0	43.7	14 900	42.0
46.0	42.8	41.1	11 500	44.6	40.6	12 000	46.2	39.4	12 400	46.0
50.0	36.4	36.0	9 700	38.2	35.4	10 100				50.0
54.0	28.9	29.3	8 200							54.0
48.8m (160 Ft.) BOOM										
13.7	80.4	62.9	44 900 *b							13.7
14.0	80.2	62.9	44 500 *b							14.0
16.0	78.3	62.4	42 100 *b							16.0
18.0	76.4	61.9	40 000 *b	78.4	61.6	32 800*b				18.0
20.0	74.4	61.4	38 100 *b	76.4	61.0	31 600*b	78.5	60.2	25 200*	20.0
22.0	72.5	60.7	36 300 *b	74.5	60.4	30 600*b	76.5	59.6	24 200*	22.0
24.0	70.5	60.0	34 100 b	72.5	59.6	29 600*	74.5	58.8	23 400*	24.0
26.0	68.5	59.2	30 700 b	70.5	58.8	28 800*	72.4	58.0	22 600*	26.0
28.0	66.4	58.3	27 400 b	68.4	57.9	27 800	70.3	57.1	21 800*	28.0
30.0	64.4	57.3	24 500 b	66.3	56.9	25 500	68.2	56.1	21 200*	30.0
32.0	62.3	56.2	22 000	64.2	55.9	22 900	66.1	55.0	20 600*	32.0
34.0	60.1	55.1	19 800	62.0	54.7	20 600	63.9	53.8	20 000*	34.0
36.0	57.9	53.8	17 900	59.8	53.4	18 700	61.6	52.5	19 200	36.0
38.0	55.7	52.4	16 200	57.5	52.0	16 900	59.3	51.1	17 600	38.0
42.0	50.9	49.3	13 400	52.8	48.9	14 000	54.4	47.9	14 600	42.0
46.0	45.8	45.5	11 100	47.6	45.1	11 600	49.1	44.0	12 100	46.0
50.0	40.2	41.0	9 200	42.0	40.5	9 600				50.0
54.0	33.8	35.5	7 600	35.5	34.8	8 000				54.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
13.7	80.9	66.0	45 300 *b							13.7
14.0	80.6	66.0	45 000 *b							14.0
16.0	78.8	65.6	42 800 *b							16.0
18.0	77.0	65.1	40 600 *b	79.0	64.7	33 100*b				18.0
20.0	75.2	64.5	38 800 *b	77.1	64.2	32 000*b	79.1	63.4	25 500*	20.0
22.0	73.3	63.9	36 800 b	75.2	63.6	31 000*b	77.2	62.8	24 600*	22.0
24.0	71.4	63.2	33 600 b	73.4	62.9	30 000*	75.3	62.1	23 700*	24.0
26.0	69.6	62.5	30 100 b	71.5	62.1	29 200*	73.3	61.3	22 900*	26.0
28.0	67.6	61.6	27 100 b	69.5	61.3	28 000	71.4	60.4	22 200*	28.0
30.0	65.7	60.7	24 300 b	67.6	60.3	25 300	69.4	59.5	21 500*	30.0
32.0	63.7	59.7	21 800 b	65.6	59.3	22 600	67.3	58.5	21 000*	32.0
34.0	61.7	58.6	19 600	63.5	58.2	20 400	65.3	57.4	20 400*	34.0
36.0	59.6	57.4	17 700	61.4	57.0	18 500	63.2	56.1	19 300	36.0
38.0	57.5	56.1	16 000	59.3	55.7	16 700	61.0	54.8	17 400	38.0
42.0	53.1	53.2	13 100	54.9	52.8	13 800	56.5	51.8	14 400	42.0
46.0	48.5	49.8	10 900	50.2	49.3	11 400	51.7	48.3	11 900	46.0
50.0	43.4	45.7	9 000	45.1	45.2	9 500	46.5	44.1	9 900	50.0
54.0	37.8	40.8	7 400	39.4	40.3	7 800				54.0
58.0	31.3	34.7	6 100							58.0
54.9m (180 Ft.) BOOM										
15.2	80.0	68.8	44 300 *b							15.2
16.0	79.3	68.7	43 400 *b							16.0
18.0	77.6	68.2	41 300 *b	79.5	67.9	33 500*b				18.0
20.0	75.9	67.7	39 400 b	77.7	67.4	32 400*b	79.6	66.6	25 700*	20.0
22.0	74.1	67.1	36 700 b	75.9	66.8	31 400*b	77.8	66.0	24 800*	22.0
24.0	72.3	66.5	32 600 b	74.1	66.1	30 400*	76.0	65.3	24 000*	24.0
26.0	70.5	65.7	29 300 b	72.3	65.4	29 500	74.1	64.6	23 200*	26.0
28.0	68.7	64.9	26 400 b	70.5	64.6	27 600	72.3	63.8	22 500*	28.0
30.0	66.9	64.1	23 800 b	68.6	63.7	24 800	70.4	62.9	21 900*	30.0
32.0	65.0	63.1	21 400 b	66.8	62.8	22 300	68.5	61.9	21 300*	32.0
34.0	63.1	62.1	19 200 b	64.8	61.7	20 000	66.5	60.8	20 600	34.0
36.0	61.1	61.0	17 300	62.9	60.6	18 100	64.6	59.7	18 900	36.0
38.0	59.2	59.8	15 600	60.9	59.4	16 400	62.5	58.5	17 100	38.0
42.0	55.1	57.1	12 700	56.8	56.6	13 400	58.3	55.7	14 100	42.0
46.0	50.7	53.9	10 400	52.4	53.4	11 000	53.9	52.4	11 600	46.0
50.0	46.1	50.2	8 500	47.8	49.7	9 100	49.1	48.6	9 500	50.0
54.0	41.1	45.8	7 000	42.7	45.3	7 400				54.0
58.0	35.5	40.5	5 600	37.0	39.9	6 000				58.0
62.0	28.9	33.8	4 500							62.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
15.2	80.4	71.9	44 900 *b							15.2
16.0	79.8	71.8	44 000 *b							16.0
18.0	78.2	71.4	41 900 *b	79.9	71.0	33 800*b				18.0
20.0	76.5	70.9	40 000 b	78.3	70.5	32 700*b	80.0	69.7	25 900*	20.0
22.0	74.8	70.3	35 700 b	76.6	69.9	31 700*b	78.3	69.1	25 100*	22.0
24.0	73.1	69.7	31 800 b	74.9	69.3	30 800*	76.6	68.5	24 300*	24.0
26.0	71.4	69.0	28 500 b	73.1	68.6	29 700	74.9	67.8	23 500*	26.0
28.0	69.7	68.2	25 700 b	71.4	67.9	26 800	73.1	67.0	22 800*	28.0
30.0	67.9	67.4	23 200 b	69.6	67.0	24 200	71.3	66.2	22 200*	30.0
32.0	66.1	66.5	21 000 b	67.8	66.1	22 000	69.5	65.3	21 600*	32.0
34.0	64.3	65.5	18 800 b	66.0	65.2	19 700	67.7	64.3	20 800	34.0
36.0	62.5	64.5	16 900	64.2	64.1	17 700	65.8	63.2	18 600	36.0
38.0	60.6	63.3	15 200	62.3	62.9	16 000	63.9	62.0	16 800	38.0
42.0	56.8	60.8	12 300	58.4	60.4	13 100	60.0	59.4	13 700	42.0
46.0	52.8	57.8	10 100	54.4	57.4	10 700	55.8	56.4	11 300	46.0
50.0	48.5	54.4	8 200	50.1	53.9	8 700	51.4	52.9	9 200	50.0
54.0	43.9	50.4	6 600	45.5	49.9	7 000	46.7	48.7	7 500	54.0
58.0	38.9	45.7	5 200	40.4	45.1	5 600				58.0
62.0	33.2	39.9	4 100	34.6	39.3	4 400				62.0
61.0m (200 Ft.) BOOM										
15.2	80.8	75.0	45 300 *b							15.2
16.0	80.2	74.9	44 500 *b							16.0
18.0	78.7	74.5	42 600 *b							18.0
20.0	77.1	74.0	39 300 b	78.8	73.7	33 000*b	80.5	72.8	26 100*	20.0
22.0	75.5	73.5	34 700 b	77.1	73.1	32 000*b	78.8	72.3	25 400*	22.0
24.0	73.8	72.9	30 900 b	75.5	72.5	31 100*b	77.2	71.7	24 500*	24.0
26.0	72.2	72.2	27 800 b	73.9	71.9	28 900	75.5	71.0	23 800*	26.0
28.0	70.5	71.5	25 000 b	72.2	71.1	26 100	73.8	70.3	23 100*	28.0
30.0	68.9	70.7	22 500 b	70.5	70.3	23 500	72.1	69.5	22 500*	30.0
32.0	67.2	69.9	20 400 b	68.8	69.5	21 400	70.4	68.6	21 900*	32.0
34.0	65.5	68.9	18 400 b	67.1	68.6	19 300	68.7	67.7	20 300	34.0
36.0	63.7	67.9	16 500	65.4	67.5	17 400	66.9	66.7	18 200	36.0
38.0	62.0	66.9	14 800	63.6	66.5	15 600	65.1	65.6	16 500	38.0
42.0	58.4	64.4	11 900	59.9	64.0	12 700	61.4	63.1	13 400	42.0
46.0	54.6	61.7	9 600	56.1	61.2	10 300	57.5	60.3	10 900	46.0
50.0	50.6	58.5	7 700	52.1	58.0	8 300	53.5	57.0	8 900	50.0
54.0	46.4	54.8	6 100	47.9	54.3	6 600	49.1	53.2	7 100	54.0
58.0	41.8	50.5	4 800	43.3	50.0	5 200				58.0
62.0	36.8	45.4	3 600	38.2	44.8	4 000				62.0
66.0	31.0	39.2	2 700							66.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
16.8	80.1	77.9	40 800 *b							16.8
18.0	79.1	77.6	40 800 *b							18.0
20.0	77.6	77.1	38 500 b	79.2	76.8	33 300 *b				20.0
22.0	76.0	76.6	34 000 b	77.7	76.3	32 300 *b	79.3	75.5	25 600 *	22.0
24.0	74.5	76.1	30 300 b	76.1	75.7	31 200 b	77.7	74.9	24 800 *	24.0
26.0	72.9	75.4	27 100 b	74.5	75.1	28 300	76.1	74.2	24 000 *	26.0
28.0	71.4	74.8	24 400 b	73.0	74.4	25 500	74.5	73.5	23 400 *	28.0
30.0	69.8	74.0	21 900 b	71.4	73.6	23 000	72.9	72.8	22 800 *	30.0
32.0	68.1	73.2	19 800 b	69.7	72.8	20 800	71.3	72.0	21 900	32.0
34.0	66.5	72.3	17 900 b	68.1	71.9	18 900	69.6	71.1	19 900	34.0
36.0	64.9	71.3	16 200 b	66.4	71.0	17 100	67.9	70.1	18 000	36.0
38.0	63.2	70.3	14 500	64.7	69.9	15 400	66.2	69.0	16 200	38.0
42.0	59.8	68.0	11 600	61.3	67.6	12 400	62.7	66.7	13 200	42.0
46.0	56.2	65.4	9 300	57.7	65.0	10 000	59.1	64.0	10 700	46.0
50.0	52.5	62.4	7 400	54.0	62.0	8 100	55.3	61.0	8 700	50.0
54.0	48.5	59.0	5 800	50.0	58.5	6 400	51.2	57.5	6 900	54.0
58.0	44.3	55.0	4 500	45.8	54.5	5 000	46.9	53.4	5 500	58.0
62.0	39.8	50.4	3 300	41.2	49.9	3 800				62.0
66.0	34.7	45.0	2 300	36.0	44.3	2 700				66.0
67.1m (220 Ft.) BOOM										
16.8	80.4	81.0	40 800 *b							16.8
18.0	79.5	80.7	40 800 *b							18.0
20.0	78.1	80.3	37 500 b	79.6	79.9	33 600 *b				20.0
22.0	76.6	79.8	33 100 b	78.2	79.4	32 600 *b	79.7	78.6	25 700 *	22.0
24.0	75.1	79.2	29 500 b	76.7	78.9	30 800 b	78.2	78.1	25 000 *	24.0
26.0	73.6	78.6	26 400 b	75.2	78.3	27 600 b	76.7	77.4	24 300 *	26.0
28.0	72.1	78.0	23 600 b	73.6	77.6	24 800	75.2	76.8	23 600 *	28.0
30.0	70.6	77.3	21 200 b	72.1	76.9	22 300	73.6	76.0	23 000 *	30.0
32.0	69.0	76.5	19 100 b	70.6	76.1	20 200	72.0	75.2	21 300	32.0
34.0	67.5	75.6	17 300 b	69.0	75.3	18 300	70.5	74.4	19 300	34.0
36.0	65.9	74.7	15 600 b	67.4	74.3	16 600	68.9	73.5	17 500	36.0
38.0	64.3	73.8	14 100 b	65.8	73.4	15 000	67.2	72.5	15 900	38.0
42.0	61.0	71.6	11 200	62.5	71.2	12 100	63.9	70.3	12 900	42.0
46.0	57.7	69.1	8 900	59.1	68.7	9 700	60.5	67.7	10 400	46.0
50.0	54.2	66.3	7 000	55.6	65.9	7 700	56.9	64.9	8 300	50.0
54.0	50.5	63.1	5 400	51.9	62.6	6 000	53.1	61.6	6 600	54.0
58.0	46.6	59.4	4 100	48.0	58.9	4 600	49.1	57.8	5 100	58.0
62.0	42.4	55.2	2 900	43.7	54.6	3 400	44.8	53.4	3 800	62.0
66.0				39.1	49.7	2 300				66.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
16.8	80.8	84.1	40 800 *b							16.8
18.0	79.9	83.8	40 800 *b							18.0
20.0	78.5	83.4	36 500 b	80.0	83.0	33 800*b				20.0
22.0	77.1	82.9	32 300 b	78.6	82.6	32 800b	80.1	81.7	25 900*	22.0
24.0	75.7	82.4	28 700 b	77.2	82.0	30 300b	78.7	81.2	25 300*	24.0
26.0	74.2	81.8	25 600b	75.7	81.5	26 900b	77.2	80.6	24 500*	26.0
28.0	72.8	81.2	22 900 b	74.3	80.8	24 100	75.7	80.0	23 900*	28.0
30.0	71.3	80.5	20 600 b	72.8	80.1	21 700	74.3	79.3	22 800	30.0
32.0	69.8	79.8	18 500 b	71.3	79.4	19 600	72.8	78.5	20 700	32.0
34.0	68.4	79.0	16 600 b	69.8	78.6	17 700	71.2	77.7	18 700	34.0
36.0	66.8	78.1	15 000 b	68.3	77.7	16 000	69.7	76.8	17 000	36.0
38.0	65.3	77.2	13 500 b	66.8	76.8	14 400	68.2	75.9	15 400	38.0
42.0	62.2	75.1	10 800	63.6	74.7	11 700	65.0	73.8	12 600	42.0
46.0	59.0	72.7	8 500	60.4	72.3	9 300	61.7	71.4	10 100	46.0
50.0	55.7	70.1	6 600	57.1	69.6	7 300	58.3	68.7	8 000	50.0
54.0	52.2	67.0	5 000	53.6	66.6	5 700	54.8	65.6	6 300	54.0
58.0	48.6	63.6	3 600	49.9	63.1	4 200	51.1	62.0	4 800	58.0
62.0	44.7	59.7	2 500	46.0	59.2	3 000	47.1	58.0	3 500	62.0
73.2m (240 Ft.) BOOM										
18.3	80.1	86.9	39 800 b							18.3
20.0	78.9	86.5	35 600 b	80.4	86.2	34 100*b				20.0
22.0	77.6	86.1	31 400 b	79.0	85.7	32 700b	80.5	84.9	26 100*	22.0
24.0	76.2	85.6	27 900 b	77.6	85.2	29 400b	79.1	84.4	25 500*	24.0
26.0	74.8	85.0	24 900 b	76.2	84.6	26 200b	77.7	83.8	24 800*	26.0
28.0	73.4	84.4	22 200 b	74.8	84.0	23 400b	76.3	83.2	24 000	28.0
30.0	72.0	83.7	19 900 b	73.4	83.4	21 100	74.8	82.5	22 400	30.0
32.0	70.6	83.0	17 800 b	72.0	82.6	19 000	73.4	81.8	20 100	32.0
34.0	69.2	82.2	16 000 b	70.6	81.9	17 000	72.0	81.0	18 100	34.0
36.0	67.7	81.4	14 400 b	69.1	81.0	15 400	70.5	80.2	16 400	36.0
38.0	66.3	80.5	12 900 b	67.7	80.1	13 900	69.0	79.2	14 800	38.0
42.0	63.3	78.6	10 300	64.7	78.1	11 200	66.0	77.2	12 100	42.0
46.0	60.2	76.3	8 100	61.6	75.9	8 900	62.9	75.0	9 700	46.0
50.0	57.1	73.8	6 200	58.4	73.3	6 900	59.7	72.4	7 700	50.0
54.0	53.8	70.9	4 600	55.1	70.5	5 300	56.3	69.5	5 900	54.0
58.0	50.4	67.7	3 200	51.7	67.2	3 800	52.8	66.1	4 400	58.0
62.0	46.8	64.0	2 000	48.0	63.5	2 600	49.1	62.4	3 100	62.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
18.3	80.4	90.0	39 500 b							18.3
20.0	79.3	89.6	35 400 b	80.7	89.3	34 300* b				20.0
22.0	78.0	89.2	31 300 b	79.4	88.8	32 800 b				22.0
24.0	76.7	88.7	27 800 b	78.1	88.3	29 200 b	79.5	87.5	25 600*	24.0
26.0	75.3	88.2	24 800 b	76.7	87.8	26 100 b	78.1	87.0	25 000*	26.0
28.0	74.0	87.6	22 200 b	75.4	87.2	23 400 b	76.8	86.4	24 200	28.0
30.0	72.6	87.0	19 900 b	74.0	86.6	21 100	75.4	85.7	22 400	30.0
32.0	71.3	86.3	17 900 b	72.7	85.9	19 000	74.0	85.0	20 100	32.0
34.0	69.9	85.5	16 100 b	71.3	85.1	17 100	72.6	84.3	18 200	34.0
36.0	68.5	84.7	14 400 b	69.9	84.3	15 400	71.2	83.5	16 500	36.0
38.0	67.1	83.9	13 000 b	68.5	83.5	13 900	69.8	82.6	14 900	38.0
42.0	64.3	82.0	10 400 b	65.6	81.6	11 300	66.9	80.7	12 200	42.0
46.0	61.4	79.8	8 300	62.7	79.4	9 200	63.9	78.5	10 000	46.0
50.0	58.4	77.4	6 400	59.7	77.0	7 200	60.9	76.0	7 900	50.0
54.0	55.2	74.7	4 800	56.5	74.3	5 500	57.7	73.3	6 200	54.0
58.0	52.0	71.6	3 400	53.3	71.2	4 100	54.4	70.1	4 700	58.0
62.0	48.6	68.2	2 300	49.9	67.7	2 900	50.9	66.6	3 400	62.0
66.0							47.2	62.6	2 300	66.0
79.2m (260 Ft.) BOOM										
18.3	80.8	93.1	38 500 b							18.3
20.0	79.7	92.7	34 500 b							20.0
22.0	78.4	92.3	30 400 b	79.8	92.0	32 000 b				22.0
24.0	77.1	91.9	27 000 b	78.5	91.5	28 500 b	79.8	90.6	25 800*	24.0
26.0	75.8	91.3	24 000 b	77.2	91.0	25 400 b	78.5	90.1	25 200*	26.0
28.0	74.5	90.8	21 500 b	75.9	90.4	22 800 b	77.2	89.6	24 200	28.0
30.0	73.2	90.2	19 200 b	74.6	89.8	20 400	75.9	88.9	21 700	30.0
32.0	71.9	89.5	17 200 b	73.3	89.1	18 400	74.6	88.3	19 500	32.0
34.0	70.6	88.8	15 400 b	71.9	88.4	16 500	73.2	87.5	17 600	34.0
36.0	69.3	88.0	13 800 b	70.6	87.6	14 800	71.9	86.7	15 900	36.0
38.0	67.9	87.2	12 400 b	69.2	86.8	13 400	70.5	85.9	14 400	38.0
42.0	65.2	85.4	9 800 b	66.5	85.0	10 800	67.7	84.1	11 700	42.0
46.0	62.4	83.3	7 800	63.7	82.9	8 600	64.9	82.0	9 400	46.0
50.0	59.5	81.0	6 000	60.8	80.6	6 800	62.0	79.6	7 500	50.0
54.0	56.6	78.4	4 400	57.8	78.0	5 100	59.0	77.0	5 800	54.0
58.0	53.5	75.5	3 000	54.7	75.1	3 700	55.8	74.0	4 300	58.0
62.0				51.5	71.8	2 500	52.5	70.7	3 000	62.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
15.2	79.8	59.4	32 800 *b	78.1	57.5	26 400*	79.2	55.7	18 000*	15.2
16.0	79.0	59.2	32 500 *b							16.0
18.0	77.0	58.7	31 600 *							18.0
20.0	75.0	58.1	30 800 *							20.0
22.0	72.9	57.4	30 000 *							22.0
24.0	70.8	56.6	29 300 *	73.9	56.1	25 400*	77.1	54.9	17 200*	24.0
26.0	68.6	55.8	28 600 *	71.8	55.2	25 000*	74.9	54.0	16 600*	26.0
28.0	66.5	54.8	28 000 *	69.6	54.2	24 500*	72.6	53.0	15 900*	28.0
30.0	64.3	53.8	26 700	67.3	53.2	23 600*	70.3	51.9	15 300*	30.0
32.0	62.0	52.6	24 100	65.0	52.0	22 700*	68.0	50.8	14 800*	32.0
34.0	59.7	51.4	22 000	62.7	50.8	21 800*	65.6	49.5	14 300*	34.0
36.0	57.3	50.0	20 000	60.3	49.4	20 700	63.1	48.0	13 900*	36.0
38.0	54.9	48.5	18 400	57.8	47.9	19 100	60.5	46.5	13 400*	38.0
42.0	49.7	45.1	15 500	52.6	44.4	16 100	55.1	42.9	12 800*	42.0
46.0	44.1	41.0	13 100	46.8	40.2	13 700	49.1	38.5	12 200*	46.0
50.0	37.7	35.8	11 200	40.3	34.9	11 700				50.0
54.0	30.1	29.2	9 600							54.0
42.7m (140 Ft.) BOOM										
15.2	80.3	62.5	33 100 *b	78.7	60.7	26 500*	79.8	58.9	18 200*	15.2
16.0	79.6	62.4	32 700 *b							16.0
18.0	77.7	61.9	31 900 *							18.0
20.0	75.7	61.3	31 100 *							20.0
22.0	73.8	60.6	30 300 *							22.0
24.0	71.8	59.9	29 600 *	74.8	59.3	25 600*	77.8	58.1	17 500*	24.0
26.0	69.8	59.1	29 000 *	72.7	58.5	25 200*	75.7	57.3	16 800*	26.0
28.0	67.7	58.2	28 300	70.7	57.6	24 700*	73.6	56.4	16 200*	28.0
30.0	65.7	57.2	26 500	68.6	56.6	24 200*	71.4	55.4	15 600*	30.0
32.0	63.6	56.2	23 800	66.4	55.5	23 200*	69.3	54.3	15 100*	32.0
34.0	61.4	55.0	21 500	64.3	54.4	22 300	67.0	53.1	14 600*	34.0
36.0	59.2	53.7	19 600	62.0	53.1	20 500	64.7	51.7	14 100*	36.0
38.0	56.9	52.3	17 900	59.7	51.7	18 700	62.4	50.3	13 700*	38.0
42.0	52.2	49.2	15 000	54.9	48.5	15 700	57.4	47.0	13 000*	42.0
46.0	47.1	45.4	12 700	49.7	44.7	13 300	52.0	43.1	12 400*	46.0
50.0	41.5	40.9	10 800	44.0	40.1	11 300				50.0
54.0	35.0	35.3	9 200	37.4	34.3	9 600				54.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
15.2	80.8	65.6	33 200 *b							15.2
16.0	80.1	65.5	32 900 *b							16.0
18.0	78.3	65.0	32 100 *							18.0
20.0	76.4	64.5	31 400 *	79.3	63.9	26 500 *				20.0
22.0	74.6	63.8	30 600 *	77.4	63.3	26 200 *	80.3	62.1	18 400 *	22.0
24.0	72.7	63.2	29 900 *	75.5	62.6	25 700 *	78.4	61.4	17 700 *	24.0
26.0	70.8	62.4	29 200 *	73.6	61.8	25 300 *	76.4	60.6	17 000 *	26.0
28.0	68.9	61.5	28 400	71.7	60.9	24 900 *	74.5	59.7	16 400 *	28.0
30.0	66.9	60.6	26 100	69.7	60.0	24 500 *	72.4	58.8	15 800 *	30.0
32.0	64.9	59.6	23 400	67.7	59.0	23 700 *	70.4	57.7	15 300 *	32.0
34.0	62.9	58.5	21 200	65.6	57.9	22 300	68.3	56.6	14 800 *	34.0
36.0	60.8	57.3	19 300	63.6	56.7	20 200	66.1	55.3	14 400 *	36.0
38.0	58.7	56.0	17 600	61.4	55.4	18 400	64.0	54.0	14 000 *	38.0
42.0	54.3	53.1	14 700	57.0	52.4	15 400	59.4	51.0	13 300 *	42.0
46.0	49.7	49.7	12 400	52.2	48.9	13 000	54.5	47.4	12 700 *	46.0
50.0	44.6	45.6	10 400	47.1	44.8	11 000	49.1	43.1	11 300	50.0
54.0	39.0	40.7	8 800	41.3	39.8	9 300				54.0
58.0	32.5	34.6	7 400							58.0
48.8m (160 Ft.) BOOM										
16.8	79.9	68.4	32 800 *b							16.8
18.0	78.8	68.1	32 400 *							18.0
20.0	77.0	67.6	31 600 *	79.8	67.0	26 600 *				20.0
22.0	75.3	67.0	30 900 *	78.0	66.4	26 400 *				22.0
24.0	73.5	66.4	30 200 *	76.2	65.8	25 900 *	79.0	64.6	17 900 *	24.0
26.0	71.7	65.7	29 600	74.4	65.1	25 500 *	77.1	63.8	17 200 *	26.0
28.0	69.9	64.9	28 500	72.6	64.2	25 100 *	75.2	63.0	16 600 *	28.0
30.0	68.0	64.0	25 600	70.7	63.4	24 800 *	73.3	62.1	16 000 *	30.0
32.0	66.1	63.0	23 000	68.8	62.4	24 100	71.4	61.1	15 500 *	32.0
34.0	64.2	62.0	20 800	66.9	61.4	21 800	69.4	60.1	15 000 *	34.0
36.0	62.3	60.9	18 900	64.9	60.2	19 900	67.4	58.9	14 600 *	36.0
38.0	60.3	59.7	17 200	62.9	59.0	18 100	65.4	57.6	14 200 *	38.0
42.0	56.2	57.0	14 300	58.8	56.3	15 100	61.1	54.8	13 500 *	42.0
46.0	51.9	53.8	11 900	54.4	53.0	12 600	56.6	51.5	12 800	46.0
50.0	47.3	50.1	10 000	49.7	49.3	10 600	51.7	47.6	11 000	50.0
54.0	42.2	45.7	8 400	44.5	44.8	8 900				54.0
58.0	36.6	40.3	7 000	38.7	39.3	7 400				58.0
62.0	29.9	33.6	5 800							62.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
16.8	80.3	71.5	33 100 *b							16.8
18.0	79.3	71.3	32 600 *b							18.0
20.0	77.6	70.8	31 800 *	80.3	70.2	26 500 *				20.0
22.0	75.9	70.2	31 200 *	78.6	69.6	26 400 *				22.0
24.0	74.2	69.6	30 500 *	76.8	69.0	26 100 *	79.5	67.8	18 000 *	24.0
26.0	72.5	68.9	29 800	75.1	68.3	25 700 *	77.7	67.1	17 400 *	26.0
28.0	70.8	68.1	27 800	73.4	67.5	25 300 *	75.9	66.3	16 800 *	28.0
30.0	69.0	67.3	25 200	71.6	66.7	24 900 *	74.1	65.4	16 300 *	30.0
32.0	67.3	66.4	22 800	69.8	65.8	23 900	72.3	64.5	15 700 *	32.0
34.0	65.5	65.4	20 600	68.0	64.8	21 700	70.4	63.5	15 300 *	34.0
36.0	63.6	64.4	18 700	66.1	63.7	19 700	68.5	62.4	14 800 *	36.0
38.0	61.8	63.2	16 900	64.2	62.6	17 900	66.6	61.2	14 400 *	38.0
42.0	57.9	60.7	14 000	60.3	60.0	14 900	62.6	58.6	13 700 *	42.0
46.0	53.9	57.7	11 700	56.3	57.0	12 400	58.4	55.5	12 900	46.0
50.0	49.6	54.3	9 700	51.9	53.5	10 400	53.9	51.9	10 800	50.0
54.0	45.0	50.3	8 100	47.2	49.4	8 700	49.1	47.7	9 000	54.0
58.0	40.0	45.5	6 700	42.1	44.6	7 200				58.0
62.0	34.3	39.8	5 600	36.3	38.7	5 900				62.0
54.9m (180 Ft.) BOOM										
16.8	80.7	74.7	33 200 *b							16.8
18.0	79.7	74.4	32 800 *b							18.0
20.0	78.1	73.9	32 000 *	80.7	73.3	26 500 *				20.0
22.0	76.5	73.4	31 400 *	79.1	72.8	26 500 *				22.0
24.0	74.9	72.8	30 700 *	77.4	72.2	26 200 *	79.9	70.9	18 200 *	24.0
26.0	73.3	72.1	29 800	75.8	71.5	25 800 *	78.3	70.3	17 600 *	26.0
28.0	71.6	71.4	27 000	74.1	70.8	25 400 *	76.6	69.5	17 000 *	28.0
30.0	70.0	70.6	24 500	72.4	70.0	25 100 *	74.8	68.7	16 500 *	30.0
32.0	68.3	69.8	22 300	70.7	69.1	23 500	73.1	67.8	16 000 *	32.0
34.0	66.6	68.8	20 200	69.0	68.2	21 400	71.3	66.9	15 500 *	34.0
36.0	64.8	67.8	18 200	67.2	67.2	19 400	69.5	65.8	15 000 *	36.0
38.0	63.0	66.8	16 500	65.4	66.1	17 500	67.7	64.7	14 600 *	38.0
42.0	59.4	64.4	13 600	61.8	63.7	14 600	64.0	62.2	13 900 *	42.0
46.0	55.6	61.6	11 300	57.9	60.8	12 100	60.0	59.4	12 600	46.0
50.0	51.6	58.4	9 300	53.9	57.6	10 100	55.9	56.0	10 500	50.0
54.0	47.4	54.7	7 700	49.6	53.8	8 300	51.5	52.1	8 700	54.0
58.0	42.8	50.4	6 300	44.9	49.5	6 900				58.0
62.0	37.8	45.2	5 100	39.8	44.2	5 600				62.0
66.0	32.0	39.0	4 100							66.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
18.3	79.9	77.5	32 900 *b							18.3
20.0	78.6	77.1	32 300 *							20.0
22.0	77.1	76.5	31 600 *	79.5	75.9	26 500 *				22.0
24.0	75.5	76.0	31 000 *	77.9	75.4	26 300 *				24.0
26.0	74.0	75.3	29 100	76.4	74.7	25 900 *	78.8	73.5	17 700 *	26.0
28.0	72.4	74.7	26 300	74.8	74.0	25 600 *	77.1	72.8	17 200 *	28.0
30.0	70.8	73.9	23 800	73.2	73.3	24 900	75.5	72.0	16 600 *	30.0
32.0	69.2	73.1	21 700	71.5	72.4	23 000	73.8	71.1	16 100 *	32.0
34.0	67.6	72.2	19 800	69.9	71.6	20 900	72.2	70.2	15 700 *	34.0
36.0	65.9	71.3	17 900	68.2	70.6	19 100	70.5	69.2	15 200 *	36.0
38.0	64.2	70.2	16 200	66.5	69.6	17 200	68.7	68.2	14 800 *	38.0
42.0	60.8	67.9	13 300	63.1	67.3	14 200	65.2	65.8	14 100 *	42.0
46.0	57.2	65.3	10 900	59.4	64.6	11 800	61.5	63.1	12 300	46.0
50.0	53.5	62.3	9 000	55.7	61.6	9 700	57.6	60.0	10 200	50.0
54.0	49.5	58.9	7 300	51.7	58.1	8 000	53.5	56.4	8 400	54.0
58.0	45.3	54.9	6 000	47.4	54.1	6 500	49.1	52.3	6 900	58.0
62.0	40.8	50.3	4 700	42.8	49.3	5 300				62.0
66.0	35.7	44.8	3 700	37.6	43.7	4 100				66.0
70.0	29.8	38.0	2 800							70.0
61.0m (200 Ft.) BOOM										
18.3	80.3	80.6	33 100 *b							18.3
20.0	79.1	80.2	32 500 *b							20.0
22.0	77.6	79.7	31 800 *	79.9	79.1	26 500 *				22.0
24.0	76.1	79.2	31 000	78.4	78.5	26 400 *				24.0
26.0	74.6	78.6	28 300	76.9	77.9	26 100 *	79.2	76.6	17 900 *	26.0
28.0	73.1	77.9	25 600	75.4	77.3	25 700 *	77.7	76.0	17 300 *	28.0
30.0	71.6	77.2	23 200	73.8	76.5	24 600	76.1	75.2	16 800 *	30.0
32.0	70.0	76.4	21 000	72.3	75.7	22 300	74.5	74.4	16 300 *	32.0
34.0	68.5	75.5	19 100	70.7	74.9	20 400	72.9	73.6	15 800 *	34.0
36.0	66.9	74.6	17 500	69.1	74.0	18 600	71.3	72.6	15 400 *	36.0
38.0	65.3	73.7	15 800	67.5	73.0	16 900	69.7	71.6	15 000 *	38.0
42.0	62.0	71.5	12 900	64.2	70.8	13 900	66.3	69.4	14 300	42.0
46.0	58.6	69.0	10 500	60.8	68.3	11 400	62.8	66.8	12 000	46.0
50.0	55.1	66.2	8 600	57.2	65.4	9 400	59.2	63.9	9 800	50.0
54.0	51.4	63.0	6 900	53.5	62.2	7 600	55.3	60.6	8 100	54.0
58.0	47.5	59.3	5 500	49.6	58.4	6 200	51.2	56.7	6 500	58.0
62.0	43.4	55.0	4 300	45.3	54.1	4 900	46.8	52.2	5 200	62.0
66.0	38.8	50.1	3 300	40.6	49.1	3 800				66.0
70.0	33.7	44.2	2 400	35.4	43.0	2 800				70.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
18.3	80.7	83.7	33 200 *b							18.3
20.0	79.5	83.3	32 600 *b							20.0
22.0	78.1	82.8	32 000 *	80.3	82.2	26 400 *				22.0
24.0	76.6	82.3	30 700	78.9	81.7	26 400 *				24.0
26.0	75.2	81.7	27 700	77.4	81.1	26 100 *	79.6	79.8	18 000 *	26.0
28.0	73.7	81.1	25 000	76.0	80.5	25 800	78.2	79.2	17 500 *	28.0
30.0	72.3	80.4	22 600	74.5	79.8	24 200	76.7	78.5	17 000 *	30.0
32.0	70.8	79.7	20 500	73.0	79.0	21 900	75.1	77.7	16 500 *	32.0
34.0	69.3	78.9	18 600	71.5	78.2	19 900	73.6	76.9	16 000 *	34.0
36.0	67.8	78.0	17 000	70.0	77.3	18 100	72.1	76.0	15 600 *	36.0
38.0	66.3	77.1	15 400	68.4	76.4	16 600	70.5	75.0	15 200 *	38.0
42.0	63.2	75.0	12 600	65.3	74.3	13 600	67.3	72.9	14 300	42.0
46.0	60.0	72.6	10 200	62.0	71.9	11 200	64.0	70.5	11 800	46.0
50.0	56.6	70.0	8 300	58.7	69.2	9 200	60.5	67.7	9 700	50.0
54.0	53.2	66.9	6 600	55.2	66.1	7 400	56.9	64.6	7 900	54.0
58.0	49.5	63.5	5 300	51.5	62.7	6 000	53.1	61.0	6 300	58.0
62.0	45.6	59.6	4 100	47.5	58.7	4 700	49.1	56.9	5 000	62.0
66.0	41.4	55.0	3 000	43.3	54.1	3 600				66.0
70.0	36.9	49.8	2 100	38.6	48.7	2 600				70.0
67.1m (220 Ft.) BOOM										
19.8	80.0	86.5	32 900 *b							19.8
20.0	79.9	86.4	32 800 *b							20.0
22.0	78.5	86.0	32 200 *b							22.0
24.0	77.1	85.5	30 300	79.3	84.8	26 400 *				24.0
26.0	75.7	84.9	27 000	77.9	84.3	26 300 *	80.0	83.0	18 200 *	26.0
28.0	74.3	84.3	24 300	76.5	83.7	25 700	78.6	82.4	17 600 *	28.0
30.0	72.9	83.6	21 900	75.1	83.0	23 500	77.2	81.7	17 100 *	30.0
32.0	71.5	82.9	19 900	73.6	82.3	21 300	75.7	80.9	16 600 *	32.0
34.0	70.1	82.2	18 000	72.2	81.5	19 300	74.2	80.1	16 200 *	34.0
36.0	68.6	81.3	16 300	70.7	80.6	17 600	72.8	79.3	15 800 *	36.0
38.0	67.2	80.4	14 900	69.3	79.7	16 000	71.3	78.4	15 300 *	38.0
42.0	64.2	78.5	12 200	66.3	77.8	13 300	68.2	76.3	14 100	42.0
46.0	61.1	76.2	9 900	63.2	75.5	10 900	65.1	74.0	11 500	46.0
50.0	58.0	73.7	7 900	60.0	72.9	8 800	61.8	71.4	9 300	50.0
54.0	54.7	70.8	6 300	56.7	70.0	7 100	58.4	68.5	7 600	54.0
58.0	51.3	67.6	4 900	53.2	66.7	5 600	54.8	65.1	6 000	58.0
62.0	47.6	63.9	3 700	49.5	63.0	4 300	51.1	61.3	4 600	62.0
66.0	43.8	59.7	2 600	45.6	58.8	3 200	47.0	56.9	3 500	66.0
70.0				41.3	53.9	2 200				70.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters			
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms				
70.1m (230 Ft.) BOOM													
19.8	80.3	89.6	33 100 *b							19.8			
20.0	80.2	89.5	33 000 *b							20.0			
22.0	78.9	89.1	32 100 b							22.0			
24.0	77.6	88.6	29 500							79.7	88.0	26 400*	24.0
26.0	76.2	88.1	26 300							78.3	87.4	26 400	80.4
28.0	74.9	87.5	23 600	77.0	86.8	25 400	79.0	85.5	17 800*	28.0			
30.0	73.5	86.9	21 300	75.6	86.2	22 800	77.6	84.9	17 300*	30.0			
32.0	72.2	86.2	19 200	74.2	85.5	20 700	76.2	84.2	16 800*	32.0			
34.0	70.8	85.4	17 400	72.8	84.8	18 700	74.8	83.4	16 300*	34.0			
36.0	69.4	84.6	15 800	71.4	84.0	17 000	73.4	82.6	15 900*	36.0			
38.0	68.0	83.8	14 300	70.0	83.1	15 500	72.0	81.7	15 500*	38.0			
42.0	65.2	81.9	11 700	67.1	81.2	12 800	69.0	79.8	13 600	42.0			
46.0	62.2	79.7	9 500	64.2	79.0	10 500	66.0	77.6	11 200	46.0			
50.0	59.2	77.3	7 500	61.2	76.6	8 500	62.9	75.1	9 100	50.0			
54.0	56.1	74.6	5 900	58.0	73.8	6 800	59.7	72.3	7 200	54.0			
58.0	52.9	71.5	4 500	54.7	70.7	5 300	56.4	69.1	5 700	58.0			
62.0	49.5	68.1	3 300	51.3	67.2	4 000	52.8	65.5	4 400	62.0			
66.0	45.9	64.2	2 200	47.6	63.3	2 900	49.1	61.5	3 200	66.0			
70.0				43.7	58.8	1 900				70.0			
73.2m (240 Ft.) BOOM													
19.8	80.7	92.7	33 200 *b							19.8			
20.0	80.5	92.7	33 100 *b							20.0			
22.0	79.3	92.2	32 000 b							22.0			
24.0	78.0	91.8	28 600							80.0	91.1	26 300*	24.0
26.0	76.7	91.2	25 500							78.7	90.6	26 300	80.7
28.0	75.4	90.7	22 900	77.4	90.0	24 700	79.4	88.7	17 900*	28.0			
30.0	74.1	90.1	20 600	76.1	89.4	22 200	78.1	88.1	17 400*	30.0			
32.0	72.8	89.4	18 600	74.8	88.7	20 100	76.7	87.4	16 900*	32.0			
34.0	71.5	88.7	16 800	73.4	88.0	18 200	75.4	86.7	16 400*	34.0			
36.0	70.1	87.9	15 100	72.1	87.2	16 500	74.0	85.9	16 100*	36.0			
38.0	68.8	87.1	13 700	70.7	86.4	14 900	72.6	85.0	15 700*	38.0			
42.0	66.1	85.3	11 100	68.0	84.6	12 300	69.8	83.2	13 100	42.0			
46.0	63.3	83.2	9 000	65.2	82.5	10 100	66.9	81.1	10 800	46.0			
50.0	60.4	80.9	7 100	62.2	80.2	8 100	64.0	78.7	8 700	50.0			
54.0	57.4	78.3	5 500	59.2	77.6	6 400	60.9	76.0	6 900	54.0			
58.0	54.3	75.4	4 000	56.1	74.6	4 900	57.7	73.0	5 400	58.0			
62.0	51.1	72.2	2 900	52.9	71.3	3 600	54.4	69.6	4 000	62.0			
66.0				49.5	67.6	2 500	50.9	65.8	2 800	66.0			
70.0							47.2	61.5	1 800	70.0			



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
19.8	81.0	95.8	27 200 *b							19.8
20.0	80.9	95.8	27 200 *b							20.0
22.0	79.6	95.3	27 200 *b							22.0
24.0	78.4	94.9	27 200 *							24.0
26.0	77.1	94.4	25 500							26.0
28.0	75.9	93.9	22 900	79.1	93.7	26 300				
30.0	74.6	93.3	20 600	77.8	93.2	24 600	79.8	91.9	18 000*	28.0
32.0	73.4	92.6	18 600	76.6	92.6	22 200	78.5	91.3	17 500*	30.0
34.0	72.1	91.9	16 800	75.3	91.9	20 000	77.2	90.6	17 100*	32.0
36.0	70.8	91.2	15 200	74.0	91.3	18 200	75.9	89.9	16 600*	34.0
				72.7	90.5	16 500	74.6	89.1	16 200*	36.0
38.0	69.5	90.4	13 700	71.4	89.7	15 000	73.2	88.3	15 800*	38.0
42.0	66.9	88.6	11 200	68.7	87.9	12 400	70.5	86.5	13 200	42.0
46.0	64.2	86.7	9 100	66.0	86.0	10 100	67.8	84.5	10 900	46.0
50.0	61.4	84.5	7 300	63.3	83.7	8 300	65.0	82.2	8 900	50.0
54.0	58.6	82.0	5 700	60.4	81.2	6 600	62.0	79.7	7 100	54.0
58.0	55.7	79.2	4 300	57.4	78.4	5 100	59.0	76.8	5 600	58.0
62.0	52.6	76.1	3 000	54.4	75.3	3 800	55.9	73.7	4 200	62.0
66.0	49.4	72.7	2 000	51.1	71.8	2 700	52.6	70.1	3 000	66.0
70.0							49.1	66.1	2 000	70.0
79.2m (260 Ft.) BOOM										
21.3	80.3	98.6	27 200 *b							21.3
22.0	79.9	98.5	27 200 *b							22.0
24.0	78.8	98.0	27 100							24.0
26.0	77.6	97.5	24 800							26.0
28.0	76.3	97.0	22 200							28.0
30.0	75.1	96.4	19 900	79.4	96.9	26 200				
32.0	73.9	95.8	18 000	78.2	96.4	24 000	80.1	95.0	18 100*	
34.0	72.7	95.2	16 200	77.0	95.8	21 600	78.9	94.4	17 600*	30.0
36.0	71.4	94.4	14 600	75.8	95.2	19 500	77.6	93.8	17 100*	32.0
38.0	70.2	93.7	13 100	74.5	94.5	17 600	76.4	93.1	16 700*	34.0
				73.3	93.8	16 000	75.1	92.4	16 300*	36.0
				72.0	93.0	14 400	73.8	91.6	15 400	38.0
42.0	67.6	92.0	10 600	69.5	91.3	11 800	71.2	89.9	12 700	42.0
46.0	65.1	90.1	8 500	66.9	89.4	9 700	68.6	87.9	10 400	46.0
50.0	62.4	88.0	6 700	64.2	87.2	7 700	65.8	85.8	8 400	50.0
54.0	59.7	85.6	5 200	61.4	84.8	6 100	63.1	83.3	6 700	54.0
58.0	56.9	83.0	3 900	58.6	82.2	4 700	60.2	80.6	5 200	58.0
62.0	54.0	80.0	2 700	55.7	79.2	3 400	57.2	77.6	3 900	62.0
66.0				52.6	75.9	2 400	54.1	74.2	2 700	66.0

Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
16.8	80.2	65.3	23 300 *							16.8
18.0	79.0	65.0	22 900 *							18.0
20.0	77.2	64.4	22 300 *							20.0
22.0	75.3	63.8	21 700 *	79.2	63.1	19 700*				22.0
24.0	73.5	63.1	21 100 *	77.3	62.4	19 300*				24.0
26.0	71.6	62.4	20 600 *	75.4	61.7	18 900*	79.3	60.3	14 200*	26.0
28.0	69.6	61.5	20 100 *	73.4	60.8	18 500*	77.3	59.4	13 600*	28.0
30.0	67.7	60.6	19 700 *	71.5	59.9	18 100*	75.3	58.4	13 000*	30.0
32.0	65.7	59.6	19 200 *	69.5	58.9	17 800*	73.2	57.4	12 500*	32.0
34.0	63.7	58.5	18 800 *	67.4	57.8	17 400*	71.1	56.2	12 100*	34.0
36.0	61.6	57.3	18 400 *	65.3	56.6	17 100*	68.9	55.0	11 700*	36.0
38.0	59.5	56.0	18 000 *	63.2	55.2	16 800*	66.7	53.7	11 300*	38.0
42.0	55.1	53.1	16 100	58.7	52.3	15 400*	62.1	50.6	10 600*	42.0
46.0	50.4	49.7	13 700	53.9	48.8	14 300	57.2	47.0	10 000*	46.0
50.0	45.4	45.6	11 800	48.8	44.6	12 200	51.8	42.6	9 600*	50.0
54.0	39.7	40.7	10 100	43.0	39.6	10 500				54.0
58.0	33.2	34.5	8 800							58.0
42.7m (140 Ft.) BOOM										
16.8	80.6	68.4	23 500 *							16.8
18.0	79.6	68.1	23 100 *							18.0
20.0	77.8	67.6	22 500 *							20.0
22.0	76.0	67.0	21 900 *	79.7	66.3	19 900*				22.0
24.0	74.3	66.4	21 400 *	77.9	65.7	19 400*				24.0
26.0	72.4	65.6	20 900 *	76.1	64.9	19 000*	79.8	63.5	14 300*	26.0
28.0	70.6	64.8	20 400 *	74.3	64.1	18 700*	77.9	62.7	13 700*	28.0
30.0	68.8	64.0	19 900 *	72.4	63.2	18 300*	76.0	61.8	13 200*	30.0
32.0	66.9	63.0	19 500 *	70.5	62.3	18 000*	74.1	60.8	12 700*	32.0
34.0	65.0	62.0	19 100 *	68.6	61.2	17 600*	72.1	59.7	12 300*	34.0
36.0	63.0	60.9	18 700 *	66.6	60.1	17 300*	70.1	58.5	11 900*	36.0
38.0	61.1	59.7	18 300 *	64.6	58.9	17 000*	68.0	57.3	11 500*	38.0
42.0	57.0	56.9	15 700	60.4	56.1	15 900*	63.7	54.4	10 800*	42.0
46.0	52.6	53.8	13 400	56.0	52.9	13 900	59.2	51.1	10 200*	46.0
50.0	48.0	50.0	11 400	51.3	49.1	11 900	54.2	47.1	9 700*	50.0
54.0	43.0	45.6	9 800	46.1	44.6	10 100	48.8	42.4	9 400*	54.0
58.0	37.3	40.3	8 400	40.3	39.1	8 700				58.0
62.0	30.7	33.6	7 100							62.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
18.3	79.8	71.2	23 200*							18.3
20.0	78.3	70.8	22 700*							20.0
22.0	76.7	70.2	22 100*	80.2	69.5	20 000*				22.0
24.0	75.0	69.6	21 600*	78.5	68.9	19 600*				24.0
26.0	73.2	68.9	21 100*	76.7	68.2	19 200*	80.3	66.7	14 400*	26.0
28.0	71.5	68.1	20 600*	75.0	67.4	18 800*	78.5	65.9	13 900*	28.0
30.0	69.8	67.3	20 200*	73.2	66.6	18 500*	76.7	65.0	13 300*	30.0
32.0	68.0	66.4	19 700*	71.4	65.6	18 100*	74.8	64.1	12 900*	32.0
34.0	66.2	65.4	19 300*	69.6	64.7	17 800*	73.0	63.1	12 500*	34.0
36.0	64.3	64.4	18 900*	67.7	63.6	17 500*	71.1	62.0	12 000*	36.0
38.0	62.5	63.2	18 200	65.8	62.4	17 200*	69.1	60.8	11 700*	38.0
42.0	58.6	60.7	15 300	61.9	59.8	16 100	65.1	58.1	11 000*	42.0
46.0	54.6	57.7	13 000	57.8	56.8	13 600	60.9	55.0	10 400*	46.0
50.0	50.3	54.3	11 100	53.5	53.3	11 600	56.4	51.4	9 900*	50.0
54.0	45.7	50.2	9 400	48.8	49.2	9 800	51.5	47.1	9 500*	54.0
58.0	40.7	45.5	8 000	43.6	44.4	8 400				58.0
62.0	35.0	39.7	6 800	37.7	38.4	7 100				62.0
48.8m (160 Ft.) BOOM										
18.3	80.2	74.3	23 300*							18.3
20.0	78.8	73.9	22 800*							20.0
22.0	77.2	73.4	22 300*							22.0
24.0	75.6	72.8	21 800*	79.0	72.0	19 700*				24.0
26.0	74.0	72.1	21 300*	77.3	71.4	19 300*	80.7	69.9	14 600*	26.0
28.0	72.3	71.4	20 800*	75.7	70.6	18 900*	79.0	69.1	14 000*	28.0
30.0	70.6	70.6	20 400*	74.0	69.8	18 600*	77.3	68.3	13 500*	30.0
32.0	69.0	69.7	20 000*	72.3	69.0	18 300*	75.6	67.4	13 000*	32.0
34.0	67.2	68.8	19 600*	70.5	68.0	17 900*	73.8	66.5	12 600*	34.0
36.0	65.5	67.8	19 200*	68.8	67.0	17 600*	72.0	65.4	12 200*	36.0
38.0	63.7	66.7	17 900	67.0	65.9	17 400*	70.1	64.3	11 800*	38.0
42.0	60.1	64.3	15 000	63.3	63.5	15 800	66.4	61.8	11 200*	42.0
46.0	56.3	61.5	12 600	59.4	60.7	13 300	62.4	58.9	10 600*	46.0
50.0	52.3	58.3	10 600	55.4	57.4	11 200	58.2	55.5	10 100*	50.0
54.0	48.1	54.6	9 000	51.1	53.7	9 500	53.7	51.6	9 700	54.0
58.0	43.5	50.3	7 600	46.4	49.2	8 000	48.9	47.0	8 400	58.0
62.0	38.5	45.2	6 400	41.2	44.0	6 700				62.0
66.0	32.7	38.9	5 300							66.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
18.3	80.6	77.4	23 400 *							18.3
20.0	79.3	77.0	23 000 *							20.0
22.0	77.7	76.5	22 500 *							22.0
24.0	76.2	76.0	22 000 *	79.4	75.2	19 800*				24.0
26.0	74.6	75.3	21 500 *	77.9	74.6	19 400*				26.0
28.0	73.1	74.6	21 000 *	76.3	73.9	19 100*	79.5	72.3	14 100*	28.0
30.0	71.5	73.9	20 600 *	74.6	73.1	18 700*	77.9	71.6	13 600*	30.0
32.0	69.8	73.1	20 200 *	73.0	72.3	18 400*	76.2	70.7	13 200*	32.0
34.0	68.2	72.2	19 800 *	71.4	71.4	18 100*	74.5	69.8	12 700*	34.0
36.0	66.6	71.2	19 200	69.7	70.4	17 800*	72.8	68.8	12 300*	36.0
38.0	64.9	70.2	17 700	68.0	69.4	17 500*	71.0	67.8	12 000*	38.0
42.0	61.4	67.9	14 800	64.5	67.1	15 500	67.5	65.4	11 300*	42.0
46.0	57.9	65.3	12 400	60.9	64.4	13 000	63.8	62.6	10 800*	46.0
50.0	54.1	62.3	10 400	57.1	61.4	11 000	59.8	59.5	10 200*	50.0
54.0	50.2	58.9	8 800	53.1	57.9	9 300	55.7	55.9	9 700	54.0
58.0	46.0	54.9	7 400	48.8	53.8	7 800	51.2	51.7	8 200	58.0
62.0	41.4	50.3	6 100	44.1	49.1	6 500				62.0
66.0	36.3	44.8	5 100	38.9	43.4	5 400				66.0
70.0	30.4	38.0	4 100							70.0
54.9m (180 Ft.) BOOM										
18.3	81.0	80.5	23 600 *							18.3
20.0	79.7	80.2	23 100 *							20.0
22.0	78.2	79.7	22 600 *							22.0
24.0	76.7	79.1	22 100 *	79.9	78.4	19 900*				24.0
26.0	75.2	78.5	21 700 *	78.3	77.8	19 500*				26.0
28.0	73.7	77.9	21 200 *	76.8	77.1	19 200*	79.9	75.5	14 300*	28.0
30.0	72.2	77.1	20 800 *	75.3	76.4	18 800*	78.4	74.8	13 800*	30.0
32.0	70.7	76.4	20 400 *	73.7	75.6	18 500*	76.8	74.0	13 300*	32.0
34.0	69.1	75.5	20 000 *	72.1	74.7	18 300*	75.2	73.1	12 900*	34.0
36.0	67.5	74.6	19 100	70.5	73.8	18 000*	73.5	72.2	12 500*	36.0
38.0	65.9	73.6	17 300	68.9	72.8	17 700*	71.9	71.2	12 100*	38.0
42.0	62.7	71.5	14 400	65.6	70.6	15 200	68.5	68.9	11 500*	42.0
46.0	59.3	69.0	12 000	62.2	68.1	12 700	65.0	66.3	10 900*	46.0
50.0	55.8	66.2	10 000	58.6	65.2	10 700	61.3	63.4	10 400*	50.0
54.0	52.1	62.9	8 400	54.9	62.0	8 900	57.4	60.0	9 400	54.0
58.0	48.2	59.2	7 000	50.9	58.2	7 400	53.3	56.1	7 900	58.0
62.0	44.0	55.0	5 700	46.6	53.9	6 100	48.9	51.6	6 500	62.0
66.0	39.4	50.1	4 700	42.0	48.8	5 000				66.0
70.0	34.3	44.1	3 700	36.7	42.7	4 000				70.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
19.8	80.2	83.3	23 300 *							19.8
20.0	80.1	83.3	23 300 *							20.0
22.0	78.7	82.8	22 800 *							22.0
24.0	77.2	82.3	22 300 *							24.0
26.0	75.8	81.7	21 800 *	78.8	80.9	19 600*				26.0
28.0	74.4	81.1	21 400 *	77.3	80.3	19 300*	80.3	78.7	14 400*	28.0
30.0	72.9	80.4	21 000 *	75.8	79.6	19 000*	78.8	78.0	13 900*	30.0
32.0	71.4	79.6	20 600 *	74.4	78.8	18 700*	77.3	77.2	13 400*	32.0
34.0	69.9	78.8	20 000	72.8	78.0	18 400*	75.8	76.4	13 000*	34.0
36.0	68.4	78.0	18 600	71.3	77.1	18 100*	74.2	75.5	12 600*	36.0
38.0	66.9	77.0	16 900	69.8	76.2	17 800*	72.6	74.5	12 300*	38.0
42.0	63.8	75.0	14 000	66.6	74.1	14 900	69.4	72.4	11 600*	42.0
46.0	60.6	72.6	11 600	63.4	71.7	12 400	66.1	70.0	11 000*	46.0
50.0	57.2	69.9	9 700	60.0	69.0	10 300	62.6	67.2	10 600*	50.0
54.0	53.8	66.9	8 000	56.5	65.9	8 600	59.0	64.0	9 100	54.0
58.0	50.1	63.5	6 600	52.8	62.4	7 100	55.1	60.4	7 600	58.0
62.0	46.2	59.5	5 400	48.8	58.4	5 800	51.0	56.2	6 200	62.0
66.0	42.0	55.0	4 300	44.6	53.8	4 700				66.0
70.0	37.5	49.7	3 400	39.9	48.4	3 700				70.0
74.0	32.3	43.4	2 600							74.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

61.0m (200 Ft.) BOOM										
19.8	80.6	86.4	23 400 *							19.8
20.0	80.5	86.4	23 400 *							20.0
22.0	79.1	85.9	22 900 *							22.0
24.0	77.7	85.4	22 400 *							24.0
26.0	76.3	84.9	22 000 *	79.2	84.1	19 700 *				26.0
28.0	74.9	84.3	21 600 *	77.8	83.5	19 400 *				28.0
30.0	73.5	83.6	21 200 *	76.4	82.8	19 100 *	79.3	81.2	14 000 *	30.0
32.0	72.1	82.9	20 800 *	74.9	82.1	18 800 *	77.8	80.5	13 600 *	32.0
34.0	70.7	82.1	19 600	73.5	81.3	18 500 *	76.3	79.7	13 100 *	34.0
36.0	69.2	81.3	17 900	72.0	80.5	18 200 *	74.8	78.8	12 700 *	36.0
38.0	67.8	80.4	16 400	70.6	79.6	17 400	73.3	77.9	12 400 *	38.0
42.0	64.8	78.4	13 700	67.6	77.6	14 600	70.2	75.8	11 700 *	42.0
46.0	61.7	76.2	11 300	64.5	75.3	12 100	67.1	73.5	11 200 *	46.0
50.0	58.6	73.6	9 300	61.3	72.7	10 000	63.8	70.9	10 600	50.0
54.0	55.3	70.8	7 600	57.9	69.8	8 200	60.4	67.9	8 900	54.0
58.0	51.8	67.5	6 200	54.4	66.5	6 800	56.8	64.5	7 300	58.0
62.0	48.2	63.9	5 000	50.8	62.8	5 400	53.0	60.6	5 900	62.0
66.0	44.4	59.7	3 900	46.8	58.5	4 300	48.9	56.2	4 700	66.0
70.0	40.2	54.9	3 000	42.6	53.6	3 300				70.0
74.0	35.6	49.2	2 200	37.8	47.8	2 400				74.0

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
19.8	80.9	89.6	23 600 *							19.8
20.0	80.8	89.5	23 500 *							20.0
22.0	79.5	89.1	23 100 *							22.0
24.0	78.1	88.6	22 600 *							24.0
26.0	76.8	88.1	22 200 *	79.6	87.3	19 800*				26.0
28.0	75.5	87.5	21 700 *	78.2	86.7	19 500*				28.0
30.0	74.1	86.8	21 300 *	76.9	86.0	19 200*	79.7	84.4	14 100*	30.0
32.0	72.7	86.1	21 000 *	75.5	85.3	18 900*	78.3	83.7	13 600*	32.0
34.0	71.4	85.4	19 100	74.1	84.6	18 600*	76.8	82.9	13 300*	34.0
36.0	70.0	84.6	17 500	72.7	83.8	18 300	75.4	82.1	12 900*	36.0
38.0	68.6	83.7	15 900	71.3	82.9	17 100	74.0	81.2	12 500*	38.0
42.0	65.7	81.8	13 400	68.4	81.0	14 300	71.0	79.3	11 900*	42.0
46.0	62.8	79.7	11 000	65.4	78.8	11 900	68.0	77.0	11 300*	46.0
50.0	59.8	77.3	9 000	62.4	76.4	9 800	64.9	74.5	10 500	50.0
54.0	56.7	74.6	7 400	59.2	73.6	8 000	61.6	71.7	8 700	54.0
58.0	53.4	71.5	6 000	56.0	70.5	6 500	58.2	68.5	7 100	58.0
62.0	50.0	68.0	4 700	52.5	67.0	5 200	54.7	64.9	5 700	62.0
66.0	46.4	64.1	3 600	48.8	63.0	4 100	50.9	60.8	4 500	66.0
70.0	42.6	59.7	2 700	44.9	58.5	3 100	46.8	56.1	3 400	70.0
74.0	38.4	54.6	1 900	40.6	53.3	2 200				74.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

67.1m (220 Ft.) BOOM										
21.3	80.2	92.3	23 400 *							21.3
22.0	79.8	92.2	23 200 *							22.0
24.0	78.5	91.7	22 700 *							24.0
26.0	77.3	91.2	22 300 *	80.0	90.4	19 900 *				26.0
28.0	76.0	90.6	21 900 *	78.6	89.8	19 600 *				28.0
30.0	74.7	90.0	21 500 *	77.3	89.2	19 300 *	80.0	87.6	14 200 *	30.0
32.0	73.3	89.4	20 300	76.0	88.5	19 000 *	78.7	86.9	13 800 *	32.0
34.0	72.0	88.6	18 500	74.7	87.8	18 700 *	77.3	86.2	13 400 *	34.0
36.0	70.7	87.9	16 900	73.3	87.0	18 100	75.9	85.4	13 000 *	36.0
38.0	69.3	87.1	15 400	72.0	86.2	16 500	74.6	84.5	12 700 *	38.0
42.0	66.6	85.2	12 800	69.2	84.4	13 800	71.7	82.6	12 000 *	42.0
46.0	63.8	83.2	10 600	66.4	82.3	11 500	68.8	80.5	11 400 *	46.0
50.0	60.9	80.9	8 700	63.5	80.0	9 400	65.9	78.1	10 200	50.0
54.0	57.9	78.3	7 000	60.4	77.3	7 700	62.8	75.4	8 400	54.0
58.0	54.9	75.4	5 500	57.3	74.4	6 200	59.6	72.4	6 800	58.0
62.0	51.7	72.1	4 300	54.1	71.1	4 900	56.2	69.0	5 400	62.0
66.0	48.3	68.5	3 300	50.6	67.4	3 700	52.7	65.2	4 200	66.0
70.0	44.7	64.3	2 300	47.0	63.2	2 700	48.9	60.8	3 100	70.0

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
21.3	80.6	95.5	23 400*							21.3
22.0	80.2	95.3	23 300*							22.0
24.0	78.9	94.9	22 900*							24.0
26.0	77.7	94.4	22 400*	80.3	93.6	20 000*				26.0
28.0	76.4	93.8	22 000*	79.0	93.0	19 700*				28.0
30.0	75.2	93.2	21 500	77.8	92.4	19 400*				30.0
32.0	73.9	92.6	19 700	76.5	91.8	19 100*	79.1	90.1	13 900*	32.0
34.0	72.6	91.9	17 900	75.2	91.1	18 800	77.8	89.4	13 500*	34.0
36.0	71.3	91.1	16 300	73.9	90.3	17 600	76.4	88.6	13 100*	36.0
38.0	70.0	90.4	14 900	72.6	89.5	16 000	75.1	87.8	12 800*	38.0
42.0	67.4	88.6	12 300	69.9	87.7	13 300	72.4	86.0	12 100*	42.0
46.0	64.7	86.6	10 200	67.2	85.8	11 100	69.6	84.0	11 600	46.0
50.0	62.0	84.4	8 300	64.4	83.5	9 100	66.8	81.7	9 900	50.0
54.0	59.1	81.9	6 600	61.5	81.0	7 400	63.8	79.1	8 100	54.0
58.0	56.2	79.2	5 200	58.6	78.2	5 900	60.8	76.2	6 500	58.0
62.0	53.1	76.1	4 000	55.5	75.1	4 600	57.6	73.0	5 100	62.0
66.0	50.0	72.6	2 900	52.3	71.6	3 400	54.3	69.4	3 900	66.0
70.0	46.6	68.8	2 000	48.8	67.6	2 400	50.7	65.4	2 800	70.0

Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

73.2m (240 Ft.) BOOM										
21.3	80.9	98.6	23 600 *							21.3
22.0	80.5	98.4	23 400 *							22.0
24.0	79.3	98.0	23 000 *							24.0
26.0	78.1	97.5	22 600 *	80.6	96.7	20 100 *				26.0
28.0	76.9	97.0	22 200 *	79.4	96.2	19 800 *				28.0
30.0	75.6	96.4	21 200	78.2	95.6	19 500 *				30.0
32.0	74.4	95.8	19 100	76.9	95.0	19 200 *	79.4	93.3	14 000 *	32.0
34.0	73.2	95.1	17 300	75.7	94.3	18 700	78.2	92.6	13 600 *	34.0
36.0	71.9	94.4	15 700	74.4	93.6	17 000	76.9	91.9	13 200 *	36.0
38.0	70.7	93.6	14 300	73.2	92.8	15 500	75.6	91.1	12 800 *	38.0
42.0	68.2	92.0	11 700	70.6	91.1	12 800	73.0	89.3	12 300 *	42.0
46.0	65.6	90.1	9 600	68.0	89.2	10 600	70.3	87.4	11 600	46.0
50.0	62.9	87.9	7 800	65.3	87.0	8 600	67.6	85.2	9 500	50.0
54.0	60.2	85.6	6 200	62.6	84.6	7 000	64.8	82.7	7 700	54.0
58.0	57.4	82.9	4 800	59.7	81.9	5 500	61.9	80.0	6 200	58.0
62.0	54.5	80.0	3 600	56.8	79.0	4 200	58.9	76.9	4 800	62.0
66.0	51.5	76.7	2 500	53.7	75.7	3 000	55.7	73.5	3 500	66.0
70.0				50.5	72.0	2 100	52.4	69.7	2 500	70.0

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
22.9	80.3	101.4	23 400 *							22.9
24.0	79.6	101.1	23 100 *							24.0
26.0	78.4	100.6	22 700 *	80.9	99.8	20 100 *				26.0
28.0	77.3	100.1	22 300 *	79.7	99.3	19 800 *				28.0
30.0	76.1	99.6	21 200	78.5	98.7	19 600 *				30.0
32.0	74.9	99.0	19 100	77.3	98.1	19 300 *	79.8	96.5	14 100 *	32.0
34.0	73.7	98.3	17 300	76.1	97.5	18 800	78.6	95.8	13 700 *	34.0
36.0	72.5	97.6	15 700	74.9	96.8	17 000	77.3	95.1	13 300 *	36.0
38.0	71.3	96.9	14 300	73.7	96.0	15 500	76.1	94.3	12 900 *	38.0
42.0	68.9	95.3	11 800	71.2	94.4	12 800	73.6	92.7	12 300 *	42.0
46.0	66.4	93.5	9 700	68.7	92.6	10 600	71.0	90.8	11 600	46.0
50.0	63.8	91.4	7 900	66.1	90.5	8 700	68.4	88.7	9 600	50.0
54.0	61.2	89.1	6 300	63.5	88.2	7 100	65.7	86.3	7 900	54.0
58.0	58.5	86.6	5 000	60.8	85.6	5 700	62.9	83.7	6 300	58.0
62.0	55.8	83.8	3 800	58.0	82.8	4 400	60.0	80.8	5 000	62.0
66.0	52.9	80.7	2 700	55.1	79.7	3 200	57.0	77.6	3 700	66.0
70.0				52.0	76.2	2 200	53.9	74.0	2 700	70.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
18.3	80.1	71.2	18 300 *							18.3
20.0	78.7	70.8	17 900 *							20.0
22.0	77.0	70.2	17 400 *							22.0
24.0	75.3	69.6	16 900 *	79.8	68.9	15 400 *				24.0
26.0	73.6	68.9	16 500 *	78.0	68.2	15 000 *				26.0
28.0	71.9	68.1	16 100 *	76.3	67.4	14 600 *				28.0
30.0	70.1	67.3	15 700 *	74.5	66.6	14 200 *	79.4	65.1	11 500 *	30.0
32.0	68.3	66.4	15 300 *	72.7	65.7	13 800 *	77.5	64.2	11 100 *	32.0
34.0	66.5	65.4	14 900 *	70.9	64.7	13 400 *	75.6	63.2	10 600 *	34.0
36.0	64.7	64.4	14 400 *	69.0	63.6	13 100 *	73.7	62.1	10 300 *	36.0
38.0	62.8	63.2	14 000 *	67.1	62.4	12 800 *	71.8	61.0	9 900 *	38.0
42.0	59.0	60.7	13 300 *	63.2	59.9	12 200 *	67.8	58.3	9 300 *	42.0
46.0	54.9	57.7	12 600 *	59.1	56.8	11 600 *	63.6	55.3	8 700 *	46.0
50.0	50.7	54.3	11 900 *	54.8	53.3	10 800 *	59.1	51.7	8 200 *	50.0
54.0	46.1	50.3	10 400	50.1	49.3	10 100 *	54.2	47.5	7 800 *	54.0
58.0	41.0	45.5	9 000	44.9	44.4	9 400	48.8	42.4	7 500 *	58.0
62.0	35.3	39.8	7 800	39.1	38.4	8 100				62.0
42.7m (140 Ft.) BOOM										
18.3	80.5	74.3	18 500 *							18.3
20.0	79.2	73.9	18 000 *							20.0
22.0	77.6	73.4	17 500 *							22.0
24.0	75.9	72.8	17 100 *							24.0
26.0	74.3	72.1	16 700 *	78.6	71.4	15 100 *				26.0
28.0	72.7	71.4	16 300 *	76.9	70.6	14 700 *				28.0
30.0	71.0	70.6	15 900 *	75.2	69.8	14 300 *	79.8	68.4	11 700 *	30.0
32.0	69.3	69.8	15 500 *	73.5	69.0	14 000 *	78.1	67.5	11 200 *	32.0
34.0	67.6	68.8	15 100 *	71.8	68.0	13 600 *	76.3	66.6	10 800 *	34.0
36.0	65.8	67.8	14 700 *	70.0	67.0	13 300 *	74.5	65.5	10 400 *	36.0
38.0	64.1	66.8	14 300 *	68.2	65.9	12 900 *	72.7	64.4	10 000 *	38.0
42.0	60.4	64.3	13 500 *	64.5	63.5	12 300 *	68.9	61.9	9 400 *	42.0
46.0	56.7	61.6	12 800 *	60.7	60.7	11 800 *	65.0	59.1	8 800 *	46.0
50.0	52.7	58.4	11 700	56.6	57.4	11 100 *	60.8	55.7	8 400 *	50.0
54.0	48.4	54.7	10 000	52.3	53.7	10 400	56.3	51.9	8 000 *	54.0
58.0	43.9	50.4	8 600	47.7	49.2	9 000	51.5	47.3	7 600 *	58.0
62.0	38.8	45.2	7 400	42.5	44.0	7 800	46.0	41.9	7 300 *	62.0
66.0	33.0	39.0	6 400	36.5	37.5	6 600				66.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
18.3	80.9	77.4	18 500 *							18.3
20.0	79.6	77.1	18 100 *							20.0
22.0	78.1	76.5	17 700 *							22.0
24.0	76.5	76.0	17 300 *							24.0
26.0	75.0	75.3	16 800 *	79.0	74.6	15 200*				26.0
28.0	73.4	74.7	16 400 *	77.4	73.9	14 900*				28.0
30.0	71.8	73.9	16 100 *	75.8	73.1	14 500*				30.0
32.0	70.2	73.1	15 700 *	74.2	72.3	14 100*	78.6	70.8	11 300*	32.0
34.0	68.5	72.2	15 300 *	72.6	71.4	13 800*	76.9	69.9	10 900*	34.0
36.0	66.9	71.2	14 900 *	70.9	70.4	13 400*	75.2	68.9	10 600*	36.0
38.0	65.2	70.2	14 500 *	69.2	69.4	13 100*	73.5	67.8	10 200*	38.0
42.0	61.8	67.9	13 800 *	65.7	67.1	12 500*	69.9	65.5	9 600*	42.0
46.0	58.2	65.3	13 100	62.1	64.4	12 000*	66.2	62.8	9 000*	46.0
50.0	54.5	62.3	11 300	58.3	61.4	11 400*	62.3	59.7	8 500*	50.0
54.0	50.5	58.9	9 700	54.3	57.9	10 200	58.2	56.1	8 100*	54.0
58.0	46.3	54.9	8 300	50.0	53.8	8 700	53.7	51.9	7 700*	58.0
62.0	41.8	50.3	7 000	45.3	49.1	7 400	48.9	47.0	7 500*	62.0
66.0	36.7	44.8	6 000	40.1	43.4	6 300				66.0
70.0	30.8	38.0	5 100	34.0	36.4	5 300				70.0
48.8m (160 Ft.) BOOM										
19.8	80.2	80.2	18 300 *							19.8
20.0	80.0	80.2	18 300 *							20.0
22.0	78.5	79.7	17 800 *							22.0
24.0	77.1	79.1	17 400 *							24.0
26.0	75.6	78.5	17 000 *	79.5	77.7	15 300*				26.0
28.0	74.0	77.9	16 600 *	78.0	77.1	15 000*				28.0
30.0	72.5	77.2	16 200 *	76.4	76.4	14 600*				30.0
32.0	71.0	76.4	15 900 *	74.9	75.6	14 200*	79.1	74.0	11 500*	32.0
34.0	69.4	75.5	15 500 *	73.3	74.7	13 900*	77.5	73.1	11 100*	34.0
36.0	67.8	74.6	15 200 *	71.7	73.8	13 600*	75.9	72.2	10 700*	36.0
38.0	66.2	73.7	14 800 *	70.1	72.8	13 300*	74.2	71.2	10 400*	38.0
42.0	63.0	71.5	14 000 *	66.8	70.6	12 700*	70.8	69.0	9 700*	42.0
46.0	59.6	69.0	12 900	63.3	68.1	12 200*	67.3	66.4	9 200*	46.0
50.0	56.1	66.2	10 900	59.8	65.2	11 500	63.6	63.5	8 700*	50.0
54.0	52.4	63.0	9 300	56.0	62.0	9 900	59.8	60.2	8 300*	54.0
58.0	48.5	59.3	7 900	52.0	58.2	8 400	55.7	56.3	7 900*	58.0
62.0	44.3	55.0	6 600	47.8	53.9	7 100	51.2	51.8	7 600*	62.0
66.0	39.7	50.1	5 600	43.1	48.8	6 000	46.4	46.6	6 600	66.0
70.0	34.6	44.2	4 600	37.8	42.7	5 000				70.0
74.0	28.6	36.8	3 800							74.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
19.8	80.5	83.3	18 500 *							19.8
20.0	80.4	83.3	18 400 *							20.0
22.0	79.0	82.8	17 900 *							22.0
24.0	77.5	82.3	17 500 *							24.0
26.0	76.1	81.7	17 200 *	79.9	80.9	15 400*				26.0
28.0	74.7	81.1	16 800 *	78.4	80.3	15 100*				28.0
30.0	73.2	80.4	16 400 *	76.9	79.6	14 700*				30.0
32.0	71.7	79.7	16 100 *	75.5	78.8	14 400*	79.5	77.2	11 600*	32.0
34.0	70.2	78.8	15 700 *	73.9	78.0	14 100*	78.0	76.4	11 200*	34.0
36.0	68.7	78.0	15 400 *	72.4	77.1	13 700*	76.4	75.5	10 800*	36.0
38.0	67.2	77.0	15 000 *	70.9	76.2	13 400*	74.9	74.6	10 400*	38.0
42.0	64.1	75.0	14 300 *	67.7	74.1	12 800*	71.6	72.4	9 800*	42.0
46.0	60.9	72.6	12 600	64.5	71.7	12 300*	68.3	70.0	9 300*	46.0
50.0	57.5	69.9	10 700	61.1	69.0	11 500	64.9	67.3	8 800*	50.0
54.0	54.1	66.9	9 000	57.6	65.9	9 700	61.2	64.1	8 400*	54.0
58.0	50.4	63.5	7 600	53.9	62.4	8 200	57.4	60.5	8 000*	58.0
62.0	46.5	59.5	6 400	49.9	58.4	6 900	53.3	56.4	7 600	62.0
66.0	42.4	55.0	5 300	45.6	53.8	5 800	48.9	51.6	6 400	66.0
70.0	37.8	49.7	4 400	40.9	48.4	4 700				70.0
74.0	32.6	43.4	3 600	35.6	41.8	3 900				74.0
54.9m (180 Ft.) BOOM										
19.8	80.9	86.5	18 500 *							19.8
20.0	80.7	86.4	18 500 *							20.0
22.0	79.4	86.0	18 100 *							22.0
24.0	78.0	85.5	17 700 *							24.0
26.0	76.6	84.9	17 300 *	80.3	84.1	15 500*				26.0
28.0	75.2	84.3	16 900 *	78.9	83.5	15 200*				28.0
30.0	73.8	83.6	16 500 *	77.4	82.8	14 800*				30.0
32.0	72.4	82.9	16 200 *	76.0	82.1	14 500*				32.0
34.0	71.0	82.1	15 900 *	74.6	81.3	14 200*	78.5	79.6	11 300*	34.0
36.0	69.5	81.3	15 500 *	73.1	80.4	13 900*	77.0	78.8	10 900*	36.0
38.0	68.1	80.4	15 200 *	71.6	79.5	13 600*	75.5	77.9	10 600*	38.0
42.0	65.1	78.4	14 400	68.6	77.5	13 000*	72.4	75.9	10 000*	42.0
46.0	62.0	76.2	12 300	65.5	75.3	12 500*	69.2	73.5	9 400*	46.0
50.0	58.9	73.7	10 300	62.3	72.7	11 100	65.9	70.9	9 000*	50.0
54.0	55.6	70.8	8 600	59.0	69.8	9 300	62.5	68.0	8 500*	54.0
58.0	52.1	67.5	7 200	55.5	66.5	7 900	58.9	64.6	8 200*	58.0
62.0	48.5	63.9	6 000	51.8	62.8	6 500	55.1	60.8	7 400	62.0
66.0	44.7	59.7	4 900	47.9	58.5	5 400	51.1	56.4	6 200	66.0
70.0	40.5	54.9	4 000	43.6	53.6	4 400	46.6	51.3	5 100	70.0
74.0	35.9	49.2	3 200	38.9	47.8	3 500				74.0
78.0	30.6	42.4	2 400							78.0

Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
21.3	80.2	89.2	18 300 *							21.3
22.0	79.7	89.1	18 200 *							22.0
24.0	78.4	88.6	17 800 *							24.0
26.0	77.1	88.1	17 400 *	80.6	87.2	15 600*				26.0
28.0	75.7	87.5	17 000 *	79.3	86.6	15 300*				28.0
30.0	74.4	86.8	16 700 *	77.9	86.0	14 900*				30.0
32.0	73.0	86.2	16 400 *	76.5	85.3	14 600*				32.0
34.0	71.7	85.4	16 000 *	75.1	84.5	14 300*	78.9	82.9	11 400*	34.0
36.0	70.3	84.6	15 700 *	73.7	83.7	14 000*	77.5	82.1	11 000*	36.0
38.0	68.9	83.8	15 400 *	72.3	82.9	13 700*	76.0	81.2	10 700*	38.0
42.0	66.0	81.9	14 400	69.4	81.0	13 200*	73.1	79.2	10 100*	42.0
46.0	63.1	79.7	11 900	66.5	78.8	12 600	70.1	77.0	9 500*	46.0
50.0	60.1	77.3	9 900	63.4	76.3	10 800	66.9	74.6	9 100*	50.0
54.0	57.0	74.6	8 300	60.3	73.6	9 000	63.7	71.7	8 600*	54.0
58.0	53.7	71.5	6 900	57.0	70.5	7 500	60.3	68.6	8 300	58.0
62.0	50.3	68.1	5 600	53.5	67.0	6 200	56.8	65.0	7 100	62.0
66.0	46.7	64.2	4 600	49.8	63.0	5 100	53.0	60.9	5 900	66.0
70.0	42.9	59.7	3 600	45.9	58.5	4 100	48.9	56.2	4 800	70.0
74.0	38.7	54.6	2 800	41.6	53.2	3 200				74.0
78.0	34.0	48.6	2 100	36.8	47.0	2 400				78.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
21.3	80.5	92.4	18 500 *							21.3
22.0	80.1	92.2	18 300 *							22.0
24.0	78.8	91.7	17 900 *							24.0
26.0	77.5	91.2	17 500 *							26.0
28.0	76.2	90.7	17 200 *	79.6	89.8	15 300*				28.0
30.0	74.9	90.0	16 800 *	78.3	89.2	15 100*				30.0
32.0	73.6	89.4	16 500 *	77.0	88.5	14 700*				32.0
34.0	72.3	88.7	16 200 *	75.7	87.8	14 400*	79.3	86.1	11 500*	34.0
36.0	71.0	87.9	15 900 *	74.3	87.0	14 100*	77.9	85.3	11 100*	36.0
38.0	69.6	87.1	15 600 *	72.9	86.2	13 800*	76.5	84.5	10 800*	38.0
42.0	66.9	85.3	13 800	70.2	84.3	13 300*	73.7	82.6	10 200*	42.0
46.0	64.1	83.2	11 500	67.3	82.3	12 600	70.8	80.5	9 700*	46.0
50.0	61.2	80.9	9 600	64.4	79.9	10 500	67.8	78.1	9 200*	50.0
54.0	58.2	78.3	7 900	61.4	77.3	8 700	64.8	75.5	8 800*	54.0
58.0	55.1	75.4	6 500	58.3	74.3	7 200	61.6	72.4	8 300	58.0
62.0	51.9	72.1	5 200	55.0	71.0	5 900	58.2	69.1	6 800	62.0
66.0	48.6	68.5	4 200	51.6	67.3	4 700	54.7	65.3	5 600	66.0
70.0	45.0	64.4	3 200	48.0	63.1	3 700	50.9	60.9	4 500	70.0
74.0	41.1	59.7	2 400	44.0	58.3	2 800	46.8	56.0	3 500	74.0
78.0				39.7	52.7	2 000				78.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
21.3	80.8	95.5	18 500 *							21.3
22.0	80.4	95.3	18 400 *							22.0
24.0	79.2	94.9	18 000 *							24.0
26.0	77.9	94.4	17 700 *							26.0
28.0	76.7	93.8	17 300 *	80.0	93.0	15 400*				28.0
30.0	75.4	93.2	17 000 *	78.7	92.4	15 100*				30.0
32.0	74.2	92.6	16 600 *	77.4	91.7	14 800*				32.0
34.0	72.9	91.9	16 300 *	76.1	91.0	14 500*	79.7	89.3	11 600*	34.0
36.0	71.6	91.2	16 000 *	74.8	90.3	14 200*	78.4	88.5	11 200*	36.0
38.0	70.3	90.4	15 700 *	73.5	89.5	14 000*	77.0	87.7	10 900*	38.0
42.0	67.7	88.6	13 400	70.9	87.7	13 400*	74.3	85.9	10 300*	42.0
46.0	65.0	86.7	11 300	68.2	85.7	12 300	71.5	83.9	9 800*	46.0
50.0	62.2	84.4	9 300	65.4	83.5	10 200	68.7	81.6	9 300*	50.0
54.0	59.4	82.0	7 600	62.5	81.0	8 500	65.7	79.1	8 900*	54.0
58.0	56.5	79.2	6 200	59.5	78.2	7 000	62.7	76.2	8 100	58.0
62.0	53.4	76.1	5 000	56.4	75.0	5 600	59.5	73.1	6 700	62.0
66.0	50.2	72.7	3 900	53.2	71.5	4 500	56.2	69.5	5 400	66.0
70.0	46.9	68.8	3 000	49.8	67.6	3 500	52.7	65.4	4 300	70.0
74.0	43.3	64.4	2 200	46.1	63.1	2 600	48.9	60.8	3 300	74.0
67.1m (220 Ft.) BOOM										
22.9	80.2	98.3	18 300 *							22.9
24.0	79.5	98.0	18 100 *							24.0
26.0	78.3	97.5	17 800 *							26.0
28.0	77.1	97.0	17 400 *	80.3	96.1	15 500*				28.0
30.0	75.9	96.4	17 100 *	79.1	95.5	15 200*				30.0
32.0	74.7	95.8	16 800 *	77.8	94.9	14 900*				32.0
34.0	73.4	95.1	16 500 *	76.6	94.2	14 600*	80.0	92.5	11 700*	34.0
36.0	72.2	94.4	16 200 *	75.3	93.5	14 300*	78.8	91.8	11 300*	36.0
38.0	71.0	93.7	15 400	74.1	92.7	14 000*	77.5	91.0	11 000*	38.0
42.0	68.4	92.0	12 900	71.5	91.0	13 500*	74.9	89.3	10 400*	42.0
46.0	65.8	90.1	10 700	68.9	89.1	11 800	72.2	87.3	9 900*	46.0
50.0	63.2	87.9	8 900	66.2	87.0	9 900	69.5	85.1	9 400*	50.0
54.0	60.5	85.6	7 300	63.5	84.6	8 200	66.6	82.7	9 000*	54.0
58.0	57.7	82.9	5 800	60.6	81.9	6 600	63.7	80.0	7 800	58.0
62.0	54.8	80.0	4 600	57.7	78.9	5 300	60.7	76.9	6 400	62.0
66.0	51.7	76.7	3 500	54.6	75.6	4 100	57.6	73.6	5 100	66.0
70.0	48.6	73.1	2 600	51.4	71.9	3 100	54.3	69.8	4 000	70.0
74.0				48.0	67.7	2 200	50.7	65.5	3 000	74.0
78.0							47.0	60.6	2 100	78.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
22.9	80.5	101.4	18 400*							22.9
24.0	79.8	101.1	18 200*							24.0
26.0	78.7	100.7	17 900*							26.0
28.0	77.5	100.1	17 500*	80.6	99.3	15 600*				28.0
30.0	76.3	99.6	17 200*	79.4	98.7	15 300*				30.0
32.0	75.2	99.0	16 900*	78.2	98.1	15 000*				32.0
34.0	74.0	98.3	16 600*	77.0	97.4	14 700*	80.4	95.7	11 700*	34.0
36.0	72.8	97.7	16 100	75.8	96.7	14 500*	79.1	95.0	11 400*	36.0
38.0	71.6	96.9	14 900	74.6	96.0	14 200*	77.9	94.2	11 100*	38.0
42.0	69.1	95.3	12 300	72.1	94.4	13 500	75.4	92.6	10 500*	42.0
46.0	66.6	93.5	10 200	69.6	92.5	11 400	72.8	90.7	10 000*	46.0
50.0	64.1	91.4	8 500	67.0	90.4	9 500	70.2	88.6	9 500*	50.0
54.0	61.5	89.1	6 900	64.4	88.1	7 800	67.5	86.3	9 000	54.0
58.0	58.8	86.6	5 500	61.7	85.6	6 300	64.7	83.7	7 500	58.0
62.0	56.0	83.8	4 200	58.9	82.7	5 000	61.8	80.8	6 100	62.0
66.0	53.1	80.7	3 200	56.0	79.6	3 800	58.8	77.5	4 900	66.0
70.0	50.1	77.3	2 200	52.9	76.1	2 800	55.7	74.0	3 700	70.0
74.0				49.7	72.2	1 900	52.4	70.0	2 800	74.0
73.2m (240 Ft.) BOOM										
22.9	80.8	104.5	18 500*							22.9
24.0	80.2	104.2	18 300*							24.0
26.0	79.0	103.8	18 000*							26.0
28.0	77.9	103.3	17 600*							28.0
30.0	76.7	102.8	17 300*	79.7	101.8	15 400*				30.0
32.0	75.6	102.2	17 000*	78.6	101.3	15 100*				32.0
34.0	74.5	101.6	16 700	77.4	100.6	14 800*	80.7	98.8	11 800*	34.0
36.0	73.3	100.9	15 800	76.3	100.0	14 600*	79.5	98.2	11 500*	36.0
38.0	72.1	100.2	14 300	75.1	99.2	14 300*	78.3	97.4	11 200*	38.0
42.0	69.8	98.6	11 800	72.7	97.7	13 200	75.8	95.8	10 600*	42.0
46.0	67.4	96.8	9 700	70.3	95.9	10 900	73.4	94.0	10 100*	46.0
50.0	64.9	94.9	7 900	67.8	93.9	9 000	70.8	92.0	9 600*	50.0
54.0	62.4	92.7	6 400	65.2	91.7	7 400	68.2	89.8	8 800	54.0
58.0	59.8	90.3	5 000	62.6	89.2	5 900	65.6	87.3	7 200	58.0
62.0	57.2	87.6	3 900	60.0	86.5	4 600	62.8	84.5	5 800	62.0
66.0	54.4	84.6	2 800	57.2	83.5	3 500	60.0	81.5	4 600	66.0
70.0	51.6	81.3	1 800	54.3	80.2	2 500	57.0	78.1	3 500	70.0
74.0							53.9	74.3	2 500	74.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
18.3	80.9	77.5	14 800 *							18.3
20.0	79.6	77.1	14 400 *							20.0
22.0	78.0	76.6	13 900 *							22.0
24.0	76.5	76.0	13 500 *							24.0
26.0	74.9	75.4	13 000 *	80.1	74.8	10 800 *				26.0
28.0	73.4	74.7	12 600 *	78.5	74.1	10 400 *				28.0
30.0	71.8	73.9	12 100 *	76.9	73.4	10 000 *				30.0
32.0	70.1	73.1	11 700 *	75.3	72.6	9 700 *				32.0
34.0	68.5	72.2	11 200 *	73.7	71.7	9 400 *	78.7	70.0	8 100 *	34.0
36.0	66.9	71.3	10 800 *	72.0	70.7	9 100 *	77.0	69.0	7 900 *	36.0
38.0	65.2	70.3	10 400 *	70.3	69.7	8 800 *	75.3	68.0	7 700 *	38.0
42.0	61.8	68.0	9 700 *	66.8	67.4	8 200 *	71.7	65.6	7 200 *	42.0
46.0	58.2	65.4	9 000 *	63.2	64.8	7 700 *	68.0	63.0	6 800 *	46.0
50.0	54.5	62.4	8 400 *	59.5	61.8	7 200 *	64.2	59.9	6 400 *	50.0
54.0	50.5	58.9	7 800 *	55.5	58.4	6 800 *	60.0	56.3	6 100 *	54.0
58.0	46.3	55.0	7 300 *	51.3	54.4	6 400 *	55.6	52.1	5 800 *	58.0
62.0	41.8	50.4	6 800 *	46.6	49.7	6 000 *	50.8	47.3	5 600 *	62.0
66.0	36.7	44.9	6 400 *	41.5	44.2	5 700 *	45.3	41.4	5 400 *	66.0
70.0	30.8	38.1	6 000	35.5	37.3	5 500 *				70.0
42.7m (140 Ft.) BOOM										
19.8	80.1	80.3	14 600 *							19.8
20.0	80.0	80.2	14 600 *							20.0
22.0	78.5	79.7	14 100 *							22.0
24.0	77.0	79.2	13 600 *							24.0
26.0	75.5	78.6	13 200 *	80.5	78.0	10 900 *				26.0
28.0	74.0	77.9	12 700 *	79.0	77.3	10 500 *				28.0
30.0	72.5	77.2	12 300 *	77.5	76.6	10 200 *				30.0
32.0	71.0	76.4	11 900 *	75.9	75.8	9 800 *				32.0
34.0	69.4	75.6	11 500 *	74.3	75.0	9 500 *	79.2	73.3	8 200 *	34.0
36.0	67.8	74.7	11 100 *	72.8	74.1	9 200 *	77.6	72.3	8 000 *	36.0
38.0	66.2	73.7	10 700 *	71.1	73.1	8 900 *	75.9	71.3	7 800 *	38.0
42.0	63.0	71.5	10 000 *	67.9	70.9	8 300 *	72.6	69.1	7 300 *	42.0
46.0	59.6	69.1	9 300 *	64.4	68.5	7 800 *	69.1	66.6	6 900 *	46.0
50.0	56.1	66.2	8 700 *	60.9	65.6	7 300 *	65.4	63.7	6 500 *	50.0
54.0	52.4	63.0	8 100 *	57.2	62.4	7 000 *	61.6	60.3	6 200 *	54.0
58.0	48.5	59.3	7 600 *	53.2	58.7	6 600 *	57.5	56.5	5 900 *	58.0
62.0	44.3	55.1	7 100 *	49.0	54.4	6 200 *	53.0	52.0	5 700 *	62.0
66.0	39.7	50.2	6 500	44.4	49.5	5 900 *	48.2	46.8	5 500 *	66.0
70.0	34.6	44.3	5 600	39.2	43.5	5 600 *				70.0
74.0	28.6	36.9	4 800	33.0	36.0	5 300				74.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
19.8	80.5	83.4	14 700 *							19.8
20.0	80.4	83.3	14 700 *							20.0
22.0	78.9	82.9	14 200 *							22.0
24.0	77.5	82.4	13 800 *							24.0
26.0	76.1	81.8	13 400 *							26.0
28.0	74.6	81.1	12 900 *	79.4	80.5	10 600*				28.0
30.0	73.2	80.4	12 500 *	78.0	79.8	10 300*				30.0
32.0	71.7	79.7	12 100 *	76.5	79.1	9 900*				32.0
34.0	70.2	78.9	11 700 *	75.0	78.3	9 600*	79.7	76.5	8 300*	34.0
36.0	68.7	78.0	11 300 *	73.5	77.4	9 300*	78.1	75.6	8 000*	36.0
38.0	67.2	77.1	10 900 *	71.9	76.5	9 000*	76.5	74.7	7 900*	38.0
42.0	64.1	75.0	10 200 *	68.8	74.4	8 500*	73.3	72.6	7 400*	42.0
46.0	60.8	72.7	9 500 *	65.5	72.0	8 000*	70.0	70.1	7 000*	46.0
50.0	57.5	70.0	8 900 *	62.2	69.4	7 500*	66.5	67.4	6 600*	50.0
54.0	54.1	67.0	8 300 *	58.7	66.3	7 100*	62.9	64.2	6 300*	54.0
58.0	50.4	63.5	7 800 *	55.0	62.9	6 700*	59.1	60.7	6 100*	58.0
62.0	46.5	59.6	7 200	51.1	58.9	6 300*	55.0	56.6	5 800*	62.0
66.0	42.4	55.1	6 100	46.9	54.4	6 000*	50.6	51.8	5 600*	66.0
70.0	37.8	49.8	5 200	42.2	49.1	5 800*	45.7	46.2	5 400*	70.0
74.0	32.6	43.5	4 400	36.9	42.6	4 900				74.0
48.8m (160 Ft.) BOOM										
19.8	80.8	86.5	14 800 *							19.8
20.0	80.7	86.5	14 800 *							20.0
22.0	79.4	86.0	14 300 *							22.0
24.0	78.0	85.5	14 000 *							24.0
26.0	76.6	84.9	13 500 *							26.0
28.0	75.2	84.3	13 100 *	79.8	83.7	10 700*				28.0
30.0	73.8	83.7	12 700 *	78.4	83.0	10 400*				30.0
32.0	72.4	83.0	12 300 *	77.0	82.3	10 100*				32.0
34.0	70.9	82.2	11 900 *	75.5	81.5	9 800*	80.1	79.7	8 400*	34.0
36.0	69.5	81.4	11 500 *	74.1	80.7	9 500*	78.6	78.9	8 100*	36.0
38.0	68.0	80.5	11 100 *	72.6	79.8	9 200*	77.1	78.0	7 900*	38.0
42.0	65.1	78.5	10 400 *	69.6	77.8	8 600*	74.0	76.0	7 500*	42.0
46.0	62.0	76.2	9 700 *	66.5	75.6	8 100*	70.8	73.6	7 000*	46.0
50.0	58.8	73.7	9 200 *	63.3	73.0	7 700*	67.6	71.0	6 800*	50.0
54.0	55.6	70.8	8 600 *	60.0	70.2	7 200*	64.1	68.1	6 400*	54.0
58.0	52.1	67.6	8 000	56.6	66.9	6 800*	60.6	64.7	6 200*	58.0
62.0	48.5	63.9	6 800	52.9	63.2	6 500*	56.8	60.9	5 900*	62.0
66.0	44.7	59.8	5 700	49.0	59.0	6 200*	52.7	56.5	5 700*	66.0
70.0	40.5	55.0	4 800	44.8	54.2	5 500	48.2	51.4	5 500*	70.0
74.0	35.9	49.3	4 000	40.1	48.5	4 600				74.0
78.0	30.6	42.5	3 300	34.7	41.6	3 800				78.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
21.3	80.2	89.3	14 600 *							21.3
22.0	79.7	89.1	14 500 *							22.0
24.0	78.4	88.7	14 100 *							24.0
26.0	77.1	88.1	13 700 *							26.0
28.0	75.7	87.5	13 200 *	80.2	86.8	10 800*				28.0
30.0	74.4	86.9	12 800 *	78.8	86.2	10 400*				30.0
32.0	73.0	86.2	12 500 *	77.5	85.5	10 200*				32.0
34.0	71.6	85.5	12 100 *	76.1	84.8	9 900*	80.4	82.9	8 400*	34.0
36.0	70.2	84.7	11 700 *	74.7	84.0	9 600*	79.0	82.1	8 200*	36.0
38.0	68.8	83.8	11 400 *	73.3	83.1	9 300*	77.6	81.3	8 000*	38.0
42.0	66.0	81.9	10 600 *	70.4	81.2	8 800*	74.6	79.3	7 600*	42.0
46.0	63.1	79.8	10 000 *	67.4	79.1	8 300*	71.6	77.1	7 200*	46.0
50.0	60.1	77.3	9 400 *	64.4	76.7	7 800*	68.5	74.6	6 900*	50.0
54.0	56.9	74.6	8 800 *	61.3	73.9	7 400*	65.2	71.8	6 500*	54.0
58.0	53.7	71.6	7 700	58.0	70.9	7 000*	61.9	68.7	6 200*	58.0
62.0	50.3	68.1	6 500	54.6	67.4	6 700*	58.3	65.1	6 000*	62.0
66.0	46.7	64.2	5 500	50.9	63.5	6 300	54.5	61.0	5 800*	66.0
70.0	42.9	59.8	4 600	47.0	59.0	5 300	50.5	56.3	5 600*	70.0
74.0	38.7	54.7	3 700	42.8	53.9	4 400	46.0	50.9	4 800	74.0
78.0	34.0	48.7	3 000	38.0	47.8	3 600				78.0
82.0	28.7	41.4	2 300	32.5	40.3	2 900				82.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
21.3	80.5	92.4	14 700 *							21.3
22.0	80.1	92.3	14 600 *							22.0
24.0	78.8	91.8	14 200 *							24.0
26.0	77.5	91.3	13 800 *							26.0
28.0	76.2	90.7	13 400 *	80.5	90.0	10 900*				28.0
30.0	74.9	90.1	13 000 *	79.2	89.4	10 500*				30.0
32.0	73.6	89.4	12 700 *	77.9	88.7	10 200*				32.0
34.0	72.3	88.7	12 200 *	76.6	88.0	9 900*				34.0
36.0	70.9	87.9	11 900 *	75.2	87.2	9 700*	79.4	85.4	8 300*	36.0
38.0	69.6	87.1	11 500 *	73.9	86.4	9 400*	78.0	84.5	8 000*	38.0
42.0	66.9	85.3	10 800 *	71.1	84.6	8 900*	75.2	82.7	7 700*	42.0
46.0	64.1	83.3	10 200 *	68.3	82.6	8 400*	72.3	80.6	7 300*	46.0
50.0	61.2	80.9	9 600 *	65.4	80.2	8 000*	69.3	78.2	6 900*	50.0
54.0	58.2	78.3	8 800	62.4	77.6	7 600*	66.3	75.5	6 600*	54.0
58.0	55.1	75.4	7 400	59.3	74.7	7 200*	63.1	72.5	6 300*	58.0
62.0	51.9	72.2	6 200	56.0	71.5	6 800*	59.7	69.1	6 100*	62.0
66.0	48.6	68.5	5 100	52.6	67.8	6 000	56.2	65.3	5 900*	66.0
70.0	45.0	64.4	4 100	49.0	63.6	5 000	52.4	61.0	5 500	70.0
74.0	41.1	59.7	3 300	45.1	58.9	4 100	48.3	56.0	4 500	74.0
78.0	36.9	54.3	2 600	40.8	53.4	3 300				78.0
82.0	32.2	47.9	2 000	36.0	46.9	2 500				82.0

Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
21.3	80.8	95.5	14 800 *							21.3
22.0	80.4	95.4	14 700 *							22.0
24.0	79.2	94.9	14 300 *							24.0
26.0	77.9	94.4	13 900 *							26.0
28.0	76.7	93.9	13 500 *							28.0
30.0	75.4	93.3	13 100 *	79.6	92.6	10 600*				30.0
32.0	74.1	92.6	12 800 *	78.3	91.9	10 300*				32.0
34.0	72.9	92.0	12 400 *	77.0	91.2	10 000*				34.0
36.0	71.6	91.2	12 100 *	75.7	90.5	9 800*	79.8	88.6	8 300*	36.0
38.0	70.3	90.4	11 700 *	74.4	89.7	9 500*	78.5	87.8	8 100*	38.0
42.0	67.7	88.7	11 100 *	71.8	88.0	9 000*	75.7	86.0	7 700*	42.0
46.0	65.0	86.7	10 400 *	69.1	86.0	8 500*	73.0	84.0	7 400*	46.0
50.0	62.2	84.5	9 800 *	66.3	83.8	8 100*	70.1	81.7	7 000*	50.0
54.0	59.4	82.0	8 400	63.4	81.3	7 700*	67.2	79.1	6 700*	54.0
58.0	56.4	79.2	7 000	60.5	78.5	7 300*	64.1	76.3	6 400*	58.0
62.0	53.4	76.2	5 800	57.4	75.4	6 900	61.0	73.1	6 200*	62.0
66.0	50.2	72.7	4 700	54.2	72.0	5 700	57.6	69.5	6 000*	66.0
70.0	46.9	68.9	3 800	50.8	68.1	4 700	54.1	65.5	5 200	70.0
74.0	43.3	64.5	3 000	47.2	63.7	3 800	50.3	60.9	4 300	74.0
78.0	39.5	59.5	2 300	43.3	58.7	3 000	46.2	55.6	3 400	78.0
82.0				39.0	52.8	2 200				82.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
22.9	80.2	98.3	14 600 *							22.9
24.0	79.5	98.0	14 400 *							24.0
26.0	78.3	97.6	14 000 *							26.0
28.0	77.1	97.0	13 700 *							28.0
30.0	75.9	96.5	13 300 *	79.9	95.7	10 700*				30.0
32.0	74.7	95.8	12 900 *	78.7	95.1	10 400*				32.0
34.0	73.4	95.2	12 600 *	77.5	94.4	10 100*				34.0
36.0	72.2	94.5	12 200 *	76.2	93.7	9 900*	80.1	91.8	8 400*	36.0
38.0	70.9	93.7	11 900 *	74.9	93.0	9 600*	78.8	91.0	8 200*	38.0
42.0	68.4	92.0	11 200 *	72.4	91.3	9 100*	76.2	89.3	7 800*	42.0
46.0	65.8	90.1	10 600 *	69.8	89.4	8 700*	73.6	87.3	7 400*	46.0
50.0	63.2	88.0	9 700	67.1	87.3	8 200*	70.8	85.2	7 100*	50.0
54.0	60.5	85.6	8 000	64.4	84.9	7 800*	68.0	82.7	6 800*	54.0
58.0	57.7	83.0	6 600	61.5	82.2	7 500*	65.1	80.0	6 500*	58.0
62.0	54.8	80.1	5 400	58.6	79.3	6 600	62.1	77.0	6 300*	62.0
66.0	51.7	76.8	4 300	55.6	76.0	5 400	59.0	73.6	6 000	66.0
70.0	48.6	73.1	3 400	52.4	72.4	4 400	55.7	69.8	5 000	70.0
74.0	45.2	69.1	2 600	49.0	68.2	3 400	52.1	65.5	4 000	74.0
78.0				45.4	63.6	2 600	48.4	60.7	3 100	78.0
82.0				41.5	58.3	1 900	44.2	55.1	2 300	82.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
76 750 kg Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
22.9	80.5	101.4	14 700 *							22.9
24.0	79.8	101.2	14 500 *							24.0
26.0	78.7	100.7	14 200 *							26.0
28.0	77.5	100.2	13 800 *							28.0
30.0	76.3	99.6	13 500 *	80.2	98.9	10 800*				30.0
32.0	75.1	99.0	13 100 *	79.0	98.3	10 500*				32.0
34.0	73.9	98.4	12 800 *	77.9	97.6	10 200*				34.0
36.0	72.7	97.7	12 400 *	76.6	96.9	10 000*				36.0
38.0	71.5	97.0	12 000 *	75.4	96.2	9 700*	79.2	94.2	8 200*	38.0
42.0	69.1	95.3	11 400 *	73.0	94.6	9 200*	76.7	92.6	7 900*	42.0
46.0	66.6	93.5	10 800 *	70.4	92.8	8 800*	74.1	90.7	7 500*	46.0
50.0	64.1	91.5	9 400	67.9	90.7	8 300*	71.5	88.6	7 200*	50.0
54.0	61.5	89.2	7 800	65.3	88.4	8 000*	68.8	86.3	6 900*	54.0
58.0	58.8	86.7	6 400	62.5	85.9	7 600	66.0	83.7	6 600*	58.0
62.0	56.0	83.9	5 100	59.8	83.1	6 300	63.2	80.8	6 400*	62.0
66.0	53.1	80.8	4 100	56.9	80.0	5 200	60.2	77.6	5 900	66.0
70.0	50.1	77.3	3 100	53.8	76.5	4 200	57.0	74.0	4 800	70.0
74.0	47.0	73.5	2 300	50.7	72.6	3 200	53.8	70.0	3 800	74.0
78.0				47.3	68.3	2 400	50.2	65.5	2 900	78.0
82.0							46.5	60.3	2 100	82.0



Liftcrane Jib Capacities

2250 SERIES 1

Jib No. 132 with 6 096 mm Strut on
 Boom No. 44 With Heavy Lift Top
 76 750 kg Counterweight
 360 Degree Rating

Maximum Operating Wind Speeds
 (all Jib Lengths)
 10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
22.9	80.8	104.5	14 800 *							22.9
24.0	80.1	104.3	14 700 *							24.0
26.0	79.0	103.8	14 300 *							26.0
28.0	77.9	103.3	13 900 *							28.0
30.0	76.7	102.8	13 600 *							30.0
32.0	75.6	102.2	13 200 *	79.4	101.4	10 600*				32.0
34.0	74.4	101.6	12 900 *	78.2	100.8	10 300*				34.0
36.0	73.3	100.9	12 500 *	77.1	100.2	10 100*				36.0
38.0	72.1	100.2	12 200 *	75.9	99.4	9 800*	79.6	97.4	8 300*	38.0
42.0	69.7	98.7	11 600 *	73.5	97.9	9 300*	77.1	95.8	7 900*	42.0
46.0	67.3	96.9	10 700	71.1	96.1	8 900*	74.7	94.0	7 600*	46.0
50.0	64.9	94.9	8 900	68.6	94.1	8 500*	72.1	92.0	7 300*	50.0
54.0	62.4	92.7	7 400	66.1	92.0	8 100*	69.5	89.8	7 000*	54.0
58.0	59.8	90.3	6 000	63.5	89.5	7 400	66.9	87.3	6 700*	58.0
62.0	57.2	87.6	4 800	60.8	86.8	6 100	64.1	84.5	6 400*	62.0
66.0	54.4	84.7	3 700	58.0	83.9	4 900	61.3	81.5	5 600	66.0
70.0	51.6	81.4	2 700	55.2	80.6	3 800	58.3	78.1	4 500	70.0
74.0	48.6	77.7	1 900	52.2	76.9	2 900	55.2	74.3	3 500	74.0
78.0				49.0	72.8	2 100	51.9	70.1	2 600	78.0
70.1m (230 Ft.) BOOM										
24.4	80.2	107.3	14 700 *							24.4
26.0	79.3	107.0	14 400 *							26.0
28.0	78.2	106.5	14 100 *							28.0
30.0	77.1	106.0	13 700 *							30.0
32.0	76.0	105.4	13 300 *	79.7	104.6	10 700*				32.0
34.0	74.9	104.8	13 000 *	78.6	104.0	10 400*				34.0
36.0	73.8	104.2	12 700 *	77.4	103.4	10 200*				36.0
38.0	72.6	103.5	12 400 *	76.3	102.7	9 900*	79.9	100.6	8 400*	38.0
42.0	70.4	101.9	11 800 *	74.0	101.2	9 400*	77.5	99.1	8 000*	42.0
46.0	68.0	100.2	10 200	71.7	99.5	9 000*	75.1	97.3	7 600*	46.0
50.0	65.7	98.3	8 400	69.3	97.6	8 600*	72.7	95.4	7 300*	50.0
54.0	63.2	96.2	6 900	66.8	95.4	8 200*	70.2	93.2	7 000*	54.0
58.0	60.8	93.9	5 600	64.3	93.1	7 000	67.6	90.8	6 700*	58.0
62.0	58.2	91.3	4 400	61.8	90.5	5 800	65.0	88.2	6 500*	62.0
66.0	55.6	88.5	3 300	59.1	87.7	4 600	62.3	85.3	5 400	66.0
70.0	52.9	85.4	2 400	56.4	84.5	3 600	59.5	82.0	4 200	70.0
74.0				53.5	81.1	2 600	56.5	78.5	3 200	74.0
78.0							53.4	74.5	2 300	78.0