

Liftcrane Boom Extended Upper Point Capacities

2250 SERIES 2

**7.6m Extended Upper Boom Point With 4 267 mm Strut On
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating**

**Meets
ANSI B30.5
Requirements**

LIFTING CAPACITIES: Chart supplements Boom Capacity chart **No. 8008-AM**. Lifting capacities for various boom lengths and operating radii are for freely suspended loads and do not exceed 75% of a static tipping load. Capacities based on structural competence are denoted by an asterisk (*).

76.2m and 79.2m boom lengths require only the middle three sheaves to be used on lower boom point. All other sheaves must be removed from lower boom point.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom point sheaves, is considered part of extended upper boom point load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging **No. 179809**, extended upper boom point assembly **No. 194251** and Counterweight Arrangement chart **No. 8026-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines. Wind conditions for boom with fixed jib apply to extended upper boom point.

MACHINE TRAVEL: Machine to travel on a firm, level, and uniformly supporting surface and boom within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8027-A**. Travel tables for boom lengths including all jib lengths and offset angles apply to extended upper boom point.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

EXTENDED UPPER BOOM POINT ELEVATION: Extended upper boom point elevation is vertical distance from ground level to centerline of extended upper boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 9 373 mm crawlers, 1 219 mm treads, 8 534 mm retractable gantry, 12 part boom hoist reeving, boom support straps, 94 890 kg crane counterweight and two 13 610 kg carbody counterweights.

Maximum capacity on 28.6 mm wire rope is 13 610 kg per line. Extended upper boom point wire rope whip line length of 450m required with 4 parts line and boom length of 79.2m which allows hook to touch ground. Maximum hook travel for extended upper boom point application may be restricted when whip line length exceeds 360m using 622 mm Dia. lagging on left rear drum or 390m on bare left rear drum. Refer to Wire Rope Specification chart **No. 8025-A**.

Maximum Boom Length Lifted Unassisted Over Front, Side or Rear of Crawlers	
Boom Length	7.6m Extended Upper Boom Point
(a) 91.4m	—
88.4m	—
85.3m	—
82.3m	—
79.2m	7.6m
Load block, hook and weight ball on ground at start. (a) When equipped with boom catwalks, upper boom point cannot be used on 91.4m boom.	

Boom Catwalks Deduct

Deduct 250 kg from capacities when boom catwalks are attached.

Liftcrane Boom Extended Upper Point Capacities

2250 SERIES 2

7.6m Extended Upper Boom Point With 4 267 mm Strut On
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Meets
ANSI B30.5
Requirements

39.6m (130 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
13.7	80.1	48.3	45 300 *
14.0	79.7	48.2	45 300 *
16.0	77.2	47.7	44 400 *
18.0	74.6	47.0	41 500 *
20.0	72.0	46.2	39 200 *
22.0	69.4	45.3	37 200 *
24.0	66.7	44.4	35 500 *
26.0	63.9	43.2	33 900 *
28.0	61.1	42.0	32 500 *
30.0	58.1	40.6	31 300 *
32.0	55.1	39.1	30 100 *
34.0	51.9	37.3	27 600
36.0	48.5	35.4	25 400
38.0	44.9	33.2	23 400

45.7m (150 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
15.2	79.5	54.2	45 300 *
16.0	78.7	54.0	45 100 *
18.0	76.5	53.4	43 400 *
20.0	74.2	52.7	41 100 *
22.0	71.9	52.0	39 100 *
24.0	69.6	51.1	37 400 *
26.0	67.2	50.2	35 800 *
28.0	64.8	49.1	34 300 *
30.0	62.3	47.9	32 500
32.0	59.7	46.6	29 700
34.0	57.1	45.2	27 100
36.0	54.4	43.6	24 900
38.0	51.5	41.9	22 900
40.0	48.5	40.0	21 100
42.0	45.4	37.8	19 500
44.0	42.1	35.4	18 100

51.8m (170 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
15.2	80.6	60.5	45 300 *
16.0	79.9	60.3	45 300 *
18.0	77.9	59.8	44 700 *
20.0	75.9	59.2	42 700 *
22.0	73.8	58.5	40 800 *
24.0	71.8	57.7	39 000 *
26.0	69.7	56.9	37 400 *
28.0	67.6	56.0	35 700
30.0	65.4	54.9	32 300
32.0	63.2	53.8	29 300
34.0	61.0	52.6	26 800
36.0	58.6	51.3	24 500
38.0	56.3	49.8	22 500
40.0	53.8	48.2	20 800
42.0	51.3	46.5	19 100
44.0	48.6	44.6	17 700
48.0	42.9	40.2	15 200

42.7m (140 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
13.7	80.7	51.4	45 300 *
14.0	80.3	51.4	45 300 *
16.0	78.0	50.8	44 700 *
18.0	75.6	50.2	42 500 *
20.0	73.2	49.5	40 200 *
22.0	70.7	48.7	38 200 *
24.0	68.2	47.8	36 400 *
26.0	65.7	46.7	34 900 *
28.0	63.1	45.6	33 500 *
30.0	60.4	44.3	32 200 *
32.0	57.6	42.9	29 900
34.0	54.7	41.3	27 400
36.0	51.7	39.6	25 100
38.0	48.5	37.7	23 100
40.0	45.2	35.5	21 400
42.0	41.6	33.1	19 700

48.8m (160 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
15.2	80.1	57.3	45 300 *
16.0	79.3	57.1	45 300 *
18.0	77.2	56.6	44 200 *
20.0	75.1	56.0	41 900 *
22.0	72.9	55.2	40 000 *
24.0	70.7	54.4	38 200 *
26.0	68.5	53.5	36 600 *
28.0	66.3	52.6	35 100
30.0	63.9	51.5	32 500
32.0	61.6	50.3	29 400
34.0	59.2	49.0	26 900
36.0	56.7	47.5	24 600
38.0	54.1	45.9	22 600
40.0	51.4	44.2	20 900
42.0	48.6	42.3	19 300
44.0	45.6	40.2	17 800

54.9m (180 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
16.8	79.7	63.2	45 300 *
18.0	78.5	62.9	45 200 *
20.0	76.6	62.3	43 400 *
22.0	74.7	61.7	41 500 *
24.0	72.7	61.0	39 800 *
26.0	70.8	60.2	38 200
28.0	68.8	59.3	35 600
30.0	66.7	58.4	32 000
32.0	64.7	57.3	29 100
34.0	62.5	56.2	26 500
36.0	60.4	54.9	24 300
38.0	58.2	53.6	22 300
40.0	55.9	52.1	20 500
42.0	53.6	50.5	18 900
44.0	51.1	48.8	17 500
48.0	46.0	44.8	14 900

Liftcrane Boom Extended Upper Point Capacities

2250 SERIES 2

7.6m Extended Upper Boom Point With 4 267 mm Strut On
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Meets
ANSI B30.5
Requirements

57.9m (190 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
16.8	80.2	66.3	45 300 *
18.0	79.0	66.1	45 300 *
20.0	77.2	65.5	44 200 *
22.0	75.4	64.9	42 300 *
24.0	73.6	64.2	40 500 *
26.0	71.7	63.5	38 900
28.0	69.8	62.7	35 300
30.0	67.9	61.8	31 800
32.0	65.9	60.8	28 800
34.0	64.0	59.7	26 300
36.0	61.9	58.5	24 000
38.0	59.9	57.3	22 000
40.0	57.8	55.9	20 300
42.0	55.6	54.4	18 600
44.0	53.3	52.8	17 200
48.0	48.6	49.2	14 700
52.0	43.5	44.9	12 600

64.0m (210 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
16.8	81.0	72.6	45 300 *
18.0	80.0	72.3	45 300 *
20.0	78.4	71.8	45 100 *
22.0	76.7	71.3	43 600 *
24.0	75.0	70.7	41 900 *
26.0	73.3	70.0	38 900
28.0	71.6	69.2	34 800
30.0	69.9	68.4	31 400
32.0	68.2	67.5	28 400
34.0	66.4	66.6	25 900
36.0	64.6	65.5	23 600
38.0	62.7	64.4	21 600
40.0	60.9	63.2	19 900
42.0	59.0	61.9	18 200
44.0	57.0	60.5	16 800
48.0	53.0	57.4	14 300
52.0	48.7	53.8	12 200
56.0	44.0	49.6	10 400

70.1m (230 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
18.3	80.6	78.5	45 300 *
20.0	79.3	78.1	45 300 *
22.0	77.8	77.6	44 800 *
24.0	76.2	77.0	42 800
26.0	74.7	76.4	38 400
28.0	73.1	75.7	34 400
30.0	71.6	75.0	30 900
32.0	70.0	74.2	27 900
34.0	68.4	73.3	25 400
36.0	66.7	72.4	23 100
38.0	65.1	71.4	21 100
40.0	63.4	70.3	19 300
42.0	61.7	69.1	17 700
44.0	60.0	67.9	16 300
48.0	56.4	65.1	13 800
52.0	52.7	62.0	11 700
56.0	48.7	58.4	9 900
60.0	44.4	54.2	8 300

61.0m (200 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
16.8	80.6	69.5	45 300 *
18.0	79.5	69.2	45 300 *
20.0	77.8	68.7	44 900 *
22.0	76.1	68.1	42 900 *
24.0	74.3	67.5	41 200 *
26.0	72.6	66.7	39 100
28.0	70.8	66.0	35 000
30.0	68.9	65.1	31 600
32.0	67.1	64.2	28 600
34.0	65.2	63.2	26 000
36.0	63.3	62.1	23 800
38.0	61.4	60.9	21 800
40.0	59.4	59.6	20 000
42.0	57.4	58.2	18 400
44.0	55.3	56.7	17 000
48.0	50.9	53.4	14 400
52.0	46.3	49.4	12 300
56.0	41.1	44.8	10 500

67.1m (220 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
18.3	80.2	75.4	45 300 *
20.0	78.8	75.0	45 200 *
22.0	77.3	74.4	44 300 *
24.0	75.7	73.9	42 500 *
26.0	74.0	73.2	38 700
28.0	72.4	72.5	34 600
30.0	70.8	71.7	31 100
32.0	69.1	70.9	28 200
34.0	67.4	70.0	25 600
36.0	65.7	69.0	23 400
38.0	64.0	67.9	21 400
40.0	62.2	66.8	19 600
42.0	60.4	65.6	18 000
44.0	58.6	64.2	16 500
48.0	54.8	61.3	14 000
52.0	50.8	58.0	11 900
56.0	46.5	54.1	10 100
60.0	41.9	49.5	8 600

73.2m (240 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
18.3	80.9	81.6	45 300 *
20.0	79.7	81.2	45 300 *
22.0	78.2	80.7	45 000 *
24.0	76.8	80.2	42 800
26.0	75.3	79.6	38 200
28.0	73.8	79.0	34 100
30.0	72.3	78.2	30 700
32.0	70.8	77.5	27 700
34.0	69.2	76.6	25 100
36.0	67.7	75.8	22 900
38.0	66.1	74.8	20 900
40.0	64.5	73.8	19 000
42.0	62.9	72.7	17 400
44.0	61.3	71.5	16 000
48.0	57.9	68.9	13 500
52.0	54.3	65.9	11 400
56.0	50.6	62.6	9 600
60.0	46.7	58.7	8 000
64.0	42.5	54.3	6 700

Liftcrane Boom Extended Upper Point Capacities

2250 SERIES 2

7.6m Extended Upper Boom Point With 4 267 mm Strut On
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Meets
ANSI B30.5
Requirements

76.2m (250 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
19.8	80.2	84.4	45 300 *
20.0	80.1	84.3	45 300 *
22.0	78.7	83.9	45 200 *
24.0	77.3	83.4	43 200
26.0	75.8	82.8	38 400
28.0	74.4	82.2	34 400
30.0	73.0	81.5	30 900
32.0	71.5	80.7	27 900
34.0	70.0	80.0	25 400
36.0	68.6	79.1	23 100
38.0	67.1	78.2	21 100
40.0	65.5	77.2	19 300
42.0	64.0	76.1	17 700
44.0	62.4	75.0	16 300
48.0	59.2	72.6	13 800
52.0	55.9	69.8	11 700
56.0	52.4	66.6	9 900
60.0	48.7	63.0	8 400
64.0	44.8	58.9	7 000

79.3m (260 Ft.) Boom

Ext. Upper Boom Pt. Oper. Rad. Meters	Boom Ang. Deg.	Ext. Upper Boom Point Elev. Meters	Extended Upper Boom Point Capacity Kilograms
19.8	80.6	87.5	45 000 *
20.0	80.4	87.5	44 900 *
22.0	79.1	87.0	44 100 *
24.0	77.7	86.5	42 600
26.0	76.4	86.0	38 200
28.0	75.0	85.4	34 100
30.0	73.6	84.7	30 700
32.0	72.2	84.0	27 700
34.0	70.8	83.2	25 100
36.0	69.4	82.4	22 900
38.0	67.9	81.5	20 900
40.0	66.5	80.6	19 000
42.0	65.0	79.6	17 400
44.0	63.5	78.5	16 000
48.0	60.4	76.2	13 500
52.0	57.3	73.5	11 400
56.0	54.0	70.5	9 600
60.0	50.5	67.1	8 000
64.0	46.9	63.3	6 700
68.0	43.0	59.0	5 500