

Liftcrane Boom Capacities

Boom No. B60:500

with Mast No. M10:503 or Mast No. M11:503

215 000 kg VPC (Variable Position Counterweight)

Crawler Machine on a Barge

0 Degree thru 2 Degree Static Machine List

No Travel - 360 Degree Rating

**MLC300
VPC-MAX
SERIES 3**



LIFTING CAPACITIES: Lifting capacities are for a crawler machine when operating on a barge. Machine shall be positively secured to prevent shifting. Lifting capacities for various boom lengths and operating radii are for freely suspended loads and may be based on percent of static tipping or strength of structural components. Capacities must be reduced by applicable deducts.

Upper boom point capacity for liftcrane service with single part whip line from Drum 6 is 13 600 kg or 27 200 kg with two part whip line. When Drum 2 or Drum 3 is used, capacity with single part whip line is 16 600 kg or 33 300 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves is considered part of the load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

BOOM BACKWARD STABILITY: Capacities indicated by (b) require 4 530 kg minimum weight suspended beneath lower boom point, (c) require 9 970 kg minimum weight, and (d) require 13 600 kg minimum weight. **Caution: Do not operate in areas indicated by (b), (c), or (d) without required minimum weight. Boom may not lower and boom hoist wire rope may go slack causing wire rope damage or failure.**

OPERATING CONDITIONS: Machine to operate on a firm and uniformly supporting surface with machine list not to exceed degrees noted. Refer to Boom Rigging **No. 81023382**, Mast Rigging **No. 81025690** or **No. 84045340**, Wire Rope Specification chart **No. 9434-A**, Counterweight Arrangements chart **No. 9345-A**, and Wind Conditions chart **No. 9435-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.



OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation at barge deck to center of vertical hoist line or load block.



BOOM ANGLE: Boom angle in degrees (°) is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.



BOOM POINT ELEVATION: Boom point elevation is vertical distance from barge deck to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with VPC-MAX, 9 700 mm crawlers, 1 219 mm or 1 524 mm treads, 9 144 mm live mast, 30,0 m mast, 10 part boom hoist reeving, boom support straps, and 215 000 kg VPC.

Warning: Luffing jib backstay straps must be removed before use of this chart. *Crane tipping or structural damage can occur.*

Consult chart **No. 9654-AM** when Jib No. 148 is attached.

Deduct From Capacities When Jib No. 148 Is Attached	
Jib Length (m)	Deduct (kg)
12,0	14 300
18 0	17 900
24,0	22 300
30,0	27 100
36,0	34 100
42,0	38 900
Weight of jib and 2 950 kg suspended beneath jib point have been included in determination of deduct.	

MLC300

VPC-MAX S-3



Refer to Table 1 for raising ability with the maximum weight of all load blocks, hooks, weight ball, slings, and hoist lines beneath boom point sheaves. For block weights shown with #, load blocks, hooks, weight ball, and slings must remain on barge deck until combined weights are within rated capacity of chart. Raising is not permitted in shaded areas of table.

Select counterweight position from Table 1 that will allow raising and lowering of boom length. Counterweight position selection may be changed with boom on barge deck or while boom is within operating range of capacity chart.

Combined weight beneath boom point sheaves must not exceed block weight shown.

Table 1

Over End or Side of Crawlers						
Boom Length (m)	Counterweight Position					
	10,6 m			14,6 m		
	Machine List					
	0°	1°	2°	0°	1°	2°
	Block Weight (kg)					
42,0	10 300	10 300	10 300	10 300	10 300	10 300
48,0	10 300	10 300	10 300	10 300	10 300	10 300
54,0	10 300	10 300	10 300	10 300	10 300	10 300
60,0	10 300	10 300	10 300	10 300	10 300	10 300
66,0	10 300	10 300	10 300	10 300	10 300	10 300
72,0	10 300	10 300	10 300	10 300	10 300	10 300
78,0	10 300	10 300	10 300	10 300	10 300	10 300
84,0	10 300	10 300	10 300	10 300	10 300	10 300
90,0	10 300	10 300	10 300	10 300	10 300	10 300
96,0	3 700	#	#	3 700	#	#
102,0	#	#	#	#	#	#
108,0	#	#	#	#	#	#
114,0	#	#		#	#	
120,0	#			#		

Explanation of Symbols



Boom No. B60:500



VPC (Variable Position Counterweight)



360 Degree Rating



Boom Length



Operating Radius
(see page 1)




Boom Angle
(see page 1)



Boom Point Elevation
(see page 1)



Counterweight Position
from Axis of Rotation



Machine List



Lifting Capacities
(see page 1)

MLC300 VPC-MAX S-3



B60



215 000 kg



360°



42,0 m

			10,6 m			14,6 m			
m	°	m	kg	kg	kg	kg	kg	kg	m
7,9	82,7	43,7	300 000d			300 000d			7,9
8,0	82,6	43,7	300 000d			300 000d			8,0
9,0	81,2	43,5	300 000c			300 000c			9,0
10,0	79,8	43,3	292 000c	227 600d		292 000c	227 600d		10,0
12,0	77,0	42,9	267 600c	227 100c	171 200d	267 600c	227 100c	171 200d	12,0
14,0	74,2	42,3	231 200b	211 800c	171 200c	246 700b	213 200c	171 200c	14,0
16,0	71,3	41,6	196 900b	186 800b	169 800c	235 000b	199 700b	171 100c	16,0
18,0	68,4	40,8	170 500	162 800b	155 800b	231 700	187 600b	167 700b	18,0
20,0	65,4	39,9	149 900	143 900b	138 300b	206 500	185 300b	159 600b	20,0
22,0	62,3	38,9	133 500	128 700	124 200b	182 800	174 900	154 300b	22,0
24,0	59,1	37,7	119 900	116 000	112 400	163 500	157 200	149 800	24,0
26,0	55,8	36,3	108 500	105 300	102 300	147 600	142 400	137 500	26,0
28,0	52,4	34,8	98 900	96 300	93 800	134 500	130 200	126 100	28,0
30,0	48,8	33,1	90 600	88 400	86 400	123 200	119 700	116 300	30,0
32,0	45,0	31,1	83 300	81 500	79 800	113 500	110 500	107 700	32,0
34,0	40,9	28,8	77 000	75 600	74 100	105 200	102 700	100 300	34,0
36,0	36,3	26,2	71 400	70 200	69 100	97 800	95 700	93 700	36,0
38,0	31,2	23,0	66 400	65 400	64 500	91 200	89 500	87 800	38,0
40,0	25,2	19,1	61 900	61 100	60 400	85 400	84 000	82 700	40,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

48,0 m

48,0 m									
			10,6 m			14,6 m			
			0°	1°	2°	0°	1°	2°	
m	°	m	kg	kg	kg	kg	kg	kg	m
7,3	84,4	49,8	278 000d			278 000d			7,3
8,0	83,5	49,8	278 000d			278 000d			8,0
9,0	82,3	49,6	278 000c			278 000c			9,0
10,0	81,1	49,4	276 000c	218 500d		276 000c	218 500d		10,0
12,0	78,7	49,0	255 400b	213 900c	164 400d	255 400b	213 900c	164 400d	12,0
14,0	76,2	48,5	231 100b	200 500c	164 400c	236 400b	200 500c	164 400c	14,0
16,0	73,7	48,0	196 700b	183 900b	163 300c	223 800b	188 400b	163 300c	16,0
18,0	71,2	47,3	170 300	161 400b	152 700b	221 900	177 600b	157 200b	18,0
20,0	68,7	46,5	149 600	142 600	136 200b	206 400	168 700	149 500b	20,0
22,0	66,1	45,6	133 200	127 600	122 400b	182 700	167 200	142 500b	22,0
24,0	63,4	44,6	119 600	115 000	110 700	163 400	156 000	139 700	24,0
26,0	60,6	43,5	108 100	104 300	100 800	147 400	141 400	135 700	26,0
28,0	57,8	42,2	98 500	95 400	92 400	134 300	129 200	124 500	28,0
30,0	54,9	40,8	90 200	87 500	85 000	123 000	118 800	114 800	30,0
32,0	51,9	39,3	82 900	80 700	78 500	113 300	109 700	106 200	32,0
34,0	48,7	37,5	76 600	74 700	72 900	104 900	101 800	98 900	34,0
36,0	45,4	35,6	71 000	69 400	67 800	97 500	94 900	92 400	36,0
38,0	41,9	33,4	66 000	64 600	63 300	91 000	88 700	86 500	38,0
40,0	38,0	30,9	61 500	60 300	59 200	85 200	83 200	81 400	40,0
42,0	33,8	28,0	57 400	56 500	55 600	79 900	78 300	76 700	42,0
44,0	29,1	24,6	53 700	52 900	52 200	75 200	73 800	72 500	44,0
46,0	23,4	20,3	50 300	49 700	49 200	70 900	69 800	68 700	46,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

54,0 m

54,0 m									
			10,6 m			14,6 m			
			0°	1°	2°	0°	1°	2°	
m	°	m	kg	kg	kg	kg	kg	kg	m
7,3	85,0	55,9	251 200d			251 200d			7,3
8,0	84,3	55,8	251 200d			251 200d			8,0
9,0	83,2	55,7	251 200c			251 200c			9,0
10,0	82,1	55,5	251 200c	198 700d		251 200c	198 700d		10,0
12,0	80,0	55,2	243 000b	198 000c	143 000d	243 000b	198 000c	143 000d	12,0
14,0	77,8	54,7	224 400b	188 200c	143 000c	225 900b	188 200c	143 000c	14,0
16,0	75,6	54,2	196 900b	177 600b	143 000c	210 800b	177 600b	143 000c	16,0
18,0	73,4	53,6	170 400	160 400b	143 000b	205 300	168 000b	143 000b	18,0
20,0	71,1	52,9	149 800	141 800	134 600b	203 400	159 200	140 200b	20,0
22,0	68,9	52,2	133 300	126 900	121 000	182 800	153 800	134 000	22,0
24,0	66,6	51,3	119 700	114 400	109 500	163 500	152 500	128 200	24,0
26,0	64,2	50,3	108 200	103 800	99 700	147 500	140 700	124 700	26,0
28,0	61,8	49,3	98 600	94 900	91 500	134 400	128 700	122 400	28,0
30,0	59,3	48,1	90 300	87 100	84 200	123 100	118 300	113 700	30,0
32,0	56,8	46,8	83 000	80 300	77 800	113 400	109 200	105 300	32,0
34,0	54,2	45,3	76 700	74 400	72 200	105 000	101 400	98 000	34,0
36,0	51,5	43,8	71 100	69 100	67 200	97 600	94 500	91 600	36,0
38,0	48,7	42,0	66 000	64 300	62 700	91 000	88 400	85 800	38,0
40,0	45,7	40,1	61 600	60 100	58 700	85 200	82 900	80 600	40,0
42,0	42,6	38,0	57 500	56 200	55 000	80 000	78 000	76 000	42,0
44,0	39,3	35,6	53 800	52 700	51 700	75 300	73 500	71 800	44,0
46,0	35,7	32,8	50 500	49 500	48 600	71 000	69 500	68 000	46,0
48,0	31,8	29,7	47 400	46 600	45 800	67 100	65 800	64 500	48,0
50,0	27,3	26,0	44 500	43 900	43 300	63 500	62 400	61 300	50,0
52,0	22,0	21,4	41 900	41 400	40 900	60 200	59 300	58 400	52,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

60,0 m

60,0 m									
			10,6 m			14,6 m			
			0°	1°	2°	0°	1°	2°	
m	°	m	kg	kg	kg	kg	kg	kg	m
7,9	84,9	61,8	226 800c			226 800c			7,9
8,0	84,8	61,9	226 800c			226 800c			8,0
9,0	83,9	61,7	226 800c			226 800c			9,0
10,0	82,9	61,6	226 800c	164 400d		226 800c	164 400d		10,0
12,0	81,0	61,3	226 800b	164 400c	119 300c	226 800b	164 400c	119 300c	12,0
14,0	79,0	60,9	214 300b	164 400b	119 300c	214 300b	164 400b	119 300c	14,0
16,0	77,1	60,4	195 200	163 600b	119 300c	200 600	163 600b	119 300c	16,0
18,0	75,1	59,9	169 800	156 900	119 300b	188 300	157 700	119 300b	18,0
20,0	73,1	59,3	149 100	140 200	119 300b	186 600	149 900	119 300b	20,0
22,0	71,1	58,6	132 700	125 400	116 900	180 800	142 800	119 300	22,0
24,0	69,0	57,8	119 000	113 000	107 600	163 100	139 900	119 100	24,0
26,0	67,0	57,0	107 500	102 500	98 000	147 100	139 300	115 200	26,0
28,0	64,9	56,0	97 900	93 700	89 800	133 900	127 500	111 900	28,0
30,0	62,7	55,0	89 600	86 000	82 600	122 600	117 200	110 600	30,0
32,0	60,5	53,9	82 300	79 200	76 300	112 900	108 200	103 800	32,0
34,0	58,3	52,7	76 000	73 300	70 800	104 500	100 400	96 600	34,0
36,0	56,0	51,3	70 300	68 000	65 800	97 100	93 600	90 200	36,0
38,0	53,6	49,8	65 300	63 300	61 300	90 500	87 400	84 500	38,0
40,0	51,2	48,2	60 800	59 000	57 400	84 700	82 000	79 400	40,0
42,0	48,6	46,5	56 800	55 200	53 700	79 500	77 100	74 800	42,0
44,0	46,0	44,6	53 100	51 700	50 400	74 800	72 600	70 600	44,0
46,0	43,2	42,5	49 700	48 500	47 400	70 500	68 600	66 800	46,0
48,0	40,3	40,2	46 600	45 600	44 600	66 600	64 900	63 300	48,0
50,0	37,2	37,6	43 800	42 900	42 000	63 000	61 600	60 100	50,0
52,0	33,8	34,7	41 200	40 400	39 700	59 700	58 500	57 200	52,0
54,0	30,1	31,3	38 800	38 100	37 500	56 700	55 600	54 500	54,0
56,0	25,9	27,4	36 500	36 000	35 400	53 900	53 000	52 000	56,0
58,0	20,8	22,5	34 400	33 900	33 500	51 300	50 500	49 700	58,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

66,0 m

	°	m	10,6 m			14,6 m			m
			0°	1°	2°	0°	1°	2°	
			kg	kg	kg	kg	kg	kg	
8,5	84,8	67,8	204 100c			204 100c			8,5
9,0	84,4	67,8	204 100c			204 100c			9,0
10,0	83,6	67,6	204 100c	140 000d		204 100c	140 000d		10,0
12,0	81,8	67,3	204 100b	140 000c	101 300c	204 100b	140 000c	101 300c	12,0
14,0	80,0	67,0	202 400	140 000b	101 300c	202 400	140 000b	101 300c	14,0
16,0	78,3	66,6	190 000	140 000b	101 300b	190 800	140 000b	101 300b	16,0
18,0	76,5	66,1	169 700	140 000	101 300b	179 800	140 000	101 300b	18,0
20,0	74,7	65,5	149 000	138 600	101 300	170 600	139 600	101 300	20,0
22,0	72,9	64,9	132 500	124 600	101 300	170 600	134 900	101 300	22,0
24,0	71,0	64,2	118 900	112 300	101 300	162 400	129 000	101 300	24,0
26,0	69,2	63,5	107 400	101 800	96 800	147 000	127 200	101 300	26,0
28,0	67,3	62,6	97 800	93 100	88 700	133 900	125 100	101 300	28,0
30,0	65,4	61,7	89 400	85 400	81 700	122 600	116 500	100 900	30,0
32,0	63,4	60,7	82 100	78 600	75 400	112 800	107 600	100 700	32,0
34,0	61,5	59,6	75 800	72 800	70 000	104 400	99 900	95 700	34,0
36,0	59,4	58,5	70 200	67 500	65 100	97 000	93 100	89 400	36,0
38,0	57,4	57,2	65 100	62 800	60 600	90 500	87 000	83 700	38,0
40,0	55,3	55,8	60 700	58 600	56 700	84 600	81 600	78 700	40,0
42,0	53,1	54,3	56 600	54 800	53 100	79 400	76 700	74 100	42,0
44,0	50,9	52,7	52 900	51 300	49 800	74 700	72 300	69 900	44,0
46,0	48,6	50,9	49 600	48 100	46 800	70 400	68 300	66 200	46,0
48,0	46,2	49,0	46 500	45 200	44 000	66 500	64 600	62 700	48,0
50,0	43,7	47,0	43 700	42 600	41 500	63 000	61 200	59 600	50,0
52,0	41,0	44,7	41 100	40 100	39 100	59 700	58 100	56 600	52,0
54,0	38,3	42,2	38 700	37 800	37 000	56 700	55 300	53 900	54,0
56,0	35,3	39,4	36 400	35 700	34 900	53 900	52 600	51 400	56,0
58,0	32,1	36,3	34 300	33 700	33 000	51 300	50 200	49 100	58,0
60,0	28,6	32,8	32 400	31 800	31 300	48 900	47 900	47 000	60,0
62,0	24,5	28,6	30 500	30 100	29 600	46 600	45 800	44 900	62,0
64,0	19,7	23,4	28 800	28 400	28 000	44 500	43 800	43 100	64,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

72,0 m

			10,6 m			14,6 m			
			kg	kg	kg	kg	kg	kg	
9,1	84,8	73,8	176 900c			176 900c			9,1
10,0	84,1	73,7	176 900b			176 900b			10,0
12,0	82,5	73,4	176 900b	120 400c	86 800c	176 900b	120 400c	86 800c	12,0
14,0	80,9	73,1	176 900	120 400b	86 800c	176 900	120 400b	86 800c	14,0
16,0	79,3	72,7	174 900	120 400b	86 800b	174 900	120 400b	86 800b	16,0
18,0	77,6	72,3	169 700	120 400	86 800b	169 700	120 400	86 800b	18,0
20,0	76,0	71,8	156 000	120 400	86 800	161 300	120 400	86 800	20,0
22,0	74,3	71,2	138 700	120 400	86 800	155 800	120 400	86 800	22,0
24,0	72,7	70,6	124 400	116 000	86 800	155 100	120 300	86 800	24,0
26,0	71,0	69,9	112 400	106 000	86 800	146 400	116 400	86 800	26,0
28,0	69,3	69,1	102 300	96 900	86 800	133 200	113 700	86 800	28,0
30,0	67,6	68,3	93 600	88 900	84 200	121 900	113 200	86 800	30,0
32,0	65,8	67,4	85 900	81 900	78 200	112 100	106 500	86 800	32,0
34,0	64,1	66,4	79 300	75 800	72 600	103 800	98 800	86 800	34,0
36,0	62,3	65,4	73 400	70 400	67 500	96 400	92 000	86 400	36,0
38,0	60,4	64,3	68 200	65 400	62 900	89 800	85 900	82 300	38,0
40,0	58,6	63,0	63 500	61 100	58 800	84 000	80 600	77 400	40,0
42,0	56,7	61,7	59 200	57 100	55 100	78 800	75 700	72 800	42,0
44,0	54,7	60,3	55 400	53 500	51 700	74 000	71 300	68 700	44,0
46,0	52,7	58,8	51 900	50 200	48 600	69 700	67 300	65 000	46,0
48,0	50,7	57,2	48 700	47 100	45 700	65 900	63 700	61 600	48,0
50,0	48,5	55,4	45 700	44 300	43 000	62 300	60 300	58 400	50,0
52,0	46,4	53,5	43 000	41 800	40 600	59 000	57 200	55 500	52,0
54,0	44,1	51,5	40 500	39 400	38 300	56 000	54 400	52 800	54,0
56,0	41,7	49,3	38 100	37 200	36 200	53 200	51 700	50 300	56,0
58,0	39,2	46,8	36 000	35 100	34 200	50 600	49 300	48 000	58,0
60,0	36,6	44,2	33 900	33 200	32 400	48 200	47 000	45 900	60,0
62,0	33,7	41,3	32 000	31 300	30 700	45 900	44 900	43 800	62,0
64,0	30,7	38,0	30 200	29 600	29 100	43 800	42 900	42 000	64,0
66,0	27,3	34,2	28 500	28 000	27 500	41 900	41 000	40 200	66,0
68,0	23,5	29,8	26 900	26 500	26 100	40 000	39 300	38 500	68,0
70,0	18,9	24,4	25 400	25 100	24 700	38 200	37 600	37 000	70,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

78,0 m

			10,6 m			14,6 m			
			0°	1°	2°	0°	1°	2°	
m	°	m	kg	kg	kg	kg	kg	kg	m
9,8	84,7	79,7	147 300b			147 300b			9,8
10,0	84,6	79,7	147 300b			147 300b			10,0
12,0	83,1	79,5	147 300	104 500b		147 300	104 500b		12,0
14,0	81,6	79,2	147 300	104 500b	75 500c	147 300	104 500b	75 500c	14,0
16,0	80,1	78,8	147 300	104 500	75 500b	147 300	104 500	75 500b	16,0
18,0	78,6	78,4	147 300	104 500	75 500	147 300	104 500	75 500	18,0
20,0	77,1	78,0	146 800	104 500	75 500	147 300	104 500	75 500	20,0
22,0	75,6	77,4	138 400	104 500	75 500	146 000	104 500	75 500	22,0
24,0	74,0	76,9	124 000	104 500	75 500	144 400	104 500	75 500	24,0
26,0	72,5	76,2	112 000	104 200	75 500	140 500	104 500	75 500	26,0
28,0	71,0	75,6	101 900	96 000	75 500	133 000	104 400	75 500	28,0
30,0	69,4	74,8	93 200	88 100	75 500	121 700	104 100	75 500	30,0
32,0	67,8	74,0	85 500	81 100	75 500	111 900	104 100	75 500	32,0
34,0	66,2	73,1	78 900	75 100	71 500	103 500	98 100	75 500	34,0
36,0	64,6	72,2	73 000	69 600	66 500	96 100	91 400	75 500	36,0
38,0	62,9	71,1	67 700	64 700	62 000	89 500	85 300	75 500	38,0
40,0	61,2	70,0	63 000	60 400	57 900	83 700	80 000	75 100	40,0
42,0	59,5	68,9	58 800	56 400	54 200	78 500	75 100	72 000	42,0
44,0	57,8	67,6	54 900	52 800	50 800	73 700	70 800	67 900	44,0
46,0	56,0	66,3	51 400	49 500	47 700	69 500	66 800	64 200	46,0
48,0	54,2	64,8	48 200	46 500	44 900	65 600	63 100	60 800	48,0
50,0	52,4	63,3	45 300	43 700	42 300	62 000	59 800	57 700	50,0
52,0	50,5	61,7	42 600	41 200	39 800	58 700	56 700	54 800	52,0
54,0	48,5	59,9	40 100	38 800	37 600	55 700	53 900	52 200	54,0
56,0	46,5	58,0	37 700	36 600	35 500	52 900	51 300	49 700	56,0
58,0	44,4	56,0	35 600	34 500	33 500	50 300	48 800	47 400	58,0
60,0	42,2	53,8	33 500	32 600	31 700	47 900	46 600	45 200	60,0
62,0	40,0	51,4	31 700	30 800	30 000	45 700	44 400	43 200	62,0
64,0	37,6	48,9	29 900	29 100	28 400	43 600	42 500	41 300	64,0
66,0	35,0	46,1	28 200	27 500	26 900	41 600	40 600	39 600	66,0
68,0	32,3	43,0	26 600	26 000	25 500	39 800	38 800	37 900	68,0
70,0	29,4	39,5	25 100	24 600	24 100	38 000	37 200	36 400	70,0
72,0	26,2	35,6	23 700	23 300	22 800	36 400	35 600	34 900	72,0
74,0	22,5	31,0	22 400	22 000	21 600	34 800	34 200	33 500	74,0
76,0	18,1	25,4	21 100	20 800	20 500	33 300	32 800	32 200	76,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

84,0 m

			10,6 m			14,6 m			
			0°	1°	2°	0°	1°	2°	
m	°	m	kg	kg	kg	kg	kg	kg	m
10,4	84,7	85,7	125 100b			125 100b			10,4
12,0	83,6	85,5	125 100	88 200b		125 100	88 200b		12,0
14,0	82,2	85,3	125 100	88 200b	66 000c	125 100	88 200b	66 000c	14,0
16,0	80,8	84,9	125 100	88 200	66 000b	125 100	88 200	66 000b	16,0
18,0	79,4	84,6	125 100	88 200	66 000	125 100	88 200	66 000	18,0
20,0	78,0	84,1	125 100	88 200	66 000	125 100	88 200	66 000	20,0
22,0	76,6	83,7	125 100	88 200	66 000	125 100	88 200	66 000	22,0
24,0	75,2	83,1	124 500	88 200	66 000	125 100	88 200	66 000	24,0
26,0	73,8	82,5	114 200	88 200	66 000	125 000	88 200	66 000	26,0
28,0	72,4	81,9	103 500	88 200	66 000	122 500	88 200	66 000	28,0
30,0	70,9	81,2	94 400	86 800	66 000	118 300	88 200	66 000	30,0
32,0	69,5	80,5	86 400	81 000	66 000	111 200	88 200	66 000	32,0
34,0	68,0	79,7	79 700	74 900	66 000	102 800	88 200	66 000	34,0
36,0	66,5	78,8	73 700	69 400	64 900	95 400	88 200	66 000	36,0
38,0	65,0	77,9	68 300	64 600	61 100	88 800	84 200	66 000	38,0
40,0	63,5	76,9	63 600	60 300	57 200	83 000	78 900	66 000	40,0
42,0	61,9	75,8	59 400	56 400	53 600	77 700	74 100	66 000	42,0
44,0	60,4	74,7	55 600	52 900	50 300	73 000	69 700	66 000	44,0
46,0	58,8	73,4	52 100	49 700	47 400	68 700	65 800	63 000	46,0
48,0	57,2	72,2	49 000	46 800	44 700	64 800	62 200	59 700	48,0
50,0	55,5	70,8	46 100	44 100	42 100	61 300	58 800	56 600	50,0
52,0	53,8	69,3	43 400	41 600	39 800	58 000	55 800	53 700	52,0
54,0	52,1	67,8	41 000	39 300	37 700	55 000	53 000	51 000	54,0
56,0	50,3	66,1	38 800	37 200	35 700	52 200	50 400	48 600	56,0
58,0	48,5	64,4	36 700	35 200	33 900	49 600	47 900	46 300	58,0
60,0	46,6	62,5	34 700	33 400	32 200	47 200	45 700	44 200	60,0
62,0	44,7	60,5	32 900	31 700	30 500	45 000	43 500	42 200	62,0
64,0	42,7	58,3	31 200	30 100	29 000	42 800	41 600	40 300	64,0
66,0	40,6	56,0	29 400	28 600	27 600	40 900	39 700	38 500	66,0
68,0	38,4	53,5	27 800	27 000	26 300	39 000	38 000	36 900	68,0
70,0	36,1	50,8	26 200	25 600	24 900	37 300	36 300	35 300	70,0
72,0	33,7	47,9	24 800	24 200	23 600	35 700	34 800	33 900	72,0
74,0	31,1	44,7	23 400	22 800	22 300	34 100	33 300	32 500	74,0
76,0	28,3	41,0	22 100	21 600	21 100	32 600	31 900	31 200	76,0
78,0	25,2	36,9	20 800	20 400	20 000	31 200	30 600	29 900	78,0
80,0	21,7	32,2	19 600	19 300	18 900	29 900	29 300	28 700	80,0
82,0	17,4	26,3	18 400	18 200	17 900	28 600	28 100	27 600	82,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

90,0 m

			10,6 m			14,6 m			
m	°	m	0° kg	1° kg	2° kg	0° kg	1° kg	2° kg	m
11,0	84,7	91,7	104 900			104 900			11,0
12,0	84,0	91,6	104 900			104 900			12,0
14,0	82,7	91,3	104 900	72 900	54 900c	104 900	72 900	54 900c	14,0
16,0	81,4	91,0	104 900	72 900	54 900b	104 900	72 900	54 900b	16,0
18,0	80,1	90,7	104 900	72 900	54 900	104 900	72 900	54 900	18,0
20,0	78,8	90,3	104 900	72 900	54 900	104 900	72 900	54 900	20,0
22,0	77,5	89,8	104 900	72 900	54 900	104 900	72 900	54 900	22,0
24,0	76,2	89,3	104 900	72 900	54 900	104 900	72 900	54 900	24,0
26,0	74,9	88,8	104 800	72 900	54 900	104 800	72 900	54 900	26,0
28,0	73,6	88,2	102 200	72 900	54 900	103 500	72 900	54 900	28,0
30,0	72,2	87,6	94 300	72 900	54 900	100 800	72 900	54 900	30,0
32,0	70,9	86,9	86 300	72 900	54 900	98 000	72 900	54 900	32,0
34,0	69,5	86,1	79 500	72 500	54 900	94 900	72 900	54 900	34,0
36,0	68,2	85,3	73 600	69 000	54 900	91 900	72 900	54 900	36,0
38,0	66,8	84,5	68 200	64 200	54 900	88 500	72 900	54 900	38,0
40,0	65,4	83,6	63 500	59 900	54 800	82 800	72 900	54 900	40,0
42,0	64,0	82,6	59 300	56 100	53 100	77 600	72 500	54 900	42,0
44,0	62,5	81,5	55 500	52 600	49 800	72 900	69 400	54 900	44,0
46,0	61,1	80,4	52 000	49 400	46 900	68 600	65 400	54 900	46,0
48,0	59,6	79,3	48 900	46 500	44 200	64 700	61 800	54 900	48,0
50,0	58,1	78,0	46 000	43 800	41 700	61 100	58 500	54 900	50,0
52,0	56,6	76,7	43 300	41 300	39 400	57 900	55 500	53 200	52,0
54,0	55,0	75,3	40 900	39 100	37 300	54 900	52 700	50 600	54,0
56,0	53,4	73,8	38 600	36 900	35 300	52 100	50 100	48 100	56,0
58,0	51,8	72,3	36 500	35 000	33 500	49 500	47 600	45 900	58,0
60,0	50,2	70,6	34 600	33 200	31 800	47 100	45 400	43 800	60,0
62,0	48,5	68,8	32 800	31 500	30 200	44 800	43 300	41 800	62,0
64,0	46,7	67,0	31 000	29 900	28 700	42 700	41 300	39 900	64,0
66,0	44,9	65,0	29 300	28 300	27 300	40 800	39 400	38 200	66,0
68,0	43,1	62,9	27 600	26 800	25 900	38 900	37 700	36 500	68,0
70,0	41,2	60,6	26 100	25 300	24 500	37 200	36 100	35 000	70,0
72,0	39,2	58,2	24 600	23 900	23 200	35 600	34 500	33 500	72,0
74,0	37,1	55,6	23 300	22 600	21 900	34 000	33 100	32 100	74,0
76,0	34,9	52,7	21 900	21 300	20 800	32 600	31 700	30 800	76,0
78,0	32,5	49,7	20 700	20 200	19 600	31 200	30 400	29 600	78,0
80,0	30,0	46,3	19 500	19 000	18 600	29 800	29 100	28 400	80,0
82,0	27,3	42,5	18 400	17 900	17 500	28 600	27 900	27 300	82,0
84,0	24,3	38,2	17 300	16 900	16 600	27 400	26 800	26 200	84,0
86,0	20,9	33,3	16 200	15 900	15 600	26 200	25 700	25 200	86,0
88,0	16,8	27,2	15 200	15 000	14 700	25 100	24 700	24 200	88,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

96,0 m

			10,6 m			14,6 m			
			0°	1°	2°	0°	1°	2°	
m	°	m	kg	kg	kg	kg	kg	kg	m
11,0	85,0	97,7	90 400			90 400			11,0
12,0	84,4	97,6	90 400			90 400			12,0
14,0	83,2	97,4	90 400	61 500		90 400	61 500		14,0
16,0	82,0	97,1	90 400	61 500	46 300b	90 400	61 500	46 300b	16,0
18,0	80,8	96,8	90 400	61 500	46 300	90 400	61 500	46 300	18,0
20,0	79,6	96,4	90 400	61 500	46 300	90 400	61 500	46 300	20,0
22,0	78,3	96,0	90 400	61 500	46 300	90 400	61 500	46 300	22,0
24,0	77,1	95,5	90 400	61 500	46 300	90 400	61 500	46 300	24,0
26,0	75,9	95,0	90 400	61 500	46 300	90 400	61 500	46 300	26,0
28,0	74,6	94,5	90 400	61 500	46 300	90 400	61 500	46 300	28,0
30,0	73,4	93,9	90 400	61 500	46 300	90 400	61 500	46 300	30,0
32,0	72,1	93,2	85 600	61 500	46 300	90 400	61 500	46 300	32,0
34,0	70,9	92,5	78 900	61 500	46 300	90 400	61 500	46 300	34,0
36,0	69,6	91,8	72 900	61 500	46 300	90 400	61 500	46 300	36,0
38,0	68,3	91,0	67 500	61 500	46 300	87 800	61 500	46 300	38,0
40,0	67,0	90,1	62 800	59 000	46 300	82 100	61 500	46 300	40,0
42,0	65,7	89,2	58 600	55 100	46 300	76 900	61 500	46 300	42,0
44,0	64,4	88,3	54 700	51 600	46 300	72 200	61 500	46 300	44,0
46,0	63,1	87,3	51 300	48 400	45 800	67 900	61 500	46 300	46,0
48,0	61,7	86,2	48 100	45 600	43 100	64 000	60 500	46 300	48,0
50,0	60,3	85,1	45 200	42 900	40 700	60 400	57 600	46 200	50,0
52,0	58,9	83,9	42 600	40 400	38 400	57 100	54 500	46 100	52,0
54,0	57,5	82,6	40 200	38 200	36 300	54 100	51 700	46 000	54,0
56,0	56,1	81,2	37 900	36 100	34 300	51 300	49 100	45 900	56,0
58,0	54,6	79,8	35 800	34 100	32 500	48 700	46 700	44 800	58,0
60,0	53,1	78,3	33 800	32 300	30 800	46 300	44 500	42 700	60,0
62,0	51,6	76,8	31 800	30 500	29 200	44 100	42 400	40 700	62,0
64,0	50,1	75,1	30 000	28 800	27 700	42 000	40 400	38 900	64,0
66,0	48,5	73,3	28 200	27 200	26 100	40 000	38 600	37 200	66,0
68,0	46,8	71,5	26 600	25 600	24 700	38 200	36 800	35 500	68,0
70,0	45,2	69,5	25 100	24 100	23 300	36 400	35 200	34 000	70,0
72,0	43,4	67,4	23 600	22 800	22 000	34 800	33 600	32 500	72,0
74,0	41,6	65,2	22 200	21 500	20 700	33 300	32 200	31 100	74,0
76,0	39,8	62,8	20 900	20 200	19 500	31 800	30 800	29 800	76,0
78,0	37,9	60,2	19 700	19 000	18 400	30 400	29 500	28 600	78,0
80,0	35,8	57,5	18 500	17 900	17 300	29 100	28 300	27 400	80,0
82,0	33,7	54,6	17 400	16 800	16 300	27 900	27 100	26 300	82,0
84,0	31,4	51,3	16 300	15 800	15 300	26 700	25 900	25 200	84,0
86,0	29,0	47,8	15 300	14 800	14 400	25 500	24 900	24 200	86,0
88,0	26,4	43,9	14 300	13 900	13 500	24 400	23 800	23 200	88,0
90,0	23,5	39,5	13 300	13 000	12 700	23 400	22 800	22 300	90,0
92,0	20,2	34,3	12 400	12 100	11 900	22 400	21 900	21 200	92,0
94,0	16,3	28,0	11 500	11 300	11 100	21 400	19 700	16 900	94,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

102,0 m

102,0 m									
			10,6 m			14,6 m			
m	°	m	kg	kg	kg	kg	kg	kg	m
11,6	85,0	103,7	76 200			76 200			11,6
12,0	84,7	103,6	76 200			76 200			12,0
14,0	83,6	103,4	76 200	50 500		76 200	50 500		14,0
16,0	82,4	103,1	76 200	50 500	38 000b	76 200	50 500	38 000b	16,0
18,0	81,3	102,8	76 200	50 500	38 000	76 200	50 500	38 000	18,0
20,0	80,2	102,5	76 200	50 500	38 000	76 200	50 500	38 000	20,0
22,0	79,0	102,1	76 200	50 500	38 000	76 200	50 500	38 000	22,0
24,0	77,9	101,7	76 200	50 500	38 000	76 200	50 500	38 000	24,0
26,0	76,7	101,2	76 200	50 500	38 000	76 200	50 500	38 000	26,0
28,0	75,6	100,7	76 200	50 500	38 000	76 200	50 500	38 000	28,0
30,0	74,4	100,1	76 200	50 500	38 000	76 200	50 500	38 000	30,0
32,0	73,2	99,5	76 200	50 500	38 000	76 200	50 500	38 000	32,0
34,0	72,0	98,9	75 600	50 500	38 000	75 600	50 500	38 000	34,0
36,0	70,9	98,2	72 600	50 500	38 000	74 600	50 500	38 000	36,0
38,0	69,7	97,4	67 300	50 500	38 000	72 600	50 500	38 000	38,0
40,0	68,4	96,6	62 600	50 500	38 000	70 600	50 500	38 000	40,0
42,0	67,2	95,8	58 300	50 500	38 000	68 500	50 500	38 000	42,0
44,0	66,0	94,9	54 500	50 500	38 000	66 600	50 500	38 000	44,0
46,0	64,8	94,0	51 000	48 000	38 000	64 800	50 500	38 000	46,0
48,0	63,5	93,0	47 900	45 100	37 900	63 000	50 500	37 900	48,0
50,0	62,2	91,9	45 000	42 500	37 900	60 200	50 400	37 900	50,0
52,0	60,9	90,8	42 300	40 000	37 700	56 900	50 300	37 800	52,0
54,0	59,6	89,6	39 900	37 800	35 800	53 900	50 200	37 700	54,0
56,0	58,3	88,4	37 600	35 700	33 900	51 100	48 700	37 700	56,0
58,0	57,0	87,1	35 500	33 700	32 000	48 500	46 300	37 600	58,0
60,0	55,6	85,7	33 400	31 900	30 400	46 100	44 100	37 500	60,0
62,0	54,2	84,3	31 500	30 100	28 700	43 900	42 000	37 400	62,0
64,0	52,8	82,8	29 600	28 300	27 100	41 600	40 000	37 300	64,0
66,0	51,4	81,2	27 900	26 700	25 600	39 400	38 100	36 700	66,0
68,0	49,9	79,5	26 300	25 200	24 100	37 300	36 200	35 000	68,0
70,0	48,4	77,8	24 700	23 700	22 800	35 500	34 400	33 300	70,0
72,0	46,9	75,9	23 300	22 300	21 500	33 800	32 800	31 800	72,0
74,0	45,3	73,9	21 900	21 000	20 200	32 200	31 300	30 400	74,0
76,0	43,7	71,9	20 600	19 800	19 000	30 700	29 900	29 000	76,0
78,0	42,0	69,7	19 400	18 600	17 900	29 400	28 600	27 800	78,0
80,0	40,3	67,3	18 200	17 500	16 900	28 200	27 400	26 700	80,0
82,0	38,5	64,8	17 100	16 500	15 800	27 000	26 400	25 700	82,0
84,0	36,6	62,2	16 000	15 400	14 900	26 000	25 400	24 800	84,0
86,0	34,7	59,3	15 000	14 500	14 000	25 100	24 500	23 800	86,0
88,0	32,6	56,3	14 000	13 500	13 100	24 200	23 500	22 800	88,0
90,0	30,4	52,9	13 100	12 600	12 200	23 200	22 600	21 900	90,0
92,0	28,1	49,3	12 200	11 800	11 400	22 200	21 600	21 000	92,0
94,0	25,6	45,2	11 300	11 000	10 600	21 300	20 700	20 200	94,0
98,0	19,5	35,3	9 700	9 400	9 200	19 500	19 000	17 100	98,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

108,0 m

			10,6 m			14,6 m			
			0°	1°	2°	0°	1°	2°	
m	°	m	kg	kg	kg	kg	kg	kg	m
12,2	84,9	109,7	66 800			66 800			12,2
14,0	83,9	109,5	66 800			66 800			14,0
16,0	82,9	109,2	66 800			66 800			16,0
18,0	81,8	108,9	66 800	42 900	31 500	66 800	42 900	31 500	18,0
20,0	80,7	108,6	66 800	42 900	31 500	66 800	42 900	31 500	20,0
22,0	79,6	108,2	66 800	42 900	31 500	66 800	42 900	31 500	22,0
24,0	78,6	107,8	66 800	42 900	31 500	66 800	42 900	31 500	24,0
26,0	77,5	107,4	66 800	42 900	31 500	66 800	42 900	31 500	26,0
28,0	76,4	106,9	66 800	42 900	31 500	66 800	42 900	31 500	28,0
30,0	75,3	106,4	66 800	42 900	31 500	66 800	42 900	31 500	30,0
32,0	74,2	105,8	66 700	42 900	31 500	66 700	42 900	31 500	32,0
34,0	73,1	105,2	64 300	42 900	31 500	64 300	42 900	31 500	34,0
36,0	72,0	104,5	62 100	42 900	31 500	62 100	42 900	31 500	36,0
38,0	70,8	103,8	59 900	42 900	31 500	59 900	42 900	31 500	38,0
40,0	69,7	103,1	57 900	42 900	31 500	57 900	42 900	31 500	40,0
42,0	68,6	102,3	55 900	42 900	31 500	55 900	42 900	31 500	42,0
44,0	67,4	101,5	53 600	42 900	31 500	54 100	42 900	31 500	44,0
46,0	66,3	100,6	50 300	42 900	31 500	52 300	42 900	31 500	46,0
48,0	65,1	99,7	47 100	42 800	31 400	50 600	42 800	31 400	48,0
50,0	63,9	98,7	44 300	41 500	31 400	49 000	42 800	31 400	50,0
52,0	62,7	97,7	41 600	39 200	31 400	47 500	42 700	31 400	52,0
54,0	61,5	96,6	39 100	36 900	31 300	46 100	42 400	31 300	54,0
56,0	60,3	95,4	36 800	34 800	31 300	44 700	41 400	31 300	56,0
58,0	59,0	94,2	34 500	32 700	31 100	43 500	40 300	31 200	58,0
60,0	57,8	93,0	32 400	30 800	29 200	42 300	39 300	31 200	60,0
62,0	56,5	91,7	30 400	28 900	27 500	41 200	38 300	31 100	62,0
64,0	55,2	90,3	28 600	27 200	25 900	40 200	37 400	31 100	64,0
66,0	53,9	88,8	26 900	25 600	24 400	39 000	36 600	31 000	66,0
68,0	52,6	87,3	25 200	24 000	22 900	37 200	35 500	30 900	68,0
70,0	51,2	85,7	23 700	22 600	21 500	35 500	34 000	30 900	70,0
72,0	49,8	84,0	22 300	21 200	20 200	33 900	32 500	30 700	72,0
74,0	48,4	82,2	20 900	19 900	19 000	32 300	31 000	29 800	74,0
76,0	47,0	80,4	19 600	18 700	17 800	30 900	29 600	28 500	76,0
78,0	45,5	78,4	18 400	17 500	16 700	29 400	28 300	27 200	78,0
80,0	44,0	76,4	17 200	16 400	15 700	28 100	27 100	26 100	80,0
82,0	42,4	74,2	16 100	15 400	14 700	26 900	25 900	25 000	82,0
84,0	40,8	71,9	15 000	14 400	13 700	25 700	24 800	23 900	84,0
86,0	39,1	69,5	14 000	13 400	12 800	24 600	23 700	22 900	86,0
88,0	37,4	66,9	13 000	12 500	11 900	23 500	22 700	21 900	88,0
90,0	35,6	64,1	12 100	11 600	11 100	22 500	21 700	21 000	90,0
92,0	33,7	61,1	11 200	10 700	10 300	21 500	20 800	20 100	92,0
94,0	31,7	58,0	10 400	9 900	9 500	20 600	19 900	19 300	94,0
98,0	27,3	50,7	8 800	8 400	8 000	18 800	18 200	17 700	98,0
102,0	22,1	41,8	7 200	7 000	6 700	17 200	16 700	16 200	102,0

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

			10,6 m		14,6 m			
m	°	m	kg	kg	kg	kg	m	m
13,7	84,4	115,5	58 600		58 600		13,7	
14,0	84,3	115,5	58 600		58 600		14,0	
16,0	83,2	115,3	58 600	36 100	58 600	36 100	16,0	
18,0	82,2	115,0	58 600	36 100	58 600	36 100	18,0	
20,0	81,2	114,7	58 600	36 100	58 600	36 100	20,0	
22,0	80,2	114,3	58 600	36 100	58 600	36 100	22,0	
24,0	79,2	113,9	58 600	36 100	58 600	36 100	24,0	
26,0	78,1	113,5	58 500	36 100	58 500	36 100	26,0	
28,0	77,1	113,1	58 500	36 100	58 500	36 100	28,0	
30,0	76,1	112,6	58 400	36 100	58 400	36 100	30,0	
32,0	75,0	112,0	58 200	36 100	58 200	36 100	32,0	
34,0	74,0	111,5	57 700	36 100	57 700	36 100	34,0	
36,0	72,9	110,8	56 900	36 100	56 900	36 100	36,0	
38,0	71,9	110,2	55 200	36 100	55 200	36 100	38,0	
40,0	70,8	109,5	53 400	36 100	53 400	36 100	40,0	
42,0	69,7	108,8	51 600	36 100	51 600	36 100	42,0	
44,0	68,7	108,0	50 000	36 100	50 000	36 100	44,0	
46,0	67,6	107,1	48 400	36 100	48 400	36 100	46,0	
48,0	66,5	106,3	46 600	36 000	46 900	36 000	48,0	
50,0	65,4	105,4	44 000	36 000	45 400	36 000	50,0	
52,0	64,3	104,4	41 300	35 900	44 000	35 900	52,0	
54,0	63,1	103,4	38 800	35 700	42 700	35 900	54,0	
56,0	62,0	102,3	36 400	34 300	41 500	35 800	56,0	
58,0	60,8	101,2	34 100	32 200	40 300	35 800	58,0	
60,0	59,7	100,0	32 000	30 300	39 200	35 700	60,0	
62,0	58,5	98,8	30 000	28 400	38 100	35 300	62,0	
64,0	57,3	97,5	28 200	26 700	37 100	34 500	64,0	
66,0	56,1	96,2	26 500	25 100	36 200	33 700	66,0	
68,0	54,9	94,8	24 800	23 500	35 300	32 900	68,0	
70,0	53,6	93,3	23 300	22 100	34 200	32 100	70,0	
72,0	52,4	91,8	21 900	20 700	32 400	31 200	72,0	
74,0	51,1	90,2	20 500	19 400	30 700	29 600	74,0	
76,0	49,8	88,5	19 200	18 200	29 100	28 000	76,0	
78,0	48,4	86,7	18 000	17 100	27 600	26 600	78,0	
80,0	47,0	84,9	16 800	16 000	26 200	25 300	80,0	
82,0	45,6	82,9	15 700	14 900	24 900	24 100	82,0	
84,0	44,2	80,9	14 600	13 900	23 700	22 900	84,0	
86,0	42,7	78,7	13 600	12 900	22 600	21 800	86,0	
88,0	41,2	76,5	12 700	12 000	21 500	20 900	88,0	
90,0	39,6	74,1	11 700	11 100	20 600	19 900	90,0	
92,0	38,0	71,5	10 800	10 300	19 700	19 100	92,0	
94,0	36,3	68,8	10 000	9 500	18 900	18 300	94,0	
98,0	32,7	62,9	8 400	8 000	17 500	17 000	98,0	
102,0	28,7	56,0	6 900	6 500	16 400	16 000	102,0	
106,0	24,1	47,8	5 500	5 200	15 400	14 900	106,0	
110,0	18,5	37,2			14 000	13 600	110,0	

MLC300 VPC-MAX S-3



B60



215 000 kg



360°

120,0 m					
10,6 m	14,6 m	0°	0°	0°	0°
m	°	m	kg	kg	m
13,7	84,7	121,6	51 400	51 400	13,7
14,0	84,5	121,5	51 400	51 400	14,0
16,0	83,6	121,3	51 400	51 400	16,0
18,0	82,6	121,0	51 400	51 400	18,0
20,0	81,7	120,8	51 400	51 400	20,0
22,0	80,7	120,4	51 400	51 400	22,0
24,0	79,7	120,1	51 400	51 400	24,0
26,0	78,7	119,7	51 300	51 300	26,0
28,0	77,8	119,2	51 300	51 300	28,0
30,0	76,8	118,8	51 200	51 200	30,0
32,0	75,8	118,2	51 100	51 100	32,0
34,0	74,8	117,7	50 800	50 800	34,0
36,0	73,8	117,1	50 300	50 300	36,0
38,0	72,8	116,5	49 900	49 900	38,0
40,0	71,8	115,8	48 800	48 800	40,0
42,0	70,8	115,2	47 200	47 200	42,0
44,0	69,8	114,4	45 800	45 800	44,0
46,0	68,8	113,6	44 300	44 300	46,0
48,0	67,7	112,8	43 000	43 000	48,0
50,0	66,7	112,0	41 700	41 700	50,0
52,0	65,6	111,1	40 300	40 400	52,0
54,0	64,6	110,1	37 700	39 200	54,0
56,0	63,5	109,1	35 300	38 000	56,0
58,0	62,4	108,1	33 000	36 900	58,0
60,0	61,4	107,0	30 900	35 900	60,0
62,0	60,3	105,8	29 000	34 900	62,0
64,0	59,1	104,6	27 100	33 900	64,0
66,0	58,0	103,4	25 400	33 100	66,0
68,0	56,9	102,1	23 800	32 200	68,0
70,0	55,7	100,7	22 200	31 100	70,0
72,0	54,6	99,3	20 800	29 400	72,0
74,0	53,4	97,8	19 400	27 700	74,0
76,0	52,2	96,3	18 100	26 100	76,0
78,0	50,9	94,7	16 900	24 600	78,0
80,0	49,7	93,0	15 700	23 300	80,0
82,0	48,4	91,2	14 600	22 000	82,0
84,0	47,1	89,3	13 600	20 800	84,0
86,0	45,8	87,4	12 500	19 600	86,0
88,0	44,4	85,4	11 600	18 600	88,0
90,0	43,0	83,3	10 700	17 600	90,0
92,0	41,6	81,0	9 800	16 600	92,0
94,0	40,1	78,7	8 900	15 800	94,0
98,0	37,0	73,5	7 300	14 200	98,0
102,0	33,7	67,8	5 900	12 800	102,0
106,0	30,0	61,2		11 700	106,0
110,0	25,8	53,5		10 200	110,0
114,0	20,9	44,0		8 600	114,0