

Liftcrane Boom Capacities

Boom No. B10:500

**with 200 200 kg Fixed Position Counterweight
at 4,1 m Position**

Crawler Machine on a Barge

0 Degree thru 3 Degree Static Machine List

No Travel - 360 Degree Rating - Two Swing Drives

**MLC300
SERIES 3**



LIFTING CAPACITIES: Lifting capacities are for a crawler machine when operating on a barge. Machine shall be positively secured to prevent shifting. Lifting capacities for various boom lengths and operating radii are for freely suspended loads and may be based on percent of static tipping or strength of structural components.

Upper boom point capacity for liftcrane service with single part whip line from Drum 6 is 13 600 kg or 27 200 kg with two part whip line. When Drum 2 or Drum 3 is used, capacity with single part whip line is 16 600 kg or 33 300 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom point sheaves is considered part of load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate on a firm and uniformly supporting surface with machine list not to exceed degrees noted. Refer to Boom Rigging **No. 81023380**, Wire Rope Specifications chart **No. 9341-A**, Counterweight Arrangements **No. 9345-A**, and Wind Conditions chart **No. 9344-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.



OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation at barge deck to center of vertical hoist line or load block.



BOOM ANGLE: Boom angle in degrees (°) is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.



BOOM POINT ELEVATION: Boom point elevation is vertical distance from barge deck to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with two swing drives, 9 700 mm crawlers, 1 219 mm or 1 524 mm treads, 9 144 mm live mast, 24 part boom hoist reeving, boom support straps, and 200 200 kg Fixed Position Counterweight.

Warning: Luffing jib backstay straps must be removed before use of this chart. *Crane tipping or structural damage can occur.*

Refer to Tables 1 and 2 for raising ability with the maximum weight of all load blocks, hooks, weight ball, slings, and hoist lines beneath boom point sheaves. For block weights shown with #, load blocks, hooks, weight ball, and slings must remain on barge deck until combined weights are within rated capacity of chart. For boom lengths shown with (a), upper boom point must be removed. Raising is not permitted in shaded areas of table.

Combined weight beneath boom point sheaves must not exceed block weight shown.

Table 1

Over End or Side of Crawlers				
Boom Length (m)	Machine List			
	0°	1°	2°	3°
	Block Weight (kg)			
36,0	10 300	Raising Not Permitted		
42,0	10 300	10 300	10 300	10 300
48,0	10 300	10 300	10 300	10 300
54,0	10 300	10 300	10 300	10 300
60,0	10 300	10 300	10 300	10 300
66,0	7 100	7 100	7 100	7 100
72,0	3 700	3 700	3 700	3 700
78,0	3 700	#	#	#
84,0	#	#	#	#
(a)90,0	Raising Not Permitted			

Table 2

Over End of Blocked Crawlers				
Boom Length (m)	Machine List			
	0°	1°	2°	3°
	Block Weight (kg)			
36,0	10 300	Raising Not Permitted		
42,0	10 300	10 300	10 300	10 300
48,0	10 300	10 300	10 300	10 300
54,0	10 300	10 300	10 300	10 300
60,0	10 300	10 300	10 300	10 300
66,0	7 100	7 100	7 100	7 100
72,0	3 700	3 700	3 700	3 700
78,0	3 700	#	#	#
84,0	#	#	#	#
(a)90,0	#	Raising Not Permitted		
Warning: Crane must remain in-line with crawlers when raising over end of blocked crawlers until operating radius is within 360 degree chart. <i>Crane tipping or structural damage can occur.</i>				

Explanation of Symbols



Boom No. B10:500



Fixed Position Counterweight



360 Degree Rating



Boom Length




Operating Radius
(see page 1)



Boom Angle
(see page 1)



Boom Point Elevation
(see page 1)





Machine List



Lifting Capacities
(see page 1)



36,0 m			
m	°	m	 0°  kg
12,2	74,5	36,6	158 200
13,0	73,1	36,3	144 700
14,0	71,5	36,0	129 200
15,0	69,7	35,6	116 800
16,0	68,0	35,2	106 600
17,0	66,3	34,7	97 500
18,0	64,5	34,2	90 000
19,0	62,7	33,7	83 400
20,0	60,9	33,1	77 400
22,0	57,1	31,8	67 700
24,0	53,1	30,3	59 800
26,0	48,9	28,6	53 200
28,0	44,4	26,6	47 800
30,0	39,5	24,2	43 200
32,0	33,9	21,4	39 100
34,0	27,3	17,7	35 600



m	°	m	kg	kg	kg	kg	m
11,6	77,6	43,0	171 100				11,6
12,0	77,0	42,9	162 300				12,0
13,0	75,6	42,6	144 700				13,0
14,0	74,2	42,3	129 200	118 900			14,0
15,0	72,8	42,0	116 800	108 100			15,0
16,0	71,3	41,6	106 500	99 100	92 500		16,0
17,0	69,9	41,2	97 400	91 100	85 300	80 100	17,0
18,0	68,4	40,8	89 800	84 300	79 300	74 700	18,0
19,0	66,9	40,4	83 200	78 400	73 900	69 800	19,0
20,0	65,4	39,9	77 200	73 000	69 000	65 400	20,0
22,0	62,3	38,9	67 500	64 100	60 900	58 000	22,0
24,0	59,1	37,7	59 600	56 800	54 200	51 800	24,0
26,0	55,8	36,3	53 000	50 800	48 600	46 600	26,0
28,0	52,4	34,8	47 600	45 800	43 900	42 200	28,0
30,0	48,8	33,1	43 000	41 400	39 900	38 400	30,0
32,0	45,0	31,1	39 000	37 600	36 300	35 100	32,0
34,0	40,9	28,8	35 500	34 400	33 300	32 200	34,0
36,0	36,3	26,2	32 500	31 500	30 600	29 700	36,0
38,0	31,2	23,0	29 700	28 900	28 100	27 400	38,0
40,0	25,2	19,1	27 300	26 600	26 000	25 300	40,0

B10



200 200 kg



360°

m	°	m	kg	kg	kg	kg	m
10,4	80,7	49,4	196 000				10,4
11,0	79,9	49,3	185 300				11,0
12,0	78,7	49,0	162 100				12,0
13,0	77,5	48,8	144 500	130 300			13,0
14,0	76,2	48,5	128 900	117 300			14,0
15,0	75,0	48,3	116 500	106 700			15,0
16,0	73,7	48,0	106 200	97 800	90 500		16,0
17,0	72,5	47,6	97 100	89 900	83 500	77 800	17,0
18,0	71,2	47,3	89 500	83 200	77 600	72 500	18,0
19,0	69,9	46,9	82 900	77 400	72 400	67 800	19,0
20,0	68,7	46,5	76 900	72 000	67 600	63 500	20,0
22,0	66,1	45,6	67 100	63 200	59 700	56 300	22,0
24,0	63,4	44,6	59 200	56 000	53 100	50 300	24,0
26,0	60,6	43,5	52 600	50 000	47 600	45 200	26,0
28,0	57,8	42,2	47 200	45 000	42 900	41 000	28,0
30,0	54,9	40,8	42 600	40 700	38 900	37 300	30,0
32,0	51,9	39,3	38 600	37 000	35 400	34 000	32,0
34,0	48,7	37,5	35 100	33 700	32 400	31 200	34,0
36,0	45,4	35,6	32 100	30 900	29 700	28 600	36,0
38,0	41,9	33,4	29 300	28 300	27 300	26 400	38,0
40,0	38,0	30,9	26 900	26 100	25 200	24 400	40,0
42,0	33,8	28,0	24 800	24 000	23 300	22 500	42,0
44,0	29,1	24,6	22 800	22 100	21 500	20 900	44,0
46,0	23,4	20,3	21 000	20 400	19 900	19 400	46,0



 m	 °	 m	 kg	 kg	 kg	 kg	 m
9,8	82,4	55,6	199 800				9,8
10,0	82,1	55,5	196 000				10,0
11,0	81,0	55,4	181 300				11,0
12,0	80,0	55,2	162 200	143 200			12,0
13,0	78,9	55,0	144 600	128 900			13,0
14,0	77,8	54,7	129 000	116 100	105 200		14,0
15,0	76,7	54,5	116 500	105 700	96 400		15,0
16,0	75,6	54,2	106 200	96 900	88 900	81 800	16,0
17,0	74,5	53,9	97 100	89 100	82 100	75 900	17,0
18,0	73,4	53,6	89 500	82 500	76 300	70 800	18,0
19,0	72,3	53,3	82 800	76 700	71 200	66 300	19,0
20,0	71,1	52,9	76 800	71 400	66 500	62 100	20,0
22,0	68,9	52,2	67 100	62 700	58 800	55 100	22,0
24,0	66,6	51,3	59 100	55 600	52 300	49 300	24,0
26,0	64,2	50,3	52 600	49 600	46 900	44 300	26,0
28,0	61,8	49,3	47 200	44 700	42 300	40 100	28,0
30,0	59,3	48,1	42 500	40 400	38 400	36 500	30,0
32,0	56,8	46,8	38 500	36 700	34 900	33 300	32,0
34,0	54,2	45,3	35 100	33 500	32 000	30 500	34,0
36,0	51,5	43,8	32 000	30 600	29 300	28 000	36,0
38,0	48,7	42,0	29 300	28 100	26 900	25 800	38,0
40,0	45,7	40,1	26 900	25 800	24 800	23 800	40,0
42,0	42,6	38,0	24 700	23 800	22 900	22 000	42,0
44,0	39,3	35,6	22 800	22 000	21 200	20 400	44,0
46,0	35,7	32,8	21 000	20 300	19 600	18 900	46,0
48,0	31,8	29,7	19 400	18 700	18 100	17 500	48,0
50,0	27,3	26,0	17 900	17 300	16 800	16 300	50,0
52,0	22,0	21,4	16 500	16 000	15 600	15 100	52,0

B10



200 200 kg



360°

m	°	m	kg	kg	kg	kg	m
8,5	84,3	61,8	190 900				8,5
9,0	83,9	61,7	187 400				9,0
10,0	82,9	61,6	179 200				10,0
11,0	82,0	61,5	171 300	134 500			11,0
12,0	81,0	61,3	160 600	129 200			12,0
13,0	80,0	61,1	144 200	122 400			13,0
14,0	79,0	60,9	128 500	114 400	102 600		14,0
15,0	78,1	60,7	116 000	104 100	94 100		15,0
16,0	77,1	60,4	105 700	95 500	86 800	79 200	16,0
17,0	76,1	60,2	96 600	87 800	80 200	73 600	17,0
18,0	75,1	59,9	88 900	81 200	74 500	68 600	18,0
19,0	74,1	59,6	82 300	75 500	69 600	64 300	19,0
20,0	73,1	59,3	76 300	70 300	65 000	60 200	20,0
22,0	71,1	58,6	66 500	61 700	57 300	53 400	22,0
24,0	69,0	57,8	58 500	54 600	51 000	47 700	24,0
26,0	67,0	57,0	51 900	48 700	45 700	42 900	26,0
28,0	64,9	56,0	46 500	43 700	41 200	38 800	28,0
30,0	62,7	55,0	41 900	39 500	37 300	35 200	30,0
32,0	60,5	53,9	37 800	35 800	33 900	32 100	32,0
34,0	58,3	52,7	34 400	32 600	30 900	29 400	34,0
36,0	56,0	51,3	31 400	29 800	28 300	26 900	36,0
38,0	53,6	49,8	28 600	27 300	26 000	24 700	38,0
40,0	51,2	48,2	26 200	25 000	23 900	22 800	40,0
42,0	48,6	46,5	24 100	23 000	22 000	21 000	42,0
44,0	46,0	44,6	22 100	21 200	20 200	19 400	44,0
46,0	43,2	42,5	20 400	19 500	18 700	17 900	46,0
48,0	40,3	40,2	18 800	18 000	17 200	16 500	48,0
50,0	37,2	37,6	17 300	16 600	15 900	15 300	50,0
52,0	33,8	34,7	15 900	15 300	14 700	14 100	52,0
54,0	30,1	31,3	14 600	14 100	13 600	13 100	54,0
56,0	25,9	27,4	13 500	13 000	12 500	12 100	56,0
58,0	20,8	22,5	12 300	11 900	11 600	11 200	58,0

MLC300 S-3



8,5	84,8	67,8	169 300				8,5
9,0	84,4	67,8	166 900				9,0
10,0	83,6	67,6	160 500				10,0
11,0	82,7	67,5	154 000	120 100			11,0
12,0	81,8	67,3	147 800	115 700			12,0
13,0	80,9	67,2	138 900	111 500	94 300		13,0
14,0	80,0	67,0	128 500	107 000	92 800		14,0
15,0	79,2	66,8	116 000	101 900	89 700		15,0
16,0	78,3	66,6	105 600	94 500	84 500	74 600	16,0
17,0	77,4	66,3	96 500	86 900	78 800	71 700	17,0
18,0	76,5	66,1	88 800	80 500	73 300	67 000	18,0
19,0	75,6	65,8	82 200	74 800	68 400	62 700	19,0
20,0	74,7	65,5	76 100	69 600	63 900	58 800	20,0
22,0	72,9	64,9	66 300	61 100	56 400	52 200	22,0
24,0	71,0	64,2	58 400	54 000	50 200	46 600	24,0
26,0	69,2	63,5	51 800	48 200	44 900	41 900	26,0
28,0	67,3	62,6	46 300	43 300	40 500	37 900	28,0
30,0	65,4	61,7	41 700	39 100	36 700	34 400	30,0
32,0	63,4	60,7	37 700	35 400	33 300	31 300	32,0
34,0	61,5	59,6	34 200	32 200	30 400	28 700	34,0
36,0	59,4	58,5	31 200	29 400	27 800	26 300	36,0
38,0	57,4	57,2	28 400	26 900	25 500	24 100	38,0
40,0	55,3	55,8	26 100	24 700	23 400	22 200	40,0
42,0	53,1	54,3	23 900	22 700	21 500	20 400	42,0
44,0	50,9	52,7	21 900	20 900	19 800	18 800	44,0
46,0	48,6	50,9	20 200	19 200	18 300	17 400	46,0
48,0	46,2	49,0	18 600	17 700	16 800	16 000	48,0
50,0	43,7	47,0	17 100	16 300	15 500	14 800	50,0
52,0	41,0	44,7	15 700	15 000	14 300	13 700	52,0
54,0	38,3	42,2	14 500	13 800	13 200	12 600	54,0
56,0	35,3	39,4	13 300	12 700	12 200	11 600	56,0
58,0	32,1	36,3	12 200	11 700	11 200	10 700	58,0
60,0	28,6	32,8	11 200	10 800	10 300	9 900	60,0
62,0	24,5	28,6	10 300	9 900	9 500	9 100	62,0
64,0	19,7	23,4	9 400	9 000	8 700	8 300	64,0

B10



200 200 kg



360°

m	°	m	kg	kg	kg	kg	m
9,1	84,8	73,8	140 100				9,1
10,0	84,1	73,7	139 300				10,0
11,0	83,3	73,6	137 200	100 700			11,0
12,0	82,5	73,4	132 000	100 300	77 600		12,0
13,0	81,7	73,3	127 100	98 400	77 300		13,0
14,0	80,9	73,1	121 500	95 800	77 000	61 900	14,0
15,0	80,1	72,9	114 100	92 500	76 700	61 700	15,0
16,0	79,3	72,7	105 000	89 300	75 900	61 500	16,0
17,0	78,4	72,5	95 800	85 400	74 300	61 400	17,0
18,0	77,6	72,3	88 200	79 100	70 900	61 200	18,0
19,0	76,8	72,0	81 500	73 500	66 700	59 500	19,0
20,0	76,0	71,8	75 500	68 400	62 300	56 900	20,0
22,0	74,3	71,2	65 600	60 000	54 900	50 500	22,0
24,0	72,7	70,6	57 600	53 000	48 800	45 100	24,0
26,0	71,0	69,9	51 000	47 100	43 600	40 400	26,0
28,0	69,3	69,1	45 600	42 300	39 300	36 500	28,0
30,0	67,6	68,3	40 900	38 100	35 500	33 100	30,0
32,0	65,8	67,4	36 900	34 400	32 200	30 100	32,0
34,0	64,1	66,4	33 400	31 300	29 300	27 400	34,0
36,0	62,3	65,4	30 400	28 500	26 700	25 100	36,0
38,0	60,4	64,3	27 700	26 000	24 400	22 900	38,0
40,0	58,6	63,0	25 300	23 800	22 400	21 000	40,0
42,0	56,7	61,7	23 100	21 800	20 500	19 300	42,0
44,0	54,7	60,3	21 200	20 000	18 800	17 700	44,0
46,0	52,7	58,8	19 400	18 300	17 300	16 300	46,0
48,0	50,7	57,2	17 800	16 800	15 900	15 000	48,0
50,0	48,5	55,4	16 300	15 400	14 600	13 700	50,0
52,0	46,4	53,5	15 000	14 100	13 400	12 600	52,0
54,0	44,1	51,5	13 700	13 000	12 300	11 600	54,0
56,0	41,7	49,3	12 500	11 900	11 200	10 600	56,0
58,0	39,2	46,8	11 500	10 900	10 300	9 700	58,0
60,0	36,6	44,2	10 500	9 900	9 400	8 900	60,0
62,0	33,7	41,3	9 500	9 000	8 500	8 100	62,0
64,0	30,7	38,0	8 600	8 200	7 800	7 300	64,0
66,0	27,3	34,2	7 800	7 400	7 000	6 600	66,0
68,0	23,5	29,8	7 000	6 700	6 300	5 900	68,0
70,0	18,9	24,4	6 300	5 900	5 500	5 200	70,0



78,0 m							
m	°	m	kg	kg	kg	kg	m
9,8	84,7	79,7	116 300				9,8
10,0	84,6	79,7	116 100				10,0
11,0	83,8	79,6	115 300	83 400			11,0
12,0	83,1	79,5	114 600	82 900			12,0
13,0	82,3	79,3	113 800	82 500	63 400		13,0
14,0	81,6	79,2	113 100	82 100	63 100	50 300	14,0
15,0	80,8	79,0	112 400	81 700	62 900	50 200	15,0
16,0	80,1	78,8	104 900	81 400	62 700	50 000	16,0
17,0	79,4	78,6	95 700	80 400	62 400	49 900	17,0
18,0	78,6	78,4	88 000	77 300	62 200	49 700	18,0
19,0	77,8	78,2	81 300	72 700	62 000	49 500	19,0
20,0	77,1	78,0	75 200	67 700	61 100	49 400	20,0
22,0	75,6	77,4	65 400	59 300	53 900	48 100	22,0
24,0	74,0	76,9	57 400	52 300	47 900	43 900	24,0
26,0	72,5	76,2	50 800	46 600	42 800	39 400	26,0
28,0	71,0	75,6	45 300	41 700	38 500	35 600	28,0
30,0	69,4	74,8	40 600	37 600	34 800	32 200	30,0
32,0	67,8	74,0	36 600	33 900	31 500	29 200	32,0
34,0	66,2	73,1	33 100	30 800	28 600	26 700	34,0
36,0	64,6	72,2	30 100	28 000	26 100	24 300	36,0
38,0	62,9	71,1	27 300	25 500	23 800	22 200	38,0
40,0	61,2	70,0	24 900	23 300	21 800	20 400	40,0
42,0	59,5	68,9	22 800	21 300	19 900	18 600	42,0
44,0	57,8	67,6	20 800	19 500	18 300	17 100	44,0
46,0	56,0	66,3	19 100	17 900	16 700	15 700	46,0
48,0	54,2	64,8	17 500	16 400	15 300	14 400	48,0
50,0	52,4	63,3	16 000	15 000	14 100	13 200	50,0
52,0	50,5	61,7	14 600	13 700	12 900	12 000	52,0
54,0	48,5	59,9	13 400	12 600	11 800	11 000	54,0
56,0	46,5	58,0	12 200	11 500	10 700	10 000	56,0
58,0	44,4	56,0	11 100	10 500	9 800	9 200	58,0
60,0	42,2	53,8	10 100	9 500	8 900	8 300	60,0
62,0	40,0	51,4	9 200	8 600	8 100	7 500	62,0
64,0	37,6	48,9	8 300	7 800	7 300	6 700	64,0
66,0	35,0	46,1	7 500	7 000	6 500	5 900	66,0
68,0	32,3	43,0	6 700	6 200	5 700	5 100	68,0
70,0	29,4	39,5	5 900	5 400	4 900	4 400	70,0
72,0	26,2	35,6	5 100	4 600	4 100		72,0
74,0	22,5	31,0	4 300				74,0

B10



200 200 kg



360°

m	°	m	kg	kg	kg	kg	m
10,4	84,7	85,7	98 000				10,4
11,0	84,3	85,7	97 500				11,0
12,0	83,6	85,5	96 800	69 400			12,0
13,0	82,9	85,4	96 200	69 000			13,0
14,0	82,2	85,3	95 500	68 700	52 200		14,0
15,0	81,5	85,1	94 900	68 300	52 000		15,0
16,0	80,8	84,9	94 200	68 000	51 700	40 700	16,0
17,0	80,1	84,8	92 400	67 600	51 500	40 600	17,0
18,0	79,4	84,6	86 800	67 300	51 300	40 500	18,0
19,0	78,7	84,3	80 700	66 900	51 100	40 300	19,0
20,0	78,0	84,1	74 600	65 900	50 900	40 200	20,0
22,0	76,6	83,7	64 700	58 200	50 200	39 900	22,0
24,0	75,2	83,1	56 700	51 300	46 600	39 600	24,0
26,0	73,8	82,5	50 000	45 500	41 500	38 000	26,0
28,0	72,4	81,9	44 600	40 700	37 300	34 200	28,0
30,0	70,9	81,2	39 900	36 600	33 600	30 900	30,0
32,0	69,5	80,5	35 800	33 000	30 400	28 000	32,0
34,0	68,0	79,7	32 400	29 900	27 600	25 400	34,0
36,0	66,5	78,8	29 300	27 100	25 000	23 100	36,0
38,0	65,0	77,9	26 600	24 600	22 800	21 100	38,0
40,0	63,5	76,9	24 200	22 400	20 800	19 200	40,0
42,0	61,9	75,8	22 000	20 400	18 900	17 500	42,0
44,0	60,4	74,7	20 000	18 600	17 300	16 000	44,0
46,0	58,8	73,4	18 300	17 000	15 700	14 600	46,0
48,0	57,2	72,2	16 700	15 500	14 400	13 300	48,0
50,0	55,5	70,8	15 200	14 100	13 100	12 100	50,0
52,0	53,8	69,3	13 800	12 800	11 900	11 000	52,0
54,0	52,1	67,8	12 600	11 700	10 800	10 000	54,0
56,0	50,3	66,1	11 400	10 600	9 800	9 000	56,0
58,0	48,5	64,4	10 300	9 600	8 800	8 100	58,0
60,0	46,6	62,5	9 300	8 600	7 900	7 200	60,0
62,0	44,7	60,5	8 400	7 700	7 000	6 200	62,0
64,0	42,7	58,3	7 500	6 800	6 100	5 400	64,0
66,0	40,6	56,0	6 500	5 900	5 200	4 600	66,0
68,0	38,4	53,5	5 600	5 000	4 400		68,0
70,0	36,1	50,8	4 800	4 200			70,0



 90,0 m			
 m	 °	 m	 kg
11,0	84,7	91,7	82 500
12,0	84,0	91,6	81 900
13,0	83,4	91,5	81 300
14,0	82,7	91,3	80 400
15,0	82,1	91,2	78 600
16,0	81,4	91,0	76 500
17,0	80,8	90,9	74 400
18,0	80,1	90,7	72 400
19,0	79,5	90,5	70 500
20,0	78,8	90,3	68 700
22,0	77,5	89,8	63 900
24,0	76,2	89,3	56 500
26,0	74,9	88,8	49 900
28,0	73,6	88,2	44 400
30,0	72,2	87,6	39 700
32,0	70,9	86,9	35 700
34,0	69,5	86,1	32 200
36,0	68,2	85,3	29 100
38,0	66,8	84,5	26 400
40,0	65,4	83,6	24 000
42,0	64,0	82,6	21 800
44,0	62,5	81,5	19 900
46,0	61,1	80,4	18 100
48,0	59,6	79,3	16 500
50,0	58,1	78,0	15 000
52,0	56,6	76,7	13 700
54,0	55,0	75,3	12 400
56,0	53,4	73,8	11 300
58,0	51,8	72,3	10 200
60,0	50,2	70,6	9 200
62,0	48,5	68,8	8 300
64,0	46,7	67,0	7 300
66,0	44,9	65,0	6 300
68,0	43,1	62,9	5 400
70,0	41,2	60,6	4 500