

Liftcrane Boom Capacities

Boom No. B10:500

**with 140 200 kg Fixed Position Counterweight
at 4,1 m Position**

Crawler Machine on a Barge

0 Degree thru 3 Degree Static Machine List

No Travel - 360 Degree Rating - Two Swing Drives

MLC300 SERIES 1



LIFTING CAPACITIES: Lifting capacities are for a crawler machine when operating on a barge. Machine shall be positively secured to prevent shifting. Lifting capacities for various boom lengths and operating radii are for freely suspended loads and may be based on percent of static tipping or strength of structural components.

Upper boom point capacity for liftcrane service with single part whip line from Drum 6 is 13 600 kg or 27 200 kg with two part whip line. When Drum 2 or Drum 3 is used, capacity with single part whip line is 16 600 kg or 33 300 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom point sheaves is considered part of load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

BOOM BACKWARD STABILITY: Capacities indicated by (b) require 2 270 kg minimum weight suspended beneath boom point. **Caution: Do not operate in areas indicated by (b) without required minimum weight.** *Boom may not lower and boom hoist wire rope may go slack causing wire rope damage or failure.*

OPERATING CONDITIONS: Machine to operate on a firm and uniformly supporting surface with machine list not to exceed degrees noted. Refer to Boom Rigging **No. 81023380**, Wire Rope Specifications chart **No. 9341-A**, Counterweight Arrangements **No. 9345-A**, and Wind Conditions chart **No. 9344-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.



OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation at barge deck to center of vertical hoist line or load block.



BOOM ANGLE: Boom angle in degrees (°) is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.



BOOM POINT ELEVATION: Boom point elevation is vertical distance from barge deck to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with two swing drives, 9 700 mm crawlers, 1 219 mm or 1 524 mm treads, 9 144 mm live mast, 24 part boom hoist reeving, boom support straps, and 140 200 kg Fixed Position Counterweight.

Warning: Luffing jib backstay straps must be removed before use of this chart. *Crane tipping or structural damage can occur.*

Refer to Tables 1 and 2 for raising ability with the maximum weight of all load blocks, hooks, weight ball, slings, and hoist lines beneath boom point sheaves. For block weights shown with #, load blocks, hooks, weight ball, and slings must remain on barge deck until combined weights are within rated capacity of chart. Raising is not permitted in shaded areas of table.

Combined weight beneath boom point sheaves must not exceed block weight shown.

Table 1

Over End or Side of Crawlers				
Boom Length (m)	Machine List			
	0°	1°	2°	3°
	Block Weight (kg)			
30,0	10 300	10 300	10 300	10 300
36,0	10 300	10 300	10 300	10 300
42,0	10 300	10 300	10 300	10 300
48,0	10 300	10 300	10 300	10 300
54,0	7 100	7 100	7 100	7 100
60,0	3 700	3 700	3 700	3 700
66,0	#	#	#	#
72,0	#	#	#	#
78,0	Raising Not Permitted			

Table 2

Over End of Blocked Crawlers				
Boom Length (m)	Machine List			
	0°	1°	2°	3°
	Block Weight (kg)			
30,0	10 300	10 300	10 300	10 300
36,0	10 300	10 300	10 300	10 300
42,0	10 300	10 300	10 300	10 300
48,0	10 300	10 300	10 300	10 300
54,0	7 100	7 100	7 100	7 100
60,0	3 700	3 700	3 700	3 700
66,0	#	#	#	#
72,0	#	#	#	#
78,0	#	#	#	#
Warning: Crane must remain in-line with crawlers when raising over end of blocked crawlers until operating radius is within 360 degree chart. Crane tipping or structural damage can occur.				

Explanation of Symbols

 **B10** Boom No. B10:500

 Fixed Position Counterweight


 360 Degree Rating

 Boom Length

 Operating Radius
(see page 1)

 Boom Angle
(see page 1)

 Boom Point Elevation
(see page 1)

 Machine List

 Lifting Capacities
(see page 1)

B10



140 200 kg



360°

m	o	m	kg	kg	kg	kg	m
5,5	84,5	31,9	300 000 b				5,5
6,0	83,5	31,9	300 000 b				6,0
6,5	82,5	31,8	290 500 b	244 300 b			6,5
7,0	81,6	31,7	274 100 b	243 200 b			7,0
7,5	80,6	31,6	258 400	234 000	183 400 b		7,5
8,0	79,6	31,5	241 100	212 100	181 800		8,0
8,5	78,6	31,4	215 600	191 800	171 900		8,5
9,0	77,6	31,2	195 200	175 300	158 600		9,0
10,0	75,7	31,0	163 300	148 800	136 300	125 500	10,0
11,0	73,7	30,7	139 600	128 600	119 000	110 500	11,0
12,0	71,6	30,3	121 900	113 200	105 500	98 700	12,0
13,0	69,6	29,9	108 400	101 300	95 000	89 200	13,0
14,0	67,5	29,5	96 500	90 800	85 500	80 700	14,0
15,0	65,4	29,0	87 000	82 200	77 800	73 700	15,0
16,0	63,2	28,5	79 200	75 100	71 300	67 800	16,0
17,0	61,0	27,9	72 200	68 700	65 500	62 500	17,0
18,0	58,8	27,3	66 400	63 400	60 600	57 900	18,0
19,0	56,5	26,6	61 300	58 700	56 200	53 900	19,0
20,0	54,1	25,8	56 700	54 400	52 300	50 200	20,0
22,0	49,0	24,1	49 200	47 400	45 800	44 100	22,0
24,0	43,6	22,1	43 100	41 700	40 400	39 100	24,0
26,0	37,4	19,5	38 000	36 900	35 900	34 900	26,0
28,0	30,2	16,3	33 800	32 900	32 100	31 300	28,0
30,0	20,5	11,7	30 000	29 400	28 800	28 300	30,0



m	°	m	kg	kg	kg	kg	m
5,8	84,9	37,9	294 700 b				5,8
6,0	84,6	37,9	293 700 b				6,0
6,5	83,8	37,8	281 500	235 600 b			6,5
7,0	83,0	37,8	266 100	232 200 b			7,0
7,5	82,2	37,7	252 000	224 200	178 400 b		7,5
8,0	81,4	37,6	237 600	207 900	176 600		8,0
8,5	80,6	37,5	215 800	188 400	166 100	138 600	8,5
9,0	79,7	37,4	195 600	172 300	153 500	135 800	9,0
10,0	78,1	37,2	163 600	146 600	132 400	120 400	10,0
11,0	76,5	36,9	139 900	126 900	115 900	106 400	11,0
12,0	74,8	36,6	122 100	111 900	103 000	95 200	12,0
13,0	73,1	36,3	108 600	100 200	92 800	86 300	13,0
14,0	71,5	36,0	96 600	89 800	83 700	78 200	14,0
15,0	69,7	35,6	87 100	81 400	76 200	71 500	15,0
16,0	68,0	35,2	79 200	74 300	69 900	65 900	16,0
17,0	66,3	34,7	72 200	68 100	64 200	60 700	17,0
18,0	64,5	34,2	66 400	62 800	59 400	56 300	18,0
19,0	62,7	33,7	61 300	58 200	55 200	52 500	19,0
20,0	60,9	33,1	56 700	53 900	51 300	48 900	20,0
22,0	57,1	31,8	49 200	47 000	45 000	43 000	22,0
24,0	53,1	30,3	43 100	41 400	39 700	38 100	24,0
26,0	48,9	28,6	38 000	36 600	35 300	34 000	26,0
28,0	44,4	26,6	33 900	32 700	31 600	30 500	28,0
30,0	39,5	24,2	30 300	29 300	28 400	27 500	30,0
32,0	33,9	21,4	27 100	26 400	25 600	24 900	32,0
34,0	27,3	17,7	24 400	23 800	23 200	22 600	34,0

B10



140 200 kg



360°

6,4	84,8	43,9	267 800				6,4
6,5	84,7	43,9	267 000				6,5
7,0	84,0	43,8	257 200				7,0
7,5	83,3	43,8	244 100	205 600			7,5
8,0	82,6	43,7	231 400	200 800	165 400		8,0
8,5	81,9	43,6	215 700	184 700	160 100	131 300	8,5
9,0	81,2	43,5	195 900	169 300	148 600	129 600	9,0
10,0	79,8	43,3	163 800	144 300	128 500	115 500	10,0
11,0	78,4	43,1	139 900	125 100	112 800	102 400	11,0
12,0	77,0	42,9	122 100	110 400	100 400	91 800	12,0
13,0	75,6	42,6	108 500	98 900	90 600	83 400	13,0
14,0	74,2	42,3	96 600	88 700	81 800	75 700	14,0
15,0	72,8	42,0	87 000	80 400	74 500	69 300	15,0
16,0	71,3	41,6	79 100	73 500	68 400	63 900	16,0
17,0	69,9	41,2	72 100	67 300	62 900	58 900	17,0
18,0	68,4	40,8	66 200	62 000	58 200	54 700	18,0
19,0	66,9	40,4	61 200	57 500	54 100	51 000	19,0
20,0	65,4	39,9	56 500	53 300	50 300	47 500	20,0
22,0	62,3	38,9	49 000	46 500	44 100	41 800	22,0
24,0	59,1	37,7	42 900	40 800	38 900	37 000	24,0
26,0	55,8	36,3	37 900	36 200	34 500	33 000	26,0
28,0	52,4	34,8	33 700	32 300	30 900	29 600	28,0
30,0	48,8	33,1	30 100	28 900	27 800	26 700	30,0
32,0	45,0	31,1	27 000	26 000	25 000	24 100	32,0
34,0	40,9	28,8	24 300	23 500	22 700	21 900	34,0
36,0	36,3	26,2	22 000	21 200	20 500	19 900	36,0
38,0	31,2	23,0	19 800	19 200	18 600	18 100	38,0
40,0	25,2	19,1	17 900	17 400	16 900	16 500	40,0

MLC300 S-1



m	°	m	kg	kg	kg	kg	m
7,3	84,4	49,8	239 600				7,3
7,5	84,1	49,8	235 500				7,5
8,0	83,5	49,8	224 300	182 900			8,0
8,5	82,9	49,7	214 100	180 300	149 200		8,5
9,0	82,3	49,6	195 700	166 300	142 500		9,0
10,0	81,1	49,4	163 700	141 900	124 700	110 700	10,0
11,0	79,9	49,3	139 800	123 200	109 700	98 400	11,0
12,0	78,7	49,0	121 900	108 700	97 800	88 500	12,0
13,0	77,5	48,8	108 300	97 500	88 300	80 400	13,0
14,0	76,2	48,5	96 300	87 400	79 800	73 100	14,0
15,0	75,0	48,3	86 700	79 300	72 700	67 000	15,0
16,0	73,7	48,0	78 800	72 400	66 800	61 800	16,0
17,0	72,5	47,6	71 800	66 300	61 400	57 100	17,0
18,0	71,2	47,3	65 900	61 100	56 800	53 000	18,0
19,0	69,9	46,9	60 800	56 600	52 800	49 400	19,0
20,0	68,7	46,5	56 200	52 500	49 100	46 000	20,0
22,0	66,1	45,6	48 700	45 700	43 000	40 500	22,0
24,0	63,4	44,6	42 500	40 100	37 900	35 800	24,0
26,0	60,6	43,5	37 500	35 500	33 600	31 900	26,0
28,0	57,8	42,2	33 300	31 600	30 000	28 500	28,0
30,0	54,9	40,8	29 700	28 300	26 900	25 700	30,0
32,0	51,9	39,3	26 600	25 400	24 200	23 100	32,0
34,0	48,7	37,5	23 900	22 900	21 900	20 900	34,0
36,0	45,4	35,6	21 600	20 700	19 800	19 000	36,0
38,0	41,9	33,4	19 500	18 700	17 900	17 200	38,0
40,0	38,0	30,9	17 600	16 900	16 300	15 700	40,0
42,0	33,8	28,0	15 900	15 300	14 800	14 200	42,0
44,0	29,1	24,6	14 300	13 900	13 400	12 900	44,0
46,0	23,4	20,3	12 900	12 500	12 100	11 700	46,0

MLC300 S-1








B10



140 200 kg



360°

54,0 m							
 m	 °	 m	 kg	 kg	 kg	 kg	 m
7,3	85,0	55,9	222 700				7,3
7,5	84,8	55,9	221 200				7,5
8,0	84,3	55,8	216 300				8,0
8,5	83,7	55,7	206 900	163 600			8,5
9,0	83,2	55,7	194 200	160 400			9,0
10,0	82,1	55,5	164 000	139 900	121 300		10,0
11,0	81,0	55,4	140 000	121 600	107 000	95 000	11,0
12,0	80,0	55,2	122 000	107 400	95 500	85 600	12,0
13,0	78,9	55,0	108 400	96 400	86 400	78 000	13,0
14,0	77,8	54,7	96 400	86 500	78 200	71 000	14,0
15,0	76,7	54,5	86 800	78 500	71 300	65 200	15,0
16,0	75,6	54,2	78 800	71 700	65 500	60 100	16,0
17,0	74,5	53,9	71 800	65 700	60 300	55 600	17,0
18,0	73,4	53,6	65 900	60 600	55 800	51 600	18,0
19,0	72,3	53,3	60 800	56 100	51 900	48 100	19,0
20,0	71,1	52,9	56 100	52 000	48 300	44 900	20,0
22,0	68,9	52,2	48 600	45 300	42 300	39 500	22,0
24,0	66,6	51,3	42 500	39 800	37 300	35 000	24,0
26,0	64,2	50,3	37 400	35 100	33 100	31 100	26,0
28,0	61,8	49,3	33 200	31 300	29 600	27 900	28,0
30,0	59,3	48,1	29 600	28 000	26 500	25 100	30,0
32,0	56,8	46,8	26 500	25 100	23 800	22 600	32,0
34,0	54,2	45,3	23 900	22 700	21 500	20 400	34,0
36,0	51,5	43,8	21 500	20 500	19 500	18 500	36,0
38,0	48,7	42,0	19 400	18 500	17 600	16 800	38,0
40,0	45,7	40,1	17 500	16 700	16 000	15 200	40,0
42,0	42,6	38,0	15 900	15 200	14 500	13 800	42,0
44,0	39,3	35,6	14 300	13 700	13 100	12 600	44,0
46,0	35,7	32,8	13 000	12 400	11 900	11 400	46,0
48,0	31,8	29,7	11 700	11 200	10 800	10 300	48,0
50,0	27,3	26,0	10 500	10 100	9 700	9 300	50,0
52,0	22,0	21,4	9 400	9 100	8 800	8 400	52,0



 m	 °	 m	 0° kg	 1° kg	 2° kg	 3° kg	 m
7,9	84,9	61,8	192 300				7,9
8,0	84,8	61,9	192 100				8,0
8,5	84,4	61,8	190 900				8,5
9,0	83,9	61,7	187 400				9,0
10,0	82,9	61,6	163 800	135 000			10,0
11,0	82,0	61,5	139 700	119 600	103 900	91 600	11,0
12,0	81,0	61,3	121 700	105 700	92 900	82 400	12,0
13,0	80,0	61,1	108 000	94 800	84 000	75 100	13,0
14,0	79,0	60,9	95 900	85 100	76 100	68 500	14,0
15,0	78,1	60,7	86 300	77 200	69 400	62 900	15,0
16,0	77,1	60,4	78 300	70 500	63 800	58 000	16,0
17,0	76,1	60,2	71 200	64 500	58 700	53 600	17,0
18,0	75,1	59,9	65 300	59 500	54 300	49 800	18,0
19,0	74,1	59,6	60 200	55 000	50 500	46 400	19,0
20,0	73,1	59,3	55 600	51 000	46 900	43 300	20,0
22,0	71,1	58,6	48 000	44 300	41 000	38 000	22,0
24,0	69,0	57,8	41 800	38 800	36 100	33 600	24,0
26,0	67,0	57,0	36 800	34 300	32 000	29 900	26,0
28,0	64,9	56,0	32 600	30 500	28 500	26 700	28,0
30,0	62,7	55,0	29 000	27 200	25 500	23 900	30,0
32,0	60,5	53,9	25 900	24 300	22 900	21 500	32,0
34,0	58,3	52,7	23 200	21 900	20 600	19 400	34,0
36,0	56,0	51,3	20 800	19 700	18 500	17 500	36,0
38,0	53,6	49,8	18 700	17 700	16 700	15 800	38,0
40,0	51,2	48,2	16 900	16 000	15 100	14 300	40,0
42,0	48,6	46,5	15 200	14 400	13 600	12 900	42,0
44,0	46,0	44,6	13 700	13 000	12 300	11 600	44,0
46,0	43,2	42,5	12 300	11 700	11 100	10 500	46,0
48,0	40,3	40,2	11 100	10 500	9 900	9 400	48,0
50,0	37,2	37,6	9 900	9 400	8 900	8 400	50,0
52,0	33,8	34,7	8 900	8 400	8 000	7 500	52,0
54,0	30,1	31,3	7 900	7 500	7 100	6 700	54,0
56,0	25,9	27,4	6 900	6 600	6 200	5 900	56,0
58,0	20,8	22,5	6 100	5 700	5 400	5 000	58,0

MLC300 S-1



B10



140 200 kg



360°

m	°	m	kg	kg	kg	kg	m
8,5	84,8	67,8	169 300				8,5
9,0	84,4	67,8	166 900				9,0
10,0	83,6	67,6	158 800	122 800			10,0
11,0	82,7	67,5	139 800	117 900	95 300		11,0
12,0	81,8	67,3	121 700	104 300	90 700		12,0
13,0	80,9	67,2	108 000	93 700	82 200	72 200	13,0
14,0	80,0	67,0	95 900	84 100	74 500	66 500	14,0
15,0	79,2	66,8	86 200	76 300	68 000	61 100	15,0
16,0	78,3	66,6	78 200	69 700	62 500	56 400	16,0
17,0	77,4	66,3	71 100	63 800	57 600	52 200	17,0
18,0	76,5	66,1	65 200	58 800	53 300	48 500	18,0
19,0	75,6	65,8	60 100	54 400	49 500	45 200	19,0
20,0	74,7	65,5	55 400	50 400	46 100	42 200	20,0
22,0	72,9	64,9	47 900	43 800	40 300	37 100	22,0
24,0	71,0	64,2	41 700	38 400	35 400	32 700	24,0
26,0	69,2	63,5	36 600	33 900	31 400	29 100	26,0
28,0	67,3	62,6	32 400	30 100	27 900	26 000	28,0
30,0	65,4	61,7	28 800	26 800	25 000	23 300	30,0
32,0	63,4	60,7	25 700	24 000	22 400	20 900	32,0
34,0	61,5	59,6	23 000	21 500	20 100	18 800	34,0
36,0	59,4	58,5	20 700	19 300	18 100	16 900	36,0
38,0	57,4	57,2	18 600	17 400	16 300	15 300	38,0
40,0	55,3	55,8	16 700	15 700	14 700	13 800	40,0
42,0	53,1	54,3	15 000	14 100	13 200	12 400	42,0
44,0	50,9	52,7	13 500	12 700	11 900	11 200	44,0
46,0	48,6	50,9	12 100	11 400	10 700	10 000	46,0
48,0	46,2	49,0	10 900	10 200	9 600	9 000	48,0
50,0	43,7	47,0	9 700	9 200	8 600	8 000	50,0
52,0	41,0	44,7	8 700	8 200	7 600	7 100	52,0
54,0	38,3	42,2	7 700	7 200	6 700	6 200	54,0
56,0	35,3	39,4	6 800	6 300	5 800	5 300	56,0
58,0	32,1	36,3	5 900	5 400	4 900	4 400	58,0
60,0	28,6	32,8	4 900	4 500			60,0
62,0	24,5	28,6	4 000				62,0

MLC300 S-1



9,1	84,8	73,8	140 100				9,1
10,0	84,1	73,7	139 300				10,0
11,0	83,3	73,6	136 900	100 700			11,0
12,0	82,5	73,4	121 300	100 200	77 600		12,0
13,0	81,7	73,3	107 500	92 000	75 700		13,0
14,0	80,9	73,1	95 400	82 600	72 400	61 100	14,0
15,0	80,1	72,9	85 600	74 900	66 100	58 300	15,0
16,0	79,3	72,7	77 600	68 400	60 800	54 300	16,0
17,0	78,4	72,5	70 500	62 600	55 900	50 200	17,0
18,0	77,6	72,3	64 600	57 700	51 800	46 700	18,0
19,0	76,8	72,0	59 400	53 300	48 100	43 500	19,0
20,0	76,0	71,8	54 800	49 300	44 700	40 500	20,0
22,0	74,3	71,2	47 200	42 800	39 000	35 600	22,0
24,0	72,7	70,6	41 000	37 400	34 200	31 300	24,0
26,0	71,0	69,9	35 900	32 900	30 200	27 800	26,0
28,0	69,3	69,1	31 700	29 100	26 800	24 700	28,0
30,0	67,6	68,3	28 000	25 900	23 900	22 100	30,0
32,0	65,8	67,4	24 900	23 000	21 300	19 700	32,0
34,0	64,1	66,4	22 200	20 600	19 100	17 700	34,0
36,0	62,3	65,4	19 900	18 400	17 100	15 800	36,0
38,0	60,4	64,3	17 800	16 500	15 300	14 200	38,0
40,0	58,6	63,0	15 900	14 800	13 700	12 700	40,0
42,0	56,7	61,7	14 200	13 200	12 300	11 400	42,0
44,0	54,7	60,3	12 700	11 800	11 000	10 100	44,0
46,0	52,7	58,8	11 400	10 500	9 800	9 000	46,0
48,0	50,7	57,2	10 100	9 400	8 700	7 900	48,0
50,0	48,5	55,4	9 000	8 300	7 600	6 800	50,0
52,0	46,4	53,5	7 900	7 200	6 500	5 800	52,0
54,0	44,1	51,5	6 800	6 100	5 500	4 800	54,0
56,0	41,7	49,3	5 700	5 100	4 500	3 900	56,0
58,0	39,2	46,8	4 800				58,0

MLC300 S-1








B10



140 200 kg



360°

78,0 m							
 m	 °	 m	 kg	 kg	 kg	 kg	 m
9,8	84,7	79,7	116 300				9,8
10,0	84,6	79,7	116 100				10,0
11,0	83,8	79,6	115 300	83 400			11,0
12,0	83,1	79,5	114 600	82 900			12,0
13,0	82,3	79,3	105 700	82 500	63 400		13,0
14,0	81,6	79,2	95 300	80 400	63 100	50 300	14,0
15,0	80,8	79,0	85 500	73 800	62 900	50 200	15,0
16,0	80,1	78,8	77 500	67 600	59 300	49 900	16,0
17,0	79,4	78,6	70 400	61 800	54 800	48 800	17,0
18,0	78,6	78,4	64 400	56 900	50 700	45 300	18,0
19,0	77,8	78,2	59 200	52 600	47 100	42 200	19,0
20,0	77,1	78,0	54 500	48 700	43 700	39 400	20,0
22,0	75,6	77,4	46 900	42 200	38 100	34 500	22,0
24,0	74,0	76,9	40 700	36 900	33 400	30 400	24,0
26,0	72,5	76,2	35 600	32 400	29 500	26 900	26,0
28,0	71,0	75,6	31 400	28 600	26 200	23 900	28,0
30,0	69,4	74,8	27 700	25 400	23 300	21 300	30,0
32,0	67,8	74,0	24 600	22 600	20 700	19 000	32,0
34,0	66,2	73,1	21 900	20 200	18 500	17 000	34,0
36,0	64,6	72,2	19 600	18 000	16 500	15 200	36,0
38,0	62,9	71,1	17 500	16 100	14 800	13 600	38,0
40,0	61,2	70,0	15 600	14 400	13 200	12 100	40,0
42,0	59,5	68,9	13 900	12 800	11 800	10 800	42,0
44,0	57,8	67,6	12 400	11 400	10 500	9 600	44,0
46,0	56,0	66,3	11 000	10 100	9 300	8 400	46,0
48,0	54,2	64,8	9 800	9 000	8 100	7 200	48,0
50,0	52,4	63,3	8 600	7 800	6 900	6 100	50,0
52,0	50,5	61,7	7 400	6 600	5 800	5 000	52,0
54,0	48,5	59,9	6 300	5 500	4 800		54,0
56,0	46,5	58,0	5 200	4 500			56,0