

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
Boom No. B10:500
with Fixed Position Counterweight
at 4,1 m (13.4 ft) Position

Jobsite Travel

MLC300 SERIES 1 must be equipped with 140 200 kg (309,100 lb) counterweight; MLC300 SERIES 2 must be equipped with 180 200 kg (397,300 lb) counterweight; MLC300 Series 3 must be equipped with 200 200 kg (441,400 lb) counterweight. Refer to Wind Conditions chart for maximum wind speed for various boom lengths and capacity charts for maximum boom and jib lengths lifted unassisted. Travel slowly and smoothly to avoid shock loading boom, jib and rigging. **Warning: Maintain adequate clearance between boom or jib and load blocks, hooks, or weight ball while traveling.** *The boom or jib can buckle and collapse if the load blocks, hooks or weight ball contact the boom or jib.*

1. Machine Travel With Load

- A. Machine can swing and travel with 360 degree rating.
- B. Grade in any direction must not exceed 1 percent (0.5 degrees).
- C. Travel surface must be firm, level and uniformly supporting. Capacity charts are based on static conditions; therefore judgment must be used to allow for dynamic effects of traveling with load. Carry load as close to ground as possible. Stabilize load with taglines.

2. Machine Travel Without Load - Without Boom Angle Adjustment on Grade

- A. Load blocks, hooks, weight ball, slings, hoist lines, etc., may be suspended beneath boom or jib point, or tied off to machine. Total combined suspended weight beneath boom point must not exceed 10 000 kg (22,000 lb). Total suspended weight beneath jib point must not exceed 2 950 kg (6,500 lb).
- B. Machine to travel on a firm and uniformly supporting surface. Travel allowed with 360 degree swing up to 1 percent (0.5 degrees) grade; crane upperworks must be in-line with crawlers and grade when grade exceeds 1 percent. Side-to-side grade must not exceed 2 percent (1.1 degrees) measured at boom hinge pins.
- C. Refer to Tables 2 thru 4 for boom angle, boom length, and direction for various grades. **Adjust boom** within boom angle range shown in table with machine in a level position **before traveling** onto grade. **Do not adjust boom angle after crane has been traveled onto grade.** Boom angle is angle between horizontal and centerline of boom butt and inserts. Refer to Table 1 for grade vs. angle when traveling.
- D. Do not exceed 2 percent (1.1 degrees) side-to-side grade at boom hinge pins when cutting (turning on grade).
- E. Boom lengths shown in Tables 2 thru 4 include all jib lengths and offset angles.
- F. **Warning:** Travel prohibited for boom angle range not shown in Tables 2 thru 4. *Crane could tip.*

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
 Boom No. B10:500
 with Fixed Position Counterweight
 at 4,1 m (13.4 ft) Position

3. Machine Travel Without Load - With Boom Angle Adjustment on Grade

- A. Load blocks, hooks, weight ball, slings, hoist lines, etc., may be suspended beneath boom or jib point, or tied off to machine. Total combined suspended weight beneath boom point must not exceed 10 000 kg (22,000 lb). Total suspended weight beneath jib point must not exceed 2 950 kg (6,500 lb).
- B. Machine to travel on a firm and uniformly supporting surface. Travel allowed with 360 degree swing up to 1 percent (0.5 degrees) grade; crane upperworks must be in-line with crawlers and grade when grade exceeds 1 percent. Side-to-side grade must not exceed 2 percent (1.1 degrees) measured at boom hinge pins.
- C. Refer to Tables 5 thru 7 for boom angle, boom length, and direction for various grades. **Adjust boom** to remain within boom angle range shown in table **while traveling on grade**. Boom angle is angle between horizontal and centerline of boom butt and inserts. Refer to Table 1 for grade vs. angle when traveling.
- D. Do not exceed 2 percent (1.1 degrees) side-to-side grade at boom hinge pins when cutting (turning on grade).
- E. Boom lengths shown in Tables 5 thru 7 include all jib lengths and offset angles.
- F. **Warning:** Travel prohibited for boom angle range not shown in Tables 5 thru 7. *Crane could tip.*

Table 1

Percent Grade Vs. Angle In Degrees	
Percent Grade	Angle
5	2.9
10	5.7
20	11.3
30	16.7

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
 Boom No. B10:500
 with Fixed Position Counterweight
 at 4,1 m (13.4 ft) Position

Table 2a - Without Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
30,0	98.4	32 - 75	38 - 75	50 - 75	60 - 75
36,0	118.1	45 - 75	51 - 75	60 - 75	69 - 75
42,0	137.8	53 - 75	57 - 75	67 - 75	—
48,0	157.5	60 - 75	64 - 75	72 - 75	—
54,0	177.2	64 - 75	68 - 75	—	—
60,0	196.9	66 - 75	70 - 75	—	—
66,0	216.5	66 - 75	70 - 75	—	—

Table 2b - Without Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
30,0	98.4	31 - 72	31 - 69	31 - 52	31 - 37
36,0	118.1	41 - 72	41 - 69	41 - 60	41 - 47
42,0	137.8	50 - 72	50 - 69	50 - 63	50 - 52
48,0	157.5	56 - 72	56 - 69	56 - 63	—
54,0	177.2	60 - 72	60 - 69	60 - 63	—
60,0	196.9	63 - 72	63 - 69	—	—
66,0	216.5	63 - 72	63 - 69	—	—

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
 Boom No. B10:500
 with Fixed Position Counterweight
 at 4,1 m (13.4 ft) Position

Table 3a - Without Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
30,0	98.4	31 - 72	32 - 72	35 - 72	43 - 72
36,0	118.1	33 - 75	34 - 75	47 - 75	59 - 75
42,0	137.8	43 - 75	46 - 75	57 - 75	67 - 75
48,0	157.5	51 - 75	55 - 75	64 - 75	73 - 75
54,0	177.2	57 - 75	60 - 75	69 - 75	—
60,0	196.9	61 - 75	65 - 75	73 - 75	—
66,0	216.5	64 - 75	68 - 75	—	—
72,0	236.2	65 - 75	68 - 75	—	—

Table 3b - Without Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
30,0	98.4	31 - 63	31 - 53	31 - 33	—
36,0	118.1	33 - 70	33 - 62	33 - 45	—
42,0	137.8	37 - 72	37 - 66	37 - 52	—
48,0	157.5	46 - 72	46 - 69	46 - 58	—
54,0	177.2	53 - 72	53 - 69	53 - 61	—
60,0	196.9	57 - 72	57 - 69	57 - 63	—
66,0	216.5	61 - 72	61 - 69	61 - 63	—
72,0	236.2	61 - 72	61 - 69	61 - 63	—

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
Boom No. B10:500
with Fixed Position Counterweight
at 4,1 m (13.4 ft) Position

Table 4a - Without Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING DOWNHILL			
36,0	118.1	33 - 73	33 - 73
42,0	137.8	35 - 75	41 - 75
48,0	157.5	46 - 75	51 - 75
54,0	177.2	53 - 75	57 - 75
60,0	196.9	58 - 75	62 - 75
66,0	216.5	61 - 75	66 - 75
72,0	236.2	64 - 75	67 - 75
78,0	255.9	64 - 75	67 - 75

Table 4b - Without Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING UPHILL			
36,0	118.1	33 - 64	33 - 56
42,0	137.8	33 - 69	33 - 61
48,0	157.5	41 - 72	41 - 67
54,0	177.2	49 - 72	49 - 69
60,0	196.9	53 - 72	53 - 69
66,0	216.5	58 - 72	58 - 69
72,0	236.2	59 - 72	59 - 69
78,0	255.9	60 - 72	60 - 69

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
 Boom No. B10:500
 with Fixed Position Counterweight
 at 4,1 m (13.4 ft) Position

Table 5a - With Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
30,0	98.4	31 - 80	32 - 78	38 - 72	43 - 67
36,0	118.1	42 - 81	44 - 78	48 - 73	53 - 67
42,0	137.8	51 - 81	51 - 78	55 - 72	58 - 67
48,0	157.5	57 - 81	58 - 78	60 - 73	63 - 67
54,0	177.2	60 - 81	62 - 78	63 - 73	—
60,0	196.9	63 - 81	64 - 78	66 - 73	—
66,0	216.5	63 - 82	64 - 79	66 - 73	—

Table 5b - With Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
30,0	98.4	34 - 83	37 - 81	42 - 72	48 - 66
36,0	118.1	40 - 84	40 - 83	43 - 78	49 - 73
42,0	137.8	49 - 84	49 - 84	49 - 79	49 - 75
48,0	157.5	56 - 84	56 - 84	56 - 82	56 - 79
54,0	177.2	60 - 84	60 - 84	60 - 84	60 - 80
60,0	196.9	63 - 84	63 - 84	63 - 84	63 - 82
66,0	216.5	62 - 84	62 - 84	62 - 84	62 - 83

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
 Boom No. B10:500
 with Fixed Position Counterweight
 at 4,1 m (13.4 ft) Position

Table 6a - With Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
30,0	98.4	31 - 68	31 - 65	31 - 59	31 - 54
36,0	118.1	32 - 75	32 - 72	35 - 66	42 - 61
42,0	137.8	39 - 77	40 - 74	46 - 69	50 - 63
48,0	157.5	47 - 80	49 - 77	52 - 71	56 - 66
54,0	177.2	53 - 81	54 - 78	57 - 73	60 - 67
60,0	196.9	58 - 81	59 - 78	62 - 73	—
66,0	216.5	61 - 81	62 - 78	64 - 73	—
72,0	236.2	62 - 81	62 - 78	65 - 73	—

Table 6b - With Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
30,0	98.4	34 - 71	37 - 69	42 - 61	—
36,0	118.1	35 - 77	38 - 75	43 - 67	49 - 61
42,0	137.8	36 - 80	36 - 77	41 - 72	47 - 67
48,0	157.5	46 - 82	46 - 81	46 - 75	48 - 72
54,0	177.2	52 - 83	52 - 82	52 - 78	52 - 74
60,0	196.9	56 - 84	56 - 83	56 - 80	56 - 77
66,0	216.5	61 - 84	61 - 84	61 - 82	61 - 78
72,0	236.2	61 - 84	61 - 84	61 - 83	61 - 80

Maximum Allowable Travel Specifications

MLC300

Jib No. 148 on
 Boom No. B10:500
 with Fixed Position Counterweight
 at 4,1 m (13.4 ft) Position

Table 7a - With Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING DOWNHILL			
36,0	118.1	32 - 70	32 - 67
42,0	137.8	33 - 74	35 - 71
48,0	157.5	43 - 77	45 - 74
54,0	177.2	49 - 79	50 - 76
60,0	196.9	55 - 81	56 - 78
66,0	216.5	59 - 81	60 - 78
72,0	236.2	60 - 81	61 - 78
78,0	255.9	60 - 81	61 - 79

Table 7b - With Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length (including all jib lengths and offsets)		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING UPHILL			
36,0	118.1	35 - 73	38 - 71
42,0	137.8	33 - 76	36 - 74
48,0	157.5	40 - 80	40 - 78
54,0	177.2	48 - 82	48 - 79
60,0	196.9	54 - 83	54 - 82
66,0	216.5	58 - 84	58 - 83
72,0	236.2	59 - 84	59 - 84
78,0	255.9	59 - 84	59 - 84