

Liftcrane Boom

Extended Upper Point Capacities

MLC300 SERIES 2

Boom No. B45:505-500

with 7,0 m Extended Upper Boom Point

175 200 kg VPC (Variable Position Counterweight)

360 Degree Rating



LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and may be based on percent of static tipping or strength of structural components. Capacities must be reduced by applicable deducts.

Upper boom point (upper sheave) capacity for liftcrane service with single part whip line from Drum 6 is 13 600 kg. When Drum 2 or Drum 3 is used, capacity with single part whip line is 16 600 kg. In all cases, upper boom point capacities cannot exceed those listed for extended upper boom point (lower sheave) capacity.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath sheaves is considered part of load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate on a firm, level, and uniformly supporting surface. Refer to Boom Rigging **No. 84049567**, Wire Rope Specifications chart **No. 9647-A**, Counterweight Arrangements chart **No. 9345-A**, and Wind Conditions chart **No. 9646-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.

MACHINE TRAVEL: Machine to travel on a firm, level, and uniformly supporting surface. Boom must be within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specifications chart **No. 9645-A**.



EXTENDED UPPER BOOM POINT OPERATING RADIUS: Extended upper boom point operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block.



BOOM ANGLE: Boom angle in degrees (°) is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.



EXTENDED UPPER BOOM POINT ELEVATION: Extended upper boom point elevation is vertical distance from ground level to centerline of extended upper boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 9 700 mm crawlers, 1 219 mm or 1 524 mm treads, 9 144 mm live mast, 24 part boom hoist reeving, boom support straps, and 175 200 kg VPC.

Luffing Jib Backstay Deduct	
Boom Length (m)	Deduct (kg)
35,0	1 400
38,0	1 500
41,0	1 700
44,0	1 800
47,0	2 000
50,0	2 100
53,0	2 200
56,0	2 300
59,0	2 400
62,0	2 600
65,0	2 700
68,0	2 900
71,0	3 000
74,0	3 200
77,0	3 200
Deduct the appropriate value from capacities when luffing jib backstays are stored on boom.	

Refer to Table 1 (with luffing jib backstays stored) and Table 2 (without luffing jib backstays stored) for raising ability with the maximum weight of all load blocks, hooks, weight ball, slings, and hoist lines beneath extended upper boom point (lower or upper sheaves). For block weights shown with #, load blocks, hooks, weight ball, and slings must remain on ground until combined weights are within rated capacity of chart. Raising is not permitted in shaded areas of table.

Combined weight beneath extended upper boom point (lower or upper sheaves) must not exceed block weight shown.

Table 1a: With Luffing Jib Backstays

Over End or Side of Crawlers	
Boom Length (m)	Block Weight (kg)
35,0	3 400
38,0	3 400
41,0	3 400
44,0	3 400
47,0	3 400
50,0	3 400
53,0	3 400
56,0	3 400
59,0	3 400
62,0	3 400
65,0	3 400
68,0	3 400
71,0	3 400
74,0	3 400
77,0	#
80,0	Raising Not Permitted
83,0	
86,0	
89,0	

Table 1b: With Luffing Jib Backstays

Over End of Blocked Crawlers	
Boom Length (m)	Block Weight (kg)
35,0	3 400
38,0	3 400
41,0	3 400
44,0	3 400
47,0	3 400
50,0	3 400
53,0	3 400
56,0	3 400
59,0	3 400
62,0	3 400
65,0	3 400
68,0	3 400
71,0	3 400
74,0	3 400
77,0	#
80,0	Raising Not Permitted
83,0	
86,0	
89,0	

Warning: Crane must remain in-line with crawlers when raising over end of blocked crawlers until operating radius is within 360 degree chart. Crane tipping or structural damage can occur.

Table 2a: Without Luffing Jib Backstays

Over End or Side of Crawlers	
Boom Length (m)	Block Weight (kg)
35,0	3 400
38,0	3 400
41,0	3 400
44,0	3 400
47,0	3 400
50,0	3 400
53,0	3 400
56,0	3 400
59,0	3 400
62,0	3 400
65,0	3 400
68,0	3 400
71,0	3 400
74,0	3 400
77,0	3 400
80,0	#
83,0	#
86,0	#
89,0	Raising Not Permitted

Table 2b: With Luffing Jib Backstays

Over End of Blocked Crawlers	
Boom Length (m)	Block Weight (kg)
35,0	3 400
38,0	3 400
41,0	3 400
44,0	3 400
47,0	3 400
50,0	3 400
53,0	3 400
56,0	3 400
59,0	3 400
62,0	3 400
65,0	3 400
68,0	3 400
71,0	3 400
74,0	3 400
77,0	3 400
80,0	#
83,0	#
86,0	#
89,0	#

Warning: Crane must remain in-line with crawlers when raising over end of blocked crawlers until operating radius is within 360 degree chart. Crane tipping or structural damage can occur.

Explanation of Symbols




Boom No. B45:505-500




VPC (Variable Position Counterweight)



360 Degree Rating



Boom Length



Extended Upper Boom Point Operating Radius
(see page 1)




Boom Angle
(see page 1)



Extended Upper Boom Point Elevation
(see page 1)



Lifting Capacities
(see page 1)



175 200 kg



360°

35,0 m			
m	°	m	kg
11,0	82,7	42,5	86 600
11,5	81,9	42,4	86 000
12,0	81,2	42,3	85 500
12,5	80,5	42,1	84 900
13,0	79,8	42,0	84 400
14,0	78,3	41,7	83 400
16,0	75,4	41,0	81 500
18,0	72,4	40,2	79 800
20,0	69,4	39,3	76 900
22,0	66,2	38,2	68 400
24,0	63,0	37,0	61 400
26,0	59,6	35,6	55 700
28,0	56,1	34,0	51 000
30,0	52,4	32,3	47 000
32,0	48,5	30,2	43 500
34,0	44,2	27,9	40 500
36,0	39,5	25,2	37 800

38,0 m			
m	°	m	kg
11,3	82,8	45,5	90 400
11,5	82,5	45,5	90 200
12,0	81,8	45,4	89 800
12,5	81,2	45,2	89 300
13,0	80,5	45,1	88 900
14,0	79,1	44,8	88 100
16,0	76,4	44,2	86 500
18,0	73,7	43,4	85 100
20,0	70,9	42,6	77 400
22,0	68,0	41,6	68 800
24,0	65,1	40,5	61 800
26,0	62,0	39,3	56 100
28,0	58,9	37,9	51 400
30,0	55,6	36,3	47 300
32,0	52,2	34,5	43 800
34,0	48,5	32,5	40 800
36,0	44,6	30,2	38 100
38,0	40,3	27,6	35 800

41,0 m			
m	°	m	kg
11,6	82,9	48,5	94 100
12,0	82,3	48,4	93 800
12,5	81,7	48,3	93 500
13,0	81,1	48,2	93 200
13,5	80,5	48,0	92 900
14,0	79,9	47,9	92 600
16,0	77,3	47,3	91 400
18,0	74,8	46,6	87 600
20,0	72,2	45,8	77 700
22,0	69,5	44,9	69 100
24,0	66,8	43,9	62 100
26,0	64,0	42,8	56 400
28,0	61,2	41,5	51 600
30,0	58,2	40,1	47 500
32,0	55,1	38,5	44 000
34,0	51,9	36,7	41 000
36,0	48,5	34,7	38 300
38,0	44,8	32,5	36 000
40,0	40,9	29,9	33 900

B45



175 200 kg



360°

44,0 m				47,0 m				50,0 m			
m	o	m	kg	m	o	m	kg	m	o	m	kg
11,9	82,9	51,5	97 600	12,5	82,7	54,4	100 000	12,8	82,8	57,4	100 000
12,0	82,8	51,5	97 600	13,0	82,1	54,3	100 000	13,0	82,6	57,4	100 000
12,5	82,2	51,4	97 400	13,5	81,6	54,2	100 000	13,5	82,0	57,3	100 000
13,0	81,6	51,3	97 100	14,0	81,0	54,1	99 900	14,0	81,5	57,1	100 000
13,5	81,1	51,1	96 900	14,5	80,5	54,0	99 600	14,5	81,0	57,0	100 000
14,0	80,5	51,0	96 700	16,0	78,8	53,6	97 900	16,0	79,4	56,7	98 700
16,0	78,1	50,5	95 800	18,0	76,6	53,0	89 400	18,0	77,3	56,1	90 000
18,0	75,7	49,8	88 900	20,0	74,3	52,3	78 500	20,0	75,2	55,4	78 900
20,0	73,3	49,1	78 200	22,0	72,0	51,5	69 800	22,0	73,0	54,7	70 200
22,0	70,8	48,2	69 500	24,0	69,6	50,6	62 800	24,0	70,8	53,9	63 100
24,0	68,3	47,3	62 500	26,0	67,3	49,6	57 000	26,0	68,6	53,0	57 300
26,0	65,8	46,3	56 700	28,0	64,8	48,5	52 200	28,0	66,3	51,9	52 500
28,0	63,1	45,1	51 900	30,0	62,3	47,3	48 100	30,0	64,0	50,8	48 400
30,0	60,4	43,8	47 800	32,0	59,7	46,0	44 500	32,0	61,6	49,6	44 800
32,0	57,6	42,3	44 300	34,0	57,1	44,6	41 500	34,0	59,1	48,3	41 700
34,0	54,7	40,7	41 300	36,0	54,3	42,9	38 800	36,0	56,6	46,8	39 000
36,0	51,7	39,0	38 600	38,0	51,4	41,2	36 400	38,0	54,0	45,2	36 600
38,0	48,5	37,0	36 200	40,0	48,4	39,2	34 300	40,0	51,3	43,4	34 100
40,0	45,1	34,8	34 100	42,0	45,2	37,0	32 000	42,0	48,4	41,4	31 600
42,0	41,4	32,2	32 000	44,0	41,8	34,5	29 700	44,0	45,4	39,2	29 300
44,0	37,4	29,3	29 700	46,0	38,1	31,7	27 600	46,0	42,2	36,8	27 200
								48,0	38,8	34,1	25 300



175 200 kg



360°

53,0 m			
m	o	m	kg
13,1	82,8	60,4	100 000
13,5	82,4	60,3	100 000
14,0	82,0	60,2	100 000
14,5	81,5	60,1	100 000
15,0	81,0	60,0	100 000
16,0	80,0	59,8	99 200
18,0	78,0	59,2	90 400
20,0	76,0	58,6	79 200
22,0	73,9	57,9	70 500
24,0	71,8	57,1	63 400
26,0	69,7	56,3	57 500
28,0	67,6	55,3	52 700
30,0	65,4	54,3	48 600
32,0	63,2	53,1	45 000
34,0	60,9	51,9	41 900
36,0	58,6	50,5	39 200
38,0	56,2	49,0	36 800
40,0	53,7	47,4	34 000
42,0	51,1	45,6	31 500
44,0	48,4	43,7	29 200
46,0	45,6	41,5	27 100
48,0	42,6	39,1	25 200
50,0	39,4	36,5	23 400

56,0 m			
m	o	m	kg
13,4	82,9	63,4	100 000
13,5	82,8	63,4	100 000
14,0	82,3	63,3	100 000
14,5	81,9	63,2	100 000
15,0	81,4	63,1	100 000
16,0	80,5	62,8	99 600
18,0	78,6	62,3	90 900
20,0	76,7	61,7	79 600
22,0	74,7	61,1	70 900
24,0	72,8	60,3	63 700
26,0	70,8	59,5	57 800
28,0	68,8	58,6	53 000
30,0	66,7	57,7	48 800
32,0	64,6	56,6	45 200
34,0	62,5	55,4	42 200
36,0	60,3	54,1	39 300
38,0	58,1	52,8	36 300
40,0	55,8	51,3	33 500
42,0	53,4	49,6	31 000
44,0	51,0	47,8	28 700
46,0	48,4	45,9	26 600
48,0	45,7	43,8	24 700
50,0	42,9	41,4	23 000
52,0	39,8	38,8	21 400
54,0	36,6	35,9	19 900

59,0 m			
m	o	m	kg
13,7	83,0	66,4	100 000
14,0	82,7	66,3	100 000
14,5	82,3	66,2	100 000
15,0	81,8	66,1	100 000
15,5	81,4	66,0	100 000
16,0	80,9	65,9	100 000
18,0	79,1	65,4	91 300
20,0	77,3	64,9	79 900
22,0	75,5	64,3	71 100
24,0	73,6	63,6	63 900
26,0	71,7	62,8	58 000
28,0	69,8	61,9	53 200
30,0	67,9	61,0	49 000
32,0	65,9	60,0	45 400
34,0	63,9	58,9	42 300
36,0	61,9	57,7	39 300
38,0	59,8	56,4	36 200
40,0	57,6	55,0	33 400
42,0	55,4	53,5	30 900
44,0	53,2	51,9	28 600
46,0	50,8	50,1	26 500
48,0	48,4	48,1	24 600
50,0	45,8	46,0	22 900
52,0	43,2	43,7	21 300
54,0	40,3	41,2	19 800
56,0	37,3	38,3	18 400



175 200 kg



360°

62,0 m			
m	o	m	kg
14,3	82,7	69,3	100 000
14,5	82,6	69,3	100 000
15,0	82,2	69,2	100 000
15,5	81,7	69,1	100 000
16,0	81,3	69,0	100 000
18,0	79,6	68,5	91 700
20,0	77,9	68,0	80 300
22,0	76,1	67,4	71 500
24,0	74,3	66,7	64 300
26,0	72,6	66,0	58 300
28,0	70,8	65,2	53 500
30,0	68,9	64,3	49 300
32,0	67,1	63,4	45 600
34,0	65,2	62,3	42 400
36,0	63,3	61,2	38 900
38,0	61,3	60,0	35 800
40,0	59,3	58,7	32 900
42,0	57,2	57,3	30 400
44,0	55,1	55,7	28 100
46,0	52,9	54,1	26 000
48,0	50,7	52,3	24 200
50,0	48,4	50,4	22 400
52,0	45,9	48,3	20 800
54,0	43,4	46,0	19 300
56,0	40,7	43,5	18 000
58,0	37,8	40,7	16 700

65,0 m			
m	o	m	kg
14,6	82,8	72,3	100 000
15,0	82,5	72,3	100 000
15,5	82,1	72,2	100 000
16,0	81,7	72,1	100 000
16,5	81,3	72,0	99 900
18,0	80,0	71,6	91 900
20,0	78,4	71,1	80 600
22,0	76,7	70,5	71 700
24,0	75,0	69,9	64 500
26,0	73,3	69,2	58 600
28,0	71,6	68,4	53 700
30,0	69,9	67,6	49 500
32,0	68,1	66,7	45 800
34,0	66,3	65,7	42 400
36,0	64,5	64,7	38 800
38,0	62,7	63,5	35 600
40,0	60,8	62,3	32 800
42,0	58,8	61,0	30 300
44,0	56,9	59,5	28 000
46,0	54,8	58,0	25 900
48,0	52,8	56,3	24 000
50,0	50,6	54,5	22 300
52,0	48,4	52,6	20 700
54,0	46,1	50,5	19 200
56,0	43,6	48,3	17 800
58,0	41,1	45,8	16 600
60,0	38,4	43,1	15 400

68,0 m			
m	o	m	kg
14,9	82,9	75,3	100 000
15,0	82,8	75,3	100 000
15,5	82,4	75,2	100 000
16,0	82,0	75,1	100 000
16,5	81,6	75,0	100 000
18,0	80,5	74,7	92 300
20,0	78,9	74,2	81 000
22,0	77,3	73,6	72 100
24,0	75,7	73,0	64 800
26,0	74,0	72,4	58 900
28,0	72,4	71,6	53 900
30,0	70,7	70,9	49 700
32,0	69,1	70,0	45 900
34,0	67,4	69,1	41 900
36,0	65,6	68,0	38 300
38,0	63,9	67,0	35 100
40,0	62,1	65,8	32 300
42,0	60,3	64,5	29 800
44,0	58,4	63,2	27 500
46,0	56,5	61,8	25 400
48,0	54,6	60,2	23 500
50,0	52,6	58,5	21 800
52,0	50,5	56,8	20 200
54,0	48,4	54,8	18 700
56,0	46,1	52,8	17 300
58,0	43,8	50,5	16 100
60,0	41,4	48,1	14 900
62,0	38,8	45,4	13 800
64,0	36,1	42,5	12 700



71,0 m			
m	o	m	kg
15,2	82,9	78,3	100 000
15,5	82,7	78,2	100 000
16,0	82,3	78,1	100 000
16,5	82,0	78,0	99 900
17,0	81,6	77,9	98 400
18,0	80,8	77,7	92 100
20,0	79,3	77,3	80 700
22,0	77,8	76,7	71 800
24,0	76,2	76,2	64 500
26,0	74,7	75,5	58 500
28,0	73,1	74,8	53 600
30,0	71,5	74,1	49 400
32,0	69,9	73,2	45 700
34,0	68,3	72,4	41 900
36,0	66,7	71,4	38 300
38,0	65,0	70,4	35 100
40,0	63,3	69,3	32 300
42,0	61,6	68,1	29 700
44,0	59,8	66,8	27 400
46,0	58,0	65,4	25 400
48,0	56,2	64,0	23 500
50,0	54,3	62,4	21 700
52,0	52,4	60,8	20 100
54,0	50,4	59,0	18 700
56,0	48,3	57,1	17 300
58,0	46,2	55,0	16 000
60,0	44,0	52,8	14 900
62,0	41,7	50,4	13 800
64,0	39,2	47,7	12 700
66,0	36,6	44,9	11 700

74,0 m			
m	o	m	kg
15,5	83,0	81,3	100 000
16,0	82,6	81,2	100 000
16,5	82,3	81,1	99 900
17,0	81,9	81,0	98 500
17,5	81,5	80,9	95 400
18,0	81,2	80,8	92 400
20,0	79,7	80,4	81 100
22,0	78,2	79,9	72 200
24,0	76,8	79,3	64 900
26,0	75,3	78,7	58 900
28,0	73,8	78,0	53 900
30,0	72,3	77,3	49 700
32,0	70,7	76,5	45 400
34,0	69,2	75,7	41 400
36,0	67,6	74,7	37 800
38,0	66,0	73,8	34 600
40,0	64,4	72,7	31 800
42,0	62,8	71,6	29 200
44,0	61,1	70,4	26 900
46,0	59,4	69,1	24 800
48,0	57,7	67,7	23 000
50,0	55,9	66,2	21 200
52,0	54,1	64,7	19 600
54,0	52,2	63,0	18 200
56,0	50,3	61,2	16 800
58,0	48,3	59,3	15 500
60,0	46,3	57,3	14 300
62,0	44,2	55,1	13 200
64,0	42,0	52,7	12 200
66,0	39,6	50,1	11 200
68,0	37,2	47,3	10 300

77,0 m			
m	o	m	kg
16,2	82,8	84,2	100 000
16,5	82,6	84,1	99 900
17,0	82,2	84,1	99 500
17,5	81,9	84,0	96 300
18,0	81,5	83,9	92 900
20,0	80,1	83,4	81 400
22,0	78,7	82,9	72 400
24,0	77,3	82,4	65 100
26,0	75,8	81,8	59 100
28,0	74,4	81,2	54 100
30,0	72,9	80,5	49 800
32,0	71,5	79,7	45 300
34,0	70,0	78,9	41 200
36,0	68,5	78,0	37 600
38,0	66,9	77,1	34 400
40,0	65,4	76,1	31 600
42,0	63,8	75,0	29 100
44,0	62,3	73,9	26 800
46,0	60,6	72,6	24 700
48,0	59,0	71,3	22 800
50,0	57,3	69,9	21 000
52,0	55,6	68,5	19 400
54,0	53,9	66,9	18 000
56,0	52,1	65,2	16 600
58,0	50,2	63,4	15 400
60,0	48,3	61,5	14 200
62,0	46,4	59,5	13 100
64,0	44,3	57,3	12 000
66,0	42,2	55,0	11 100
68,0	40,0	52,4	10 200
70,0	37,6	49,7	9 300



175 200 kg



80,0 m			
m	o	m	kg
16,5	82,8	87,2	97 800
17,0	82,5	87,1	97 400
17,5	82,1	87,0	96 500
18,0	81,8	86,9	93 500
18,5	81,5	86,8	90 400
20,0	80,4	86,5	81 900
22,0	79,1	86,1	72 900
24,0	77,7	85,5	65 500
26,0	76,3	85,0	59 500
28,0	74,9	84,4	54 400
30,0	73,5	83,7	49 400
32,0	72,1	83,0	44 700
34,0	70,7	82,2	40 600
36,0	69,3	81,3	37 000
38,0	67,8	80,4	33 800
40,0	66,3	79,5	30 900
42,0	64,8	78,4	28 400
44,0	63,3	77,3	26 100
46,0	61,8	76,2	24 000
48,0	60,2	74,9	22 100
50,0	58,6	73,6	20 300
52,0	57,0	72,2	18 700
54,0	55,4	70,7	17 300
56,0	53,7	69,2	15 900
58,0	52,0	67,5	14 600
60,0	50,2	65,7	13 400
62,0	48,3	63,8	12 300
64,0	46,5	61,8	11 300
66,0	44,5	59,6	10 300
68,0	42,5	57,3	9 400
70,0	40,3	54,8	8 600
72,0	38,1	52,0	7 700

83,0 m			
m	o	m	kg
16,8	82,9	90,2	95 100
17,0	82,7	90,1	94 900
17,5	82,4	90,1	94 600
18,0	82,1	90,0	93 500
18,5	81,8	89,9	90 400
20,0	80,8	89,6	82 000
22,0	79,5	89,1	72 900
24,0	78,1	88,6	65 600
26,0	76,8	88,1	59 500
28,0	75,5	87,5	54 500
30,0	74,1	86,8	49 700
32,0	72,8	86,1	45 000
34,0	71,4	85,4	40 900
36,0	70,0	84,6	37 300
38,0	68,6	83,7	34 100
40,0	67,2	82,8	31 300
42,0	65,8	81,8	28 700
44,0	64,3	80,8	26 400
46,0	62,8	79,6	24 300
48,0	61,4	78,5	22 400
50,0	59,8	77,2	20 700
52,0	58,3	75,9	19 100
54,0	56,7	74,5	17 600
56,0	55,1	73,0	16 300
58,0	53,5	71,4	15 000
60,0	51,8	69,7	13 800
62,0	50,1	67,9	12 700
64,0	48,3	66,0	11 700
66,0	46,5	64,0	10 700
68,0	44,6	61,8	9 800
70,0	42,7	59,5	9 000
72,0	40,6	57,1	8 100
74,0	38,5	54,4	7 400
76,0	36,2	51,5	6 600

86,0 m			
m	o	m	kg
17,1	82,9	93,2	89 000
17,5	82,7	93,1	88 500
18,0	82,3	93,0	88 000
18,5	82,0	92,9	87 100
19,0	81,7	92,8	85 700
20,0	81,1	92,6	82 400
22,0	79,8	92,2	73 300
24,0	78,5	91,7	65 900
26,0	77,3	91,2	59 800
28,0	76,0	90,6	54 500
30,0	74,7	90,0	49 300
32,0	73,4	89,3	44 500
34,0	72,0	88,6	40 400
36,0	70,7	87,8	36 800
38,0	69,4	87,0	33 600
40,0	68,0	86,1	30 700
42,0	66,6	85,2	28 200
44,0	65,2	84,2	25 900
46,0	63,8	83,1	23 800
48,0	62,4	82,0	21 900
50,0	61,0	80,8	20 100
52,0	59,5	79,5	18 500
54,0	58,0	78,2	17 100
56,0	56,5	76,7	15 700
58,0	54,9	75,2	14 400
60,0	53,3	73,6	13 300
62,0	51,7	72,0	12 200
64,0	50,0	70,2	11 100
66,0	48,3	68,3	10 200
68,0	46,6	66,3	9 200
70,0	44,8	64,1	8 400
72,0	42,9	61,8	7 600
74,0	40,9	59,4	6 800
76,0	38,9	56,8	6 100
78,0	36,7	53,9	5 400

MLC300 S-2

ASME B30.5



175 200 kg



17,4	83,0	96,2	83 300
17,5	82,9	96,1	83 100
18,0	82,6	96,1	82 500
18,5	82,3	96,0	82 000
19,0	82,0	95,9	81 400
20,0	81,4	95,7	80 100
22,0	80,1	95,3	73 500
24,0	78,9	94,8	66 100
26,0	77,7	94,3	60 000
28,0	76,4	93,7	54 600
30,0	75,2	93,1	49 100
32,0	73,9	92,5	44 300
34,0	72,6	91,8	40 200
36,0	71,3	91,0	36 600
38,0	70,0	90,2	33 400
40,0	68,7	89,4	30 500
42,0	67,4	88,5	28 000
44,0	66,1	87,5	25 700
46,0	64,7	86,5	23 600
48,0	63,4	85,4	21 700
50,0	62,0	84,2	19 900
52,0	60,6	83,0	18 300
54,0	59,1	81,8	16 900
56,0	57,7	80,4	15 500
58,0	56,2	79,0	14 200
60,0	54,7	77,5	13 100
62,0	53,2	75,9	12 000
64,0	51,6	74,2	10 900
66,0	50,0	72,4	10 000
68,0	48,3	70,5	9 000
70,0	46,6	68,5	8 200
72,0	44,9	66,4	7 400
74,0	43,0	64,1	6 600
76,0	41,2	61,7	5 900
78,0	39,2	59,1	5 200