



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

LIFTING CAPACITIES:

- Lifting capacities are for a crawler crane when operating on a barge. Machine to operate on a firm uniformly supporting surface with machine list not to exceed degrees noted. The user must limit rated loads to allow for adverse conditions (such as soft or uneven ground, out-of-level conditions, wind, side loads, pendulum action, jerking or sudden stopping of loads, inexperience of personnel, and multiple machine lifts).
- Capacities do not exceed 75% of minimum tipping loads. Capacities based on factors other than machine stability such as structural competence are shown by asterisk * in the charts.
- Attempting to lift more than rated loads may cause machine to tip or collapse. Do not tip machine to determine capacity.
- Do not attempt to lift where no radius on load chart is listed as crane may tip or collapse.
- Weight of hooks, hook blocks, slings and other lifting devices beneath boom point sheaves are part of the total load. Their total weight must be subtracted from the rated load to obtain the weight that can be lifted.
- Load radius is horizontal distance from axis of rotation to center of gravity of the freely suspended load. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of radius. In all cases, operating radius shall govern capacity.
- Least stable position is over the side.
- Boom point elevation is vertical distance from barge deck to centerline of boom point shaft.
- In all cases, upper boom point capacities cannot exceed those listed for Liftcrane Boom capacity reduced by 400 kg.
- Lifting capacities listed apply only to the machine as originally manufactured and designed. Modifications to this machine or use of equipment other than that specified can reduce operating capacity.
- Machine travel with load (pick and carry) is not permitted.
- Jib installation is prohibited when crane is on a barge.

Hoist Reeving for Upper Boom Point

No. of Parts of Line	1	2
Maximum Loads (kg)	11 300	22 600

OPERATING CONDITION:

- The machine must be reeved and set-up as stated in the Operator Manual. If this manual is missing, obtain replacement.
 - Boom backstops are required for all boom lengths.
 - Gantry must be fully raised position for all operation.
 - Crawlers must be fully extended and be locked in position.
 - Crane shall be positively secured to prevent shifting.
 - Refer to operator manual for operating guidelines.

Maximum Boom Lengths Lifted Unassisted
Over End of Crawlers
70,1 m (a)
Load block, hook and weight ball on barge deck at start. (a) Upper boom point cannot be attached on 70,1 m boom.

- See Operator Manual Section 6 for Wire Rope Specifications.
- Machine equipped with 6 770 mm crawlers, 900 mm treads, 10 parts of boom hoist reeving, 34 600 kg crane counterweight and 6 500 kg carbody counterweight.

Hoist Reeving for Main Boom Loads

No. of Parts of Line	1	2	3	4	5
Maximum Loads (kg)	11 300	22 600	34 000	45 300	56 700

No. of Parts of Line	6	7	8	9	10
Maximum Loads (kg)	68 000	79 300	90 700	102 000	110 000

Operation of this equipment in excess of rated loads or disregard of instruction voids the warranty.



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
15,2 m Boom							
3,6	81,4	17,2	110 000 *				3,6
4,0	80,0	17,2	99 000 *				4,0
4,5	78,1	17,1	88 200 *	86 600 *			4,5
5,0	76,2	16,9	77 700 *	77 700 *			5,0
5,5	74,2	16,8	67 800 *	67 800 *	62 800		5,5
6,0	72,2	16,6	62 200 *	62 200 *	59 000		6,0
7,0	68,2	16,3	53 300 *	51 500	48 600	45 500	7,0
8,0	64,0	15,8	44 600	42 600	40 600	38 900	8,0
9,0	59,8	15,2	37 600	36 200	34 800	33 700	9,0
10,0	55,2	14,6	32 500	31 500	30 500	29 600	10,0
11,5	47,6	13,1	26 600	26 000	25 400	24 800	11,5
18,3 m Boom							
4,1	81,4	20,2	95 200 *				4,1
4,5	80,1	20,2	87 600 *				4,5
5,0	78,5	20,1	77 700 *	75 300 *			5,0
5,5	76,9	20,0	67 800 *	67 800 *			5,5
6,0	75,3	19,8	62 200 *	62 200 *			6,0
7,0	72,0	19,5	53 200 *	50 800	46 300		7,0
8,0	68,7	19,1	44 400	42 000	39 800	36 900	8,0
9,0	65,2	18,7	37 500	35 700	34 200	32 600	9,0
10,0	61,7	18,2	32 400	31 100	29 900	28 800	10,0
12,0	54,2	16,9	25 300	24 600	23 800	23 200	12,0
13,7	47,2	15,3	21 100	20 700	20 200	19 700	13,7
21,3 m Boom							
4,5	81,4	23,3	86 100 *				4,5
5,0	80,1	23,2	77 700 *				5,0
5,5	78,8	23,1	67 800 *	64 700			5,5
6,0	77,4	23,0	62 200 *	60 800			6,0
7,0	74,6	22,7	53 200 *	50 200			7,0
8,0	71,8	22,4	44 400	41 500	38 700		8,0
9,0	69,0	22,0	37 400	35 400	33 500	31 100	9,0
10,0	66,0	21,6	32 300	30 800	29 400	28 000	10,0
12,0	59,9	20,5	25 200	24 300	23 400	22 500	12,0
14,0	53,5	19,2	20 500	20 000	19 300	18 800	14,0
16,0	46,3	17,5	17 300	16 900	16 600	16 200	16,0
16,7	43,5	16,2	16 200	15 900	15 600	15 300	16,7



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
24,4 m Boom							
5,0	81,4	26,3	77 500 *				5,0
5,5	80,2	26,2	67 800 *				5,5
6,0	79,0	26,1	62 200 *				6,0
7,0	76,6	25,9	53 100 *	49 300			7,0
8,0	74,2	25,6	44 200	41 000			8,0
9,0	71,7	25,3	37 300	34 900	32 600		9,0
10,0	69,2	24,9	32 100	30 300	28 700	26 500	10,0
12,0	64,1	24,0	25 100	24 000	22 900	22 000	12,0
14,0	58,6	22,9	20 400	19 700	19 000	18 400	14,0
16,0	52,9	21,5	17 100	16 700	16 200	15 800	16,0
18,0	46,7	19,8	14 600	14 400	14 000	13 700	18,0
19,8	40,5	17,3	12 900	12 700	12 500	12 200	19,8
27,4 m Boom							
5,4	81,4	29,3	68 000 *				5,4
5,5	81,3	29,3	67 800 *				5,5
6,0	80,2	29,2	61 900 *				6,0
7,0	78,1	29,0	53 100 *				7,0
8,0	76,0	28,8	44 200	40 600			8,0
9,0	73,8	28,5	37 300	34 600	30 800		9,0
10,0	71,6	28,1	32 100	30 100	28 300		10,0
12,0	67,1	27,4	25 000	23 800	22 500	21 600	12,0
14,0	62,5	26,4	20 300	19 600	18 700	18 000	14,0
16,0	57,6	25,2	17 100	16 600	16 000	15 400	16,0
18,0	52,5	23,8	14 600	14 200	13 800	13 400	18,0
20,0	47,0	22,1	12 700	12 400	12 100	11 800	20,0
21,3	43,0	21,2	11 600	11 400	11 200	11 000	21,3
30,5 m Boom							
5,9	81,4	32,3	62 300 *				5,9
6,0	81,2	32,3	61 900 *				6,0
7,0	79,3	32,1	53 000 *				7,0
8,0	77,4	31,9	44 200	40 000			8,0
9,0	75,4	31,6	37 200	34 200			9,0
10,0	73,5	31,4	32 000	29 800	26 900		10,0
12,0	69,5	30,7	24 900	23 500	22 300	20 300	12,0
14,0	65,5	29,8	20 200	19 300	18 400	17 600	14,0
16,0	61,2	28,8	16 900	16 300	15 700	15 100	16,0
18,0	56,8	27,6	14 500	14 000	13 500	13 100	18,0
20,0	52,1	26,1	12 500	12 100	11 800	11 500	20,0
22,0	47,2	24,4	11 000	10 700	10 500	10 200	22,0
24,0	41,7	22,3	9 700	9 600	9 400	9 200	24,0
24,3	40,7	22,1	9 500	9 400	9 200	9 000	24,3



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
33,5 m Boom							
6,3	81,4	35,3	58 300 *				6,3
7,0	80,3	35,2	52 900 *				7,0
8,0	78,5	35,0	44 100				8,0
9,0	76,8	34,8	37 100	33 800			9,0
10,0	75,0	34,5	31 900	29 500			10,0
12,0	71,5	33,9	24 800	23 200	21 900		12,0
14,0	67,8	33,1	20 100	19 100	18 100	17 000	14,0
16,0	64,0	32,2	16 800	16 100	15 400	14 800	16,0
18,0	60,1	31,2	14 300	13 800	13 300	12 800	18,0
20,0	56,1	29,9	12 400	12 000	11 600	11 200	20,0
22,0	51,8	28,4	10 900	10 600	10 300	10 000	22,0
24,0	47,3	26,7	9 700	9 400	9 200	8 900	24,0
25,9	42,7	24,9	8 600	8 500	8 300	8 200	25,9
36,6 m Boom							
6,8	81,4	38,3	54 800 *				6,8
7,0	81,1	38,3	53 200 *				7,0
8,0	79,5	38,1	44 100				8,0
9,0	77,9	37,9	37 100				9,0
10,0	76,3	37,7	31 900	29 300			10,0
12,0	73,1	37,1	24 800	23 100	21 100		12,0
14,0	69,8	36,4	20 100	19 000	17 900	15 800	14,0
16,0	66,4	35,6	16 800	16 000	15 200	14 300	16,0
18,0	62,9	34,6	14 300	13 700	13 100	12 600	18,0
20,0	59,3	33,5	12 400	11 900	11 500	11 100	20,0
22,0	55,5	32,2	10 900	10 500	10 100	9 800	22,0
24,0	51,6	30,7	9 600	9 300	9 000	8 800	24,0
26,0	47,5	29,0	8 600	8 300	8 100	7 900	26,0
28,0	43,0	27,0	7 700	7 500	7 400	7 200	28,0
28,9	40,8	25,9	7 300	7 200	7 000	6 900	28,9



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
39,6 m Boom							
7,2	81,4	41,4	45 300 *				7,2
8,0	80,3	41,2	44 000				8,0
9,0	78,9	41,0	37 000				9,0
10,0	77,4	40,8	31 800	28 900			10,0
12,0	74,4	40,3	24 700	22 900			12,0
14,0	71,3	39,7	20 000	18 800	17 700		14,0
16,0	68,3	38,9	16 700	15 900	15 000	13 700	16,0
18,0	65,1	38,0	14 200	13 500	12 900	12 300	18,0
20,0	61,8	37,0	12 300	11 800	11 300	10 800	20,0
22,0	58,5	35,9	10 800	10 400	9 900	9 600	22,0
24,0	55,0	34,5	9 500	9 200	8 900	8 600	24,0
26,0	51,4	33,0	8 500	8 200	8 000	7 800	26,0
28,0	47,6	31,3	7 600	7 400	7 200	7 000	28,0
30,0	43,5	29,3	6 800	6 700	6 500	6 400	30,0
32,0	39,1	27,0	6 200	6 100	6 000	5 900	32,0
42,7 m Boom							
7,7	81,4	44,4	45 300 *				7,7
8,0	81,0	44,3	43 900				8,0
9,0	79,6	44,1	36 900				9,0
10,0	78,3	43,9	31 700				10,0
12,0	75,5	43,5	24 600	22 600			12,0
14,0	72,7	42,9	19 900	18 600	16 800		14,0
16,0	69,9	42,2	16 600	15 700	14 700		16,0
18,0	67,0	41,4	14 100	13 400	12 600	11 900	18,0
20,0	64,1	40,5	12 100	11 600	11 000	10 500	20,0
22,0	61,0	39,4	10 600	10 200	9 800	9 400	22,0
24,0	57,9	38,2	9 300	9 000	8 600	8 300	24,0
26,0	54,6	36,9	8 300	8 000	7 700	7 500	26,0
28,0	51,2	35,3	7 400	7 200	7 000	6 800	28,0
30,0	47,7	33,6	6 700	6 500	6 300	6 100	30,0
32,0	44,0	31,6	6 000	5 900	5 800	5 600	32,0
34,0	39,9	29,4	5 500	5 400	5 200	5 200	34,0
35,0	37,7	28,1	5 200	5 100	5 000	4 900	35,0



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
45,7 m Boom							
8,1	81,4	47,4	42 000				8,1
9,0	80,3	47,2	36 800				9,0
10,0	79,1	47,0	31 600				10,0
12,0	76,5	46,6	24 400	22 300			12,0
14,0	73,9	46,1	19 700	18 300	15 400		14,0
16,0	71,3	45,4	16 400	15 400	14 200		16,0
18,0	68,6	44,7	13 900	13 100	12 400		18,0
20,0	65,9	43,8	12 000	11 400	10 800	10 200	20,0
22,0	63,1	42,9	10 500	9 900	9 500	9 100	22,0
24,0	60,2	41,8	9 200	8 800	8 400	8 100	24,0
26,0	57,3	40,5	8 100	7 800	7 500	7 300	26,0
28,0	54,3	39,2	7 300	7 000	6 800	6 600	28,0
30,0	51,1	37,6	6 500	6 300	6 100	5 900	30,0
32,0	47,8	35,9	5 900	5 700	5 500	5 300	32,0
34,0	44,3	33,9	5 300	5 200	5 000	4 900	34,0
36,0	40,5	31,7	4 800	4 700	4 600	4 500	36,0
36,5	39,5	30,8	4 700	4 600	4 500	4 400	36,5
48,8 m Boom							
8,6	81,4	50,4	34 000 *				8,6
9,0	80,9	50,3	34 000 *				9,0
10,0	79,8	50,1	31 600				10,0
12,0	77,4	49,7	24 500	22 000			12,0
14,0	74,9	49,2	19 800	18 200			14,0
16,0	72,5	48,6	16 400	15 400	13 500		16,0
18,0	70,0	47,9	14 000	13 100	12 300		18,0
20,0	67,5	47,2	12 000	11 300	10 700	9 700	20,0
22,0	64,9	46,3	10 500	9 900	9 400	9 000	22,0
24,0	62,3	45,3	9 200	8 800	8 400	8 100	24,0
26,0	59,5	44,1	8 200	7 800	7 500	7 200	26,0
28,0	56,8	42,9	7 300	7 000	6 700	6 500	28,0
30,0	53,9	41,5	6 500	6 300	6 100	5 900	30,0
32,0	51,0	39,9	5 900	5 700	5 500	5 300	32,0
34,0	47,8	38,2	5 300	5 100	5 000	4 800	34,0
36,0	44,6	36,3	4 800	4 700	4 500	4 400	36,0
38,0	41,1	34,1	4 400	4 300	4 100	4 100	38,0
39,6	38,1	31,4	4 100	3 900	3 900	3 800	39,6



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
51,8 m Boom							
9,1	81,4	53,4	34 000 *				9,1
10,0	80,4	53,2	31 500				10,0
12,0	78,1	52,9	24 300	20 800			12,0
14,0	75,8	52,4	19 600	18 000			14,0
16,0	73,6	51,8	16 300	15 200			16,0
18,0	71,2	51,2	13 800	12 900	11 800		18,0
20,0	68,8	50,4	11 800	11 100	10 500	8 800	20,0
22,0	66,5	49,6	10 300	9 700	9 200	8 500	22,0
24,0	64,0	48,7	9 100	8 600	8 200	7 700	24,0
26,0	61,5	47,6	8 000	7 600	7 300	6 900	26,0
28,0	59,0	46,5	7 100	6 800	6 500	6 300	28,0
30,0	56,4	45,2	6 400	6 100	5 900	5 600	30,0
32,0	53,7	43,8	5 700	5 500	5 300	5 100	32,0
34,0	50,9	42,2	5 100	5 000	4 800	4 700	34,0
36,0	47,9	40,5	4 700	4 500	4 400	4 200	36,0
38,0	44,8	38,6	4 200	4 100	4 000	3 900	38,0
40,0	41,6	36,4	3 900	3 700	3 600	3 500	40,0
42,6	37,0	33,5	3 300	3 300	3 200	3 100	42,6
54,9 m Boom							
9,5	81,4	56,4	33 200				9,5
10,0	80,9	56,3	31 400				10,0
12,0	78,8	56,0	24 200				12,0
14,0	76,7	55,5	19 500	17 700			14,0
16,0	74,5	55,0	16 100	14 900			16,0
18,0	72,3	54,4	13 600	12 700	11 000		18,0
20,0	70,0	53,7	11 700	11 000	10 200	8 000	20,0
22,0	67,8	52,9	10 100	9 600	9 000	7 800	22,0
24,0	65,6	52,1	8 800	8 400	8 000	7 400	24,0
26,0	63,2	51,1	7 900	7 500	7 100	6 800	26,0
28,0	60,9	50,0	7 000	6 700	6 300	6 000	28,0
30,0	58,4	48,8	6 200	5 900	5 600	5 400	30,0
32,0	56,0	47,5	5 500	5 300	5 100	4 900	32,0
34,0	53,4	46,1	5 000	4 800	4 600	4 400	34,0
36,0	50,7	44,5	4 500	4 300	4 200	4 000	36,0
38,0	48,0	42,8	4 100	3 900	3 700	3 600	38,0
40,0	45,1	40,9	3 600	3 500	3 400	3 300	40,0
44,0	38,8	36,4	3 000	2 900	2 800	2 700	44,0
45,7	35,9	33,6	2 700	2 700	2 600	2 500	45,7



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
57,9 m Boom							
10,0	81,4	59,4	30 000 *				10,0
12,0	79,3	59,1	24 100				12,0
14,0	77,4	58,7	19 400	16 700			14,0
16,0	75,3	58,2	16 000	14 600			16,0
18,0	73,3	57,6	13 500	12 500			18,0
20,0	71,2	56,9	11 600	10 700	9 600	7 100	20,0
22,0	69,1	56,2	10 000	9 400	8 800	6 900	22,0
24,0	67,0	55,4	8 800	8 200	7 800	6 800	24,0
26,0	64,7	54,5	7 700	7 300	6 900	6 500	26,0
28,0	62,5	53,5	6 800	6 500	6 200	5 800	28,0
30,0	60,3	52,4	6 100	5 800	5 500	5 200	30,0
32,0	58,0	51,2	5 400	5 100	4 900	4 700	32,0
34,0	55,6	49,9	4 800	4 600	4 400	4 200	34,0
36,0	53,2	48,4	4 300	4 100	4 000	3 700	36,0
38,0	50,7	46,8	4 000	3 700	3 600	3 400	38,0
40,0	48,0	45,1	3 500	3 300	3 200	3 000	40,0
44,0	42,4	41,1	2 800	2 700	2 600	2 500	44,0
47,2	37,4	40,1	2 300	2 300	2 200	2 100	47,2
61,0 m Boom							
10,4	81,4	62,4	22 600 *				10,4
12,0	79,9	62,2	22 600 *				12,0
14,0	78,0	61,8	19 400	15 400			14,0
16,0	76,1	61,3	16 000	14 400			16,0
18,0	74,1	60,8	13 600	12 500			18,0
20,0	72,2	60,2	11 600	10 800	8 800		20,0
22,0	70,2	59,5	10 000	9 400	8 500	6 300	22,0
24,0	68,1	58,7	8 800	8 200	7 700	6 100	24,0
26,0	66,1	57,8	7 700	7 200	6 800	5 900	26,0
28,0	64,1	56,9	6 800	6 500	6 100	5 700	28,0
30,0	61,9	55,9	6 100	5 800	5 500	5 200	30,0
32,0	59,8	54,7	5 400	5 200	4 900	4 700	32,0
34,0	57,5	53,5	4 900	4 600	4 400	4 200	34,0
36,0	55,3	52,2	4 400	4 200	3 900	3 700	36,0
38,0	53,0	50,7	4 000	3 700	3 500	3 300	38,0
40,0	50,6	49,1	3 500	3 300	3 100	3 000	40,0
44,0	45,5	45,5	2 800	2 600	2 500	2 400	44,0
48,0	39,9	41,1	2 100	2 000	1 900	1 900	48,0
50,2	36,5	38,6	1 800	1 800	1 700	1 600	50,2



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
64,0 m Boom							
10,9	81,4	65,5	22 600 *				10,9
12,0	80,4	65,3	22 600 *				12,0
14,0	78,6	64,9	19 300				14,0
16,0	76,8	64,5	15 900				16,0
18,0	74,9	63,9	13 400	12 200			18,0
20,0	73,0	63,4	11 500	10 600	8 000		20,0
22,0	71,1	62,7	9 900	9 200	7 800		22,0
24,0	69,2	62,0	8 700	8 100	7 400	5 400	24,0
26,0	67,3	61,2	7 600	7 100	6 700	5 200	26,0
28,0	65,4	60,3	6 700	6 300	5 900	5 100	28,0
30,0	63,3	59,3	5 900	5 600	5 300	4 900	30,0
32,0	61,4	58,3	5 300	5 000	4 700	4 400	32,0
34,0	59,3	57,1	4 700	4 500	4 200	4 000	34,0
36,0	57,2	55,9	4 200	4 000	3 700	3 600	36,0
38,0	55,0	54,5	3 700	3 500	3 300	3 100	38,0
40,0	52,7	53,0	3 300	3 100	2 900	2 700	40,0
44,0	48,1	49,7	2 600	2 400	2 200	2 100	44,0
48,0	43,1	45,8	1 900	1 800	1 700	1 600	48,0
48,7	42,1	43,6	1 800	1 700	1 600	1 500	48,7
67,1 m Boom							
11,3	81,4	68,5	21 800 *				11,3
12,0	80,8	68,4	21 300 *				12,0
14,0	79,1	68,0	19 100				14,0
16,0	77,4	67,6	15 800				16,0
18,0	75,6	67,1	13 300				18,0
20,0	73,8	66,5	11 300	10 400			20,0
22,0	72,0	65,9	9 800	9 000	7 000		22,0
24,0	70,2	65,2	8 400	7 900	6 800	4 800	24,0
26,0	68,4	64,5	7 500	7 000	6 400	4 700	26,0
28,0	66,5	63,6	6 600	6 200	5 800	4 500	28,0
30,0	64,6	62,7	5 800	5 400	5 100	4 300	30,0
32,0	62,8	61,7	5 100	4 800	4 600	4 200	32,0
34,0	60,8	60,6	4 600	4 300	4 100	3 800	34,0
36,0	58,8	59,5	4 100	3 800	3 600	3 300	36,0
38,0	56,8	58,2	3 600	3 400	3 100	2 900	38,0
40,0	54,8	56,8	3 100	3 000	2 700	2 600	40,0
44,0	50,4	53,7	2 300	2 200	2 100	2 000	44,0
47,2	46,8	51,3	1 900	1 800	1 700	1 600	47,2



Liftcrane Boom Capacities

34 600 kg Crane Counterweight
6 500 kg Carbody Counterweight
Crawler Crane on a Barge
0 Degree through 3 Degree Crane List
Extended Position Crawlers
360 Degree Rating

12000-1

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	0 Degree Crane List	1 Degree Crane List	2 Degree Crane List	3 Degree Crane List	Load Radius (m)
70,1 m Boom							
11,8	81,4	71,5	19 500 *				11,8
12,0	81,2	71,5	19 400 *				12,0
14,0	79,6	71,1	17 900 *				14,0
16,0	77,9	70,7	15 600				16,0
18,0	76,2	70,2	13 100	10 900			18,0
20,0	74,5	69,7	11 200	10 100			20,0
22,0	72,8	69,1	9 600	8 900	6 200		22,0
24,0	71,1	68,5	8 300	7 700	6 100		24,0
26,0	69,4	67,7	7 300	6 800	5 900	4 100	26,0
28,0	67,6	66,9	6 400	6 000	5 500	3 900	28,0
30,0	65,8	66,1	5 700	5 300	4 900	3 700	30,0
32,0	64,1	65,1	5 000	4 700	4 400	3 600	32,0
34,0	62,2	64,1	4 400	4 100	3 800	3 400	34,0
36,0	60,3	63,0	3 900	3 600	3 400	3 100	36,0
38,0	58,4	61,8	3 300	3 100	2 900	2 700	38,0
40,0	56,5	60,5	3 000	2 700	2 500	2 300	40,0
44,0	52,5	57,6	2 200	2 000	1 900	1 700	44,0
45,7	50,7	56,7	1 900	1 800	1 700	1 500	45,7