



POTAIN®

Igo 24-19


EN 14439:2025 C25-D25
EN 14439:2025 C50-D50




Courbes de charges / Lastkurven / Load curves / Curvas de cargas / Curve di carico
Curvas de carga / Кривые нагрузок



		2,8	▶	10,2	11,2	12	13	14	15	16	17	18	19	20	21	22	23	24	m
24 m				2000	-	1640	1480	1350	1250	1150	1070	1000	930	880	830	780	740	700	kg
					2000	1840	1670	1530	1410	1300	1210	1130	1060	1000	940	890	840	800	kg P+
		2,8	▶		10,9	12	13	14	15	16	17	18	19	20	21	m			
21 m					2000	1780	1610	1470	1350	1250	1160	1090	1020	960	900	kg			
						2000	1810	1660	1530	1410	1310	1230	1150	1080	1020	kg P+			
		2,8	▶		11,3	12	12,4	m											
24 - 21 m					2000	1870	1800	kg											
						2000	kg P+												



24 m		2,8	►					15,3	16	17	18	19	20	21	22	23	23,8	m
								1200	1140	1060	990	920	870	820	770	730	700	kg
21 m		2,8	►					16,4	17	18	19	20	20,7	m				
								1200	1150	1070	1000	940	900	kg				





24 m		2,8	►															22,8	m
																		700	kg
21 m		2,8	►															19,9	m
																		700	kg


230 V - 50 Hz 400 V - 50 Hz 480 V - 60 Hz									ch - PS hp	kW
	10 LVF 10 Optima	230 V 	m/min	1,7	5,5	10,5	14,4	17	3,3	2,4
		20 A 	kg	2000	2000	1000	700	500		
		230 V 	m/min	1,7	9,5	18,5	25,3	30	5,2	3,8
		32 A 	kg	2000	2000	1000	700	500		
		400 V 	m/min	1,7	15,6	31,2	46,4	49,3	10	7,5
		480 V 	kg	2000	2000	1000	700	500		
	1 DVF 4 Optima		m/min	7	25	31	36	1,5	1,1	
			kg	2000	2000	1000	700			
	RVF 20		tr/min U/min rpm	0 → 1					1,5	1,1

 IEC 60204-32	
230 V (+10% -10%) 50 Hz 400 V (+10% -10%) 50 Hz 480 V (+6% -10%) 60Hz	230 V 20 A : 4,6 kVA 230 V 32 A : 7,4 kVA 400 V / 480 V : 9 → 6 kVA 


10 LVF 10 Optima



Montage / Montage / Erection / Montaje / Montaggio
Montagem / Монтаж




Transport / Transport / Transport / Transporte / Trasporto
Transporte / Транспортировка



	km/h	D (m)	H (m)	I1 (m)	I2 (m)	P / P1 / P2 (kg)
DS62/S81	10	0,39/0,24	2,97/2,81	2,48	2,2	1
DS65/S65	25	0,4/0,26	2,96/2,81	2,48	2	
..... / 1						

40' Open Top



	FR	DE	EN	ES	IT	PT	RU
R	Rayon de giration	Schwenk radius	Rear slewing radius	Radio de giro	Raggio di rotazione	Raio de rotação	Задний габарит
1	Nous consulter	Auf Anfrage	Consult us	Consultarnos	Consultateci	Consultar-nos	Проконсультируйтесь у нас
●	Réactions en service	Reaktionskräfte in Betrieb	Reactions in service	Reacciones en servicio	Reazioni in servizio	Reacções em serviço	Реакция при работе
■	Réactions hors service	Reaktionskräfte außer Betrieb	Reactions out of service	Reacciones fuera de servicio	Reazioni fuori servizio	Reacções fora de serviço	Реакция в покое
🏠	Poids à vide, sans lest, sans trains de transport, avec flèche maxi. et hauteur standard	Gewicht ohne Last, ohne Ballast, ohne Transportachsen, mit max. Auslager und Standardhöhe	Weight without load, without ballast, without transport axes, with max. jib and standard height	Peso en vacío, sin lastre, sin trenes de transporte con flecha y altura estándar	Peso a vuoto, senza zavorra, senza assali di trasporto, con braccio max e altezza standard	Peso em vazio, sem lastro, sem eixos de transporte com lança máxima e altura standard	Вес без груза, без балласта, без осей для транспортировки, с максимальным вылетом стрелы и стандартной высотой
⚖️	Poids total du lest	Ballast-Gesamtgewicht	Total ballast weight	Peso total del lastre	Peso totale della zavorra	Peso total do lastro	Общий вес балласта
P+	Fonction Potain Plus : Courbes de charges Plus	Funktion Potain Plus: Plus-Lastkurven	Potain Plus function: Plus load curves	Función Potain Plus: Diagrama de cargas Plus	Funzione Potain Plus: Curve di carico Plus	Função Potain Plus: Diagrama de cargas Plus	Функция контроля мощности Potain Plus: Диаграммы грузоподъемности Plus
□	Équipements standards	Standardausrüstungen	Standard equipment	Equipamiento de serie	Equipaggiamento standard	Equipamento de série	Стандартное оборудование
⚙️	Équipements optionnels	Sonderausrüstungen	Options	Equipamiento opcional	Equipaggiamento in opzione	Equipamento opcional	Дополнительное оборудование (опция)
📶	Levage	Heben	Hoisting	Elevación	Sollevamento	Elevação	Подъем
📶	Distribution	Katzfahren	Trolleying	Distribución	Distribuzione	Distribuição	Перемещение по стреле
📶	Orientation	Schwenken	Slewing	Orientación	Rotazione	Rotação	Поворот
⚡	50 Hz Monophasé	50 Hz Einphasige	50 Hz Single phase	50 Hz Monofasica	50 Hz Monofase	50 Hz monofásica	Однофазное напряжение 50Hz
kVA	Puissance requise	Erforderliche Leistung	Required power	Potencia Necesaria	Potenza richiesta	Potência Necessária	Потребляемая мощность
🕒	Fonction Power Control : vitesses treuils adaptées à la puissance disponible	Funktion Power Control: Geschwindigkeiten der Triebwerke werden an die verfügbare Leistung angepasst	Power Control Function: winch speeds adapted to the available power	Función Power Control: marchas de los cabrestantes adaptadas a la potencia disponible	Funzione Power Control: velocità degli organi adattate alla potenza disponibile	Função Power Control: velocidades de guincho adaptadas à potência disponível	Функция контроля мощности Power Control: регулировка скорости лебедок в зависимости от доступной мощности
⚠️	Hauteurs sous crochet données moufle plaquée	Hakenhöhen werden mit plattiertem Haken angegeben	Hook heights given with plated pulley block	Altura bajo gancho con pasteca bloqueada	Altezza sotto gancio con bozzello in contatto con carrello	Altura ao gancho com o cadernal em contacto com o carrinho	высота под крюком дана при условии, что крюковая подвеска соприкасается с кареткой
	Document commercial non contractuel	Unverbindliches Vertriebsdokument	This commercial document is not legally binding	Documento comercial no contractual	Documento commerciale non vincolante	Documento comercial não contratual	Этот коммерческий документ не является юридически обязательным
	Pour toute information technique se référer à la notice correspondante	Für technische Informationen, siehe die entsprechenden Anweisungen	For any technical information, please refer to the corresponding instructions	Para cualquier información técnica, ver la noticia correspondiente	Per tutte le informazioni tecniche fare riferimento al catalogo istruzioni	Para qualquer informação técnica complementar consultar as respectivas instruções	Для получения технической информации, см. соответствующие инструкции

