

MANITOWOC 4600 SERIES 4

LIFT CRANE CAPACITIES - 120,000 # CWT. OR 123,000# CWT.

BOOM #27B WITH OPEN THROAT TOP

CRAWLER MACHINE ON BARGE - 1 DEGREE MACHINE LIST

RAD. IN FT.	CAPACITIES IN THOUSANDS OF LBS.																		
	BOOM LENGTH - FT.																		
	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260
20	488.8*																		
21	467.3*																		
22	447.6*																		
23	429.4*																		
24	412.6*																		
25	397.0*																		
26	383.0*																		
27	362.8*																		
28	343.1*																		
29	325.4*																		
30	309.9*																		
32	281.5*																		
34	258.0*																		
36	238.5*																		
38	220.0*																		
40	205.8*																		
45	175.6*																		
50	152.7*																		
55	134.9*																		
60	120.5*																		
65	108.7*																		
70	98.8*																		
75	90.5*																		
80																			
85																			
90																			
95																			
100																			
105																			
110																			
115																			
120																			
125																			
130																			
135																			
140																			
145																			
150																			
155																			
160																			
165																			
170																			
175																			
180																			
185																			
190																			
195																			
200																			

CAPACITIES ARE FOR A CRAWLER MACHINE WHEN OPERATING ON A BARGE. MACHINE SHALL BE POSITIVELY SECURED TO PREVENT SHIFTING. CAPACITIES FOR VARIOUS BOOM LENGTHS AND OPERATING RADII ARE FOR FREELY SUSPENDED LOADS AND DO NOT EXCEED 75% OF A STATIC TIPPING LOAD. CAPACITIES BASED ON STRUCTURAL COMPETENCE ARE DENOTED BY AN ASTERISK (*).

WEIGHT OF ALL LOAD BLOCKS, HOOKS, WEIGHT BALL, SLINGS, HOIST LINES BENEATH BOOM POINT SHEAVES, ETC., IS CONSIDERED PART OF THE MAIN BOOM LOAD. BOOM IS NOT TO BE LOWERED BEYOND RADII WHERE COMBINED WEIGHTS ARE GREATER THAN RATED CAPACITY. WHERE NO CAPACITY IS SHOWN, OPERATION IS NOT INTENDED OR APPROVED.

REFER TO RIGGING #65234, LOAD LINE SPECIFICATION CHART #6495-A AND RANGE CHART #6785-A. CRANE OPERATOR JUDGMENT MUST BE USED TO ALLOW FOR DYNAMIC LOAD EFFECTS OF SWINGING, HOISTING OR LOWERING, AS WELL AS ADVERSE OPERATING CONDITIONS AND PHYSICAL MACHINE DEPRECIATION.

OPERATING RADIUS IS THE HORIZONTAL DISTANCE FROM THE AXIS OF ROTATION AT BARGE DECK TO THE CENTER OF VERTICAL HOIST LINE OR LOAD BLOCK.

MACHINE EQUIPPED WITH 30"-5 CRAWLERS, 60 IN. TREADS, 33' RETRACTABLE GANTRY, 12 PART BOOM HOIST REEVING, FOUR 1-3/8 IN. BOOM PENDANTS, 123,000# CWT. WITH CWT. ASSEMBLY #190821 (120,000# WITH CWT. ASSEMBLY #49667).