




Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating**

European Standards	
14 m/s Maximum Wind	thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom	
7 m/s with 54.9m Boom	



555 SERIES 1

LIFTING CAPACITIES: Chart supplements boom capacity chart **No. 8434-AM**. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and are calculated to comply with prEN 13000, ISO 4305 and include factors based on a 4.0 degree tipping angle. Capacities based on structural competence are denoted by an asterisk (*).

Weight of all load blocks, hooks, weight ball, slings, etc., beneath boom and jib point sheaves, is considered part of jib load. Reeved hoist line included in jib weight. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface. Refer to boom rigging **No. A00952**, jib assembly **No. A00953** and Wire Rope Specification chart **No. 8444-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

WIND CONDITIONS: Machine may be operated in winds stated in maximum wind speed table provided crane operator judgment is used to allow for wind effect on lifted load and other considerations noted on capacity chart are followed. Wind will have a considerable effect on load. Loads must be compensated for accordingly by reducing load ratings, reducing operating speeds, or by a combination of both. Recommend stopping operation and lowering boom and jib to 68 degree

boom angle when wind exceeds conditions stated in column A. Lower boom and jib to ground when wind is above 22 m/s (column B).

MACHINE TRAVEL: Machine to travel on a firm, level [up to 1 percent (0.5 degrees) grade] and uniformly supporting surface. *Travel with 100 percent of rated load prohibited.* Travel restricted to 90 percent of rated capacity with speed not to exceed 1.4 km/hr. Boom must be within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8446-A**.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

JIB POINT ELEVATION: Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with 7 264 mm crawlers, 1 219 mm treads, 7 010 mm live mast, 16 part boom hoist reeving, boom support straps, rotating bed No. A01066¹ or No. A03188 (refer to I.D. plate at front of rotating bed) and 32 430 kg crane counterweight.

¹WARNING: 570 kg front counterweight is required for cranes with rotating bed No. A01066 that do not have free-fall option. Counterweight can be removed only if crane has free-fall option on both front and rear drums.

Maximum Wind Speeds (all jib lengths)		
Boom Lengths	A Working Wind	B Lower To Ground
27.4m - 39.6m	14 m/s	22 m/s
42.7m - 51.8m	10 m/s	22 m/s
54.9m	7 m/s	22 m/s
Refer to table on page 2 for maximum boom and jib raising combinations.		

Maximum whip line capacity on 28 mm wire rope with single part line is 13 610 kg or 26 760 kg with two part line (9 070 kg per line when auxiliary drum equipped for 26 mm wire rope is used).



32 430 kg Crane Counterweight
4 Side Boxes

Upper boom point and upper wire rope guide (No. A04352) for third line must be removed before use of this chart.



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating**

European Standards
14 m/s Maximum Wind thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom

555 SERIES 1

Capacities based on structural competence are denoted by an asterisk (*).

Maximum Boom and Jib Lengths Lifted Unassisted			
Over End of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 134	Boom Length	Jib No. 134
(a,b) 64.0m	—	54.9m	—
(b) 61.0m	—	51.8m	—
57.9m	—	48.8m	12.2m
54.9m	12.2m	45.7m	18.3m
51.8m	18.3m	42.7m	24.4m
48.8m	24.4m		
Load block, hook and weight ball on ground at start.			
(a) Upper boom point cannot be attached on 64.0m boom.			
(b) Upper wire rope guide (No. A04352) for third line cannot be attached on 61.0m and 64.0m booms.			

9.1m (30 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.4m (90 Ft.) BOOM										
9.1	79.2	37.6	26 700 *							9.1
10.0	77.8	37.4	26 700 *							10.0
12.0	74.6	36.9	26 700 *	77.1	36.6	25 900*				12.0
14.0	71.3	36.2	23 900	73.7	36.0	24 500	76.3	35.4	19 500*	14.0
16.0	67.9	35.4	20 100	70.4	35.2	20 500	72.8	34.6	18 200*	16.0
18.0	64.4	34.5	16 900	66.9	34.2	17 200	69.3	33.6	17 100*	18.0
20.0	60.9	33.4	14 300	63.3	33.1	14 700	65.6	32.5	15 000	20.0
22.0	57.2	32.1	12 300	59.5	31.9	12 600	61.8	31.2	12 900	22.0
24.0	53.3	30.7	10 700	55.6	30.4	11 000	57.8	29.7	11 200	24.0
26.0	49.2	29.0	9 400	51.5	28.7	9 600	53.5	28.0	9 800	26.0
28.0	44.8	27.1	8 200	47.1	26.7	8 400	49.0	26.0	8 600	28.0
32.0	34.8	22.1	6 400	36.8	21.6	6 500				32.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m (30 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
30.5m (100 Ft.) BOOM										
9.1	80.0	40.7	26 700 *							9.1
10.0	78.8	40.5	26 700 *							10.0
12.0	75.8	40.1	26 700 *	78.1	39.8	26 100*				12.0
14.0	72.8	39.4	23 200	75.1	39.2	23 900	77.4	38.6	19 900*	14.0
16.0	69.7	38.7	19 700	72.0	38.5	20 100	74.2	37.9	18 700*	16.0
18.0	66.5	37.9	16 800	68.8	37.6	17 200	71.0	37.0	17 400	18.0
20.0	63.3	36.9	14 300	65.6	36.6	14 600	67.7	36.0	14 900	20.0
22.0	60.0	35.8	12 300	62.2	35.5	12 500	64.3	34.9	12 900	22.0
24.0	56.5	34.5	10 600	58.7	34.2	10 900	60.8	33.5	11 100	24.0
26.0	53.0	33.0	9 200	55.1	32.7	9 500	57.1	32.0	9 700	26.0
28.0	49.2	31.3	8 100	51.3	31.0	8 300	53.2	30.3	8 500	28.0
32.0	40.8	27.2	6 300	42.8	26.8	6 400	44.4	25.9	6 500	32.0
36.0	30.6	21.4	4 900	32.4	20.9	5 000				36.0
33.5m (110 Ft.) BOOM										
9.1	80.7	43.8	26 700 *							9.1
10.0	79.6	43.7	26 700 *							10.0
12.0	76.8	43.2	26 600	79.0	43.0	26 300*				12.0
14.0	74.0	42.6	22 600	76.2	42.4	23 200	78.3	41.8	20 300*	14.0
16.0	71.2	42.0	19 100	73.3	41.7	19 600	75.5	41.1	19 100*	16.0
18.0	68.3	41.2	16 400	70.4	40.9	16 800	72.5	40.3	17 400	18.0
20.0	65.4	40.3	14 000	67.5	40.0	14 400	69.5	39.4	14 800	20.0
22.0	62.3	39.3	12 000	64.4	39.0	12 300	66.4	38.4	12 700	22.0
24.0	59.2	38.1	10 400	61.3	37.8	10 700	63.2	37.2	10 900	24.0
26.0	56.0	36.8	9 100	58.0	36.5	9 300	59.9	35.8	9 600	26.0
28.0	52.7	35.3	7 900	54.7	35.0	8 100	56.5	34.3	8 300	28.0
32.0	45.4	31.7	6 100	47.4	31.4	6 200	49.0	30.6	6 400	32.0
36.0	37.1	27.0	4 700	38.9	26.6	4 800				36.0
40.0	26.6	20.3	3 600							40.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m (30 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
36.6m (120 Ft.) BOOM										
10.7	79.4	46.6	26 700 *							10.7
12.0	77.7	46.3	26 000							12.0
14.0	75.1	45.8	21 900	77.1	45.6	22 500	79.2	45.0	20 700*	14.0
16.0	72.5	45.2	18 600	74.5	44.9	19 100	76.5	44.4	19 300	16.0
18.0	69.8	44.5	16 000	71.8	44.2	16 400	73.8	43.6	16 900	18.0
20.0	67.1	43.7	13 800	69.1	43.4	14 200	71.0	42.8	14 600	20.0
22.0	64.3	42.7	11 900	66.3	42.4	12 200	68.2	41.8	12 500	22.0
24.0	61.5	41.7	10 200	63.4	41.4	10 500	65.3	40.7	10 800	24.0
26.0	58.6	40.5	8 900	60.5	40.2	9 100	62.3	39.5	9 400	26.0
28.0	55.6	39.1	7 700	57.4	38.8	7 900	59.2	38.1	8 200	28.0
32.0	49.1	35.9	5 900	51.0	35.6	6 100	52.6	34.8	6 300	32.0
36.0	42.0	31.9	4 500	43.7	31.5	4 600	45.2	30.6	4 800	36.0
40.0	33.6	26.5	3 400	35.2	26.1	3 500				40.0
44.0	22.7	18.7	2 500							44.0
39.6m (130 Ft.) BOOM										
10.7	80.1	49.7	26 700 *							10.7
12.0	78.5	49.5	25 300							12.0
14.0	76.1	49.0	21 300	78.0	48.7	21 900	79.9	48.1	21 000*	14.0
16.0	73.6	48.4	18 000	75.5	48.1	18 500	77.4	47.6	19 300	16.0
18.0	71.2	47.7	15 500	73.0	47.5	15 900	74.9	46.9	16 400	18.0
20.0	68.6	47.0	13 400	70.5	46.7	13 800	72.3	46.1	14 200	20.0
22.0	66.1	46.1	11 600	67.9	45.8	12 000	69.7	45.2	12 400	22.0
24.0	63.5	45.1	10 000	65.3	44.8	10 300	67.0	44.2	10 600	24.0
26.0	60.8	44.0	8 600	62.6	43.7	8 900	64.3	43.1	9 200	26.0
28.0	58.0	42.8	7 500	59.8	42.5	7 800	61.4	41.8	8 000	28.0
32.0	52.2	39.9	5 700	53.9	39.6	5 800	55.5	38.9	6 100	32.0
36.0	45.9	36.3	4 300	47.6	36.0	4 400	49.0	35.2	4 600	36.0
40.0	38.8	31.8	3 200	40.4	31.4	3 300				40.0
44.0	30.3	25.8	2 300	31.7	25.3	2 400				44.0




Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom

10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m (30 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.7m (140 Ft.) BOOM										
10.7	80.7	52.8	26 700*							10.7
12.0	79.2	52.6	24 700							12.0
14.0	76.9	52.1	20 700	78.7	51.9	21 300	80.5	51.3	21 200	14.0
16.0	74.6	51.6	17 600	76.4	51.3	18 000	78.2	50.7	18 800	16.0
18.0	72.3	51.0	15 000	74.1	50.7	15 500	75.8	50.1	16 000	18.0
20.0	70.0	50.2	13 000	71.7	50.0	13 400	73.4	49.4	13 800	20.0
22.0	67.6	49.4	11 300	69.3	49.2	11 700	71.0	48.5	12 000	22.0
24.0	65.1	48.5	9 800	66.8	48.2	10 200	68.5	47.6	10 500	24.0
26.0	62.7	47.5	8 500	64.4	47.2	8 800	66.0	46.6	9 100	26.0
28.0	60.1	46.4	7 300	61.8	46.1	7 600	63.4	45.4	7 900	28.0
32.0	54.8	43.7	5 500	56.5	43.4	5 700	58.0	42.7	5 900	32.0
36.0	49.1	40.5	4 100	50.7	40.2	4 300	52.1	39.4	4 400	36.0
40.0	42.9	36.5	3 000	44.4	36.2	3 200	45.7	35.3	3 300	40.0
44.0	35.8	31.5	2 200	37.2	31.1	2 300				44.0
45.7m (150 Ft.) BOOM										
12.2	79.6	55.7	23 700							12.2
14.0	77.7	55.3	20 100	79.3	55.0	20 800				14.0
16.0	75.5	54.8	17 000	77.2	54.5	17 600	78.9	53.9	18 200	16.0
18.0	73.3	54.2	14 500	75.0	53.9	15 000	76.6	53.3	15 600	18.0
20.0	71.1	53.5	12 500	72.8	53.2	13 000	74.4	52.6	13 400	20.0
22.0	68.9	52.7	10 900	70.5	52.5	11 300	72.1	51.8	11 700	22.0
24.0	66.6	51.9	9 500	68.2	51.6	9 800	69.8	51.0	10 200	24.0
26.0	64.3	50.9	8 300	65.9	50.7	8 600	67.5	50.0	8 900	26.0
28.0	61.9	49.9	7 100	63.5	49.6	7 400	65.1	48.9	7 700	28.0
32.0	57.1	47.5	5 300	58.6	47.1	5 500	60.1	46.5	5 800	32.0
36.0	51.9	44.5	3 900	53.4	44.2	4 100	54.7	43.4	4 300	36.0
40.0	46.3	40.9	2 800	47.7	40.6	2 900	49.0	39.8	3 100	40.0
44.0	40.1	36.6	1 900	41.5	36.1	2 000				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m (30 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.8m (160 Ft.) BOOM										
12.2	80.1	58.8	23 000							12.2
14.0	78.3	58.4	19 500	79.9	58.1	20 200				14.0
16.0	76.3	57.9	16 500	77.9	57.6	17 000	79.5	57.0	17 700	16.0
18.0	74.2	57.4	14 100	75.8	57.1	14 600	77.4	56.5	15 100	18.0
20.0	72.2	56.7	12 100	73.7	56.4	12 600	75.3	55.8	13 100	20.0
22.0	70.0	56.0	10 500	71.6	55.7	10 900	73.1	55.1	11 300	22.0
24.0	67.9	55.2	9 100	69.5	54.9	9 500	71.0	54.3	9 900	24.0
26.0	65.8	54.3	7 900	67.3	54.0	8 200	68.8	53.4	8 600	26.0
28.0	63.5	53.3	6 900	65.1	53.0	7 200	66.5	52.4	7 500	28.0
32.0	59.0	51.1	5 100	60.5	50.8	5 300	61.9	50.1	5 600	32.0
36.0	54.2	48.4	3 700	55.7	48.0	3 900	57.0	47.3	4 100	36.0
40.0	49.1	45.1	2 600	50.5	44.8	2 800	51.8	44.0	2 900	40.0
44.0				44.9	40.8	1 900	46.1	39.9	2 000	44.0
51.8m (170 Ft.) BOOM										
12.2	80.6	61.9	22 300							12.2
14.0	78.9	61.5	18 900	80.4	61.2	19 600				14.0
16.0	77.0	61.1	16 000	78.5	60.8	16 600	80.0	60.2	17 300	16.0
18.0	75.0	60.5	13 600	76.5	60.3	14 100	78.0	59.6	14 700	18.0
20.0	73.1	59.9	11 700	74.6	59.7	12 100	76.1	59.0	12 700	20.0
22.0	71.1	59.3	10 100	72.6	59.0	10 500	74.0	58.4	10 900	22.0
24.0	69.1	58.5	8 700	70.6	58.2	9 100	72.0	57.6	9 500	24.0
26.0	67.0	57.7	7 600	68.5	57.4	7 900	69.9	56.7	8 200	26.0
28.0	65.0	56.7	6 600	66.4	56.5	6 800	67.8	55.8	7 200	28.0
32.0	60.7	54.6	4 900	62.1	54.3	5 100	63.5	53.6	5 400	32.0
36.0	56.3	52.1	3 500	57.7	51.8	3 700	59.0	51.1	3 900	36.0
40.0	51.6	49.1	2 400	52.9	48.8	2 600	54.1	48.0	2 800	40.0
44.0							49.0	44.4	1 800	44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards		
14 m/s Maximum Wind	thru 39.6m Boom	
10 m/s with 42.7m thru 51.8m Boom		
7 m/s with 54.9m Boom		



555 SERIES 1

Capacities based on structural competence are denoted by an asterisk (*).

9.1m (30 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
13.7	79.7	64.7	18 900							13.7
14.0	79.4	64.6	18 400							14.0
16.0	77.6	64.2	15 500	79.1	63.9	16 100				16.0
18.0	75.8	63.7	13 200	77.2	63.4	13 700	78.6	62.8	14 300	18.0
20.0	73.9	63.1	11 300	75.3	62.8	11 800	76.7	62.2	12 300	20.0
22.0	72.0	62.5	9 800	73.4	62.2	10 100	74.8	61.6	10 600	22.0
24.0	70.1	61.8	8 400	71.5	61.5	8 800	72.9	60.9	9 200	24.0
26.0	68.2	61.0	7 200	69.6	60.7	7 600	71.0	60.1	8 000	26.0
28.0	66.2	60.1	6 300	67.6	59.8	6 600	69.0	59.2	6 900	28.0
32.0	62.2	58.1	4 600	63.6	57.8	4 900	64.9	57.1	5 200	32.0
36.0	58.1	55.8	3 300	59.4	55.5	3 500	60.7	54.7	3 800	36.0
40.0	53.7	53.0	2 200	55.0	52.7	2 400	56.2	51.9	2 600	40.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m (40 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.4m (90 Ft.) BOOM										
9.1	80.7	40.7	23 500 *							9.1
10.0	79.5	40.5	23 100 *							10.0
12.0	76.5	40.0	22 200 *							12.0
14.0	73.4	39.4	21 400 *	76.5	39.1	19 600*	79.7	38.4	16 400*	14.0
16.0	70.4	38.7	20 200	73.4	38.4	19 100*	76.5	37.6	15 300*	16.0
18.0	67.2	37.9	17 200	70.3	37.5	17 600	73.3	36.8	14 400*	18.0
20.0	64.0	36.9	14 600	67.0	36.5	15 000	70.0	35.7	13 500*	20.0
22.0	60.7	35.7	12 600	63.6	35.4	13 000	66.5	34.6	12 800	22.0
24.0	57.2	34.4	10 900	60.2	34.1	11 300	63.0	33.2	11 700	24.0
26.0	53.6	33.0	9 600	56.5	32.6	9 900	59.2	31.7	10 100	26.0
28.0	49.9	31.3	8 400	52.7	30.9	8 700	55.3	29.9	8 900	28.0
32.0	41.5	27.1	6 600	44.2	26.6	6 800	46.4	25.5	6 900	32.0
36.0	31.3	21.3	5 200	33.7	20.7	5 300				36.0
30.5m (100 Ft.) BOOM										
10.7	79.3	43.5	23 100 *							10.7
12.0	77.5	43.2	22 500 *							12.0
14.0	74.7	42.6	21 700	77.5	42.3	19 800*	80.5	41.6	16 700*	14.0
16.0	71.8	42.0	19 900	74.7	41.6	19 300*	77.6	40.9	15 600*	16.0
18.0	69.0	41.2	16 900	71.8	40.8	17 600	74.6	40.1	14 700*	18.0
20.0	66.0	40.3	14 500	68.8	39.9	14 900	71.6	39.1	13 900*	20.0
22.0	63.0	39.3	12 500	65.8	38.9	12 800	68.5	38.1	13 100	22.0
24.0	59.9	38.1	10 800	62.6	37.7	11 200	65.3	36.9	11 500	24.0
26.0	56.7	36.8	9 500	59.4	36.4	9 700	61.9	35.5	10 000	26.0
28.0	53.3	35.3	8 300	56.0	34.9	8 600	58.4	34.0	8 800	28.0
32.0	46.1	31.7	6 500	48.6	31.2	6 700	50.9	30.2	6 800	32.0
36.0	37.7	26.9	5 100	40.1	26.4	5 200				36.0
40.0	27.2	20.2	4 000							40.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m (40 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m (110 Ft.) BOOM										
10.7	80.0	46.6	23 300 *							10.7
12.0	78.3	46.3	22 800 *							12.0
14.0	75.7	45.8	21 900	78.4	45.5	20 000*				14.0
16.0	73.1	45.2	19 200	75.8	44.8	19 200	78.5	44.1	15 900*	16.0
18.0	70.4	44.5	16 400	73.1	44.1	17 000	75.7	43.3	15 000*	18.0
20.0	67.7	43.6	14 300	70.3	43.3	14 700	73.0	42.5	14 200*	20.0
22.0	64.9	42.7	12 300	67.5	42.3	12 700	70.1	41.5	13 200	22.0
24.0	62.1	41.6	10 600	64.7	41.2	11 000	67.2	40.4	11 400	24.0
26.0	59.2	40.4	9 200	61.7	40.0	9 600	64.2	39.2	9 900	26.0
28.0	56.2	39.1	8 100	58.7	38.7	8 400	61.0	37.8	8 700	28.0
32.0	49.7	35.9	6 300	52.2	35.4	6 500	54.4	34.5	6 700	32.0
36.0	42.6	31.8	4 900	44.9	31.3	5 000	46.8	30.2	5 200	36.0
40.0	34.2	26.5	3 800	36.3	25.9	3 900				40.0
44.0	23.2	18.7	2 800							44.0
36.6m (120 Ft.) BOOM										
10.7	80.7	49.7	23 500 *							10.7
12.0	79.1	49.4	23 000 *							12.0
14.0	76.6	49.0	22 000	79.2	48.6	20 100*				14.0
16.0	74.2	48.4	18 500	76.7	48.0	19 100	79.3	47.3	16 200*	16.0
18.0	71.7	47.7	16 000	74.2	47.4	16 500	76.7	46.6	15 300*	18.0
20.0	69.2	46.9	13 900	71.7	46.6	14 300	74.1	45.8	14 500	20.0
22.0	66.6	46.1	12 100	69.1	45.7	12 500	71.5	44.9	13 000	22.0
24.0	64.0	45.1	10 400	66.4	44.7	10 800	68.8	43.9	11 200	24.0
26.0	61.3	44.0	9 100	63.7	43.6	9 400	66.0	42.7	9 800	26.0
28.0	58.6	42.8	7 900	60.9	42.4	8 200	63.2	41.5	8 500	28.0
32.0	52.8	39.9	6 100	55.1	39.4	6 300	57.2	38.5	6 600	32.0
36.0	46.5	36.3	4 700	48.7	35.8	4 900	50.6	34.8	5 000	36.0
40.0	39.3	31.8	3 600	41.4	31.2	3 700				40.0
44.0	30.8	25.7	2 700	32.7	25.0	2 800				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
12.2	79.5	52.5	23 100*							12.2
14.0	77.4	52.1	21 300	79.8	51.7	20 300				14.0
16.0	75.2	51.6	18 000	77.5	51.2	18 900	79.9	50.4	16 400*	16.0
18.0	72.8	50.9	15 500	75.2	50.6	16 000	77.6	49.8	15 500*	18.0
20.0	70.5	50.2	13 400	72.8	49.9	13 900	75.1	49.1	14 600	20.0
22.0	68.1	49.4	11 700	70.4	49.0	12 100	72.7	48.2	12 700	22.0
24.0	65.7	48.5	10 200	67.9	48.1	10 600	70.2	47.3	11 000	24.0
26.0	63.2	47.5	8 800	65.4	47.1	9 200	67.6	46.2	9 600	26.0
28.0	60.6	46.4	7 700	62.9	45.9	8 000	65.0	45.1	8 400	28.0
32.0	55.3	43.7	5 800	57.5	43.3	6 100	59.6	42.4	6 400	32.0
36.0	49.6	40.5	4 400	51.8	40.0	4 600	53.7	39.0	4 800	36.0
40.0	43.4	36.5	3 400	45.4	36.0	3 500	47.1	34.8	3 700	40.0
44.0	36.3	31.5	2 400	38.2	30.9	2 600				44.0
42.7m (140 Ft.) BOOM										
12.2	80.1	55.6	23 300*							12.2
14.0	78.2	55.2	20 700	80.4	54.9	20 300				14.0
16.0	76.0	54.7	17 500	78.2	54.4	18 400				16.0
18.0	73.8	54.1	15 000	76.0	53.8	15 600	78.3	53.0	15 800*	18.0
20.0	71.6	53.5	13 000	73.8	53.1	13 500	76.0	52.3	14 200	20.0
22.0	69.4	52.7	11 300	71.6	52.3	11 800	73.7	51.5	12 300	22.0
24.0	67.1	51.9	9 900	69.3	51.5	10 400	71.4	50.6	10 800	24.0
26.0	64.8	50.9	8 700	66.9	50.5	9 100	69.0	49.7	9 500	26.0
28.0	62.4	49.9	7 500	64.6	49.5	7 900	66.6	48.6	8 200	28.0
32.0	57.5	47.4	5 700	59.6	47.0	5 900	61.6	46.1	6 300	32.0
36.0	52.4	44.5	4 300	54.4	44.0	4 500	56.2	43.0	4 700	36.0
40.0	46.7	40.9	3 200	48.7	40.4	3 300	50.4	39.3	3 500	40.0
44.0	40.5	36.5	2 300	42.4	36.0	2 400	43.9	34.7	2 600	44.0




Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom

10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m (40 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
12.2	80.6	58.7	23 500*							12.2
14.0	78.8	58.4	20 000							14.0
16.0	76.8	57.9	17 000	78.9	57.5	17 700				16.0
18.0	74.7	57.3	14 600	76.8	57.0	15 100	78.9	56.2	15 700	18.0
20.0	72.6	56.7	12 600	74.7	56.3	13 100	76.8	55.5	13 700	20.0
22.0	70.5	56.0	10 900	72.6	55.6	11 400	74.7	54.8	12 000	22.0
24.0	68.4	55.2	9 500	70.4	54.8	10 000	72.5	54.0	10 500	24.0
26.0	66.2	54.3	8 300	68.3	53.9	8 700	70.3	53.0	9 200	26.0
28.0	64.0	53.3	7 300	66.0	52.9	7 700	68.0	52.0	8 100	28.0
32.0	59.5	51.1	5 400	61.5	50.6	5 800	63.3	49.7	6 100	32.0
36.0	54.7	48.3	4 100	56.6	47.9	4 300	58.4	46.9	4 600	36.0
40.0	49.6	45.1	2 900	51.5	44.6	3 200	53.1	43.6	3 300	40.0
44.0	44.0	41.2	2 100	45.9	40.6	2 200	47.4	39.5	2 400	44.0
48.8m (160 Ft.) BOOM										
13.7	79.6	61.5	20 000							13.7
14.0	79.4	61.5	19 500							14.0
16.0	77.4	61.0	16 500	79.4	60.7	17 200				16.0
18.0	75.5	60.5	14 100	77.5	60.1	14 700	79.5	59.3	15 400	18.0
20.0	73.5	59.9	12 200	75.5	59.5	12 700	77.5	58.7	13 400	20.0
22.0	71.5	59.2	10 600	73.5	58.8	11 000	75.5	58.0	11 600	22.0
24.0	69.5	58.5	9 200	71.5	58.1	9 600	73.4	57.2	10 100	24.0
26.0	67.5	57.6	8 000	69.4	57.2	8 400	71.4	56.4	8 900	26.0
28.0	65.4	56.7	7 000	67.4	56.3	7 400	69.2	55.4	7 800	28.0
32.0	61.2	54.6	5 300	63.1	54.2	5 600	64.9	53.3	5 900	32.0
36.0	56.7	52.1	3 900	58.6	51.6	4 100	60.3	50.7	4 400	36.0
40.0	52.0	49.1	2 800	53.8	48.6	3 000	55.5	47.6	3 200	40.0
44.0	47.0	45.5	1 800	48.7	45.0	2 000	50.2	43.9	2 200	44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
13.7	80.1	64.6	19 400							13.7
14.0	79.9	64.6	18 900							14.0
16.0	78.0	64.2	16 000	80.0	63.8	16 700				16.0
18.0	76.2	63.7	13 600	78.1	63.3	14 300				18.0
20.0	74.3	63.1	11 700	76.2	62.7	12 300	78.2	61.9	13 000	20.0
22.0	72.5	62.5	10 100	74.3	62.1	10 600	76.2	61.2	11 300	22.0
24.0	70.6	61.7	8 800	72.4	61.3	9 300	74.3	60.5	9 800	24.0
26.0	68.6	61.0	7 700	70.5	60.6	8 100	72.3	59.7	8 600	26.0
28.0	66.7	60.1	6 600	68.5	59.7	7 000	70.3	58.8	7 500	28.0
32.0	62.7	58.1	5 000	64.5	57.7	5 300	66.2	56.8	5 700	32.0
36.0	58.5	55.7	3 600	60.3	55.3	3 900	62.0	54.4	4 200	36.0
40.0	54.2	53.0	2 500	55.9	52.5	2 800	57.5	51.5	3 000	40.0
44.0				51.2	49.2	1 800	52.7	48.1	2 000	44.0
54.9m (180 Ft.) BOOM										
13.7	80.6	67.7	18 800							13.7
14.0	80.3	67.7	18 400							14.0
16.0	78.6	67.3	15 500							16.0
18.0	76.8	66.8	13 200	78.7	66.4	13 900				18.0
20.0	75.1	66.3	11 400	76.9	65.9	11 900	78.7	65.1	12 600	20.0
22.0	73.3	65.7	9 800	75.1	65.3	10 300	76.9	64.4	10 900	22.0
24.0	71.5	65.0	8 500	73.3	64.6	8 900	75.1	63.7	9 500	24.0
26.0	69.7	64.2	7 300	71.4	63.8	7 800	73.2	63.0	8 200	26.0
28.0	67.8	63.4	6 400	69.6	63.0	6 700	71.3	62.1	7 200	28.0
32.0	64.0	61.5	4 700	65.8	61.1	5 000	67.4	60.2	5 400	32.0
36.0	60.1	59.3	3 400	61.8	58.9	3 700	63.4	58.0	4 000	36.0
40.0	56.0	56.7	2 400	57.7	56.3	2 600	59.3	55.3	2 800	40.0
44.0							54.8	52.2	1 900	44.0




Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom

10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m (50 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.4m (90 Ft.) BOOM										
10.7	79.7	43.5	19 000 *							10.7
12.0	77.8	43.2	18 500 *							12.0
14.0	75.0	42.6	17 800 *	78.7	42.2	16 300*				14.0
16.0	72.2	42.0	17 200 *	75.8	41.6	15 800*				16.0
18.0	69.3	41.2	16 600 *	72.9	40.8	15 300*	77.0	40.1	12 700*	18.0
20.0	66.4	40.3	14 800	69.9	39.9	14 900	73.9	39.1	12 000*	20.0
22.0	63.4	39.2	12 700	66.9	38.8	13 300	70.8	38.1	11 300*	22.0
24.0	60.2	38.1	11 100	63.7	37.7	11 500	67.6	36.9	10 800*	24.0
26.0	57.0	36.8	9 700	60.5	36.3	10 100	64.3	35.6	10 200	26.0
28.0	53.7	35.3	8 600	57.1	34.8	8 900	60.8	34.0	9 500	28.0
32.0	46.4	31.7	6 800	49.7	31.2	7 000	53.2	30.3	7 400	32.0
36.0	38.1	26.9	5 300	41.2	26.3	5 500				36.0
40.0	27.6	20.2	4 200							40.0
30.5m (100 Ft.) BOOM										
10.7	80.4	46.6	19 100 *							10.7
12.0	78.7	46.3	18 700 *							12.0
14.0	76.1	45.8	18 000 *	79.5	45.4	16 400*				14.0
16.0	73.4	45.2	17 400 *	76.8	44.8	16 000*				16.0
18.0	70.8	44.5	16 700	74.1	44.1	15 500*	77.9	43.3	12 900*	18.0
20.0	68.1	43.6	14 700	71.4	43.2	15 100	75.1	42.5	12 200*	20.0
22.0	65.3	42.7	12 600	68.6	42.3	13 100	72.3	41.5	11 600*	22.0
24.0	62.4	41.6	11 000	65.7	41.2	11 400	69.3	40.4	11 000*	24.0
26.0	59.5	40.4	9 600	62.7	40.0	10 000	66.3	39.2	10 500	26.0
28.0	56.5	39.1	8 400	59.7	38.6	8 700	63.2	37.8	9 300	28.0
32.0	50.1	35.9	6 600	53.2	35.4	6 800	56.5	34.5	7 300	32.0
36.0	42.9	31.8	5 200	45.9	31.3	5 400	49.1	30.3	5 800	36.0
40.0	34.6	26.5	4 100	37.3	25.8	4 200				40.0
44.0	23.5	18.7	3 200							44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m (50 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m (110 Ft.) BOOM										
10.7	81.0	49.7	19 300 *							10.7
12.0	79.4	49.4	18 900 *							12.0
14.0	77.0	49.0	18 200 *	80.1	48.6	16 600*				14.0
16.0	74.5	48.4	17 700 *	77.7	48.0	16 100*				16.0
18.0	72.0	47.7	16 400	75.2	47.3	15 700*	78.7	46.5	13 100*	18.0
20.0	69.5	46.9	14 200	72.6	46.5	14 800	76.2	45.7	12 500*	20.0
22.0	67.0	46.1	12 400	70.0	45.6	12 900	73.5	44.9	11 900*	22.0
24.0	64.3	45.1	10 800	67.4	44.7	11 200	70.8	43.9	11 300*	24.0
26.0	61.7	44.0	9 400	64.7	43.5	9 800	68.1	42.7	10 500	26.0
28.0	58.9	42.8	8 200	61.9	42.3	8 600	65.2	41.5	9 200	28.0
32.0	53.1	39.9	6 400	56.0	39.4	6 700	59.2	38.5	7 200	32.0
36.0	46.8	36.3	5 000	49.6	35.7	5 200	52.6	34.8	5 600	36.0
40.0	39.7	31.8	3 800	42.4	31.1	4 000				40.0
44.0	31.2	25.7	3 000	33.6	24.9	3 100				44.0
36.6m (120 Ft.) BOOM										
12.2	79.8	52.5	19 000 *							12.2
14.0	77.8	52.1	18 500 *							14.0
16.0	75.5	51.6	17 800	78.4	51.2	16 300*				16.0
18.0	73.1	50.9	16 000	76.1	50.5	15 800*	79.5	49.7	13 100*	18.0
20.0	70.8	50.2	13 800	73.7	49.8	14 400	77.0	49.0	12 700*	20.0
22.0	68.4	49.4	12 100	71.3	49.0	12 600	74.6	48.2	12 100*	22.0
24.0	66.0	48.5	10 600	68.9	48.1	11 000	72.1	47.2	11 500*	24.0
26.0	63.5	47.5	9 200	66.3	47.0	9 600	69.5	46.2	10 300	26.0
28.0	60.9	46.3	8 000	63.8	45.9	8 400	66.9	45.1	9 000	28.0
32.0	55.6	43.7	6 200	58.4	43.2	6 500	61.5	42.4	7 000	32.0
36.0	49.9	40.5	4 800	52.7	39.9	5 000	55.6	39.0	5 500	36.0
40.0	43.7	36.5	3 700	46.3	35.9	3 900	49.0	34.9	4 200	40.0
44.0	36.6	31.5	2 800	39.0	30.8	2 900				44.0
48.0	27.9	24.7	2 100							48.0




Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom

10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m (50 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
12.2	80.4	55.6	19 100*							12.2
14.0	78.4	55.2	18 600*							14.0
16.0	76.3	54.7	17 700	79.1	54.3	16 400*				16.0
18.0	74.1	54.1	15 400	76.9	53.7	15 800				18.0
20.0	71.9	53.5	13 300	74.7	53.0	14 000	77.8	52.2	12 900*	20.0
22.0	69.7	52.7	11 700	72.4	52.3	12 200	75.5	51.4	12 300*	22.0
24.0	67.4	51.9	10 300	70.1	51.4	10 700	73.2	50.6	11 500	24.0
26.0	65.1	50.9	9 000	67.8	50.5	9 400	70.8	49.6	10 200	26.0
28.0	62.7	49.9	7 800	65.4	49.4	8 200	68.4	48.6	8 900	28.0
32.0	57.8	47.4	5 900	60.5	46.9	6 300	63.4	46.1	6 900	32.0
36.0	52.6	44.5	4 500	55.2	44.0	4 800	58.0	43.1	5 300	36.0
40.0	47.0	40.9	3 400	49.5	40.3	3 700	52.2	39.4	4 100	40.0
44.0	40.8	36.5	2 500	43.2	35.9	2 700	45.7	34.8	3 100	44.0
48.0				35.9	30.2	1 900				48.0
42.7m (140 Ft.) BOOM										
12.2	80.9	58.7	19 300*							12.2
14.0	79.1	58.4	18 800*							14.0
16.0	77.0	57.9	17 600	79.7	57.5	16 500*				16.0
18.0	75.0	57.3	14 900	77.6	56.9	15 600				18.0
20.0	72.9	56.7	12 900	75.5	56.3	13 600	78.5	55.4	13 000*	20.0
22.0	70.8	56.0	11 300	73.4	55.5	11 900	76.4	54.7	12 400	22.0
24.0	68.7	55.2	9 900	71.3	54.7	10 400	74.2	53.9	11 300	24.0
26.0	66.5	54.3	8 700	69.1	53.8	9 200	72.0	53.0	10 000	26.0
28.0	64.3	53.3	7 600	66.8	52.8	8 100	69.7	52.0	8 800	28.0
32.0	59.7	51.0	5 800	62.3	50.6	6 100	65.0	49.7	6 800	32.0
36.0	55.0	48.3	4 400	57.4	47.8	4 700	60.1	46.9	5 200	36.0
40.0	49.8	45.1	3 300	52.2	44.5	3 500	54.8	43.6	4 000	40.0
44.0	44.3	41.2	2 400	46.6	40.5	2 600	49.0	39.5	2 900	44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m (50 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
13.7	79.9	61.5	19 000 *							13.7
14.0	79.6	61.5	18 800							14.0
16.0	77.7	61.0	17 000							16.0
18.0	75.7	60.5	14 400	78.3	60.1	15 200				18.0
20.0	73.8	59.9	12 500	76.3	59.5	13 200	79.1	58.6	13 100*	20.0
22.0	71.8	59.2	10 900	74.3	58.8	11 500	77.1	57.9	12 500	22.0
24.0	69.8	58.5	9 500	72.3	58.0	10 000	75.0	57.2	11 000	24.0
26.0	67.8	57.6	8 300	70.2	57.2	8 800	72.9	56.3	9 600	26.0
28.0	65.7	56.7	7 300	68.1	56.2	7 800	70.8	55.4	8 500	28.0
32.0	61.4	54.6	5 600	63.8	54.1	5 900	66.5	53.2	6 600	32.0
36.0	57.0	52.1	4 100	59.3	51.6	4 400	61.9	50.7	5 100	36.0
40.0	52.3	49.1	3 000	54.6	48.5	3 300	57.0	47.6	3 800	40.0
44.0	47.2	45.5	2 200	49.5	44.9	2 400	51.8	43.9	2 800	44.0
48.0							46.1	39.5	1 900	48.0
48.8m (160 Ft.) BOOM										
13.7	80.4	64.6	19 100 *							13.7
14.0	80.1	64.6	18 800							14.0
16.0	78.3	64.2	16 400							16.0
18.0	76.4	63.7	14 000	78.8	63.2	14 800				18.0
20.0	74.6	63.1	12 100	77.0	62.6	12 800	79.7	61.8	13 100	20.0
22.0	72.7	62.4	10 500	75.1	62.0	11 100	77.8	61.1	12 200	22.0
24.0	70.8	61.7	9 200	73.2	61.3	9 700	75.8	60.4	10 600	24.0
26.0	68.9	60.9	8 000	71.2	60.5	8 500	73.8	59.6	9 400	26.0
28.0	66.9	60.1	7 000	69.2	59.6	7 500	71.8	58.7	8 300	28.0
32.0	62.9	58.1	5 300	65.2	57.6	5 800	67.7	56.7	6 400	32.0
36.0	58.8	55.7	3 900	61.0	55.2	4 300	63.5	54.3	4 900	36.0
40.0	54.4	52.9	2 800	56.6	52.4	3 100	59.0	51.5	3 700	40.0
44.0	49.8	49.7	1 900	51.9	49.1	2 200	54.2	48.1	2 600	44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards		
14 m/s Maximum Wind thru 39.6m Boom		
10 m/s with 42.7m thru 51.8m Boom		
7 m/s with 54.9m Boom		



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m (50 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
13.7	80.8	67.7	19 100							13.7
14.0	80.6	67.7	18 700							14.0
16.0	78.8	67.3	15 900							16.0
18.0	77.1	66.8	13 600	79.4	66.4	14 300				18.0
20.0	75.3	66.3	11 700	77.6	65.8	12 400	80.2	64.9	13 100	20.0
22.0	73.5	65.7	10 100	75.8	65.2	10 700	78.3	64.3	11 800	22.0
24.0	71.7	65.0	8 800	74.0	64.5	9 400	76.5	63.6	10 300	24.0
26.0	69.9	64.2	7 700	72.1	63.8	8 200	74.6	62.9	9 100	26.0
28.0	68.0	63.4	6 600	70.3	62.9	7 100	72.7	62.0	8 000	28.0
32.0	64.3	61.5	5 000	66.5	61.0	5 400	68.9	60.1	6 200	32.0
36.0	60.3	59.3	3 700	62.5	58.8	4 100	64.9	57.9	4 700	36.0
40.0	56.3	56.7	2 600	58.4	56.2	2 900	60.7	55.2	3 500	40.0
44.0				54.1	53.1	2 000	56.3	52.1	2 500	44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m (60 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.4m (90 Ft.) BOOM										
10.7	80.8	46.7	13 600 *							10.7
12.0	79.1	46.4	13 600 *							12.0
14.0	76.5	45.9	13 500 *	80.6	45.5	12 600*				14.0
16.0	73.9	45.3	13 300 *	78.0	44.9	12 200*				16.0
18.0	71.2	44.6	12 800 *	75.3	44.2	11 800*				18.0
20.0	68.5	43.8	12 400 *	72.6	43.4	11 400*	76.7	42.4	10 500*	20.0
22.0	65.8	42.8	12 000 *	69.8	42.4	11 100*	73.8	41.5	10 100*	22.0
24.0	62.9	41.8	11 300	66.9	41.4	10 800*	70.9	40.4	9 400*	24.0
26.0	60.0	40.6	10 100	64.0	40.2	10 400	67.9	39.2	8 900*	26.0
28.0	57.0	39.3	8 800	60.9	38.8	9 200	64.7	37.8	8 400*	28.0
32.0	50.6	36.1	7 000	54.4	35.6	7 300	58.1	34.5	7 600	32.0
36.0	43.6	32.2	5 600	47.2	31.6	5 800	50.6	30.3	6 000	36.0
40.0	35.3	26.9	4 500	38.8	26.2	4 600				40.0
44.0	24.6	19.4	3 500							44.0
30.5m (100 Ft.) BOOM										
12.2	79.6	49.5	13 600 *							12.2
14.0	77.4	49.0	13 600 *							14.0
16.0	74.9	48.5	13 400 *	78.8	48.1	12 300*				16.0
18.0	72.5	47.8	13 000 *	76.3	47.4	11 900*				18.0
20.0	70.0	47.1	12 600 *	73.7	46.6	11 600*	77.6	45.7	10 600*	20.0
22.0	67.4	46.2	12 200 *	71.1	45.8	11 300*	75.0	44.8	10 300*	22.0
24.0	64.8	45.2	11 300	68.5	44.8	10 900*	72.3	43.8	9 700*	24.0
26.0	62.1	44.2	9 900	65.8	43.7	10 300	69.5	42.7	9 100*	26.0
28.0	59.4	43.0	8 800	63.0	42.5	9 100	66.6	41.4	8 700*	28.0
32.0	53.6	40.1	6 900	57.2	39.6	7 200	60.6	38.5	7 500	32.0
36.0	47.3	36.6	5 500	50.8	36.0	5 700	54.1	34.8	6 000	36.0
40.0	40.3	32.1	4 300	43.7	31.5	4 500	46.6	30.1	4 700	40.0
44.0	31.9	26.3	3 400	35.1	25.5	3 600				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m (60 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m (110 Ft.) BOOM										
12.2	80.2	52.6	13 600 *							12.2
14.0	78.1	52.2	13 600 *							14.0
16.0	75.9	51.7	13 500 *	79.5	51.2	12 400*				16.0
18.0	73.5	51.0	13 200 *	77.1	50.6	12 100*				18.0
20.0	71.2	50.3	12 800 *	74.8	49.9	11 700*	78.4	48.9	10 700*	20.0
22.0	68.8	49.5	12 300	72.3	49.1	11 400*	75.9	48.1	10 400*	22.0
24.0	66.4	48.6	11 100	69.9	48.2	11 100*	73.4	47.2	9 900*	24.0
26.0	63.9	47.6	9 700	67.4	47.2	10 100	70.9	46.2	9 400*	26.0
28.0	61.4	46.5	8 500	64.8	46.1	9 000	68.3	45.0	8 900*	28.0
32.0	56.1	43.9	6 700	59.5	43.4	7 000	62.8	42.3	7 400	32.0
36.0	50.4	40.7	5 200	53.8	40.2	5 500	56.9	39.0	5 800	36.0
40.0	44.2	36.8	4 100	47.5	36.2	4 300	50.4	34.9	4 600	40.0
44.0	37.2	31.9	3 200	40.3	31.2	3 400				44.0
48.0	28.6	25.3	2 500							48.0
36.6m (120 Ft.) BOOM										
12.2	80.7	55.7	13 600 *							12.2
14.0	78.8	55.3	13 600 *							14.0
16.0	76.7	54.8	13 600 *	80.1	54.4	12 500*				16.0
18.0	74.5	54.2	13 300 *	77.9	53.8	12 200*				18.0
20.0	72.3	53.6	13 000 *	75.7	53.1	11 800*	79.1	52.2	10 800*	20.0
22.0	70.1	52.8	12 400	73.4	52.4	11 600*	76.8	51.4	10 500*	22.0
24.0	67.8	52.0	10 800	71.1	51.5	11 200	74.5	50.5	10 100*	24.0
26.0	65.5	51.1	9 500	68.8	50.6	10 000	72.1	49.6	9 600*	26.0
28.0	63.1	50.0	8 300	66.4	49.5	8 800	69.7	48.5	9 100	28.0
32.0	58.3	47.6	6 500	61.5	47.1	6 800	64.6	46.0	7 300	32.0
36.0	53.1	44.7	5 100	56.3	44.2	5 300	59.2	43.0	5 700	36.0
40.0	47.5	41.2	3 900	50.6	40.6	4 200	53.4	39.3	4 400	40.0
44.0	41.4	36.9	3 000	44.3	36.2	3 200	46.9	34.7	3 400	44.0
48.0	34.3	31.4	2 300	37.1	30.6	2 400				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m (60 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
13.7	79.7	58.5	13 600 *							13.7
14.0	79.4	58.4	13 600 *							14.0
16.0	77.4	58.0	13 600 *							16.0
18.0	75.3	57.4	13 400 *	78.5	57.0	12 300*				18.0
20.0	73.3	56.8	13 100	76.4	56.3	12 000*	79.7	55.3	10 900*	20.0
22.0	71.2	56.1	11 900	74.3	55.6	11 600*	77.6	54.6	10 600*	22.0
24.0	69.0	55.3	10 400	72.2	54.8	11 000	75.4	53.8	10 300*	24.0
26.0	66.9	54.4	9 200	70.0	54.0	9 800	73.1	52.9	9 800*	26.0
28.0	64.7	53.5	8 100	67.8	53.0	8 600	70.9	51.9	9 200	28.0
32.0	60.1	51.2	6 300	63.2	50.7	6 700	66.2	49.6	7 100	32.0
36.0	55.4	48.5	4 900	58.4	48.0	5 200	61.3	46.8	5 500	36.0
40.0	50.3	45.3	3 700	53.2	44.8	4 000	56.0	43.5	4 300	40.0
44.0	44.8	41.5	2 800	47.7	40.8	3 000	50.2	39.4	3 300	44.0
48.0	38.6	36.7	2 000	41.4	36.0	2 200				48.0
42.7m (140 Ft.) BOOM										
13.7	80.2	61.6	13 600 *							13.7
14.0	80.0	61.5	13 600 *							14.0
16.0	78.0	61.1	13 600 *							16.0
18.0	76.1	60.6	13 600 *	79.1	60.1	12 400*				18.0
20.0	74.1	60.0	13 200	77.2	59.5	12 100*	80.3	58.5	10 900*	20.0
22.0	72.1	59.3	11 500	75.2	58.9	11 700	78.2	57.8	10 700*	22.0
24.0	70.1	58.6	10 100	73.1	58.1	10 800	76.2	57.1	10 500*	24.0
26.0	68.1	57.8	8 900	71.1	57.3	9 500	74.1	56.2	10 000	26.0
28.0	66.0	56.9	7 900	69.0	56.4	8 400	72.0	55.3	9 000	28.0
32.0	61.8	54.8	6 100	64.7	54.3	6 500	67.6	53.1	7 000	32.0
36.0	57.4	52.3	4 700	60.2	51.7	5 000	63.0	50.6	5 400	36.0
40.0	52.7	49.3	3 600	55.5	48.8	3 800	58.1	47.5	4 200	40.0
44.0	47.7	45.8	2 700	50.4	45.2	2 900	52.9	43.8	3 100	44.0
48.0	42.2	41.6	1 900	44.9	40.9	2 100	47.2	39.4	2 300	48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m (60 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
13.7	80.7	64.7	13 600 *							13.7
14.0	80.4	64.7	13 600 *							14.0
16.0	78.6	64.2	13 600 *							16.0
18.0	76.8	63.7	13 600 *	79.7	63.3	12 500*				18.0
20.0	74.9	63.2	12 800	77.8	62.7	12 200*	80.8	61.7	11 000*	20.0
22.0	73.0	62.6	11 100	75.9	62.1	11 700	78.8	61.0	10 800*	22.0
24.0	71.1	61.9	9 700	74.0	61.4	10 400	76.9	60.3	10 500*	24.0
26.0	69.2	61.1	8 600	72.1	60.6	9 200	74.9	59.5	9 800	26.0
28.0	67.3	60.2	7 600	70.1	59.7	8 100	72.9	58.6	8 700	28.0
32.0	63.3	58.3	5 900	66.1	57.7	6 300	68.8	56.6	6 800	32.0
36.0	59.1	55.9	4 500	61.9	55.4	4 900	64.5	54.2	5 200	36.0
40.0	54.8	53.2	3 300	57.5	52.6	3 700	60.0	51.4	4 000	40.0
44.0	50.2	49.9	2 400	52.8	49.3	2 700	55.2	48.0	3 000	44.0
48.0				47.8	45.5	1 900	50.1	44.0	2 100	48.0
48.8m (160 Ft.) BOOM										
15.2	79.8	67.5	13 600 *							15.2
16.0	79.1	67.4	13 600 *							16.0
18.0	77.4	66.9	13 600 *							18.0
20.0	75.6	66.4	12 300	78.4	65.9	12 300				20.0
22.0	73.8	65.8	10 700	76.6	65.3	11 600	79.4	64.2	10 800*	22.0
24.0	72.0	65.1	9 400	74.8	64.6	10 000	77.5	63.5	10 600	24.0
26.0	70.2	64.4	8 200	72.9	63.9	8 800	75.7	62.8	9 500	26.0
28.0	68.4	63.5	7 200	71.1	63.0	7 800	73.8	61.9	8 400	28.0
32.0	64.6	61.7	5 600	67.3	61.2	6 100	69.9	60.0	6 600	32.0
36.0	60.7	59.5	4 300	63.3	59.0	4 700	65.9	57.8	5 100	36.0
40.0	56.6	56.9	3 200	59.2	56.4	3 500	61.7	55.1	3 800	40.0
44.0	52.3	53.9	2 300	54.9	53.3	2 500	57.3	52.0	2 800	44.0
48.0							52.5	48.4	2 000	48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
15.2	80.2	70.6	13 600 *							15.2
16.0	79.6	70.5	13 600 *							16.0
18.0	77.9	70.0	13 600 *							18.0
20.0	76.3	69.5	11 900	78.9	69.0	12 300				20.0
22.0	74.6	68.9	10 300	77.2	68.5	11 100	79.9	67.4	10 900*	22.0
24.0	72.8	68.3	9 000	75.5	67.8	9 700	78.1	66.7	10 400	24.0
26.0	71.1	67.6	7 900	73.7	67.1	8 500	76.3	66.0	9 200	26.0
28.0	69.4	66.8	6 900	71.9	66.3	7 500	74.5	65.2	8 100	28.0
32.0	65.8	65.1	5 300	68.3	64.6	5 800	70.9	63.4	6 300	32.0
36.0	62.1	63.0	4 000	64.6	62.5	4 400	67.1	61.3	4 900	36.0
40.0	58.3	60.6	2 900	60.8	60.0	3 300	63.2	58.8	3 700	40.0
44.0	54.3	57.8	2 000	56.7	57.2	2 300	59.0	55.9	2 700	44.0




Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom

10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m (70 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.4m (90 Ft.) BOOM										
12.2	79.4	49.5	11 900 *							12.2
14.0	77.2	49.1	11 500 *							14.0
16.0	74.7	48.5	11 100 *	79.2	48.1	10 300*				16.0
18.0	72.3	47.8	10 800 *	76.8	47.5	10 000*				18.0
20.0	69.8	47.1	10 400 *	74.2	46.7	9 700*	78.8	45.8	8 900*	20.0
22.0	67.2	46.2	10 100 *	71.6	45.8	9 400*	76.2	44.9	8 700*	22.0
24.0	64.6	45.3	9 800 *	69.0	44.9	9 100*	73.5	43.9	8 400*	24.0
26.0	61.9	44.2	9 500 *	66.3	43.8	8 800*	70.8	42.8	7 900*	26.0
28.0	59.2	43.0	9 000	63.5	42.5	8 600*	67.9	41.5	7 500*	28.0
32.0	53.4	40.1	7 100	57.7	39.7	7 500	61.9	38.6	6 700*	32.0
36.0	47.1	36.6	5 700	51.3	36.1	6 000	55.3	34.9	6 100*	36.0
40.0	40.1	32.2	4 600	44.2	31.6	4 800	47.9	30.1	5 100	40.0
44.0	31.8	26.3	3 700	35.6	25.5	3 900				44.0
30.5m (100 Ft.) BOOM										
12.2	80.0	52.6	12 000 *							12.2
14.0	78.0	52.2	11 700 *							14.0
16.0	75.7	51.7	11 300 *	79.9	51.3	10 400*				16.0
18.0	73.4	51.1	11 000 *	77.6	50.7	10 100*				18.0
20.0	71.0	50.4	10 600 *	75.2	49.9	9 800*	79.6	49.0	9 000*	20.0
22.0	68.6	49.6	10 300 *	72.8	49.1	9 500*	77.1	48.2	8 800*	22.0
24.0	66.2	48.7	10 000 *	70.4	48.2	9 200*	74.6	47.2	8 500*	24.0
26.0	63.7	47.7	9 700	67.9	47.2	9 000*	72.1	46.2	8 100*	26.0
28.0	61.2	46.5	8 900	65.3	46.1	8 700*	69.4	45.0	7 700*	28.0
32.0	55.9	43.9	7 000	60.0	43.5	7 300	64.0	42.4	6 900*	32.0
36.0	50.3	40.8	5 600	54.3	40.3	5 900	58.1	39.0	6 200	36.0
40.0	44.1	36.9	4 500	48.0	36.3	4 700	51.6	34.9	5 000	40.0
44.0	37.0	31.9	3 600	40.8	31.2	3 800	44.0	29.6	3 900	44.0
48.0	28.5	25.3	2 800	32.0	24.4	2 900				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m (70 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m (110 Ft.) BOOM										
12.2	80.6	55.7	12 100 *							12.2
14.0	78.6	55.3	11 800 *							14.0
16.0	76.5	54.8	11 400 *							16.0
18.0	74.3	54.3	11 100 *	78.3	53.8	10 200*				18.0
20.0	72.1	53.6	10 800 *	76.1	53.2	9 900*	80.2	52.2	9 000*	20.0
22.0	69.9	52.8	10 500 *	73.8	52.4	9 600*	77.9	51.4	8 800*	22.0
24.0	67.6	52.0	10 200 *	71.5	51.6	9 400*	75.6	50.5	8 600*	24.0
26.0	65.3	51.1	9 800	69.2	50.6	9 100*	73.2	49.6	8 300*	26.0
28.0	63.0	50.0	8 600	66.8	49.6	8 800	70.8	48.5	7 900*	28.0
32.0	58.1	47.6	6 800	61.9	47.2	7 200	65.7	46.0	7 100*	32.0
36.0	52.9	44.7	5 400	56.7	44.2	5 700	60.4	43.0	6 100	36.0
40.0	47.4	41.2	4 200	51.1	40.7	4 500	54.5	39.3	4 800	40.0
44.0	41.2	36.9	3 300	44.8	36.3	3 600	48.0	34.8	3 800	44.0
48.0	34.1	31.4	2 600	37.6	30.7	2 800				48.0
52.0	25.3	24.0	2 000							52.0
36.6m (120 Ft.) BOOM										
13.7	79.5	58.5	11 900 *							13.7
14.0	79.3	58.5	11 900 *							14.0
16.0	77.2	58.0	11 600 *							16.0
18.0	75.2	57.4	11 200 *	78.9	57.0	10 300*				18.0
20.0	73.1	56.8	10 900 *	76.9	56.4	10 000*	80.8	55.4	9 100*	20.0
22.0	71.0	56.1	10 600 *	74.7	55.7	9 700*	78.6	54.6	8 900*	22.0
24.0	68.9	55.3	10 300 *	72.6	54.9	9 500*	76.4	53.8	8 700*	24.0
26.0	66.7	54.5	9 600	70.4	54.0	9 200*	74.2	52.9	8 500*	26.0
28.0	64.5	53.5	8 400	68.2	53.0	8 900	71.9	51.9	8 000*	28.0
32.0	60.0	51.3	6 600	63.6	50.8	7 000	67.2	49.6	7 300*	32.0
36.0	55.2	48.6	5 200	58.8	48.1	5 500	62.3	46.9	5 900	36.0
40.0	50.1	45.4	4 000	53.7	44.8	4 300	57.0	43.5	4 700	40.0
44.0	44.6	41.5	3 200	48.1	40.9	3 400	51.2	39.5	3 700	44.0
48.0	38.5	36.8	2 400	41.8	36.1	2 600	44.7	34.4	2 800	48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m (70 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
13.7	80.1	61.6	12 100 *							13.7
14.0	79.8	61.6	12 000 *							14.0
16.0	77.9	61.1	11 700 *							16.0
18.0	75.9	60.6	11 300 *	79.5	60.2	10 300 *				18.0
20.0	74.0	60.0	11 000 *	77.5	59.6	10 100 *				20.0
22.0	72.0	59.4	10 800 *	75.5	58.9	9 800 *	79.2	57.8	9 000 *	22.0
24.0	70.0	58.6	10 300	73.5	58.2	9 600 *	77.2	57.1	8 800 *	24.0
26.0	68.0	57.8	9 200	71.5	57.3	9 400	75.1	56.2	8 600 *	26.0
28.0	65.9	56.9	8 200	69.4	56.4	8 800	72.9	55.3	8 200 *	28.0
32.0	61.6	54.8	6 300	65.1	54.3	6 800	68.6	53.2	7 300	32.0
36.0	57.2	52.3	4 900	60.6	51.8	5 300	64.0	50.6	5 800	36.0
40.0	52.5	49.3	3 800	55.9	48.8	4 200	59.1	47.5	4 500	40.0
44.0	47.5	45.8	2 900	50.8	45.2	3 200	53.9	43.8	3 500	44.0
48.0	42.1	41.6	2 200	45.3	41.0	2 400	48.2	39.4	2 600	48.0
42.7m (140 Ft.) BOOM										
13.7	80.5	64.7	12 200 *							13.7
14.0	80.3	64.7	12 100 *							14.0
16.0	78.5	64.2	11 800 *							16.0
18.0	76.6	63.8	11 500 *							18.0
20.0	74.8	63.2	11 200 *	78.2	62.8	10 200 *				20.0
22.0	72.9	62.6	10 900 *	76.3	62.1	9 900 *	79.8	61.0	9 000 *	22.0
24.0	71.0	61.9	10 200	74.4	61.4	9 700 *	77.8	60.3	8 800 *	24.0
26.0	69.1	61.1	8 900	72.4	60.6	9 400	75.8	59.5	8 700 *	26.0
28.0	67.1	60.2	7 900	70.5	59.8	8 500	73.8	58.6	8 400 *	28.0
32.0	63.1	58.3	6 200	66.4	57.8	6 700	69.7	56.6	7 200	32.0
36.0	59.0	55.9	4 800	62.3	55.4	5 200	65.5	54.2	5 600	36.0
40.0	54.6	53.2	3 700	57.9	52.7	4 000	61.0	51.4	4 400	40.0
44.0	50.0	50.0	2 800	53.2	49.4	3 000	56.2	48.0	3 400	44.0
48.0	45.1	46.1	2 000	48.2	45.5	2 300	51.0	44.0	2 500	48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m (70 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
13.7	81.0	67.8	12 200 *							13.7
14.0	80.7	67.8	12 200 *							14.0
16.0	79.0	67.4	11 900 *							16.0
18.0	77.2	66.9	11 600 *							18.0
20.0	75.5	66.4	11 300 *	78.7	65.9	10 200*				20.0
22.0	73.7	65.8	10 900	76.9	65.3	10 000*	80.3	64.2	9 100*	22.0
24.0	71.9	65.1	9 700	75.1	64.6	9 800*	78.4	63.5	8 900*	24.0
26.0	70.1	64.4	8 600	73.3	63.9	9 200	76.5	62.8	8 700*	26.0
28.0	68.2	63.6	7 600	71.4	63.1	8 200	74.7	61.9	8 500	28.0
32.0	64.4	61.7	5 900	67.6	61.2	6 400	70.8	60.0	7 000	32.0
36.0	60.6	59.5	4 600	63.7	59.0	5 000	66.8	57.8	5 500	36.0
40.0	56.5	56.9	3 400	59.6	56.4	3 800	62.6	55.1	4 200	40.0
44.0	52.2	53.9	2 500	55.3	53.4	2 900	58.1	52.0	3 200	44.0
48.0				50.7	49.8	2 100	53.4	48.4	2 300	48.0
48.8m (160 Ft.) BOOM										
15.2	80.1	70.6	12 100 *							15.2
16.0	79.5	70.5	11 900 *							16.0
18.0	77.8	70.0	11 700 *							18.0
20.0	76.1	69.5	11 400	79.2	69.1	10 300*				20.0
22.0	74.4	69.0	10 800	77.5	68.5	10 100*				22.0
24.0	72.7	68.3	9 300	75.8	67.9	9 900*	79.0	66.7	8 900*	24.0
26.0	71.0	67.6	8 200	74.0	67.2	8 900	77.2	66.0	8 700*	26.0
28.0	69.2	66.9	7 200	72.3	66.4	7 800	75.4	65.2	8 500	28.0
32.0	65.6	65.1	5 600	68.7	64.6	6 200	71.7	63.4	6 800	32.0
36.0	62.0	63.0	4 300	65.0	62.5	4 800	67.9	61.3	5 300	36.0
40.0	58.1	60.6	3 300	61.1	60.1	3 700	64.0	58.8	4 100	40.0
44.0	54.2	57.8	2 300	57.1	57.3	2 700	59.9	55.9	3 000	44.0
48.0				52.8	54.0	1 900	55.5	52.5	2 200	48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m (80 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.4m (90 Ft.) BOOM										
12.2	79.6	52.6	9 200 *							12.2
14.0	77.5	52.2	9 200 *							14.0
16.0	75.3	51.7	9 100 *	80.1	51.3	8 800*				16.0
18.0	72.9	51.1	9 000 *	77.8	50.7	8 500*				18.0
20.0	70.6	50.4	8 900 *	75.4	50.0	8 200*	80.6	49.1	7 500*	20.0
22.0	68.2	49.6	8 600 *	73.0	49.2	7 900*	78.1	48.3	7 300*	22.0
24.0	65.8	48.7	8 300 *	70.6	48.3	7 700*	75.6	47.3	7 100*	24.0
26.0	63.3	47.7	8 000 *	68.1	47.3	7 400*	73.1	46.3	6 900*	26.0
28.0	60.8	46.6	7 700 *	65.6	46.2	7 200*	70.5	45.2	6 700*	28.0
32.0	55.5	44.0	7 100	60.2	43.6	6 800*	65.0	42.5	6 000*	32.0
36.0	49.9	40.8	5 700	54.5	40.3	6 100	59.1	39.2	5 400*	36.0
40.0	43.7	36.9	4 600	48.3	36.4	4 900	52.6	35.1	4 900*	40.0
44.0	36.6	31.9	3 800	41.1	31.4	3 900	45.2	29.8	4 200	44.0
48.0	28.1	25.3	3 000	32.4	24.6	3 200				48.0
30.5m (100 Ft.) BOOM										
12.2	80.2	55.7	9 300 *							12.2
14.0	78.2	55.3	9 200 *							14.0
16.0	76.1	54.9	9 100 *							16.0
18.0	73.9	54.3	9 000 *	78.5	53.9	8 600*				18.0
20.0	71.7	53.6	8 900 *	76.3	53.2	8 300*				20.0
22.0	69.5	52.9	8 800 *	74.1	52.5	8 000*	78.8	51.5	7 400*	22.0
24.0	67.2	52.0	8 400 *	71.8	51.6	7 800*	76.5	50.6	7 200*	24.0
26.0	64.9	51.1	8 200 *	69.5	50.7	7 600*	74.1	49.7	7 000*	26.0
28.0	62.6	50.1	7 900 *	67.1	49.7	7 300*	71.7	48.6	6 800*	28.0
32.0	57.7	47.7	7 000	62.2	47.2	6 900*	66.7	46.1	6 200*	32.0
36.0	52.5	44.8	5 600	57.0	44.3	5 900	61.3	43.1	5 600*	36.0
40.0	47.0	41.2	4 500	51.3	40.8	4 800	55.5	39.5	5 100	40.0
44.0	40.8	36.9	3 600	45.1	36.4	3 800	49.0	34.9	4 100	44.0
48.0	33.8	31.5	2 900	37.9	30.8	3 000				48.0
52.0	24.9	24.0	2 200							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m (110 Ft.) BOOM										
12.2	80.7	58.8	9 300 *							12.2
14.0	78.9	58.5	9 200 *							14.0
16.0	76.8	58.0	9 100 *							16.0
18.0	74.8	57.5	9 000 *	79.1	57.1	8 600 *				18.0
20.0	72.7	56.8	9 000 *	77.1	56.5	8 400 *				20.0
22.0	70.6	56.1	8 900 *	74.9	55.7	8 100 *	79.5	54.7	7 400 *	22.0
24.0	68.5	55.3	8 600 *	72.8	55.0	7 900 *	77.3	53.9	7 200 *	24.0
26.0	66.3	54.5	8 300 *	70.6	54.1	7 700 *	75.1	53.0	7 000 *	26.0
28.0	64.1	53.5	8 100 *	68.4	53.1	7 500 *	72.8	52.0	6 800 *	28.0
32.0	59.6	51.3	6 800	63.8	50.8	7 100 *	68.1	49.7	6 300 *	32.0
36.0	54.8	48.6	5 400	59.0	48.1	5 800	63.2	46.9	5 800 *	36.0
40.0	49.8	45.4	4 300	53.9	44.9	4 600	57.9	43.6	4 900	40.0
44.0	44.3	41.5	3 300	48.3	41.0	3 600	52.2	39.6	3 900	44.0
48.0	38.1	36.8	2 600	42.1	36.2	2 800	45.7	34.5	3 100	48.0
52.0	31.0	30.7	2 000	34.8	30.0	2 100				52.0
36.6m (120 Ft.) BOOM										
13.7	79.7	61.6	9 200 *							13.7
14.0	79.4	61.6	9 200 *							14.0
16.0	77.5	61.1	9 200 *							16.0
18.0	75.6	60.6	9 100 *	79.7	60.2	8 700 *				18.0
20.0	73.6	60.0	9 000 *	77.7	59.6	8 500 *				20.0
22.0	71.6	59.4	8 900 *	75.7	59.0	8 200 *	80.1	57.9	7 500 *	22.0
24.0	69.6	58.6	8 800 *	73.7	58.2	8 000 *	78.0	57.2	7 300 *	24.0
26.0	67.6	57.8	8 500 *	71.7	57.4	7 800 *	75.9	56.3	7 100 *	26.0
28.0	65.5	56.9	8 200	69.6	56.5	7 600 *	73.8	55.4	6 900 *	28.0
32.0	61.3	54.8	6 600	65.3	54.4	7 100	69.4	53.2	6 500 *	32.0
36.0	56.9	52.3	5 200	60.9	51.9	5 600	64.8	50.7	5 900	36.0
40.0	52.2	49.4	4 100	56.1	48.9	4 400	60.0	47.6	4 800	40.0
44.0	47.2	45.9	3 200	51.1	45.3	3 400	54.8	43.9	3 800	44.0
48.0	41.7	41.6	2 400	45.5	41.1	2 700	49.0	39.5	2 900	48.0
52.0				39.3	35.8	2 000	42.5	34.0	2 200	52.0




Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom

10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m (80 Ft.) JIB


Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
13.7	80.2	64.7	9 300 *							13.7
14.0	80.0	64.7	9 300 *							14.0
16.0	78.1	64.3	9 200 *							16.0
18.0	76.3	63.8	9 100 *							18.0
20.0	74.4	63.2	9 100 *	78.3	62.8	8 500*				20.0
22.0	72.5	62.6	9 000 *	76.5	62.2	8 300*				22.0
24.0	70.6	61.9	8 900 *	74.5	61.5	8 100*	78.6	60.4	7 300*	24.0
26.0	68.7	61.1	8 600	72.6	60.7	7 900*	76.6	59.6	7 200*	26.0
28.0	66.8	60.3	8 100	70.7	59.8	7 700*	74.6	58.7	7 000*	28.0
32.0	62.8	58.3	6 300	66.6	57.9	6 900	70.5	56.7	6 700*	32.0
36.0	58.6	56.0	4 900	62.5	55.5	5 400	66.3	54.3	5 900	36.0
40.0	54.3	53.2	3 800	58.1	52.7	4 200	61.8	51.4	4 600	40.0
44.0	49.7	50.0	2 900	53.4	49.5	3 300	57.0	48.1	3 600	44.0
48.0	44.7	46.2	2 200	48.4	45.6	2 400	51.8	44.1	2 700	48.0
52.0							46.1	39.3	2 000	52.0
42.7m (140 Ft.) BOOM										
13.7	80.7	67.8	9 300 *							13.7
14.0	80.4	67.8	9 300 *							14.0
16.0	78.7	67.4	9 200 *							16.0
18.0	76.9	66.9	9 200 *							18.0
20.0	75.1	66.4	9 100 *	78.9	66.0	8 600*				20.0
22.0	73.4	65.8	9 000 *	77.1	65.4	8 400*				22.0
24.0	71.6	65.1	8 900 *	75.3	64.7	8 200*	79.2	63.6	7 400*	24.0
26.0	69.7	64.4	8 800	73.5	64.0	8 000*	77.3	62.8	7 200*	26.0
28.0	67.9	63.6	7 800	71.6	63.1	7 800*	75.4	62.0	7 100*	28.0
32.0	64.1	61.7	6 200	67.8	61.3	6 700	71.5	60.1	6 800*	32.0
36.0	60.2	59.5	4 800	63.9	59.1	5 200	67.5	57.8	5 800	36.0
40.0	56.2	57.0	3 700	59.8	56.5	4 100	63.3	55.2	4 500	40.0
44.0	51.9	54.0	2 800	55.5	53.5	3 100	58.9	52.1	3 500	44.0
48.0	47.4	50.5	2 000	50.9	49.9	2 300	54.2	48.4	2 600	48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 84
32 430 kg Crane Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind
thru 39.6m Boom
10 m/s with 42.7m thru 51.8m Boom
7 m/s with 54.9m Boom



555 SERIES 1

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
15.2	79.8	70.7	9 300 *							15.2
16.0	79.2	70.5	9 200 *							16.0
18.0	77.5	70.1	9 200 *							18.0
20.0	75.8	69.6	9 100 *	79.4	69.1	8 700 *				20.0
22.0	74.1	69.0	9 000 *	77.7	68.6	8 500 *				22.0
24.0	72.4	68.4	9 000 *	76.0	67.9	8 300 *	79.7	66.8	7 400 *	24.0
26.0	70.7	67.7	8 400	74.2	67.2	8 100 *	77.9	66.1	7 300 *	26.0
28.0	68.9	66.9	7 400	72.5	66.4	7 800	76.1	65.3	7 100 *	28.0
32.0	65.3	65.1	5 800	68.9	64.7	6 400	72.4	63.5	6 800 *	32.0
36.0	61.7	63.1	4 500	65.2	62.6	5 000	68.7	61.3	5 600	36.0
40.0	57.8	60.6	3 400	61.3	60.2	3 800	64.7	58.9	4 300	40.0
44.0	53.9	57.8	2 500	57.3	57.3	2 900	60.6	56.0	3 300	44.0
48.0				53.0	54.0	2 100	56.2	52.6	2 400	48.0
48.8m (160 Ft.) BOOM										
15.2	80.2	73.8	9 300 *							15.2
16.0	79.6	73.6	9 300 *							16.0
18.0	78.0	73.2	9 200 *							18.0
20.0	76.4	72.7	9 100 *	79.9	72.3	8 700 *				20.0
22.0	74.8	72.2	9 000 *	78.2	71.7	8 500 *				22.0
24.0	73.2	71.6	9 000	76.6	71.1	8 300 *				24.0
26.0	71.5	70.9	8 100	74.9	70.4	8 200 *	78.4	69.3	7 300 *	26.0
28.0	69.8	70.2	7 100	73.2	69.7	7 800	76.7	68.5	7 200 *	28.0
32.0	66.4	68.5	5 500	69.8	68.0	6 100	73.3	66.8	6 800	32.0
36.0	63.0	66.5	4 200	66.3	66.0	4 800	69.7	64.8	5 300	36.0
40.0	59.3	64.2	3 200	62.7	63.8	3 700	66.0	62.5	4 200	40.0
44.0	55.6	61.6	2 300	58.9	61.1	2 700	62.1	59.7	3 200	44.0
48.0				54.9	58.0	1 900	58.0	56.6	2 300	48.0