


# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

Meets  
ANSI B30.5  
Requirements



**LIFTING CAPACITIES:** Chart supplements boom capacity chart **No. 8462-AM**. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and do not exceed 85% of a static tipping load. Capacities based on structural competence are denoted by an asterisk (\*). Capacities indicated by a (b) require 2 010 kg minimum block weight with 4 part hoist line reeving on 12.2m jib and 3 part on 18.3m jib.

82.3m and 91.4m boom lengths require only the middle three sheaves to be used on lower boom point. All other sheaves must be removed from lower boom point.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc. beneath boom and jib point sheaves is considered part of jib load. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

**OPERATING CONDITIONS:** Machine to operate in a level position on a firm uniformly supporting surface with gantry up and outriggers fully extended (9 373 mm) and set. Refer to operators manual for outrigger positioning. Radii less than 12.8m not recommended when lifting over front of truck. Minimum boom angle over truck cab is 5 degrees.

**Note:** Set four main jacks first, then lower center front jack until it just contacts ground to prevent preloading of center front jack. Center front jack must be used when operating on outriggers.

Refer to boom rigging **No. A03746**, jib assembly **No. 192352**, Wire Rope Specification chart **No. 8464-A** and Counterweight Arrangement chart **No. 8469-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

**MACHINE TRAVEL:** Refer to Maximum Allowable Travel Specification chart **No. 8468-A** for machine travel without load.

**OPERATING RADIUS:** Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

**JIB POINT ELEVATION:** Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

**MACHINE EQUIPMENT:** Machine equipped with Manitowoc - Pierce T300 12 x 6 carrier, 7 976 mm wheel base, 3 505 mm front axle track, 2 946 mm rear axle track, 505/95R25 front tires, 445/95R25 rear tires, 4 686 mm outriggers, 8 534 mm retractable gantry, 12 part boom hoist reeving, two boom support straps and 80 560 kg counterweight.

Maximum capacity on 29mm wire rope is 13 610 kg per line.

Maximum Boom and Jib Lengths Lifted Unassisted Over Side or Rear of Extended Outriggers	
Boom Length	Jib No. 132
(a) 91.4m	—
88.4m	—
85.3m	—
82.3m	—
79.2m	18.3m
76.2m	24.4m
73.2m	30.5m
70.1m	36.6m
Load block, hook and weight ball on ground at start. (a) Upper boom point cannot be used on 91.4m boom.	




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>39.6m (130 Ft.) BOOM</b>										
12.2	80.5	54.8	45 300 *b							12.2
13.0	79.6	54.6	43 900 *b							13.0
14.0	78.4	54.4	42 300 *b							14.0
15.0	77.3	54.1	41 000 *b							15.0
16.0	76.2	53.9	39 800 *b	78.6	53.6	32 900 *b				16.0
18.0	73.9	53.3	37 600 *b	76.3	53.0	31 600 *b	78.7	52.2	25 300*	18.0
20.0	71.6	52.6	35 700 *b	74.0	52.3	30 300*	76.3	51.5	24 200*	20.0
22.0	69.2	51.8	33 900 *b	71.6	51.5	29 200*	73.9	50.7	23 200*	22.0
24.0	66.9	50.9	32 400 *b	69.2	50.6	28 200*	71.5	49.8	22 300*	24.0
26.0	64.4	50.0	31 100 *b	66.7	49.6	27 300*	69.0	48.8	21 400*	26.0
28.0	61.9	48.9	29 800 *	64.2	48.5	26 500*	66.4	47.7	20 700*	28.0
30.0	59.4	47.7	28 700 *	61.7	47.3	25 800*	63.8	46.5	20 000*	30.0
32.0	56.8	46.3	27 700 *	59.0	46.0	25 100*	61.1	45.1	19 400*	32.0
34.0	54.1	44.9	26 800 *	56.3	44.5	24 500*	58.3	43.6	18 800*	34.0
36.0	51.3	43.3	25 900 *	53.5	42.9	24 000*	55.4	41.9	18 400*	36.0
38.0	48.3	41.5	25 200 *	50.5	41.0	23 500*	52.4	40.0	17 900*	38.0
40.0	45.2	39.5	24 500 *	47.4	39.0	23 100*	49.2	38.0	17 500*	40.0
44.0	38.5	34.7	23 000 *	40.5	34.2	22 400*				44.0
48.0	30.4	28.5	19 000 *							48.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>42.7m (140 Ft.) BOOM</b>										
12.2	81.0	57.9	45 300 *b							12.2
13.0	80.1	57.7	44 300 *b							13.0
14.0	79.1	57.5	43 100 *b							14.0
15.0	78.0	57.3	41 800 *b							15.0
16.0	77.0	57.0	40 600 *b	79.2	56.7	33 300*b				16.0
18.0	74.8	56.5	38 400 *b	77.1	56.1	32 000*b	79.3	55.4	25 600*	18.0
20.0	72.6	55.8	36 500 *b	74.9	55.5	30 800*b	77.1	54.7	24 500*	20.0
22.0	70.4	55.1	34 800 *b	72.7	54.8	29 700*	74.9	54.0	23 500*	22.0
24.0	68.2	54.3	33 200 *b	70.4	53.9	28 700*	72.6	53.1	22 600*	24.0
26.0	65.9	53.4	31 900 *b	68.1	53.0	27 800*	70.3	52.2	21 800*	26.0
28.0	63.6	52.4	30 600 *b	65.8	52.0	27 000*	67.9	51.2	21 100*	28.0
30.0	61.3	51.2	29 500 *	63.4	50.9	26 300*	65.5	50.0	20 400*	30.0
32.0	58.9	50.0	28 500 *	61.0	49.6	25 600*	63.0	48.8	19 800*	32.0
34.0	56.4	48.7	27 500 *	58.5	48.3	25 000*	60.4	47.4	19 200*	34.0
36.0	53.8	47.2	26 700 *	55.9	46.8	24 400*	57.8	45.9	18 800*	36.0
38.0	51.1	45.6	25 900 *	53.2	45.1	23 900*	55.1	44.2	18 300*	38.0
40.0	48.4	43.8	25 200 *	50.4	43.3	23 500*	52.2	42.3	17 900*	40.0
44.0	42.4	39.6	23 200 *	44.4	39.1	22 700*	46.0	38.0	17 200*	44.0
48.0	35.6	34.4	19 400 *	37.5	33.8	19 800*				48.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>45.7m (150 Ft.) BOOM</b>										
13.7	79.9	60.7	44 200 *b							13.7
14.0	79.7	60.6	43 800 *b							14.0
15.0	78.7	60.4	42 600 *b							15.0
16.0	77.7	60.2	41 400 *b	79.8	59.8	33 700 *b				16.0
18.0	75.6	59.6	39 200 *b	77.8	59.3	32 400 *b				18.0
20.0	73.6	59.0	37 300 *b	75.7	58.7	31 200 *b	77.8	57.9	24 800 *	20.0
22.0	71.5	58.3	35 600 *b	73.6	58.0	30 200 *	75.7	57.2	23 900 *	22.0
24.0	69.4	57.6	34 100 *b	71.5	57.2	29 200 *	73.6	56.4	23 000 *	24.0
26.0	67.3	56.7	32 700 *b	69.4	56.4	28 300 *	71.4	55.6	22 200 *	26.0
28.0	65.1	55.8	31 400 *b	67.2	55.4	27 500 *	69.2	54.6	21 500 *	28.0
30.0	62.9	54.7	30 300 *	65.0	54.4	26 700 *	66.9	53.5	20 800 *	30.0
32.0	60.7	53.6	29 200 *	62.7	53.2	26 000 *	64.6	52.4	20 200 *	32.0
34.0	58.4	52.3	28 300 *	60.4	52.0	25 400 *	62.3	51.1	19 600 *	34.0
36.0	56.0	51.0	27 400 *	58.0	50.6	24 900 *	59.8	49.7	19 100 *	36.0
38.0	53.5	49.5	26 600 *	55.5	49.1	24 300 *	57.3	48.1	18 700 *	38.0
40.0	51.0	47.9	25 900 *	53.0	47.4	23 900 *	54.7	46.5	18 200 *	40.0
44.0	45.7	44.1	23 100 *	47.6	43.6	23 100 *	49.2	42.6	17 500 *	44.0
48.0	39.7	39.5	19 400 *	41.5	39.0	19 800 *				48.0
52.0	32.8	33.8	16 200 *	34.5	33.1	16 500 *				52.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>48.8m (160 Ft.) BOOM</b>										
13.7	80.4	63.8	44 900 *b							13.7
14.0	80.2	63.7	44 500 *b							14.0
15.0	79.2	63.5	43 300 *b							15.0
16.0	78.3	63.3	42 100 *b							16.0
18.0	76.4	62.8	40 000 *b	78.4	62.5	32 800*b				18.0
20.0	74.4	62.2	38 100 *b	76.4	61.9	31 600*b	78.5	61.1	25 200*	20.0
22.0	72.5	61.6	36 300 *b	74.5	61.2	30 600*b	76.5	60.4	24 200*	22.0
24.0	70.5	60.9	34 800 *b	72.5	60.5	29 600*	74.5	59.7	23 400*	24.0
26.0	68.5	60.0	33 400 *b	70.5	59.7	28 800*	72.4	58.9	22 600*	26.0
28.0	66.4	59.2	32 200 *b	68.4	58.8	27 900*	70.3	58.0	21 800*	28.0
30.0	64.4	58.2	31 000 *b	66.3	57.8	27 200*	68.2	57.0	21 200*	30.0
32.0	62.3	57.1	29 900 *	64.2	56.7	26 500*	66.1	55.9	20 600*	32.0
34.0	60.1	55.9	29 000 *	62.0	55.6	25 900*	63.9	54.7	20 000*	34.0
36.0	57.9	54.7	28 100 *	59.8	54.3	25 300*	61.6	53.4	19 500*	36.0
38.0	55.7	53.3	27 300 *	57.5	52.9	24 700*	59.3	52.0	19 000*	38.0
40.0	53.3	51.8	26 500 *	55.2	51.4	24 300*	56.9	50.4	18 600*	40.0
44.0	48.4	48.4	23 000 *	50.3	47.9	23 400*	51.8	46.9	17 800*	44.0
48.0	43.1	44.3	19 300 *	44.9	43.8	19 800*	46.3	42.6	17 200*	48.0
52.0	37.2	39.3	16 200 *	38.8	38.7	16 600*				52.0
56.0	30.2	32.9	13 500 *							56.0




**2250T**

# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>51.8m (170 Ft.) BOOM</b>										
13.7	80.9	66.9	45 300 *b							13.7
14.0	80.6	66.8	45 000 *b							14.0
15.0	79.7	66.6	43 900 *b							15.0
16.0	78.8	66.4	42 800 *b							16.0
18.0	77.0	66.0	40 600 *b	79.0	65.6	33 100 *b				18.0
20.0	75.2	65.4	38 800 *b	77.1	65.1	32 000 *b	79.1	64.3	25 500*	20.0
22.0	73.3	64.8	37 000 *b	75.2	64.4	31 000 *b	77.2	63.6	24 600*	22.0
24.0	71.4	64.1	35 500 *b	73.4	63.8	30 000*	75.3	62.9	23 700*	24.0
26.0	69.6	63.3	34 100 *b	71.5	63.0	29 200*	73.3	62.2	22 900*	26.0
28.0	67.6	62.5	32 900 *b	69.5	62.1	28 300*	71.4	61.3	22 200*	28.0
30.0	65.7	61.6	31 700 *b	67.6	61.2	27 600*	69.4	60.4	21 500*	30.0
32.0	63.7	60.6	30 700 *b	65.6	60.2	26 900*	67.3	59.3	21 000*	32.0
34.0	61.7	59.5	29 700 *	63.5	59.1	26 300*	65.3	58.2	20 400*	34.0
36.0	59.6	58.3	28 800 *	61.4	57.9	25 700*	63.2	57.0	19 900*	36.0
38.0	57.5	57.0	27 900 *	59.3	56.6	25 100*	61.0	55.7	19 400*	38.0
40.0	55.3	55.6	27 100 *	57.1	55.2	24 700*	58.8	54.3	18 900*	40.0
44.0	50.8	52.5	23 100 *	52.6	52.0	23 600*	54.1	51.0	18 100*	44.0
48.0	46.0	48.7	19 400 *	47.7	48.3	19 900*	49.1	47.2	17 500*	48.0
52.0	40.7	44.3	16 200 *	42.3	43.8	16 700*				52.0
56.0	34.7	38.8	13 600 *	36.3	38.2	13 900*				56.0
60.0	27.6	31.9	11 100 *							60.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>54.9m (180 Ft.) BOOM</b>										
15.2	80.0	69.7	44 300 *b							15.2
16.0	79.3	69.5	43 400 *b							16.0
18.0	77.6	69.1	41 300 *b	79.5	68.7	33 500 *b				18.0
20.0	75.9	68.6	39 500 *b	77.7	68.2	32 400 *b	79.6	67.4	25 700 *	20.0
22.0	74.1	68.0	37 800 *b	75.9	67.6	31 400 *b	77.8	66.8	24 800 *	22.0
24.0	72.3	67.3	36 200 *b	74.1	67.0	30 400 *	76.0	66.2	24 000 *	24.0
26.0	70.5	66.6	34 900 *b	72.3	66.3	29 500 *	74.1	65.4	23 200 *	26.0
28.0	68.7	65.8	33 600 *b	70.5	65.5	28 800 *	72.3	64.6	22 500 *	28.0
30.0	66.9	64.9	32 400 *b	68.6	64.6	28 000 *	70.4	63.7	21 900 *	30.0
32.0	65.0	64.0	31 300 *b	66.8	63.6	27 300 *	68.5	62.8	21 300 *	32.0
34.0	63.1	63.0	30 300 *b	64.8	62.6	26 700 *	66.5	61.7	20 700 *	34.0
36.0	61.1	61.8	29 400 *	62.9	61.5	26 100 *	64.6	60.6	20 200 *	36.0
38.0	59.2	60.6	28 600 *	60.9	60.2	25 600 *	62.5	59.3	19 700 *	38.0
40.0	57.1	59.3	27 100	58.9	58.9	25 100 *	60.5	58.0	19 200 *	40.0
44.0	52.9	56.4	22 900 *	54.6	56.0	23 600 *	56.2	55.0	18 500 *	44.0
48.0	48.5	53.0	19 200 *	50.1	52.5	19 800 *	51.6	51.5	17 800 *	48.0
52.0	43.7	48.9	16 100 *	45.3	48.4	16 600 *	46.6	47.3	17 000 *	52.0
56.0	38.4	44.1	13 500 *	39.9	43.6	13 900 *				56.0
60.0	32.3	38.2	11 200 *	33.8	37.6	11 400 *				60.0




# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements

**2250T**



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>57.9m (190 Ft.) BOOM</b>										
15.2	80.4	72.8	44 900 *b							15.2
16.0	79.8	72.7	44 000 *b							16.0
18.0	78.2	72.2	41 900 *b	79.9	71.9	33 800 *b				18.0
20.0	76.5	71.7	40 100 *b	78.3	71.4	32 700 *b	80.0	70.6	25 900*	20.0
22.0	74.8	71.2	38 400 *b	76.6	70.8	31 700 *b	78.3	70.0	25 100*	22.0
24.0	73.1	70.6	36 900 *b	74.9	70.2	30 800*	76.6	69.4	24 300*	24.0
26.0	71.4	69.9	35 500 *b	73.1	69.5	29 900*	74.9	68.7	23 500*	26.0
28.0	69.7	69.1	34 200 *b	71.4	68.7	29 100*	73.1	67.9	22 800*	28.0
30.0	67.9	68.3	33 100 *b	69.6	67.9	28 400*	71.3	67.1	22 200*	30.0
32.0	66.1	67.4	32 000 *b	67.8	67.0	27 700*	69.5	66.1	21 600*	32.0
34.0	64.3	66.4	31 000 *b	66.0	66.0	27 100*	67.7	65.2	21 000*	34.0
36.0	62.5	65.3	30 100 *	64.2	65.0	26 500*	65.8	64.1	20 500*	36.0
38.0	60.6	64.2	29 000	62.3	63.8	26 000*	63.9	62.9	20 000*	38.0
40.0	58.7	63.0	26 800	60.4	62.6	25 400*	61.9	61.7	19 600*	40.0
44.0	54.8	60.2	22 900	56.4	59.8	23 400	57.9	58.8	18 800*	44.0
48.0	50.7	57.1	19 200 *	52.3	56.6	19 700*	53.7	55.6	18 100*	48.0
52.0	46.3	53.4	16 100 *	47.8	52.9	16 500*	49.1	51.8	17 000*	52.0
56.0	41.5	49.0	13 400 *	43.0	48.5	13 800*	44.2	47.3	14 100*	56.0
60.0	36.2	43.8	11 100 *	37.6	43.2	11 400*				60.0
64.0	30.0	37.4	9 000 *	31.3	36.7	9 300*				64.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>61.0m (200 Ft.) BOOM</b>										
15.2	80.8	75.9	45 300 *b							15.2
16.0	80.2	75.8	44 500 *b							16.0
18.0	78.7	75.4	42 600 *b							18.0
20.0	77.1	74.9	40 700 *b	78.8	74.5	33 000*b	80.5	73.7	26 100*	20.0
22.0	75.5	74.3	39 100 *b	77.1	74.0	32 000*b	78.8	73.2	25 400*	22.0
24.0	73.8	73.7	37 500 *b	75.5	73.4	31 100*b	77.2	72.6	24 500*	24.0
26.0	72.2	73.1	36 100 *b	73.9	72.7	30 300*	75.5	71.9	23 800*	26.0
28.0	70.5	72.4	34 900 *b	72.2	72.0	29 500*	73.8	71.2	23 100*	28.0
30.0	68.9	71.6	33 700 *b	70.5	71.2	28 800*	72.1	70.4	22 500*	30.0
32.0	67.2	70.7	32 600 *b	68.8	70.4	28 100*	70.4	69.5	21 900*	32.0
34.0	65.5	69.8	31 600 *b	67.1	69.4	27 500*	68.7	68.6	21 300*	34.0
36.0	63.7	68.8	30 700 *	65.4	68.4	26 900*	66.9	67.5	20 800*	36.0
38.0	62.0	67.7	28 800	63.6	67.3	26 300*	65.1	66.4	20 300*	38.0
40.0	60.2	66.6	26 400	61.8	66.2	25 800*	63.3	65.3	19 900*	40.0
44.0	56.5	64.0	22 500	58.1	63.6	23 000	59.5	62.6	19 100*	44.0
48.0	52.6	61.0	19 000 *	54.2	60.6	19 600*	55.5	59.6	18 400*	48.0
52.0	48.5	57.6	15 900 *	50.0	57.1	16 400*	51.3	56.0	16 800*	52.0
56.0	44.1	53.6	13 200 *	45.6	53.1	13 600*	46.8	51.9	14 000*	56.0
60.0	39.4	48.9	10 900 *	40.8	48.4	11 200*				60.0
64.0	34.0	43.3	8 900 *	35.4	42.7	9 200*				64.0
68.0	27.7	36.3	7 000 *							68.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>64.0m (210 Ft.) BOOM</b>										
16.8	80.1	78.7	40 800 * <b>b</b>							16.8
18.0	79.1	78.5	40 800 * <b>b</b>							18.0
20.0	77.6	78.0	40 700 * <b>b</b>	79.2	77.7	33 300* <b>b</b>				20.0
22.0	76.0	77.5	39 700 * <b>b</b>	77.7	77.1	32 300* <b>b</b>	79.3	76.3	25 600*	22.0
24.0	74.5	76.9	38 100 * <b>b</b>	76.1	76.6	31 400* <b>b</b>	77.7	75.8	24 800*	24.0
26.0	72.9	76.3	36 800 * <b>b</b>	74.5	75.9	30 600*	76.1	75.1	24 000*	26.0
28.0	71.4	75.6	35 500 * <b>b</b>	73.0	75.3	29 800*	74.5	74.4	23 400*	28.0
30.0	69.8	74.9	34 300 * <b>b</b>	71.4	74.5	29 100*	72.9	73.7	22 800*	30.0
32.0	68.1	74.1	33 200 * <b>b</b>	69.7	73.7	28 400*	71.3	72.8	22 200*	32.0
34.0	66.5	73.2	32 200 * <b>b</b>	68.1	72.8	27 800*	69.6	71.9	21 600*	34.0
36.0	64.9	72.2	31 000 <b>b</b>	66.4	71.8	27 200*	67.9	71.0	21 100*	36.0
38.0	63.2	71.2	28 600	64.7	70.8	26 700*	66.2	69.9	20 600*	38.0
40.0	61.5	70.1	26 300	63.0	69.7	26 100	64.5	68.8	20 200*	40.0
44.0	58.0	67.7	22 400	59.5	67.2	22 900	60.9	66.3	19 400*	44.0
48.0	54.4	64.9	19 100 *	55.9	64.4	19 600	57.2	63.4	18 600*	48.0
52.0	50.5	61.7	16 000 *	52.0	61.2	16 500*	53.3	60.2	17 000*	52.0
56.0	46.5	58.0	13 300 *	47.9	57.5	13 800*	49.1	56.4	14 200*	56.0
60.0	42.1	53.7	11 000 *	43.5	53.2	11 400*	44.6	52.0	11 700*	60.0
64.0	37.3	48.7	9 000 *	38.7	48.1	9 300*				64.0
68.0	31.9	42.6	7 200 *	33.2	42.0	7 500*				68.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>67.1m (220 Ft.) BOOM</b>										
16.8	80.4	81.8	40 800 *b							16.8
18.0	79.5	81.6	40 800 *b							18.0
20.0	78.1	81.1	40 800 *b	79.6	80.8	33 600*b				20.0
22.0	76.6	80.7	40 400 *b	78.2	80.3	32 600*b	79.7	79.5	25 700*	22.0
24.0	75.1	80.1	38 700 *b	76.7	79.7	31 800*b	78.2	78.9	25 000*	24.0
26.0	73.6	79.5	37 400 *b	75.2	79.1	30 900*b	76.7	78.3	24 300*	26.0
28.0	72.1	78.9	36 100 *b	73.6	78.5	30 200*	75.2	77.6	23 600*	28.0
30.0	70.6	78.1	34 900 *b	72.1	77.8	29 400*	73.6	76.9	23 000*	30.0
32.0	69.0	77.4	33 800 *b	70.6	77.0	28 800*	72.0	76.1	22 400*	32.0
34.0	67.5	76.5	32 800 b	69.0	76.1	28 200*	70.5	75.3	21 900*	34.0
36.0	65.9	75.6	31 000 b	67.4	75.2	27 600*	68.9	74.3	21 400*	36.0
38.0	64.3	74.6	28 300 b	65.8	74.2	27 000*	67.2	73.3	20 900*	38.0
40.0	62.7	73.6	26 000	64.2	73.2	26 300	65.6	72.3	20 500*	40.0
44.0	59.4	71.3	22 100	60.8	70.9	22 600	62.2	69.9	19 600*	44.0
48.0	55.9	68.6	18 900	57.4	68.2	19 300	58.7	67.2	18 900*	48.0
52.0	52.3	65.6	15 800 *	53.8	65.2	16 300*	55.0	64.1	16 900*	52.0
56.0	48.6	62.2	13 100 *	50.0	61.7	13 600*	51.1	60.6	14 000*	56.0
60.0	44.5	58.2	10 800 *	45.9	57.7	11 200*	47.0	56.6	11 600*	60.0
64.0	40.2	53.7	8 800 *	41.5	53.1	9 200*				64.0
68.0	35.4	48.3	7 000 *	36.6	47.7	7 300*				68.0
72.0	29.9	41.8	5 400 *							72.0




**2250T**

# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
 Boom No. 44A With Heavy Lift Top  
 80 560 kg Counterweight  
 360 Degree Rating  
 On Extended Outriggers**

**Meets  
 ANSI B30.5  
 Requirements**



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>70.1m (230 Ft.) BOOM</b>										
16.8	80.8	84.9	40 800 *b							16.8
18.0	79.9	84.7	40 800 *b							18.0
20.0	78.5	84.3	40 800 *b	80.0	83.9	33 800*b				20.0
22.0	77.1	83.8	40 500 *b	78.6	83.4	32 900*b	80.1	82.6	25 900*	22.0
24.0	75.7	83.3	39 300 *b	77.2	82.9	32 000*b	78.7	82.1	25 300*	24.0
26.0	74.2	82.7	37 900 *b	75.7	82.3	31 200*b	77.2	81.5	24 500*	26.0
28.0	72.8	82.1	36 700 *b	74.3	81.7	30 500*	75.7	80.9	23 900*	28.0
30.0	71.3	81.4	35 500 *b	72.8	81.0	29 800*	74.3	80.2	23 300*	30.0
32.0	69.8	80.6	34 400 *b	71.3	80.3	29 100*	72.8	79.4	22 700*	32.0
34.0	68.4	79.8	32 900 *b	69.8	79.4	28 500*	71.2	78.6	22 100*	34.0
36.0	66.8	79.0	30 400 *b	68.3	78.6	27 900*	69.7	77.7	21 700*	36.0
38.0	65.3	78.0	28 000 b	66.8	77.6	27 300*	68.2	76.7	21 200*	38.0
40.0	63.8	77.0	25 700 b	65.2	76.6	26 400	66.6	75.7	20 700*	40.0
44.0	60.6	74.8	21 800	62.0	74.4	22 300	63.4	73.5	19 900*	44.0
48.0	57.4	72.3	18 600	58.8	71.9	19 000	60.0	70.9	19 100	48.0
52.0	54.0	69.5	15 600 *	55.4	69.0	16 200*	56.6	68.0	16 700	52.0
56.0	50.4	66.3	12 900 *	51.8	65.8	13 400*	53.0	64.7	13 900*	56.0
60.0	46.7	62.6	10 600 *	48.0	62.1	11 100*	49.1	61.0	11 400*	60.0
64.0	42.7	58.4	8 600 *	44.0	57.9	9 000*	45.0	56.6	9 300*	64.0
68.0	38.3	53.5	6 900 *	39.6	52.9	7 100*				68.0
72.0	33.5	47.8	5 200 *	34.7	47.1	5 500*				72.0
76.0	27.9	40.7	3 800 *							76.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>73.2m (240 Ft.) BOOM</b>										
18.3	80.1	87.7	40 800 *b							18.3
20.0	78.9	87.4	40 800 *b	80.4	87.0	34 100*b				20.0
22.0	77.6	86.9	40 700 *b	79.0	86.6	33 200*b	80.5	85.7	26 100*	22.0
24.0	76.2	86.4	39 900 *b	77.6	86.1	32 300*b	79.1	85.2	25 500*	24.0
26.0	74.8	85.9	38 400 *b	76.2	85.5	31 500*b	77.7	84.7	24 800*	26.0
28.0	73.4	85.3	37 200 *b	74.8	84.9	30 800*b	76.3	84.1	24 100*	28.0
30.0	72.0	84.6	36 000 *b	73.4	84.2	30 100*	74.8	83.4	23 500*	30.0
32.0	70.6	83.9	34 700 *b	72.0	83.5	29 400*	73.4	82.7	22 900*	32.0
34.0	69.2	83.1	32 000 *b	70.6	82.7	28 800*	72.0	81.9	22 400*	34.0
36.0	67.7	82.3	29 600 *b	69.1	81.9	28 200*	70.5	81.0	21 900*	36.0
38.0	66.3	81.4	27 400 *b	67.7	81.0	27 700*	69.0	80.1	21 400*	38.0
40.0	64.8	80.4	25 400 b	66.2	80.0	25 800	67.5	79.1	21 000*	40.0
44.0	61.8	78.3	21 400	63.2	77.9	22 000	64.4	77.0	20 200*	44.0
48.0	58.7	76.0	18 200	60.0	75.5	18 700	61.3	74.6	19 200	48.0
52.0	55.5	73.3	15 300 *	56.8	72.8	16 000	58.0	71.8	16 300	52.0
56.0	52.1	70.2	12 700 *	53.4	69.8	13 200*	54.6	68.7	13 700*	56.0
60.0	48.6	66.8	10 400 *	49.9	66.3	10 800*	51.0	65.2	11 200*	60.0
64.0	44.9	62.9	8 300 *	46.1	62.4	8 800*	47.2	61.2	9 100*	64.0
68.0	40.9	58.4	6 600 *	42.1	57.9	6 900*				68.0
72.0	36.5	53.2	5 000 *	37.7	52.6	5 300*				72.0
76.0	31.6	47.1	3 600 *	32.7	46.4	3 800*				76.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>76.2m (250 Ft.) BOOM</b>										
18.3	80.4	90.8	40 800 *b							18.3
20.0	79.3	90.5	40 800 *b	80.7	90.1	34 300*b				20.0
22.0	78.0	90.1	40 800 *b	79.4	89.7	33 400*b				22.0
24.0	76.7	89.6	40 200 *b	78.1	89.2	32 600*b	79.5	88.4	25 600*	24.0
26.0	75.3	89.0	39 000 *b	76.7	88.7	31 800*b	78.1	87.8	25 000*	26.0
28.0	74.0	88.5	37 700 *b	75.4	88.1	31 000*b	76.8	87.2	24 300*	28.0
30.0	72.6	87.8	36 500 *b	74.0	87.4	30 400*	75.4	86.6	23 700*	30.0
32.0	71.3	87.1	34 100 *b	72.7	86.8	29 700*	74.0	85.9	23 200*	32.0
34.0	69.9	86.4	31 400 *b	71.3	86.0	29 100*	72.6	85.1	22 600*	34.0
36.0	68.5	85.6	29 000 *b	69.9	85.2	28 500*	71.2	84.3	22 200*	36.0
38.0	67.1	84.7	26 900 *b	68.5	84.3	27 300*	69.8	83.5	21 700*	38.0
40.0	65.7	83.8	25 000 *b	67.1	83.4	25 400*	68.4	82.5	21 200*	40.0
44.0	62.8	81.8	21 300	64.2	81.4	21 900	65.4	80.5	20 400*	44.0
48.0	59.9	79.5	18 100	61.2	79.1	18 600	62.4	78.2	19 100	48.0
52.0	56.8	77.0	15 400 *	58.1	76.5	15 800	59.3	75.6	16 300	52.0
56.0	53.6	74.1	12 700 *	54.9	73.6	13 200*	56.1	72.6	13 700*	56.0
60.0	50.3	70.9	10 400 *	51.6	70.4	10 800*	52.7	69.3	11 300*	60.0
64.0	46.8	67.2	8 400 *	48.1	66.7	8 800*	49.1	65.6	9 200*	64.0
68.0	43.1	63.1	6 600 *	44.3	62.5	7 000*	45.3	61.3	7 200*	68.0
72.0	39.1	58.3	5 000 *	40.3	57.7	5 300*				72.0
76.0	34.8	52.8	3 600 *	35.9	52.2	3 900*				76.0
80.0	29.8	46.2	2 300 *							80.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>79.2m (260 Ft.) BOOM</b>										
18.3	80.8	93.9	40 800 *b							18.3
20.0	79.7	93.6	40 800 *b							20.0
22.0	78.4	93.2	40 800 *b	79.8	92.8	33 600 *b				22.0
24.0	77.1	92.7	40 600 *b	78.5	92.4	32 800 *b	79.8	91.5	25 800 *	24.0
26.0	75.8	92.2	39 500 *b	77.2	91.8	32 100 *b	78.5	91.0	25 200 *	26.0
28.0	74.5	91.6	38 300 *b	75.9	91.3	31 300 *b	77.2	90.4	24 500 *	28.0
30.0	73.2	91.0	36 400 *b	74.6	90.7	30 700 *	75.9	89.8	24 000 *	30.0
32.0	71.9	90.4	33 300 *b	73.3	90.0	30 000 *	74.6	89.1	23 400 *	32.0
34.0	70.6	89.7	30 600 *b	71.9	89.3	29 400 *	73.2	88.4	22 900 *	34.0
36.0	69.3	88.9	28 200 *b	70.6	88.5	28 500 *	71.9	87.6	22 400 *	36.0
38.0	67.9	88.1	26 200 *b	69.2	87.7	26 600 *	70.5	86.8	21 900 *	38.0
40.0	66.6	87.2	24 200 *b	67.9	86.8	24 600 *	69.1	85.9	21 500 *	40.0
44.0	63.8	85.3	20 900 *b	65.1	84.8	21 300 *	66.3	83.9	20 700 *	44.0
48.0	61.0	83.1	17 800	62.3	82.7	18 200	63.4	81.7	18 800	48.0
52.0	58.1	80.6	15 100	59.3	80.2	15 500	60.5	79.2	15 900	52.0
56.0	55.0	77.9	12 400 *	56.3	77.4	13 000 *	57.4	76.4	13 500	56.0
60.0	51.9	74.8	10 100 *	53.1	74.4	10 600 *	54.2	73.3	11 100 *	60.0
64.0	48.6	71.4	8 100 *	49.8	70.9	8 500 *	50.8	69.8	8 900 *	64.0
68.0	45.2	67.5	6 300 *	46.3	67.0	6 700 *	47.3	65.8	7 100 *	68.0
72.0	41.5	63.1	4 800 *	42.6	62.6	5 100 *				72.0
76.0	37.5	58.1	3 400 *	38.6	57.5	3 700 *				76.0
80.0	33.0	52.2	2 100 *	34.1	51.5	2 300 *				80.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>39.6m (130 Ft.) BOOM</b>										
15.2	79.8	60.3	32 800 *b							15.2
16.0	79.0	60.1	32 500 *b							16.0
18.0	77.0	59.6	31 600 *							18.0
20.0	75.0	59.0	30 800 *	78.1	58.4	26 300*				20.0
22.0	72.9	58.3	30 000 *	76.0	57.7	25 900*	79.2	56.6	18 800*	22.0
24.0	70.8	57.5	29 300 *	73.9	56.9	25 400*	77.1	55.8	18 000*	24.0
26.0	68.6	56.6	28 600 *	71.8	56.1	25 000*	74.9	54.9	17 200*	26.0
28.0	66.5	55.7	28 000 *	69.6	55.1	24 500*	72.6	53.9	16 600*	28.0
30.0	64.3	54.7	27 400 *	67.3	54.1	23 600*	70.3	52.8	16 000*	30.0
32.0	62.0	53.5	26 900 *	65.0	52.9	22 700*	68.0	51.6	15 400*	32.0
34.0	59.7	52.3	26 400 *	62.7	51.6	21 800*	65.6	50.3	14 900*	34.0
36.0	57.3	50.9	25 900 *	60.3	50.2	21 100*	63.1	48.9	14 400*	36.0
38.0	54.9	49.4	25 500 *	57.8	48.7	20 400*	60.5	47.3	14 000*	38.0
40.0	52.4	47.8	24 900 *	55.3	47.1	19 700*	57.9	45.6	13 600*	40.0
44.0	47.0	44.0	22 600 *	49.8	43.2	18 600*	52.2	41.7	12 900*	44.0
48.0	41.0	39.4	20 700 *	43.7	38.6	17 500*				48.0
52.0	34.1	33.6	18 000 *	36.6	32.6	16 500*				52.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>42.7m (140 Ft.) BOOM</b>										
15.2	80.3	63.4	33 100 * <b>b</b>							15.2
16.0	79.6	63.2	32 700 * <b>b</b>							16.0
18.0	77.7	62.7	31 900 *							18.0
20.0	75.7	62.2	31 100 *	78.7	61.6	26 500*				20.0
22.0	73.8	61.5	30 300 *	76.8	60.9	26 000*	79.8	59.8	19 000*	22.0
24.0	71.8	60.8	29 600 *	74.8	60.2	25 600*	77.8	59.0	18 200*	24.0
26.0	69.8	60.0	29 000 *	72.7	59.4	25 200*	75.7	58.2	17 500*	26.0
28.0	67.7	59.1	28 400 *	70.7	58.5	24 700*	73.6	57.3	16 900*	28.0
30.0	65.7	58.1	27 800 *	68.6	57.5	24 200*	71.4	56.2	16 200*	30.0
32.0	63.6	57.0	27 300 *	66.4	56.4	23 200*	69.3	55.1	15 700*	32.0
34.0	61.4	55.9	26 700 *	64.3	55.2	22 400*	67.0	53.9	15 200*	34.0
36.0	59.2	54.6	26 300 *	62.0	53.9	21 600*	64.7	52.6	14 700*	36.0
38.0	56.9	53.2	25 800 *	59.7	52.5	20 900*	62.4	51.2	14 300*	38.0
40.0	54.6	51.7	25 400 *	57.4	51.0	20 200*	59.9	49.6	13 900*	40.0
44.0	49.7	48.3	23 700 *	52.4	47.5	19 100*	54.8	46.0	13 200*	44.0
48.0	44.3	44.2	21 200 *	47.0	43.3	18 000*	49.1	41.6	12 600*	48.0
52.0	38.4	39.2	18 000 *	40.8	38.2	17 100*				52.0
56.0	31.4	32.8	15 200 *							56.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>45.7m (150 Ft.) BOOM</b>										
15.2	80.8	66.5	33 200 * <b>b</b>							15.2
16.0	80.1	66.4	32 900 * <b>b</b>							16.0
18.0	78.3	65.9	32 100 *							18.0
20.0	76.4	65.3	31 400 *	79.3	64.8	26 700*				20.0
22.0	74.6	64.7	30 600 *	77.4	64.1	26 200*	80.3	62.9	19 200*	22.0
24.0	72.7	64.0	29 900 *	75.5	63.4	25 700*	78.4	62.2	18 500*	24.0
26.0	70.8	63.3	29 300 *	73.6	62.7	25 300*	76.4	61.4	17 700*	26.0
28.0	68.9	62.4	28 700 *	71.7	61.8	24 900*	74.5	60.6	17 100*	28.0
30.0	66.9	61.5	28 100 *	69.7	60.9	24 500*	72.4	59.6	16 500*	30.0
32.0	64.9	60.5	27 600 *	67.7	59.9	23 700*	70.4	58.6	16 000*	32.0
34.0	62.9	59.4	27 100 *	65.6	58.8	22 900*	68.3	57.5	15 500*	34.0
36.0	60.8	58.2	26 600 *	63.6	57.6	22 100*	66.1	56.2	15 000*	36.0
38.0	58.7	56.9	26 100 *	61.4	56.2	21 400*	64.0	54.9	14 600*	38.0
40.0	56.6	55.5	25 700 *	59.2	54.8	20 700*	61.7	53.4	14 200*	40.0
44.0	52.0	52.4	24 700 *	54.6	51.6	19 600*	57.0	50.1	13 500*	44.0
48.0	47.2	48.6	21 000 *	49.7	47.8	18 600*	51.9	46.2	12 900*	48.0
52.0	41.9	44.2	17 900 *	44.3	43.3	17 600*				52.0
56.0	35.9	38.7	15 100 *	38.1	37.7	15 600*				56.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>48.8m (160 Ft.) BOOM</b>										
16.8	79.9	69.3	32 800 *b							16.8
18.0	78.8	69.0	32 400 *							18.0
20.0	77.0	68.5	31 600 *	79.8	67.9	26 800*				20.0
22.0	75.3	67.9	30 900 *	78.0	67.3	26 300*				22.0
24.0	73.5	67.3	30 200 *	76.2	66.7	25 900*	79.0	65.4	18 700*	24.0
26.0	71.7	66.5	29 600 *	74.4	65.9	25 500*	77.1	64.7	18 000*	26.0
28.0	69.9	65.7	29 000 *	72.6	65.1	25 100*	75.2	63.9	17 400*	28.0
30.0	68.0	64.9	28 400 *	70.7	64.2	24 800*	73.3	63.0	16 800*	30.0
32.0	66.1	63.9	27 900 *	68.8	63.3	24 200*	71.4	62.0	16 200*	32.0
34.0	64.2	62.9	27 400 *	66.9	62.2	23 400*	69.4	60.9	15 800*	34.0
36.0	62.3	61.8	26 900 *	64.9	61.1	22 600*	67.4	59.8	15 300*	36.0
38.0	60.3	60.5	26 500 *	62.9	59.9	21 900*	65.4	58.5	14 800*	38.0
40.0	58.3	59.2	26 100 *	60.9	58.6	21 200*	63.3	57.2	14 400*	40.0
44.0	54.1	56.3	24 600	56.6	55.6	20 000*	58.9	54.1	13 800*	44.0
48.0	49.6	52.9	20 900 *	52.1	52.1	19 000*	54.2	50.5	13 100*	48.0
52.0	44.8	48.8	17 700 *	47.2	48.0	18 000*	49.1	46.2	12 600*	52.0
56.0	39.5	44.0	15 000 *	41.7	43.1	15 500*				56.0
60.0	33.4	38.1	12 600 *							60.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>51.8m (170 Ft.) BOOM</b>										
16.8	80.3	72.4	33 100 * <b>b</b>							16.8
18.0	79.3	72.1	32 600 * <b>b</b>							18.0
20.0	77.6	71.6	31 800 *	80.3	71.1	26 900*				20.0
22.0	75.9	71.1	31 200 *	78.6	70.5	26 500*				22.0
24.0	74.2	70.5	30 500 *	76.8	69.9	26 100*	79.5	68.6	18 900*	24.0
26.0	72.5	69.8	29 900 *	75.1	69.2	25 700*	77.7	67.9	18 200*	26.0
28.0	70.8	69.0	29 300 *	73.4	68.4	25 300*	75.9	67.1	17 600*	28.0
30.0	69.0	68.2	28 700 *	71.6	67.6	24 900*	74.1	66.3	17 000*	30.0
32.0	67.3	67.3	28 200 *	69.8	66.7	24 600*	72.3	65.4	16 500*	32.0
34.0	65.5	66.3	27 700 *	68.0	65.7	23 900*	70.4	64.4	16 000*	34.0
36.0	63.6	65.3	27 300 *	66.1	64.6	23 100*	68.5	63.3	15 500*	36.0
38.0	61.8	64.1	26 800 *	64.2	63.4	22 300*	66.6	62.1	15 100*	38.0
40.0	59.8	62.9	26 400 *	62.3	62.2	21 700*	64.6	60.8	14 700*	40.0
44.0	55.9	60.1	24 300	58.3	59.4	20 500*	60.5	58.0	14 000*	44.0
48.0	51.8	56.9	20 900 *	54.1	56.2	19 500*	56.2	54.6	13 400*	48.0
52.0	47.3	53.2	17 700 *	49.6	52.4	18 500*	51.6	50.7	12 900*	52.0
56.0	42.5	48.9	15 000 *	44.7	48.0	15 600*	46.5	46.1	12 500*	56.0
60.0	37.2	43.7	12 700 *	39.3	42.6	13 100*				60.0
64.0	31.0	37.2	10 600 *							64.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>54.9m (180 Ft.) BOOM</b>										
16.8	80.7	75.5	33 200 *b							16.8
18.0	79.7	75.3	32 800 *b							18.0
20.0	78.1	74.8	32 000 *	80.7	74.2	27 000*				20.0
22.0	76.5	74.3	31 400 *	79.1	73.7	26 600*				22.0
24.0	74.9	73.7	30 700 *	77.4	73.0	26 200*	79.9	71.8	19 100*	24.0
26.0	73.3	73.0	30 100 *	75.8	72.4	25 800*	78.3	71.1	18 400*	26.0
28.0	71.6	72.3	29 500 *	74.1	71.7	25 400*	76.6	70.4	17 800*	28.0
30.0	70.0	71.5	29 000 *	72.4	70.9	25 100*	74.8	69.6	17 200*	30.0
32.0	68.3	70.6	28 500 *	70.7	70.0	24 800*	73.1	68.7	16 700*	32.0
34.0	66.6	69.7	28 000 *	69.0	69.1	24 300*	71.3	67.7	16 200*	34.0
36.0	64.8	68.7	27 600 *	67.2	68.0	23 500*	69.5	66.7	15 800*	36.0
38.0	63.0	67.6	27 100 *	65.4	67.0	22 800*	67.7	65.6	15 300*	38.0
40.0	61.2	66.5	26 700 *	63.6	65.8	22 100*	65.9	64.4	14 900*	40.0
44.0	57.5	63.9	24 000	59.9	63.2	20 900*	62.0	61.7	14 200*	44.0
48.0	53.7	60.9	20 700	55.9	60.1	19 900*	58.0	58.6	13 600*	48.0
52.0	49.6	57.5	17 600 *	51.8	56.7	18 300*	53.7	55.0	13 100*	52.0
56.0	45.2	53.5	14 900 *	47.3	52.6	15 500*	49.1	50.8	12 700*	56.0
60.0	40.4	48.8	12 500 *	42.4	47.8	13 000*				60.0
64.0	35.0	43.2	10 500 *	36.9	42.1	10 800*				64.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
 Boom No. 44A With Heavy Lift Top  
 80 560 kg Counterweight  
 360 Degree Rating  
 On Extended Outriggers

Meets  
 ANSI B30.5  
 Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>57.9m (190 Ft.) BOOM</b>										
18.3	79.9	78.3	32 900 * <b>b</b>							18.3
20.0	78.6	77.9	32 300 *							20.0
22.0	77.1	77.4	31 600 *	79.5	76.8	26 700*				22.0
24.0	75.5	76.8	31 000 *	77.9	76.2	26 300*				24.0
26.0	74.0	76.2	30 400 *	76.4	75.6	25 900*	78.8	74.3	18 600*	26.0
28.0	72.4	75.5	29 800 *	74.8	74.9	25 600*	77.1	73.6	18 000*	28.0
30.0	70.8	74.8	29 300 *	73.2	74.1	25 200*	75.5	72.8	17 400*	30.0
32.0	69.2	74.0	28 800 *	71.5	73.3	24 900*	73.8	72.0	17 000*	32.0
34.0	67.6	73.1	28 300 *	69.9	72.4	24 600*	72.2	71.1	16 400*	34.0
36.0	65.9	72.1	27 800 *	68.2	71.5	24 000*	70.5	70.1	16 000*	36.0
38.0	64.2	71.1	27 400 *	66.5	70.4	23 200*	68.7	69.1	15 600*	38.0
40.0	62.5	70.0	26 900	64.8	69.3	22 600*	67.0	67.9	15 200*	40.0
44.0	59.0	67.6	23 700	61.3	66.8	21 400*	63.4	65.4	14 500*	44.0
48.0	55.4	64.8	20 400	57.6	64.0	20 300*	59.6	62.5	13 900*	48.0
52.0	51.5	61.5	17 500 *	53.7	60.8	18 200	55.6	59.2	13 300*	52.0
56.0	47.5	57.9	14 700 *	49.6	57.0	15 400*	51.3	55.3	12 900*	56.0
60.0	43.1	53.6	12 400 *	45.1	52.7	12 900*				60.0
64.0	38.3	48.5	10 300 *	40.2	47.5	10 800*				64.0
68.0	32.9	42.5	8 500 *							68.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>61.0m (200 Ft.) BOOM</b>										
18.3	80.3	81.4	33 100 * <sup>b</sup>							18.3
20.0	79.1	81.1	32 500 * <sup>b</sup>							20.0
22.0	77.6	80.6	31 800 *	79.9	79.9	26 800*				22.0
24.0	76.1	80.0	31 200 *	78.4	79.4	26 400*				24.0
26.0	74.6	79.4	30 600 *	76.9	78.8	26 100*	79.2	77.5	18 800*	26.0
28.0	73.1	78.8	30 000 *	75.4	78.1	25 700*	77.7	76.8	18 200*	28.0
30.0	71.6	78.0	29 500 *	73.8	77.4	25 400*	76.1	76.1	17 700*	30.0
32.0	70.0	77.3	29 000 *	72.3	76.6	25 100*	74.5	75.3	17 100*	32.0
34.0	68.5	76.4	28 600 *	70.7	75.8	24 700*	72.9	74.4	16 700*	34.0
36.0	66.9	75.5	28 100 *	69.1	74.8	24 400*	71.3	73.5	16 200*	36.0
38.0	65.3	74.5	27 700 *	67.5	73.9	23 600*	69.7	72.5	15 800*	38.0
40.0	63.7	73.5	27 100	65.9	72.8	23 000*	68.0	71.4	15 400*	40.0
44.0	60.4	71.2	23 300	62.5	70.5	21 700*	64.6	69.0	14 700*	44.0
48.0	56.9	68.5	20 100	59.0	67.8	20 500	61.0	66.3	14 100*	48.0
52.0	53.3	65.5	17 200 *	55.4	64.7	17 900	57.3	63.2	13 500*	52.0
56.0	49.5	62.1	14 500 *	51.6	61.2	15 200*	53.3	59.6	13 100*	56.0
60.0	45.5	58.1	12 200 *	47.5	57.2	12 800*	49.1	55.4	12 600*	60.0
64.0	41.1	53.5	10 200 *	43.0	52.6	10 600*				64.0
68.0	36.3	48.2	8 300 *	38.1	47.1	8 700*				68.0
72.0	30.8	41.6	6 700 *							72.0




**2250T**

# Liftcrane Jib Capacities

Meets  
ANSI B30.5  
Requirements

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>64.0m (210 Ft.) BOOM</b>										
18.3	80.7	84.5	33 200 * <b>b</b>							18.3
20.0	79.5	84.2	32 600 * <b>b</b>							20.0
22.0	78.1	83.7	32 000 *	80.3	83.1	26 900*				22.0
24.0	76.6	83.2	31 400 *	78.9	82.6	26 500*				24.0
26.0	75.2	82.6	30 900 *	77.4	82.0	26 200*	79.6	80.7	19 000*	26.0
28.0	73.7	82.0	30 300 *	76.0	81.3	25 800*	78.2	80.0	18 400*	28.0
30.0	72.3	81.3	29 800 *	74.5	80.6	25 500*	76.7	79.3	17 900*	30.0
32.0	70.8	80.5	29 300 *	73.0	79.9	25 200*	75.1	78.6	17 300*	32.0
34.0	69.3	79.7	28 800 *	71.5	79.1	24 900*	73.6	77.7	16 900*	34.0
36.0	67.8	78.9	28 400 *	70.0	78.2	24 600*	72.1	76.8	16 400*	36.0
38.0	66.3	77.9	27 900 *	68.4	77.3	24 000*	70.5	75.9	16 000*	38.0
40.0	64.7	76.9	27 200	66.9	76.2	23 400*	68.9	74.9	15 600*	40.0
44.0	61.6	74.7	23 200	63.7	74.0	22 100*	65.6	72.6	14 900*	44.0
48.0	58.3	72.2	20 000	60.4	71.5	20 600	62.3	70.0	14 300*	48.0
52.0	54.9	69.4	17 300	56.9	68.6	17 800	58.8	67.0	13 800*	52.0
56.0	51.4	66.1	14 600 *	53.3	65.3	15 300*	55.1	63.7	13 200*	56.0
60.0	47.6	62.5	12 300 *	49.5	61.6	12 900*	51.2	59.9	12 800*	60.0
64.0	43.6	58.3	10 200 *	45.5	57.3	10 700*	46.9	55.4	11 100*	64.0
68.0	39.2	53.4	8 400 *	41.0	52.4	8 800*				68.0
72.0	34.4	47.6	6 800 *	36.0	46.5	7 100*				72.0
76.0	28.7	40.5	5 300 *							76.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>67.1m (220 Ft.) BOOM</b>										
19.8	80.0	87.3	32 900 *b							19.8
20.0	79.9	87.3	32 800 *b							20.0
22.0	78.5	86.8	32 200 *b							22.0
24.0	77.1	86.3	31 600 *	79.3	85.7	26 600*				24.0
26.0	75.7	85.8	31 000 *	77.9	85.1	26 300*	80.0	83.9	19 100*	26.0
28.0	74.3	85.2	30 500 *	76.5	84.5	25 900*	78.6	83.2	18 600*	28.0
30.0	72.9	84.5	30 000 *	75.1	83.9	25 600*	77.2	82.5	18 000*	30.0
32.0	71.5	83.8	29 500 *	73.6	83.1	25 300*	75.7	81.8	17 600*	32.0
34.0	70.1	83.0	29 000 *	72.2	82.4	25 000*	74.2	81.0	17 100*	34.0
36.0	68.6	82.2	28 600 *	70.7	81.5	24 800*	72.8	80.2	16 600*	36.0
38.0	67.2	81.3	28 200 *	69.3	80.6	24 400*	71.3	79.2	16 200*	38.0
40.0	65.7	80.3	26 900	67.8	79.7	23 700*	69.7	78.3	15 800*	40.0
44.0	62.7	78.2	22 900	64.7	77.5	22 500*	66.6	76.1	15 100*	44.0
48.0	59.6	75.8	19 700	61.6	75.1	20 300	63.4	73.6	14 500*	48.0
52.0	56.4	73.1	16 900	58.3	72.4	17 500	60.1	70.9	13 900*	52.0
56.0	53.0	70.1	14 400 *	54.9	69.3	15 100	56.6	67.7	13 500*	56.0
60.0	49.5	66.7	12 000 *	51.4	65.8	12 600*	53.0	64.1	12 900*	60.0
64.0	45.8	62.7	10 000 *	47.6	61.9	10 500*	49.1	60.0	11 000*	64.0
68.0	41.7	58.3	8 200 *	43.5	57.3	8 600*				68.0
72.0	37.4	53.1	6 600 *	39.1	52.0	6 900*				72.0
76.0	32.5	46.9	5 100 *							76.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
 Boom No. 44A With Heavy Lift Top  
 80 560 kg Counterweight  
 360 Degree Rating  
 On Extended Outriggers

Meets  
 ANSI B30.5  
 Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>70.1m (230 Ft.) BOOM</b>										
19.8	80.3	90.5	33 100 * <b>b</b>							19.8
20.0	80.2	90.4	33 000 * <b>b</b>							20.0
22.0	78.9	90.0	32 400 * <b>b</b>							22.0
24.0	77.6	89.5	31 800 *	79.7	88.8	26 700*				24.0
26.0	76.2	89.0	31 300 *	78.3	88.3	26 400*	80.4	87.0	19 300*	26.0
28.0	74.9	88.4	30 700 *	77.0	87.7	26 100*	79.0	86.4	18 700*	28.0
30.0	73.5	87.7	30 200 *	75.6	87.1	25 700*	77.6	85.8	18 200*	30.0
32.0	72.2	87.0	29 800 *	74.2	86.4	25 400*	76.2	85.0	17 700*	32.0
34.0	70.8	86.3	29 300 *	72.8	85.6	25 200*	74.8	84.3	17 300*	34.0
36.0	69.4	85.5	28 900 *	71.4	84.8	24 900*	73.4	83.5	16 800*	36.0
38.0	68.0	84.6	28 400 *	70.0	84.0	24 600*	72.0	82.6	16 400*	38.0
40.0	66.6	83.7	26 600	68.6	83.0	24 100*	70.5	81.6	16 000*	40.0
44.0	63.7	81.7	22 600	65.7	81.0	22 900*	67.6	79.6	15 300*	44.0
48.0	60.7	79.4	19 300	62.7	78.7	20 000	64.5	77.2	14 700*	48.0
52.0	57.7	76.9	16 700	59.6	76.1	17 200	61.3	74.6	14 100*	52.0
56.0	54.5	74.0	14 200 *	56.4	73.2	14 900	58.1	71.6	13 600*	56.0
60.0	51.2	70.7	11 800 *	53.0	69.9	12 500*	54.6	68.2	13 100*	60.0
64.0	47.7	67.1	9 800 *	49.5	66.2	10 300*	51.0	64.4	10 800*	64.0
68.0	44.0	62.9	8 000 *	45.7	62.0	8 500*	47.1	60.1	8 900*	68.0
72.0	40.0	58.2	6 300 *	41.6	57.2	6 800*				72.0
76.0	35.6	52.6	4 900 *	37.2	51.5	5 200*				76.0
80.0	30.6	46.0	3 600 *							80.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>73.2m (240 Ft.) BOOM</b>										
19.8	80.7	93.6	33 200 *b							19.8
20.0	80.5	93.5	33 100 *b							20.0
22.0	79.3	93.1	32 500 *b							22.0
24.0	78.0	92.6	32 000 *	80.0	92.0	26 800*				24.0
26.0	76.7	92.1	31 500 *	78.7	91.5	26 500*	80.7	90.2	19 400*	26.0
28.0	75.4	91.5	30 900 *	77.4	90.9	26 200*	79.4	89.6	18 900*	28.0
30.0	74.1	90.9	30 400 *	76.1	90.3	25 900*	78.1	88.9	18 400*	30.0
32.0	72.8	90.3	30 000 *	74.8	89.6	25 600*	76.7	88.3	17 900*	32.0
34.0	71.5	89.6	29 500 *	73.4	88.9	25 300*	75.4	87.5	17 400*	34.0
36.0	70.1	88.8	29 000 *	72.1	88.1	25 000*	74.0	86.7	17 000*	36.0
38.0	68.8	88.0	27 900 *	70.7	87.3	24 800*	72.6	85.9	16 600*	38.0
40.0	67.4	87.1	25 900 *	69.4	86.4	24 500*	71.2	85.0	16 200*	40.0
44.0	64.7	85.1	22 200	66.6	84.4	23 000	68.4	83.0	15 500*	44.0
48.0	61.8	83.0	19 000	63.7	82.2	19 700	65.5	80.8	14 900*	48.0
52.0	58.9	80.5	16 300	60.8	79.8	16 900	62.5	78.3	14 300*	52.0
56.0	55.9	77.8	13 900	57.7	77.0	14 600	59.4	75.4	13 800*	56.0
60.0	52.7	74.7	11 600 *	54.5	73.9	12 300*	56.1	72.2	13 000*	60.0
64.0	49.5	71.3	9 500 *	51.2	70.4	10 100*	52.7	68.7	10 700*	64.0
68.0	46.0	67.4	7 700 *	47.7	66.5	8 200*	49.1	64.6	8 700*	68.0
72.0	42.3	63.0	6 100 *	43.9	62.0	6 600*				72.0
76.0	38.3	57.9	4 600 *	39.8	56.9	5 100*				76.0
80.0	33.8	52.1	3 300 *	35.3	50.9	3 600*				80.0




# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements

**2250T**



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>76.2m (250 Ft.) BOOM</b>										
19.8	81.0	96.7	27 200 *b							19.8
20.0	80.9	96.6	27 200 *b							20.0
22.0	79.6	96.2	27 200 *b							22.0
24.0	78.4	95.8	27 200 *							24.0
26.0	77.1	95.3	27 200 *	79.1	94.6	26 600*				26.0
28.0	75.9	94.7	27 200 *	77.8	94.1	26 300*	79.8	92.7	19 000*	28.0
30.0	74.6	94.1	27 200 *	76.6	93.5	26 000*	78.5	92.1	18 500*	30.0
32.0	73.4	93.5	27 200 *	75.3	92.8	25 700*	77.2	91.5	18 000*	32.0
34.0	72.1	92.8	27 200 *	74.0	92.1	25 400*	75.9	90.8	17 600*	34.0
36.0	70.8	92.1	27 200 *	72.7	91.4	25 100*	74.6	90.0	17 200*	36.0
38.0	69.5	91.3	27 200 *	71.4	90.6	24 900*	73.2	89.2	16 800*	38.0
40.0	68.2	90.4	25 500 *	70.1	89.7	24 600*	71.9	88.3	16 400*	40.0
44.0	65.5	88.6	22 100	67.4	87.9	22 600*	69.2	86.4	15 700*	44.0
48.0	62.8	86.5	18 800	64.7	85.7	19 600	66.4	84.3	15 100*	48.0
52.0	60.0	84.1	16 200	61.8	83.4	16 800	63.5	81.9	14 500*	52.0
56.0	57.1	81.5	13 900	58.9	80.7	14 400	60.5	79.2	14 000*	56.0
60.0	54.2	78.6	11 500 *	55.9	77.8	12 300*	57.5	76.2	12 800	60.0
64.0	51.0	75.3	9 500 *	52.8	74.5	10 100*	54.2	72.8	10 700*	64.0
68.0	47.8	71.7	7 700 *	49.5	70.8	8 200*	50.8	69.0	8 700*	68.0
72.0	44.3	67.6	6 100 *	46.0	66.6	6 600*	47.2	64.7	7 000*	72.0
76.0	40.6	62.9	4 600 *	42.2	61.9	5 100*				76.0
80.0	36.6	57.6	3 300 *	38.1	56.5	3 700*				80.0
84.0	32.1	51.3	2 200 *							84.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>79.2m (260 Ft.) BOOM</b>										
21.3	80.3	99.5	27 200 * <b>b</b>							21.3
22.0	79.9	99.3	27 200 * <b>b</b>							22.0
24.0	78.8	98.9	27 200 *							24.0
26.0	77.6	98.4	27 200 *	79.4	97.8	26 700*				26.0
28.0	76.3	97.9	27 200 *	78.2	97.2	26 400*	80.1	95.9	19 200*	28.0
30.0	75.1	97.3	27 200 *	77.0	96.6	26 100*	78.9	95.3	18 700*	30.0
32.0	73.9	96.7	27 200 *	75.8	96.0	25 800*	77.6	94.7	18 200*	32.0
34.0	72.7	96.0	27 200 *	74.5	95.3	25 500*	76.4	94.0	17 800*	34.0
36.0	71.4	95.3	27 200 *	73.3	94.6	25 200*	75.1	93.3	17 400*	36.0
38.0	70.2	94.5	26 600 *	72.0	93.9	25 000*	73.8	92.5	16 900*	38.0
40.0	68.9	93.7	24 700 *	70.7	93.0	24 700*	72.5	91.6	16 600*	40.0
44.0	66.4	91.9	21 400 *	68.2	91.2	22 000*	69.9	89.8	15 900*	44.0
48.0	63.7	89.9	18 500	65.5	89.2	19 100*	67.2	87.8	15 300*	48.0
52.0	61.1	87.7	15 800	62.8	86.9	16 500	64.5	85.4	14 700*	52.0
56.0	58.3	85.2	13 500	60.0	84.4	14 100	61.6	82.9	14 200*	56.0
60.0	55.5	82.4	11 200 *	57.2	81.6	12 000*	58.7	80.0	12 600	60.0
64.0	52.5	79.3	9 200 *	54.2	78.5	9 900*	55.6	76.8	10 500*	64.0
68.0	49.4	75.9	7 400 *	51.1	75.0	8 000*	52.4	73.2	8 500*	68.0
72.0	46.2	72.0	5 800 *	47.8	71.1	6 300*	49.1	69.2	6 700*	72.0
76.0	42.7	67.7	4 400 *	44.3	66.7	4 800*				76.0
80.0	39.0	62.8	3 100 *	40.5	61.7	3 400*				80.0
84.0				36.4	55.9	2 200*				84.0




**2250T**

# Liftcrane Jib Capacities

Meets  
ANSI B30.5  
Requirements

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>39.6m (130 Ft.) BOOM</b>										
16.8	80.2	66.2	23 300 *							16.8
18.0	79.0	65.9	22 900 *							18.0
20.0	77.2	65.3	22 300 *							20.0
22.0	75.3	64.7	21 700 *	79.2	64.0	19 700*				22.0
24.0	73.5	64.0	21 100 *	77.3	63.3	19 300*				24.0
26.0	71.6	63.2	20 600 *	75.4	62.5	18 900*	79.3	61.1	14 700*	26.0
28.0	69.6	62.4	20 100 *	73.4	61.7	18 500*	77.3	60.3	14 100*	28.0
30.0	67.7	61.5	19 700 *	71.5	60.8	18 100*	75.3	59.3	13 500*	30.0
32.0	65.7	60.5	19 200 *	69.5	59.7	17 800*	73.2	58.3	13 000*	32.0
34.0	63.7	59.4	18 800 *	67.4	58.6	17 400*	71.1	57.1	12 500*	34.0
36.0	61.6	58.2	18 400 *	65.3	57.4	17 100*	68.9	55.9	12 100*	36.0
38.0	59.5	56.9	18 000 *	63.2	56.1	16 800*	66.7	54.5	11 700*	38.0
40.0	57.3	55.5	17 700 *	61.0	54.7	16 600*	64.5	53.1	11 400*	40.0
44.0	52.8	52.3	17 000 *	56.4	51.5	15 300*	59.7	49.7	10 700*	44.0
48.0	48.0	48.6	16 500 *	51.4	47.7	14 200*	54.5	45.8	10 200*	48.0
52.0	42.6	44.1	15 900 *	46.0	43.1	13 300*	48.8	41.0	9 700*	52.0
56.0	36.6	38.7	14 700 *	39.8	37.5	12 500*				56.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>42.7m (140 Ft.) BOOM</b>										
16.8	80.6	69.3	23 500 *							16.8
18.0	79.6	69.0	23 100 *							18.0
20.0	77.8	68.5	22 500 *							20.0
22.0	76.0	67.9	21 900 *	79.7	67.2	19 900*				22.0
24.0	74.3	67.2	21 400 *	77.9	66.5	19 400*				24.0
26.0	72.4	66.5	20 900 *	76.1	65.8	19 000*	79.8	64.4	14 800*	26.0
28.0	70.6	65.7	20 400 *	74.3	65.0	18 700*	77.9	63.5	14 300*	28.0
30.0	68.8	64.8	19 900 *	72.4	64.1	18 300*	76.0	62.6	13 700*	30.0
32.0	66.9	63.9	19 500 *	70.5	63.1	18 000*	74.1	61.6	13 200*	32.0
34.0	65.0	62.9	19 100 *	68.6	62.1	17 600*	72.1	60.6	12 800*	34.0
36.0	63.0	61.7	18 700 *	66.6	61.0	17 300*	70.1	59.4	12 300*	36.0
38.0	61.1	60.5	18 300 *	64.6	59.7	17 000*	68.0	58.1	11 900*	38.0
40.0	59.0	59.2	18 000 *	62.5	58.4	16 800*	65.9	56.8	11 600*	40.0
44.0	54.8	56.3	17 300 *	58.2	55.4	15 800*	61.5	53.7	10 900*	44.0
48.0	50.4	52.8	16 700 *	53.7	51.9	14 700*	56.8	50.1	10 400*	48.0
52.0	45.5	48.8	16 200 *	48.8	47.8	13 700*	51.6	45.7	9 900*	52.0
56.0	40.2	44.0	15 300 *	43.3	42.9	12 900*				56.0
60.0	34.1	38.0	14 200 *	37.1	36.7	12 200*				60.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>45.7m (150 Ft.) BOOM</b>										
18.3	79.8	72.1	23 200 *							18.3
20.0	78.3	71.6	22 700 *							20.0
22.0	76.7	71.1	22 100 *	80.2	70.4	20 000*				22.0
24.0	75.0	70.4	21 600 *	78.5	69.7	19 600*				24.0
26.0	73.2	69.8	21 100 *	76.7	69.0	19 200*	80.3	67.6	15 000*	26.0
28.0	71.5	69.0	20 600 *	75.0	68.3	18 800*	78.5	66.8	14 400*	28.0
30.0	69.8	68.2	20 200 *	73.2	67.4	18 500*	76.7	65.9	13 900*	30.0
32.0	68.0	67.3	19 700 *	71.4	66.5	18 100*	74.8	65.0	13 400*	32.0
34.0	66.2	66.3	19 300 *	69.6	65.5	17 800*	73.0	64.0	13 000*	34.0
36.0	64.3	65.2	18 900 *	67.7	64.5	17 500*	71.1	62.9	12 500*	36.0
38.0	62.5	64.1	18 600 *	65.8	63.3	17 200*	69.1	61.7	12 200*	38.0
40.0	60.6	62.9	18 200 *	63.9	62.0	17 000*	67.1	60.4	11 800*	40.0
44.0	56.6	60.1	17 600 *	59.9	59.3	16 300*	63.0	57.5	11 100*	44.0
48.0	52.5	56.9	17 000 *	55.7	56.0	15 100*	58.7	54.2	10 600*	48.0
52.0	48.0	53.2	16 500 *	51.2	52.2	14 200*	54.0	50.2	10 100*	52.0
56.0	43.2	48.8	15 900 *	46.3	47.8	13 300*	48.8	45.6	9 700*	56.0
60.0	37.9	43.6	14 100 *	40.8	42.4	12 600*				60.0
64.0	31.7	37.2	11 900 *	34.4	35.7	12 100*				64.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>48.8m (160 Ft.) BOOM</b>										
18.3	80.2	75.2	23 300 *							18.3
20.0	78.8	74.8	22 800 *							20.0
22.0	77.2	74.2	22 300 *							22.0
24.0	75.6	73.6	21 800 *	79.0	72.9	19 700*				24.0
26.0	74.0	73.0	21 300 *	77.3	72.2	19 300*	80.7	70.7	15 200*	26.0
28.0	72.3	72.3	20 800 *	75.7	71.5	18 900*	79.0	70.0	14 600*	28.0
30.0	70.6	71.5	20 400 *	74.0	70.7	18 600*	77.3	69.2	14 100*	30.0
32.0	69.0	70.6	20 000 *	72.3	69.8	18 300*	75.6	68.3	13 600*	32.0
34.0	67.2	69.7	19 600 *	70.5	68.9	17 900*	73.8	67.3	13 100*	34.0
36.0	65.5	68.7	19 200 *	68.8	67.9	17 600*	72.0	66.3	12 700*	36.0
38.0	63.7	67.6	18 800 *	67.0	66.8	17 400*	70.1	65.2	12 300*	38.0
40.0	61.9	66.4	18 500 *	65.1	65.6	17 100*	68.3	64.0	12 000*	40.0
44.0	58.2	63.9	17 800 *	61.4	63.0	16 600*	64.4	61.3	11 400*	44.0
48.0	54.3	60.9	17 300 *	57.5	60.0	15 600*	60.3	58.1	10 800*	48.0
52.0	50.2	57.4	16 700 *	53.3	56.5	14 600*	56.0	54.5	10 300*	52.0
56.0	45.8	53.4	16 100 *	48.8	52.4	13 700*	51.4	50.3	9 900*	56.0
60.0	41.1	48.7	13 900 *	43.9	47.6	13 000*				60.0
64.0	35.7	43.1	11 800 *	38.4	41.8	12 300*				64.0
68.0	29.4	36.1	9 800 *							68.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>51.8m (170 Ft.) BOOM</b>										
18.3	80.6	78.3	23 400 *							18.3
20.0	79.3	77.9	23 000 *							20.0
22.0	77.7	77.4	22 500 *							22.0
24.0	76.2	76.8	22 000 *	79.4	76.1	19 800*				24.0
26.0	74.6	76.2	21 500 *	77.9	75.4	19 400*				26.0
28.0	73.1	75.5	21 000 *	76.3	74.7	19 100*	79.5	73.2	14 800*	28.0
30.0	71.5	74.8	20 600 *	74.6	74.0	18 700*	77.9	72.4	14 200*	30.0
32.0	69.8	73.9	20 200 *	73.0	73.2	18 400*	76.2	71.6	13 800*	32.0
34.0	68.2	73.0	19 800 *	71.4	72.3	18 100*	74.5	70.7	13 300*	34.0
36.0	66.6	72.1	19 400 *	69.7	71.3	17 800*	72.8	69.7	12 900*	36.0
38.0	64.9	71.1	19 100 *	68.0	70.3	17 500*	71.0	68.6	12 500*	38.0
40.0	63.2	70.0	18 700 *	66.3	69.1	17 300*	69.3	67.5	12 200*	40.0
44.0	59.7	67.5	18 100 *	62.7	66.7	16 800*	65.6	64.9	11 500*	44.0
48.0	56.0	64.7	17 500 *	59.0	63.8	16 000*	61.8	62.0	11 000*	48.0
52.0	52.2	61.5	16 900 *	55.1	60.6	15 000*	57.8	58.6	10 500*	52.0
56.0	48.1	57.8	16 200 *	51.0	56.8	14 100*	53.5	54.7	10 100*	56.0
60.0	43.8	53.5	13 900 *	46.5	52.4	13 400*	48.9	50.2	9 700*	60.0
64.0	39.0	48.5	11 800 *	41.6	47.3	12 300*				64.0
68.0	33.5	42.4	9 900 *	36.0	41.0	10 300*				68.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>54.9m (180 Ft.) BOOM</b>										
18.3	81.0	81.4	23 600 *							18.3
20.0	79.7	81.0	23 100 *							20.0
22.0	78.2	80.5	22 600 *							22.0
24.0	76.7	80.0	22 100 *	79.9	79.2	19 900*				24.0
26.0	75.2	79.4	21 700 *	78.3	78.6	19 500*				26.0
28.0	73.7	78.7	21 200 *	76.8	78.0	19 200*	79.9	76.4	14 900*	28.0
30.0	72.2	78.0	20 800 *	75.3	77.2	18 800*	78.4	75.7	14 400*	30.0
32.0	70.7	77.2	20 400 *	73.7	76.4	18 500*	76.8	74.9	13 900*	32.0
34.0	69.1	76.4	20 000 *	72.1	75.6	18 300*	75.2	74.0	13 500*	34.0
36.0	67.5	75.5	19 600 *	70.5	74.7	18 000*	73.5	73.0	13 100*	36.0
38.0	65.9	74.5	19 300 *	68.9	73.7	17 700*	71.9	72.0	12 700*	38.0
40.0	64.3	73.5	18 900 *	67.3	72.6	17 400*	70.2	70.9	12 400*	40.0
44.0	61.0	71.1	18 300 *	63.9	70.3	16 900*	66.7	68.5	11 700*	44.0
48.0	57.5	68.5	17 700 *	60.4	67.6	16 400*	63.2	65.8	11 200*	48.0
52.0	53.9	65.5	17 200 *	56.8	64.5	15 400*	59.4	62.6	10 700*	52.0
56.0	50.1	62.0	16 100 *	52.9	61.0	14 500*	55.4	59.0	10 300*	56.0
60.0	46.1	58.1	13 700 *	48.8	57.0	13 700*	51.1	54.8	9 900*	60.0
64.0	41.7	53.5	11 600 *	44.4	52.3	12 200*	46.5	49.9	9 600*	64.0
68.0	36.9	48.1	9 700 *	39.4	46.8	10 300*				68.0
72.0	31.4	41.6	8 100 *							72.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>57.9m (190 Ft.) BOOM</b>										
19.8	80.2	84.2	23 300 *							19.8
20.0	80.1	84.2	23 300 *							20.0
22.0	78.7	83.7	22 800 *							22.0
24.0	77.2	83.2	22 300 *							24.0
26.0	75.8	82.6	21 800 *	78.8	81.8	19 600*				26.0
28.0	74.4	81.9	21 400 *	77.3	81.2	19 300*	80.3	79.6	15 000*	28.0
30.0	72.9	81.3	21 000 *	75.8	80.5	19 000*	78.8	78.9	14 500*	30.0
32.0	71.4	80.5	20 600 *	74.4	79.7	18 700*	77.3	78.1	14 100*	32.0
34.0	69.9	79.7	20 200 *	72.8	78.9	18 400*	75.8	77.3	13 600*	34.0
36.0	68.4	78.8	19 800 *	71.3	78.0	18 100*	74.2	76.4	13 300*	36.0
38.0	66.9	77.9	19 500 *	69.8	77.1	17 800*	72.6	75.4	12 900*	38.0
40.0	65.3	76.9	19 200 *	68.2	76.1	17 500*	71.0	74.4	12 500*	40.0
44.0	62.2	74.7	18 500 *	65.0	73.8	17 100*	67.8	72.1	11 900*	44.0
48.0	58.9	72.2	17 900 *	61.7	71.3	16 700*	64.4	69.5	11 300*	48.0
52.0	55.5	69.3	17 400 *	58.3	68.4	15 800*	60.8	66.5	10 900*	52.0
56.0	52.0	66.1	15 900	54.7	65.1	14 900*	57.1	63.1	10 400*	56.0
60.0	48.2	62.4	13 500 *	50.8	61.4	14 000*	53.1	59.3	10 100*	60.0
64.0	44.2	58.2	11 400 *	46.7	57.1	12 100*	48.9	54.8	9 700*	64.0
68.0	39.8	53.3	9 600 *	42.3	52.1	10 100*				68.0
72.0	34.9	47.6	7 900 *	37.3	46.2	8 400*				72.0
76.0	29.3	40.5	6 400 *							76.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>61.0m (200 Ft.) BOOM</b>										
19.8	80.6	87.3	23 400 *							19.8
20.0	80.5	87.3	23 400 *							20.0
22.0	79.1	86.8	22 900 *							22.0
24.0	77.7	86.3	22 400 *							24.0
26.0	76.3	85.8	22 000 *	79.2	85.0	19 700*				26.0
28.0	74.9	85.1	21 600 *	77.8	84.4	19 400*				28.0
30.0	73.5	84.5	21 200 *	76.4	83.7	19 100*	79.3	82.1	14 700*	30.0
32.0	72.1	83.8	20 800 *	74.9	83.0	18 800*	77.8	81.3	14 200*	32.0
34.0	70.7	83.0	20 400 *	73.5	82.2	18 500*	76.3	80.5	13 800*	34.0
36.0	69.2	82.2	20 000 *	72.0	81.3	18 200*	74.8	79.7	13 400*	36.0
38.0	67.8	81.3	19 700 *	70.6	80.4	18 000*	73.3	78.8	13 000*	38.0
40.0	66.3	80.3	19 300 *	69.1	79.5	17 700*	71.8	77.8	12 700*	40.0
44.0	63.3	78.2	18 700 *	66.0	77.3	17 200*	68.7	75.6	12 100*	44.0
48.0	60.2	75.8	18 200 *	62.9	74.9	16 800*	65.4	73.1	11 500*	48.0
52.0	56.9	73.1	17 600	59.6	72.2	16 100*	62.1	70.3	11 000*	52.0
56.0	53.6	70.1	15 600	56.2	69.1	15 300*	58.6	67.1	10 600*	56.0
60.0	50.1	66.6	13 300 *	52.6	65.6	14 100*	54.9	63.5	10 200*	60.0
64.0	46.3	62.7	11 200 *	48.8	61.6	11 900*	51.0	59.4	9 900*	64.0
68.0	42.3	58.2	9 300 *	44.7	57.0	10 000*	46.7	54.6	9 600*	68.0
72.0	37.9	53.0	7 700 *	40.3	51.7	8 200*				72.0
76.0	33.0	46.8	6 200 *	35.2	45.3	6 600*				76.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>64.0m (210 Ft.) BOOM</b>										
19.8	80.9	90.4	23 600 *							19.8
20.0	80.8	90.4	23 500 *							20.0
22.0	79.5	89.9	23 100 *							22.0
24.0	78.1	89.5	22 600 *							24.0
26.0	76.8	88.9	22 200 *	79.6	88.1	19 800*				26.0
28.0	75.5	88.3	21 700 *	78.2	87.5	19 500*				28.0
30.0	74.1	87.7	21 300 *	76.9	86.9	19 200*	79.7	85.3	14 800*	30.0
32.0	72.7	87.0	21 000 *	75.5	86.2	18 900*	78.3	84.6	14 400*	32.0
34.0	71.4	86.3	20 600 *	74.1	85.4	18 600*	76.8	83.8	14 000*	34.0
36.0	70.0	85.5	20 200 *	72.7	84.6	18 300*	75.4	83.0	13 600*	36.0
38.0	68.6	84.6	19 900 *	71.3	83.8	18 100*	74.0	82.1	13 200*	38.0
40.0	67.2	83.7	19 500 *	69.9	82.8	17 800*	72.5	81.1	12 900*	40.0
44.0	64.3	81.7	18 900 *	66.9	80.8	17 300*	69.5	79.1	12 200*	44.0
48.0	61.3	79.4	18 300 *	63.9	78.5	16 900*	66.4	76.7	11 700*	48.0
52.0	58.2	76.8	17 800 *	60.8	75.9	16 500*	63.3	74.0	11 200*	52.0
56.0	55.1	73.9	15 500 *	57.6	73.0	15 600*	60.0	71.0	10 800*	56.0
60.0	51.7	70.7	13 300 *	54.2	69.7	14 100	56.5	67.6	10 400*	60.0
64.0	48.3	67.0	11 200 *	50.7	66.0	11 900*	52.8	63.8	10 000*	64.0
68.0	44.5	62.9	9 400 *	46.9	61.7	10 000*	48.9	59.4	9 700*	68.0
72.0	40.5	58.1	7 700 *	42.8	56.9	8 300*				72.0
76.0	36.1	52.6	6 300 *	38.3	51.2	6 700*				76.0
80.0	31.1	46.0	4 900 *							80.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>67.1m (220 Ft.) BOOM</b>										
21.3	80.2	93.2	23 400 *							21.3
22.0	79.8	93.1	23 200 *							22.0
24.0	78.5	92.6	22 700 *							24.0
26.0	77.3	92.1	22 300 *	80.0	91.3	19 900*				26.0
28.0	76.0	91.5	21 900 *	78.6	90.7	19 600*				28.0
30.0	74.7	90.9	21 500 *	77.3	90.1	19 300*	80.0	88.5	14 900*	30.0
32.0	73.3	90.2	21 100 *	76.0	89.4	19 000*	78.7	87.8	14 500*	32.0
34.0	72.0	89.5	20 700 *	74.7	88.7	18 700*	77.3	87.0	14 100*	34.0
36.0	70.7	88.7	20 400 *	73.3	87.9	18 500*	75.9	86.2	13 700*	36.0
38.0	69.3	87.9	20 100 *	72.0	87.1	18 200*	74.6	85.4	13 300*	38.0
40.0	68.0	87.0	19 800 *	70.6	86.2	18 000*	73.1	84.5	13 000*	40.0
44.0	65.2	85.1	19 100 *	67.8	84.2	17 500*	70.3	82.5	12 400*	44.0
48.0	62.4	82.9	18 500 *	64.9	82.0	17 100*	67.4	80.2	11 800*	48.0
52.0	59.4	80.5	17 500	62.0	79.6	16 700*	64.3	77.7	11 400*	52.0
56.0	56.4	77.7	15 200	58.9	76.8	15 800	61.2	74.8	10 900*	56.0
60.0	53.3	74.7	13 100 *	55.7	73.7	13 800	57.9	71.6	10 500*	60.0
64.0	50.0	71.2	11 000 *	52.4	70.2	11 700*	54.5	68.0	10 200*	64.0
68.0	46.5	67.3	9 100 *	48.8	66.2	9 800*	50.8	63.9	9 900*	68.0
72.0	42.8	62.9	7 500 *	45.1	61.7	8 100*				72.0
76.0	38.8	57.9	6 100 *	41.0	56.6	6 500*				76.0
80.0	34.4	52.0	4 700 *	36.4	50.5	5 100*				80.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>70.1m (230 Ft.) BOOM</b>										
21.3	80.6	96.3	23 400 *							21.3
22.0	80.2	96.2	23 300 *							22.0
24.0	78.9	95.7	22 900 *							24.0
26.0	77.7	95.2	22 400 *	80.3	94.4	20 000*				26.0
28.0	76.4	94.7	22 000 *	79.0	93.9	19 700*				28.0
30.0	75.2	94.1	21 600 *	77.8	93.3	19 400*				30.0
32.0	73.9	93.5	21 300 *	76.5	92.6	19 100*	79.1	91.0	14 600*	32.0
34.0	72.6	92.8	20 900 *	75.2	91.9	18 800*	77.8	90.3	14 200*	34.0
36.0	71.3	92.0	20 600 *	73.9	91.2	18 600*	76.4	89.5	13 800*	36.0
38.0	70.0	91.2	20 200 *	72.6	90.4	18 300*	75.1	88.7	13 500*	38.0
40.0	68.7	90.4	19 900 *	71.3	89.5	18 100*	73.7	87.8	13 100*	40.0
44.0	66.1	88.5	19 300 *	68.6	87.6	17 600*	71.0	85.9	12 500*	44.0
48.0	63.3	86.4	18 800 *	65.8	85.5	17 200*	68.2	83.7	12 000*	48.0
52.0	60.6	84.1	17 200	63.0	83.2	16 800*	65.3	81.3	11 500*	52.0
56.0	57.7	81.5	14 900	60.1	80.5	15 600	62.3	78.6	11 100*	56.0
60.0	54.7	78.5	12 800 *	57.1	77.6	13 500	59.2	75.5	10 600*	60.0
64.0	51.6	75.3	10 700 *	53.9	74.2	11 600*	56.0	72.1	10 300*	64.0
68.0	48.3	71.6	8 900 *	50.6	70.5	9 600*	52.5	68.3	10 000*	68.0
72.0	44.8	67.5	7 300 *	47.1	66.4	7 900*	48.9	64.0	8 400*	72.0
76.0	41.1	62.9	5 800 *	43.3	61.6	6 300*				76.0
80.0	37.1	57.5	4 500 *	39.2	56.1	4 900*				80.0
84.0	32.6	51.3	3 300 *							84.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>73.2m (240 Ft.) BOOM</b>										
21.3	80.9	99.4	23 600 *							21.3
22.0	80.5	99.3	23 400 *							22.0
24.0	79.3	98.9	23 000 *							24.0
26.0	78.1	98.4	22 600 *	80.6	97.6	20 100*				26.0
28.0	76.9	97.8	22 200 *	79.4	97.0	19 800*				28.0
30.0	75.6	97.3	21 800 *	78.2	96.4	19 500*				30.0
32.0	74.4	96.7	21 400 *	76.9	95.8	19 200*	79.4	94.1	14 700*	32.0
34.0	73.2	96.0	21 100 *	75.7	95.2	18 900*	78.2	93.5	14 300*	34.0
36.0	71.9	95.3	20 700 *	74.4	94.4	18 700*	76.9	92.7	14 000*	36.0
38.0	70.7	94.5	20 400 *	73.2	93.7	18 400*	75.6	91.9	13 600*	38.0
40.0	69.4	93.7	20 100 *	71.9	92.8	18 200*	74.3	91.1	13 300*	40.0
44.0	66.9	91.9	19 500 *	69.3	91.0	17 700*	71.7	89.3	12 700*	44.0
48.0	64.3	89.9	18 900 *	66.7	89.0	17 300*	69.0	87.2	12 100*	48.0
52.0	61.6	87.6	16 800	63.9	86.7	16 900*	66.2	84.9	11 600*	52.0
56.0	58.8	85.1	14 500	61.2	84.2	15 300	63.3	82.3	11 200*	56.0
60.0	56.0	82.4	12 500	58.3	81.4	13 200	60.4	79.4	10 800*	60.0
64.0	53.0	79.3	10 400 *	55.3	78.2	11 300	57.3	76.2	10 400*	64.0
68.0	49.9	75.8	8 600 *	52.2	74.7	9 400*	54.1	72.6	10 000*	68.0
72.0	46.7	72.0	7 000 *	48.9	70.8	7 600*	50.7	68.5	8 200*	72.0
76.0	43.2	67.6	5 500 *	45.3	66.4	6 100*	47.0	63.9	6 600*	76.0
80.0	39.5	62.7	4 200 *	41.6	61.4	4 700*				80.0
84.0	35.5	57.0	3 000 *	37.4	55.6	3 400*				84.0
88.0	30.9	50.4	1 900 *							88.0




# Liftcrane Jib Capacities

Meets  
**ANSI B30.5**  
 Requirements

## 2250T

**Jib No. 132 With 6 096 mm Strut On**  
**Boom No. 44A With Heavy Lift Top**  
**80 560 kg Counterweight**  
**360 Degree Rating**  
**On Extended Outriggers**



### 24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>76.2m (250 Ft.) BOOM</b>										
22.9	80.3	102.2	23 400 *							22.9
24.0	79.6	102.0	23 100 *							24.0
26.0	78.4	101.5	22 700 *	80.9	100.7	20 100*				26.0
28.0	77.3	101.0	22 300 *	79.7	100.2	19 800*				28.0
30.0	76.1	100.4	21 900 *	78.5	99.6	19 600*				30.0
32.0	74.9	99.8	21 600 *	77.3	99.0	19 300*	79.8	97.3	14 800*	32.0
34.0	73.7	99.2	21 200 *	76.1	98.4	19 000*	78.6	96.7	14 500*	34.0
36.0	72.5	98.5	20 900 *	74.9	97.7	18 700*	77.3	96.0	14 100*	36.0
38.0	71.3	97.8	20 600 *	73.7	96.9	18 500*	76.1	95.2	13 800*	38.0
40.0	70.1	97.0	20 300 *	72.5	96.1	18 300*	74.8	94.4	13 400*	40.0
44.0	67.6	95.3	19 700 *	70.0	94.4	17 800*	72.3	92.6	12 800*	44.0
48.0	65.1	93.3	19 000	67.4	92.4	17 400*	69.7	90.6	12 300*	48.0
52.0	62.5	91.2	16 700	64.8	90.2	17 100	67.0	88.4	11 800*	52.0
56.0	59.9	88.8	14 400	62.2	87.8	15 100	64.3	85.9	11 300*	56.0
60.0	57.2	86.1	12 400	59.4	85.1	13 100	61.5	83.1	11 000*	60.0
64.0	54.3	83.2	10 400 *	56.6	82.1	11 300	58.6	80.1	10 600*	64.0
68.0	51.4	79.9	8 600 *	53.6	78.8	9 300*	55.5	76.7	10 000*	68.0
72.0	48.3	76.2	6 900 *	50.5	75.1	7 600*	52.3	72.9	8 200*	72.0
76.0	45.1	72.2	5 500 *	47.2	71.0	6 100*	48.9	68.6	6 600*	76.0
80.0	41.7	67.6	4 200 *	43.7	66.3	4 700*				80.0
84.0	38.0	62.4	3 000 *	39.9	61.0	3 400*				84.0
88.0	33.9	56.4	1 900 *	35.7	54.9	2 200*				88.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>39.6m (130 Ft.) BOOM</b>										
18.3	80.1	72.1	18 300 *							18.3
20.0	78.7	71.6	17 900 *							20.0
22.0	77.0	71.1	17 400 *							22.0
24.0	75.3	70.5	16 900 *	79.8	69.7	15 400*				24.0
26.0	73.6	69.8	16 500 *	78.0	69.0	15 000*				26.0
28.0	71.9	69.0	16 100 *	76.3	68.3	14 600*				28.0
30.0	70.1	68.2	15 700 *	74.5	67.4	14 200*	79.4	66.0	11 800*	30.0
32.0	68.3	67.3	15 300 *	72.7	66.5	13 800*	77.5	65.1	11 300*	32.0
34.0	66.5	66.3	14 900 *	70.9	65.5	13 400*	75.6	64.1	10 900*	34.0
36.0	64.7	65.3	14 400 *	69.0	64.5	13 100*	73.7	63.0	10 500*	36.0
38.0	62.8	64.1	14 000 *	67.1	63.3	12 800*	71.8	61.8	10 200*	38.0
40.0	60.9	62.9	13 600 *	65.2	62.1	12 500*	69.8	60.6	9 800*	40.0
44.0	57.0	60.1	12 900 *	61.2	59.3	11 900*	65.7	57.7	9 200*	44.0
48.0	52.8	56.9	12 200 *	57.0	56.0	11 300*	61.4	54.4	8 700*	48.0
52.0	48.4	53.2	11 600 *	52.5	52.3	10 900*	56.7	50.5	8 200*	52.0
56.0	43.6	48.9	11 100 *	47.6	47.8	10 200*	51.6	45.9	7 800*	56.0
60.0	38.3	43.7	10 600 *	42.1	42.4	9 600*				60.0
64.0	32.1	37.2	10 200 *	35.7	35.7	9 000*				64.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>42.7m (140 Ft.) BOOM</b>										
18.3	80.5	75.2	18 500 *							18.3
20.0	79.2	74.8	18 000 *							20.0
22.0	77.6	74.3	17 500 *							22.0
24.0	75.9	73.7	17 100 *							24.0
26.0	74.3	73.0	16 700 *	78.6	72.2	15 100*				26.0
28.0	72.7	72.3	16 300 *	76.9	71.5	14 700*				28.0
30.0	71.0	71.5	15 900 *	75.2	70.7	14 300*	79.8	69.2	11 900*	30.0
32.0	69.3	70.6	15 500 *	73.5	69.9	14 000*	78.1	68.4	11 500*	32.0
34.0	67.6	69.7	15 100 *	71.8	68.9	13 600*	76.3	67.4	11 100*	34.0
36.0	65.8	68.7	14 700 *	70.0	67.9	13 300*	74.5	66.4	10 700*	36.0
38.0	64.1	67.6	14 300 *	68.2	66.8	12 900*	72.7	65.3	10 300*	38.0
40.0	62.3	66.5	13 900 *	66.4	65.6	12 600*	70.8	64.1	10 000*	40.0
44.0	58.6	63.9	13 200 *	62.6	63.0	12 000*	67.0	61.4	9 400*	44.0
48.0	54.7	60.9	12 500 *	58.7	60.0	11 500*	62.9	58.3	8 800*	48.0
52.0	50.6	57.5	11 900 *	54.5	56.5	11 000*	58.6	54.8	8 400*	52.0
56.0	46.2	53.5	11 400 *	50.0	52.4	10 500*	54.0	50.6	8 000*	56.0
60.0	41.4	48.8	10 900 *	45.1	47.6	9 900*	48.9	45.6	7 600*	60.0
64.0	36.0	43.2	10 400 *	39.6	41.8	9 300*				64.0
68.0	29.7	36.1	10 100 *							68.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>45.7m (150 Ft.) BOOM</b>										
18.3	80.9	78.3	18 500*							18.3
20.0	79.6	77.9	18 100*							20.0
22.0	78.1	77.4	17 700*							22.0
24.0	76.5	76.8	17 300*							24.0
26.0	75.0	76.2	16 800*	79.0	75.4	15 200*				26.0
28.0	73.4	75.5	16 400*	77.4	74.7	14 900*				28.0
30.0	71.8	74.8	16 100*	75.8	74.0	14 500*				30.0
32.0	70.2	74.0	15 700*	74.2	73.2	14 100*	78.6	71.6	11 700*	32.0
34.0	68.5	73.1	15 300*	72.6	72.3	13 800*	76.9	70.7	11 200*	34.0
36.0	66.9	72.1	14 900*	70.9	71.3	13 400*	75.2	69.7	10 800*	36.0
38.0	65.2	71.1	14 500*	69.2	70.3	13 100*	73.5	68.7	10 500*	38.0
40.0	63.5	70.0	14 200*	67.5	69.1	12 800*	71.7	67.6	10 100*	40.0
44.0	60.0	67.5	13 500*	63.9	66.7	12 200*	68.1	65.0	9 500*	44.0
48.0	56.4	64.7	12 800*	60.2	63.8	11 700*	64.3	62.2	9 000*	48.0
52.0	52.5	61.5	12 200*	56.3	60.6	11 200*	60.3	58.8	8 500*	52.0
56.0	48.5	57.8	11 600*	52.2	56.8	10 800*	56.0	55.0	8 100*	56.0
60.0	44.1	53.6	11 100*	47.7	52.4	10 200*	51.4	50.5	7 800*	60.0
64.0	39.3	48.5	10 700*	42.8	47.3	9 600*	46.2	45.1	7 500*	64.0
68.0	33.9	42.5	10 300*	37.2	41.0	9 100*				68.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>48.8m (160 Ft.) BOOM</b>										
19.8	80.2	81.1	18 300 *							19.8
20.0	80.0	81.1	18 300 *							20.0
22.0	78.5	80.6	17 800 *							22.0
24.0	77.1	80.0	17 400 *							24.0
26.0	75.6	79.4	17 000 *	79.5	78.6	15 300*				26.0
28.0	74.0	78.8	16 600 *	78.0	77.9	15 000*				28.0
30.0	72.5	78.0	16 200 *	76.4	77.2	14 600*				30.0
32.0	71.0	77.2	15 900 *	74.9	76.4	14 200*	79.1	74.9	11 700*	32.0
34.0	69.4	76.4	15 500 *	73.3	75.6	13 900*	77.5	74.0	11 400*	34.0
36.0	67.8	75.5	15 200 *	71.7	74.7	13 600*	75.9	73.1	11 000*	36.0
38.0	66.2	74.5	14 800 *	70.1	73.7	13 300*	74.2	72.1	10 600*	38.0
40.0	64.6	73.5	14 400 *	68.4	72.6	13 000*	72.5	71.0	10 300*	40.0
44.0	61.3	71.2	13 700 *	65.1	70.3	12 400*	69.1	68.6	9 700*	44.0
48.0	57.9	68.5	13 000 *	61.6	67.6	11 900*	65.5	65.9	9 200*	48.0
52.0	54.3	65.5	12 400 *	57.9	64.5	11 400*	61.7	62.8	8 700*	52.0
56.0	50.5	62.0	11 900 *	54.1	61.0	11 000*	57.8	59.2	8 300*	56.0
60.0	46.4	58.1	11 400 *	50.0	57.0	10 500*	53.5	55.0	7 900*	60.0
64.0	42.1	53.5	10 900 *	45.5	52.3	9 900*	48.9	50.2	7 700*	64.0
68.0	37.3	48.1	10 500 *	40.5	46.8	9 400*				68.0
72.0	31.7	41.6	9 200 *							72.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>51.8m (170 Ft.) BOOM</b>										
19.8	80.5	84.2	18 500 *							19.8
20.0	80.4	84.2	18 400 *							20.0
22.0	79.0	83.7	17 900 *							22.0
24.0	77.5	83.2	17 500 *							24.0
26.0	76.1	82.6	17 200 *	79.9	81.8	15 400*				26.0
28.0	74.7	82.0	16 800 *	78.4	81.1	15 100*				28.0
30.0	73.2	81.3	16 400 *	76.9	80.4	14 700*				30.0
32.0	71.7	80.5	16 100 *	75.5	79.7	14 400*	79.5	78.1	11 900*	32.0
34.0	70.2	79.7	15 700 *	73.9	78.9	14 100*	78.0	77.3	11 500*	34.0
36.0	68.7	78.8	15 400 *	72.4	78.0	13 700*	76.4	76.4	11 100*	36.0
38.0	67.2	77.9	15 000 *	70.9	77.1	13 400*	74.9	75.4	10 800*	38.0
40.0	65.6	76.9	14 600 *	69.3	76.0	13 100*	73.3	74.4	10 500*	40.0
44.0	62.5	74.7	14 000 *	66.1	73.8	12 600*	70.0	72.1	9 900*	44.0
48.0	59.2	72.2	13 300 *	62.8	71.3	12 100*	66.6	69.5	9 300*	48.0
52.0	55.8	69.4	12 700 *	59.4	68.4	11 600*	63.1	66.6	8 900*	52.0
56.0	52.3	66.1	12 100 *	55.7	65.1	11 200*	59.3	63.3	8 500*	56.0
60.0	48.5	62.4	11 600 *	51.9	61.4	10 800*	55.4	59.4	8 100*	60.0
64.0	44.5	58.2	11 200 *	47.8	57.1	10 200*	51.1	55.0	7 800*	64.0
68.0	40.1	53.4	10 700 *	43.4	52.1	9 700*	46.5	49.8	7 500*	68.0
72.0	35.3	47.6	9 100 *	38.4	46.1	9 200*				72.0
76.0	29.6	40.5	7 600 *							76.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>54.9m (180 Ft.) BOOM</b>										
19.8	80.9	87.3	18 500*							19.8
20.0	80.7	87.3	18 500*							20.0
22.0	79.4	86.8	18 100*							22.0
24.0	78.0	86.3	17 700*							24.0
26.0	76.6	85.8	17 300*	80.3	84.9	15 500*				26.0
28.0	75.2	85.2	16 900*	78.9	84.3	15 200*				28.0
30.0	73.8	84.5	16 500*	77.4	83.7	14 800*				30.0
32.0	72.4	83.8	16 200*	76.0	82.9	14 500*				32.0
34.0	71.0	83.0	15 900*	74.6	82.2	14 200*	78.5	80.5	11 600*	34.0
36.0	69.5	82.2	15 500*	73.1	81.3	13 900*	77.0	79.7	11 300*	36.0
38.0	68.1	81.3	15 200*	71.6	80.4	13 600*	75.5	78.7	10 900*	38.0
40.0	66.6	80.3	14 900*	70.1	79.4	13 300*	73.9	77.8	10 600*	40.0
44.0	63.6	78.2	14 200*	67.1	77.3	12 700*	70.8	75.6	10 000*	44.0
48.0	60.5	75.8	13 500*	63.9	74.9	12 200*	67.6	73.2	9 500*	48.0
52.0	57.2	73.1	12 900*	60.7	72.2	11 800*	64.3	70.4	9 000*	52.0
56.0	53.9	70.1	12 400*	57.3	69.1	11 300*	60.8	67.2	8 600*	56.0
60.0	50.4	66.6	11 900*	53.7	65.6	11 000*	57.1	63.6	8 200*	60.0
64.0	46.6	62.7	11 400*	49.9	61.6	10 500*	53.1	59.5	7 900*	64.0
68.0	42.6	58.3	10 600*	45.8	57.0	9 900*	48.9	54.8	7 700*	68.0
72.0	38.2	53.1	8 900*	41.3	51.7	9 400*				72.0
76.0	33.3	46.9	7 400*	36.2	45.3	7 900*				76.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>57.9m (190 Ft.) BOOM</b>										
21.3	80.2	90.1	18 300 *							21.3
22.0	79.7	90.0	18 200 *							22.0
24.0	78.4	89.5	17 800 *							24.0
26.0	77.1	88.9	17 400 *	80.6	88.1	15 600*				26.0
28.0	75.7	88.4	17 000 *	79.3	87.5	15 300*				28.0
30.0	74.4	87.7	16 700 *	77.9	86.9	14 900*				30.0
32.0	73.0	87.0	16 400 *	76.5	86.2	14 600*				32.0
34.0	71.7	86.3	16 000 *	75.1	85.4	14 300*	78.9	83.7	11 700*	34.0
36.0	70.3	85.5	15 700 *	73.7	84.6	14 000*	77.5	82.9	11 400*	36.0
38.0	68.9	84.6	15 400 *	72.3	83.7	13 700*	76.0	82.1	11 000*	38.0
40.0	67.4	83.7	15 000 *	70.9	82.8	13 400*	74.6	81.1	10 700*	40.0
44.0	64.6	81.7	14 400 *	68.0	80.8	12 900*	71.6	79.0	10 100*	44.0
48.0	61.6	79.4	13 800 *	65.0	78.5	12 400*	68.5	76.7	9 600*	48.0
52.0	58.5	76.8	13 200 *	61.9	75.9	11 900*	65.3	74.1	9 200*	52.0
56.0	55.4	74.0	12 600 *	58.6	72.9	11 500*	62.0	71.1	8 800*	56.0
60.0	52.0	70.7	12 100 *	55.3	69.6	11 100*	58.6	67.7	8 400*	60.0
64.0	48.5	67.1	11 700 *	51.7	65.9	10 700*	54.9	63.9	8 100*	64.0
68.0	44.8	62.9	10 300 *	47.9	61.7	10 200*	51.0	59.5	7 800*	68.0
72.0	40.8	58.1	8 700 *	43.8	56.8	9 400*	46.7	54.5	7 500*	72.0
76.0	36.4	52.6	7 300 *	39.3	51.1	7 800*				76.0
80.0	31.4	46.0	5 900 *							80.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>61.0m (200 Ft.) BOOM</b>										
21.3	80.5	93.2	18 500 *							21.3
22.0	80.1	93.1	18 300 *							22.0
24.0	78.8	92.6	17 900 *							24.0
26.0	77.5	92.1	17 500 *							26.0
28.0	76.2	91.5	17 200 *	79.6	90.7	15 300*				28.0
30.0	74.9	90.9	16 800 *	78.3	90.1	15 100*				30.0
32.0	73.6	90.3	16 500 *	77.0	89.4	14 700*				32.0
34.0	72.3	89.5	16 200 *	75.7	88.7	14 400*	79.3	87.0	11 800*	34.0
36.0	71.0	88.8	15 900 *	74.3	87.9	14 100*	77.9	86.2	11 500*	36.0
38.0	69.6	87.9	15 600 *	72.9	87.0	13 800*	76.5	85.3	11 200*	38.0
40.0	68.3	87.1	15 300 *	71.6	86.2	13 600*	75.1	84.4	10 800*	40.0
44.0	65.5	85.1	14 600 *	68.8	84.2	13 000*	72.3	82.5	10 300*	44.0
48.0	62.6	82.9	14 000 *	65.9	82.0	12 600*	69.3	80.2	9 700*	48.0
52.0	59.7	80.5	13 400 *	62.9	79.5	12 100*	66.3	77.7	9 300*	52.0
56.0	56.7	77.8	12 800 *	59.9	76.7	11 700*	63.2	74.9	8 900*	56.0
60.0	53.6	74.7	12 400 *	56.7	73.6	11 300*	59.9	71.7	8 500*	60.0
64.0	50.3	71.2	11 900 *	53.3	70.1	10 900*	56.5	68.1	8 200*	64.0
68.0	46.8	67.4	10 100 *	49.8	66.2	10 500*	52.8	64.0	7 900*	68.0
72.0	43.1	63.0	8 500 *	46.0	61.7	9 200*	48.9	59.4	7 600*	72.0
76.0	39.1	57.9	7 000 *	41.9	56.5	7 600*				76.0
80.0	34.6	52.0	5 700 *	37.4	50.4	6 200*				80.0
84.0	29.6	44.9	4 500 *							84.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>64.0m (210 Ft.) BOOM</b>										
21.3	80.8	96.3	18 500 *							21.3
22.0	80.4	96.2	18 400 *							22.0
24.0	79.2	95.7	18 000 *							24.0
26.0	77.9	95.2	17 700 *							26.0
28.0	76.7	94.7	17 300 *	80.0	93.8	15 400*				28.0
30.0	75.4	94.1	17 000 *	78.7	93.2	15 100*				30.0
32.0	74.2	93.5	16 600 *	77.4	92.6	14 800*				32.0
34.0	72.9	92.8	16 300 *	76.1	91.9	14 500*	79.7	90.2	11 900*	34.0
36.0	71.6	92.0	16 000 *	74.8	91.1	14 200*	78.4	89.4	11 600*	36.0
38.0	70.3	91.2	15 700 *	73.5	90.3	14 000*	77.0	88.6	11 300*	38.0
40.0	69.0	90.4	15 400 *	72.2	89.5	13 700*	75.7	87.7	11 000*	40.0
44.0	66.3	88.5	14 800 *	69.5	87.6	13 200*	72.9	85.8	10 400*	44.0
48.0	63.6	86.4	14 200 *	66.8	85.5	12 700*	70.1	83.7	9 900*	48.0
52.0	60.8	84.1	13 600 *	63.9	83.1	12 200*	67.2	81.3	9 400*	52.0
56.0	57.9	81.5	13 100 *	61.0	80.5	11 800*	64.2	78.6	9 000*	56.0
60.0	55.0	78.6	12 600 *	58.0	77.5	11 400*	61.1	75.6	8 700*	60.0
64.0	51.8	75.3	11 900 *	54.8	74.2	11 100*	57.9	72.2	8 300*	64.0
68.0	48.6	71.7	10 100 *	51.5	70.5	10 700*	54.5	68.4	8 000*	68.0
72.0	45.1	67.5	8 500 *	48.0	66.3	9 200*	50.8	64.1	7 800*	72.0
76.0	41.4	62.9	7 000 *	44.2	61.6	7 600*	46.9	59.2	7 500*	76.0
80.0	37.4	57.6	5 700 *	40.1	56.1	6 200*				80.0
84.0	32.9	51.3	4 500 *	35.5	49.6	4 900*				84.0




# Liftcrane Jib Capacities

Meets  
ANSI B30.5  
Requirements

## 2250T

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**



### 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>67.1m (220 Ft.) BOOM</b>										
22.9	80.2	99.1	18 300 *							22.9
24.0	79.5	98.9	18 100 *							24.0
26.0	78.3	98.4	17 800 *							26.0
28.0	77.1	97.9	17 400 *	80.3	97.0	15 500*				28.0
30.0	75.9	97.3	17 100 *	79.1	96.4	15 200*				30.0
32.0	74.7	96.7	16 800 *	77.8	95.8	14 900*				32.0
34.0	73.4	96.0	16 500 *	76.6	95.1	14 600*	80.0	93.4	12 000*	34.0
36.0	72.2	95.3	16 200 *	75.3	94.4	14 400*	78.8	92.6	11 700*	36.0
38.0	71.0	94.5	15 800 *	74.1	93.6	14 100*	77.5	91.8	11 400*	38.0
40.0	69.7	93.7	15 600 *	72.8	92.8	13 800*	76.2	91.0	11 100*	40.0
44.0	67.1	91.9	15 000 *	70.2	91.0	13 300*	73.5	89.2	10 500*	44.0
48.0	64.5	89.9	14 400 *	67.6	88.9	12 800*	70.8	87.1	10 000*	48.0
52.0	61.8	87.7	13 800 *	64.9	86.7	12 400*	68.1	84.8	9 500*	52.0
56.0	59.1	85.2	13 300 *	62.1	84.1	12 000*	65.2	82.2	9 100*	56.0
60.0	56.2	82.4	12 800 *	59.2	81.3	11 600*	62.2	79.4	8 800*	60.0
64.0	53.3	79.3	11 600 *	56.2	78.2	11 200*	59.2	76.2	8 400*	64.0
68.0	50.2	75.8	9 800 *	53.1	74.7	10 700*	55.9	72.6	8 100*	68.0
72.0	46.9	72.0	8 200 *	49.8	70.8	9 000*	52.5	68.6	7 900*	72.0
76.0	43.5	67.6	6 700 *	46.2	66.3	7 400*	48.9	64.0	7 700*	76.0
80.0	39.8	62.7	5 400 *	42.5	61.3	6 000*				80.0
84.0	35.7	57.1	4 200 *	38.3	55.5	4 700*				84.0
88.0	31.2	50.4	3 100 *							88.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>70.1m (230 Ft.) BOOM</b>										
22.9	80.5	102.2	18 400 *							22.9
24.0	79.8	102.0	18 200 *							24.0
26.0	78.7	101.5	17 900 *							26.0
28.0	77.5	101.0	17 500 *	80.6	100.1	15 600*				28.0
30.0	76.3	100.5	17 200 *	79.4	99.6	15 300*				30.0
32.0	75.2	99.9	16 900 *	78.2	99.0	15 000*				32.0
34.0	74.0	99.2	16 600 *	77.0	98.3	14 700*	80.4	96.5	12 100*	34.0
36.0	72.8	98.5	16 300 *	75.8	97.6	14 500*	79.1	95.8	11 800*	36.0
38.0	71.6	97.8	16 000 *	74.6	96.9	14 200*	77.9	95.1	11 500*	38.0
40.0	70.3	97.0	15 700 *	73.4	96.1	13 900*	76.6	94.3	11 200*	40.0
44.0	67.9	95.3	15 200 *	70.9	94.3	13 400*	74.1	92.5	10 600*	44.0
48.0	65.4	93.3	14 600 *	68.3	92.4	13 000*	71.5	90.5	10 100*	48.0
52.0	62.8	91.2	14 000 *	65.7	90.2	12 500*	68.8	88.3	9 700*	52.0
56.0	60.1	88.8	13 500 *	63.0	87.8	12 100*	66.1	85.9	9 300*	56.0
60.0	57.4	86.1	13 000	60.3	85.1	11 700*	63.3	83.1	8 900*	60.0
64.0	54.6	83.2	11 400 *	57.4	82.1	11 400*	60.3	80.1	8 600*	64.0
68.0	51.7	79.9	9 600 *	54.5	78.8	10 500*	57.3	76.7	8 300*	68.0
72.0	48.6	76.3	7 900 *	51.4	75.1	8 800*	54.1	72.9	8 000*	72.0
76.0	45.4	72.2	6 500 *	48.1	70.9	7 200*	50.7	68.6	7 800*	76.0
80.0	41.9	67.6	5 200 *	44.6	66.3	5 800*	47.0	63.8	6 600*	80.0
84.0	38.2	62.4	4 000 *	40.8	61.0	4 500*				84.0
88.0	34.1	56.5	2 900 *	36.6	54.8	3 400*				88.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>73.2m (240 Ft.) BOOM</b>										
22.9	80.8	105.4	18 500 *							22.9
24.0	80.2	105.1	18 300 *							24.0
26.0	79.0	104.7	18 000 *							26.0
28.0	77.9	104.2	17 600 *							28.0
30.0	76.7	103.6	17 300 *	79.7	102.7	15 400*				30.0
32.0	75.6	103.0	17 000 *	78.6	102.1	15 100*				32.0
34.0	74.5	102.4	16 700 *	77.4	101.5	14 800*	80.7	99.7	12 100*	34.0
36.0	73.3	101.8	16 400 *	76.3	100.8	14 600*	79.5	99.0	11 900*	36.0
38.0	72.1	101.0	16 200 *	75.1	100.1	14 300*	78.3	98.3	11 600*	38.0
40.0	70.9	100.3	15 900 *	73.9	99.3	14 100*	77.1	97.5	11 300*	40.0
44.0	68.6	98.6	15 300 *	71.5	97.7	13 500*	74.6	95.8	10 700*	44.0
48.0	66.1	96.8	14 800 *	69.0	95.8	13 100*	72.1	93.9	10 200*	48.0
52.0	63.7	94.7	14 200 *	66.5	93.7	12 600*	69.5	91.8	9 800*	52.0
56.0	61.1	92.4	13 700 *	64.0	91.3	12 200*	66.9	89.4	9 400*	56.0
60.0	58.5	89.8	13 000	61.3	88.8	11 900*	64.2	86.8	9 000*	60.0
64.0	55.8	87.0	11 100	58.6	85.9	11 500*	61.4	83.9	8 700*	64.0
68.0	53.0	83.9	9 300 *	55.8	82.7	10 300*	58.5	80.7	8 400*	68.0
72.0	50.1	80.4	7 700 *	52.8	79.2	8 500*	55.5	77.1	8 100*	72.0
76.0	47.1	76.6	6 200 *	49.7	75.3	7 000*	52.3	73.1	7 900*	76.0
80.0	43.8	72.3	4 900 *	46.4	71.0	5 500*	48.9	68.6	6 400*	80.0
84.0	40.4	67.5	3 700 *	42.9	66.1	4 300*				84.0
88.0	36.7	62.0	2 600 *	39.1	60.5	3 100*				88.0
92.0				34.8	53.9	2 000*				92.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>39.6m (130 Ft.) BOOM</b>										
18.3	80.9	78.4	14 800 *							18.3
20.0	79.6	78.0	14 500 *							20.0
22.0	78.0	77.5	13 900 *							22.0
24.0	76.5	76.9	13 500 *							24.0
26.0	74.9	76.3	13 000 *	80.1	75.7	10 800*				26.0
28.0	73.4	75.6	12 600 *	78.5	75.0	10 400*				28.0
30.0	71.8	74.8	12 100 *	76.9	74.2	10 000*				30.0
32.0	70.1	74.0	11 700 *	75.3	73.4	9 700*				32.0
34.0	68.5	73.1	11 200 *	73.7	72.5	9 400*	78.7	70.9	8 100*	34.0
36.0	66.9	72.2	10 800 *	72.0	71.6	9 100*	77.0	69.9	7 900*	36.0
38.0	65.2	71.1	10 400 *	70.3	70.6	8 800*	75.3	68.9	7 700*	38.0
40.0	63.5	70.0	10 100 *	68.6	69.5	8 500*	73.5	67.7	7 400*	40.0
44.0	60.0	67.6	9 400 *	65.1	67.0	7 900*	69.9	65.2	7 000*	44.0
48.0	56.3	64.8	8 700 *	61.4	64.2	7 400*	66.1	62.3	6 600*	48.0
52.0	52.5	61.6	8 100 *	57.5	61.0	7 000*	62.1	59.0	6 300*	52.0
56.0	48.5	57.9	7 600 *	53.4	57.3	6 600*	57.9	55.2	6 000*	56.0
60.0	44.1	53.6	7 100 *	49.0	53.0	6 200*	53.2	50.7	5 700*	60.0
64.0	39.3	48.6	6 600 *	44.2	48.0	5 900*	48.1	45.3	5 500*	64.0
68.0	33.9	42.6	6 200 *	38.6	41.8	5 600*				68.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>42.7m (140 Ft.) BOOM</b>										
19.8	80.1	81.1	14 600 *							19.8
20.0	80.0	81.1	14 600 *							20.0
22.0	78.5	80.6	14 100 *							22.0
24.0	77.0	80.1	13 600 *							24.0
26.0	75.5	79.5	13 200 *	80.5	78.8	10 900*				26.0
28.0	74.0	78.8	12 700 *	79.0	78.2	10 500*				28.0
30.0	72.5	78.1	12 300 *	77.5	77.5	10 200*				30.0
32.0	71.0	77.3	11 900 *	75.9	76.7	9 800*				32.0
34.0	69.4	76.5	11 500 *	74.3	75.8	9 500*	79.2	74.1	8 200*	34.0
36.0	67.8	75.5	11 100 *	72.8	74.9	9 200*	77.6	73.2	8 000*	36.0
38.0	66.2	74.6	10 700 *	71.1	74.0	8 900*	75.9	72.2	7 800*	38.0
40.0	64.6	73.5	10 300 *	69.5	72.9	8 600*	74.3	71.1	7 500*	40.0
44.0	61.3	71.2	9 600 *	66.2	70.6	8 100*	70.8	68.8	7 100*	44.0
48.0	57.8	68.6	8 900 *	62.7	68.0	7 600*	67.3	66.0	6 700*	48.0
52.0	54.2	65.5	8 400 *	59.1	64.9	7 100*	63.5	62.9	6 400*	52.0
56.0	50.5	62.1	7 800 *	55.2	61.5	6 700*	59.5	59.3	6 100*	56.0
60.0	46.4	58.2	7 300 *	51.2	57.5	6 400*	55.3	55.2	5 800*	60.0
64.0	42.1	53.6	6 900 *	46.8	52.9	6 000*	50.7	50.4	5 600*	64.0
68.0	37.3	48.2	6 500 *	41.9	47.5	5 800*	45.5	44.6	5 400*	68.0
72.0	31.8	41.7	6 100 *	36.3	40.9	5 500*				72.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>45.7m (150 Ft.) BOOM</b>										
19.8	80.5	84.3	14 700 *							19.8
20.0	80.4	84.2	14 700 *							20.0
22.0	78.9	83.7	14 300 *							22.0
24.0	77.5	83.2	13 800 *							24.0
26.0	76.1	82.6	13 400 *							26.0
28.0	74.6	82.0	12 900 *	79.4	81.4	10 600*				28.0
30.0	73.2	81.3	12 500 *	78.0	80.7	10 300*				30.0
32.0	71.7	80.6	12 100 *	76.5	79.9	9 900*				32.0
34.0	70.2	79.8	11 700 *	75.0	79.1	9 600*	79.7	77.4	8 300*	34.0
36.0	68.7	78.9	11 300 *	73.5	78.3	9 300*	78.1	76.5	8 000*	36.0
38.0	67.2	78.0	10 900 *	71.9	77.3	9 000*	76.5	75.5	7 900*	38.0
40.0	65.6	77.0	10 500 *	70.4	76.3	8 700*	74.9	74.5	7 600*	40.0
44.0	62.5	74.8	9 900 *	67.2	74.1	8 200*	71.7	72.3	7 200*	44.0
48.0	59.2	72.3	9 200 *	63.9	71.6	7 800*	68.3	69.7	6 800*	48.0
52.0	55.8	69.4	8 600 *	60.4	68.8	7 300*	64.7	66.7	6 500*	52.0
56.0	52.3	66.2	8 100 *	56.9	65.5	6 900*	61.0	63.4	6 200*	56.0
60.0	48.5	62.5	7 600 *	53.1	61.8	6 500*	57.1	59.6	5 900*	60.0
64.0	44.5	58.3	7 100 *	49.0	57.6	6 200*	52.9	55.1	5 700*	64.0
68.0	40.1	53.4	6 700 *	44.6	52.7	5 900*	48.2	50.0	5 500*	68.0
72.0	35.3	47.7	6 300 *	39.7	46.9	5 700*				72.0
76.0	29.7	40.6	6 000 *	33.9	39.7	5 500*				76.0




# Liftcrane Jib Capacities

Meets  
ANSI B30.5  
Requirements

**2250T**

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>48.8m (160 Ft.) BOOM</b>										
19.8	80.8	87.4	14 800 *							19.8
20.0	80.7	87.3	14 800 *							20.0
22.0	79.4	86.9	14 400 *							22.0
24.0	78.0	86.4	14 000 *							24.0
26.0	76.6	85.8	13 500 *							26.0
28.0	75.2	85.2	13 100 *	79.8	84.5	10 700*				28.0
30.0	73.8	84.5	12 700 *	78.4	83.9	10 400*				30.0
32.0	72.4	83.8	12 300 *	77.0	83.2	10 100*				32.0
34.0	70.9	83.1	11 900 *	75.5	82.4	9 800*	80.1	80.6	8 400*	34.0
36.0	69.5	82.2	11 500 *	74.1	81.6	9 500*	78.6	79.8	8 100*	36.0
38.0	68.0	81.3	11 100 *	72.6	80.7	9 200*	77.1	78.8	7 900*	38.0
40.0	66.6	80.4	10 800 *	71.1	79.7	8 900*	75.5	77.9	7 700*	40.0
44.0	63.5	78.3	10 100 *	68.1	77.6	8 400*	72.4	75.7	7 300*	44.0
48.0	60.4	75.9	9 500 *	65.0	75.2	7 900*	69.2	73.3	6 900*	48.0
52.0	57.2	73.2	8 900 *	61.7	72.5	7 500*	65.9	70.5	6 600*	52.0
56.0	53.9	70.1	8 300 *	58.3	69.5	7 100*	62.4	67.3	6 300*	56.0
60.0	50.4	66.7	7 800 *	54.8	66.0	6 700*	58.7	63.7	6 000*	60.0
64.0	46.6	62.8	7 300 *	51.0	62.1	6 300*	54.8	59.7	5 800*	64.0
68.0	42.6	58.3	6 900 *	46.9	57.6	6 100*	50.5	54.9	5 600*	68.0
72.0	38.3	53.1	6 500 *	42.5	52.3	5 800*	45.8	49.4	5 400*	72.0
76.0	33.4	47.0	6 200 *	37.5	46.1	5 600*				76.0
80.0	27.6	39.3	5 900 *							80.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>51.8m (170 Ft.) BOOM</b>										
21.3	80.2	90.2	14 600 *							21.3
22.0	79.7	90.0	14 500 *							22.0
24.0	78.4	89.5	14 100 *							24.0
26.0	77.1	89.0	13 700 *							26.0
28.0	75.7	88.4	13 300 *	80.2	87.7	10 800*				28.0
30.0	74.4	87.8	12 800 *	78.8	87.1	10 400*				30.0
32.0	73.0	87.1	12 500 *	77.5	86.4	10 200*				32.0
34.0	71.6	86.3	12 100 *	76.1	85.6	9 900*	80.4	83.8	8 400*	34.0
36.0	70.2	85.5	11 700 *	74.7	84.8	9 600*	79.0	83.0	8 200*	36.0
38.0	68.8	84.7	11 400 *	73.3	84.0	9 300*	77.6	82.1	8 000*	38.0
40.0	67.4	83.8	11 000 *	71.8	83.1	9 000*	76.1	81.2	7 800*	40.0
44.0	64.5	81.7	10 300 *	68.9	81.1	8 500*	73.1	79.1	7 400*	44.0
48.0	61.6	79.5	9 700 *	65.9	78.8	8 000*	70.1	76.8	7 000*	48.0
52.0	58.5	76.9	9 100 *	62.8	76.2	7 600*	66.9	74.1	6 700*	52.0
56.0	55.3	74.0	8 500 *	59.6	73.3	7 200*	63.6	71.2	6 400*	56.0
60.0	52.0	70.8	8 000 *	56.3	70.1	6 800*	60.1	67.8	6 100*	60.0
64.0	48.5	67.1	7 600 *	52.8	66.4	6 500*	56.5	64.0	5 900*	64.0
68.0	44.8	63.0	7 200 *	49.0	62.2	6 200*	52.5	59.6	5 700*	68.0
72.0	40.8	58.2	6 800 *	45.0	57.4	6 000*	48.3	54.6	5 500*	72.0
76.0	36.4	52.7	6 400 *	40.5	51.8	5 700*				76.0
80.0	31.5	46.1	6 100 *	35.4	45.1	5 500*				80.0




# Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers**

**Meets  
ANSI B30.5  
Requirements**

**2250T**



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>54.9m (180 Ft.) BOOM</b>										
21.3	80.5	93.3	14 700 *							21.3
22.0	80.1	93.1	14 600 *							22.0
24.0	78.8	92.7	14 200 *							24.0
26.0	77.5	92.1	13 800 *							26.0
28.0	76.2	91.6	13 400 *	80.5	90.9	10 900*				28.0
30.0	74.9	91.0	13 000 *	79.2	90.3	10 500*				30.0
32.0	73.6	90.3	12 700 *	77.9	89.6	10 200*				32.0
34.0	72.3	89.6	12 200 *	76.6	88.9	9 900*				34.0
36.0	70.9	88.8	11 900 *	75.2	88.1	9 700*	79.4	86.2	8 300*	36.0
38.0	69.6	88.0	11 500 *	73.9	87.3	9 400*	78.0	85.4	8 000*	38.0
40.0	68.2	87.1	11 200 *	72.5	86.4	9 200*	76.6	84.5	7 900*	40.0
44.0	65.5	85.2	10 500 *	69.7	84.5	8 600*	73.8	82.5	7 400*	44.0
48.0	62.6	83.0	9 900 *	66.8	82.3	8 200*	70.8	80.3	7 100*	48.0
52.0	59.7	80.6	9 300 *	63.9	79.8	7 700*	67.8	77.8	6 800*	52.0
56.0	56.7	77.8	8 800 *	60.8	77.1	7 400*	64.7	74.9	6 500*	56.0
60.0	53.5	74.7	8 300 *	57.7	74.0	7 000*	61.4	71.8	6 200*	60.0
64.0	50.3	71.3	7 800 *	54.4	70.6	6 700*	58.0	68.2	6 000*	64.0
68.0	46.8	67.4	7 400 *	50.8	66.7	6 400*	54.3	64.1	5 800*	68.0
72.0	43.1	63.0	7 000 *	47.1	62.2	6 100*	50.4	59.5	5 600*	72.0
76.0	39.1	58.0	6 600 *	43.0	57.1	5 800*	46.1	54.1	5 400*	76.0
80.0	34.7	52.1	6 300 *	38.5	51.2	5 600*				80.0
84.0	29.6	45.0	5 500 *							84.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>57.9m (190 Ft.) BOOM</b>										
21.3	80.8	96.4	14 800 *							21.3
22.0	80.4	96.2	14 700 *							22.0
24.0	79.2	95.8	14 300 *							24.0
26.0	77.9	95.3	13 900 *							26.0
28.0	76.7	94.7	13 500 *							28.0
30.0	75.4	94.2	13 200 *	79.6	93.4	10 600*				30.0
32.0	74.1	93.5	12 800 *	78.3	92.8	10 300*				32.0
34.0	72.9	92.8	12 400 *	77.0	92.1	10 000*				34.0
36.0	71.6	92.1	12 100 *	75.7	91.4	9 800*	79.8	89.4	8 300*	36.0
38.0	70.3	91.3	11 700 *	74.4	90.6	9 500*	78.5	88.6	8 100*	38.0
40.0	69.0	90.4	11 400 *	73.1	89.7	9 200*	77.1	87.8	7 900*	40.0
44.0	66.3	88.6	10 700 *	70.4	87.9	8 800*	74.4	85.9	7 500*	44.0
48.0	63.6	86.5	10 100 *	67.7	85.8	8 300*	71.5	83.7	7 200*	48.0
52.0	60.8	84.2	9 500 *	64.9	83.4	7 900*	68.7	81.3	6 900*	52.0
56.0	57.9	81.5	9 000 *	62.0	80.8	7 500*	65.7	78.6	6 600*	56.0
60.0	54.9	78.6	8 500 *	58.9	77.9	7 100*	62.6	75.6	6 300*	60.0
64.0	51.8	75.4	8 000 *	55.8	74.6	6 800*	59.3	72.2	6 100*	64.0
68.0	48.6	71.7	7 600 *	52.5	70.9	6 500*	55.9	68.4	5 900*	68.0
72.0	45.1	67.6	7 200 *	49.0	66.8	6 200*	52.3	64.1	5 700*	72.0
76.0	41.4	63.0	6 800 *	45.3	62.1	5 900*	48.3	59.2	5 500*	76.0
80.0	37.4	57.6	6 400 *	41.2	56.7	5 700*				80.0
84.0	32.9	51.4	5 300 *	36.6	50.4	5 600*				84.0
88.0	27.8	43.8	4 200 *							88.0




**2250T**

# Liftcrane Jib Capacities

Meets  
ANSI B30.5  
Requirements

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>61.0m (200 Ft.) BOOM</b>										
22.9	80.2	99.2	14 600 *							22.9
24.0	79.5	98.9	14 400 *							24.0
26.0	78.3	98.4	14 000 *							26.0
28.0	77.1	97.9	13 700 *							28.0
30.0	75.9	97.3	13 300 *	79.9	96.6	10 700*				30.0
32.0	74.7	96.7	12 900 *	78.7	96.0	10 400*				32.0
34.0	73.4	96.1	12 600 *	77.5	95.3	10 100*				34.0
36.0	72.2	95.3	12 200 *	76.2	94.6	9 900*	80.1	92.7	8 400*	36.0
38.0	70.9	94.6	11 900 *	74.9	93.8	9 600*	78.8	91.9	8 200*	38.0
40.0	69.7	93.8	11 500 *	73.7	93.0	9 400*	77.5	91.0	8 000*	40.0
44.0	67.1	92.0	10 900 *	71.1	91.2	8 900*	74.9	89.2	7 600*	44.0
48.0	64.5	90.0	10 300 *	68.5	89.2	8 400*	72.2	87.2	7 300*	48.0
52.0	61.8	87.7	9 700 *	65.7	87.0	8 000*	69.4	84.9	7 000*	52.0
56.0	59.1	85.2	9 200 *	63.0	84.5	7 700*	66.6	82.3	6 700*	56.0
60.0	56.2	82.4	8 700 *	60.1	81.7	7 300*	63.6	79.4	6 400*	60.0
64.0	53.3	79.3	8 200 *	57.1	78.6	6 900*	60.6	76.2	6 200*	64.0
68.0	50.2	75.9	7 800 *	54.0	75.1	6 600*	57.3	72.6	5 900*	68.0
72.0	46.9	72.0	7 400 *	50.7	71.2	6 300*	53.9	68.6	5 700*	72.0
76.0	43.5	67.7	7 000 *	47.2	66.9	6 100*	50.3	64.0	5 600*	76.0
80.0	39.8	62.8	6 300 *	43.5	61.9	5 800*	46.3	58.8	5 500*	80.0
84.0	35.8	57.2	5 100 *	39.4	56.2	5 600*				84.0
88.0	31.2	50.5	4 000 *	34.7	49.4	4 600*				88.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>64.0m (210 Ft.) BOOM</b>										
22.9	80.5	102.3	14 700 *							22.9
24.0	79.8	102.0	14 500 *							24.0
26.0	78.7	101.6	14 200 *							26.0
28.0	77.5	101.1	13 800 *							28.0
30.0	76.3	100.5	13 500 *	80.2	99.7	10 800*				30.0
32.0	75.1	99.9	13 100 *	79.0	99.1	10 500*				32.0
34.0	73.9	99.3	12 700 *	77.9	98.5	10 200*				34.0
36.0	72.7	98.6	12 400 *	76.6	97.8	10 000*				36.0
38.0	71.5	97.8	12 000 *	75.4	97.1	9 700*	79.2	95.1	8 200*	38.0
40.0	70.3	97.1	11 700 *	74.2	96.3	9 500*	78.0	94.3	8 000*	40.0
44.0	67.9	95.3	11 100 *	71.7	94.6	9 000*	75.4	92.5	7 700*	44.0
48.0	65.3	93.4	10 500 *	69.2	92.6	8 600*	72.8	90.6	7 300*	48.0
52.0	62.8	91.2	9 900 *	66.6	90.5	8 100*	70.2	88.3	7 000*	52.0
56.0	60.1	88.8	9 400 *	63.9	88.1	7 700*	67.4	85.9	6 700*	56.0
60.0	57.4	86.2	8 900 *	61.2	85.4	7 400*	64.6	83.1	6 500*	60.0
64.0	54.6	83.2	8 400 *	58.3	82.4	7 100*	61.7	80.1	6 300*	64.0
68.0	51.7	80.0	8 000 *	55.4	79.2	6 800*	58.6	76.7	6 000*	68.0
72.0	48.6	76.3	7 600 *	52.3	75.5	6 500*	55.4	72.9	5 800*	72.0
76.0	45.4	72.3	7 200 *	49.0	71.4	6 200*	52.0	68.7	5 700*	76.0
80.0	41.9	67.7	6 200 *	45.5	66.8	6 000*	48.4	63.8	5 500*	80.0
84.0	38.2	62.5	5 100 *	41.8	61.6	5 700*				84.0
88.0	34.1	56.5	4 000 *	37.6	55.5	4 600*				88.0
92.0	29.5	49.5	2 900 *	32.9	48.3	4 000*				92.0




**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>67.1m (220 Ft.) BOOM</b>										
22.9	80.8	105.4	14 800 *							22.9
24.0	80.1	105.2	14 700 *							24.0
26.0	79.0	104.7	14 300 *							26.0
28.0	77.9	104.2	13 900 *							28.0
30.0	76.7	103.7	13 600 *							30.0
32.0	75.6	103.1	13 200 *	79.4	102.3	10 600*				32.0
34.0	74.4	102.5	12 900 *	78.2	101.7	10 300*				34.0
36.0	73.3	101.8	12 500 *	77.1	101.0	10 100*				36.0
38.0	72.1	101.1	12 200 *	75.9	100.3	9 800*	79.6	98.3	8 300*	38.0
40.0	70.9	100.3	11 900 *	74.7	99.6	9 600*	78.3	97.5	8 100*	40.0
44.0	68.5	98.7	11 300 *	72.3	97.9	9 100*	75.9	95.8	7 700*	44.0
48.0	66.1	96.8	10 700 *	69.8	96.0	8 700*	73.4	93.9	7 400*	48.0
52.0	63.6	94.7	10 100 *	67.3	93.9	8 300*	70.8	91.8	7 100*	52.0
56.0	61.1	92.4	9 600 *	64.8	91.6	7 900*	68.2	89.4	6 800*	56.0
60.0	58.5	89.9	9 100 *	62.2	89.1	7 500*	65.5	86.8	6 600*	60.0
64.0	55.8	87.0	8 600 *	59.4	86.3	7 200*	62.7	83.9	6 300*	64.0
68.0	53.0	83.9	8 200 *	56.6	83.1	6 900*	59.8	80.7	6 100*	68.0
72.0	50.1	80.5	7 800 *	53.7	79.7	6 600*	56.8	77.1	5 900*	72.0
76.0	47.1	76.7	7 200 *	50.6	75.8	6 400*	53.6	73.1	5 700*	76.0
80.0	43.8	72.4	5 900 *	47.3	71.5	6 100*	50.2	68.6	5 600*	80.0
84.0	40.4	67.6	4 800 *	43.9	66.7	5 700*	46.5	63.5	5 400*	84.0
88.0	36.7	62.1	3 700 *	40.1	61.1	4 500*				88.0
92.0	32.6	55.8	2 700 *	35.9	54.7	3 300*				92.0
96.0	27.9	48.2	1 800 *							96.0






**2250T**

# Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On  
Boom No. 44A With Heavy Lift Top  
80 560 kg Counterweight  
360 Degree Rating  
On Extended Outriggers

Meets  
ANSI B30.5  
Requirements



## 36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
<b>70.1m (230 Ft.) BOOM</b>										
24.4	80.2	108.2	14 700 *							24.4
26.0	79.3	107.8	14 400 *							26.0
28.0	78.2	107.4	14 000 *							28.0
30.0	77.1	106.8	13 700 *							30.0
32.0	76.0	106.3	13 300 *	79.7	105.5	10 700*				32.0
34.0	74.9	105.7	13 000 *	78.6	104.9	10 400*				34.0
36.0	73.8	105.0	12 700 *	77.4	104.2	10 200*				36.0
38.0	72.6	104.3	12 400 *	76.3	103.5	9 900*	79.9	101.5	8 400*	38.0
40.0	71.5	103.6	12 100 *	75.2	102.8	9 700*	78.7	100.8	8 200*	40.0
44.0	69.2	102.0	11 400 *	72.8	101.2	9 200*	76.3	99.1	7 800*	44.0
48.0	66.9	100.2	10 900 *	70.5	99.4	8 800*	73.9	97.3	7 500*	48.0
52.0	64.5	98.2	10 300 *	68.1	97.4	8 400*	71.5	95.2	7 200*	52.0
56.0	62.0	96.0	9 800 *	65.6	95.2	8 000*	68.9	92.9	6 900*	56.0
60.0	59.5	93.5	9 300 *	63.1	92.7	7 700*	66.3	90.4	6 600*	60.0
64.0	56.9	90.8	8 800 *	60.5	90.0	7 300*	63.7	87.6	6 400*	64.0
68.0	54.3	87.8	8 400 *	57.8	87.0	7 000*	60.9	84.6	6 200*	68.0
72.0	51.5	84.5	8 000 *	55.0	83.7	6 700*	58.0	81.2	6 000*	72.0
76.0	48.6	80.9	7 000 *	52.1	80.1	6 400*	55.0	77.4	5 800*	76.0
80.0	45.6	76.9	5 700 *	49.0	76.0	6 200*	51.8	73.2	5 600*	80.0
84.0	42.4	72.4	4 500 *	45.8	71.5	5 400*	48.4	68.5	5 500*	84.0
88.0	38.9	67.4	3 400 *	42.3	66.4	4 200*	44.8	63.1	4 800*	88.0
92.0	35.2	61.6	2 400 *	38.5	60.6	3 100*				92.0
96.0				34.2	53.8	2 100*				96.0