


Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

Meets
ANSI B30.5
Requirements



LIFTING CAPACITIES: Chart supplements boom capacity chart **No. 8462-AM**. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and do not exceed 85% of a static tipping load. Capacities based on structural competence are denoted by an asterisk (*). Capacities indicated by a (b) require 2 010 kg minimum block weight with 4 part hoist line reeving on 12.2m jib and 3 part on 18.3m jib.

82.3m and 85.3m boom lengths require only the middle three sheaves to be used on lower boom point. All other sheaves must be removed from lower boom point.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc. beneath boom and jib point sheaves is considered part of jib load. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up and outriggers fully extended (9 373 mm) and set. Refer to operators manual for outrigger positioning. Radii less than 12.8m not recommended when lifting over front of truck. Minimum boom angle over truck cab is 5 degrees.

Note: Set four main jacks first, then lower center front jack until it just contacts ground to prevent preloading of center front jack. Center front jack must be used when operating on outriggers.

Refer to boom rigging **No. A03746**, jib assembly **No. 192352**, Wire Rope Specification chart **No. 8464-A** and Counterweight Arrangement chart **No. 8469-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

MACHINE TRAVEL: Refer to Maximum Allowable Travel Specification chart **No. 8468-A** for machine travel without load.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

JIB POINT ELEVATION: Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with Manitowoc - Pierce T300 12 x 6 carrier, 7 976 mm wheel base, 3 505 mm front axle track, 2 946 mm rear axle track, 505/95R25 front tires, 445/95R25 rear tires, 4 686 mm outriggers, 8 534 mm retractable gantry, 12 part boom hoist reeving, two boom support straps and 55 880 kg counterweight.

Maximum capacity on 29mm wire rope is 13 610 kg per line.

Maximum Boom and Jib Lengths Lifted Unassisted Over Side or Rear of Extended Outriggers	
Boom Length	Jib No. 132
85.3m	—
82.3m	—
79.2m	—
76.2m	12.2m
73.2m	18.3m
70.1m	30.5m
67.1m	36.6m
Load block, hook and weight ball on ground at start.	




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
12.2	80.5	54.8	45 300 *b							12.2
13.0	79.6	54.6	43 900 *b							13.0
14.0	78.4	54.4	42 300 *b							14.0
15.0	77.3	54.1	41 000 *b							15.0
16.0	76.2	53.9	39 800 *b	78.6	53.6	32 900 *b				16.0
18.0	73.9	53.3	37 600 *b	76.3	53.0	31 600 *b	78.7	52.2	25 300*	18.0
20.0	71.6	52.6	35 700 *b	74.0	52.3	30 300*	76.3	51.5	24 200*	20.0
22.0	69.2	51.8	33 900 *b	71.6	51.5	29 200*	73.9	50.7	23 200*	22.0
24.0	66.9	50.9	32 400 *b	69.2	50.6	28 200*	71.5	49.8	22 300*	24.0
26.0	64.4	50.0	31 100 *b	66.7	49.6	27 300*	69.0	48.8	21 400*	26.0
28.0	61.9	48.9	29 800 *	64.2	48.5	26 500*	66.4	47.7	20 700*	28.0
30.0	59.4	47.7	28 700 *	61.7	47.3	25 800*	63.8	46.5	20 000*	30.0
32.0	56.8	46.3	27 700 *	59.0	46.0	25 100*	61.1	45.1	19 400*	32.0
34.0	54.1	44.9	26 800 *	56.3	44.5	24 500*	58.3	43.6	18 800*	34.0
36.0	51.3	43.3	25 900 *	53.5	42.9	24 000*	55.4	41.9	18 400*	36.0
38.0	48.3	41.5	24 500	50.5	41.0	23 500*	52.4	40.0	17 900*	38.0
40.0	45.2	39.5	22 500	47.4	39.0	22 900	49.2	38.0	17 500*	40.0
44.0	38.5	34.7	19 300	40.5	34.2	19 500				44.0
48.0	30.4	28.5	16 600							48.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.7m (140 Ft.) BOOM										
12.2	81.0	57.9	45 300 *b							12.2
13.0	80.1	57.7	44 300 *b							13.0
14.0	79.1	57.5	43 100 *b							14.0
15.0	78.0	57.3	41 800 *b							15.0
16.0	77.0	57.0	40 600 *b	79.2	56.7	33 300*b				16.0
18.0	74.8	56.5	38 400 *b	77.1	56.1	32 000*b	79.3	55.4	25 600*	18.0
20.0	72.6	55.8	36 500 *b	74.9	55.5	30 800*b	77.1	54.7	24 500*	20.0
22.0	70.4	55.1	34 800 *b	72.7	54.8	29 700*	74.9	54.0	23 500*	22.0
24.0	68.2	54.3	33 200 *b	70.4	53.9	28 700*	72.6	53.1	22 600*	24.0
26.0	65.9	53.4	31 900 *b	68.1	53.0	27 800*	70.3	52.2	21 800*	26.0
28.0	63.6	52.4	30 600 *b	65.8	52.0	27 000*	67.9	51.2	21 100*	28.0
30.0	61.3	51.2	29 500 *	63.4	50.9	26 300*	65.5	50.0	20 400*	30.0
32.0	58.9	50.0	28 500 *	61.0	49.6	25 600*	63.0	48.8	19 800*	32.0
34.0	56.4	48.7	27 500 *	58.5	48.3	25 000*	60.4	47.4	19 200*	34.0
36.0	53.8	47.2	26 300	55.9	46.8	24 400*	57.8	45.9	18 800*	36.0
38.0	51.1	45.6	24 100	53.2	45.1	23 900*	55.1	44.2	18 300*	38.0
40.0	48.4	43.8	22 200	50.4	43.3	22 600	52.2	42.3	17 900*	40.0
44.0	42.4	39.6	19 000	44.4	39.1	19 200	46.0	38.0	17 200*	44.0
48.0	35.6	34.4	16 300	37.5	33.8	16 500				48.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
13.7	79.9	60.7	44 200 *b							13.7
14.0	79.7	60.6	43 800 *b							14.0
15.0	78.7	60.4	42 600 *b							15.0
16.0	77.7	60.2	41 400 *b	79.8	59.8	33 700*b				16.0
18.0	75.6	59.6	39 200 *b	77.8	59.3	32 400*b				18.0
20.0	73.6	59.0	37 300 *b	75.7	58.7	31 200*b	77.8	57.9	24 800*	20.0
22.0	71.5	58.3	35 600 *b	73.6	58.0	30 200*	75.7	57.2	23 900*	22.0
24.0	69.4	57.6	34 100 *b	71.5	57.2	29 200*	73.6	56.4	23 000*	24.0
26.0	67.3	56.7	32 700 *b	69.4	56.4	28 300*	71.4	55.6	22 200*	26.0
28.0	65.1	55.8	31 400 *b	67.2	55.4	27 500*	69.2	54.6	21 500*	28.0
30.0	62.9	54.7	30 300 *	65.0	54.4	26 700*	66.9	53.5	20 800*	30.0
32.0	60.7	53.6	29 200 *	62.7	53.2	26 000*	64.6	52.4	20 200*	32.0
34.0	58.4	52.3	28 100	60.4	52.0	25 400*	62.3	51.1	19 600*	34.0
36.0	56.0	51.0	25 900	58.0	50.6	24 900*	59.8	49.7	19 100*	36.0
38.0	53.5	49.5	23 700	55.5	49.1	24 000	57.3	48.1	18 700*	38.0
40.0	51.0	47.9	21 800	53.0	47.4	22 100	54.7	46.5	18 200*	40.0
44.0	45.7	44.1	18 600	47.6	43.6	18 800	49.2	42.6	17 500*	44.0
48.0	39.7	39.5	15 900	41.5	39.0	16 100				48.0
52.0	32.8	33.8	13 600	34.5	33.1	13 800				52.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.8m (160 Ft.) BOOM										
13.7	80.4	63.8	44 900 *b							13.7
14.0	80.2	63.7	44 500 *b							14.0
15.0	79.2	63.5	43 300 *b							15.0
16.0	78.3	63.3	42 100 *b							16.0
18.0	76.4	62.8	40 000 *b	78.4	62.5	32 800*b				18.0
20.0	74.4	62.2	38 100 *b	76.4	61.9	31 600*b	78.5	61.1	25 200*	20.0
22.0	72.5	61.6	36 300 *b	74.5	61.2	30 600*b	76.5	60.4	24 200*	22.0
24.0	70.5	60.9	34 800 *b	72.5	60.5	29 600*	74.5	59.7	23 400*	24.0
26.0	68.5	60.0	33 400 *b	70.5	59.7	28 800*	72.4	58.9	22 600*	26.0
28.0	66.4	59.2	32 200 *b	68.4	58.8	27 900*	70.3	58.0	21 800*	28.0
30.0	64.4	58.2	31 000 *b	66.3	57.8	27 200*	68.2	57.0	21 200*	30.0
32.0	62.3	57.1	29 900 *	64.2	56.7	26 500*	66.1	55.9	20 600*	32.0
34.0	60.1	55.9	28 000	62.0	55.6	25 900*	63.9	54.7	20 000*	34.0
36.0	57.9	54.7	25 500	59.8	54.3	25 300*	61.6	53.4	19 500*	36.0
38.0	55.7	53.3	23 400	57.5	52.9	23 800	59.3	52.0	19 000*	38.0
40.0	53.3	51.8	21 400	55.2	51.4	21 900	56.9	50.4	18 600*	40.0
44.0	48.4	48.4	18 200	50.3	47.9	18 500	51.8	46.9	17 800*	44.0
48.0	43.1	44.3	15 500	44.9	43.8	15 800	46.3	42.6	16 000	48.0
52.0	37.2	39.3	13 300	38.8	38.7	13 500				52.0
56.0	30.2	32.9	11 400							56.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
13.7	80.9	66.9	45 300 *b							13.7
14.0	80.6	66.8	45 000 *b							14.0
15.0	79.7	66.6	43 900 *b							15.0
16.0	78.8	66.4	42 800 *b							16.0
18.0	77.0	66.0	40 600 *b	79.0	65.6	33 100 *b				18.0
20.0	75.2	65.4	38 800 *b	77.1	65.1	32 000 *b	79.1	64.3	25 500*	20.0
22.0	73.3	64.8	37 000 *b	75.2	64.4	31 000 *b	77.2	63.6	24 600*	22.0
24.0	71.4	64.1	35 500 *b	73.4	63.8	30 000*	75.3	62.9	23 700*	24.0
26.0	69.6	63.3	34 100 *b	71.5	63.0	29 200*	73.3	62.2	22 900*	26.0
28.0	67.6	62.5	32 900 *b	69.5	62.1	28 300*	71.4	61.3	22 200*	28.0
30.0	65.7	61.6	31 700 *b	67.6	61.2	27 600*	69.4	60.4	21 500*	30.0
32.0	63.7	60.6	30 500 b	65.6	60.2	26 900*	67.3	59.3	21 000*	32.0
34.0	61.7	59.5	27 700	63.5	59.1	26 300*	65.3	58.2	20 400*	34.0
36.0	59.6	58.3	25 200	61.4	57.9	25 500	63.2	57.0	19 900*	36.0
38.0	57.5	57.0	23 100	59.3	56.6	23 600	61.0	55.7	19 400*	38.0
40.0	55.3	55.6	21 200	57.1	55.2	21 600	58.8	54.3	18 900*	40.0
44.0	50.8	52.5	17 900	52.6	52.0	18 300	54.1	51.0	18 100*	44.0
48.0	46.0	48.7	15 300	47.7	48.3	15 600	49.1	47.2	15 800	48.0
52.0	40.7	44.3	13 100	42.3	43.8	13 300				52.0
56.0	34.7	38.8	11 200	36.3	38.2	11 400				56.0
60.0	27.6	31.9	9 500							60.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
15.2	80.0	69.7	44 300 *b							15.2
16.0	79.3	69.5	43 400 *b							16.0
18.0	77.6	69.1	41 300 *b	79.5	68.7	33 500 *b				18.0
20.0	75.9	68.6	39 500 *b	77.7	68.2	32 400 *b	79.6	67.4	25 700 *	20.0
22.0	74.1	68.0	37 800 *b	75.9	67.6	31 400 *b	77.8	66.8	24 800 *	22.0
24.0	72.3	67.3	36 200 *b	74.1	67.0	30 400 *	76.0	66.2	24 000 *	24.0
26.0	70.5	66.6	34 900 *b	72.3	66.3	29 500 *	74.1	65.4	23 200 *	26.0
28.0	68.7	65.8	33 600 *b	70.5	65.5	28 800 *	72.3	64.6	22 500 *	28.0
30.0	66.9	64.9	32 400 *b	68.6	64.6	28 000 *	70.4	63.7	21 900 *	30.0
32.0	65.0	64.0	30 200 b	66.8	63.6	27 300 *	68.5	62.8	21 300 *	32.0
34.0	63.1	63.0	27 400 b	64.8	62.6	26 700 *	66.5	61.7	20 700 *	34.0
36.0	61.1	61.8	24 900	62.9	61.5	25 500	64.6	60.6	20 200 *	36.0
38.0	59.2	60.6	22 800	60.9	60.2	23 300	62.5	59.3	19 700 *	38.0
40.0	57.1	59.3	20 800	58.9	58.9	21 300	60.5	58.0	19 200 *	40.0
44.0	52.9	56.4	17 600	54.6	56.0	18 000	56.2	55.0	18 300	44.0
48.0	48.5	53.0	14 900	50.1	52.5	15 300	51.6	51.5	15 600	48.0
52.0	43.7	48.9	12 700	45.3	48.4	13 000	46.6	47.3	13 200	52.0
56.0	38.4	44.1	10 800	39.9	43.6	11 100				56.0
60.0	32.3	38.2	9 200	33.8	37.6	9 400				60.0




Liftcrane Jib Capacities

**Meets
 ANSI B30.5
 Requirements**

2250T

**Jib No. 132 With 6 096 mm Strut On
 Boom No. 44A With Heavy Lift Top
 55 880 kg Counterweight
 360 Degree Rating
 On Extended Outriggers**



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
15.2	80.4	72.8	44 900 * b							15.2
16.0	79.8	72.7	44 000 * b							16.0
18.0	78.2	72.2	41 900 * b	79.9	71.9	33 800 * b				18.0
20.0	76.5	71.7	40 100 * b	78.3	71.4	32 700 * b	80.0	70.6	25 900*	20.0
22.0	74.8	71.2	38 400 * b	76.6	70.8	31 700 * b	78.3	70.0	25 100*	22.0
24.0	73.1	70.6	36 900 * b	74.9	70.2	30 800*	76.6	69.4	24 300*	24.0
26.0	71.4	69.9	35 500 * b	73.1	69.5	29 900*	74.9	68.7	23 500*	26.0
28.0	69.7	69.1	34 200 * b	71.4	68.7	29 100*	73.1	67.9	22 800*	28.0
30.0	67.9	68.3	32 800 b	69.6	67.9	28 400*	71.3	67.1	22 200*	30.0
32.0	66.1	67.4	29 900 b	67.8	67.0	27 700*	69.5	66.1	21 600*	32.0
34.0	64.3	66.4	27 100 b	66.0	66.0	27 000	67.7	65.2	21 000*	34.0
36.0	62.5	65.3	24 600	64.2	65.0	25 300	65.8	64.1	20 500*	36.0
38.0	60.6	64.2	22 500	62.3	63.8	23 000	63.9	62.9	20 000*	38.0
40.0	58.7	63.0	20 500	60.4	62.6	21 000	61.9	61.7	19 600*	40.0
44.0	54.8	60.2	17 300	56.4	59.8	17 700	57.9	58.8	18 100	44.0
48.0	50.7	57.1	14 600	52.3	56.6	15 000	53.7	55.6	15 300	48.0
52.0	46.3	53.4	12 400	47.8	52.9	12 700	49.1	51.8	13 000	52.0
56.0	41.5	49.0	10 500	43.0	48.5	10 700	44.2	47.3	11 000	56.0
60.0	36.2	43.8	8 900	37.6	43.2	9 100				60.0
64.0	30.0	37.4	7 500	31.3	36.7	7 600				64.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
15.2	80.8	75.9	45 300 *b							15.2
16.0	80.2	75.8	44 500 *b							16.0
18.0	78.7	75.4	42 600 *b							18.0
20.0	77.1	74.9	40 700 *b	78.8	74.5	33 000*b	80.5	73.7	26 100*	20.0
22.0	75.5	74.3	39 100 *b	77.1	74.0	32 000*b	78.8	73.2	25 400*	22.0
24.0	73.8	73.7	37 500 *b	75.5	73.4	31 100*b	77.2	72.6	24 500*	24.0
26.0	72.2	73.1	36 100 *b	73.9	72.7	30 300*	75.5	71.9	23 800*	26.0
28.0	70.5	72.4	34 900 *b	72.2	72.0	29 500*	73.8	71.2	23 100*	28.0
30.0	68.9	71.6	32 800 b	70.5	71.2	28 800*	72.1	70.4	22 500*	30.0
32.0	67.2	70.7	29 600 b	68.8	70.4	28 100*	70.4	69.5	21 900*	32.0
34.0	65.5	69.8	26 700 b	67.1	69.4	27 300	68.7	68.6	21 300*	34.0
36.0	63.7	68.8	24 300	65.4	68.4	25 000	66.9	67.5	20 800*	36.0
38.0	62.0	67.7	22 100	63.6	67.3	22 700	65.1	66.4	20 300*	38.0
40.0	60.2	66.6	20 200	61.8	66.2	20 700	63.3	65.3	19 900*	40.0
44.0	56.5	64.0	16 900	58.1	63.6	17 400	59.5	62.6	17 800	44.0
48.0	52.6	61.0	14 300	54.2	60.6	14 700	55.5	59.6	15 000	48.0
52.0	48.5	57.6	12 100	50.0	57.1	12 400	51.3	56.0	12 600	52.0
56.0	44.1	53.6	10 100	45.6	53.1	10 400	46.8	51.9	10 700	56.0
60.0	39.4	48.9	8 500	40.8	48.4	8 800				60.0
64.0	34.0	43.3	7 100	35.4	42.7	7 300				64.0
68.0	27.7	36.3	5 900							68.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
16.8	80.1	78.7	40 800 *b							16.8
18.0	79.1	78.5	40 800 *b							18.0
20.0	77.6	78.0	40 700 *b	79.2	77.7	33 300*b				20.0
22.0	76.0	77.5	39 700 *b	77.7	77.1	32 300*b	79.3	76.3	25 600*	22.0
24.0	74.5	76.9	38 100 *b	76.1	76.6	31 400*b	77.7	75.8	24 800*	24.0
26.0	72.9	76.3	36 800 *b	74.5	75.9	30 600*	76.1	75.1	24 000*	26.0
28.0	71.4	75.6	35 400 b	73.0	75.3	29 800*	74.5	74.4	23 400*	28.0
30.0	69.8	74.9	32 900 b	71.4	74.5	29 100*	72.9	73.7	22 800*	30.0
32.0	68.1	74.1	29 400 b	69.7	73.7	28 400*	71.3	72.8	22 200*	32.0
34.0	66.5	73.2	26 600 b	68.1	72.8	27 500	69.6	71.9	21 600*	34.0
36.0	64.9	72.2	24 200 b	66.4	71.8	24 800	67.9	71.0	21 100*	36.0
38.0	63.2	71.2	22 000	64.7	70.8	22 600	66.2	69.9	20 600*	38.0
40.0	61.5	70.1	20 100	63.0	69.7	20 600	64.5	68.8	20 200*	40.0
44.0	58.0	67.7	16 800	59.5	67.2	17 300	60.9	66.3	17 700	44.0
48.0	54.4	64.9	14 100	55.9	64.4	14 500	57.2	63.4	14 900	48.0
52.0	50.5	61.7	11 900	52.0	61.2	12 300	53.3	60.2	12 600	52.0
56.0	46.5	58.0	10 100	47.9	57.5	10 300	49.1	56.4	10 600	56.0
60.0	42.1	53.7	8 400	43.5	53.2	8 700	44.6	52.0	8 900	60.0
64.0	37.3	48.7	7 000	38.7	48.1	7 200				64.0
68.0	31.9	42.6	5 800	33.2	42.0	6 000				68.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
16.8	80.4	81.8	40 800 *b							16.8
18.0	79.5	81.6	40 800 *b							18.0
20.0	78.1	81.1	40 800 *b	79.6	80.8	33 600 *b				20.0
22.0	76.6	80.7	40 400 *b	78.2	80.3	32 600 *b	79.7	79.5	25 700 *	22.0
24.0	75.1	80.1	38 700 *b	76.7	79.7	31 800 *b	78.2	78.9	25 000 *	24.0
26.0	73.6	79.5	37 400 *b	75.2	79.1	30 900 *b	76.7	78.3	24 300 *	26.0
28.0	72.1	78.9	35 800 b	73.6	78.5	30 200 *	75.2	77.6	23 600 *	28.0
30.0	70.6	78.1	32 500 b	72.1	77.8	29 400 *	73.6	76.9	23 000 *	30.0
32.0	69.0	77.4	29 100 b	70.6	77.0	28 800 *	72.0	76.1	22 400 *	32.0
34.0	67.5	76.5	26 300 b	69.0	76.1	27 100	70.5	75.3	21 900 *	34.0
36.0	65.9	75.6	23 800 b	67.4	75.2	24 500	68.9	74.3	21 400 *	36.0
38.0	64.3	74.6	21 700 b	65.8	74.2	22 300	67.2	73.3	20 900 *	38.0
40.0	62.7	73.6	19 700	64.2	73.2	20 300	65.6	72.3	20 400	40.0
44.0	59.4	71.3	16 500	60.8	70.9	17 000	62.2	69.9	17 400	44.0
48.0	55.9	68.6	13 800	57.4	68.2	14 300	58.7	67.2	14 600	48.0
52.0	52.3	65.6	11 600	53.8	65.2	12 000	55.0	64.1	12 300	52.0
56.0	48.6	62.2	9 700	50.0	61.7	10 000	51.1	60.6	10 300	56.0
60.0	44.5	58.2	8 100	45.9	57.7	8 300	47.0	56.6	8 600	60.0
64.0	40.2	53.7	6 700	41.5	53.1	6 900				64.0
68.0	35.4	48.3	5 400	36.6	47.7	5 600				68.0
72.0	29.9	41.8	4 300							72.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
16.8	80.8	84.9	40 800 * b							16.8
18.0	79.9	84.7	40 800 * b							18.0
20.0	78.5	84.3	40 800 * b	80.0	83.9	33 800 * b				20.0
22.0	77.1	83.8	40 500 * b	78.6	83.4	32 900 * b	80.1	82.6	25 900*	22.0
24.0	75.7	83.3	39 300 * b	77.2	82.9	32 000 * b	78.7	82.1	25 300*	24.0
26.0	74.2	82.7	37 900 * b	75.7	82.3	31 200 * b	77.2	81.5	24 500*	26.0
28.0	72.8	82.1	36 100 b	74.3	81.7	30 500*	75.7	80.9	23 900*	28.0
30.0	71.3	81.4	32 100 b	72.8	81.0	29 800*	74.3	80.2	23 300*	30.0
32.0	69.8	80.6	28 800 b	71.3	80.3	29 100*	72.8	79.4	22 700*	32.0
34.0	68.4	79.8	26 000 b	69.8	79.4	26 800	71.2	78.6	22 100*	34.0
36.0	66.8	79.0	23 500 b	68.3	78.6	24 200	69.7	77.7	21 700*	36.0
38.0	65.3	78.0	21 400 b	66.8	77.6	22 000	68.2	76.7	21 200*	38.0
40.0	63.8	77.0	19 400 b	65.2	76.6	20 100	66.6	75.7	20 600	40.0
44.0	60.6	74.8	16 200	62.0	74.4	16 700	63.4	73.5	17 200	44.0
48.0	57.4	72.3	13 500	58.8	71.9	13 900	60.0	70.9	14 300	48.0
52.0	54.0	69.5	11 300	55.4	69.0	11 600	56.6	68.0	12 000	52.0
56.0	50.4	66.3	9 400	51.8	65.8	9 700	53.0	64.7	10 000	56.0
60.0	46.7	62.6	7 800	48.0	62.1	8 100	49.1	61.0	8 300	60.0
64.0	42.7	58.4	6 300	44.0	57.9	6 600	45.0	56.6	6 800	64.0
68.0	38.3	53.5	5 100	39.6	52.9	5 300				68.0
72.0	33.5	47.8	4 000	34.7	47.1	4 200				72.0
76.0	27.9	40.7	3 100							76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
73.2m (240 Ft.) BOOM										
18.3	80.1	87.7	40 800 *b							18.3
20.0	78.9	87.4	40 800 *b	80.4	87.0	34 100 *b				20.0
22.0	77.6	86.9	40 700 *b	79.0	86.6	33 200 *b	80.5	85.7	26 100 *	22.0
24.0	76.2	86.4	39 900 *b	77.6	86.1	32 300 *b	79.1	85.2	25 500 *	24.0
26.0	74.8	85.9	38 400 b	76.2	85.5	31 500 *b	77.7	84.7	24 800 *	26.0
28.0	73.4	85.3	35 800 b	74.8	84.9	30 800 *b	76.3	84.1	24 100 *	28.0
30.0	72.0	84.6	31 800 b	73.4	84.2	30 100 *	74.8	83.4	23 500 *	30.0
32.0	70.6	83.9	28 500 b	72.0	83.5	29 400	73.4	82.7	22 900 *	32.0
34.0	69.2	83.1	25 700 b	70.6	82.7	26 500	72.0	81.9	22 400 *	34.0
36.0	67.7	82.3	23 200 b	69.1	81.9	23 900	70.5	81.0	21 900 *	36.0
38.0	66.3	81.4	21 000 b	67.7	81.0	21 700	69.0	80.1	21 400 *	38.0
40.0	64.8	80.4	19 100 b	66.2	80.0	19 700	67.5	79.1	20 400	40.0
44.0	61.8	78.3	15 800	63.2	77.9	16 400	64.4	77.0	16 900	44.0
48.0	58.7	76.0	13 100	60.0	75.5	13 600	61.3	74.6	14 100	48.0
52.0	55.5	73.3	10 900	56.8	72.8	11 300	58.0	71.8	11 700	52.0
56.0	52.1	70.2	9 000	53.4	69.8	9 400	54.6	68.7	9 700	56.0
60.0	48.6	66.8	7 400	49.9	66.3	7 700	51.0	65.2	8 000	60.0
64.0	44.9	62.9	6 000	46.1	62.4	6 300	47.2	61.2	6 500	64.0
68.0	40.9	58.4	4 800	42.1	57.9	5 000				68.0
72.0	36.5	53.2	3 700	37.7	52.6	3 900				72.0
76.0	31.6	47.1	2 700	32.7	46.4	2 900				76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
18.3	80.4	90.8	40 800 *b							18.3
20.0	79.3	90.5	40 800 *b	80.7	90.1	34 300 *b				20.0
22.0	78.0	90.1	40 800 *b	79.4	89.7	33 400 *b				22.0
24.0	76.7	89.6	40 200 *b	78.1	89.2	32 600 *b	79.5	88.4	25 600*	24.0
26.0	75.3	89.0	38 900 b	76.7	88.7	31 800 *b	78.1	87.8	25 000*	26.0
28.0	74.0	88.5	35 600 b	75.4	88.1	31 000 *b	76.8	87.2	24 300*	28.0
30.0	72.6	87.8	31 600 b	74.0	87.4	30 400*	75.4	86.6	23 700*	30.0
32.0	71.3	87.1	28 400 b	72.7	86.8	29 300	74.0	85.9	23 200*	32.0
34.0	69.9	86.4	25 500 b	71.3	86.0	26 300	72.6	85.1	22 600*	34.0
36.0	68.5	85.6	23 000 b	69.9	85.2	23 800	71.2	84.3	22 200*	36.0
38.0	67.1	84.7	20 900 b	68.5	84.3	21 600	69.8	83.5	21 700*	38.0
40.0	65.7	83.8	18 900 b	67.1	83.4	19 600	68.4	82.5	20 300	40.0
44.0	62.8	81.8	15 700	64.2	81.4	16 200	65.4	80.5	16 700	44.0
48.0	59.9	79.5	13 000	61.2	79.1	13 500	62.4	78.2	13 900	48.0
52.0	56.8	77.0	10 800	58.1	76.5	11 200	59.3	75.6	11 600	52.0
56.0	53.6	74.1	8 900	54.9	73.6	9 300	56.1	72.6	9 600	56.0
60.0	50.3	70.9	7 300	51.6	70.4	7 600	52.7	69.3	7 900	60.0
64.0	46.8	67.2	5 800	48.1	66.7	6 200	49.1	65.6	6 400	64.0
68.0	43.1	63.1	4 700	44.3	62.5	4 900	45.3	61.3	5 100	68.0
72.0	39.1	58.3	3 600	40.3	57.7	3 800				72.0
76.0	34.8	52.8	2 600	35.9	52.2	2 800				76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
15.2	79.8	60.3	32 800 *b							15.2
16.0	79.0	60.1	32 500 *b							16.0
18.0	77.0	59.6	31 600 *							18.0
20.0	75.0	59.0	30 800 *	78.1	58.4	26 300*				20.0
22.0	72.9	58.3	30 000 *	76.0	57.7	25 900*	79.2	56.6	18 800*	22.0
24.0	70.8	57.5	29 300 *	73.9	56.9	25 400*	77.1	55.8	18 000*	24.0
26.0	68.6	56.6	28 600 *	71.8	56.1	25 000*	74.9	54.9	17 200*	26.0
28.0	66.5	55.7	28 000 *	69.6	55.1	24 500*	72.6	53.9	16 600*	28.0
30.0	64.3	54.7	27 400 *	67.3	54.1	23 600*	70.3	52.8	16 000*	30.0
32.0	62.0	53.5	26 900 *	65.0	52.9	22 700*	68.0	51.6	15 400*	32.0
34.0	59.7	52.3	26 400 *	62.7	51.6	21 800*	65.6	50.3	14 900*	34.0
36.0	57.3	50.9	25 900 *	60.3	50.2	21 100*	63.1	48.9	14 400*	36.0
38.0	54.9	49.4	25 200	57.8	48.7	20 400*	60.5	47.3	14 000*	38.0
40.0	52.4	47.8	23 300	55.3	47.1	19 700*	57.9	45.6	13 600*	40.0
44.0	47.0	44.0	20 000	49.8	43.2	18 600*	52.2	41.7	12 900*	44.0
48.0	41.0	39.4	17 300	43.7	38.6	17 400				48.0
52.0	34.1	33.6	15 100	36.6	32.6	15 300				52.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.7m (140 Ft.) BOOM										
15.2	80.3	63.4	33 100 * b							15.2
16.0	79.6	63.2	32 700 * b							16.0
18.0	77.7	62.7	31 900 *							18.0
20.0	75.7	62.2	31 100 *	78.7	61.6	26 500*				20.0
22.0	73.8	61.5	30 300 *	76.8	60.9	26 000*	79.8	59.8	19 000*	22.0
24.0	71.8	60.8	29 600 *	74.8	60.2	25 600*	77.8	59.0	18 200*	24.0
26.0	69.8	60.0	29 000 *	72.7	59.4	25 200*	75.7	58.2	17 500*	26.0
28.0	67.7	59.1	28 400 *	70.7	58.5	24 700*	73.6	57.3	16 900*	28.0
30.0	65.7	58.1	27 800 *	68.6	57.5	24 200*	71.4	56.2	16 200*	30.0
32.0	63.6	57.0	27 300 *	66.4	56.4	23 200*	69.3	55.1	15 700*	32.0
34.0	61.4	55.9	26 700 *	64.3	55.2	22 400*	67.0	53.9	15 200*	34.0
36.0	59.2	54.6	26 300 *	62.0	53.9	21 600*	64.7	52.6	14 700*	36.0
38.0	56.9	53.2	24 900	59.7	52.5	20 900*	62.4	51.2	14 300*	38.0
40.0	54.6	51.7	23 000	57.4	51.0	20 200*	59.9	49.6	13 900*	40.0
44.0	49.7	48.3	19 700	52.4	47.5	19 100*	54.8	46.0	13 200*	44.0
48.0	44.3	44.2	17 000	47.0	43.3	17 400	49.1	41.6	12 600*	48.0
52.0	38.4	39.2	14 800	40.8	38.2	15 000				52.0
56.0	31.4	32.8	12 900							56.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
15.2	80.8	66.5	33 200 * b							15.2
16.0	80.1	66.4	32 900 * b							16.0
18.0	78.3	65.9	32 100 *							18.0
20.0	76.4	65.3	31 400 *	79.3	64.8	26 700*				20.0
22.0	74.6	64.7	30 600 *	77.4	64.1	26 200*	80.3	62.9	19 200*	22.0
24.0	72.7	64.0	29 900 *	75.5	63.4	25 700*	78.4	62.2	18 500*	24.0
26.0	70.8	63.3	29 300 *	73.6	62.7	25 300*	76.4	61.4	17 700*	26.0
28.0	68.9	62.4	28 700 *	71.7	61.8	24 900*	74.5	60.6	17 100*	28.0
30.0	66.9	61.5	28 100 *	69.7	60.9	24 500*	72.4	59.6	16 500*	30.0
32.0	64.9	60.5	27 600 *	67.7	59.9	23 700*	70.4	58.6	16 000*	32.0
34.0	62.9	59.4	27 100 *	65.6	58.8	22 900*	68.3	57.5	15 500*	34.0
36.0	60.8	58.2	26 400	63.6	57.6	22 100*	66.1	56.2	15 000*	36.0
38.0	58.7	56.9	24 500	61.4	56.2	21 400*	64.0	54.9	14 600*	38.0
40.0	56.6	55.5	22 600	59.2	54.8	20 700*	61.7	53.4	14 200*	40.0
44.0	52.0	52.4	19 300	54.6	51.6	19 600*	57.0	50.1	13 500*	44.0
48.0	47.2	48.6	16 600	49.7	47.8	17 000	51.9	46.2	12 900*	48.0
52.0	41.9	44.2	14 400	44.3	43.3	14 700				52.0
56.0	35.9	38.7	12 500	38.1	37.7	12 700				56.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.8m (160 Ft.) BOOM										
16.8	79.9	69.3	32 800 * b							16.8
18.0	78.8	69.0	32 400 *							18.0
20.0	77.0	68.5	31 600 *	79.8	67.9	26 800*				20.0
22.0	75.3	67.9	30 900 *	78.0	67.3	26 300*				22.0
24.0	73.5	67.3	30 200 *	76.2	66.7	25 900*	79.0	65.4	18 700*	24.0
26.0	71.7	66.5	29 600 *	74.4	65.9	25 500*	77.1	64.7	18 000*	26.0
28.0	69.9	65.7	29 000 *	72.6	65.1	25 100*	75.2	63.9	17 400*	28.0
30.0	68.0	64.9	28 400 *	70.7	64.2	24 800*	73.3	63.0	16 800*	30.0
32.0	66.1	63.9	27 900 *	68.8	63.3	24 200*	71.4	62.0	16 200*	32.0
34.0	64.2	62.9	27 400 *	66.9	62.2	23 400*	69.4	60.9	15 800*	34.0
36.0	62.3	61.8	26 400	64.9	61.1	22 600*	67.4	59.8	15 300*	36.0
38.0	60.3	60.5	24 200	62.9	59.9	21 900*	65.4	58.5	14 800*	38.0
40.0	58.3	59.2	22 200	60.9	58.6	21 200*	63.3	57.2	14 400*	40.0
44.0	54.1	56.3	19 000	56.6	55.6	19 500	58.9	54.1	13 800*	44.0
48.0	49.6	52.9	16 300	52.1	52.1	16 700	54.2	50.5	13 100*	48.0
52.0	44.8	48.8	14 000	47.2	48.0	14 400	49.1	46.2	12 600*	52.0
56.0	39.5	44.0	12 100	41.7	43.1	12 400				56.0
60.0	33.4	38.1	10 500							60.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
16.8	80.3	72.4	33 100 * b							16.8
18.0	79.3	72.1	32 600 * b							18.0
20.0	77.6	71.6	31 800 *	80.3	71.1	26 900*				20.0
22.0	75.9	71.1	31 200 *	78.6	70.5	26 500*				22.0
24.0	74.2	70.5	30 500 *	76.8	69.9	26 100*	79.5	68.6	18 900*	24.0
26.0	72.5	69.8	29 900 *	75.1	69.2	25 700*	77.7	67.9	18 200*	26.0
28.0	70.8	69.0	29 300 *	73.4	68.4	25 300*	75.9	67.1	17 600*	28.0
30.0	69.0	68.2	28 700 *	71.6	67.6	24 900*	74.1	66.3	17 000*	30.0
32.0	67.3	67.3	28 200 *	69.8	66.7	24 600*	72.3	65.4	16 500*	32.0
34.0	65.5	66.3	27 700	68.0	65.7	23 900*	70.4	64.4	16 000*	34.0
36.0	63.6	65.3	26 200	66.1	64.6	23 100*	68.5	63.3	15 500*	36.0
38.0	61.8	64.1	23 900	64.2	63.4	22 300*	66.6	62.1	15 100*	38.0
40.0	59.8	62.9	22 000	62.3	62.2	21 700*	64.6	60.8	14 700*	40.0
44.0	55.9	60.1	18 700	58.3	59.4	19 300	60.5	58.0	14 000*	44.0
48.0	51.8	56.9	16 000	54.1	56.2	16 500	56.2	54.6	13 400*	48.0
52.0	47.3	53.2	13 800	49.6	52.4	14 100	51.6	50.7	12 900*	52.0
56.0	42.5	48.9	11 900	44.7	48.0	12 200	46.5	46.1	12 300	56.0
60.0	37.2	43.7	10 200	39.3	42.6	10 500				60.0
64.0	31.0	37.2	8 800							64.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
16.8	80.7	75.5	33 200 * b							16.8
18.0	79.7	75.3	32 800 * b							18.0
20.0	78.1	74.8	32 000 *	80.7	74.2	27 000*				20.0
22.0	76.5	74.3	31 400 *	79.1	73.7	26 600*				22.0
24.0	74.9	73.7	30 700 *	77.4	73.0	26 200*	79.9	71.8	19 100*	24.0
26.0	73.3	73.0	30 100 *	75.8	72.4	25 800*	78.3	71.1	18 400*	26.0
28.0	71.6	72.3	29 500 *	74.1	71.7	25 400*	76.6	70.4	17 800*	28.0
30.0	70.0	71.5	29 000 *	72.4	70.9	25 100*	74.8	69.6	17 200*	30.0
32.0	68.3	70.6	28 500 *	70.7	70.0	24 800*	73.1	68.7	16 700*	32.0
34.0	66.6	69.7	27 800	69.0	69.1	24 300*	71.3	67.7	16 200*	34.0
36.0	64.8	68.7	25 900	67.2	68.0	23 500*	69.5	66.7	15 800*	36.0
38.0	63.0	67.6	23 600	65.4	67.0	22 800*	67.7	65.6	15 300*	38.0
40.0	61.2	66.5	21 600	63.6	65.8	22 100	65.9	64.4	14 900*	40.0
44.0	57.5	63.9	18 400	59.9	63.2	19 000	62.0	61.7	14 200*	44.0
48.0	53.7	60.9	15 700	55.9	60.1	16 200	58.0	58.6	13 600*	48.0
52.0	49.6	57.5	13 400	51.8	56.7	13 800	53.7	55.0	13 100*	52.0
56.0	45.2	53.5	11 500	47.3	52.6	11 900	49.1	50.8	12 200	56.0
60.0	40.4	48.8	9 900	42.4	47.8	10 200				60.0
64.0	35.0	43.2	8 400	36.9	42.1	8 700				64.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
18.3	79.9	78.3	32 900 *b							18.3
20.0	78.6	77.9	32 300 *							20.0
22.0	77.1	77.4	31 600 *	79.5	76.8	26 700*				22.0
24.0	75.5	76.8	31 000 *	77.9	76.2	26 300*				24.0
26.0	74.0	76.2	30 400 *	76.4	75.6	25 900*	78.8	74.3	18 600*	26.0
28.0	72.4	75.5	29 800 *	74.8	74.9	25 600*	77.1	73.6	18 000*	28.0
30.0	70.8	74.8	29 300 *	73.2	74.1	25 200*	75.5	72.8	17 400*	30.0
32.0	69.2	74.0	28 800 *	71.5	73.3	24 900*	73.8	72.0	17 000*	32.0
34.0	67.6	73.1	28 000	69.9	72.4	24 600*	72.2	71.1	16 400*	34.0
36.0	65.9	72.1	25 500	68.2	71.5	24 000*	70.5	70.1	16 000*	36.0
38.0	64.2	71.1	23 300	66.5	70.4	23 200*	68.7	69.1	15 600*	38.0
40.0	62.5	70.0	21 400	64.8	69.3	22 200	67.0	67.9	15 200*	40.0
44.0	59.0	67.6	18 100	61.3	66.8	18 700	63.4	65.4	14 500*	44.0
48.0	55.4	64.8	15 300	57.6	64.0	15 900	59.6	62.5	13 900*	48.0
52.0	51.5	61.5	13 100	53.7	60.8	13 600	55.6	59.2	13 300*	52.0
56.0	47.5	57.9	11 200	49.6	57.0	11 600	51.3	55.3	11 900	56.0
60.0	43.1	53.6	9 600	45.1	52.7	9 900				60.0
64.0	38.3	48.5	8 200	40.2	47.5	8 400				64.0
68.0	32.9	42.5	6 900							68.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
18.3	80.3	81.4	33 100 * b							18.3
20.0	79.1	81.1	32 500 * b							20.0
22.0	77.6	80.6	31 800 *	79.9	79.9	26 800*				22.0
24.0	76.1	80.0	31 200 *	78.4	79.4	26 400*				24.0
26.0	74.6	79.4	30 600 *	76.9	78.8	26 100*	79.2	77.5	18 800*	26.0
28.0	73.1	78.8	30 000 *	75.4	78.1	25 700*	77.7	76.8	18 200*	28.0
30.0	71.6	78.0	29 500 *	73.8	77.4	25 400*	76.1	76.1	17 700*	30.0
32.0	70.0	77.3	29 000 *	72.3	76.6	25 100*	74.5	75.3	17 100*	32.0
34.0	68.5	76.4	27 800	70.7	75.8	24 700*	72.9	74.4	16 700*	34.0
36.0	66.9	75.5	25 200	69.1	74.8	24 400*	71.3	73.5	16 200*	36.0
38.0	65.3	74.5	23 000	67.5	73.9	23 600*	69.7	72.5	15 800*	38.0
40.0	63.7	73.5	21 000	65.9	72.8	21 800	68.0	71.4	15 400*	40.0
44.0	60.4	71.2	17 700	62.5	70.5	18 400	64.6	69.0	14 700*	44.0
48.0	56.9	68.5	15 000	59.0	67.8	15 600	61.0	66.3	14 100*	48.0
52.0	53.3	65.5	12 800	55.4	64.7	13 300	57.3	63.2	13 500	52.0
56.0	49.5	62.1	10 900	51.6	61.2	11 300	53.3	59.6	11 700	56.0
60.0	45.5	58.1	9 200	47.5	57.2	9 600	49.1	55.4	9 900	60.0
64.0	41.1	53.5	7 800	43.0	52.6	8 100				64.0
68.0	36.3	48.2	6 600	38.1	47.1	6 800				68.0
72.0	30.8	41.6	5 400							72.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
18.3	80.7	84.5	33 200 *b							18.3
20.0	79.5	84.2	32 600 *b							20.0
22.0	78.1	83.7	32 000 *	80.3	83.1	26 900*				22.0
24.0	76.6	83.2	31 400 *	78.9	82.6	26 500*				24.0
26.0	75.2	82.6	30 900 *	77.4	82.0	26 200*	79.6	80.7	19 000*	26.0
28.0	73.7	82.0	30 300 *	76.0	81.3	25 800*	78.2	80.0	18 400*	28.0
30.0	72.3	81.3	29 800 *	74.5	80.6	25 500*	76.7	79.3	17 900*	30.0
32.0	70.8	80.5	29 300 *	73.0	79.9	25 200*	75.1	78.6	17 300*	32.0
34.0	69.3	79.7	27 600	71.5	79.1	24 900*	73.6	77.7	16 900*	34.0
36.0	67.8	78.9	25 000	70.0	78.2	24 600*	72.1	76.8	16 400*	36.0
38.0	66.3	77.9	22 800	68.4	77.3	23 700	70.5	75.9	16 000*	38.0
40.0	64.7	76.9	20 900	66.9	76.2	21 700	68.9	74.9	15 600*	40.0
44.0	61.6	74.7	17 600	63.7	74.0	18 300	65.6	72.6	14 900*	44.0
48.0	58.3	72.2	14 900	60.4	71.5	15 500	62.3	70.0	14 300*	48.0
52.0	54.9	69.4	12 600	56.9	68.6	13 100	58.8	67.0	13 700	52.0
56.0	51.4	66.1	10 700	53.3	65.3	11 200	55.1	63.7	11 600	56.0
60.0	47.6	62.5	9 100	49.5	61.6	9 500	51.2	59.9	9 800	60.0
64.0	43.6	58.3	7 700	45.5	57.3	8 000	46.9	55.4	8 300	64.0
68.0	39.2	53.4	6 400	41.0	52.4	6 700				68.0
72.0	34.4	47.6	5 300	36.0	46.5	5 500				72.0
76.0	28.7	40.5	4 300							76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
 Boom No. 44A With Heavy Lift Top
 55 880 kg Counterweight
 360 Degree Rating
 On Extended Outriggers

Meets
 ANSI B30.5
 Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
19.8	80.0	87.3	32 900 * b							19.8
20.0	79.9	87.3	32 800 * b							20.0
22.0	78.5	86.8	32 200 * b							22.0
24.0	77.1	86.3	31 600 *	79.3	85.7	26 600*				24.0
26.0	75.7	85.8	31 000 *	77.9	85.1	26 300*	80.0	83.9	19 100*	26.0
28.0	74.3	85.2	30 500 *	76.5	84.5	25 900*	78.6	83.2	18 600*	28.0
30.0	72.9	84.5	30 000 *	75.1	83.9	25 600*	77.2	82.5	18 000*	30.0
32.0	71.5	83.8	29 500 *	73.6	83.1	25 300*	75.7	81.8	17 600*	32.0
34.0	70.1	83.0	27 300	72.2	82.4	25 000*	74.2	81.0	17 100*	34.0
36.0	68.6	82.2	24 700	70.7	81.5	24 800*	72.8	80.2	16 600*	36.0
38.0	67.2	81.3	22 500	69.3	80.6	23 400	71.3	79.2	16 200*	38.0
40.0	65.7	80.3	20 600	67.8	79.7	21 400	69.7	78.3	15 800*	40.0
44.0	62.7	78.2	17 300	64.7	77.5	18 000	66.6	76.1	15 100*	44.0
48.0	59.6	75.8	14 500	61.6	75.1	15 200	63.4	73.6	14 500*	48.0
52.0	56.4	73.1	12 300	58.3	72.4	12 900	60.1	70.9	13 400	52.0
56.0	53.0	70.1	10 400	54.9	69.3	10 900	56.6	67.7	11 300	56.0
60.0	49.5	66.7	8 800	51.4	65.8	9 200	53.0	64.1	9 500	60.0
64.0	45.8	62.7	7 300	47.6	61.9	7 700	49.1	60.0	8 000	64.0
68.0	41.7	58.3	6 100	43.5	57.3	6 400				68.0
72.0	37.4	53.1	5 000	39.1	52.0	5 200				72.0
76.0	32.5	46.9	4 000							76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
19.8	80.3	90.5	33 100 *b							19.8
20.0	80.2	90.4	33 000 *b							20.0
22.0	78.9	90.0	32 400 *b							22.0
24.0	77.6	89.5	31 800 *	79.7	88.8	26 700*				24.0
26.0	76.2	89.0	31 300 *	78.3	88.3	26 400*	80.4	87.0	19 300*	26.0
28.0	74.9	88.4	30 700 *	77.0	87.7	26 100*	79.0	86.4	18 700*	28.0
30.0	73.5	87.7	30 200 *	75.6	87.1	25 700*	77.6	85.8	18 200*	30.0
32.0	72.2	87.0	29 800 *	74.2	86.4	25 400*	76.2	85.0	17 700*	32.0
34.0	70.8	86.3	26 900	72.8	85.6	25 200*	74.8	84.3	17 300*	34.0
36.0	69.4	85.5	24 400	71.4	84.8	24 900	73.4	83.5	16 800*	36.0
38.0	68.0	84.6	22 200	70.0	84.0	23 200	72.0	82.6	16 400*	38.0
40.0	66.6	83.7	20 300	68.6	83.0	21 100	70.5	81.6	16 000*	40.0
44.0	63.7	81.7	17 000	65.7	81.0	17 700	67.6	79.6	15 300*	44.0
48.0	60.7	79.4	14 300	62.7	78.7	14 900	64.5	77.2	14 700*	48.0
52.0	57.7	76.9	12 000	59.6	76.1	12 600	61.3	74.6	13 100	52.0
56.0	54.5	74.0	10 100	56.4	73.2	10 600	58.1	71.6	11 000	56.0
60.0	51.2	70.7	8 400	53.0	69.9	8 900	54.6	68.2	9 300	60.0
64.0	47.7	67.1	7 000	49.5	66.2	7 400	51.0	64.4	7 700	64.0
68.0	44.0	62.9	5 800	45.7	62.0	6 100	47.1	60.1	6 400	68.0
72.0	40.0	58.2	4 700	41.6	57.2	4 900				72.0
76.0	35.6	52.6	3 700	37.2	51.5	3 900				76.0
80.0	30.6	46.0	2 800							80.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
73.2m (240 Ft.) BOOM										
19.8	80.7	93.6	33 200 * b							19.8
20.0	80.5	93.5	33 100 * b							20.0
22.0	79.3	93.1	32 500 * b							22.0
24.0	78.0	92.6	32 000 *	80.0	92.0	26 800*				24.0
26.0	76.7	92.1	31 500 *	78.7	91.5	26 500*	80.7	90.2	19 400*	26.0
28.0	75.4	91.5	30 900 *	77.4	90.9	26 200*	79.4	89.6	18 900*	28.0
30.0	74.1	90.9	30 400 *	76.1	90.3	25 900*	78.1	88.9	18 400*	30.0
32.0	72.8	90.3	29 500	74.8	89.6	25 600*	76.7	88.3	17 900*	32.0
34.0	71.5	89.6	26 700	73.4	88.9	25 300*	75.4	87.5	17 400*	34.0
36.0	70.1	88.8	24 200	72.1	88.1	24 800	74.0	86.7	17 000*	36.0
38.0	68.8	88.0	21 900	70.7	87.3	23 000	72.6	85.9	16 600*	38.0
40.0	67.4	87.1	20 000	69.4	86.4	20 900	71.2	85.0	16 200*	40.0
44.0	64.7	85.1	16 700	66.6	84.4	17 400	68.4	83.0	15 500*	44.0
48.0	61.8	83.0	13 900	63.7	82.2	14 600	65.5	80.8	14 900	48.0
52.0	58.9	80.5	11 600	60.8	79.8	12 300	62.5	78.3	12 800	52.0
56.0	55.9	77.8	9 700	57.7	77.0	10 300	59.4	75.4	10 800	56.0
60.0	52.7	74.7	8 100	54.5	73.9	8 600	56.1	72.2	9 000	60.0
64.0	49.5	71.3	6 700	51.2	70.4	7 100	52.7	68.7	7 400	64.0
68.0	46.0	67.4	5 400	47.7	66.5	5 800	49.1	64.6	6 100	68.0
72.0	42.3	63.0	4 300	43.9	62.0	4 600				72.0
76.0	38.3	57.9	3 300	39.8	56.9	3 600				76.0
80.0	33.8	52.1	2 400	35.3	50.9	2 600				80.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
16.8	80.2	66.2	23 300 *							16.8
18.0	79.0	65.9	22 900 *							18.0
20.0	77.2	65.3	22 300 *							20.0
22.0	75.3	64.7	21 700 *	79.2	64.0	19 700*				22.0
24.0	73.5	64.0	21 100 *	77.3	63.3	19 300*				24.0
26.0	71.6	63.2	20 600 *	75.4	62.5	18 900*	79.3	61.1	14 700*	26.0
28.0	69.6	62.4	20 100 *	73.4	61.7	18 500*	77.3	60.3	14 100*	28.0
30.0	67.7	61.5	19 700 *	71.5	60.8	18 100*	75.3	59.3	13 500*	30.0
32.0	65.7	60.5	19 200 *	69.5	59.7	17 800*	73.2	58.3	13 000*	32.0
34.0	63.7	59.4	18 800 *	67.4	58.6	17 400*	71.1	57.1	12 500*	34.0
36.0	61.6	58.2	18 400 *	65.3	57.4	17 100*	68.9	55.9	12 100*	36.0
38.0	59.5	56.9	18 000 *	63.2	56.1	16 800*	66.7	54.5	11 700*	38.0
40.0	57.3	55.5	17 700 *	61.0	54.7	16 600*	64.5	53.1	11 400*	40.0
44.0	52.8	52.3	17 000 *	56.4	51.5	15 300*	59.7	49.7	10 700*	44.0
48.0	48.0	48.6	16 500 *	51.4	47.7	14 200*	54.5	45.8	10 200*	48.0
52.0	42.6	44.1	15 600	46.0	43.1	13 300*	48.8	41.0	9 700*	52.0
56.0	36.6	38.7	13 700	39.8	37.5	12 500*				56.0




2250T

Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.7m (140 Ft.) BOOM										
16.8	80.6	69.3	23 500 *							16.8
18.0	79.6	69.0	23 100 *							18.0
20.0	77.8	68.5	22 500 *							20.0
22.0	76.0	67.9	21 900 *	79.7	67.2	19 900*				22.0
24.0	74.3	67.2	21 400 *	77.9	66.5	19 400*				24.0
26.0	72.4	66.5	20 900 *	76.1	65.8	19 000*	79.8	64.4	14 800*	26.0
28.0	70.6	65.7	20 400 *	74.3	65.0	18 700*	77.9	63.5	14 300*	28.0
30.0	68.8	64.8	19 900 *	72.4	64.1	18 300*	76.0	62.6	13 700*	30.0
32.0	66.9	63.9	19 500 *	70.5	63.1	18 000*	74.1	61.6	13 200*	32.0
34.0	65.0	62.9	19 100 *	68.6	62.1	17 600*	72.1	60.6	12 800*	34.0
36.0	63.0	61.7	18 700 *	66.6	61.0	17 300*	70.1	59.4	12 300*	36.0
38.0	61.1	60.5	18 300 *	64.6	59.7	17 000*	68.0	58.1	11 900*	38.0
40.0	59.0	59.2	18 000 *	62.5	58.4	16 800*	65.9	56.8	11 600*	40.0
44.0	54.8	56.3	17 300 *	58.2	55.4	15 800*	61.5	53.7	11 000*	44.0
48.0	50.4	52.8	16 700 *	53.7	51.9	14 700*	56.8	50.1	10 400*	48.0
52.0	45.5	48.8	15 300	48.8	47.8	13 700*	51.6	45.7	9 900*	52.0
56.0	40.2	44.0	13 400	43.3	42.9	12 900*				56.0
60.0	34.1	38.0	11 700	37.1	36.7	12 000				60.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
18.3	79.8	72.1	23 200 *							18.3
20.0	78.3	71.6	22 700 *							20.0
22.0	76.7	71.1	22 100 *	80.2	70.4	20 000*				22.0
24.0	75.0	70.4	21 600 *	78.5	69.7	19 600*				24.0
26.0	73.2	69.8	21 100 *	76.7	69.0	19 200*	80.3	67.6	15 000*	26.0
28.0	71.5	69.0	20 600 *	75.0	68.3	18 800*	78.5	66.8	14 400*	28.0
30.0	69.8	68.2	20 200 *	73.2	67.4	18 500*	76.7	65.9	13 900*	30.0
32.0	68.0	67.3	19 700 *	71.4	66.5	18 100*	74.8	65.0	13 400*	32.0
34.0	66.2	66.3	19 300 *	69.6	65.5	17 800*	73.0	64.0	13 000*	34.0
36.0	64.3	65.2	18 900 *	67.7	64.5	17 500*	71.1	62.9	12 500*	36.0
38.0	62.5	64.1	18 600 *	65.8	63.3	17 200*	69.1	61.7	12 200*	38.0
40.0	60.6	62.9	18 200 *	63.9	62.0	17 000*	67.1	60.4	11 800*	40.0
44.0	56.6	60.1	17 600 *	59.9	59.3	16 300*	63.0	57.5	11 100*	44.0
48.0	52.5	56.9	16 900	55.7	56.0	15 100*	58.7	54.2	10 600*	48.0
52.0	48.0	53.2	14 900	51.2	52.2	14 200*	54.0	50.2	10 100*	52.0
56.0	43.2	48.8	13 000	46.3	47.8	13 300	48.8	45.6	9 700*	56.0
60.0	37.9	43.6	11 300	40.8	42.4	11 600				60.0
64.0	31.7	37.2	9 900	34.4	35.7	10 100				64.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.8m (160 Ft.) BOOM										
18.3	80.2	75.2	23 300 *							18.3
20.0	78.8	74.8	22 800 *							20.0
22.0	77.2	74.2	22 300 *							22.0
24.0	75.6	73.6	21 800 *	79.0	72.9	19 700*				24.0
26.0	74.0	73.0	21 300 *	77.3	72.2	19 300*	80.7	70.7	15 200*	26.0
28.0	72.3	72.3	20 800 *	75.7	71.5	18 900*	79.0	70.0	14 600*	28.0
30.0	70.6	71.5	20 400 *	74.0	70.7	18 600*	77.3	69.2	14 100*	30.0
32.0	69.0	70.6	20 000 *	72.3	69.8	18 300*	75.6	68.3	13 600*	32.0
34.0	67.2	69.7	19 600 *	70.5	68.9	17 900*	73.8	67.3	13 100*	34.0
36.0	65.5	68.7	19 200 *	68.8	67.9	17 600*	72.0	66.3	12 700*	36.0
38.0	63.7	67.6	18 800 *	67.0	66.8	17 400*	70.1	65.2	12 400*	38.0
40.0	61.9	66.4	18 500 *	65.1	65.6	17 100*	68.3	64.0	12 000*	40.0
44.0	58.2	63.9	17 800 *	61.4	63.0	16 600*	64.4	61.3	11 400*	44.0
48.0	54.3	60.9	16 900	57.5	60.0	15 600*	60.3	58.1	10 800*	48.0
52.0	50.2	57.4	14 600	53.3	56.5	14 600*	56.0	54.5	10 300*	52.0
56.0	45.8	53.4	12 600	48.8	52.4	13 100	51.4	50.3	9 900*	56.0
60.0	41.1	48.7	11 000	43.9	47.6	11 300				60.0
64.0	35.7	43.1	9 600	38.4	41.8	9 800				64.0
68.0	29.4	36.1	8 300							68.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
18.3	80.6	78.3	23 400 *							18.3
20.0	79.3	77.9	23 000 *							20.0
22.0	77.7	77.4	22 500 *							22.0
24.0	76.2	76.8	22 000 *	79.4	76.1	19 800*				24.0
26.0	74.6	76.2	21 500 *	77.9	75.4	19 400*				26.0
28.0	73.1	75.5	21 000 *	76.3	74.7	19 100*	79.5	73.2	14 800*	28.0
30.0	71.5	74.8	20 600 *	74.6	74.0	18 700*	77.9	72.4	14 300*	30.0
32.0	69.8	73.9	20 200 *	73.0	73.2	18 400*	76.2	71.6	13 800*	32.0
34.0	68.2	73.0	19 800 *	71.4	72.3	18 100*	74.5	70.7	13 300*	34.0
36.0	66.6	72.1	19 400 *	69.7	71.3	17 800*	72.8	69.7	12 900*	36.0
38.0	64.9	71.1	19 100 *	68.0	70.3	17 500*	71.0	68.6	12 500*	38.0
40.0	63.2	70.0	18 700 *	66.3	69.1	17 300*	69.3	67.5	12 200*	40.0
44.0	59.7	67.5	18 100 *	62.7	66.7	16 800*	65.6	64.9	11 500*	44.0
48.0	56.0	64.7	16 500	59.0	63.8	16 000*	61.8	62.0	11 000*	48.0
52.0	52.2	61.5	14 300	55.1	60.6	14 800	57.8	58.6	10 500*	52.0
56.0	48.1	57.8	12 400	51.0	56.8	12 800	53.5	54.7	10 100*	56.0
60.0	43.8	53.5	10 700	46.5	52.4	11 100	48.9	50.2	9 700*	60.0
64.0	39.0	48.5	9 300	41.6	47.3	9 600				64.0
68.0	33.5	42.4	8 100	36.0	41.0	8 300				68.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
18.3	81.0	81.4	23 600 *							18.3
20.0	79.7	81.0	23 100 *							20.0
22.0	78.2	80.5	22 600 *							22.0
24.0	76.7	80.0	22 100 *	79.9	79.2	19 900*				24.0
26.0	75.2	79.4	21 700 *	78.3	78.6	19 500*				26.0
28.0	73.7	78.7	21 200 *	76.8	78.0	19 200*	79.9	76.4	14 900*	28.0
30.0	72.2	78.0	20 800 *	75.3	77.2	18 800*	78.4	75.7	14 400*	30.0
32.0	70.7	77.2	20 400 *	73.7	76.4	18 500*	76.8	74.9	13 900*	32.0
34.0	69.1	76.4	20 000 *	72.1	75.6	18 300*	75.2	74.0	13 500*	34.0
36.0	67.5	75.5	19 600 *	70.5	74.7	18 000*	73.5	73.0	13 100*	36.0
38.0	65.9	74.5	19 300 *	68.9	73.7	17 700*	71.9	72.0	12 700*	38.0
40.0	64.3	73.5	18 900 *	67.3	72.6	17 400*	70.2	70.9	12 400*	40.0
44.0	61.0	71.1	18 300 *	63.9	70.3	16 900*	66.7	68.5	11 700*	44.0
48.0	57.5	68.5	16 200	60.4	67.6	16 400*	63.2	65.8	11 200*	48.0
52.0	53.9	65.5	14 000	56.8	64.5	14 500	59.4	62.6	10 700*	52.0
56.0	50.1	62.0	12 000	52.9	61.0	12 500	55.4	59.0	10 300*	56.0
60.0	46.1	58.1	10 400	48.8	57.0	10 800	51.1	54.8	9 900*	60.0
64.0	41.7	53.5	9 000	44.4	52.3	9 300	46.5	49.9	9 600*	64.0
68.0	36.9	48.1	7 700	39.4	46.8	8 000				68.0
72.0	31.4	41.6	6 600							72.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
19.8	80.2	84.2	23 300 *							19.8
20.0	80.1	84.2	23 300 *							20.0
22.0	78.7	83.7	22 800 *							22.0
24.0	77.2	83.2	22 300 *							24.0
26.0	75.8	82.6	21 800 *	78.8	81.8	19 600*				26.0
28.0	74.4	81.9	21 400 *	77.3	81.2	19 300*	80.3	79.6	15 000*	28.0
30.0	72.9	81.3	21 000 *	75.8	80.5	19 000*	78.8	78.9	14 500*	30.0
32.0	71.4	80.5	20 600 *	74.4	79.7	18 700*	77.3	78.1	14 100*	32.0
34.0	69.9	79.7	20 200 *	72.8	78.9	18 400*	75.8	77.3	13 700*	34.0
36.0	68.4	78.8	19 800 *	71.3	78.0	18 100*	74.2	76.4	13 300*	36.0
38.0	66.9	77.9	19 500 *	69.8	77.1	17 800*	72.6	75.4	12 900*	38.0
40.0	65.3	76.9	19 200 *	68.2	76.1	17 500*	71.0	74.4	12 500*	40.0
44.0	62.2	74.7	18 500	65.0	73.8	17 100*	67.8	72.1	11 900*	44.0
48.0	58.9	72.2	15 900	61.7	71.3	16 500	64.4	69.5	11 400*	48.0
52.0	55.5	69.3	13 600	58.3	68.4	14 300	60.8	66.5	10 900*	52.0
56.0	52.0	66.1	11 700	54.7	65.1	12 300	57.1	63.1	10 400*	56.0
60.0	48.2	62.4	10 100	50.8	61.4	10 600	53.1	59.3	10 100*	60.0
64.0	44.2	58.2	8 700	46.7	57.1	9 100	48.9	54.8	9 400	64.0
68.0	39.8	53.3	7 400	42.3	52.1	7 700				68.0
72.0	34.9	47.6	6 300	37.3	46.2	6 600				72.0
76.0	29.3	40.5	5 300							76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
19.8	80.6	87.3	23 400 *							19.8
20.0	80.5	87.3	23 400 *							20.0
22.0	79.1	86.8	22 900 *							22.0
24.0	77.7	86.3	22 400 *							24.0
26.0	76.3	85.8	22 000 *	79.2	85.0	19 700*				26.0
28.0	74.9	85.1	21 600 *	77.8	84.4	19 400*				28.0
30.0	73.5	84.5	21 200 *	76.4	83.7	19 100*	79.3	82.1	14 700*	30.0
32.0	72.1	83.8	20 800 *	74.9	83.0	18 800*	77.8	81.3	14 200*	32.0
34.0	70.7	83.0	20 400 *	73.5	82.2	18 500*	76.3	80.5	13 800*	34.0
36.0	69.2	82.2	20 000 *	72.0	81.3	18 200*	74.8	79.7	13 400*	36.0
38.0	67.8	81.3	19 700 *	70.6	80.4	18 000*	73.3	78.8	13 100*	38.0
40.0	66.3	80.3	19 300 *	69.1	79.5	17 700*	71.8	77.8	12 700*	40.0
44.0	63.3	78.2	18 300	66.0	77.3	17 200*	68.7	75.6	12 100*	44.0
48.0	60.2	75.8	15 600	62.9	74.9	16 400	65.4	73.1	11 500*	48.0
52.0	56.9	73.1	13 300	59.6	72.2	14 000	62.1	70.3	11 000*	52.0
56.0	53.6	70.1	11 400	56.2	69.1	12 000	58.6	67.1	10 600*	56.0
60.0	50.1	66.6	9 800	52.6	65.6	10 200	54.9	63.5	10 200*	60.0
64.0	46.3	62.7	8 300	48.8	61.6	8 800	51.0	59.4	9 100	64.0
68.0	42.3	58.2	7 100	44.7	57.0	7 400	46.7	54.6	7 700	68.0
72.0	37.9	53.0	5 900	40.3	51.7	6 200				72.0
76.0	33.0	46.8	4 900	35.2	45.3	5 200				76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
19.8	80.9	90.4	23 600 *							19.8
20.0	80.8	90.4	23 500 *							20.0
22.0	79.5	89.9	23 100 *							22.0
24.0	78.1	89.5	22 600 *							24.0
26.0	76.8	88.9	22 200 *	79.6	88.1	19 800*				26.0
28.0	75.5	88.3	21 700 *	78.2	87.5	19 500*				28.0
30.0	74.1	87.7	21 300 *	76.9	86.9	19 200*	79.7	85.3	14 800*	30.0
32.0	72.7	87.0	21 000 *	75.5	86.2	18 900*	78.3	84.6	14 400*	32.0
34.0	71.4	86.3	20 600 *	74.1	85.4	18 600*	76.8	83.8	14 000*	34.0
36.0	70.0	85.5	20 200 *	72.7	84.6	18 300*	75.4	83.0	13 600*	36.0
38.0	68.6	84.6	19 900 *	71.3	83.8	18 100*	74.0	82.1	13 200*	38.0
40.0	67.2	83.7	19 500 *	69.9	82.8	17 800*	72.5	81.1	12 900*	40.0
44.0	64.3	81.7	18 200	66.9	80.8	17 300*	69.5	79.1	12 200*	44.0
48.0	61.3	79.4	15 400	63.9	78.5	16 300	66.4	76.7	11 700*	48.0
52.0	58.2	76.8	13 100	60.8	75.9	13 900	63.3	74.0	11 200*	52.0
56.0	55.1	73.9	11 200	57.6	73.0	11 800	60.0	71.0	10 700*	56.0
60.0	51.7	70.7	9 600	54.2	69.7	10 100	56.5	67.6	10 400	60.0
64.0	48.3	67.0	8 200	50.7	66.0	8 600	52.8	63.8	9 000	64.0
68.0	44.5	62.9	6 900	46.9	61.7	7 300	48.9	59.4	7 600	68.0
72.0	40.5	58.1	5 800	42.8	56.9	6 100				72.0
76.0	36.1	52.6	4 800	38.3	51.2	5 100				76.0
80.0	31.1	46.0	3 900							80.0




Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements

2250T



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
21.3	80.2	93.2	23 400 *							21.3
22.0	79.8	93.1	23 200 *							22.0
24.0	78.5	92.6	22 700 *							24.0
26.0	77.3	92.1	22 300 *	80.0	91.3	19 900*				26.0
28.0	76.0	91.5	21 900 *	78.6	90.7	19 600*				28.0
30.0	74.7	90.9	21 500 *	77.3	90.1	19 300*	80.0	88.5	14 900*	30.0
32.0	73.3	90.2	21 100 *	76.0	89.4	19 000*	78.7	87.8	14 500*	32.0
34.0	72.0	89.5	20 700 *	74.7	88.7	18 700*	77.3	87.0	14 100*	34.0
36.0	70.7	88.7	20 400 *	73.3	87.9	18 500*	75.9	86.2	13 700*	36.0
38.0	69.3	87.9	20 100 *	72.0	87.1	18 200*	74.6	85.4	13 300*	38.0
40.0	68.0	87.0	19 800 *	70.6	86.2	18 000*	73.1	84.5	13 000*	40.0
44.0	65.2	85.1	17 900	67.8	84.2	17 500*	70.3	82.5	12 400*	44.0
48.0	62.4	82.9	15 100	64.9	82.0	16 000	67.4	80.2	11 800*	48.0
52.0	59.4	80.5	12 800	62.0	79.6	13 600	64.3	77.7	11 400*	52.0
56.0	56.4	77.7	10 900	58.9	76.8	11 600	61.2	74.8	10 900*	56.0
60.0	53.3	74.7	9 300	55.7	73.7	9 800	57.9	71.6	10 400	60.0
64.0	50.0	71.2	7 800	52.4	70.2	8 300	54.5	68.0	8 800	64.0
68.0	46.5	67.3	6 600	48.8	66.2	7 000	50.8	63.9	7 400	68.0
72.0	42.8	62.9	5 500	45.1	61.7	5 800				72.0
76.0	38.8	57.9	4 400	41.0	56.6	4 800				76.0
80.0	34.4	52.0	3 600	36.4	50.5	3 800				80.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
21.3	80.6	96.3	23 400 *							21.3
22.0	80.2	96.2	23 300 *							22.0
24.0	78.9	95.7	22 900 *							24.0
26.0	77.7	95.2	22 400 *	80.3	94.4	20 000*				26.0
28.0	76.4	94.7	22 000 *	79.0	93.9	19 700*				28.0
30.0	75.2	94.1	21 600 *	77.8	93.3	19 400*				30.0
32.0	73.9	93.5	21 300 *	76.5	92.6	19 100*	79.1	91.0	14 600*	32.0
34.0	72.6	92.8	20 900 *	75.2	91.9	18 800*	77.8	90.3	14 200*	34.0
36.0	71.3	92.0	20 600 *	73.9	91.2	18 600*	76.4	89.5	13 800*	36.0
38.0	70.0	91.2	20 200 *	72.6	90.4	18 300*	75.1	88.7	13 500*	38.0
40.0	68.7	90.4	19 900 *	71.3	89.5	18 100*	73.7	87.8	13 200*	40.0
44.0	66.1	88.5	17 500	68.6	87.6	17 600*	71.0	85.9	12 500*	44.0
48.0	63.3	86.4	14 800	65.8	85.5	15 700	68.2	83.7	12 000*	48.0
52.0	60.6	84.1	12 500	63.0	83.2	13 300	65.3	81.3	11 500*	52.0
56.0	57.7	81.5	10 600	60.1	80.5	11 300	62.3	78.6	11 100*	56.0
60.0	54.7	78.5	8 900	57.1	77.6	9 600	59.2	75.5	10 100	60.0
64.0	51.6	75.3	7 500	53.9	74.2	8 000	56.0	72.1	8 500	64.0
68.0	48.3	71.6	6 200	50.6	70.5	6 700	52.5	68.3	7 100	68.0
72.0	44.8	67.5	5 200	47.1	66.4	5 600	48.9	64.0	5 900	72.0
76.0	41.1	62.9	4 200	43.3	61.6	4 500				76.0
80.0	37.1	57.5	3 200	39.2	56.1	3 500				80.0
84.0	32.6	51.3	2 500							84.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
18.3	80.1	72.1	18 300*							18.3
20.0	78.7	71.6	17 900*							20.0
22.0	77.0	71.1	17 400*							22.0
24.0	75.3	70.5	16 900*	79.8	69.7	15 400*				24.0
26.0	73.6	69.8	16 500*	78.0	69.0	15 000*				26.0
28.0	71.9	69.0	16 100*	76.3	68.3	14 600*				28.0
30.0	70.1	68.2	15 700*	74.5	67.4	14 200*	79.4	66.0	11 800*	30.0
32.0	68.3	67.3	15 300*	72.7	66.5	13 800*	77.5	65.1	11 300*	32.0
34.0	66.5	66.3	14 900*	70.9	65.5	13 400*	75.6	64.1	10 900*	34.0
36.0	64.7	65.3	14 400*	69.0	64.5	13 100*	73.7	63.0	10 500*	36.0
38.0	62.8	64.1	14 000*	67.1	63.3	12 800*	71.8	61.8	10 200*	38.0
40.0	60.9	62.9	13 600*	65.2	62.1	12 500*	69.8	60.6	9 800*	40.0
44.0	57.0	60.1	12 900*	61.2	59.3	11 900*	65.7	57.7	9 200*	44.0
48.0	52.8	56.9	12 200*	57.0	56.0	11 300*	61.4	54.4	8 700*	48.0
52.0	48.4	53.2	11 600*	52.5	52.3	10 900*	56.7	50.5	8 200*	52.0
56.0	43.6	48.9	11 100*	47.6	47.8	10 200*	51.6	45.9	7 800*	56.0
60.0	38.3	43.7	10 600*	42.1	42.4	9 600*				60.0
64.0	32.1	37.2	10 200*	35.7	35.7	9 000*				64.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.7m (140 Ft.) BOOM										
18.3	80.5	75.2	18 500 *							18.3
20.0	79.2	74.8	18 000 *							20.0
22.0	77.6	74.3	17 500 *							22.0
24.0	75.9	73.7	17 100 *							24.0
26.0	74.3	73.0	16 700 *	78.6	72.2	15 100*				26.0
28.0	72.7	72.3	16 300 *	76.9	71.5	14 700*				28.0
30.0	71.0	71.5	15 900 *	75.2	70.7	14 300*	79.8	69.2	11 900*	30.0
32.0	69.3	70.6	15 500 *	73.5	69.9	14 000*	78.1	68.4	11 500*	32.0
34.0	67.6	69.7	15 100 *	71.8	68.9	13 600*	76.3	67.4	11 100*	34.0
36.0	65.8	68.7	14 700 *	70.0	67.9	13 300*	74.5	66.4	10 700*	36.0
38.0	64.1	67.6	14 300 *	68.2	66.8	12 900*	72.7	65.3	10 300*	38.0
40.0	62.3	66.5	13 900 *	66.4	65.6	12 600*	70.8	64.1	10 000*	40.0
44.0	58.6	63.9	13 200 *	62.6	63.0	12 000*	67.0	61.4	9 400*	44.0
48.0	54.7	60.9	12 500 *	58.7	60.0	11 500*	62.9	58.3	8 800*	48.0
52.0	50.6	57.5	11 900 *	54.5	56.5	11 000*	58.6	54.8	8 400*	52.0
56.0	46.2	53.5	11 400 *	50.0	52.4	10 500*	54.0	50.6	8 000*	56.0
60.0	41.4	48.8	10 900 *	45.1	47.6	9 900*	48.9	45.6	7 600*	60.0
64.0	36.0	43.2	10 400 *	39.6	41.8	9 300*				64.0
68.0	29.7	36.1	9 400							68.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
18.3	80.9	78.3	18 500 *							18.3
20.0	79.6	77.9	18 100 *							20.0
22.0	78.1	77.4	17 700 *							22.0
24.0	76.5	76.8	17 300 *							24.0
26.0	75.0	76.2	16 800 *	79.0	75.4	15 200*				26.0
28.0	73.4	75.5	16 400 *	77.4	74.7	14 900*				28.0
30.0	71.8	74.8	16 100 *	75.8	74.0	14 500*				30.0
32.0	70.2	74.0	15 700 *	74.2	73.2	14 100*	78.6	71.6	11 700*	32.0
34.0	68.5	73.1	15 300 *	72.6	72.3	13 800*	76.9	70.7	11 200*	34.0
36.0	66.9	72.1	14 900 *	70.9	71.3	13 400*	75.2	69.7	10 800*	36.0
38.0	65.2	71.1	14 500 *	69.2	70.3	13 100*	73.5	68.7	10 500*	38.0
40.0	63.5	70.0	14 200 *	67.5	69.1	12 800*	71.7	67.6	10 100*	40.0
44.0	60.0	67.5	13 500 *	63.9	66.7	12 200*	68.1	65.0	9 500*	44.0
48.0	56.4	64.7	12 800 *	60.2	63.8	11 700*	64.3	62.2	9 000*	48.0
52.0	52.5	61.5	12 200 *	56.3	60.6	11 200*	60.3	58.8	8 500*	52.0
56.0	48.5	57.8	11 600 *	52.2	56.8	10 800*	56.0	55.0	8 100*	56.0
60.0	44.1	53.6	11 100 *	47.7	52.4	10 200*	51.4	50.5	7 800*	60.0
64.0	39.3	48.5	10 300 *	42.8	47.3	9 600*	46.2	45.1	7 500*	64.0
68.0	33.9	42.5	9 000 *	37.2	41.0	9 100*				68.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.8m (160 Ft.) BOOM										
19.8	80.2	81.1	18 300 *							19.8
20.0	80.0	81.1	18 300 *							20.0
22.0	78.5	80.6	17 800 *							22.0
24.0	77.1	80.0	17 400 *							24.0
26.0	75.6	79.4	17 000 *	79.5	78.6	15 300*				26.0
28.0	74.0	78.8	16 600 *	78.0	77.9	15 000*				28.0
30.0	72.5	78.0	16 200 *	76.4	77.2	14 600*				30.0
32.0	71.0	77.2	15 900 *	74.9	76.4	14 200*	79.1	74.9	11 700*	32.0
34.0	69.4	76.4	15 500 *	73.3	75.6	13 900*	77.5	74.0	11 400*	34.0
36.0	67.8	75.5	15 200 *	71.7	74.7	13 600*	75.9	73.1	11 000*	36.0
38.0	66.2	74.5	14 800 *	70.1	73.7	13 300*	74.2	72.1	10 600*	38.0
40.0	64.6	73.5	14 400 *	68.4	72.6	13 000*	72.5	71.0	10 300*	40.0
44.0	61.3	71.2	13 700 *	65.1	70.3	12 400*	69.1	68.6	9 700*	44.0
48.0	57.9	68.5	13 000 *	61.6	67.6	11 900*	65.5	65.9	9 200*	48.0
52.0	54.3	65.5	12 400 *	57.9	64.5	11 400*	61.7	62.8	8 700*	52.0
56.0	50.5	62.0	11 900 *	54.1	61.0	11 000*	57.8	59.2	8 300*	56.0
60.0	46.4	58.1	11 300	50.0	57.0	10 500*	53.5	55.0	7 900*	60.0
64.0	42.1	53.5	9 900	45.5	52.3	9 900*	48.9	50.2	7 700*	64.0
68.0	37.3	48.1	8 700	40.5	46.8	9 000				68.0
72.0	31.7	41.6	7 600							72.0




2250T

Liftcrane Jib Capacities

Meets
ANSI B30.5
Requirements

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
19.8	80.5	84.2	18 500 *							19.8
20.0	80.4	84.2	18 400 *							20.0
22.0	79.0	83.7	17 900 *							22.0
24.0	77.5	83.2	17 500 *							24.0
26.0	76.1	82.6	17 200 *	79.9	81.8	15 400*				26.0
28.0	74.7	82.0	16 800 *	78.4	81.1	15 100*				28.0
30.0	73.2	81.3	16 400 *	76.9	80.4	14 700*				30.0
32.0	71.7	80.5	16 100 *	75.5	79.7	14 400*	79.5	78.1	11 900*	32.0
34.0	70.2	79.7	15 700 *	73.9	78.9	14 100*	78.0	77.3	11 500*	34.0
36.0	68.7	78.8	15 400 *	72.4	78.0	13 700*	76.4	76.4	11 100*	36.0
38.0	67.2	77.9	15 000 *	70.9	77.1	13 400*	74.9	75.4	10 800*	38.0
40.0	65.6	76.9	14 600 *	69.3	76.0	13 100*	73.3	74.4	10 500*	40.0
44.0	62.5	74.7	14 000 *	66.1	73.8	12 600*	70.0	72.1	9 900*	44.0
48.0	59.2	72.2	13 300 *	62.8	71.3	12 100*	66.6	69.5	9 300*	48.0
52.0	55.8	69.4	12 700 *	59.4	68.4	11 600*	63.1	66.6	8 900*	52.0
56.0	52.3	66.1	12 100 *	55.7	65.1	11 200*	59.3	63.3	8 500*	56.0
60.0	48.5	62.4	11 100	51.9	61.4	10 800*	55.4	59.4	8 100*	60.0
64.0	44.5	58.2	9 700	47.8	57.1	10 100	51.1	55.0	7 800*	64.0
68.0	40.1	53.4	8 400	43.4	52.1	8 800	46.5	49.8	7 500*	68.0
72.0	35.3	47.6	7 300	38.4	46.1	7 600				72.0
76.0	29.6	40.5	6 300							76.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
19.8	80.9	87.3	18 500 *							19.8
20.0	80.7	87.3	18 500 *							20.0
22.0	79.4	86.8	18 100 *							22.0
24.0	78.0	86.3	17 700 *							24.0
26.0	76.6	85.8	17 300 *	80.3	84.9	15 500*				26.0
28.0	75.2	85.2	16 900 *	78.9	84.3	15 200*				28.0
30.0	73.8	84.5	16 500 *	77.4	83.7	14 800*				30.0
32.0	72.4	83.8	16 200 *	76.0	82.9	14 500*				32.0
34.0	71.0	83.0	15 900 *	74.6	82.2	14 200*	78.5	80.5	11 600*	34.0
36.0	69.5	82.2	15 500 *	73.1	81.3	13 900*	77.0	79.7	11 300*	36.0
38.0	68.1	81.3	15 200 *	71.6	80.4	13 600*	75.5	78.7	10 900*	38.0
40.0	66.6	80.3	14 900 *	70.1	79.4	13 300*	73.9	77.8	10 600*	40.0
44.0	63.6	78.2	14 200 *	67.1	77.3	12 700*	70.8	75.6	10 000*	44.0
48.0	60.5	75.8	13 500 *	63.9	74.9	12 200*	67.6	73.2	9 500*	48.0
52.0	57.2	73.1	12 900 *	60.7	72.2	11 800*	64.3	70.4	9 000*	52.0
56.0	53.9	70.1	12 300	57.3	69.1	11 300*	60.8	67.2	8 600*	56.0
60.0	50.4	66.6	10 800	53.7	65.6	11 000*	57.1	63.6	8 200*	60.0
64.0	46.6	62.7	9 300	49.9	61.6	9 800	53.1	59.5	7 900*	64.0
68.0	42.6	58.3	8 100	45.8	57.0	8 500	48.9	54.8	7 700*	68.0
72.0	38.2	53.1	7 000	41.3	51.7	7 300				72.0
76.0	33.3	46.9	6 000	36.2	45.3	6 300				76.0




Liftcrane Jib Capacities

Meets
ANSI B30.5
Requirements

2250T

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
21.3	80.2	90.1	18 300*							21.3
22.0	79.7	90.0	18 200*							22.0
24.0	78.4	89.5	17 800*							24.0
26.0	77.1	88.9	17 400*	80.6	88.1	15 600*				26.0
28.0	75.7	88.4	17 000*	79.3	87.5	15 300*				28.0
30.0	74.4	87.7	16 700*	77.9	86.9	14 900*				30.0
32.0	73.0	87.0	16 400*	76.5	86.2	14 600*				32.0
34.0	71.7	86.3	16 000*	75.1	85.4	14 300*	78.9	83.7	11 700*	34.0
36.0	70.3	85.5	15 700*	73.7	84.6	14 000*	77.5	82.9	11 400*	36.0
38.0	68.9	84.6	15 400*	72.3	83.7	13 700*	76.0	82.1	11 000*	38.0
40.0	67.4	83.7	15 000*	70.9	82.8	13 400*	74.6	81.1	10 700*	40.0
44.0	64.6	81.7	14 400*	68.0	80.8	12 900*	71.6	79.0	10 100*	44.0
48.0	61.6	79.4	13 800*	65.0	78.5	12 400*	68.5	76.7	9 600*	48.0
52.0	58.5	76.8	13 200*	61.9	75.9	11 900*	65.3	74.1	9 200*	52.0
56.0	55.4	74.0	12 100	58.6	72.9	11 500*	62.0	71.1	8 800*	56.0
60.0	52.0	70.7	10 400	55.3	69.6	11 000	58.6	67.7	8 400*	60.0
64.0	48.5	67.1	9 000	51.7	65.9	9 600	54.9	63.9	8 100*	64.0
68.0	44.8	62.9	7 700	47.9	61.7	8 200	51.0	59.5	7 800*	68.0
72.0	40.8	58.1	6 700	43.8	56.8	7 100	46.7	54.5	7 500	72.0
76.0	36.4	52.6	5 700	39.3	51.1	6 000				76.0
80.0	31.4	46.0	4 800							80.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
21.3	80.5	93.2	18 500 *							21.3
22.0	80.1	93.1	18 300 *							22.0
24.0	78.8	92.6	17 900 *							24.0
26.0	77.5	92.1	17 500 *							26.0
28.0	76.2	91.5	17 200 *	79.6	90.7	15 300*				28.0
30.0	74.9	90.9	16 800 *	78.3	90.1	15 100*				30.0
32.0	73.6	90.3	16 500 *	77.0	89.4	14 700*				32.0
34.0	72.3	89.5	16 200 *	75.7	88.7	14 400*	79.3	87.0	11 800*	34.0
36.0	71.0	88.8	15 900 *	74.3	87.9	14 100*	77.9	86.2	11 500*	36.0
38.0	69.6	87.9	15 600 *	72.9	87.0	13 800*	76.5	85.3	11 200*	38.0
40.0	68.3	87.1	15 300 *	71.6	86.2	13 600*	75.1	84.4	10 800*	40.0
44.0	65.5	85.1	14 600 *	68.8	84.2	13 000*	72.3	82.5	10 300*	44.0
48.0	62.6	82.9	14 000 *	65.9	82.0	12 600*	69.3	80.2	9 700*	48.0
52.0	59.7	80.5	13 400	62.9	79.5	12 100*	66.3	77.7	9 300*	52.0
56.0	56.7	77.8	11 700	59.9	76.7	11 700*	63.2	74.9	8 900*	56.0
60.0	53.6	74.7	10 100	56.7	73.6	10 800	59.9	71.7	8 500*	60.0
64.0	50.3	71.2	8 700	53.3	70.1	9 300	56.5	68.1	8 200*	64.0
68.0	46.8	67.4	7 400	49.8	66.2	7 900	52.8	64.0	7 900*	68.0
72.0	43.1	63.0	6 300	46.0	61.7	6 700	48.9	59.4	7 200	72.0
76.0	39.1	57.9	5 300	41.9	56.5	5 700				76.0
80.0	34.6	52.0	4 400	37.4	50.4	4 700				80.0
84.0	29.6	44.9	3 600							84.0




Liftcrane Jib Capacities

Meets
ANSI B30.5
Requirements

2250T

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
21.3	80.8	96.3	18 500 *							21.3
22.0	80.4	96.2	18 400 *							22.0
24.0	79.2	95.7	18 000 *							24.0
26.0	77.9	95.2	17 700 *							26.0
28.0	76.7	94.7	17 300 *	80.0	93.8	15 400*				28.0
30.0	75.4	94.1	17 000 *	78.7	93.2	15 100*				30.0
32.0	74.2	93.5	16 600 *	77.4	92.6	14 800*				32.0
34.0	72.9	92.8	16 300 *	76.1	91.9	14 500*	79.7	90.2	11 900*	34.0
36.0	71.6	92.0	16 000 *	74.8	91.1	14 200*	78.4	89.4	11 600*	36.0
38.0	70.3	91.2	15 700 *	73.5	90.3	14 000*	77.0	88.6	11 300*	38.0
40.0	69.0	90.4	15 400 *	72.2	89.5	13 700*	75.7	87.7	11 000*	40.0
44.0	66.3	88.5	14 800 *	69.5	87.6	13 200*	72.9	85.8	10 400*	44.0
48.0	63.6	86.4	14 200 *	66.8	85.5	12 700*	70.1	83.7	9 900*	48.0
52.0	60.8	84.1	13 500	63.9	83.1	12 200*	67.2	81.3	9 400*	52.0
56.0	57.9	81.5	11 600	61.0	80.5	11 800*	64.2	78.6	9 000*	56.0
60.0	55.0	78.6	9 900	58.0	77.5	10 600	61.1	75.6	8 700*	60.0
64.0	51.8	75.3	8 500	54.8	74.2	9 100	57.9	72.2	8 300*	64.0
68.0	48.6	71.7	7 200	51.5	70.5	7 800	54.5	68.4	8 000*	68.0
72.0	45.1	67.5	6 200	48.0	66.3	6 600	50.8	64.1	7 100	72.0
76.0	41.4	62.9	5 200	44.2	61.6	5 600	46.9	59.2	6 000	76.0
80.0	37.4	57.6	4 300	40.1	56.1	4 600				80.0
84.0	32.9	51.3	3 500	35.5	49.6	3 700				84.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
22.9	80.2	99.1	18 300 *							22.9
24.0	79.5	98.9	18 100 *							24.0
26.0	78.3	98.4	17 800 *							26.0
28.0	77.1	97.9	17 400 *	80.3	97.0	15 500*				28.0
30.0	75.9	97.3	17 100 *	79.1	96.4	15 200*				30.0
32.0	74.7	96.7	16 800 *	77.8	95.8	14 900*				32.0
34.0	73.4	96.0	16 500 *	76.6	95.1	14 600*	80.0	93.4	12 000*	34.0
36.0	72.2	95.3	16 200 *	75.3	94.4	14 400*	78.8	92.6	11 700*	36.0
38.0	71.0	94.5	15 800 *	74.1	93.6	14 100*	77.5	91.8	11 400*	38.0
40.0	69.7	93.7	15 600 *	72.8	92.8	13 800*	76.2	91.0	11 100*	40.0
44.0	67.1	91.9	15 000 *	70.2	91.0	13 300*	73.5	89.2	10 500*	44.0
48.0	64.5	89.9	14 400 *	67.6	88.9	12 800*	70.8	87.1	10 000*	48.0
52.0	61.8	87.7	13 200	64.9	86.7	12 400*	68.1	84.8	9 500*	52.0
56.0	59.1	85.2	11 300	62.1	84.1	12 000*	65.2	82.2	9 100*	56.0
60.0	56.2	82.4	9 600	59.2	81.3	10 300	62.2	79.4	8 800*	60.0
64.0	53.3	79.3	8 200	56.2	78.2	8 800	59.2	76.2	8 400*	64.0
68.0	50.2	75.8	6 900	53.1	74.7	7 500	55.9	72.6	8 100	68.0
72.0	46.9	72.0	5 800	49.8	70.8	6 300	52.5	68.6	6 900	72.0
76.0	43.5	67.6	4 800	46.2	66.3	5 300	48.9	64.0	5 700	76.0
80.0	39.8	62.7	3 900	42.5	61.3	4 300				80.0
84.0	35.7	57.1	3 100	38.3	55.5	3 500				84.0
88.0	31.2	50.4	2 400							88.0




Liftcrane Jib Capacities

**Meets
 ANSI B30.5
 Requirements**

2250T

**Jib No. 132 With 6 096 mm Strut On
 Boom No. 44A With Heavy Lift Top
 55 880 kg Counterweight
 360 Degree Rating
 On Extended Outriggers**



30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
22.9	80.5	102.2	18 400 *							22.9
24.0	79.8	102.0	18 200 *							24.0
26.0	78.7	101.5	17 900 *							26.0
28.0	77.5	101.0	17 500 *	80.6	100.1	15 600*				28.0
30.0	76.3	100.5	17 200 *	79.4	99.6	15 300*				30.0
32.0	75.2	99.9	16 900 *	78.2	99.0	15 000*				32.0
34.0	74.0	99.2	16 600 *	77.0	98.3	14 700*	80.4	96.5	12 100*	34.0
36.0	72.8	98.5	16 300 *	75.8	97.6	14 500*	79.1	95.8	11 800*	36.0
38.0	71.6	97.8	16 000 *	74.6	96.9	14 200*	77.9	95.1	11 500*	38.0
40.0	70.3	97.0	15 700 *	73.4	96.1	13 900*	76.6	94.3	11 200*	40.0
44.0	67.9	95.3	15 200 *	70.9	94.3	13 400*	74.1	92.5	10 600*	44.0
48.0	65.4	93.3	14 600 *	68.3	92.4	13 000*	71.5	90.5	10 100*	48.0
52.0	62.8	91.2	12 900	65.7	90.2	12 500*	68.8	88.3	9 700*	52.0
56.0	60.1	88.8	11 000	63.0	87.8	11 800	66.1	85.9	9 300*	56.0
60.0	57.4	86.1	9 300	60.3	85.1	10 100	63.3	83.1	8 900*	60.0
64.0	54.6	83.2	7 800	57.4	82.1	8 600	60.3	80.1	8 600*	64.0
68.0	51.7	79.9	6 600	54.5	78.8	7 200	57.3	76.7	7 900	68.0
72.0	48.6	76.3	5 500	51.4	75.1	6 100	54.1	72.9	6 600	72.0
76.0	45.4	72.2	4 500	48.1	70.9	5 000	50.7	68.6	5 500	76.0
80.0	41.9	67.6	3 600	44.6	66.3	4 000	47.0	63.8	4 400	80.0
84.0	38.2	62.4	2 800	40.8	61.0	3 200				84.0
88.0	34.1	56.5	2 100	36.6	54.8	2 400				88.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
18.3	80.9	78.4	14 800 *							18.3
20.0	79.6	78.0	14 500 *							20.0
22.0	78.0	77.5	13 900 *							22.0
24.0	76.5	76.9	13 500 *							24.0
26.0	74.9	76.3	13 000 *	80.1	75.7	10 800*				26.0
28.0	73.4	75.6	12 600 *	78.5	75.0	10 400*				28.0
30.0	71.8	74.8	12 100 *	76.9	74.2	10 000*				30.0
32.0	70.1	74.0	11 700 *	75.3	73.4	9 700*				32.0
34.0	68.5	73.1	11 200 *	73.7	72.5	9 400*	78.7	70.9	8 100*	34.0
36.0	66.9	72.2	10 800 *	72.0	71.6	9 100*	77.0	69.9	7 900*	36.0
38.0	65.2	71.1	10 400 *	70.3	70.6	8 800*	75.3	68.9	7 700*	38.0
40.0	63.5	70.0	10 100 *	68.6	69.5	8 500*	73.5	67.7	7 400*	40.0
44.0	60.0	67.6	9 400 *	65.1	67.0	7 900*	69.9	65.2	7 000*	44.0
48.0	56.3	64.8	8 700 *	61.4	64.2	7 400*	66.1	62.3	6 600*	48.0
52.0	52.5	61.6	8 100 *	57.5	61.0	7 000*	62.1	59.0	6 300*	52.0
56.0	48.5	57.9	7 600 *	53.4	57.3	6 600*	57.9	55.2	6 000*	56.0
60.0	44.1	53.6	7 100 *	49.0	53.0	6 200*	53.2	50.7	5 700*	60.0
64.0	39.3	48.6	6 600 *	44.2	48.0	5 900*	48.1	45.3	5 500*	64.0
68.0	33.9	42.6	6 200 *	38.6	41.8	5 600*				68.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.7m (140 Ft.) BOOM										
19.8	80.1	81.1	14 600 *							19.8
20.0	80.0	81.1	14 600 *							20.0
22.0	78.5	80.6	14 100 *							22.0
24.0	77.0	80.1	13 600 *							24.0
26.0	75.5	79.5	13 200 *	80.5	78.8	10 900*				26.0
28.0	74.0	78.8	12 700 *	79.0	78.2	10 500*				28.0
30.0	72.5	78.1	12 300 *	77.5	77.5	10 200*				30.0
32.0	71.0	77.3	11 900 *	75.9	76.7	9 800*				32.0
34.0	69.4	76.5	11 500 *	74.3	75.8	9 500*	79.2	74.1	8 200*	34.0
36.0	67.8	75.5	11 100 *	72.8	74.9	9 200*	77.6	73.2	8 000*	36.0
38.0	66.2	74.6	10 700 *	71.1	74.0	8 900*	75.9	72.2	7 800*	38.0
40.0	64.6	73.5	10 300 *	69.5	72.9	8 600*	74.3	71.1	7 500*	40.0
44.0	61.3	71.2	9 600 *	66.2	70.6	8 100*	70.8	68.8	7 100*	44.0
48.0	57.8	68.6	8 900 *	62.7	68.0	7 600*	67.3	66.0	6 700*	48.0
52.0	54.2	65.5	8 400 *	59.1	64.9	7 100*	63.5	62.9	6 400*	52.0
56.0	50.5	62.1	7 800 *	55.2	61.5	6 700*	59.5	59.3	6 100*	56.0
60.0	46.4	58.2	7 300 *	51.2	57.5	6 400*	55.3	55.2	5 800*	60.0
64.0	42.1	53.6	6 900 *	46.8	52.9	6 000*	50.7	50.4	5 600*	64.0
68.0	37.3	48.2	6 500 *	41.9	47.5	5 800*	45.5	44.6	5 400*	68.0
72.0	31.8	41.7	6 100 *	36.3	40.9	5 500*				72.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
19.8	80.5	84.3	14 700 *							19.8
20.0	80.4	84.2	14 700 *							20.0
22.0	78.9	83.7	14 300 *							22.0
24.0	77.5	83.2	13 800 *							24.0
26.0	76.1	82.6	13 400 *							26.0
28.0	74.6	82.0	12 900 *	79.4	81.4	10 600*				28.0
30.0	73.2	81.3	12 500 *	78.0	80.7	10 300*				30.0
32.0	71.7	80.6	12 100 *	76.5	79.9	9 900*				32.0
34.0	70.2	79.8	11 700 *	75.0	79.1	9 600*	79.7	77.4	8 300*	34.0
36.0	68.7	78.9	11 300 *	73.5	78.3	9 300*	78.1	76.5	8 000*	36.0
38.0	67.2	78.0	10 900 *	71.9	77.3	9 000*	76.5	75.5	7 900*	38.0
40.0	65.6	77.0	10 500 *	70.4	76.3	8 700*	74.9	74.5	7 600*	40.0
44.0	62.5	74.8	9 900 *	67.2	74.1	8 200*	71.7	72.3	7 200*	44.0
48.0	59.2	72.3	9 200 *	63.9	71.6	7 800*	68.3	69.7	6 800*	48.0
52.0	55.8	69.4	8 600 *	60.4	68.8	7 300*	64.7	66.7	6 500*	52.0
56.0	52.3	66.2	8 100 *	56.9	65.5	6 900*	61.0	63.4	6 200*	56.0
60.0	48.5	62.5	7 600 *	53.1	61.8	6 500*	57.1	59.6	5 900*	60.0
64.0	44.5	58.3	7 100 *	49.0	57.6	6 200*	52.9	55.1	5 700*	64.0
68.0	40.1	53.4	6 700 *	44.6	52.7	5 900*	48.2	50.0	5 500*	68.0
72.0	35.3	47.7	6 300 *	39.7	46.9	5 700*				72.0
76.0	29.7	40.6	6 000 *	33.9	39.7	5 500*				76.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.8m (160 Ft.) BOOM										
19.8	80.8	87.4	14 800 *							19.8
20.0	80.7	87.3	14 800 *							20.0
22.0	79.4	86.9	14 400 *							22.0
24.0	78.0	86.4	14 000 *							24.0
26.0	76.6	85.8	13 500 *							26.0
28.0	75.2	85.2	13 100 *	79.8	84.5	10 700*				28.0
30.0	73.8	84.5	12 700 *	78.4	83.9	10 400*				30.0
32.0	72.4	83.8	12 300 *	77.0	83.2	10 100*				32.0
34.0	70.9	83.1	11 900 *	75.5	82.4	9 800*	80.1	80.6	8 400*	34.0
36.0	69.5	82.2	11 500 *	74.1	81.6	9 500*	78.6	79.8	8 100*	36.0
38.0	68.0	81.3	11 100 *	72.6	80.7	9 200*	77.1	78.8	7 900*	38.0
40.0	66.6	80.4	10 800 *	71.1	79.7	8 900*	75.5	77.9	7 700*	40.0
44.0	63.5	78.3	10 100 *	68.1	77.6	8 400*	72.4	75.7	7 300*	44.0
48.0	60.4	75.9	9 500 *	65.0	75.2	7 900*	69.2	73.3	6 900*	48.0
52.0	57.2	73.2	8 900 *	61.7	72.5	7 500*	65.9	70.5	6 600*	52.0
56.0	53.9	70.1	8 300 *	58.3	69.5	7 100*	62.4	67.3	6 300*	56.0
60.0	50.4	66.7	7 800 *	54.8	66.0	6 700*	58.7	63.7	6 000*	60.0
64.0	46.6	62.8	7 300 *	51.0	62.1	6 300*	54.8	59.7	5 800*	64.0
68.0	42.6	58.3	6 900 *	46.9	57.6	6 100*	50.5	54.9	5 600*	68.0
72.0	38.3	53.1	6 500 *	42.5	52.3	5 800*	45.8	49.4	5 400*	72.0
76.0	33.4	47.0	6 200 *	37.5	46.1	5 600*				76.0
80.0	27.6	39.3	5 900							80.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
21.3	80.2	90.2	14 600 *							21.3
22.0	79.7	90.0	14 500 *							22.0
24.0	78.4	89.5	14 100 *							24.0
26.0	77.1	89.0	13 700 *							26.0
28.0	75.7	88.4	13 300 *	80.2	87.7	10 800*				28.0
30.0	74.4	87.8	12 800 *	78.8	87.1	10 400*				30.0
32.0	73.0	87.1	12 500 *	77.5	86.4	10 200*				32.0
34.0	71.6	86.3	12 100 *	76.1	85.6	9 900*	80.4	83.8	8 400*	34.0
36.0	70.2	85.5	11 700 *	74.7	84.8	9 600*	79.0	83.0	8 200*	36.0
38.0	68.8	84.7	11 400 *	73.3	84.0	9 300*	77.6	82.1	8 000*	38.0
40.0	67.4	83.8	11 000 *	71.8	83.1	9 000*	76.1	81.2	7 800*	40.0
44.0	64.5	81.7	10 300 *	68.9	81.1	8 500*	73.1	79.1	7 400*	44.0
48.0	61.6	79.5	9 700 *	65.9	78.8	8 000*	70.1	76.8	7 000*	48.0
52.0	58.5	76.9	9 100 *	62.8	76.2	7 600*	66.9	74.1	6 700*	52.0
56.0	55.3	74.0	8 500 *	59.6	73.3	7 200*	63.6	71.2	6 400*	56.0
60.0	52.0	70.8	8 000 *	56.3	70.1	6 800*	60.1	67.8	6 100*	60.0
64.0	48.5	67.1	7 600 *	52.8	66.4	6 500*	56.5	64.0	5 900*	64.0
68.0	44.8	63.0	7 200 *	49.0	62.2	6 200*	52.5	59.6	5 700*	68.0
72.0	40.8	58.2	6 800 *	45.0	57.4	6 000*	48.3	54.6	5 500*	72.0
76.0	36.4	52.7	6 400 *	40.5	51.8	5 700*				76.0
80.0	31.5	46.1	5 700	35.4	45.1	5 500*				80.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
 Boom No. 44A With Heavy Lift Top
 55 880 kg Counterweight
 360 Degree Rating
 On Extended Outriggers

Meets
 ANSI B30.5
 Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
21.3	80.5	93.3	14 700 *							21.3
22.0	80.1	93.1	14 600 *							22.0
24.0	78.8	92.7	14 200 *							24.0
26.0	77.5	92.1	13 800 *							26.0
28.0	76.2	91.6	13 400 *	80.5	90.9	10 900*				28.0
30.0	74.9	91.0	13 000 *	79.2	90.3	10 500*				30.0
32.0	73.6	90.3	12 700 *	77.9	89.6	10 200*				32.0
34.0	72.3	89.6	12 200 *	76.6	88.9	9 900*				34.0
36.0	70.9	88.8	11 900 *	75.2	88.1	9 700*	79.4	86.2	8 300*	36.0
38.0	69.6	88.0	11 500 *	73.9	87.3	9 400*	78.0	85.4	8 000*	38.0
40.0	68.2	87.1	11 200 *	72.5	86.4	9 200*	76.6	84.5	7 900*	40.0
44.0	65.5	85.2	10 500 *	69.7	84.5	8 600*	73.8	82.5	7 400*	44.0
48.0	62.6	83.0	9 900 *	66.8	82.3	8 200*	70.8	80.3	7 100*	48.0
52.0	59.7	80.6	9 300 *	63.9	79.8	7 700*	67.8	77.8	6 800*	52.0
56.0	56.7	77.8	8 800 *	60.8	77.1	7 400*	64.7	74.9	6 500*	56.0
60.0	53.5	74.7	8 300 *	57.7	74.0	7 000*	61.4	71.8	6 200*	60.0
64.0	50.3	71.3	7 800 *	54.4	70.6	6 700*	58.0	68.2	6 000*	64.0
68.0	46.8	67.4	7 400 *	50.8	66.7	6 400*	54.3	64.1	5 800*	68.0
72.0	43.1	63.0	7 000 *	47.1	62.2	6 100*	50.4	59.5	5 600*	72.0
76.0	39.1	58.0	6 200	43.0	57.1	5 800*	46.1	54.1	5 400*	76.0
80.0	34.7	52.1	5 300	38.5	51.2	5 600*				80.0
84.0	29.6	45.0	4 500							84.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
21.3	80.8	96.4	14 800 *							21.3
22.0	80.4	96.2	14 700 *							22.0
24.0	79.2	95.8	14 300 *							24.0
26.0	77.9	95.3	13 900 *							26.0
28.0	76.7	94.7	13 500 *							28.0
30.0	75.4	94.2	13 200 *	79.6	93.4	10 600*				30.0
32.0	74.1	93.5	12 800 *	78.3	92.8	10 300*				32.0
34.0	72.9	92.8	12 400 *	77.0	92.1	10 000*				34.0
36.0	71.6	92.1	12 100 *	75.7	91.4	9 800*	79.8	89.4	8 300*	36.0
38.0	70.3	91.3	11 700 *	74.4	90.6	9 500*	78.5	88.6	8 100*	38.0
40.0	69.0	90.4	11 400 *	73.1	89.7	9 200*	77.1	87.8	7 900*	40.0
44.0	66.3	88.6	10 700 *	70.4	87.9	8 800*	74.4	85.9	7 500*	44.0
48.0	63.6	86.5	10 100 *	67.7	85.8	8 300*	71.5	83.7	7 200*	48.0
52.0	60.8	84.2	9 500 *	64.9	83.4	7 900*	68.7	81.3	6 900*	52.0
56.0	57.9	81.5	9 000 *	62.0	80.8	7 500*	65.7	78.6	6 600*	56.0
60.0	54.9	78.6	8 500 *	58.9	77.9	7 100*	62.6	75.6	6 300*	60.0
64.0	51.8	75.4	8 000 *	55.8	74.6	6 800*	59.3	72.2	6 100*	64.0
68.0	48.6	71.7	7 600 *	52.5	70.9	6 500*	55.9	68.4	5 900*	68.0
72.0	45.1	67.6	6 900	49.0	66.8	6 200*	52.3	64.1	5 700*	72.0
76.0	41.4	63.0	5 900	45.3	62.1	5 900*	48.3	59.2	5 500*	76.0
80.0	37.4	57.6	5 000	41.2	56.7	5 500				80.0
84.0	32.9	51.4	4 200	36.6	50.4	4 600				84.0
88.0	27.8	43.8	3 500							88.0




Liftcrane Jib Capacities

**Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers**

**Meets
ANSI B30.5
Requirements**

2250T



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
22.9	80.2	99.2	14 600 *							22.9
24.0	79.5	98.9	14 400 *							24.0
26.0	78.3	98.4	14 000 *							26.0
28.0	77.1	97.9	13 700 *							28.0
30.0	75.9	97.3	13 300 *	79.9	96.6	10 700*				30.0
32.0	74.7	96.7	12 900 *	78.7	96.0	10 400*				32.0
34.0	73.4	96.1	12 600 *	77.5	95.3	10 100*				34.0
36.0	72.2	95.3	12 200 *	76.2	94.6	9 900*	80.1	92.7	8 400*	36.0
38.0	70.9	94.6	11 900 *	74.9	93.8	9 600*	78.8	91.9	8 200*	38.0
40.0	69.7	93.8	11 500 *	73.7	93.0	9 400*	77.5	91.0	8 000*	40.0
44.0	67.1	92.0	10 900 *	71.1	91.2	8 900*	74.9	89.2	7 600*	44.0
48.0	64.5	90.0	10 300 *	68.5	89.2	8 400*	72.2	87.2	7 300*	48.0
52.0	61.8	87.7	9 700 *	65.7	87.0	8 000*	69.4	84.9	7 000*	52.0
56.0	59.1	85.2	9 200 *	63.0	84.5	7 700*	66.6	82.3	6 700*	56.0
60.0	56.2	82.4	8 700 *	60.1	81.7	7 300*	63.6	79.4	6 400*	60.0
64.0	53.3	79.3	8 200 *	57.1	78.6	6 900*	60.6	76.2	6 200*	64.0
68.0	50.2	75.9	7 700	54.0	75.1	6 600*	57.3	72.6	5 900*	68.0
72.0	46.9	72.0	6 600	50.7	71.2	6 300*	53.9	68.6	5 700*	72.0
76.0	43.5	67.7	5 600	47.2	66.9	6 100*	50.3	64.0	5 600*	76.0
80.0	39.8	62.8	4 700	43.5	61.9	5 200	46.3	58.8	5 400	80.0
84.0	35.8	57.2	3 900	39.4	56.2	4 300				84.0
88.0	31.2	50.5	3 100	34.7	49.4	3 500				88.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
22.9	80.5	102.3	14 700 *							22.9
24.0	79.8	102.0	14 500 *							24.0
26.0	78.7	101.6	14 200 *							26.0
28.0	77.5	101.1	13 800 *							28.0
30.0	76.3	100.5	13 500 *	80.2	99.7	10 800*				30.0
32.0	75.1	99.9	13 100 *	79.0	99.1	10 500*				32.0
34.0	73.9	99.3	12 700 *	77.9	98.5	10 200*				34.0
36.0	72.7	98.6	12 400 *	76.6	97.8	10 000*				36.0
38.0	71.5	97.8	12 000 *	75.4	97.1	9 700*	79.2	95.1	8 200*	38.0
40.0	70.3	97.1	11 700 *	74.2	96.3	9 500*	78.0	94.3	8 000*	40.0
44.0	67.9	95.3	11 100 *	71.7	94.6	9 000*	75.4	92.5	7 700*	44.0
48.0	65.3	93.4	10 500 *	69.2	92.6	8 600*	72.8	90.6	7 300*	48.0
52.0	62.8	91.2	9 900 *	66.6	90.5	8 100*	70.2	88.3	7 000*	52.0
56.0	60.1	88.8	9 400 *	63.9	88.1	7 700*	67.4	85.9	6 700*	56.0
60.0	57.4	86.2	8 900 *	61.2	85.4	7 400*	64.6	83.1	6 500*	60.0
64.0	54.6	83.2	8 400 *	58.3	82.4	7 100*	61.7	80.1	6 300*	64.0
68.0	51.7	80.0	7 500	55.4	79.2	6 800*	58.6	76.7	6 000*	68.0
72.0	48.6	76.3	6 400	52.3	75.5	6 500*	55.4	72.9	5 800*	72.0
76.0	45.4	72.3	5 400	49.0	71.4	6 000	52.0	68.7	5 700*	76.0
80.0	41.9	67.7	4 500	45.5	66.8	5 000	48.4	63.8	5 400	80.0
84.0	38.2	62.5	3 700	41.8	61.6	4 200				84.0
88.0	34.1	56.5	3 000	37.6	55.5	3 400				88.0
92.0	29.5	49.5	2 300	32.9	48.3	3 400				92.0




2250T

Liftcrane Jib Capacities

Jib No. 132 With 6 096 mm Strut On
Boom No. 44A With Heavy Lift Top
55 880 kg Counterweight
360 Degree Rating
On Extended Outriggers

Meets
ANSI B30.5
Requirements



36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
22.9	80.8	105.4	14 800 *							22.9
24.0	80.1	105.2	14 700 *							24.0
26.0	79.0	104.7	14 300 *							26.0
28.0	77.9	104.2	13 900 *							28.0
30.0	76.7	103.7	13 600 *							30.0
32.0	75.6	103.1	13 200 *	79.4	102.3	10 600*				32.0
34.0	74.4	102.5	12 900 *	78.2	101.7	10 300*				34.0
36.0	73.3	101.8	12 500 *	77.1	101.0	10 100*				36.0
38.0	72.1	101.1	12 200 *	75.9	100.3	9 800*	79.6	98.3	8 300*	38.0
40.0	70.9	100.3	11 900 *	74.7	99.6	9 600*	78.3	97.5	8 100*	40.0
44.0	68.5	98.7	11 300 *	72.3	97.9	9 100*	75.9	95.8	7 700*	44.0
48.0	66.1	96.8	10 700 *	69.8	96.0	8 700*	73.4	93.9	7 400*	48.0
52.0	63.6	94.7	10 100 *	67.3	93.9	8 300*	70.8	91.8	7 100*	52.0
56.0	61.1	92.4	9 600 *	64.8	91.6	7 900*	68.2	89.4	6 800*	56.0
60.0	58.5	89.9	9 100 *	62.2	89.1	7 500*	65.5	86.8	6 600*	60.0
64.0	55.8	87.0	8 400	59.4	86.3	7 200*	62.7	83.9	6 300*	64.0
68.0	53.0	83.9	7 100	56.6	83.1	6 900*	59.8	80.7	6 100*	68.0
72.0	50.1	80.5	6 100	53.7	79.7	6 600	56.8	77.1	5 900*	72.0
76.0	47.1	76.7	5 100	50.6	75.8	5 700	53.6	73.1	5 700*	76.0
80.0	43.8	72.4	4 200	47.3	71.5	4 800	50.2	68.6	5 200	80.0
84.0	40.4	67.6	3 400	43.9	66.7	3 900	46.5	63.5	4 300	84.0
88.0	36.7	62.1	2 700	40.1	61.1	3 100				88.0
92.0	32.6	55.8	2 000	35.9	54.7	2 300				92.0