

Wire Rope Specifications

999 SERIES 1, 2, 3

Liftcrane - Luffing Jib No. 135 on Boom No. 82 or 22EL

European
Standards

Wire Rope Lengths - Front Drum									
Boom and Luffing Jib Length		Luffing Jib Hoist Line Front Drum							
		4 Part		3 Part		2 Part		1 Part	
Ft.	Meters	Ft.	Meters	Ft.	Meters	Ft.	Meters	Ft.	Meters
140	42.7	750	229					310	95
150	45.7	800	244					330	101
160	48.8	850	259	700	213			350	107
170	51.8	900	274	725	221			370	113
180	54.9	950	290	775	236			390	119
190	57.9	1000	305	800	244			410	125
200	61.0	1050	320	850	259	650	198	430	131
210	64.0	1100	335	900	274	675	206	450	137
220	67.1	1150	351	925	282	700	213	470	143
230	70.1	1200	366	975	297	750	229	490	149
240	73.2	1250	381	1000	305	775	236	510	155
250	76.2	—	—	1050	320	800	244	530	162
260	79.2	—	—	1100	335	825	251	550	168
270	82.3	—	—	1125	343	850	259	570	174
280	85.3	—	—	1175	358	875	267	590	180
290	88.4	—	—	1200	366	925	282	610	186
300	91.4	—	—	—	—	950	290	630	192
310	94.5	—	—	—	—	975	297	650	198
320	97.5	—	—	—	—	1000	305	670	204
330	100.6	—	—	—	—	1025	312	690	210
340	103.6	—	—	—	—	1050	320	710	216
350	106.7	—	—	—	—	1100	335	730	223
360	109.7	—	—	—	—	1125	343	750	229
370	112.8	—	—	—	—	1150	351	770	235

Note: Hoist line lengths given in table will allow hook to touch ground. When block travel below ground is required, add additional rope equal to parts of line times added travel distance. Hoisting distance or line pull may be limited when block travel below ground is required. See tables on page 2 for auxiliary drum application.

Hoist Reeving for Main Load Block - Front Drum				
No. Parts of Line	1	2	3	4
Maximum Load - Lbs.	29,500	59,000	88,500	105,500
Maximum Load - kg	13 380	26 760	40 140	47 400



Wire Rope Specifications

999 SERIES 1, 2, 3

Liftcrane - Luffing Jib No. 135 on Boom No. 82 or 22EL

European
Standards

Wire Rope Lengths - Auxiliary Drum									
Boom and Luffing Jib Length		Luffing Jib Hoist Line Auxiliary Drum							
		4 Part		3 Part		2 Part		1 Part	
Ft.	Meters	Ft.	Meters	Ft.	Meters	Ft.	Meters	Ft.	Meters
140	42.7	750	229					310	95
150	45.7	800	244					330	101
160	48.8	850	259					350	107
170	51.8	900	274					370	113
180	54.9	950	290					390	119
190	57.9	1000	305					410	125
200	61.0	1050	320	850	259			430	131
210	64.0	1100	335	900	274			450	137
220	67.1	1150	351	925	282			470	143
230	70.1	1200	366	975	297	750	229	490	149
240	73.2	1250	381	1000	305	775	236	510	155
250	76.2	1300	396	1050	320	800	244	530	162
260	79.2	1350	411	1100	335	825	251	550	168
270	82.3	1400	427	1125	343	850	259	570	174
280	85.3	1450	442	1175	358	875	267	590	180
290	88.4	1500	457	1200	366	925	282	610	186
300	91.4	—	—	1225	373	950	290	630	192
310	94.5	—	—	1275	389	975	297	650	198
320	97.5	—	—	1300	396	1000	305	670	204
330	100.6	—	—	1350	411	1025	312	690	210
340	103.6	—	—	1400	427	1050	320	710	216
350	106.7	—	—	—	—	1100	335	730	223
360	109.7	—	—	—	—	1125	343	750	229
370	112.8	—	—	—	—	1150	351	770	235

Note: Hoist line lengths given in table will allow hook to touch ground. When block travel below ground is required, add additional rope equal to parts of line times added travel distance. Hoisting distance or line pull may be limited when block travel below ground is required.

Capacity chart restrictions will occur when auxiliary drum is used. Maximum capacity is 80,000 Lbs. (36 290 kg) with four parts line.

Hoist Reeving for Main Load Block - Auxiliary Drum				
No. Parts of Line	1	2	3	4
Maximum Load - Lbs.	20,000	40,000	60,000	80,000
Maximum Load - kg	9 070	18 140	27 220	36 290

Wire Rope Specifications

999 SERIES 1, 2, 3

Liftcrane - Luffing Jib No. 135 on Boom No. 82 or 22EL

European
Standards

Wire Rope Specifications

Rotation Resistant Wire Rope - 5:1 Safety Factor

Hoist Line: 26 mm - 2 160 N/mm² Wire Rope With Pad Eye (MCC Part No. 719430)
Right Hand Regular Lay
Minimum Breaking Strength = 161,200 Lbs. (717.0 kN)
Approx. Weight = 2.13 Lbs Per Ft. (3.17 kg/m)
No Load Dia. = 1.033 in. (26.24 mm) to 1.045 in. (26.54 mm)

Or

26 mm - Wire Rope With Pad Eye (MCC Part No. 719432)
Right Hand Lang Lay
Minimum Breaking Strength = 156,400 Lbs. (695.7 kN)
Approx. Weight = 2.39 Lbs Per Ft. (3.56 kg/m)
No Load Dia. = 1.034 in. (26.26 mm) to 1.054 in. (26.77 mm)

Hoist Line: 26 mm - 1 960 N/mm² Wire Rope (MCC Part No. 719378)
(Auxiliary Drum) Right Hand Regular Lay
Minimum Breaking Strength Required = 100,000 Lbs. (445.0 kN)
Maximum Load = 20,000 Lbs. (9 070 kg) Per Line
Approx. Weight = 2.13 Lbs. Per Ft. (3.17 kg/m)
No Load Dia. (required for lagging) = 1.033 in. (26.24 mm) to 1.045 in. (26.54 mm)

Or

26 mm - Wire Rope With Pad Eye (MCC Part No. 719432)
Right Hand Lang Lay
Minimum Breaking Strength Required = 100,000 Lbs. (445.0 kN)
Maximum Load = 20,000 Lbs. (9 070 kg) Per Line
Approx. Weight = 2.39 Lbs. Per Ft. (3.56 kg/m)
No Load Dia. (required for lagging) = 1.034 in. (26.26 mm) to 1.054 in. (26.77 mm)

Maximum Spooling Capacities

Front Drum: 26 mm Wire Rope - 7 Layers - 1,727 Ft. (526m)
(Hoist Line)

Auxiliary Drum: 26 mm Wire Rope - 6 Layers - 1,323 Ft. (403m)
(Hoist Line) 6 Layers - 1,415 Ft. (431m) with 21-1/4 in. (540 mm) Dia. Lagging

17 Ft. (5m) is deducted from maximum spooling capacities for 3 dead wraps per drum or lagging.

Note: When optional laggings are used, the recommended lagging for specific wire rope dia. must be used.

Refer to drum and lagging chart **No. 8222-A**.