

Maximum Allowable Travel Specifications

Boom No. 222HD/222 With Open Throat Top
Jib No. 10 With 12 Ft. 6 in. (3 810 mm) Strut

222HD
222HD SERIES B

Jobsite Travel

222HD must be equipped with 53,300 Lb. (24 180 kg) crane counterweight; 222HD SERIES B must be equipped with 63,300 Lb. (28 710 kg) crane counterweight and 14,000 Lb. (6 350 kg) crawler frame counterweight.

1. Machine Travel With Load

- A. Travel with crane upperworks in-line with crawlers. Grade in any direction must not exceed 1 percent (0.5 degrees).
- B. Travel surface must be firm, level and uniformly supporting. Capacity charts are based on static conditions; therefore judgment must be used to allow for dynamic effects of traveling with load. Carry load as close to ground as possible. Stabilize load with taglines. Travel slowly and smoothly to avoid shock loading boom, jib and rigging.

2. Machine Travel Without Load

- A. Load blocks and/or hook and weight balls may be suspended beneath lower boom point, upper boom point and jib point. Total combined suspended weight beneath lower and upper boom points must not exceed 3,500 Lbs. (1 590 kg) or 2,800 Lbs. (1 270 kg) on lower point when jib is attached. Total suspended weight beneath jib point must not exceed 700 Lbs. (320 kg).
- B. Machine to travel on a firm and uniformly supporting surface with crane upperworks in-line with crawlers and travel drive to rear. Grade in direction of travel should not exceed 30 percent (16.7 degrees); side-to-side grade must not exceed 2 percent (1.1 degrees) measured at boom hinge pins.
- C. See tables on pages 2-4 for boom angle, boom length and direction for various grades. Adjust boom within boom angle range shown in tables on pages 2-4 with machine in a level position before traveling onto grade. Do not change boom angle after crane has been traveled onto grade. Boom angle is angle between horizontal and centerline of boom butt and inserts. See table below for grade vs. angle when traveling.
- D. Do not exceed 2 percent (1.1 degrees) side-to-side grade at boom hinge pins when cutting (turning on grade). Travel with crane upperworks in-line with grade at all times.
- E. Boom lengths shown in tables on page 2 and 3 do not include jib. Boom lengths shown in tables on page 4 include all jib lengths and offset angles.
- F. **Warning:** Travel prohibited for boom lengths not shown in tables on pages 2, 3 and 4. *Crane could tip.*

Refer to capacity charts for maximum boom and jib length raising.

Percent Grade Vs. Angle In Degrees	
Percent Grade	Angle
10	5.7
20	11.3
30	16.7



Maximum Allowable Travel Specifications

Boom No. 222HD/222 With Open Throat Top

222HD
222HD SERIES B

Machine Travel Without Load - Boom Facing Downhill					
0 - 1% Percent Grade					
Boom Angle Range in Degrees	Boom Length (not including jib)				Boom Angle Range in Degrees
	53,300 Lb. (24 180 kg) Crane Counterweight		63,300 Lb. (28 710 kg) Crane Counterweight		
	14,000 Lb. (6 350 kg) Crawler Frame Cwt.				
	Feet	Meters	Feet	Meters	
30 - 72	40 - 120	12.2 - 36.6	40 - 140	12.2 - 42.7	30 - 72
40 - 72	130 - 140	39.6 - 42.7	150 - 160	45.7 - 48.8	40 - 72
50 - 72	150 - 160	45.7 - 48.8	170 - 180	51.8 - 54.9	50 - 72
60 - 72	170 - 200	51.8 - 61.0	190 - 200	57.9 - 61.0	60 - 72
2 - 10% Percent Grade					
30 - 72	40 - 110	12.2 - 33.5	40 - 130	12.2 - 39.6	30 - 72
40 - 72	120	36.6	140	42.7	40 - 72
50 - 72	130 - 140	39.6 - 42.7	150 - 160	45.7 - 48.8	50 - 72
60 - 72	150 - 160	45.7 - 48.8	170 - 190	51.8 - 57.9	60 - 72
65 - 72	170 - 180	51.8 - 54.9	200	61.0	65 - 72
11 - 20% Percent Grade					
30 - 72	40 - 100	12.2 - 30.5	40 - 120	12.2 - 36.6	30 - 72
40 - 72	110	33.5	130	39.6	40 - 72
50 - 72	120	36.6	140	42.7	50 - 72
60 - 72	130 - 140	39.6 - 42.7	150 - 160	45.7 - 48.8	60 - 72
65 - 72	150	45.7	170	51.8	65 - 72
21 - 30% Percent Grade					
30 - 72	40 - 90	12.2 - 27.4	40 - 100	12.2 - 30.5	30 - 72
40 - 72	100	30.5	110	33.5	40 - 72
50 - 72	110	33.5	120	36.6	50 - 72
60 - 72	120	36.6	130 - 140	39.6 - 42.7	60 - 72
65 - 72	130	39.6	150	45.7	65 - 72

Maximum Allowable Travel Specifications

Boom No. 222HD/222 With Open Throat Top

222HD
222HD SERIES B

Machine Travel Without Load - Boom Facing Uphill					
0 - 1% Percent Grade					
Boom Angle Range in Degrees	Boom Length (not including jib)				Boom Angle Range in Degrees
	53,300 Lb. (24 180 kg) Crane Counterweight		63,300 Lb. (28 710 kg) Crane Counterweight		
			14,000 Lb. (6 350 kg) Crawler Frame Cwt.		
	Feet	Meters	Feet	Meters	
30 - 66	40 - 200	12.2 - 61.0	40 - 200	12.2 - 61.0	30 - 66
2 - 10% Percent Grade					
30 - 40	50 - 70	15.2 - 21.3	60 - 70	18.3 - 21.3	30 - 40
30 - 66	80 - 140	24.4 - 42.7	80 - 150	24.4 - 45.7	30 - 66
40 - 66	150	45.7	160 - 170	48.8 - 51.8	40 - 66
50 - 66	160 - 180	48.8 - 54.9	180 - 200	54.9 - 61.0	50 - 66
60 - 66	190 - 200	57.9 - 61.0	—	—	60 - 66
11 - 20% Percent Grade					
30 - 40	70 - 100	21.3 - 30.5	80 - 110	24.4 - 33.5	30 - 40
30 - 60	110 - 150	33.5 - 45.7	120 - 170	36.6 - 51.8	30 - 60
40 - 60	160 - 170	48.8 - 51.8	180 - 190	54.9 - 57.9	40 - 60
50 - 60	180 - 200	54.9 - 61.0	200	61.0	50 - 60
21 - 30% Percent Grade					
30 - 40	100 - 150	30.5 - 45.7	100 - 160	30.5 - 48.8	30 - 40
30 - 55	160	48.8	170 - 180	51.8 - 54.9	30 - 55
40 - 55	170 - 190	51.8 - 57.9	190 - 200	57.9 - 61.0	40 - 55
50 - 55	200	61.0	—	—	50 - 55



Maximum Allowable Travel Specifications

Boom No. 222HD/222 With Open Throat Top
Jib No. 10 With 12 Ft. 6 in. (3 810 mm) Strut

222HD 222HD SERIES B

Machine Travel Without Load - Boom Facing Downhill				
0 - 1% Percent Grade				
Boom Angle Range in Degrees	Boom Length (including all jib lengths and offset angles)			
	53,300 Lb. (24 180 kg) Crane Counterweight		63,300 Lb. (28 710 kg) Crane Counterweight 14,000 Lb. (6 350 kg) Crawler Frame Cwt.	
	Feet	Meters	Feet	Meters
50 - 72	70 - 150	21.3 - 45.7	70 - 170	21.3 - 51.8
55 - 72	160	48.8	180 - 190	54.9 - 57.9
60 - 72	170 - 190	51.8 - 57.9	—	—
2 - 10% Percent Grade				
50 - 72	70 - 130	21.3 - 39.6	70 - 150	21.3 - 45.7
55 - 72	140	42.7	160	48.8
60 - 72	150	45.7	170	51.8
65 - 72	160 - 170	48.8 - 51.8	180 - 190	54.9 - 57.9
11 - 20% Percent Grade				
50 - 72	70 - 110	21.3 - 33.5	70 - 130	21.3 - 39.6
55 - 72	120	36.6	140	42.7
60 - 72	130	39.6	150	45.7
65 - 72	140	42.7	160	48.8
21 - 30% Percent Grade				
50 - 72	70 - 90	21.3 - 27.4	70 - 110	21.3 - 33.5
55 - 72	100	30.5	120	36.6
60 - 72	110	33.5	130	39.6
65 - 72	120	36.6	140	42.7

Machine Travel Without Load - Boom Facing Uphill				
0 - 1% Percent Grade				
Boom Angle Range in Degrees	Boom Length (including all jib lengths and offset angles)			
	53,300 Lb. (24 180 kg) Crane Counterweight		63,300 Lb. (28 710 kg) Crane Counterweight 14,000 Lb. (6 350 kg) Crawler Frame Cwt.	
	Feet	Meters	Feet	Meters
50 - 72	70 - 150	21.3 - 45.7	70 - 170	21.3 - 51.8
55 - 72	160	48.8	180 - 190	54.9 - 57.9
60 - 72	170 - 190	51.8 - 57.9	—	—
2 - 10% Percent Grade				
50 - 66	70 - 160	21.3 - 48.8	70 - 190	21.3 - 57.9
60 - 66	170 - 190	51.8 - 57.9	—	—
11 - 20% Percent Grade				
Not Allowed				
21 - 30% Percent Grade				
Not Allowed				