



WEIGHTS

4100W Tower

DESCRIPTION	NOTE	APPROXIMATE WEIGHT (POUNDS)
Tower No. 22A		
Tower Butt — 30'		6,315
Tower Cap — 2'-6" (with boom carrier and wire rope guide)		5,315
Tower Insert — 40' (with equalizer rails and boom latch)		4,795
Tower Insert — 40' (with 2 wire rope roller guides)		4,560
Tower Insert — 40' (with 2 wire rope roller guides and rubber bumpers)		4,480
Tower Insert — 20' (with wire rope roller guides)		2,480
Tower Insert — 10' (with wire rope roller guides)		1,395
Basic Pendant — 69'-8" (123' to 173' tower, 4 required)		330 each
Basic Pendant — 129'-8" (183' tower and over, 4 required)		545 each
Pendant — 50' (4 per set)		235 each
Pendant — 40' (4 per set)		200 each
Pendant — 20' (4 per set)		140 each
Pendant — 10' (4 per set)		105 each
Main Strut		2,050
Intermediate Strut		2,300
Boom Strut		1,450
Tower Backstay		2,030
Tower Holdback		2,145
Upper Strap (between boom strut and intermediate strut, 2 required)		540 each
Lower Strap (between main strut and intermediate strut, 2 required)		340 each
Upper Spreader (between lower strap ends)		170
Lower Spreader (between pendant links)		160
Pendant Link (on main struts, 4 required)		200 each
Equalizer with Pendant Links		1,940
Lifting Bracket		180
Tower Wire Rope Guide (lower)		380
Boom No. 23		
Boom Butt — 27'		2,440
Boom Top — 23' (with single sheave boom point)		2,075
(with double sheave boom point)		2,220
Boom Insert — 40' (with intermediate fall)		2,670
Boom Insert — 40' (with 2 wire rope roller guides)		1,720
Boom Insert — 20' (with wire rope roller guide)		980
Boom Insert — 10' (with wire rope roller guide)		580
Basic Pendant — 108'-7" (2 required)		495 each
Pendant — 40' (2 per insert)		240 each
Pendant — 20' (2 per insert)		165 each
Pendant — 10' (2 per insert)		125 each
Boom Stop Pendant — 27'-9 3/8"		265
Pendant Link (on boom point, 2 required)		45 each
Intermediate Suspension		415
Boom Wire Rope Guide (upper)		145
Jib No. 124		
Jib Top — 15'		520
Jib Butt — 15'		325
Jib Insert — 10'		170
Basic Pendant 78'-3"		100
Pendant — 9' (2 per insert)		25 each
Jib Backstay Pendant 51'-10 1/2" (2 required)		95 each
Jib Strut — 18'		350

DESCRIPTION	APPROXIMATE WEIGHT (POUNDS)
Components	
Tower Wire Rope Roller Guide	55
Boom Wire Rope Roller Guide	40
Boom Hoist Line — 12 Part 1,200' of 7/8" — 6 x 26	1,705
12 Part 1,150' of 3/4" — 6 x 26	1,200
Load Line — 1-1/8" — 6 x 31	2.34 lbs./ft.
Intermediate Fall — 1" — 6 x 25	1.8 lbs./ft.

NOTE Refer to machine weight sheet for load block, and weight ball specifications.

REFERENCE ONLY!