

# MANITOWOC ENGINEERING CO.

Division of the Manitowoc Company, Inc. Manitowoc, Wisconsin 54220



## DRUM AND LAGGING CHART

### M-1200

#### TANDEM RINGER DRUMS

APPLICATION	DRUM	PART NUMBER	DIAMETER	WIDTH	TYPE OF DRUM OR LAGGING	WIRE ROPE SIZE
<u>LIFT CRANE</u>						
HOIST	REAR	173396	29-1/2" (749 mm)	77-5/8" (1972 mm)	BARE DRUM	1-5/8" (42 mm)
HOIST (OPTIONAL)	FRONT	173396	29-1/2" (749 mm)	77-5/8" (1972 mm)	BARE DRUM	1-5/8" (42 mm)
HOIST (OPTIONAL)	REAR	502368	32-1/2" (826 mm)	77-5/8" (1972 mm)	GROOVED LAGGING	1-5/8" (42 mm)
HOIST (OPTIONAL)	FRONT	502368	32-1/2" (826 mm)	77-5/8" (1972 mm)	GROOVED LAGGING	1-5/8" (42 mm)
WHIP (OPTIONAL)	AUXILIARY	175812	28-1/2" (724 mm)	55" (1397 mm)	BARE DRUM	1-1/8" (29 mm)

NOTE: REAR DRUM APPLICATION REQUIRED WITH BOOM NO. 75A. TANDEM DRUM APPLICATION REQUIRED WITH BOOM NO. 72, BOOM NO. 72A, BOOM NO. 72/75A, AND JIB NO. 75 ON BOOM NO. 72 OR NO. 72A.