


MDT 319



Potain Plus Power Control Top Site Anti-collision systems Automatic Rotation Control

The icons represent the following features:

- Potain Plus:** P+
- Power Control:** kVA
- POTAIN CONNECT:** POTAIN CONNECT
- Top Site:** Top Site
- Anti-collision systems:** Anti-collision systems
- Automatic Rotation Control:** ARC

Mast - Reactions

6.6 ft - P 63A



Height (ft)	82	98	115	131	148	164	180	197	213	230
Height (ft)	239.5	233.9	233.9	233.9	228.7	228.7	228.7	228.7	217.5	217.5
Height/P ₊ (ft)	239.5	233.9	233.9	233.9	228.7	228.7	228.7	228.7	217.5	217.5
10.9 ft	2	0	0	0	1	1	1	1	0	0
16.4 ft	11	12	12	12	11	11	11	11	11	11
32.8 ft	1	1	1	1	1	1	1	1	1	1
F2 (USt)	● 216 ■ 341	218 330	217 329	222 336	217 319	218 327	218 328	220 326	217 300	219 308
F3 (USt)	● 159 ■ 290	159 278	158 276	161 281	156 264	155 271	156 272	155 267	153 244	155 251

6.6 ft - V 60A -

Height (ft)	82	98	115	131	148	164	180	197	213	230
Height (ft)	226	226	226	226	220.8	226	226	209.6	209.6	209.6
Height/P ₊ (ft)	226	226	226	226	220.8	226	226	209.6	209.6	209.6
10.9 ft	1	1	1	1	2	1	1	1	1	1
16.4 ft	12	12	12	12	11	12	12	11	11	11
F1 (USt)	● 122 ■ 156	124 157	123 156	124 160	119 150	125 162	125 162	121 137	121 142	122 147

6.6 ft - V 63A -

Height (ft)	82	98	115	131	148	164	180	197	213	230
Height (ft)	237.2	242.8	242.8	242.8	237.2	237.2	237.2	220.8	226.4	226.4
Height/P ₊ (ft)	237.2	242.8	242.8	242.8	237.2	237.2	237.2	220.8	226.4	226.4
10.9 ft	2	1	1	1	2	2	2	2	1	1
16.4 ft	11	12	12	12	11	11	11	10	11	11
F1 (USt)	● 136 ■ 176	140 186	140 185	141 188	136 178	136 182	136 183	128 156	131 169	135 174




6.6 ft - ZD 640 - 

W (ft)	82	98	115	131	148	164	180	197	213	230
H (ft)	154.5	154.5	154.5	154.5	154.5	160.1	154.5	154.5	149.3	149.3
H/P_r (ft)	154.5	154.5	154.5	154.5	154.5	160.1	154.5	154.5	149.3	149.3
H_{eff}	10.9 ft	0	0	0	0	2	0	0	1	1
	16.4 ft	9	9	9	9	8	9	9	8	8
FI (USt)	● 111	114	114	116	116	119	116	117	119	118
	■ 99	101	101	104	103	112	105	105	105	107

6.6 ft - ZX 640 - 

W (ft)	82	98	115	131	148	164	180	197	213	230
H (ft)	237.2	237.2	237.2	237.2	231.6	231.6	231.6	231.6	220.8	220.8
H/P_r (ft)	237.2	237.2	237.2	237.2	231.6	231.6	231.6	231.6	220.8	220.8
H_{eff}	10.9 ft	0	0	0	1	1	1	1	0	0
	16.4 ft	12	12	12	12	11	11	11	11	11
FI (USt)	● 130	134	134	136	131	132	132	134	132	133
	■ 170	173	172	176	166	170	171	169	156	160



Note: When "ASCE" is noted in this data sheet it is referring to 115 mph Wind Zone, Exposure B, Design Wind Speed = 98 mph. See back cover for design wind speed calculations.

i Motorized accesses: adapted mast compositions, base ballast and reactions.

Other mast compositions - Please consult us

Anchorage

i

Base ballast

USt / 6.6 ft - V 60A -

Δ (ft)	82	98	115	131	148	164	180	197	213	230
226	145.5	145.5	145.5	145.5		145.5	145.5			
220.8	145.5	145.5	132.3	132.3	132.3	132.3	132.3			
209.6	132.3	119.1	119.1	119.1	119.1	119.1	119.1	132.3	132.3	132.3
193.2	105.8	105.8	105.8	105.8	105.8	92.6	92.6	105.8	105.8	105.8
176.8	92.6	92.6	92.6	79.4	92.6	79.4	79.4	92.6	92.6	92.6
160.4	79.4	79.4	79.4	66.1	66.1	66.1	66.1	79.4	79.4	79.4
144	66.1	66.1	66.1	52.9	52.9	52.9	52.9	66.1	66.1	66.1
127.6	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	52.9
111.2	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	52.9
94.8	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	39.7
78.4	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	39.7
62	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	39.7

USt / 6.6 ft - V 63A -

Δ (ft)	82	98	115	131	148	164	180	197	213	230
242.8		185.2	185.2	185.2						
237.2	185.2	172	172	172	172	172	172			
226.4	158.7	158.7	145.5	145.5	145.5	145.5	158.7		145.5	158.7
220.8	145.5	145.5	145.5	145.5	132.3	145.5	145.5	145.5	145.5	145.5
204.4	119.1	119.1	119.1	119.1	119.1	105.8	105.8	119.1	119.1	119.1
188	105.8	105.8	105.8	92.6	105.8	92.6	92.6	105.8	105.8	105.8
171.6	92.6	92.6	92.6	79.4	79.4	79.4	79.4	92.6	92.6	92.6
155.2	79.4	79.4	66.1	66.1	66.1	66.1	66.1	79.4	66.1	66.1
138.8	66.1	66.1	52.9	52.9	52.9	52.9	52.9	52.9	52.9	52.9
122.4	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	39.7	52.9
106	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	39.7	52.9
89.6	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	39.7	39.7
73.2	52.9	52.9	52.9	52.9	52.9	52.9	52.9	39.7	39.7	39.7

USt / 6.6 ft - ZD 640 -

Δ (ft)	82	98	115	131	148	164	180	197	213	230
160.1						137.8				
154.5	137.8	137.8	137.8	137.8	137.8	132.3	132.3	132.3		
149.3	132.3	132.3	132.3	132.3	132.3	132.3	132.3	132.3	137.8	132.3
132.9	110.2	121.3	121.3	121.3	110.2	110.2	110.2	110.2	110.2	110.2
116.5	99.2	110.2	110.2	110.2	99.2	99.2	99.2	99.2	99.2	99.2
100.1	99.2	110.2	110.2	110.2	99.2	99.2	99.2	99.2	88.2	88.2
83.7	99.2	110.2	110.2	110.2	99.2	99.2	99.2	99.2	88.2	88.2
67.3	99.2	110.2	110.2	110.2	99.2	99.2	99.2	99.2	88.2	88.2

USt / 6.6 ft - ZX 640 -

Δ (ft)	82	98	115	131	148	164	180	197	213	230
237.2	165.4	165.4	165.4	165.4						
231.6	154.3	154.3	154.3	154.3	154.3	154.3	154.3	154.3		
220.8	143.3	143.3	143.3	143.3	143.3	143.3	143.3	143.3	154.3	154.3
204.4	121.3	121.3	121.3	121.3	121.3	121.3	121.3	121.3	132.3	132.3
188	110.2	110.2	110.2	110.2	110.2	99.2	99.2	99.2	110.2	110.2
171.6	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2	88.2
155.2	77.2	77.2	77.2	66.1	77.2	66.1	66.1	66.1	77.2	77.2
138.8	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1	55.1
122.4	44.1	55.1	55.1	55.1	55.1	44.1	44.1	44.1	44.1	44.1
106	44.1	55.1	55.1	55.1	55.1	44.1	44.1	44.1	44.1	44.1
89.6	44.1	55.1	55.1	55.1	55.1	44.1	44.1	44.1	44.1	44.1
73.2	44.1	55.1	55.1	55.1	55.1	44.1	44.1	44.1	44.1	44.1

Load curves



(ft)			72	82	89	98	105	115	121	131	138	148	154	164	171	180	187	197	203	213	220	230	ft
MAX	13.2 USt	6.6 USt																					
230	10 → 74	136 - 148	13.2	11.8	10.9	9.7	9	8.1	7.6	6.9	6.6	6.6	6.4	5.8	5.5	5	4.7	4.3	4.1	3.8	3.6	3.3	USt
	10 → 75	137 - 148	13.2	11.9	10.9	9.7	9	8.1	7.6	6.9	6.6	6.6	6.4	5.9	5.7	5.3	5	4.6	4.3	4	3.8	3.5	USt P+
213	10 → 78	144 - 155	13.2	12.5	11.5	10.2	9.5	8.6	8.1	7.4	7	6.6	6.6	6.1	5.7	5.2	4.9	4.5	4.3	4	USt		
	10 → 78	144 - 155	13.2	12.5	11.5	10.2	9.5	8.6	8.1	7.4	7	6.6	6.6	6.2	6	5.5	5.2	4.8	4.6	4.3	4	USt P+	
197	10 → 82	152 - 164	13.2	13.2	12.2	10.9	10.1	9.2	8.6	7.9	7.4	6.9	6.6	6.5	6.1	5.6	5.3	4.9	USt				
	10 → 82	153 - 164	13.2	13.2	12.2	10.9	10.1	9.2	8.6	7.9	7.4	6.9	6.6	6.6	6.3	5.9	5.5	5.1	USt P+				
180	10 → 80	148 - 159	13.2	12.9	11.9	10.6	9.8	8.9	8.3	7.6	7.2	6.7	6.6	6.4	6.1	5.8	USt						
	10 → 80	148 - 159	13.2	12.9	11.9	10.6	9.8	8.9	8.3	7.6	7.2	6.7	6.6	6.4	6.1	5.8	USt P+						
164	10 → 81	149 - 161	13.2	13	11.9	10.6	9.9	8.9	8.4	7.7	7.3	6.7	6.6	6.4	USt								
	10 → 81	149 - 161	13.2	13	11.9	10.6	9.9	8.9	8.4	7.7	7.3	6.7	6.6	6.4	USt P+								
148	10 → 84		13.2	13.2	12.4	11	10.3	9.3	8.7	8	7.6	7	USt										
	10 → 84		13.2	13.2	12.4	11	10.3	9.3	8.7	8	7.6	7	USt P+										
131	10 → 84		13.2	13.2	12.4	11	10.2	9.2	8.6	7.9	USt												
	10 → 84		13.2	13.2	12.4	11	10.2	9.2	8.6	7.9	USt P+												
115	10 → 84		13.2	13.2	12.5	11.1	10.3	9.3	USt														
	10 → 84		13.2	13.2	12.5	11.1	10.3	9.3	USt P+														
98	10 → 84		13.2	13.2	12.5	11.1	USt																
	10 → 84		13.2	13.2	12.5	11.1	USt P+																
82	10 → 82		13.2	13.2	USt																		
	10 → 82		13.2	13.2	USt P+																		

$W_{crane} = W_{jib} - 0.72 \text{ USt max.}$




(ft)			72	82	89	98	105	115	121	131	138	148	154	164	171	180	187	197	203	213	220	230	ft
MAX	13.2 USt	6.6 USt																					
230	8 → 74	137 - 139	13.2	11.9	11	9.7	9.1	8.2	7.7	7	6.6	6.2	5.9	5.4	5	4.5	4.2	3.8	3.6	3.3	3.1	2.9	USt
	8 → 75	138 - 140	13.2	11.9	11	9.7	9	8.2	7.7	7	6.6	6.2	5.9	5.5	5.2	4.8	4.5	4.2	3.9	3.6	3.4	3.1	USt P+
213	8 → 78	145 - 148	13.2	12.6	11.6	10.3	9.6	8.7	8.1	7.4	7	6.6	6.3	5.7	5.3	4.8	4.5	4.1	3.9	3.6	USt		
	8 → 78	145 - 148	13.2	12.6	11.6	10.3	9.6	8.6	8.1	7.4	7	6.6	6.3	5.8	5.6	5.1	4.8	4.4	4.2	3.9	USt P+		
197	8 → 83	153 - 157	13.2	13.2	12.3	10.9	10.2	9.2	8.7	7.9	7.5	6.9	6.6	6.2	5.8	5.2	4.9	4.5	USt				
	8 → 83	154 - 157	13.2	13.2	12.3	11	10.2	9.2	8.7	7.9	7.5	6.9	6.6	6.3	6	5.5	5.2	4.8	USt P+				
180	8 → 81	150 - 152	13.2	13	11.9	10.6	9.9	8.9	8.4	7.7	7.3	6.7	6.5	6.1	5.8	5.4	USt						
	8 → 81	150 - 152	13.2	13	11.9	10.6	9.9	8.9	8.4	7.7	7.3	6.7	6.5	6.1	5.8	5.4	USt P+						
164	8 → 81	151 - 154	13.2	13.1	12	10.7	10	9	8.5	7.7	7.3	6.8	6.6	6.1	USt								
	8 → 81	151 - 154	13.2	13.1	12	10.7	10	9	8.5	7.7	7.3	6.8	6.6	6.1	USt P+								
148	8 → 84		13.2	13.2	12.5	11.1	10.3	9.4	8.8	8.1	7.6	7	USt										
	8 → 84		13.2	13.2	12.5	11.1	10.3	9.4	8.8	8.1	7.6	7	USt P+										
131	8 → 84		13.2	13.2	12.5	11.1	10.3	9.3	8.7	7.9	USt												
	8 → 84		13.2	13.2	12.5	11.1	10.3	9.3	8.7	7.9	USt P+												
115	8 → 85		13.2	13.2	12.5	11.1	10.4	9.4	USt														
	8 → 85		13.2	13.2	12.5	11.1	10.4	9.4	USt P+														
98	8 → 85		13.2	13.2	12.6	11.1	USt																
	8 → 85		13.2	13.2	12.6	11.1	USt P+																
82	8 → 82		13.2	13.2	USt																		
	8 → 82		13.2	13.2	USt P+																		

$W_{crane} = W_{jib} - 0.21 \text{ USt max.}$

Jib weight & counter-jib ballast













MAX	(lb) (+/- 5%)								
				10,141 lb	3,373 lb	(lb)	6,768 lb	3,373 lb	(lb)
230 ft	32,587	31,744	32,721	5	2	57,452	8	1	57,519
213 ft	31,916	31,140	32,117	5	2	57,452	8	1	57,519
197 ft	31,070	30,360	31,226	5	2	57,452	8	1	57,519
180 ft	29,211	28,501	29,368	5	0	50,706	7	1	50,750
164 ft	29,527	28,817	29,683	5	0	50,706	7	1	50,750
148 ft	27,902	27,192	28,058	4	2	47,311	7	0	47,377
131 ft	27,324	26,614	27,481	4	1	43,938	6	1	43,982
115 ft	25,536	24,826	25,693	4	0	40,565	6	0	40,609
98 ft	24,209	23,499	24,365	3	2	37,170	5	1	37,214
82 ft	22,192	21,482	22,348	3	1	33,797	5	0	33,841









Dimensions and weight

Slewing crane part:  230 ft -  -  50 LVF



Slewing crane part		L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Counter-jib		36.1 36.1	3.7 3.7	8.1 8.1	21,826 20,503
Cab mast + cab		16.1	7.3	8.2	13,228
Towerhead + Hoisting winch (+ rope)		17.3	8.3	9.2	21,054
Towerhead		9.7	8.1	8.2	13,228
Hoisting winch (+ rope)		14	7.5	7.6	9,921
Jib section		35.8	5.6	9	9,348
Jib section		33.8 33.5 33.6 33.4	3.9 3.9 3.9 3.9	7.9 7.8 6.9 6	5,335 3,439 2,723 1,753
Jib section		17.6 17.3 16.7 16.7	3.9 3.9 3.9 3.9	8 7.8 5 4.6	3,164 2,116 683 485
Trolley		6.1	5	3.4	882
Pulley block		3.9	1.4	7.6	1,003
Trolley		5.2	5	3.2	463
Trolley		5.6 6.1	5 5	3.4 3.2	540 520
Pulley block		5.4 3.6	0.7 0.9	5.8 5.3	992 584


Crane tower			L (ft)	W (ft)	H (ft)	lb (+/- 5%)
Telescopic cage T 61		□ 6.6 ft	35.5	13.6	14.7	21,385
K 649B KM 649E KRM 6410B		□ 6.6 ft	33.6 33.8 33.6	6.8 6.7 6.9	6.7 6.7 6.8	11,663 10,692 15,653
KR 649A KRMT 649A K 649A KMT 649A		□ 6.6 ft	17.2 17.2 17.2 17.2	6.9 6.9 6.8 6.8	6.8 6.8 6.7 6.7	7,165 6,724 6,184 5,666
KRMT 649C		□ 6.6 ft	11.7	6.9	6.8	5,401
Fixing angles		P 63A / P 800B	2.5	2.5	4.2	1,025
Basic mast unit		V 60A V 63A	16.4 32.9	7.9 7.9	7.9 7.9	10,494 16,887
Struts		V 60A V 63A	14.8 14.8	1 1.1	1 1.1	1,036 1,235
Half-bearer		V 60A V 63A	22 22	2.3 2.3	7.6 7.6	4,057 4,101
Cross girder		ZD 640	22.2	1	4.7	7,055
1/2 Cross girder		ZD 640	10.8	1.9	4.7	2,976
Cross girder		ZX 640	30	3.9	5.1	15,168
1/2 Cross girder		ZX 640	14.3	3.3	5.1	7,319

Mechanisms

480 V - 60 Hz											hp	kW			
	50 LVF 30 Optima	fpm	105	131	172	221	54	69	90	110	50	37	1,106 ft		
		USt	6.6	5	3.3	1.7	13.2	9.9	6.6	3.5					
	90 HPL™ 30	fpm	176	228	326	469	723	90	120	172	244	361	90	66	2,772 ft
		USt	6.6	5	3.3	1.7	0.2	13.2	9.9	6.6	3.3	0.9			
	6 DVF 4 Optima	fpm	0 → 164 (13.2 USt) 0 → 328 (6.6 USt) 0 → 394 (3.3 USt)								5.5	4			
	RVF 162 Optima+	rpm					0 → 0.9				2 x 7.5	2 x 5.5			

480 V (+6% -10%) 60 Hz	50 LVF: 58 → 38 kVA 90 HPL™: 90 → 54 kVA	

50 LVF 30 Optima



These mast combinations meet the EN 14439 and ASME B30.3-2016 specifications for “out of service” wind conditions, provided the illustrated wind speed matches required design wind speed for the location of the tower crane. The “out of service” design wind speed was determined in accordance with ASCE 7-10, Figure 26.5-1A. The wind velocity, used for this configuration was 98 mph (158 kph), which represents a nominal design 3-second wind gust at 33 ft (10 m) above ground for Exposure B category. A factor of 0.85 was applied to the 700-year ultimate design wind speed of 115 mph (185 kph), per ASCE 37-02, with the assumption that this crane is considered a temporary structure used during a construction period of 2 years or less.

- Jib elevation
- Standard equipment
- Options
- Total ballast weight
- Jib weight
- Lorry 44 ft
- Potain Plus function: Plus load curves
- Container High Cube 40 ft, and/or Flat Rack 20 ft
- Travelling
- Hook heights with Plus load curves
- Required power
- Power Control Function: winch speeds adapted to the available power
- Reactions in service
- Consult us
- Reactions out of service
- Hoisting
- Slewing
- Trolleying

This commercial document is not legally binding. For any technical information, please refer to the corresponding instructions.

