

Liftcrane Mast Handling Capacities

Operating Limits for Crane Assembly - Gantry Up Crawler with 60 in. Treads Drum 2 only


HANDLING CAPACITIES: Handling capacities are for crane self-assembly using live mast. Weight of block, slings, hoist lines, etc., beneath live mast sheaves is considered part of load. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate on firm, level and uniformly supporting surface. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.

MACHINE EQUIPMENT: Machine equipped with 10 ft 3 in. gantry in up position, 30 ft live mast and 20 part boom hoist reeving.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line. Mast angle in degrees (°) is angle between horizontal and centerline of mast measured from transport position, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

30.0 ft Mast			
Operating Radius	Mast Angle	Crane on Jacks	Crane on Crawlers
Feet	Degrees	Pounds	Pounds
8	99.0		60,000
9.5	102.0	60,000	60,000
10	102.8	60,000	60,000
12	106.8	60,000	60,000
14	110.8	60,000 </td <td>60,000</td>	60,000
16	115.0		60,000
18	119.3		60,000
20	123.8		60,000
22	128.5		60,000
24	133.5		60,000
26	139.1		60,000
28	145.3		60,000
29	148.8		60,000



Operating Restrictions on Jacks (four jacks, no crawlers)

9.5 ft to 14 ft operating radius —
25 degree swing either side of center permitted for handling loads. Refer to swing diagram.

9.5 ft to 29 ft operating radius —
360 degree swing permitted for handling hooks and chains.

Greater than 29 ft operating radius —
Block installation only - drum operation not permitted (mast lacing interference).

Operating Restrictions on Jacks with One Crawler

Installed (two jacks with one crawler installed and on ground)

9.5 ft to 14 ft operating radius —
25 degree swing either side of center permitted for handling loads. Refer to swing diagram.

9.5 ft to 29 ft operating radius —
360 degree swing permitted for handling hooks and chains.

Operating Restrictions on Crawlers

8 ft to 29 ft operating radius —
360 degree swing permitted for handling loads.

Greater than 29 ft operating radius —
Block installation only - drum operation not permitted (mast lacing interference).