




POTAIN®

Igo M 24-19

EN 14439:2025 C25-D25
EN 14439:2025 C50-D50




Courbes de charges / Lastkurven / Load curves / Curvas de cargas / Curve di carico
Curvas de carga / Кривые нагрузок



1

[illegible]

2


[illegible]

1

24 m		2,7 ▶		11,8	12	13	14	15	16	17	18	19	20	21	22	23	23,7	m
				1200	1180	1070	980	900	830	770	710	670	620	590	550	520	500	kg
21 m		2,7 ▶			12,6	13	14	15	16	17	18	19	20	20,8	m			
					1200	1160	1060	980	900	840	780	730	680	650	kg			

2

24 m	2,7	▶	10,1	11	12	13	14	15	16	17	18	19	20	21	22	23	23,7	m
																		kg
			1200	1080	970	880	800	730	670	620	580	540	500	470	440	420	400	
21 m	2,7	▶		11,2	12	13	14	15	16	17	18	19	20	20,8	m			
																		ka
				1200	1100	1000	910	830	770	710	660	620	580	550				



1

24 m	2,7	▶	17,5	18	19	20	21	22	22,8	m
			700	680	630	590	560	520	500	kg

21 m	2,7	▶	18,8	19	20	m
			700	690	650	kg


2

24 m		2,7 ▶	14,8	15	16	17	18	19	20	21	22	22,8	m
			700	690	640	590	550	510	480	450	420	400	kg
21 m		2,7 ▶			16,5	17	18	19	20				m
					700	680	630	590	550				kg

230 V - 50 Hz 400 V - 50 Hz 480 V - 60 Hz							ch - PS hp	kW				
	8 LVF 9 Optima	230 V  20 A	m/min	 1,5		 5	 19,5	 13	 39	3,3	2,4	
			kg	1800		1800		700				
		230 V  32 A	m/min	 1,5		 9	 19,5	 22	 39	5,2	3,8	
			kg	1800		1800		700				
		400 V 480 V	m/min	 1,5		 18	 19,5	 36,5	 39	7,5	5,5	
			kg	1800		1800		700				
	1 DVF 4 Optima	m/min	7		28		31		36		1,5	1,1
		kg	1800		1800		1000		850			
	RVF 20	tr/min U/min rpm	0 → 1							1,5	1,1	


 IEC 60204-32	 kVA
230 V (+10% -10%) 50 Hz 400 V (+10% -10%) 50 Hz 480 V (+6% -10%) 60Hz	230 V 20 A : 4,6 kVA 230 V 32 A : 7,4 kVA 400 V / 480 V : 8 → 5 kVA 



Montage / Montage / Erection / Montaje / Montaggio
Montagem / Монтаж



Transport / Transport / Transport / Transporte / Trasporto
Transporte / Транспортировка

40' Open Top





	km/h	(kg)	R (m)	B (m)	C (m)	D (m)	E (m)	H (m)	I1	I2	P (kg)	P1 (kg)	P2 (kg)
T11A/J136	25	4820	2,5	9,81	3,24	0,43	0,65 / 0,87	3,47	2,15	2,46	12390	11850	540
	25	4820	2	9,81	3,24	0,43	0,65 / 0,87	3,47	2,15	2,46	12390	11580	810
	25	4820	2,75	9,81	3,24	0,43	0,65 / 0,87	3,47	2,5	2,46	12390	11850	540
	25	4820	2,35	9,81	3,24	0,43	0,65 / 0,87	3,47	2,5	2,46	12390	11620	770
T11A/J136 ABE / TÜV	25	4820	2,75	9,92	3,13	0,43	0,65 / 0,87	3,47	2,5	2,46	12390	11730	660
	25	4820	2,35	9,92	3,13	0,43	0,65 / 0,87	3,47	2,5	2,46	12390	11500	890
T11A/J127 (EBS) RCE / WVTA	80	4820	2,5	9,98	3,07	0,49	0,71 / 0,93	3,53	2,15	2,53	12790	12080	710
	80	4820	2	9,98	3,07	0,49	0,71 / 0,93	3,53	2,15	2,53	12790	11820	970
	80	4820	2,75	9,98	3,07	0,49	0,71 / 0,93	3,53	2,5	2,53	12790	12080	710
	80	4820	2,35	9,98	3,07	0,49	0,71 / 0,93	3,53	2,5	2,53	12790	11860	930
T11A/J127 ABE / TÜV	80	4180	2,5	9,88	3,18	0,49	0,71 / 0,93	3,53	2,15	2,53	11950	11210	740
SL011A/J127 (EBS) RCE / WVTA	80	4820	2,5	6,75	3,07	0,49	1,26	3,53	2,15	2,53	12840	11730	1110
	80	4820	2	6,75	3,07	0,49	1,26	3,53	2,15	2,53	12840	11340	1500
	80	4820	2,75	6,75	3,07	0,49	1,26	3,53	2,5	2,53	12840	11730	1110
	80	4820	2,35	6,75	3,07	0,49	1,26	3,53	2,5	2,53	12840	11400	1440

	FR	DE	EN	ES	IT	PT	RU
R	Rayon de giration	Schwenk radius	Rear slewing radius	Radio de giro	Raggio di rotazione	Raio de rotação	Задний габарит
F_{max}	Réaction maximale sur appuis	Maximale Reaktionskraft auf den Abstützungen	Maximum corner load	Reacción máxima sobre apoyos	Reazione massima su staffa	Reacção máxima sobre apoios	Макс. воздействие на опору
	Poids à vide, sans lest, sans trains de transport, avec flèche maxi. et hauteur standard	Gewicht ohne Last, ohne Ballast, ohne Transportachsen, mit max. Auslager und Standardhöhe	Weight without load, without ballast, without transport axes, with max. jib and standard height	Peso en vacío, sin lastre, sin trenes de transporte con flecha y altura estándar	Peso a vuoto, senza zavorra, senza assali di trasporto, con braccio max e altezza standard	Peso em vazio, sem lastro, sem eixos de transporte com lança máxima e altura standard	Вес без груза, без балласта, без осей для транспортировки, с максимальным вылетом стрелы и стандартной высотой
	Poids total du lest	Ballast-Gesamtgewicht	Total ballast weight	Peso total del lastre	Peso totale della zavorra	Peso total do lastro	Общий вес балласта
	Trains de transport	Transportachsen	Transport axes	Trenes de transporte	Assali di trasporto	Eixos de transporte	Оси для транспортировки
	Fonction Potain Plus : Courbes de charges Plus	Funktion Potain Plus: Plus-Lastkurven	Potain Plus function: Plus load curves	Función Potain Plus: Diagrama de cargas Plus	Funzione Potain Plus: Curve di carico Plus	Função Potain Plus: Diagrama de cargas Plus	Функция контроля мощности Potain Plus: Диаграммы грузоподъемности Plus
	Équipements standards	Standardausrüstungen	Standard equipment	Equipamiento de serie	Equipaggiamento standard	Equipamento de série	Стандартное оборудование
	Équipements optionnels	Sonderausrüstungen	Options	Equipamiento opcional	Equipaggiamento in opzione	Equipamento opcional	Дополнительное оборудование (опция)
	Levage	Heben	Hoisting	Elevación	Sollevamento	Elevação	Подъем
	Distribution	Katzfahren	Trolleying	Distribución	Distribuzione	Distribuição	Перемещение по стреле
	Orientation	Schwenken	Slewing	Orientación	Rotazione	Rotação	Поворот
	50 Hz Monophasé	50 Hz Einphasige	50 Hz Single phase	50 Hz Monofasica	50 Hz Monofase	50 Hz monofásica	Однофазное напряжение 50Hz
	Puissance requise	Erforderliche Leistung	Required power	Potencia Necesaria	Potenza richiesta	Potência Necessária	Потребляемая мощность
	Transport grue toute lestée	Krantransport mit voller Ballastierung	Transport of crane with full ballast	Transporte grúa completamente lastrada	Trasporto con gru completamente zavorrata	Transporte de grua totalmente balastrada	Перевозка крана с полным балластом
	Fonction Power Control : vitesses treuils adaptées à la puissance disponible	Funktion Power Control: Geschwindigkeiten der Triebwerke werden an die verfügbare Leistung angepasst	Power Control Function: winch speeds adapted to the available power	Función Power Control: marchas de los cabrestantes adaptadas a la potencia disponible	Funzione Power Control: velocità degli argani adattate alla potenza disponibile	Função Power Control: velocidades de guincho adaptadas à potência disponível	Функция контроля мощности Power Control: регулировка скорости лебедок в зависимости от доступной мощности
	Hauteurs sous crochet données moufle plaquée	Hakenhöhen werden mit plattiertem Haken angegeben	Hook heights given with plated pulley block	Altura bajo gancho con pasteca bloqueada	Altezza sotto gancio con bozzello in contatto con carrello	Altura ao gancho com o cadernal em contacto com o carrinho	высота под крюком дана при условии, что крюковая подвеска соприкасается с кареткой
	Document commercial non contractuel	Unverbindliches Vertriebsdokument	This commercial document is not legally binding	Documento comercial no contractual	Documento commerciale non vincolante	Documento comercial não contratual	Этот коммерческий документ не является юридически обязательным
	Pour toute information technique se référer à la notice correspondante	Für technische Informationen, siehe die entsprechenden Anweisungen	For any technical information, please refer to the corresponding instructions	Para cualquier información técnica, ver la noticia correspondiente	Per tutte le informazioni tecniche fare riferimento al catalogo istruzioni	Para qualquer informação técnica complementar consultar as respectivas instruções	Для получения технической информации, см. соответствующие инструкции

