



Manitowoc Cranes, Inc.
Manitowoc, Wisconsin 54220 U.S.A.

Maximum Allowable Travel Specifications

Model 11000 Main Boom
Model 11000 Fixed Jib

Jobsite Travel

11000 must be equipped with 75,000 lb (34 000 kg) crane counterweight.

1. Machine Travel With Load

- A. Travel with crane upperworks in-line with crawlers. Grade in any direction must not exceed 1 percent (0.5 degrees).
- B. Travel surface must be firm, level and uniformly supporting. Capacity charts are based on static conditions; therefore, judgment must be used to allow for dynamic effects of traveling with load. Carry load as close to ground as possible. Stabilize load with taglines. Travel slowly and smoothly to avoid shock loading boom, jib and rigging.

2. Machine Travel Without Load

- A. Load blocks and/or hook and weight balls may be suspended beneath lower boom point, upper boom point and jib point. Total combined suspended weight beneath lower and upper boom points must not exceed 3,500 lb (1 590 kg) or 2,800 lb (1 270 kg) on lower point when jib is attached. Total suspended weight beneath jib point must not exceed 700 lb (320 kg).
- B. Machine to travel on a firm and uniformly supporting surface with crane upperworks in-line with crawlers and travel drive to rear. Grade in direction of travel should not exceed 20 percent (11.3 degrees); side-to-side grade must not exceed 2 percent (1.1 degrees) measured at boom hinge pins.
- C. See tables on pages 2-3 for boom angle, boom length and direction for various grades. Adjust boom within boom angle range shown in tables on pages 2-3 with machine in a level position before traveling onto grade. Do not change boom angle after crane has traveled onto grade. Boom angle is angle between horizontal and centerline of boom butt and inserts. See table below for grade vs. angle when traveling.
- D. Do not exceed 2 percent (1.1 degrees) side-to-side grade at boom hinge pins when cutting (turning on grade). Travel with crane upperworks in-line with grade at all times.
- E. Boom lengths shown in tables on page 2 do not include jib. Boom lengths shown in tables on page 3 include all jib lengths and offset angles.
- F. **Warning:** Travel prohibited for boom lengths not shown in table on page 2 and page 3. *Crane could tip.*

Refer to capacity charts for maximum boom and jib length raising.

Percent Grade Vs. Angle In Degrees	
Percent Grade	Angle
10	5.7
20	11.3



11000

Manitowoc Cranes, Inc.
 Manitowoc, Wisconsin 54220 U.S.A.

Maximum Allowable Travel Specifications

Model 11000 Main Boom
 Model 11000 Fixed Jib

Machine Travel Without Load - Boom Facing Downhill		
0 -1% Percent Grade		
Boom Angle Range in Degrees	Boom Length	
	75,000 lb (34,000 kg) Crane Counterweight	
	Feet	Meters
30 - 40	80 - 100	24,4 - 30,5
35 - 55	110 - 170	33,5 - 51,8
50 - 70	180 - 200	54,9 - 61,0
60 - 75	210 - 230	64,0 - 70,1
2 -10% Percent Grade		
30 - 45	70 - 80	21,3 - 24,4
35 - 60	90 - 150	27,4 - 45,7
50 - 75	160 - 170	48,8 - 51,8
65 - 80	180 - 230	54,9 - 70,1
11 -20% Percent Grade		
35 - 50	60 - 70	18,3 - 21,3
45 - 70	80 - 140	24,4 - 42,7
60 - 80	150 - 170	45,7 - 51,8
70 - 80	180 - 230	54,9 - 70,1

Machine Travel Without Load - Boom Facing Uphill		
0 -1% Percent Grade		
Boom Angle Range in Degrees	Boom Length	
	75,000 lb (34,000 kg) Crane Counterweight	
	Feet	Meters
35 - 40	90 - 100	27,4 - 30,5
35 - 55	110 - 170	33,5 - 51,8
45 - 70	180 - 190	54,9 - 57,9
55 - 70	200 - 230	61,0 - 70,1
2 -10% Percent Grade		
30 - 35	70 - 80	21,3 - 24,4
35 - 45	90 - 150	27,4 - 45,7
40 - 55	160 - 170	48,8 - 51,8
50 - 65	180 - 230	54,9 - 70,1
11 -20% Percent Grade		
30 - 35	120	36,6
35 - 40	130 - 150	39,6 - 45,7
35 - 50	160 - 190	48,8 - 57,9
40 - 55	200 - 230	61,0 - 70,1



11000

Manitowoc Cranes, Inc.
 Manitowoc, Wisconsin 54220 U.S.A.

Maximum Allowable Travel Specifications

Model 11000 Main Boom
 Model 11000 Fixed Jib

Machine Travel Without Load - Boom Facing Downhill		
0 -1% Percent Grade		
Boom Angle Range in Degrees	Boom Length (Including all jib lengths and offset angles)	
	75,000 lb (34,000 kg) Crane Counterweight	
	Feet	Meters
30 - 45	90	27,4
30 - 55	100 - 120	30,5 - 36,6
40 - 65	130 - 140	39,6 - 42,7
50 - 70	150 - 160	45,7 - 48,8
60 - 70	170 - 190	51,8 - 57,9
65 - 70	200	61,0
2 -10% Percent Grade		
30 - 50	90 - 110	27,4 - 33,5
45 - 65	120 - 130	36,6 - 39,6
55 - 70	140 - 150	42,7 - 45,7
65 - 70	160 - 180	48,8 - 54,9
11 -20% Percent Grade		
30 - 65	90 - 100	27,4 - 30,5
50 - 70	110 - 120	33,5 - 36,6
65 - 70	130 - 150	39,6 - 45,7

Machine Travel Without Load - Boom Facing Uphill		
0 -1% Percent Grade		
Boom Angle Range in Degrees	Boom Length (Including all jib lengths and offset angles)	
	75,000 lb (34,000 kg) Crane Counterweight	
	Feet	Meters
30 - 45	90 - 100	27,4 - 30,5
30 - 60	110 - 130	33,5 - 39,6
45 - 65	140 - 150	42,7 - 45,7
55 - 70	160 - 170	48,8 - 51,8
60 - 70	180 - 190	54,9 - 57,9
65 - 70	200	61,0
2 -10% Percent Grade		
30 - 40	100 - 110	30,5 - 33,5
30 - 50	120 - 130	36,6 - 39,6
45 - 55	140 - 150	42,7 - 45,7
55 - 60	160 - 170	48,8 - 51,8
60 - 65	180 - 200	54,9 - 61,0
11 -20% Percent Grade		
30 - 40	130 - 140	39,6 - 42,7
40 - 50	150 - 160	45,7 - 48,8
50 - 55	170 - 190	51,8 - 57,9
55 - 60	200	61,0