

Wire Rope Specifications

Liftcrane - Boom No. 55-79A

32 mm Hoist Line

Wire Rope Lengths - Single Hoist Drum								
Boom Length		Whip Line Drum 2 or 3				Hoist Line Drum 1		
		1 Part		2 Part				
Ft.	Meters	Ft.	Meters	Ft.	Meters	Ft.	Meters	Parts of Line
120	36.6	300	91	425	130	2900	884	22
140	42.7	325	99	475	145	3400	1036	22
160	48.8	375	114	550	168	3500	1067	20
180	54.9	400	122	600	183	3600	1097	18
200	61.0	450	137	675	206	3600	1097	16
220	67.1	500	152	725	221	3600	1097	14
240	73.2	525	160	775	236	3700	1128	14
260	79.2	575	175	850	259	3700	1128	12
280	85.3	600	183	900	274	3700	1128	10
300	91.4	650	198	975	297	3700	1128	10
320	97.5	700	213	1025	312	3700	1128	10
340	103.6	725	221	1075	328	3700	1128	8
360	109.7	775	236	1150	351	3700	1128	8
380	115.8	800	244	1200	366	3700	1128	6
400	121.9	850	259	1275	389	3700	1128	6

Note: Hoist and whip line lengths will allow hook to touch ground. When block travel below ground is required, add additional rope equal to parts of line times added travel distance. Hoisting distance or line pull may be limited when block travel below ground is required.

Hoist Reeving for Main Load Block - Single Lead Line						
No. Parts of Line	2	4	6	8	10	12
Maximum Load - Lbs.	97,600	195,200	292,800	390,400	488,000	585,600
Maximum Load - kg	44 270	88 540	132 810	177 080	221 350	265 620
No. Parts of Line	14	16	18	20	22	
Maximum Load - Lbs.	683,200	773,600	861,900	948,400	1,000,000	
Maximum Load - kg	309 890	350 900	390 950	430 190	453 500	

Wire Rope Specifications

Liftcrane - Boom No. 55-79A

32 mm Hoist Line

Wire Rope Specifications	
<u>Rotation Resistant Wire Rope</u>	
Hoist Line:	
32 mm (Drum 1):	
Dyform 34MAX Wire Rope	
With Spelter Button and Pad Eye (MCC Part No. A06005)	
Right Hand Lang Lay	
Minimum Breaking Strength = 244,000 Lbs. (110 680 kg)	
Approx. Weight = 3.74 Lbs. Per Ft. (5.57 kg/m)	
No Load Dia. = 1.285 in. (32.64 mm) to 1.304 in. (33.12 mm)	
Whip Line:	
32 mm (Drum 2):	
Dyform 34MAX Wire Rope	
With Spelter Button and Pad Eye (MCC Part No. A06005)	
Right Hand Lang Lay	
Minimum Breaking Strength = 244,000 Lbs. (110 680 kg)	
Maximum Load = 48,800 Lbs. (22 140 kg) per line	
Approx. Weight = 3.74 Lbs. Per Ft. (5.57 kg/m)	
No Load Dia. = 1.285 in. (32.64 mm) to 1.304 in. (33.12 mm)	
28 mm (Drum 3):	
Dyform 34MAX Wire Rope With Pad Eye (MCC Part No. 719425)	
Right Hand Lang Lay	
Minimum Breaking Strength = 179,400 Lbs. (81 370 kg)	
Maximum Load = 30,000 Lbs. (13 610 kg) per line	
Approx. Weight = 2.76 Lbs. Per Ft. (4.11 kg/m)	
No Load Dia. = 1.124 in. (28.55 mm) to 1.146 in. (29.11 mm)	

Maximum Spooling Capacities	
Drum 1: (Hoist Line)	32 mm Wire Rope - 9 Layers - 3,330 Ft. (1 015m)
Drum 2: (Whip Line)	32 mm Wire Rope - 9 Layers - 3,330 Ft. (1 015m)
Drum 3: (Whip Line)	28 mm Wire Rope - 8 Layers - 1,900 Ft. (579m)
23 Ft. (7m) is deducted from maximum spooling capacities for 3 dead wraps per drum.	

Refer to Drum and Lagging chart **No. 8512-A** and Load Block Reeving folio **No. 2032**.