



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds (all Jib Lengths) 10 m/s
--

LIFTING CAPACITIES: Chart supplements boom capacity chart No. 8017-AM. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and are calculated to comply with EN 13000, ISO 4305 and include factors based on a 4.0 degree tipping angle. Capacities based on structural competence are denoted by an asterisk (*). Capacities indicated by (b) require 2 010 kg minimum block weight with 4 part hoist line reeving on 12.2m jib and 3 part on 18.3m jib.

76.2m thru 91.4m boom lengths require only the middle 3 sheaves to be used on the lower boom point. All other sheaves must be removed from the lower boom point.

Weight of all load blocks, hooks, weight ball, slings, etc., beneath boom and jib point sheaves, is considered part of jib load. Reeved hoist line included in jib weight. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging No. 179809, jib assembly No. 192352, Wire Rope Specification chart No. 8030-A, and Counterweight Arrangement chart No. 8026-A. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

WIND CONDITIONS: Machine may be operated in winds stated in Maximum Operating Wind Speed table provided crane operator judgment is used to allow for wind effect on lifted load and other considerations noted on capacity chart are followed. Wind will have a considerable effect on load with a large "sail area" and must be compensated for accordingly by reducing load ratings, reducing operating speeds or by a combination of both. Wind speed to be measured at boom point elevation. **Operation is not permitted when wind is above conditions stated in Maximum Operating Wind Speed table.** Park crane (upper inline with crawlers) with load block on ground or secured and position boom at 70 degrees. Lower boom onto blocking at ground level when wind is above 22 m/s.

MACHINE TRAVEL: Machine to travel on a firm, level, and uniformly supporting surface and boom within boom angle range shown in capacity chart. *Travel with 100 percent of rated load prohibited.* Travel restricted to 90 percent of rated capacity with speed not to exceed 0.4 m/s. Refer to Maximum Allowable Travel Specification chart No. 8998-A.

MAX PERMISSIBLE SLEWING SPEED: Slewing operation with working load shall not exceed 0.4 m/s as measured at the operating radius. The amount of time to brake or start slewing a working load shall not be less than 2.5 seconds.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

JIB POINT ELEVATION: Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with 9 373 mm crawlers, 1 219 mm treads, 8 534 mm retractable gantry, 12 part boom hoist reeving, boom support straps, 94 890 kg crane counterweight and two 13 610 kg carbody counterweights.

Maximum capacity on 29 mm wire rope is 13 610 kg per line.

Boom Catwalks Deduct
Deduct 300 kg from capacities when boom catwalks are attached.



Liftcrane Jib Capacities

2250 SERIES 2

**Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating**

**Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s**

Maximum Boom and Jib Lengths Lifted Unassisted					
Over Front of Crawlers		Over Rear of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 132	Boom Length	Jib No. 132	Boom Length	Jib No. 132
(a)(b)(e) 91.4m	—	(a) 91.4m	—	(a)(b)(e) 91.4m	—
(a) 88.4m	—	88.4m	—	(a) 88.4m	—
85.3m	—	85.3m	—	85.3m	—
82.3m	—	82.3m	—	82.3m	—
79.2m	(d) 24.4m	79.2m	24.4m	79.2m	(b)(d) 24.4m
79.2m	(d) 18.3m	76.2m	(e) 36.6m	79.2m	(d) 18.3m
76.2m	(d)(e) 36.6m	73.2m	36.6m	79.2m	(d) 12.2m
76.2m	(d) 30.5m			76.2m	(d) 30.5m
76.2m	(b) 24.4m			76.2m	(d) 24.4m
73.2m	(d)(e) 36.6m			73.2m	(d)(e) 36.6m
73.2m	(d) 30.5m			73.2m	(d) 30.5m
70.1m	(b) 36.6m			73.2m	(b) 24.4m
67.1m	36.6m			70.1m	(d) 36.6m
				67.1m	36.6m

Load block, hook and weight ball on ground at start.
 (a) Upper boom point and third line sheave assembly on boom top must be removed.
 (b) Machine must be equipped with optional upperworks jacking cylinders.
 (c) Boom *must* be rigged with one hoist lead line.
 (d) Raising reserve is less than 10% tip weight.
 (e) When equipped with boom catwalks, length cannot be raised.



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
12.2	80.5	53.9	45 300 *b							12.2
14.0	78.4	53.5	42 300 *b							14.0
16.0	76.2	53.0	39 800 *b	78.6	52.7	32 900 *b				16.0
18.0	73.9	52.4	37 600 *b	76.3	52.1	31 600 *b	78.7	51.3	25 300 *	18.0
20.0	71.6	51.7	35 700 *b	74.0	51.4	30 300 *	76.3	50.6	24 200 *	20.0
22.0	69.2	50.9	33 900 *b	71.6	50.6	29 200 *	73.9	49.8	23 200 *	22.0
24.0	66.9	50.1	32 400 *b	69.2	49.7	28 200 *	71.5	48.9	22 300 *	24.0
26.0	64.4	49.1	31 100 *b	66.7	48.7	27 300 *	69.0	47.9	21 400 *	26.0
28.0	61.9	48.0	29 800 *	64.2	47.6	26 500 *	66.4	46.8	20 700 *	28.0
30.0	59.4	46.8	28 700 *	61.7	46.4	25 800 *	63.8	45.6	20 000 *	30.0
32.0	56.8	45.5	27 700 *	59.0	45.1	25 100 *	61.1	44.2	19 400 *	32.0
34.0	54.1	44.0	26 700 *	56.3	43.6	24 500 *	58.3	42.7	18 800 *	34.0
36.0	51.3	42.4	25 600 *	53.5	42.0	24 000 *	55.4	41.0	18 300 *	36.0
38.0	48.3	40.6	23 600 *	50.5	40.2	23 500 *	52.4	39.2	17 800 *	38.0
40.0	45.2	38.6	21 800 *	47.4	38.2	22 400 *	49.2	37.1	17 300 *	40.0
44.0	38.5	33.9	18 700 *	40.5	33.3	19 100 *				44.0
48.0	30.4	27.7	16 200 *							48.0
42.7m (140 Ft.) BOOM										
12.2	81.0	57.0	45 300 *b							12.2
14.0	79.1	56.6	43 100 *b							14.0
16.0	77.0	56.2	40 600 *b	79.2	55.8	33 300 *b				16.0
18.0	74.8	55.6	38 400 *b	77.1	55.3	32 000 *b	79.3	54.5	25 600 *	18.0
20.0	72.6	55.0	36 500 *b	74.9	54.6	30 800 *b	77.1	53.8	24 500 *	20.0
22.0	70.4	54.2	34 800 *b	72.7	53.9	29 700 *	74.9	53.1	23 500 *	22.0
24.0	68.2	53.4	33 200 *b	70.4	53.1	28 700 *	72.6	52.3	22 600 *	24.0
26.0	65.9	52.5	31 900 *b	68.1	52.1	27 800 *	70.3	51.3	21 800 *	26.0
28.0	63.6	51.5	30 600 *b	65.8	51.1	27 000 *	67.9	50.3	21 100 *	28.0
30.0	61.3	50.4	29 500 *	63.4	50.0	26 200 *	65.5	49.2	20 400 *	30.0
32.0	58.9	49.1	28 400 *	61.0	48.8	25 600 *	63.0	47.9	19 800 *	32.0
34.0	56.4	47.8	27 400 *	58.5	47.4	25 000 *	60.4	46.5	19 200 *	34.0
36.0	53.8	46.3	25 300 *	55.9	45.9	24 400 *	57.8	45.0	18 700 *	36.0
38.0	51.1	44.7	23 200 *	53.2	44.3	23 700 *	55.1	43.3	18 200 *	38.0
40.0	48.4	42.9	21 400 *	50.4	42.5	21 900 *	52.2	41.5	17 700 *	40.0
44.0	42.4	38.7	18 300 *	44.4	38.2	18 700 *	46.0	37.1	17 000 *	44.0
48.0	35.6	33.5	15 800 *	37.5	32.9	16 100 *				48.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
13.7	79.9	59.8	44 200 *b							13.7
14.0	79.7	59.8	43 800 *b							14.0
16.0	77.7	59.3	41 400 *b	79.8	59.0	33 700 *b				16.0
18.0	75.6	58.8	39 200 *b	77.8	58.4	32 400 *b				18.0
20.0	73.6	58.2	37 300 *b	75.7	57.8	31 200 *b	77.8	57.1	24 800 *	20.0
22.0	71.5	57.5	35 600 *b	73.6	57.1	30 200 *	75.7	56.3	23 900 *	22.0
24.0	69.4	56.7	34 100 *b	71.5	56.4	29 200 *	73.6	55.6	23 000 *	24.0
26.0	67.3	55.9	32 700 *b	69.4	55.5	28 300 *	71.4	54.7	22 200 *	26.0
28.0	65.1	54.9	31 400 *b	67.2	54.5	27 500 *	69.2	53.7	21 500 *	28.0
30.0	62.9	53.9	30 300 *	65.0	53.5	26 700 *	66.9	52.7	20 800 *	30.0
32.0	60.7	52.7	29 200 *	62.7	52.4	26 000 *	64.6	51.5	20 200 *	32.0
34.0	58.4	51.5	27 300	60.4	51.1	25 400 *	62.3	50.2	19 600 *	34.0
36.0	56.0	50.1	24 900	58.0	49.7	24 900 *	59.8	48.8	19 100 *	36.0
38.0	53.5	48.6	22 800	55.5	48.2	23 400	57.3	47.3	18 600 *	38.0
40.0	51.0	47.0	21 000	53.0	46.6	21 600	54.7	45.6	18 100 *	40.0
44.0	45.7	43.2	17 900	47.6	42.8	18 400	49.2	41.7	17 300 *	44.0
48.0	39.7	38.7	15 300	41.5	38.1	15 700				48.0
52.0	32.8	32.9	13 200	34.5	32.3	13 600				52.0
48.8m (160 Ft.) BOOM										
13.7	80.4	62.9	44 900 *b							13.7
14.0	80.2	62.9	44 500 *b							14.0
16.0	78.3	62.4	42 100 *b							16.0
18.0	76.4	61.9	40 000 *b	78.4	61.6	32 800 *b				18.0
20.0	74.4	61.4	38 100 *b	76.4	61.0	31 600 *b	78.5	60.2	25 200 *	20.0
22.0	72.5	60.7	36 300 *b	74.5	60.4	30 600 *b	76.5	59.6	24 200 *	22.0
24.0	70.5	60.0	34 800 *b	72.5	59.6	29 600 *	74.5	58.8	23 400 *	24.0
26.0	68.5	59.2	33 400 *b	70.5	58.8	28 800 *	72.4	58.0	22 600 *	26.0
28.0	66.4	58.3	32 200 *b	68.4	57.9	27 900 *	70.3	57.1	21 800 *	28.0
30.0	64.4	57.3	31 000 *b	66.3	56.9	27 200 *	68.2	56.1	21 200 *	30.0
32.0	62.3	56.2	29 400	64.2	55.9	26 500 *	66.1	55.0	20 600 *	32.0
34.0	60.1	55.1	26 800	62.0	54.7	25 900 *	63.9	53.8	20 000 *	34.0
36.0	57.9	53.8	24 400	59.8	53.4	25 000	61.6	52.5	19 500 *	36.0
38.0	55.7	52.4	22 400	57.5	52.0	23 100	59.3	51.1	19 000 *	38.0
40.0	53.3	50.9	20 500	55.2	50.5	21 200	56.9	49.6	18 500 *	40.0
44.0	48.4	47.5	17 400	50.3	47.1	18 000	51.8	46.0	17 700 *	44.0
48.0	43.1	43.4	14 900	44.9	42.9	15 300	46.3	41.8	15 800	48.0
52.0	37.2	38.4	12 800	38.8	37.9	13 100				52.0
56.0	30.2	32.1	11 000							56.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
13.7	80.9	66.0	45 300 *b							13.7
14.0	80.6	66.0	45 000 *b							14.0
16.0	78.8	65.6	42 800 *b							16.0
18.0	77.0	65.1	40 600 *b	79.0	64.7	33 100 *b				18.0
20.0	75.2	64.5	38 800 *b	77.1	64.2	32 000 *b	79.1	63.4	25 500 *	20.0
22.0	73.3	63.9	37 000 *b	75.2	63.6	31 000 *b	77.2	62.8	24 600 *	22.0
24.0	71.4	63.2	35 500 *b	73.4	62.9	30 000 *	75.3	62.1	23 700 *	24.0
26.0	69.6	62.5	34 100 *b	71.5	62.1	29 200 *	73.3	61.3	22 900 *	26.0
28.0	67.6	61.6	32 900 *b	69.5	61.3	28 300 *	71.4	60.4	22 200 *	28.0
30.0	65.7	60.7	31 700 *b	67.6	60.3	27 600 *	69.4	59.5	21 500 *	30.0
32.0	63.7	59.7	29 200 b	65.6	59.3	26 900 *	67.3	58.5	21 000 *	32.0
34.0	61.7	58.6	26 500	63.5	58.2	26 300 *	65.3	57.4	20 400 *	34.0
36.0	59.6	57.4	24 200	61.4	57.0	25 100	63.2	56.1	19 800 *	36.0
38.0	57.5	56.1	22 100	59.3	55.7	22 800	61.0	54.8	19 300 *	38.0
40.0	55.3	54.7	20 300	57.1	54.3	21 000	58.8	53.4	18 800 *	40.0
44.0	50.8	51.6	17 200	52.6	51.1	17 800	54.1	50.1	18 000 *	44.0
48.0	46.0	47.9	14 600	47.7	47.4	15 100	49.1	46.3	15 600	48.0
52.0	40.7	43.4	12 500	42.3	42.9	13 000				52.0
56.0	34.7	38.0	10 800	36.3	37.4	11 100				56.0
60.0	27.6	31.0	9 200							60.0
54.9m (180 Ft.) BOOM										
15.2	80.0	68.8	44 300 *b							15.2
16.0	79.3	68.7	43 400 *b							16.0
18.0	77.6	68.2	41 300 *b	79.5	67.9	33 500 *b				18.0
20.0	75.9	67.7	39 500 *b	77.7	67.4	32 400 *b	79.6	66.6	25 700 *	20.0
22.0	74.1	67.1	37 800 *b	75.9	66.8	31 400 *b	77.8	66.0	24 800 *	22.0
24.0	72.3	66.5	36 200 *b	74.1	66.1	30 400 *	76.0	65.3	24 000 *	24.0
26.0	70.5	65.7	34 900 *b	72.3	65.4	29 500 *	74.1	64.6	23 200 *	26.0
28.0	68.7	64.9	33 600 *b	70.5	64.6	28 800 *	72.3	63.8	22 500 *	28.0
30.0	66.9	64.1	31 800 b	68.6	63.7	28 000 *	70.4	62.9	21 900 *	30.0
32.0	65.0	63.1	28 800 b	66.8	62.8	27 300 *	68.5	61.9	21 300 *	32.0
34.0	63.1	62.1	26 100 b	64.8	61.7	26 600	66.5	60.8	20 700 *	34.0
36.0	61.1	61.0	23 800	62.9	60.6	24 700	64.6	59.7	20 200 *	36.0
38.0	59.2	59.8	21 700	60.9	59.4	22 500	62.5	58.5	19 700 *	38.0
40.0	57.1	58.5	19 900	58.9	58.1	20 600	60.5	57.1	19 200 *	40.0
44.0	52.9	55.5	16 700	54.6	55.1	17 400	56.2	54.1	17 900	44.0
48.0	48.5	52.1	14 200	50.1	51.6	14 700	51.6	50.6	15 300	48.0
52.0	43.7	48.1	12 100	45.3	47.6	12 600	46.6	46.4	13 000	52.0
56.0	38.4	43.3	10 300	39.9	42.7	10 700				56.0
60.0	32.3	37.3	8 800	33.8	36.7	9 100				60.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
15.2	80.4	71.9	44 900 *b							15.2
16.0	79.8	71.8	44 000 *b							16.0
18.0	78.2	71.4	41 900 *b	79.9	71.0	33 800 *b				18.0
20.0	76.5	70.9	40 100 *b	78.3	70.5	32 700 *b	80.0	69.7	25 900 *	20.0
22.0	74.8	70.3	38 400 *b	76.6	69.9	31 700 *b	78.3	69.1	25 100 *	22.0
24.0	73.1	69.7	36 900 *b	74.9	69.3	30 800 *	76.6	68.5	24 300 *	24.0
26.0	71.4	69.0	35 500 *b	73.1	68.6	29 900 *	74.9	67.8	23 500 *	26.0
28.0	69.7	68.2	34 100 b	71.4	67.9	29 100 *	73.1	67.0	22 800 *	28.0
30.0	67.9	67.4	31 500 b	69.6	67.0	28 400 *	71.3	66.2	22 200 *	30.0
32.0	66.1	66.5	28 400 b	67.8	66.1	27 700 *	69.5	65.3	21 600 *	32.0
34.0	64.3	65.5	25 700 b	66.0	65.2	26 800	67.7	64.3	21 000 *	34.0
36.0	62.5	64.5	23 400	64.2	64.1	24 200	65.8	63.2	20 500 *	36.0
38.0	60.6	63.3	21 300	62.3	62.9	22 100	63.9	62.0	20 000 *	38.0
40.0	58.7	62.1	19 500	60.4	61.7	20 200	61.9	60.8	19 500 *	40.0
44.0	54.8	59.4	16 400	56.4	58.9	17 000	57.9	58.0	17 700	44.0
48.0	50.7	56.2	13 800	52.3	55.7	14 400	53.7	54.7	14 900	48.0
52.0	46.3	52.5	11 700	47.8	52.0	12 200	49.1	50.9	12 700	52.0
56.0	41.5	48.1	9 900	43.0	47.6	10 300	44.2	46.4	10 700	56.0
60.0	36.2	42.9	8 400	37.6	42.3	8 800				60.0
64.0	30.0	36.5	7 100	31.3	35.8	7 400				64.0
61.0m (200 Ft.) BOOM										
15.2	80.8	75.0	45 300 *b							15.2
16.0	80.2	74.9	44 500 *b							16.0
18.0	78.7	74.5	42 600 *b							18.0
20.0	77.1	74.0	40 700 *b	78.8	73.7	33 000 *b	80.5	72.8	26 100 *	20.0
22.0	75.5	73.5	39 100 *b	77.1	73.1	32 000 *b	78.8	72.3	25 400 *	22.0
24.0	73.8	72.9	37 500 *b	75.5	72.5	31 100 *b	77.2	71.7	24 500 *	24.0
26.0	72.2	72.2	36 100 b	73.9	71.9	30 300 *	75.5	71.0	23 800 *	26.0
28.0	70.5	71.5	33 900 b	72.2	71.1	29 500 *	73.8	70.3	23 100 *	28.0
30.0	68.9	70.7	30 700 b	70.5	70.3	28 800 *	72.1	69.5	22 500 *	30.0
32.0	67.2	69.9	28 000 b	68.8	69.5	28 000 *	70.4	68.6	21 900 *	32.0
34.0	65.5	68.9	25 300 b	67.1	68.6	26 400	68.7	67.7	21 300 *	34.0
36.0	63.7	67.9	23 000	65.4	67.5	23 900	66.9	66.7	20 800 *	36.0
38.0	62.0	66.9	20 900	63.6	66.5	21 700	65.1	65.6	20 300 *	38.0
40.0	60.2	65.7	19 000	61.8	65.3	19 800	63.3	64.4	19 800 *	40.0
44.0	56.5	63.1	15 900	58.1	62.7	16 600	59.5	61.7	17 300	44.0
48.0	52.6	60.1	13 400	54.2	59.7	14 000	55.5	58.7	14 600	48.0
52.0	48.5	56.7	11 200	50.0	56.2	11 800	51.3	55.2	12 300	52.0
56.0	44.1	52.7	9 500	45.6	52.2	9 900	46.8	51.1	10 400	56.0
60.0	39.4	48.1	7 900	40.8	47.5	8 400				60.0
64.0	34.0	42.4	6 600	35.4	41.8	7 000				64.0
										68.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
16.8	80.1	77.9	40 800 *b							16.8
18.0	79.1	77.6	40 800 *b							18.0
20.0	77.6	77.1	40 700 *b	79.2	76.8	33 300 *b				20.0
22.0	76.0	76.6	39 700 *b	77.7	76.3	32 300 *b	79.3	75.5	25 600 *	22.0
24.0	74.5	76.1	38 100 *b	76.1	75.7	31 400 *b	77.7	74.9	24 800 *	24.0
26.0	72.9	75.4	36 500 b	74.5	75.1	30 600 *	76.1	74.2	24 000 *	26.0
28.0	71.4	74.8	33 100 b	73.0	74.4	29 800 *	74.5	73.5	23 400 *	28.0
30.0	69.8	74.0	30 100 b	71.4	73.6	29 100 *	72.9	72.8	22 800 *	30.0
32.0	68.1	73.2	27 500 b	69.7	72.8	28 400 *	71.3	72.0	22 200 *	32.0
34.0	66.5	72.3	25 000 b	68.1	71.9	26 100	69.6	71.1	21 600 *	34.0
36.0	64.9	71.3	22 700 b	66.4	71.0	23 600	67.9	70.1	21 100 *	36.0
38.0	63.2	70.3	20 600	64.7	69.9	21 500	66.2	69.0	20 600 *	38.0
40.0	61.5	69.2	18 800	63.0	68.8	19 600	64.5	67.9	20 100	40.0
44.0	58.0	66.8	15 700	59.5	66.4	16 400	60.9	65.4	17 100	44.0
48.0	54.4	64.0	13 100	55.9	63.6	13 800	57.2	62.6	14 400	48.0
52.0	50.5	60.8	11 000	52.0	60.3	11 600	53.3	59.3	12 100	52.0
56.0	46.5	57.1	9 200	47.9	56.6	9 700	49.1	55.5	10 200	56.0
60.0	42.1	52.8	7 600	43.5	52.3	8 100	44.6	51.1	8 500	60.0
64.0	37.3	47.8	6 300	38.7	47.2	6 700				64.0
68.0	31.9	41.8	5 200	33.2	41.1	5 500				68.0
67.1m (220 Ft.) BOOM										
16.8	80.4	81.0	40 800 *b							16.8
18.0	79.5	80.7	40 800 *b							18.0
20.0	78.1	80.3	40 800 *b	79.6	79.9	33 600 *b				20.0
22.0	76.6	79.8	40 400 *b	78.2	79.4	32 600 *b	79.7	78.6	25 700 *	22.0
24.0	75.1	79.2	38 700 *b	76.7	78.9	31 800 *b	78.2	78.1	25 000 *	24.0
26.0	73.6	78.6	35 600 b	75.2	78.3	30 900 *b	76.7	77.4	24 300 *	26.0
28.0	72.1	78.0	32 300 b	73.6	77.6	30 200 *	75.2	76.8	23 600 *	28.0
30.0	70.6	77.3	29 400 b	72.1	76.9	29 400 *	73.6	76.0	23 000 *	30.0
32.0	69.0	76.5	26 800 b	70.6	76.1	27 900	72.0	75.2	22 400 *	32.0
34.0	67.5	75.6	24 500 b	69.0	75.3	25 500	70.5	74.4	21 900 *	34.0
36.0	65.9	74.7	22 300 b	67.4	74.3	23 300	68.9	73.5	21 400 *	36.0
38.0	64.3	73.8	20 200 b	65.8	73.4	21 100	67.2	72.5	20 900 *	38.0
40.0	62.7	72.7	18 400	64.2	72.3	19 300	65.6	71.4	20 200	40.0
44.0	59.4	70.4	15 200	60.8	70.0	16 000	62.2	69.0	16 800	44.0
48.0	55.9	67.8	12 700	57.4	67.3	13 400	58.7	66.3	14 100	48.0
52.0	52.3	64.7	10 500	53.8	64.3	11 200	55.0	63.3	11 800	52.0
56.0	48.6	61.3	8 700	50.0	60.8	9 300	51.1	59.7	9 800	56.0
60.0	44.5	57.4	7 200	45.9	56.9	7 700	47.0	55.7	8 200	60.0
64.0	40.2	52.8	5 900	41.5	52.3	6 300				64.0
68.0	35.4	47.4	4 700	36.6	46.8	5 100				68.0
72.0	29.9	40.9	3 800							72.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
16.8	80.8	84.1	40 800 *b							16.8
18.0	79.9	83.8	40 800 *b							18.0
20.0	78.5	83.4	40 800 *b	80.0	83.0	33 800 *b				20.0
22.0	77.1	82.9	40 500 *b	78.6	82.6	32 900 *b	80.1	81.7	25 900*	22.0
24.0	75.7	82.4	38 500 b	77.2	82.0	32 000 *b	78.7	81.2	25 300*	24.0
26.0	74.2	81.8	34 800 b	75.7	81.5	31 200 *b	77.2	80.6	24 500*	26.0
28.0	72.8	81.2	31 500 b	74.3	80.8	30 500*	75.7	80.0	23 900*	28.0
30.0	71.3	80.5	28 600 b	72.8	80.1	29 500	74.3	79.3	23 300*	30.0
32.0	69.8	79.8	26 100 b	71.3	79.4	27 200	72.8	78.5	22 700*	32.0
34.0	68.4	79.0	23 800 b	69.8	78.6	24 900	71.2	77.7	22 100*	34.0
36.0	66.8	78.1	21 800 b	68.3	77.7	22 800	69.7	76.8	21 700*	36.0
38.0	65.3	77.2	19 800 b	66.8	76.8	20 800	68.2	75.9	21 200*	38.0
40.0	63.8	76.2	18 000 b	65.2	75.8	18 900	66.6	74.9	19 800	40.0
44.0	60.6	74.0	14 800	62.0	73.5	15 700	63.4	72.6	16 500	44.0
48.0	57.4	71.4	12 300	58.8	71.0	13 000	60.0	70.1	13 800	48.0
52.0	54.0	68.6	10 100	55.4	68.2	10 800	56.6	67.2	11 500	52.0
56.0	50.4	65.4	8 300	51.8	64.9	8 900	53.0	63.9	9 500	56.0
60.0	46.7	61.7	6 800	48.0	61.2	7 400	49.1	60.1	7 800	60.0
64.0	42.7	57.5	5 500	44.0	57.0	5 900	45.0	55.8	6 400	64.0
68.0	38.3	52.7	4 300	39.6	52.1	4 700				68.0
72.0	33.5	46.9	3 300	34.7	46.2	3 700				72.0
76.0	27.9	39.9	2 500							76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
73.2m (240 Ft.) BOOM										
18.3	80.1	86.9	40 800 *b							18.3
20.0	78.9	86.5	40 800 *b	80.4	86.2	34 100 *b				20.0
22.0	77.6	86.1	40 500 b	79.0	85.7	33 200 *b	80.5	84.9	26 100 *	22.0
24.0	76.2	85.6	37 900 b	77.6	85.2	32 300 *b	79.1	84.4	25 500 *	24.0
26.0	74.8	85.0	33 900 b	76.2	84.6	31 500 *b	77.7	83.8	24 800 *	26.0
28.0	73.4	84.4	30 700 b	74.8	84.0	30 800 *b	76.3	83.2	24 100 *	28.0
30.0	72.0	83.7	27 900 b	73.4	83.4	29 200	74.8	82.5	23 500 *	30.0
32.0	70.6	83.0	25 400 b	72.0	82.6	26 500	73.4	81.8	22 900 *	32.0
34.0	69.2	82.2	23 100 b	70.6	81.9	24 200	72.0	81.0	22 400 *	34.0
36.0	67.7	81.4	21 100 b	69.1	81.0	22 100	70.5	80.2	21 900 *	36.0
38.0	66.3	80.5	19 300 b	67.7	80.1	20 300	69.0	79.2	21 200	38.0
40.0	64.8	79.6	17 600 b	66.2	79.2	18 500	67.5	78.3	19 500	40.0
44.0	61.8	77.5	14 400	63.2	77.1	15 300	64.4	76.1	16 200	44.0
48.0	58.7	75.1	11 800	60.0	74.7	12 600	61.3	73.7	13 400	48.0
52.0	55.5	72.4	9 700	56.8	71.9	10 400	58.0	71.0	11 100	52.0
56.0	52.1	69.3	7 900	53.4	68.9	8 600	54.6	67.9	9 200	56.0
60.0	48.6	65.9	6 400	49.9	65.4	6 900	51.0	64.3	7 500	60.0
64.0	44.9	62.0	5 000	46.1	61.5	5 600	47.2	60.3	6 000	64.0
68.0	40.9	57.5	3 900	42.1	57.0	4 300				68.0
72.0	36.5	52.4	2 900	37.7	51.7	3 300				72.0
76.0	31.6	46.2	2 000	32.7	45.5	2 300				76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
18.3	80.4	90.0	40 800 *b							18.3
20.0	79.3	89.6	40 800 *b	80.7	89.3	34 300 *b				20.0
22.0	78.0	89.2	40 400 b	79.4	88.8	33 400 *b				22.0
24.0	76.7	88.7	37 700 b	78.1	88.3	32 600 *b	79.5	87.5	25 600 *	24.0
26.0	75.3	88.2	33 800 b	76.7	87.8	31 800 *b	78.1	87.0	25 000 *	26.0
28.0	74.0	87.6	30 600 b	75.4	87.2	31 000 b	76.8	86.4	24 300 *	28.0
30.0	72.6	87.0	27 800 b	74.0	86.6	29 200	75.4	85.7	23 700 *	30.0
32.0	71.3	86.3	25 400 b	72.7	85.9	26 500	74.0	85.0	23 200 *	32.0
34.0	69.9	85.5	23 100 b	71.3	85.1	24 200	72.6	84.3	22 600 *	34.0
36.0	68.5	84.7	21 200 b	69.9	84.3	22 200	71.2	83.5	22 200 *	36.0
38.0	67.1	83.9	19 400 b	68.5	83.5	20 400	69.8	82.6	21 300	38.0
40.0	65.7	83.0	17 700 b	67.1	82.6	18 700	68.4	81.7	19 600	40.0
44.0	62.8	80.9	14 600	64.2	80.5	15 500	65.4	79.6	16 400	44.0
48.0	59.9	78.7	12 100	61.2	78.2	12 900	62.4	77.3	13 700	48.0
52.0	56.8	76.1	9 900	58.1	75.7	10 700	59.3	74.7	11 400	52.0
56.0	53.6	73.2	8 100	54.9	72.8	8 800	56.1	71.7	9 400	56.0
60.0	50.3	70.0	6 500	51.6	69.5	7 200	52.7	68.4	7 800	60.0
64.0	46.8	66.3	5 300	48.1	65.8	5 800	49.1	64.7	6 300	64.0
68.0	43.1	62.2	4 100	44.3	61.6	4 600	45.3	60.4	5 100	68.0
72.0	39.1	57.4	3 100	40.3	56.9	3 500				72.0
76.0	34.8	51.9	2 200	35.9	51.3	2 600				76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

12.2m (40 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
79.2m (260 Ft.) BOOM										
18.3	80.8	93.1	40 800 *b							18.3
20.0	79.7	92.7	40 800 *b							20.0
22.0	78.4	92.3	40 000 b	79.8	92.0	33 600 *b				22.0
24.0	77.1	91.9	36 800 b	78.5	91.5	32 800 *b	79.8	90.6	25 800 *	24.0
26.0	75.8	91.3	33 000 b	77.2	91.0	32 100 *b	78.5	90.1	25 200 *	26.0
28.0	74.5	90.8	29 900 b	75.9	90.4	31 000 b	77.2	89.6	24 500 *	28.0
30.0	73.2	90.2	27 100 b	74.6	89.8	28 400	75.9	88.9	24 000 *	30.0
32.0	71.9	89.5	24 600 b	73.3	89.1	25 800	74.6	88.3	23 400 *	32.0
34.0	70.6	88.8	22 500 b	71.9	88.4	23 600	73.2	87.5	22 900 *	34.0
36.0	69.3	88.0	20 500 b	70.6	87.6	21 600	71.9	86.7	22 300	36.0
38.0	67.9	87.2	18 700 b	69.2	86.8	19 700	70.5	85.9	20 800	38.0
40.0	66.6	86.3	17 100 b	67.9	85.9	18 100	69.1	85.0	19 100	40.0
44.0	63.8	84.4	14 200 b	65.1	84.0	15 200	66.3	83.1	16 100	44.0
48.0	61.0	82.2	11 700	62.3	81.8	12 500	63.4	80.8	13 300	48.0
52.0	58.1	79.8	9 500	59.3	79.3	10 300	60.5	78.4	11 000	52.0
56.0	55.0	77.0	7 700	56.3	76.6	8 400	57.4	75.6	9 100	56.0
60.0	51.9	74.0	6 100	53.1	73.5	6 800	54.2	72.4	7 400	60.0
64.0	48.6	70.5	4 800	49.8	70.0	5 400	50.8	68.9	5 900	64.0
68.0	45.2	66.6	3 600	46.3	66.1	4 200	47.3	64.9	4 700	68.0
72.0	41.5	62.3	2 600	42.6	61.7	3 100				72.0
76.0				38.6	56.6	2 200				76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
15.2	79.8	59.4	32 800 *b							15.2
16.0	79.0	59.2	32 500 *b							16.0
18.0	77.0	58.7	31 600 *							18.0
20.0	75.0	58.1	30 800 *	78.1	57.5	26 400 *				20.0
22.0	72.9	57.4	30 000 *	76.0	56.8	25 900 *	79.2	55.7	18 000 *	22.0
24.0	70.8	56.6	29 300 *	73.9	56.1	25 400 *	77.1	54.9	17 200 *	24.0
26.0	68.6	55.8	28 600 *	71.8	55.2	25 000 *	74.9	54.0	16 600 *	26.0
28.0	66.5	54.8	28 000 *	69.6	54.2	24 500 *	72.6	53.0	15 900 *	28.0
30.0	64.3	53.8	27 400 *	67.3	53.2	23 600 *	70.3	51.9	15 300 *	30.0
32.0	62.0	52.6	26 900 *	65.0	52.0	22 700 *	68.0	50.8	14 800 *	32.0
34.0	59.7	51.4	26 400 *	62.7	50.8	21 800 *	65.6	49.5	14 300 *	34.0
36.0	57.3	50.0	25 900 *	60.3	49.4	20 900 *	63.1	48.0	13 900 *	36.0
38.0	54.9	48.5	24 500	57.8	47.9	20 100 *	60.5	46.5	13 400 *	38.0
40.0	52.4	46.9	22 600	55.3	46.2	19 400 *	57.9	44.8	13 100 *	40.0
44.0	47.0	43.1	19 500	49.8	42.4	18 100 *	52.2	40.8	12 500 *	44.0
48.0	41.0	38.5	16 900	43.7	37.7	17 000 *				48.0
52.0	34.1	32.8	14 700	36.6	31.7	15 100				52.0
42.7m (140 Ft.) BOOM										
15.2	80.3	62.5	33 100 *b							15.2
16.0	79.6	62.4	32 700 *b							16.0
18.0	77.7	61.9	31 900 *							18.0
20.0	75.7	61.3	31 100 *	78.7	60.7	26 500 *				20.0
22.0	73.8	60.6	30 300 *	76.8	60.1	26 000 *	79.8	58.9	18 200 *	22.0
24.0	71.8	59.9	29 600 *	74.8	59.3	25 600 *	77.8	58.1	17 500 *	24.0
26.0	69.8	59.1	29 000 *	72.7	58.5	25 200 *	75.7	57.3	16 800 *	26.0
28.0	67.7	58.2	28 300 *	70.7	57.6	24 700 *	73.6	56.4	16 200 *	28.0
30.0	65.7	57.2	27 800 *	68.6	56.6	24 200 *	71.4	55.4	15 600 *	30.0
32.0	63.6	56.2	27 300 *	66.4	55.5	23 200 *	69.3	54.3	15 100 *	32.0
34.0	61.4	55.0	26 700 *	64.3	54.4	22 400 *	67.0	53.1	14 600 *	34.0
36.0	59.2	53.7	25 900	62.0	53.1	21 500 *	64.7	51.7	14 100 *	36.0
38.0	56.9	52.3	24 100	59.7	51.7	20 700 *	62.4	50.3	13 700 *	38.0
40.0	54.6	50.8	22 200	57.4	50.1	20 000 *	59.9	48.7	13 400 *	40.0
44.0	49.7	47.4	19 000	52.4	46.7	18 600 *	54.8	45.1	12 700 *	44.0
48.0	44.3	43.3	16 500	47.0	42.5	17 000	49.1	40.8	12 200 *	48.0
52.0	38.4	38.3	14 300	40.8	37.3	14 700				52.0
56.0	31.4	31.9	12 500							56.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
15.2	80.8	65.6	33 200 * ^b							15.2
16.0	80.1	65.5	32 900 * ^b							16.0
18.0	78.3	65.0	32 100 *							18.0
20.0	76.4	64.5	31 400 *	79.3	63.9	26 500 *				20.0
22.0	74.6	63.8	30 600 *	77.4	63.3	26 200 *	80.3	62.1	18 400 *	22.0
24.0	72.7	63.2	29 900 *	75.5	62.6	25 700 *	78.4	61.4	17 700 *	24.0
26.0	70.8	62.4	29 200 *	73.6	61.8	25 300 *	76.4	60.6	17 000 *	26.0
28.0	68.9	61.5	28 700 *	71.7	60.9	24 900 *	74.5	59.7	16 400 *	28.0
30.0	66.9	60.6	28 100 *	69.7	60.0	24 500 *	72.4	58.8	15 800 *	30.0
32.0	64.9	59.6	27 600 *	67.7	59.0	23 700 *	70.4	57.7	15 300 *	32.0
34.0	62.9	58.5	27 100 *	65.6	57.9	22 900 *	68.3	56.6	14 800 *	34.0
36.0	60.8	57.3	26 000	63.6	56.7	22 100 *	66.1	55.3	14 400 *	36.0
38.0	58.7	56.0	23 700	61.4	55.4	21 300 *	64.0	54.0	14 000 *	38.0
40.0	56.6	54.6	21 800	59.2	54.0	20 500 *	61.7	52.6	13 600 *	40.0
44.0	52.0	51.5	18 700	54.6	50.8	19 200 *	57.0	49.2	12 900 *	44.0
48.0	47.2	47.8	16 100	49.7	47.0	16 700	51.9	45.3	12 400 *	48.0
52.0	41.9	43.3	13 900	44.3	42.4	14 400				52.0
56.0	35.9	37.8	12 100	38.1	36.8	12 500				56.0
48.8m (160 Ft.) BOOM										
16.8	79.9	68.4	32 800 * ^b							16.8
18.0	78.8	68.1	32 400 *							18.0
20.0	77.0	67.6	31 600 *	79.8	67.0	26 600 *				20.0
22.0	75.3	67.0	30 900 *	78.0	66.4	26 400 *				22.0
24.0	73.5	66.4	30 200 *	76.2	65.8	25 900 *	79.0	64.6	17 900 *	24.0
26.0	71.7	65.7	29 600 *	74.4	65.1	25 500 *	77.1	63.8	17 200 *	26.0
28.0	69.9	64.9	29 000 *	72.6	64.2	25 100 *	75.2	63.0	16 600 *	28.0
30.0	68.0	64.0	28 400 *	70.7	63.4	24 800 *	73.3	62.1	16 000 *	30.0
32.0	66.1	63.0	27 800 *	68.8	62.4	24 200 *	71.4	61.1	15 500 *	32.0
34.0	64.2	62.0	27 300	66.9	61.4	23 400 *	69.4	60.1	15 000 *	34.0
36.0	62.3	60.9	25 500	64.9	60.2	22 600 *	67.4	58.9	14 600 *	36.0
38.0	60.3	59.7	23 300	62.9	59.0	21 800 *	65.4	57.6	14 200 *	38.0
40.0	58.3	58.4	21 400	60.9	57.7	21 100 *	63.3	56.3	13 900 *	40.0
44.0	54.1	55.4	18 300	56.6	54.7	19 000	58.9	53.2	13 200 *	44.0
48.0	49.6	52.0	15 700	52.1	51.2	16 300	54.2	49.6	12 600 *	48.0
52.0	44.8	48.0	13 500	47.2	47.1	14 100	49.1	45.4	12 200 *	52.0
56.0	39.5	43.1	11 700	41.7	42.2	12 100				56.0
60.0	33.4	37.2	10 100							60.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
16.8	80.3	71.5	33 100 *b							16.8
18.0	79.3	71.3	32 600 *b							18.0
20.0	77.6	70.8	31 800 *	80.3	70.2	26 500*				20.0
22.0	75.9	70.2	31 200 *	78.6	69.6	26 400*				22.0
24.0	74.2	69.6	30 500 *	76.8	69.0	26 100*	79.5	67.8	18 000*	24.0
26.0	72.5	68.9	29 900 *	75.1	68.3	25 700*	77.7	67.1	17 400*	26.0
28.0	70.8	68.1	29 200 *	73.4	67.5	25 300*	75.9	66.3	16 800*	28.0
30.0	69.0	67.3	28 800 *	71.6	66.7	24 900*	74.1	65.4	16 300*	30.0
32.0	67.3	66.4	28 200 *	69.8	65.8	24 600*	72.3	64.5	15 700*	32.0
34.0	65.5	65.4	27 500	68.0	64.8	23 900*	70.4	63.5	15 300*	34.0
36.0	63.6	64.4	25 200	66.1	63.7	23 100*	68.5	62.4	14 800*	36.0
38.0	61.8	63.2	23 000	64.2	62.6	22 300*	66.6	61.2	14 400*	38.0
40.0	59.8	62.0	21 200	62.3	61.3	21 600	64.6	59.9	14 000*	40.0
44.0	55.9	59.3	18 000	58.3	58.5	18 800	60.5	57.1	13 400*	44.0
48.0	51.8	56.1	15 400	54.1	55.3	16 100	56.2	53.8	12 800*	48.0
52.0	47.3	52.4	13 300	49.6	51.5	13 900	51.6	49.9	12 400*	52.0
56.0	42.5	48.0	11 400	44.7	47.1	12 000	46.5	45.3	12 000*	56.0
60.0	37.2	42.8	9 900	39.3	41.8	10 300				60.0
64.0	31.0	36.3	8 500							64.0
54.9m (180 Ft.) BOOM										
16.8	80.7	74.7	33 200 *b							16.8
18.0	79.7	74.4	32 800 *b							18.0
20.0	78.1	73.9	32 000 *	80.7	73.3	26 500*				20.0
22.0	76.5	73.4	31 400 *	79.1	72.8	26 500*				22.0
24.0	74.9	72.8	30 700 *	77.4	72.2	26 200*	79.9	70.9	18 200*	24.0
26.0	73.3	72.1	30 100 *	75.8	71.5	25 800*	78.3	70.3	17 600*	26.0
28.0	71.6	71.4	29 500 *	74.1	70.8	25 400*	76.6	69.5	17 000*	28.0
30.0	70.0	70.6	29 000 *	72.4	70.0	25 100*	74.8	68.7	16 500*	30.0
32.0	68.3	69.8	28 500 *	70.7	69.1	24 800*	73.1	67.8	16 000*	32.0
34.0	66.6	68.8	27 300	69.0	68.2	24 300*	71.3	66.9	15 500*	34.0
36.0	64.8	67.8	24 800	67.2	67.2	23 500*	69.5	65.8	15 000*	36.0
38.0	63.0	66.8	22 600	65.4	66.1	22 800*	67.7	64.7	14 600*	38.0
40.0	61.2	65.6	20 800	63.6	64.9	21 800	65.9	63.5	14 300*	40.0
44.0	57.5	63.0	17 600	59.9	62.3	18 500	62.0	60.8	13 600*	44.0
48.0	53.7	60.0	15 000	55.9	59.3	15 800	58.0	57.7	13 000*	48.0
52.0	49.6	56.6	12 800	51.8	55.8	13 500	53.7	54.2	12 500*	52.0
56.0	45.2	52.6	11 000	47.3	51.7	11 600	49.1	50.0	11 900	56.0
60.0	40.4	47.9	9 500	42.4	47.0	9 900				60.0
64.0	35.0	42.3	8 100	36.9	41.2	8 500				64.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
18.3	79.9	77.5	32 900 *b							18.3
20.0	78.6	77.1	32 300 *							20.0
22.0	77.1	76.5	31 600 *	79.5	75.9	26 500 *				22.0
24.0	75.5	76.0	31 000 *	77.9	75.4	26 300 *				24.0
26.0	74.0	75.3	30 400 *	76.4	74.7	25 900 *	78.8	73.5	17 700 *	26.0
28.0	72.4	74.7	29 800 *	74.8	74.0	25 600 *	77.1	72.8	17 200 *	28.0
30.0	70.8	73.9	29 300 *	73.2	73.3	25 200 *	75.5	72.0	16 600 *	30.0
32.0	69.2	73.1	28 800 *	71.5	72.4	24 900 *	73.8	71.1	16 100 *	32.0
34.0	67.6	72.2	26 900	69.9	71.6	24 600 *	72.2	70.2	15 700 *	34.0
36.0	65.9	71.3	24 400	68.2	70.6	24 000 *	70.5	69.2	15 200 *	36.0
38.0	64.2	70.2	22 300	66.5	69.6	23 200 *	68.7	68.2	14 800 *	38.0
40.0	62.5	69.1	20 400	64.8	68.4	21 400	67.0	67.1	14 400 *	40.0
44.0	59.0	66.7	17 200	61.3	66.0	18 200	63.4	64.5	13 800 *	44.0
48.0	55.4	63.9	14 600	57.6	63.1	15 400	59.6	61.6	13 200 *	48.0
52.0	51.5	60.7	12 500	53.7	59.9	13 200	55.6	58.3	12 700 *	52.0
56.0	47.5	57.0	10 600	49.6	56.1	11 300	51.3	54.4	11 600	56.0
60.0	43.1	52.7	9 100	45.1	51.8	9 600				60.0
64.0	38.3	47.7	7 700	40.2	46.7	8 200				64.0
68.0	32.9	41.6	6 500							68.0
61.0m (200 Ft.) BOOM										
18.3	80.3	80.6	33 100 *b							18.3
20.0	79.1	80.2	32 500 *b							20.0
22.0	77.6	79.7	31 800 *	79.9	79.1	26 500 *				22.0
24.0	76.1	79.2	31 200 *	78.4	78.5	26 400 *				24.0
26.0	74.6	78.6	30 600 *	76.9	77.9	26 100 *	79.2	76.6	17 900 *	26.0
28.0	73.1	77.9	30 000 *	75.4	77.3	25 700 *	77.7	76.0	17 300 *	28.0
30.0	71.6	77.2	29 500 *	73.8	76.5	25 400 *	76.1	75.2	16 800 *	30.0
32.0	70.0	76.4	28 700	72.3	75.7	25 100 *	74.5	74.4	16 300 *	32.0
34.0	68.5	75.5	26 300	70.7	74.9	24 700 *	72.9	73.6	15 800 *	34.0
36.0	66.9	74.6	24 000	69.1	74.0	24 400 *	71.3	72.6	15 400 *	36.0
38.0	65.3	73.7	21 900	67.5	73.0	23 000	69.7	71.6	15 000 *	38.0
40.0	63.7	72.6	20 000	65.9	71.9	21 100	68.0	70.5	14 700 *	40.0
44.0	60.4	70.3	16 800	62.5	69.6	17 800	64.6	68.1	14 000 *	44.0
48.0	56.9	67.6	14 200	59.0	66.9	15 100	61.0	65.4	13 400 *	48.0
52.0	53.3	64.6	12 100	55.4	63.9	12 800	57.3	62.3	12 900	52.0
56.0	49.5	61.2	10 200	51.6	60.4	10 900	53.3	58.7	11 300	56.0
60.0	45.5	57.2	8 600	47.5	56.4	9 300	49.1	54.6	9 600	60.0
64.0	41.1	52.7	7 300	43.0	51.7	7 800				64.0
68.0	36.3	47.3	6 100	38.1	46.2	6 600				68.0
72.0	30.8	40.7	5 100							72.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
18.3	80.7	83.7	33 200 * b							18.3
20.0	79.5	83.3	32 600 * b							20.0
22.0	78.1	82.8	32 000 *	80.3	82.2	26 400*				22.0
24.0	76.6	82.3	31 400 *	78.9	81.7	26 400*				24.0
26.0	75.2	81.7	30 900 *	77.4	81.1	26 100*	79.6	79.8	18 000*	26.0
28.0	73.7	81.1	30 300 *	76.0	80.5	25 900*	78.2	79.2	17 500*	28.0
30.0	72.3	80.4	29 800 *	74.5	79.8	25 500*	76.7	78.5	17 000*	30.0
32.0	70.8	79.7	28 100	73.0	79.0	25 200*	75.1	77.7	16 500*	32.0
34.0	69.3	78.9	25 800	71.5	78.2	24 900*	73.6	76.9	16 000*	34.0
36.0	67.8	78.0	23 700	70.0	77.3	24 500	72.1	76.0	15 600*	36.0
38.0	66.3	77.1	21 600	68.4	76.4	22 900	70.5	75.0	15 200*	38.0
40.0	64.7	76.1	19 800	66.9	75.4	20 900	68.9	74.0	14 800*	40.0
44.0	61.6	73.9	16 600	63.7	73.1	17 600	65.6	71.7	14 200*	44.0
48.0	58.3	71.3	14 000	60.4	70.6	14 900	62.3	69.1	13 600*	48.0
52.0	54.9	68.5	11 800	56.9	67.7	12 600	58.8	66.2	13 000	52.0
56.0	51.4	65.3	10 000	53.3	64.5	10 700	55.1	62.8	11 100	56.0
60.0	47.6	61.6	8 400	49.5	60.7	9 000	51.2	59.0	9 400	60.0
64.0	43.6	57.4	7 000	45.5	56.5	7 600	46.9	54.6	7 900	64.0
68.0	39.2	52.5	5 800	41.0	51.5	6 300				68.0
72.0	34.4	46.7	4 800	36.0	45.6	5 200				72.0
76.0	28.7	39.7	3 900							76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
19.8	80.0	86.5	32 900 *b							19.8
20.0	79.9	86.4	32 800 *b							20.0
22.0	78.5	86.0	32 200 *b							22.0
24.0	77.1	85.5	31 600 *	79.3	84.8	26 400 *				24.0
26.0	75.7	84.9	31 000 *	77.9	84.3	26 300 *	80.0	83.0	18 200 *	26.0
28.0	74.3	84.3	30 500 *	76.5	83.7	25 900 *	78.6	82.4	17 600 *	28.0
30.0	72.9	83.6	29 700	75.1	83.0	25 600 *	77.2	81.7	17 100 *	30.0
32.0	71.5	82.9	27 400	73.6	82.3	25 300 *	75.7	80.9	16 600 *	32.0
34.0	70.1	82.2	25 200	72.2	81.5	25 000 *	74.2	80.1	16 200 *	34.0
36.0	68.6	81.3	23 100	70.7	80.6	24 300	72.8	79.3	15 800 *	36.0
38.0	67.2	80.4	21 300	69.3	79.7	22 500	71.3	78.4	15 300 *	38.0
40.0	65.7	79.5	19 400	67.8	78.8	20 600	69.7	77.4	15 000 *	40.0
44.0	62.7	77.4	16 200	64.7	76.7	17 200	66.6	75.2	14 300 *	44.0
48.0	59.6	75.0	13 600	61.6	74.2	14 500	63.4	72.8	13 700 *	48.0
52.0	56.4	72.3	11 400	58.3	71.5	12 200	60.1	70.0	12 800	52.0
56.0	53.0	69.2	9 600	54.9	68.4	10 300	56.6	66.8	10 800	56.0
60.0	49.5	65.8	8 000	51.4	65.0	8 700	53.0	63.2	9 000	60.0
64.0	45.8	61.9	6 600	47.6	61.0	7 200	49.1	59.2	7 500	64.0
68.0	41.7	57.4	5 400	43.5	56.4	6 000				68.0
72.0	37.4	52.2	4 400	39.1	51.1	4 800				72.0
76.0	32.5	46.0	3 400							76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
19.8	80.3	89.6	33 100 *b							19.8
20.0	80.2	89.5	33 000 *b							20.0
22.0	78.9	89.1	32 400 *b							22.0
24.0	77.6	88.6	31 800 *	79.7	88.0	26 400*				24.0
26.0	76.2	88.1	31 300 *	78.3	87.4	26 400*	80.4	86.1	18 300*	26.0
28.0	74.9	87.5	30 700 *	77.0	86.8	26 000*	79.0	85.5	17 800*	28.0
30.0	73.5	86.9	29 400	75.6	86.2	25 700*	77.6	84.9	17 300*	30.0
32.0	72.2	86.2	26 800	74.2	85.5	25 400*	76.2	84.2	16 800*	32.0
34.0	70.8	85.4	24 500	72.8	84.8	25 100	74.8	83.4	16 300*	34.0
36.0	69.4	84.6	22 500	71.4	84.0	24 000	73.4	82.6	15 900*	36.0
38.0	68.0	83.8	20 700	70.0	83.1	21 900	72.0	81.7	15 500*	38.0
40.0	66.6	82.9	19 000	68.6	82.2	20 200	70.5	80.8	15 200*	40.0
44.0	63.7	80.8	15 800	65.7	80.1	16 900	67.6	78.7	14 500*	44.0
48.0	60.7	78.6	13 200	62.7	77.8	14 200	64.5	76.4	13 900*	48.0
52.0	57.7	76.0	11 000	59.6	75.2	11 900	61.3	73.7	12 500	52.0
56.0	54.5	73.1	9 200	56.4	72.3	10 000	58.1	70.7	10 500	56.0
60.0	51.2	69.9	7 600	53.0	69.0	8 400	54.6	67.4	8 700	60.0
64.0	47.7	66.2	6 200	49.5	65.3	6 900	51.0	63.6	7 200	64.0
68.0	44.0	62.1	5 000	45.7	61.1	5 600	47.1	59.2	5 900	68.0
72.0	40.0	57.3	4 000	41.6	56.3	4 500				72.0
76.0	35.6	51.8	3 100	37.2	50.6	3 500				76.0
80.0	30.6	45.2	2 300							80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
73.2m (240 Ft.) BOOM										
19.8	80.7	92.7	33 200 *b							19.8
20.0	80.5	92.7	33 100 *b							20.0
22.0	79.3	92.2	32 500 *b							22.0
24.0	78.0	91.8	32 000 *	80.0	91.1	26 300*				24.0
26.0	76.7	91.2	31 500 *	78.7	90.6	26 300*	80.7	89.3	18 400*	26.0
28.0	75.4	90.7	30 700	77.4	90.0	26 200*	79.4	88.7	17 900*	28.0
30.0	74.1	90.1	28 600	76.1	89.4	25 900*	78.1	88.1	17 400*	30.0
32.0	72.8	89.4	26 000	74.8	88.7	25 600*	76.7	87.4	16 900*	32.0
34.0	71.5	88.7	23 900	73.4	88.0	25 100	75.4	86.7	16 400*	34.0
36.0	70.1	87.9	21 800	72.1	87.2	23 200	74.0	85.9	16 100*	36.0
38.0	68.8	87.1	20 000	70.7	86.4	21 400	72.6	85.0	15 700*	38.0
40.0	67.4	86.2	18 400	69.4	85.5	19 600	71.2	84.1	15 300*	40.0
44.0	64.7	84.3	15 400	66.6	83.6	16 600	68.4	82.1	14 600*	44.0
48.0	61.8	82.1	12 800	63.7	81.4	13 800	65.5	79.9	14 100*	48.0
52.0	58.9	79.6	10 600	60.8	78.9	11 600	62.5	77.4	12 100	52.0
56.0	55.9	76.9	8 800	57.7	76.1	9 600	59.4	74.6	10 200	56.0
60.0	52.7	73.8	7 200	54.5	73.0	8 000	56.1	71.4	8 400	60.0
64.0	49.5	70.4	5 800	51.2	69.5	6 500	52.7	67.8	6 900	64.0
68.0	46.0	66.5	4 600	47.7	65.6	5 200	49.1	63.8	5 600	68.0
72.0	42.3	62.1	3 600	43.9	61.1	4 200				72.0
76.0	38.3	57.1	2 600	39.8	56.0	3 100				76.0
80.0				35.3	50.0	2 200				80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
19.8	81.0	95.8	27 200 * ^b							19.8
20.0	80.9	95.8	27 200 * ^b							20.0
22.0	79.6	95.3	27 200 * ^b							22.0
24.0	78.4	94.9	27 200 *							24.0
26.0	77.1	94.4	27 200 *	79.1	93.7	26 300 *				26.0
28.0	75.9	93.9	27 200 *	77.8	93.2	26 300 *	79.8	91.9	18 000 *	28.0
30.0	74.6	93.3	27 200 *	76.6	92.6	26 000 *	78.5	91.3	17 500 *	30.0
32.0	73.4	92.6	26 000	75.3	91.9	25 700 *	77.2	90.6	17 100 *	32.0
34.0	72.1	91.9	23 800	74.0	91.3	25 200	75.9	89.9	16 600 *	34.0
36.0	70.8	91.2	21 900	72.7	90.5	23 200	74.6	89.1	16 200 *	36.0
38.0	69.5	90.4	20 100	71.4	89.7	21 400	73.2	88.3	15 800 *	38.0
40.0	68.2	89.5	18 400	70.1	88.9	19 700	71.9	87.5	15 400 *	40.0
44.0	65.5	87.7	15 600	67.4	87.0	16 800	69.2	85.6	14 800 *	44.0
48.0	62.8	85.6	13 000	64.7	84.9	14 000	66.4	83.4	14 200 *	48.0
52.0	60.0	83.3	10 800	61.8	82.5	11 800	63.5	81.0	12 400	52.0
56.0	57.1	80.6	9 000	58.9	79.9	9 800	60.5	78.3	10 300	56.0
60.0	54.2	77.7	7 400	55.9	76.9	8 200	57.5	75.3	8 600	60.0
64.0	51.0	74.5	6 000	52.8	73.6	6 800	54.2	71.9	7 100	64.0
68.0	47.8	70.8	4 800	49.5	69.9	5 500	50.8	68.1	5 800	68.0
72.0	44.3	66.7	3 800	46.0	65.8	4 300	47.2	63.9	4 600	72.0
76.0	40.6	62.1	2 800	42.2	61.0	3 400				76.0
80.0	36.6	56.7	2 000	38.1	55.6	2 500				80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

18.3m (60 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
79.2m (260 Ft.) BOOM										
21.3	80.3	98.6	27 200 *b							21.3
22.0	79.9	98.5	27 200 *b							22.0
24.0	78.8	98.0	27 200 *							24.0
26.0	77.6	97.5	27 200 *	79.4	96.9	26 300*				26.0
28.0	76.3	97.0	27 200 *	78.2	96.4	26 300*	80.1	95.0	18 100*	28.0
30.0	75.1	96.4	27 200 *	77.0	95.8	26 100*	78.9	94.4	17 600*	30.0
32.0	73.9	95.8	25 300	75.8	95.2	25 800*	77.6	93.8	17 100*	32.0
34.0	72.7	95.2	23 100	74.5	94.5	24 700	76.4	93.1	16 700*	34.0
36.0	71.4	94.4	21 200	73.3	93.8	22 600	75.1	92.4	16 300*	36.0
38.0	70.2	93.7	19 400	72.0	93.0	20 800	73.8	91.6	15 900*	38.0
40.0	68.9	92.9	17 900	70.7	92.2	19 100	72.5	90.8	15 600*	40.0
44.0	66.4	91.1	15 000	68.2	90.4	16 200	69.9	88.9	14 900*	44.0
48.0	63.7	89.1	12 600	65.5	88.3	13 700	67.2	86.9	14 200	48.0
52.0	61.1	86.8	10 400	62.8	86.1	11 400	64.5	84.6	12 100	52.0
56.0	58.3	84.3	8 600	60.0	83.5	9 500	61.6	82.0	10 000	56.0
60.0	55.5	81.5	7 000	57.2	80.7	7 900	58.7	79.1	8 300	60.0
64.0	52.5	78.4	5 600	54.2	77.6	6 400	55.6	75.9	6 800	64.0
68.0	49.4	75.0	4 400	51.1	74.1	5 100	52.4	72.4	5 500	68.0
72.0	46.2	71.1	3 300	47.8	70.2	4 000	49.1	68.4	4 300	72.0
76.0	42.7	66.8	2 400	44.3	65.8	3 000				76.0
80.0				40.5	60.8	2 100				80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
16.8	80.2	65.3	23 300 *							16.8
18.0	79.0	65.0	22 900 *							18.0
20.0	77.2	64.4	22 300 *							20.0
22.0	75.3	63.8	21 700 *	79.2	63.1	19 700*				22.0
24.0	73.5	63.1	21 100 *	77.3	62.4	19 300*				24.0
26.0	71.6	62.4	20 600 *	75.4	61.7	18 900*	79.3	60.3	14 200*	26.0
28.0	69.6	61.5	20 100 *	73.4	60.8	18 500*	77.3	59.4	13 600*	28.0
30.0	67.7	60.6	19 700 *	71.5	59.9	18 100*	75.3	58.4	13 000*	30.0
32.0	65.7	59.6	19 200 *	69.5	58.9	17 800*	73.2	57.4	12 500*	32.0
34.0	63.7	58.5	18 800 *	67.4	57.8	17 400*	71.1	56.2	12 100*	34.0
36.0	61.6	57.3	18 400 *	65.3	56.6	17 100*	68.9	55.0	11 700*	36.0
38.0	59.5	56.0	18 000 *	63.2	55.2	16 800*	66.7	53.7	11 300*	38.0
40.0	57.3	54.6	17 700 *	61.0	53.8	16 100*	64.5	52.2	10 900*	40.0
44.0	52.8	51.5	17 000 *	56.4	50.6	14 800*	59.7	48.9	10 300*	44.0
48.0	48.0	47.7	16 500 *	51.4	46.8	13 800*	54.5	44.9	9 800*	48.0
52.0	42.6	43.3	15 300	46.0	42.2	12 900*	48.8	40.1	9 400*	52.0
56.0	36.6	37.8	13 500	39.8	36.6	12 200*				56.0
42.7m (140 Ft.) BOOM										
16.8	80.6	68.4	23 500 *							16.8
18.0	79.6	68.1	23 100 *							18.0
20.0	77.8	67.6	22 500 *							20.0
22.0	76.0	67.0	21 900 *	79.7	66.3	19 900*				22.0
24.0	74.3	66.4	21 400 *	77.9	65.7	19 400*				24.0
26.0	72.4	65.6	20 900 *	76.1	64.9	19 000*	79.8	63.5	14 300*	26.0
28.0	70.6	64.8	20 400 *	74.3	64.1	18 700*	77.9	62.7	13 700*	28.0
30.0	68.8	64.0	19 900 *	72.4	63.2	18 300*	76.0	61.8	13 200*	30.0
32.0	66.9	63.0	19 500 *	70.5	62.3	18 000*	74.1	60.8	12 700*	32.0
34.0	65.0	62.0	19 100 *	68.6	61.2	17 600*	72.1	59.7	12 300*	34.0
36.0	63.0	60.9	18 700 *	66.6	60.1	17 300*	70.1	58.5	11 900*	36.0
38.0	61.1	59.7	18 300 *	64.6	58.9	17 000*	68.0	57.3	11 500*	38.0
40.0	59.0	58.3	18 000 *	62.5	57.5	16 600*	65.9	55.9	11 100*	40.0
44.0	54.8	55.4	17 300 *	58.2	54.6	15 300*	61.5	52.8	10 500*	44.0
48.0	50.4	52.0	16 700 *	53.7	51.1	14 200*	56.8	49.2	10 000*	48.0
52.0	45.5	47.9	14 900	48.8	46.9	13 300*	51.6	44.9	9 500*	52.0
56.0	40.2	43.1	13 100	43.3	42.0	12 600*				56.0
60.0	34.1	37.1	11 400	37.1	35.8	11 800				60.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
18.3	79.8	71.2	23 200 *							18.3
20.0	78.3	70.8	22 700 *							20.0
22.0	76.7	70.2	22 100 *	80.2	69.5	20 000*				22.0
24.0	75.0	69.6	21 600 *	78.5	68.9	19 600*				24.0
26.0	73.2	68.9	21 100 *	76.7	68.2	19 200*	80.3	66.7	14 400*	26.0
28.0	71.5	68.1	20 600 *	75.0	67.4	18 800*	78.5	65.9	13 900*	28.0
30.0	69.8	67.3	20 200 *	73.2	66.6	18 500*	76.7	65.0	13 300*	30.0
32.0	68.0	66.4	19 700 *	71.4	65.6	18 100*	74.8	64.1	12 900*	32.0
34.0	66.2	65.4	19 300 *	69.6	64.7	17 800*	73.0	63.1	12 500*	34.0
36.0	64.3	64.4	18 900 *	67.7	63.6	17 500*	71.1	62.0	12 000*	36.0
38.0	62.5	63.2	18 600 *	65.8	62.4	17 200*	69.1	60.8	11 700*	38.0
40.0	60.6	62.0	18 200 *	63.9	61.2	16 900*	67.1	59.5	11 300*	40.0
44.0	56.6	59.2	17 600 *	59.9	58.4	15 700*	63.0	56.6	10 700*	44.0
48.0	52.5	56.0	16 800	55.7	55.1	14 600*	58.7	53.3	10 200*	48.0
52.0	48.0	52.3	14 600	51.2	51.4	13 700*	54.0	49.4	9 700*	52.0
56.0	43.2	48.0	12 700	46.3	46.9	12 900*	48.8	44.7	9 400*	56.0
60.0	37.9	42.8	11 100	40.8	41.5	11 400				60.0
64.0	31.7	36.3	9 700	34.4	34.8	10 000				64.0
48.8m (160 Ft.) BOOM										
18.3	80.2	74.3	23 300 *							18.3
20.0	78.8	73.9	22 800 *							20.0
22.0	77.2	73.4	22 300 *							22.0
24.0	75.6	72.8	21 800 *	79.0	72.0	19 700*				24.0
26.0	74.0	72.1	21 300 *	77.3	71.4	19 300*	80.7	69.9	14 600*	26.0
28.0	72.3	71.4	20 800 *	75.7	70.6	18 900*	79.0	69.1	14 000*	28.0
30.0	70.6	70.6	20 400 *	74.0	69.8	18 600*	77.3	68.3	13 500*	30.0
32.0	69.0	69.7	20 000 *	72.3	69.0	18 300*	75.6	67.4	13 000*	32.0
34.0	67.2	68.8	19 600 *	70.5	68.0	17 900*	73.8	66.5	12 600*	34.0
36.0	65.5	67.8	19 200 *	68.8	67.0	17 600*	72.0	65.4	12 200*	36.0
38.0	63.7	66.7	18 800 *	67.0	65.9	17 400*	70.1	64.3	11 800*	38.0
40.0	61.9	65.6	18 500 *	65.1	64.8	17 100*	68.3	63.1	11 500*	40.0
44.0	58.2	63.0	17 800 *	61.4	62.1	16 200*	64.4	60.4	10 900*	44.0
48.0	54.3	60.0	16 300	57.5	59.1	15 000*	60.3	57.3	10 300*	48.0
52.0	50.2	56.6	14 100	53.3	55.6	14 100*	56.0	53.6	9 900*	52.0
56.0	45.8	52.6	12 300	48.8	51.5	12 700	51.4	49.4	9 500*	56.0
60.0	41.1	47.9	10 700	43.9	46.7	11 100				60.0
64.0	35.7	42.2	9 300	38.4	40.9	9 600				64.0
68.0	29.4	35.2	8 100							68.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
18.3	80.6	77.4	23 400 *							18.3
20.0	79.3	77.0	23 000 *							20.0
22.0	77.7	76.5	22 500 *							22.0
24.0	76.2	76.0	22 000 *	79.4	75.2	19 800 *				24.0
26.0	74.6	75.3	21 500 *	77.9	74.6	19 400 *				26.0
28.0	73.1	74.6	21 000 *	76.3	73.9	19 100 *	79.5	72.3	14 100 *	28.0
30.0	71.5	73.9	20 600 *	74.6	73.1	18 700 *	77.9	71.6	13 600 *	30.0
32.0	69.8	73.1	20 200 *	73.0	72.3	18 400 *	76.2	70.7	13 200 *	32.0
34.0	68.2	72.2	19 800 *	71.4	71.4	18 100 *	74.5	69.8	12 700 *	34.0
36.0	66.6	71.2	19 400 *	69.7	70.4	17 800 *	72.8	68.8	12 300 *	36.0
38.0	64.9	70.2	19 100 *	68.0	69.4	17 500 *	71.0	67.8	12 000 *	38.0
40.0	63.2	69.1	18 700 *	66.3	68.3	17 300 *	69.3	66.6	11 600 *	40.0
44.0	59.7	66.7	18 100 *	62.7	65.8	16 600 *	65.6	64.1	11 000 *	44.0
48.0	56.0	63.8	16 100	59.0	63.0	15 400 *	61.8	61.1	10 500 *	48.0
52.0	52.2	60.6	13 900	55.1	59.7	14 400	57.8	57.8	10 000 *	52.0
56.0	48.1	56.9	12 100	51.0	55.9	12 500	53.5	53.9	9 600 *	56.0
60.0	43.8	52.7	10 400	46.5	51.6	10 800	48.9	49.3	9 300 *	60.0
64.0	39.0	47.6	9 100	41.6	46.4	9 400				64.0
68.0	33.5	41.6	7 900	36.0	40.1	8 200				68.0
54.9m (180 Ft.) BOOM										
18.3	81.0	80.5	23 600 *							18.3
20.0	79.7	80.2	23 100 *							20.0
22.0	78.2	79.7	22 600 *							22.0
24.0	76.7	79.1	22 100 *	79.9	78.4	19 900 *				24.0
26.0	75.2	78.5	21 700 *	78.3	77.8	19 500 *				26.0
28.0	73.7	77.9	21 200 *	76.8	77.1	19 200 *	79.9	75.5	14 300 *	28.0
30.0	72.2	77.1	20 800 *	75.3	76.4	18 800 *	78.4	74.8	13 800 *	30.0
32.0	70.7	76.4	20 400 *	73.7	75.6	18 500 *	76.8	74.0	13 300 *	32.0
34.0	69.1	75.5	20 000 *	72.1	74.7	18 300 *	75.2	73.1	12 900 *	34.0
36.0	67.5	74.6	19 600 *	70.5	73.8	18 000 *	73.5	72.2	12 500 *	36.0
38.0	65.9	73.6	19 300 *	68.9	72.8	17 700 *	71.9	71.2	12 100 *	38.0
40.0	64.3	72.6	18 900 *	67.3	71.8	17 400 *	70.2	70.1	11 800 *	40.0
44.0	61.0	70.3	18 200	63.9	69.4	16 900 *	66.7	67.7	11 200 *	44.0
48.0	57.5	67.6	15 700	60.4	66.7	15 800 *	63.2	64.9	10 700 *	48.0
52.0	53.9	64.6	13 500	56.8	63.7	14 100	59.4	61.8	10 200 *	52.0
56.0	50.1	61.2	11 600	52.9	60.2	12 200	55.4	58.1	9 800 *	56.0
60.0	46.1	57.2	10 100	48.8	56.1	10 500	51.1	54.0	9 400 *	60.0
64.0	41.7	52.6	8 700	44.4	51.5	9 100	46.5	49.1	9 200 *	64.0
68.0	36.9	47.2	7 500	39.4	45.9	7 800				68.0
72.0	31.4	40.7	6 400							72.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
19.8	80.2	83.3	23 300 *							19.8
20.0	80.1	83.3	23 300 *							20.0
22.0	78.7	82.8	22 800 *							22.0
24.0	77.2	82.3	22 300 *							24.0
26.0	75.8	81.7	21 800 *	78.8	80.9	19 600 *				26.0
28.0	74.4	81.1	21 400 *	77.3	80.3	19 300 *	80.3	78.7	14 400 *	28.0
30.0	72.9	80.4	21 000 *	75.8	79.6	19 000 *	78.8	78.0	13 900 *	30.0
32.0	71.4	79.6	20 600 *	74.4	78.8	18 700 *	77.3	77.2	13 400 *	32.0
34.0	69.9	78.8	20 200 *	72.8	78.0	18 400 *	75.8	76.4	13 000 *	34.0
36.0	68.4	78.0	19 800 *	71.3	77.1	18 100 *	74.2	75.5	12 600 *	36.0
38.0	66.9	77.0	19 500 *	69.8	76.2	17 800 *	72.6	74.5	12 300 *	38.0
40.0	65.3	76.0	19 200 *	68.2	75.2	17 500 *	71.0	73.5	12 000 *	40.0
44.0	62.2	73.8	18 000	65.0	73.0	17 100 *	67.8	71.2	11 300 *	44.0
48.0	58.9	71.3	15 400	61.7	70.4	16 100	64.4	68.6	10 800 *	48.0
52.0	55.5	68.5	13 100	58.3	67.5	13 800	60.8	65.6	10 300 *	52.0
56.0	52.0	65.2	11 300	54.7	64.2	11 900	57.1	62.3	9 900 *	56.0
60.0	48.2	61.6	9 700	50.8	60.5	10 200	53.1	58.4	9 600 *	60.0
64.0	44.2	57.3	8 300	46.7	56.2	8 700	48.9	53.9	9 100	64.0
68.0	39.8	52.5	7 100	42.3	51.2	7 400				68.0
72.0	34.9	46.7	6 000	37.3	45.3	6 300				72.0
76.0	29.3	39.6	5 100							76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
19.8	80.6	86.4	23 400 *							19.8
20.0	80.5	86.4	23 400 *							20.0
22.0	79.1	85.9	22 900 *							22.0
24.0	77.7	85.4	22 400 *							24.0
26.0	76.3	84.9	22 000 *	79.2	84.1	19 700*				26.0
28.0	74.9	84.3	21 600 *	77.8	83.5	19 400*				28.0
30.0	73.5	83.6	21 200 *	76.4	82.8	19 100*	79.3	81.2	14 000*	30.0
32.0	72.1	82.9	20 800 *	74.9	82.1	18 800*	77.8	80.5	13 600*	32.0
34.0	70.7	82.1	20 400 *	73.5	81.3	18 500*	76.3	79.7	13 100*	34.0
36.0	69.2	81.3	20 000 *	72.0	80.5	18 200*	74.8	78.8	12 700*	36.0
38.0	67.8	80.4	19 700 *	70.6	79.6	18 000*	73.3	77.9	12 400*	38.0
40.0	66.3	79.4	19 300 *	69.1	78.6	17 700*	71.8	76.9	12 100*	40.0
44.0	63.3	77.3	17 600	66.0	76.5	17 200*	68.7	74.7	11 500*	44.0
48.0	60.2	74.9	15 000	62.9	74.0	15 800	65.4	72.2	10 900*	48.0
52.0	56.9	72.2	12 800	59.6	71.3	13 500	62.1	69.4	10 500*	52.0
56.0	53.6	69.2	10 900	56.2	68.2	11 500	58.6	66.3	10 100*	56.0
60.0	50.1	65.7	9 300	52.6	64.7	9 800	54.9	62.6	9 700*	60.0
64.0	46.3	61.8	7 900	48.8	60.7	8 300	51.0	58.5	8 800	64.0
68.0	42.3	57.4	6 700	44.7	56.2	7 100	46.7	53.7	7 400	68.0
72.0	37.9	52.2	5 600	40.3	50.8	5 900				72.0
76.0	33.0	46.0	4 700	35.2	44.5	4 900				76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
19.8	80.9	89.6	23 600 *							19.8
20.0	80.8	89.5	23 500 *							20.0
22.0	79.5	89.1	23 100 *							22.0
24.0	78.1	88.6	22 600 *							24.0
26.0	76.8	88.1	22 200 *	79.6	87.3	19 800*				26.0
28.0	75.5	87.5	21 700 *	78.2	86.7	19 500*				28.0
30.0	74.1	86.8	21 300 *	76.9	86.0	19 200*	79.7	84.4	14 100*	30.0
32.0	72.7	86.1	21 000 *	75.5	85.3	18 900*	78.3	83.7	13 600*	32.0
34.0	71.4	85.4	20 600 *	74.1	84.6	18 600*	76.8	82.9	13 300*	34.0
36.0	70.0	84.6	20 200 *	72.7	83.8	18 300*	75.4	82.1	12 900*	36.0
38.0	68.6	83.7	19 900 *	71.3	82.9	18 100*	74.0	81.2	12 500*	38.0
40.0	67.2	82.8	19 500 *	69.9	82.0	17 800*	72.5	80.3	12 200*	40.0
44.0	64.3	80.8	17 400	66.9	79.9	17 300*	69.5	78.2	11 600*	44.0
48.0	61.3	78.5	14 700	63.9	77.6	15 500	66.4	75.8	11 100*	48.0
52.0	58.2	76.0	12 500	60.8	75.0	13 200	63.3	73.2	10 600*	52.0
56.0	55.1	73.1	10 600	57.6	72.1	11 300	60.0	70.2	10 200*	56.0
60.0	51.7	69.8	9 000	54.2	68.8	9 600	56.5	66.8	9 800	60.0
64.0	48.3	66.2	7 700	50.7	65.1	8 100	52.8	62.9	8 600	64.0
68.0	44.5	62.0	6 500	46.9	60.9	6 900	48.9	58.5	7 200	68.0
72.0	40.5	57.2	5 400	42.8	56.0	5 700				72.0
76.0	36.1	51.7	4 400	38.3	50.3	4 700				76.0
80.0	31.1	45.1	3 600							80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
21.3	80.2	92.3	23 400 *							21.3
22.0	79.8	92.2	23 200 *							22.0
24.0	78.5	91.7	22 700 *							24.0
26.0	77.3	91.2	22 300 *	80.0	90.4	19 900*				26.0
28.0	76.0	90.6	21 900*	78.6	89.8	19 600*				28.0
30.0	74.7	90.0	21 500 *	77.3	89.2	19 300*	80.0	87.6	14 200*	30.0
32.0	73.3	89.4	21 100 *	76.0	88.5	19 000*	78.7	86.9	13 800*	32.0
34.0	72.0	88.6	20 700 *	74.7	87.8	18 700*	77.3	86.2	13 400*	34.0
36.0	70.7	87.9	20 400 *	73.3	87.0	18 500*	75.9	85.4	13 000*	36.0
38.0	69.3	87.1	20 100 *	72.0	86.2	18 200*	74.6	84.5	12 700*	38.0
40.0	68.0	86.2	19 700	70.6	85.3	18 000*	73.1	83.6	12 300*	40.0
44.0	65.2	84.2	17 000	67.8	83.4	17 500*	70.3	81.6	11 700*	44.0
48.0	62.4	82.1	14 400	64.9	81.2	15 200	67.4	79.4	11 200*	48.0
52.0	59.4	79.6	12 100	62.0	78.7	12 900	64.3	76.8	10 700*	52.0
56.0	56.4	76.9	10 300	58.9	75.9	10 900	61.2	74.0	10 300*	56.0
60.0	53.3	73.8	8 700	55.7	72.8	9 300	57.9	70.8	9 800	60.0
64.0	50.0	70.3	7 300	52.4	69.3	7 800	54.5	67.2	8 300	64.0
68.0	46.5	66.5	6 100	48.8	65.3	6 500	50.8	63.1	6 900	68.0
72.0	42.8	62.1	5 000	45.1	60.9	5 400				72.0
76.0	38.8	57.0	4 000	41.0	55.7	4 300				76.0
80.0	34.4	51.1	3 200	36.4	49.6	3 500				80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
21.3	80.6	95.5	23 400 *							21.3
22.0	80.2	95.3	23 300 *							22.0
24.0	78.9	94.9	22 900 *							24.0
26.0	77.7	94.4	22 400 *	80.3	93.6	20 000*				26.0
28.0	76.4	93.8	22 000 *	79.0	93.0	19 700*				28.0
30.0	75.2	93.2	21 600 *	77.8	92.4	19 400*				30.0
32.0	73.9	92.6	21 300 *	76.5	91.8	19 100*	79.1	90.1	13 900*	32.0
34.0	72.6	91.9	20 900 *	75.2	91.1	18 800*	77.8	89.4	13 500*	34.0
36.0	71.3	91.1	20 600 *	73.9	90.3	18 600*	76.4	88.6	13 100*	36.0
38.0	70.0	90.4	20 200 *	72.6	89.5	18 300*	75.1	87.8	12 800*	38.0
40.0	68.7	89.5	19 600	71.3	88.7	18 100*	73.7	86.9	12 400*	40.0
44.0	66.1	87.7	16 600	68.6	86.8	17 500	71.0	85.0	11 800*	44.0
48.0	63.3	85.6	14 000	65.8	84.7	14 900	68.2	82.9	11 300*	48.0
52.0	60.6	83.2	11 800	63.0	82.3	12 600	65.3	80.4	10 800*	52.0
56.0	57.7	80.6	9 900	60.1	79.6	10 600	62.3	77.7	10 400*	56.0
60.0	54.7	77.7	8 300	57.1	76.7	8 900	59.2	74.7	9 500	60.0
64.0	51.6	74.4	6 900	53.9	73.4	7 400	56.0	71.3	8 000	64.0
68.0	48.3	70.8	5 700	50.6	69.7	6 200	52.5	67.4	6 600	68.0
72.0	44.8	66.7	4 600	47.1	65.5	5 000	48.9	63.1	5 400	72.0
76.0	41.1	62.0	3 700	43.3	60.7	4 000				76.0
80.0	37.1	56.7	2 800	39.2	55.3	3 100				80.0
84.0	32.6	50.4	2 000							84.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
73.2m (240 Ft.) BOOM										
21.3	80.9	98.6	23 600 *							21.3
22.0	80.5	98.4	23 400 *							22.0
24.0	79.3	98.0	23 000 *							24.0
26.0	78.1	97.5	22 600 *	80.6	96.7	20 100*				26.0
28.0	76.9	97.0	22 200 *	79.4	96.2	19 800*				28.0
30.0	75.6	96.4	21 800 *	78.2	95.6	19 500*				30.0
32.0	74.4	95.8	21 400 *	76.9	95.0	19 200*	79.4	93.3	14 000*	32.0
34.0	73.2	95.1	21 100 *	75.7	94.3	18 900*	78.2	92.6	13 600*	34.0
36.0	71.9	94.4	20 700 *	74.4	93.6	18 700*	76.9	91.9	13 200*	36.0
38.0	70.7	93.6	20 400 *	73.2	92.8	18 400*	75.6	91.1	12 800*	38.0
40.0	69.4	92.8	19 000	71.9	92.0	18 200*	74.3	90.2	12 500*	40.0
44.0	66.9	91.0	16 100	69.3	90.2	17 200	71.7	88.4	12 000*	44.0
48.0	64.3	89.0	13 600	66.7	88.1	14 600	69.0	86.3	11 400*	48.0
52.0	61.6	86.8	11 400	63.9	85.9	12 200	66.2	84.0	11 000*	52.0
56.0	58.8	84.3	9 500	61.2	83.3	10 300	63.3	81.4	10 500*	56.0
60.0	56.0	81.5	7 900	58.3	80.5	8 600	60.4	78.5	9 200	60.0
64.0	53.0	78.4	6 500	55.3	77.4	7 100	57.3	75.3	7 600	64.0
68.0	49.9	74.9	5 300	52.2	73.9	5 800	54.1	71.7	6 300	68.0
72.0	46.7	71.1	4 200	48.9	69.9	4 700	50.7	67.6	5 100	72.0
76.0	43.2	66.7	3 300	45.3	65.5	3 700	47.0	63.1	4 000	76.0
80.0	39.5	61.8	2 400	41.6	60.5	2 700				80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
22.9	80.3	101.4	23 400 *							22.9
24.0	79.6	101.1	23 100 *							24.0
26.0	78.4	100.6	22 700 *	80.9	99.8	20 100*				26.0
28.0	77.3	100.1	22 300 *	79.7	99.3	19 800*				28.0
30.0	76.1	99.6	21 900 *	78.5	98.7	19 600*				30.0
32.0	74.9	99.0	21 600 *	77.3	98.1	19 300*	79.8	96.5	14 100*	32.0
34.0	73.7	98.3	21 200 *	76.1	97.5	19 000*	78.6	95.8	13 700*	34.0
36.0	72.5	97.6	20 900 *	74.9	96.8	18 700*	77.3	95.1	13 300*	36.0
38.0	71.3	96.9	20 500	73.7	96.0	18 500*	76.1	94.3	12 900*	38.0
40.0	70.1	96.1	19 000	72.5	95.3	18 300*	74.8	93.5	12 600*	40.0
44.0	67.6	94.4	16 200	70.0	93.5	17 200	72.3	91.7	12 000*	44.0
48.0	65.1	92.5	13 800	67.4	91.6	14 700	69.7	89.7	11 500*	48.0
52.0	62.5	90.3	11 600	64.8	89.4	12 400	67.0	87.5	11 000*	52.0
56.0	59.9	87.9	9 700	62.2	86.9	10 400	64.3	85.0	10 600*	56.0
60.0	57.2	85.2	8 100	59.4	84.3	8 800	61.5	82.3	9 400	60.0
64.0	54.3	82.3	6 700	56.6	81.3	7 300	58.6	79.2	7 800	64.0
68.0	51.4	79.0	5 500	53.6	77.9	6 000	55.5	75.8	6 500	68.0
72.0	48.3	75.4	4 400	50.5	74.3	4 800	52.3	72.0	5 200	72.0
76.0	45.1	71.3	3 400	47.2	70.1	3 900	48.9	67.7	4 200	76.0
80.0	41.7	66.7	2 600	43.7	65.5	2 900				80.0
84.0				39.9	60.2	2 100				84.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

24.4m (80 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
79.2m (260 Ft.) BOOM										
22.9	80.5	104.5	23 400 *							22.9
24.0	79.9	104.2	23 200 *							24.0
26.0	78.8	103.8	22 800 *							26.0
28.0	77.6	103.3	22 400 *	80.0	102.4	19 900*				28.0
30.0	76.5	102.7	22 100 *	78.9	101.9	19 600*				30.0
32.0	75.4	102.2	21 700 *	77.7	101.3	19 400*	80.1	99.6	14 100*	32.0
34.0	74.2	101.5	21 400 *	76.6	100.7	19 100*	78.9	99.0	13 700*	34.0
36.0	73.0	100.9	21 000 *	75.4	100.0	18 900*	77.7	98.3	13 400*	36.0
38.0	71.9	100.2	20 000	74.2	99.3	18 600*	76.5	97.6	13 100*	38.0
40.0	70.7	99.4	18 400	73.0	98.5	18 400*	75.3	96.8	12 700*	40.0
44.0	68.3	97.7	15 600	70.6	96.8	16 700	72.9	95.1	12 200*	44.0
48.0	65.9	95.9	13 300	68.2	95.0	14 200	70.4	93.2	11 700*	48.0
52.0	63.4	93.8	11 200	65.7	92.9	12 100	67.8	91.0	11 200*	52.0
56.0	60.9	91.5	9 300	63.1	90.5	10 100	65.2	88.6	10 700	56.0
60.0	58.3	88.9	7 700	60.5	88.0	8 400	62.5	86.0	9 100	60.0
64.0	55.6	86.1	6 300	57.7	85.1	6 900	59.7	83.1	7 500	64.0
68.0	52.8	83.0	5 100	54.9	81.9	5 700	56.8	79.8	6 100	68.0
72.0	49.9	79.5	4 000	52.0	78.4	4 500	53.8	76.2	4 900	72.0
76.0	46.8	75.7	3 000	48.9	74.5	3 500	50.6	72.2	3 900	76.0
80.0	43.6	71.4	2 200	45.6	70.2	2 600	47.2	67.7	2 900	80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
18.3	80.1	71.2	18 300 *							18.3
20.0	78.7	70.8	17 900 *							20.0
22.0	77.0	70.2	17 400 *							22.0
24.0	75.3	69.6	16 900 *	79.8	68.9	15 400*				24.0
26.0	73.6	68.9	16 500 *	78.0	68.2	15 000*				26.0
28.0	71.9	68.1	16 100 *	76.3	67.4	14 600*				28.0
30.0	70.1	67.3	15 700 *	74.5	66.6	14 200*	79.4	65.1	11 500*	30.0
32.0	68.3	66.4	15 300 *	72.7	65.7	13 800*	77.5	64.2	11 100*	32.0
34.0	66.5	65.4	14 900 *	70.9	64.7	13 400*	75.6	63.2	10 600*	34.0
36.0	64.7	64.4	14 400 *	69.0	63.6	13 100*	73.7	62.1	10 300*	36.0
38.0	62.8	63.2	14 000 *	67.1	62.4	12 800*	71.8	61.0	9 900*	38.0
40.0	60.9	62.0	13 600 *	65.2	61.2	12 500*	69.8	59.7	9 600*	40.0
44.0	57.0	59.3	12 900 *	61.2	58.4	11 900*	65.7	56.9	9 000*	44.0
48.0	52.8	56.1	12 200 *	57.0	55.2	11 200*	61.4	53.5	8 400*	48.0
52.0	48.4	52.4	11 600 *	52.5	51.4	10 400*	56.7	49.7	8 000*	52.0
56.0	43.6	48.0	11 100 *	47.6	46.9	9 800*	51.6	45.1	7 700*	56.0
60.0	38.3	42.8	10 600 *	42.1	41.6	9 200*				60.0
64.0	32.1	36.3	10 200 *	35.7	34.9	8 800*				64.0
42.7m (140 Ft.) BOOM										
18.3	80.5	74.3	18 500 *							18.3
20.0	79.2	73.9	18 000 *							20.0
22.0	77.6	73.4	17 500 *							22.0
24.0	75.9	72.8	17 100 *							24.0
26.0	74.3	72.1	16 700 *	78.6	71.4	15 100*				26.0
28.0	72.7	71.4	16 300 *	76.9	70.6	14 700*				28.0
30.0	71.0	70.6	15 900 *	75.2	69.8	14 300*	79.8	68.4	11 700*	30.0
32.0	69.3	69.8	15 500 *	73.5	69.0	14 000*	78.1	67.5	11 200*	32.0
34.0	67.6	68.8	15 100 *	71.8	68.0	13 600*	76.3	66.6	10 800*	34.0
36.0	65.8	67.8	14 700 *	70.0	67.0	13 300*	74.5	65.5	10 400*	36.0
38.0	64.1	66.8	14 300 *	68.2	65.9	12 900*	72.7	64.4	10 000*	38.0
40.0	62.3	65.6	13 900 *	66.4	64.8	12 600*	70.8	63.2	9 700*	40.0
44.0	58.6	63.0	13 200 *	62.6	62.1	12 000*	67.0	60.6	9 100*	44.0
48.0	54.7	60.0	12 500 *	58.7	59.1	11 500*	62.9	57.5	8 600*	48.0
52.0	50.6	56.6	11 900 *	54.5	55.6	10 800*	58.6	53.9	8 200*	52.0
56.0	46.2	52.6	11 400 *	50.0	51.5	10 000*	54.0	49.7	7 800*	56.0
60.0	41.4	47.9	10 900 *	45.1	46.7	9 400*	48.9	44.7	7 500*	60.0
64.0	36.0	42.3	10 300 *	39.6	40.9	9 000*				64.0
68.0	29.7	35.2	9 100 *							68.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
18.3	80.9	77.4	18 500 *							18.3
20.0	79.6	77.1	18 100 *							20.0
22.0	78.1	76.5	17 700 *							22.0
24.0	76.5	76.0	17 300 *							24.0
26.0	75.0	75.3	16 800 *	79.0	74.6	15 200*				26.0
28.0	73.4	74.7	16 400 *	77.4	73.9	14 900*				28.0
30.0	71.8	73.9	16 100 *	75.8	73.1	14 500*				30.0
32.0	70.2	73.1	15 700 *	74.2	72.3	14 100*	78.6	70.8	11 300*	32.0
34.0	68.5	72.2	15 300 *	72.6	71.4	13 800*	76.9	69.9	10 900*	34.0
36.0	66.9	71.2	14 900 *	70.9	70.4	13 400*	75.2	68.9	10 600*	36.0
38.0	65.2	70.2	14 500 *	69.2	69.4	13 100*	73.5	67.8	10 200*	38.0
40.0	63.5	69.1	14 200 *	67.5	68.3	12 800*	71.7	66.7	9 900*	40.0
44.0	60.0	66.7	13 500 *	63.9	65.8	12 200*	68.1	64.2	9 300*	44.0
48.0	56.4	63.9	12 800 *	60.2	63.0	11 700*	64.3	61.3	8 700*	48.0
52.0	52.5	60.7	12 200 *	56.3	59.7	11 100*	60.3	57.9	8 300*	52.0
56.0	48.5	57.0	11 600 *	52.2	55.9	10 300*	56.0	54.1	7 900*	56.0
60.0	44.1	52.7	11 100 *	47.7	51.6	9 800*	51.4	49.6	7 600*	60.0
64.0	39.3	47.7	10 000	42.8	46.4	9 200*	46.2	44.2	7 300*	64.0
68.0	33.9	41.6	8 800	37.2	40.1	8 800*				68.0
48.8m (160 Ft.) BOOM										
19.8	80.2	80.2	18 300 *							19.8
20.0	80.0	80.2	18 300 *							20.0
22.0	78.5	79.7	17 800 *							22.0
24.0	77.1	79.1	17 400 *							24.0
26.0	75.6	78.5	17 000 *	79.5	77.7	15 300*				26.0
28.0	74.0	77.9	16 600 *	78.0	77.1	15 000*				28.0
30.0	72.5	77.2	16 200 *	76.4	76.4	14 600*				30.0
32.0	71.0	76.4	15 900 *	74.9	75.6	14 200*	79.1	74.0	11 500*	32.0
34.0	69.4	75.5	15 500 *	73.3	74.7	13 900*	77.5	73.1	11 100*	34.0
36.0	67.8	74.6	15 200 *	71.7	73.8	13 600*	75.9	72.2	10 700*	36.0
38.0	66.2	73.7	14 800 *	70.1	72.8	13 300*	74.2	71.2	10 400*	38.0
40.0	64.6	72.6	14 400 *	68.4	71.7	13 000*	72.5	70.1	10 000*	40.0
44.0	61.3	70.3	13 700 *	65.1	69.4	12 400*	69.1	67.7	9 400*	44.0
48.0	57.9	67.6	13 000 *	61.6	66.7	11 900*	65.5	65.0	8 900*	48.0
52.0	54.3	64.6	12 400 *	57.9	63.6	11 400*	61.7	61.9	8 500*	52.0
56.0	50.5	61.2	11 900 *	54.1	60.1	10 600*	57.8	58.3	8 100*	56.0
60.0	46.4	57.2	11 000	50.0	56.1	10 000*	53.5	54.2	7 800*	60.0
64.0	42.1	52.7	9 600	45.5	51.4	9 500*	48.9	49.3	7 400*	64.0
68.0	37.3	47.3	8 400	40.5	45.9	8 800				68.0
72.0	31.7	40.7	7 300							72.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
19.8	80.5	83.3	18 500 *							19.8
20.0	80.4	83.3	18 400 *							20.0
22.0	79.0	82.8	17 900 *							22.0
24.0	77.5	82.3	17 500 *							24.0
26.0	76.1	81.7	17 200 *	79.9	80.9	15 400*				26.0
28.0	74.7	81.1	16 800 *	78.4	80.3	15 100*				28.0
30.0	73.2	80.4	16 400 *	76.9	79.6	14 700*				30.0
32.0	71.7	79.7	16 100 *	75.5	78.8	14 400*	79.5	77.2	11 600*	32.0
34.0	70.2	78.8	15 700 *	73.9	78.0	14 100*	78.0	76.4	11 200*	34.0
36.0	68.7	78.0	15 400 *	72.4	77.1	13 700*	76.4	75.5	10 800*	36.0
38.0	67.2	77.0	15 000 *	70.9	76.2	13 400*	74.9	74.6	10 400*	38.0
40.0	65.6	76.0	14 600 *	69.3	75.2	13 100*	73.3	73.5	10 100*	40.0
44.0	62.5	73.8	14 000 *	66.1	72.9	12 600*	70.0	71.3	9 500*	44.0
48.0	59.2	71.3	13 300 *	62.8	70.4	12 100*	66.6	68.7	9 100*	48.0
52.0	55.8	68.5	12 700 *	59.4	67.5	11 600*	63.1	65.7	8 600*	52.0
56.0	52.3	65.3	12 100 *	55.7	64.2	10 900*	59.3	62.4	8 200*	56.0
60.0	48.5	61.6	10 700	51.9	60.5	10 200*	55.4	58.5	7 900*	60.0
64.0	44.5	57.4	9 300	47.8	56.2	9 700*	51.1	54.1	7 600*	64.0
68.0	40.1	52.5	8 100	43.4	51.2	8 500	46.5	48.9	7 300*	68.0
72.0	35.3	46.7	7 100	38.4	45.3	7 400				72.0
76.0	29.6	39.6	6 100							76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
19.8	80.9	86.5	18 500 *							19.8
20.0	80.7	86.4	18 500 *							20.0
22.0	79.4	86.0	18 100 *							22.0
24.0	78.0	85.5	17 700 *							24.0
26.0	76.6	84.9	17 300 *	80.3	84.1	15 500*				26.0
28.0	75.2	84.3	16 900 *	78.9	83.5	15 200*				28.0
30.0	73.8	83.6	16 500 *	77.4	82.8	14 800*				30.0
32.0	72.4	82.9	16 200 *	76.0	82.1	14 500*				32.0
34.0	71.0	82.1	15 900 *	74.6	81.3	14 200*	78.5	79.6	11 300*	34.0
36.0	69.5	81.3	15 500 *	73.1	80.4	13 900*	77.0	78.8	10 900*	36.0
38.0	68.1	80.4	15 200 *	71.6	79.5	13 600*	75.5	77.9	10 600*	38.0
40.0	66.6	79.5	14 900 *	70.1	78.6	13 300*	73.9	76.9	10 300*	40.0
44.0	63.6	77.3	14 200 *	67.1	76.4	12 700*	70.8	74.7	9 700*	44.0
48.0	60.5	75.0	13 500 *	63.9	74.0	12 200*	67.6	72.3	9 200*	48.0
52.0	57.2	72.3	12 900 *	60.7	71.3	11 800*	64.3	69.5	8 700*	52.0
56.0	53.9	69.2	12 000	57.3	68.2	11 200*	60.8	66.3	8 300*	56.0
60.0	50.4	65.8	10 300	53.7	64.7	10 500*	57.1	62.8	8 000*	60.0
64.0	46.6	61.9	8 900	49.9	60.7	9 400	53.1	58.7	7 700*	64.0
68.0	42.6	57.4	7 700	45.8	56.1	8 100	48.9	53.9	7 400*	68.0
72.0	38.2	52.2	6 700	41.3	50.8	7 000				72.0
76.0	33.3	46.0	5 700	36.2	44.4	6 000				76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
21.3	80.2	89.2	18 300 *							21.3
22.0	79.7	89.1	18 200 *							22.0
24.0	78.4	88.6	17 800 *							24.0
26.0	77.1	88.1	17 400 *	80.6	87.2	15 600*				26.0
28.0	75.7	87.5	17 000 *	79.3	86.6	15 300*				28.0
30.0	74.4	86.8	16 700 *	77.9	86.0	14 900*				30.0
32.0	73.0	86.2	16 400 *	76.5	85.3	14 600*				32.0
34.0	71.7	85.4	16 000 *	75.1	84.5	14 300*	78.9	82.9	11 400*	34.0
36.0	70.3	84.6	15 700 *	73.7	83.7	14 000*	77.5	82.1	11 000*	36.0
38.0	68.9	83.8	15 400 *	72.3	82.9	13 700*	76.0	81.2	10 700*	38.0
40.0	67.4	82.8	15 000 *	70.9	81.9	13 400*	74.6	80.2	10 400*	40.0
44.0	64.6	80.8	14 400 *	68.0	79.9	12 900*	71.6	78.2	9 800*	44.0
48.0	61.6	78.5	13 800 *	65.0	77.6	12 400*	68.5	75.8	9 300*	48.0
52.0	58.5	76.0	13 200 *	61.9	75.0	11 900*	65.3	73.2	8 900*	52.0
56.0	55.4	73.1	11 600 *	58.6	72.1	11 400*	62.0	70.2	8 500*	56.0
60.0	52.0	69.8	10 000 *	55.3	68.8	10 600	58.6	66.8	8 100*	60.0
64.0	48.5	66.2	8 600 *	51.7	65.0	9 100	54.9	63.0	7 800*	64.0
68.0	44.8	62.0	7 400 *	47.9	60.8	7 800	51.0	58.7	7 600*	68.0
72.0	40.8	57.3	6 300 *	43.8	55.9	6 700	46.7	53.6	7 300	72.0
76.0	36.4	51.7	5 400 *	39.3	50.3	5 700				76.0
80.0	31.4	45.1	4 500 *							80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
21.3	80.5	92.4	18 500 *							21.3
22.0	80.1	92.2	18 300 *							22.0
24.0	78.8	91.7	17 900 *							24.0
26.0	77.5	91.2	17 500 *							26.0
28.0	76.2	90.7	17 200 *	79.6	89.8	15 300*				28.0
30.0	74.9	90.0	16 800 *	78.3	89.2	15 100*				30.0
32.0	73.6	89.4	16 500 *	77.0	88.5	14 700*				32.0
34.0	72.3	88.7	16 200 *	75.7	87.8	14 400*	79.3	86.1	11 500*	34.0
36.0	71.0	87.9	15 900 *	74.3	87.0	14 100*	77.9	85.3	11 100*	36.0
38.0	69.6	87.1	15 600 *	72.9	86.2	13 800*	76.5	84.5	10 800*	38.0
40.0	68.3	86.2	15 300 *	71.6	85.3	13 500*	75.1	83.6	10 500*	40.0
44.0	65.5	84.3	14 600 *	68.8	83.3	13 000*	72.3	81.6	9 900*	44.0
48.0	62.6	82.1	14 000 *	65.9	81.1	12 600*	69.3	79.3	9 400*	48.0
52.0	59.7	79.6	13 100	62.9	78.6	12 100*	66.3	76.8	9 000*	52.0
56.0	56.7	76.9	11 200	59.9	75.9	11 700*	63.2	74.0	8 600*	56.0
60.0	53.6	73.8	9 600	56.7	72.7	10 200	59.9	70.8	8 200*	60.0
64.0	50.3	70.4	8 200	53.3	69.2	8 800	56.5	67.2	7 900*	64.0
68.0	46.8	66.5	7 000	49.8	65.3	7 500	52.8	63.2	7 700*	68.0
72.0	43.1	62.1	5 900	46.0	60.8	6 300	48.9	58.5	7 100	72.0
76.0	39.1	57.0	4 900	41.9	55.6	5 400				76.0
80.0	34.6	51.2	4 100	37.4	49.6	4 400				80.0
84.0	29.6	44.1	3 400							84.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
21.3	80.8	95.5	18 500 *							21.3
22.0	80.4	95.3	18 400 *							22.0
24.0	79.2	94.9	18 000 *							24.0
26.0	77.9	94.4	17 700 *							26.0
28.0	76.7	93.8	17 300 *	80.0	93.0	15 400*				28.0
30.0	75.4	93.2	17 000 *	78.7	92.4	15 100*				30.0
32.0	74.2	92.6	16 600 *	77.4	91.7	14 800*				32.0
34.0	72.9	91.9	16 300 *	76.1	91.0	14 500*	79.7	89.3	11 600*	34.0
36.0	71.6	91.2	16 000 *	74.8	90.3	14 200*	78.4	88.5	11 200*	36.0
38.0	70.3	90.4	15 700 *	73.5	89.5	14 000*	77.0	87.7	10 900*	38.0
40.0	69.0	89.5	15 400 *	72.2	88.6	13 700*	75.7	86.9	10 600*	40.0
44.0	66.3	87.7	14 800 *	69.5	86.7	13 100*	72.9	85.0	10 000*	44.0
48.0	63.6	85.6	14 200 *	66.8	84.6	12 700*	70.1	82.8	9 500*	48.0
52.0	60.8	83.2	12 800	63.9	82.2	12 200*	67.2	80.4	9 100*	52.0
56.0	57.9	80.6	10 900	61.0	79.6	11 600	64.2	77.7	8 700*	56.0
60.0	55.0	77.7	9 300	58.0	76.6	10 000	61.1	74.7	8 300*	60.0
64.0	51.8	74.4	7 900	54.8	73.3	8 500	57.9	71.3	8 000*	64.0
68.0	48.6	70.8	6 700	51.5	69.6	7 200	54.5	67.5	7 800*	68.0
72.0	45.1	66.7	5 600	48.0	65.4	6 100	50.8	63.2	6 900	72.0
76.0	41.4	62.0	4 700	44.2	60.7	5 100	46.9	58.3	5 800	76.0
80.0	37.4	56.7	3 800	40.1	55.2	4 200				80.0
84.0	32.9	50.4	3 100	35.5	48.7	3 400				84.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
22.9	80.2	98.3	18 300 *							22.9
24.0	79.5	98.0	18 100 *							24.0
26.0	78.3	97.5	17 800 *							26.0
28.0	77.1	97.0	17 400 *	80.3	96.1	15 500*				28.0
30.0	75.9	96.4	17 100*	79.1	95.5	15 200*				30.0
32.0	74.7	95.8	16 800 *	77.8	94.9	14 900*				32.0
34.0	73.4	95.1	16 500 *	76.6	94.2	14 600*	80.0	92.5	11 700*	34.0
36.0	72.2	94.4	16 200 *	75.3	93.5	14 300*	78.8	91.8	11 300*	36.0
38.0	71.0	93.7	15 800 *	74.1	92.7	14 000*	77.5	91.0	11 000*	38.0
40.0	69.7	92.8	15 600 *	72.8	91.9	13 800*	76.2	90.1	10 700*	40.0
44.0	67.1	91.0	15 000 *	70.2	90.1	13 300*	73.5	88.3	10 100*	44.0
48.0	64.5	89.0	14 300	67.6	88.1	12 800*	70.8	86.3	9 700*	48.0
52.0	61.8	86.8	12 400	64.9	85.8	12 400*	68.1	84.0	9 200*	52.0
56.0	59.1	84.3	10 600	62.1	83.3	11 400	65.2	81.4	8 800*	56.0
60.0	56.2	81.5	8 900	59.2	80.4	9 700	62.2	78.5	8 500*	60.0
64.0	53.3	78.4	7 500	56.2	77.3	8 200	59.2	75.3	8 200*	64.0
68.0	50.2	75.0	6 300	53.1	73.8	6 900	55.9	71.7	7 800	68.0
72.0	46.9	71.1	5 200	49.8	69.9	5 700	52.5	67.7	6 600	72.0
76.0	43.5	66.8	4 300	46.2	65.5	4 800	48.9	63.1	5 500	76.0
80.0	39.8	61.9	3 400	42.5	60.4	3 800				80.0
84.0	35.7	56.2	2 700	38.3	54.6	3 000				84.0
88.0	31.2	49.5	2 000							88.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
22.9	80.5	101.4	18 400 *							22.9
24.0	79.8	101.1	18 200 *							24.0
26.0	78.7	100.7	17 900 *							26.0
28.0	77.5	100.1	17 500 *	80.6	99.3	15 600*				28.0
30.0	76.3	99.6	17 200 *	79.4	98.7	15 300*				30.0
32.0	75.2	99.0	16 900 *	78.2	98.1	15 000*				32.0
34.0	74.0	98.3	16 600 *	77.0	97.4	14 700*	80.4	95.7	11 700*	34.0
36.0	72.8	97.7	16 300 *	75.8	96.7	14 500*	79.1	95.0	11 400*	36.0
38.0	71.6	96.9	16 000 *	74.6	96.0	14 200*	77.9	94.2	11 100*	38.0
40.0	70.3	96.1	15 700 *	73.4	95.2	13 900*	76.6	93.4	10 800*	40.0
44.0	67.9	94.4	15 200 *	70.9	93.5	13 400*	74.1	91.6	10 200*	44.0
48.0	65.4	92.5	14 300	68.3	91.5	13 000*	71.5	89.7	9 700*	48.0
52.0	62.8	90.3	12 100	65.7	89.3	12 500	68.8	87.5	9 300*	52.0
56.0	60.1	87.9	10 200	63.0	86.9	11 100	66.1	85.0	8 900*	56.0
60.0	57.4	85.3	8 600	60.3	84.2	9 400	63.3	82.2	8 600*	60.0
64.0	54.6	82.3	7 200	57.4	81.2	7 900	60.3	79.2	8 300*	64.0
68.0	51.7	79.0	6 000	54.5	77.9	6 600	57.3	75.8	7 600	68.0
72.0	48.6	75.4	4 900	51.4	74.2	5 400	54.1	72.0	6 300	72.0
76.0	45.4	71.3	3 900	48.1	70.0	4 400	50.7	67.8	5 200	76.0
80.0	41.9	66.8	3 100	44.6	65.4	3 500	47.0	63.0	4 200	80.0
84.0	38.2	61.6	2 300	40.8	60.1	2 700				84.0
88.0				36.6	53.9	1 900				88.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
73.2m (240 Ft.) BOOM										
22.9	80.8	104.5	18 500 *							22.9
24.0	80.2	104.2	18 300 *							24.0
26.0	79.0	103.8	18 000 *							26.0
28.0	77.9	103.3	17 600 *							28.0
30.0	76.7	102.8	17 300 *	79.7	101.8	15 400*				30.0
32.0	75.6	102.2	17 000 *	78.6	101.3	15 100*				32.0
34.0	74.5	101.6	16 700 *	77.4	100.6	14 800*	80.7	98.8	11 800*	34.0
36.0	73.3	100.9	16 400 *	76.3	100.0	14 600*	79.5	98.2	11 500*	36.0
38.0	72.1	100.2	16 200 *	75.1	99.2	14 300*	78.3	97.4	11 200*	38.0
40.0	70.9	99.4	15 900 *	73.9	98.5	14 100*	77.1	96.7	10 900*	40.0
44.0	68.6	97.7	15 300 *	71.5	96.8	13 500*	74.6	95.0	10 300*	44.0
48.0	66.1	95.9	13 800	69.0	94.9	13 000*	72.1	93.1	9 800*	48.0
52.0	63.7	93.8	11 700	66.5	92.8	12 600	69.5	90.9	9 400*	52.0
56.0	61.1	91.5	9 800	64.0	90.5	10 700	66.9	88.6	9 000*	56.0
60.0	58.5	88.9	8 200	61.3	87.9	9 000	64.2	85.9	8 700*	60.0
64.0	55.8	86.1	6 800	58.6	85.0	7 500	61.4	83.0	8 300*	64.0
68.0	53.0	83.0	5 600	55.8	81.9	6 200	58.5	79.8	7 300	68.0
72.0	50.1	79.6	4 500	52.8	78.4	5 100	55.5	76.2	6 100	72.0
76.0	47.1	75.7	3 500	49.7	74.5	4 100	52.3	72.2	4 900	76.0
80.0	43.8	71.4	2 700	46.4	70.1	3 100	48.9	67.7	3 900	80.0
84.0				42.9	65.2	2 300				84.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

30.5m (100 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
24.4	80.2	107.3	18 400 *							24.4
26.0	79.3	106.9	18 100 *							26.0
28.0	78.2	106.4	17 700 *							28.0
30.0	77.1	105.9	17 400 *	80.0	105.0	15 400*				30.0
32.0	76.0	105.4	17 100 *	78.9	104.4	15 200*				32.0
34.0	74.9	104.8	16 800 *	77.8	103.8	14 900*				34.0
36.0	73.8	104.1	16 500 *	76.7	103.2	14 600*	79.8	101.3	11 600*	36.0
38.0	72.7	103.4	16 300 *	75.5	102.5	14 400*	78.6	100.6	11 300*	38.0
40.0	71.5	102.7	16 000 *	74.4	101.7	14 100*	77.5	99.9	11 000*	40.0
44.0	69.2	101.1	15 500 *	72.1	100.1	13 700*	75.1	98.3	10 400*	44.0
48.0	66.9	99.3	13 900	69.7	98.3	13 200*	72.7	96.4	9 900*	48.0
52.0	64.5	97.3	11 800	67.3	96.3	12 700	70.2	94.4	9 500*	52.0
56.0	62.0	95.0	10 000	64.8	94.0	10 900	67.7	92.1	9 100*	56.0
60.0	59.5	92.6	8 400	62.3	91.5	9 200	65.1	89.6	8 800*	60.0
64.0	56.9	89.9	6 900	59.6	88.8	7 700	62.4	86.8	8 400*	64.0
68.0	54.3	86.9	5 700	56.9	85.8	6 400	59.7	83.7	7 400	68.0
72.0	51.5	83.6	4 600	54.1	82.4	5 200	56.8	80.3	6 200	72.0
76.0	48.6	80.0	3 700	51.2	78.8	4 200	53.8	76.5	5 100	76.0
80.0	45.6	76.0	2 800	48.1	74.7	3 300	50.6	72.3	4 100	80.0
84.0	42.4	71.5	2 000	44.8	70.1	2 500	47.2	67.6	3 200	84.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.6m (130 Ft.) BOOM										
18.3	80.9	77.5	14 800 *							18.3
20.0	79.6	77.1	14 400 *							20.0
22.0	78.0	76.6	13 900 *							22.0
24.0	76.5	76.0	13 500 *							24.0
26.0	74.9	75.4	13 000 *	80.1	74.8	10 800*				26.0
28.0	73.4	74.7	12 600 *	78.5	74.1	10 400*				28.0
30.0	71.8	73.9	12 100 *	76.9	73.4	10 000*				30.0
32.0	70.1	73.1	11 700 *	75.3	72.6	9 700*				32.0
34.0	68.5	72.2	11 200 *	73.7	71.7	9 400*	78.7	70.0	8 100*	34.0
36.0	66.9	71.3	10 800 *	72.0	70.7	9 100*	77.0	69.0	7 900*	36.0
38.0	65.2	70.3	10 400 *	70.3	69.7	8 800*	75.3	68.0	7 700*	38.0
40.0	63.5	69.2	10 100 *	68.6	68.6	8 500*	73.5	66.9	7 400*	40.0
44.0	60.0	66.7	9 400 *	65.1	66.2	7 900*	69.9	64.3	7 000*	44.0
48.0	56.3	63.9	8 700 *	61.4	63.4	7 400*	66.1	61.5	6 600*	48.0
52.0	52.5	60.7	8 100 *	57.5	60.1	7 000*	62.1	58.1	6 300*	52.0
56.0	48.5	57.0	7 600 *	53.4	56.4	6 500*	57.9	54.3	6 000*	56.0
60.0	44.1	52.8	7 100 *	49.0	52.1	6 200*	53.2	49.8	5 700*	60.0
64.0	39.3	47.7	6 600 *	44.2	47.1	5 900*	48.1	44.5	5 500*	64.0
68.0	33.9	41.7	6 200 *	38.6	41.0	5 600*				68.0
42.7m (140 Ft.) BOOM										
19.8	80.1	80.3	14 600 *							19.8
20.0	80.0	80.2	14 600 *							20.0
22.0	78.5	79.7	14 100 *							22.0
24.0	77.0	79.2	13 600 *							24.0
26.0	75.5	78.6	13 200 *	80.5	78.0	10 900*				26.0
28.0	74.0	77.9	12 700 *	79.0	77.3	10 500*				28.0
30.0	72.5	77.2	12 300 *	77.5	76.6	10 200*				30.0
32.0	71.0	76.4	11 900 *	75.9	75.8	9 800*				32.0
34.0	69.4	75.6	11 500 *	74.3	75.0	9 500*	79.2	73.3	8 200*	34.0
36.0	67.8	74.7	11 100 *	72.8	74.1	9 200*	77.6	72.3	8 000*	36.0
38.0	66.2	73.7	10 700 *	71.1	73.1	8 900*	75.9	71.3	7 800*	38.0
40.0	64.6	72.7	10 300 *	69.5	72.1	8 600*	74.3	70.3	7 500*	40.0
44.0	61.3	70.3	9 600 *	66.2	69.7	8 100*	70.8	67.9	7 100*	44.0
48.0	57.8	67.7	8 900 *	62.7	67.1	7 600*	67.3	65.2	6 700*	48.0
52.0	54.2	64.7	8 400 *	59.1	64.1	7 100*	63.5	62.0	6 400*	52.0
56.0	50.5	61.2	7 800 *	55.2	60.6	6 700*	59.5	58.5	6 100*	56.0
60.0	46.4	57.3	7 300 *	51.2	56.7	6 300*	55.3	54.3	5 800*	60.0
64.0	42.1	52.7	6 900 *	46.8	52.1	6 000*	50.7	49.5	5 600*	64.0
68.0	37.3	47.3	6 500 *	41.9	46.6	5 800*	45.5	43.8	5 400*	68.0
72.0	31.8	40.8	6 100 *	36.3	40.0	5 500*				72.0



Liftcrane Jib Capacities

2250 SERIES 2

**Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating**

**Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s**

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.7m (150 Ft.) BOOM										
19.8	80.5	83.4	14 700 *							19.8
20.0	80.4	83.3	14 700 *							20.0
22.0	78.9	82.9	14 200 *							22.0
24.0	77.5	82.4	13 800 *							24.0
26.0	76.1	81.8	13 400 *							26.0
28.0	74.6	81.1	12 900 *	79.4	80.5	10 600 *				28.0
30.0	73.2	80.4	12 500 *	78.0	79.8	10 300 *				30.0
32.0	71.7	79.7	12 100 *	76.5	79.1	9 900 *				32.0
34.0	70.2	78.9	11 700 *	75.0	78.3	9 600 *	79.7	76.5	8 300 *	34.0
36.0	68.7	78.0	11 300 *	73.5	77.4	9 300 *	78.1	75.6	8 000 *	36.0
38.0	67.2	77.1	10 900 *	71.9	76.5	9 000 *	76.5	74.7	7 900 *	38.0
40.0	65.6	76.1	10 500 *	70.4	75.5	8 700 *	74.9	73.6	7 600 *	40.0
44.0	62.5	73.9	9 900 *	67.2	73.3	8 200 *	71.7	71.4	7 200 *	44.0
48.0	59.2	71.4	9 200 *	63.9	70.8	7 800 *	68.3	68.8	6 800 *	48.0
52.0	55.8	68.5	8 600 *	60.4	67.9	7 300 *	64.7	65.9	6 500 *	52.0
56.0	52.3	65.3	8 100 *	56.9	64.7	6 900 *	61.0	62.5	6 200 *	56.0
60.0	48.5	61.6	7 600 *	53.1	61.0	6 500 *	57.1	58.7	5 900 *	60.0
64.0	44.5	57.4	7 100 *	49.0	56.7	6 200 *	52.9	54.3	5 700 *	64.0
68.0	40.1	52.6	6 700 *	44.6	51.8	5 900 *	48.2	49.1	5 500 *	68.0
72.0	35.3	46.8	6 300 *	39.7	46.0	5 700 *				72.0
76.0	29.7	39.7	6 000 *	33.9	38.8	5 500 *				76.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.8m (160 Ft.) BOOM										
19.8	80.8	86.5	14 800 *							19.8
20.0	80.7	86.5	14 800 *							20.0
22.0	79.4	86.0	14 300 *							22.0
24.0	78.0	85.5	14 000 *							24.0
26.0	76.6	84.9	13 500 *							26.0
28.0	75.2	84.3	13 100 *	79.8	83.7	10 700*				28.0
30.0	73.8	83.7	12 700 *	78.4	83.0	10 400*				30.0
32.0	72.4	83.0	12 300 *	77.0	82.3	10 100*				32.0
34.0	70.9	82.2	11 900 *	75.5	81.5	9 800*	80.1	79.7	8 400*	34.0
36.0	69.5	81.4	11 500 *	74.1	80.7	9 500*	78.6	78.9	8 100*	36.0
38.0	68.0	80.5	11 100 *	72.6	79.8	9 200*	77.1	78.0	7 900*	38.0
40.0	66.6	79.5	10 800 *	71.1	78.9	8 900*	75.5	77.0	7 700*	40.0
44.0	63.5	77.4	10 100 *	68.1	76.7	8 400*	72.4	74.8	7 300*	44.0
48.0	60.4	75.0	9 500 *	65.0	74.4	7 900*	69.2	72.4	6 900*	48.0
52.0	57.2	72.3	8 900 *	61.7	71.7	7 500*	65.9	69.6	6 600*	52.0
56.0	53.9	69.3	8 300 *	58.3	68.6	7 100*	62.4	66.5	6 300*	56.0
60.0	50.4	65.8	7 800 *	54.8	65.1	6 700*	58.7	62.9	6 000*	60.0
64.0	46.6	61.9	7 300 *	51.0	61.2	6 300*	54.8	58.8	5 800*	64.0
68.0	42.6	57.4	6 900 *	46.9	56.7	6 100*	50.5	54.1	5 600*	68.0
72.0	38.3	52.3	6 500 *	42.5	51.5	5 800*	45.8	48.5	5 400*	72.0
76.0	33.4	46.1	6 200 *	37.5	45.2	5 600*				76.0
80.0	27.6	38.5	5 700 *							80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.8m (170 Ft.) BOOM										
21.3	80.2	89.3	14 600 *							21.3
22.0	79.7	89.1	14 500 *							22.0
24.0	78.4	88.7	14 100 *							24.0
26.0	77.1	88.1	13 700 *							26.0
28.0	75.7	87.5	13 200 *	80.2	86.8	10 800 *				28.0
30.0	74.4	86.9	12 800 *	78.8	86.2	10 400 *				30.0
32.0	73.0	86.2	12 500 *	77.5	85.5	10 200 *				32.0
34.0	71.6	85.5	12 100 *	76.1	84.8	9 900 *	80.4	82.9	8 400 *	34.0
36.0	70.2	84.7	11 700 *	74.7	84.0	9 600 *	79.0	82.1	8 200 *	36.0
38.0	68.8	83.8	11 400 *	73.3	83.1	9 300 *	77.6	81.3	8 000 *	38.0
40.0	67.4	82.9	11 000 *	71.8	82.2	9 000 *	76.1	80.3	7 800 *	40.0
44.0	64.5	80.9	10 300 *	68.9	80.2	8 500 *	73.1	78.3	7 300 *	44.0
48.0	61.6	78.6	9 700 *	65.9	77.9	8 000 *	70.1	75.9	7 000 *	48.0
52.0	58.5	76.0	9 100 *	62.8	75.3	7 600 *	66.9	73.3	6 700 *	52.0
56.0	55.3	73.1	8 500 *	59.6	72.5	7 200 *	63.6	70.3	6 400 *	56.0
60.0	52.0	69.9	8 000 *	56.3	69.2	6 800 *	60.1	66.9	6 100 *	60.0
64.0	48.5	66.2	7 600 *	52.8	65.5	6 500 *	56.5	63.1	5 900 *	64.0
68.0	44.8	62.1	7 200 *	49.0	61.3	6 200 *	52.5	58.8	5 700 *	68.0
72.0	40.8	57.3	6 800 *	45.0	56.6	6 000 *	48.3	53.7	5 500 *	72.0
76.0	36.4	51.8	6 300 *	40.5	51.0	5 700 *				76.0
80.0	31.5	45.2	5 400 *	35.4	44.3	5 500 *				80.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.9m (180 Ft.) BOOM										
21.3	80.5	92.4	14 700 *							21.3
22.0	80.1	92.3	14 600 *							22.0
24.0	78.8	91.8	14 200 *							24.0
26.0	77.5	91.3	13 800 *							26.0
28.0	76.2	90.7	13 400 *	80.5	90.0	10 900*				28.0
30.0	74.9	90.1	13 000 *	79.2	89.4	10 500*				30.0
32.0	73.6	89.4	12 700 *	77.9	88.7	10 200*				32.0
34.0	72.3	88.7	12 200 *	76.6	88.0	9 900*				34.0
36.0	70.9	87.9	11 900 *	75.2	87.2	9 700*	79.4	85.4	8 300*	36.0
38.0	69.6	87.1	11 500 *	73.9	86.4	9 400*	78.0	84.5	8 000*	38.0
40.0	68.2	86.2	11 200 *	72.5	85.5	9 200*	76.6	83.6	7 900*	40.0
44.0	65.5	84.3	10 500 *	69.7	83.6	8 600*	73.8	81.6	7 400*	44.0
48.0	62.6	82.1	9 900 *	66.8	81.4	8 200*	70.8	79.4	7 100*	48.0
52.0	59.7	79.7	9 300 *	63.9	79.0	7 700*	67.8	76.9	6 800*	52.0
56.0	56.7	76.9	8 800 *	60.8	76.2	7 300*	64.7	74.1	6 500*	56.0
60.0	53.5	73.9	8 300 *	57.7	73.1	7 000*	61.4	70.9	6 200*	60.0
64.0	50.3	70.4	7 800 *	54.4	69.7	6 600*	58.0	67.3	6 000*	64.0
68.0	46.8	66.5	7 400 *	50.8	65.8	6 300*	54.3	63.2	5 800*	68.0
72.0	43.1	62.2	6 900 *	47.1	61.4	6 100*	50.4	58.6	5 600*	72.0
76.0	39.1	57.1	5 900 *	43.0	56.3	5 800*	46.1	53.3	5 400*	76.0
80.0	34.7	51.2	5 100 *	38.5	50.3	5 600				80.0
84.0	29.6	44.2	4 300 *							84.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.9m (190 Ft.) BOOM										
21.3	80.8	95.5	14 800 *							21.3
22.0	80.4	95.4	14 700 *							22.0
24.0	79.2	94.9	14 300 *							24.0
26.0	77.9	94.4	13 900 *							26.0
28.0	76.7	93.9	13 500 *							28.0
30.0	75.4	93.3	13 100 *	79.6	92.6	10 600 *				30.0
32.0	74.1	92.6	12 800 *	78.3	91.9	10 300 *				32.0
34.0	72.9	92.0	12 400 *	77.0	91.2	10 000 *				34.0
36.0	71.6	91.2	12 100 *	75.7	90.5	9 800 *	79.8	88.6	8 300 *	36.0
38.0	70.3	90.4	11 700 *	74.4	89.7	9 500 *	78.5	87.8	8 100 *	38.0
40.0	69.0	89.6	11 400 *	73.1	88.9	9 200 *	77.1	86.9	7 900 *	40.0
44.0	66.3	87.7	10 700 *	70.4	87.0	8 800 *	74.4	85.0	7 500 *	44.0
48.0	63.6	85.6	10 100 *	67.7	84.9	8 300 *	71.5	82.9	7 200 *	48.0
52.0	60.8	83.3	9 500 *	64.9	82.6	7 900 *	68.7	80.5	6 800 *	52.0
56.0	57.9	80.7	9 000 *	62.0	79.9	7 500 *	65.7	77.8	6 500 *	56.0
60.0	54.9	77.8	8 500 *	58.9	77.0	7 100 *	62.6	74.7	6 300 *	60.0
64.0	51.8	74.5	8 000 *	55.8	73.7	6 800 *	59.3	71.4	6 100 *	64.0
68.0	48.6	70.8	7 500 *	52.5	70.1	6 500 *	55.9	67.6	5 900 *	68.0
72.0	45.1	66.7	6 400	49.0	65.9	6 200 *	52.3	63.3	5 700 *	72.0
76.0	41.4	62.1	5 500	45.3	61.3	5 900 *	48.3	58.4	5 500 *	76.0
80.0	37.4	56.8	4 700	41.2	55.9	5 400				80.0
84.0	32.9	50.5	3 900	36.6	49.5	4 500				84.0
88.0	27.8	42.9	3 200							88.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
61.0m (200 Ft.) BOOM										
22.9	80.2	98.3	14 600 *							22.9
24.0	79.5	98.0	14 400 *							24.0
26.0	78.3	97.6	14 000 *							26.0
28.0	77.1	97.0	13 700 *							28.0
30.0	75.9	96.5	13 300 *	79.9	95.7	10 700*				30.0
32.0	74.7	95.8	12 900 *	78.7	95.1	10 400*				32.0
34.0	73.4	95.2	12 600 *	77.5	94.4	10 100*				34.0
36.0	72.2	94.5	12 200 *	76.2	93.7	9 900*	80.1	91.8	8 400*	36.0
38.0	70.9	93.7	11 900 *	74.9	93.0	9 600*	78.8	91.0	8 200*	38.0
40.0	69.7	92.9	11 500 *	73.7	92.1	9 400*	77.5	90.2	8 000*	40.0
44.0	67.1	91.1	10 900 *	71.1	90.4	8 900*	74.9	88.3	7 600*	44.0
48.0	64.5	89.1	10 300 *	68.5	88.4	8 400*	72.2	86.3	7 200*	48.0
52.0	61.8	86.8	9 700 *	65.7	86.1	8 000*	69.4	84.0	7 000*	52.0
56.0	59.1	84.3	9 200 *	63.0	83.6	7 700*	66.6	81.4	6 700*	56.0
60.0	56.2	81.6	8 700 *	60.1	80.8	7 300*	63.6	78.5	6 400*	60.0
64.0	53.3	78.5	8 200 *	57.1	77.7	6 900*	60.6	75.3	6 200*	64.0
68.0	50.2	75.0	7 100	54.0	74.2	6 600*	57.3	71.8	5 900*	68.0
72.0	46.9	71.2	6 100	50.7	70.4	6 300*	53.9	67.7	5 700*	72.0
76.0	43.5	66.8	5 100	47.2	66.0	5 900	50.3	63.2	5 600*	76.0
80.0	39.8	61.9	4 300	43.5	61.0	5 000	46.3	58.0	5 400	80.0
84.0	35.8	56.3	3 500	39.4	55.3	4 200				84.0
88.0	31.2	49.6	2 800	34.7	48.6	3 400				88.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
64.0m (210 Ft.) BOOM										
22.9	80.5	101.4	14 700 *							22.9
24.0	79.8	101.2	14 500 *							24.0
26.0	78.7	100.7	14 200 *							26.0
28.0	77.5	100.2	13 800 *							28.0
30.0	76.3	99.6	13 500 *	80.2	98.9	10 800*				30.0
32.0	75.1	99.0	13 100 *	79.0	98.3	10 500*				32.0
34.0	73.9	98.4	12 800 *	77.9	97.6	10 200*				34.0
36.0	72.7	97.7	12 400 *	76.6	96.9	10 000*				36.0
38.0	71.5	97.0	12 000 *	75.4	96.2	9 700*	79.2	94.2	8 200*	38.0
40.0	70.3	96.2	11 700 *	74.2	95.4	9 500*	78.0	93.4	8 000*	40.0
44.0	67.9	94.5	11 100 *	71.7	93.7	9 000*	75.4	91.7	7 700*	44.0
48.0	65.3	92.5	10 500 *	69.2	91.8	8 600*	72.8	89.7	7 300*	48.0
52.0	62.8	90.4	9 900 *	66.6	89.6	8 100*	70.2	87.5	7 000*	52.0
56.0	60.1	88.0	9 400 *	63.9	87.2	7 700*	67.4	85.0	6 700*	56.0
60.0	57.4	85.3	8 900 *	61.2	84.5	7 400*	64.6	82.3	6 500*	60.0
64.0	54.6	82.4	8 100	58.3	81.6	7 100*	61.7	79.2	6 300*	64.0
68.0	51.7	79.1	6 900	55.4	78.3	6 800*	58.6	75.8	6 000*	68.0
72.0	48.6	75.4	5 800	52.3	74.6	6 500*	55.4	72.0	5 800*	72.0
76.0	45.4	71.4	4 800	49.0	70.5	5 800	52.0	67.8	5 700*	76.0
80.0	41.9	66.8	4 000	45.5	65.9	4 800	48.4	63.0	5 300	80.0
84.0	38.2	61.6	3 200	41.8	60.7	3 900				84.0
88.0	34.1	55.7	2 500	37.6	54.7	3 200				88.0
92.0	29.5	48.6	2 000							92.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
67.1m (220 Ft.) BOOM										
22.9	80.8	104.5	14 800 *							22.9
24.0	80.1	104.3	14 700 *							24.0
26.0	79.0	103.8	14 300 *							26.0
28.0	77.9	103.3	13 900 *							28.0
30.0	76.7	102.8	13 600 *							30.0
32.0	75.6	102.2	13 200 *	79.4	101.4	10 600*				32.0
34.0	74.4	101.6	12 900 *	78.2	100.8	10 300*				34.0
36.0	73.3	100.9	12 500 *	77.1	100.2	10 100*				36.0
38.0	72.1	100.2	12 200 *	75.9	99.4	9 800*	79.6	97.4	8 300*	38.0
40.0	70.9	99.5	11 900 *	74.7	98.7	9 600*	78.3	96.7	8 100*	40.0
44.0	68.5	97.8	11 300 *	72.3	97.0	9 100*	75.9	95.0	7 700*	44.0
48.0	66.1	95.9	10 700 *	69.8	95.2	8 700*	73.4	93.1	7 400*	48.0
52.0	63.6	93.9	10 100 *	67.3	93.1	8 300*	70.8	90.9	7 100*	52.0
56.0	61.1	91.5	9 600 *	64.8	90.8	7 900*	68.2	88.6	6 800*	56.0
60.0	58.5	89.0	9 000	62.2	88.2	7 500*	65.5	85.9	6 600*	60.0
64.0	55.8	86.2	7 700	59.4	85.4	7 200*	62.7	83.0	6 300*	64.0
68.0	53.0	83.1	6 500	56.6	82.3	6 900*	59.8	79.8	6 100*	68.0
72.0	50.1	79.6	5 400	53.7	78.8	6 500	56.8	76.2	5 900*	72.0
76.0	47.1	75.8	4 400	50.6	74.9	5 400	53.6	72.2	5 700*	76.0
80.0	43.8	71.5	3 600	47.3	70.6	4 500	50.2	67.7	4 900	80.0
84.0	40.4	66.7	2 800	43.9	65.8	3 600	46.5	62.7	4 000	84.0
88.0	36.7	61.3	2 200	40.1	60.3	2 800				88.0
92.0				35.9	53.8	2 100				92.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
70.1m (230 Ft.) BOOM										
24.4	80.2	107.3	14 700 *							24.4
26.0	79.3	107.0	14 400 *							26.0
28.0	78.2	106.5	14 100 *							28.0
30.0	77.1	106.0	13 700 *							30.0
32.0	76.0	105.4	13 300 *	79.7	104.6	10 700*				32.0
34.0	74.9	104.8	13 000 *	78.6	104.0	10 400*				34.0
36.0	73.8	104.2	12 700 *	77.4	103.4	10 200*				36.0
38.0	72.6	103.5	12 400 *	76.3	102.7	9 900*	79.9	100.6	8 400*	38.0
40.0	71.5	102.7	12 100 *	75.2	101.9	9 700*	78.7	99.9	8 200*	40.0
44.0	69.2	101.1	11 400 *	72.8	100.3	9 200*	76.3	98.2	7 800*	44.0
48.0	66.9	99.3	10 900 *	70.5	98.5	8 800*	73.9	96.4	7 500*	48.0
52.0	64.5	97.3	10 300 *	68.1	96.5	8 400*	71.5	94.4	7 200*	52.0
56.0	62.0	95.1	9 800 *	65.6	94.3	8 000*	68.9	92.1	6 900*	56.0
60.0	59.5	92.6	8 700 *	63.1	91.8	7 700*	66.3	89.6	6 600*	60.0
64.0	56.9	89.9	7 300 *	60.5	89.1	7 300*	63.7	86.8	6 400*	64.0
68.0	54.3	87.0	6 100 *	57.8	86.1	7 000*	60.9	83.7	6 200*	68.0
72.0	51.5	83.7	5 000 *	55.0	82.8	6 200 *	58.0	80.3	6 000*	72.0
76.0	48.6	80.1	4 100 *	52.1	79.2	5 100 *	55.0	76.5	5 700 *	76.0
80.0	45.6	76.0	3 200 *	49.0	75.1	4 200 *	51.8	72.3	4 700 *	80.0
84.0	42.4	71.5	2 500 *	45.8	70.6	3 300 *	48.4	67.6	3 800 *	84.0
88.0				42.3	65.5	2 600 *	44.8	62.2	2 900 *	88.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
73.2m (240 Ft.) BOOM										
24.4	80.5	110.4	14 700 *							24.4
26.0	79.6	110.1	14 400 *							26.0
28.0	78.6	109.6	14 100 *							28.0
30.0	77.5	109.1	13 800 *							30.0
32.0	76.4	108.6	13 500 *	80.0	107.8	10 700*				32.0
34.0	75.3	108.0	13 200 *	78.9	107.2	10 500*				34.0
36.0	74.2	107.4	12 800 *	77.8	106.6	10 200*				36.0
38.0	73.1	106.7	12 500 *	76.7	105.9	10 000*				38.0
40.0	72.0	106.0	12 200 *	75.6	105.2	9 700*	79.1	103.1	8 200*	40.0
44.0	69.8	104.4	11 600 *	73.3	103.6	9 300*	76.8	101.5	7 900*	44.0
48.0	67.5	102.7	11 000 *	71.1	101.9	8 900*	74.4	99.7	7 600*	48.0
52.0	65.2	100.7	10 400 *	68.7	99.9	8 500*	72.0	97.8	7 200*	52.0
56.0	62.9	98.6	9 900	66.4	97.8	8 100*	69.6	95.6	7 000*	56.0
60.0	60.5	96.2	8 400	63.9	95.4	7 800*	67.1	93.1	6 700*	60.0
64.0	58.0	93.6	6 900	61.4	92.8	7 400*	64.6	90.5	6 500*	64.0
68.0	55.4	90.8	5 700	58.8	90.0	7 000	61.9	87.5	6 300*	68.0
72.0	52.8	87.7	4 700	56.2	86.8	5 800	59.2	84.3	6 100*	72.0
76.0	50.0	84.2	3 700	53.4	83.3	4 800	56.3	80.7	5 400	76.0
80.0	47.2	80.4	2 800	50.5	79.5	3 800	53.3	76.7	4 400	80.0
84.0	44.2	76.2	2 100	47.5	75.3	3 000	50.1	72.3	3 500	84.0
88.0				44.2	70.5	2 200	46.7	67.3	2 600	88.0



Liftcrane Jib Capacities

2250 SERIES 2

Jib No. 132 with 6 096 mm Strut on
Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds
(all Jib Lengths)
10 m/s

36.6m (120 Ft.) JIB

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			30 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg	Jib Point Elev. Meters	Jib Capacity Kilograms	
76.2m (250 Ft.) BOOM										
24.4	80.7	113.5	14 800 *							24.4
26.0	79.9	113.2	14 600 *							26.0
28.0	78.9	112.8	14 200 *							28.0
30.0	77.8	112.3	13 900 *							30.0
32.0	76.8	111.7	13 600 *							32.0
34.0	75.7	111.2	13 200 *	79.2	110.3	10 600*				34.0
36.0	74.7	110.6	12 900 *	78.2	109.7	10 300*				36.0
38.0	73.6	109.9	12 700 *	77.1	109.1	10 100*				38.0
40.0	72.5	109.2	12 300 *	76.0	108.4	9 800*	79.4	106.3	8 300*	40.0
44.0	70.4	107.7	11 700 *	73.8	106.9	9 400*	77.1	104.8	7 900*	44.0
48.0	68.2	106.0	11 200 *	71.6	105.2	9 000*	74.9	103.0	7 600*	48.0
52.0	66.0	104.1	10 600 *	69.4	103.3	8 600*	72.6	101.1	7 300*	52.0
56.0	63.7	102.1	10 000	67.1	101.3	8 200*	70.2	99.0	7 000*	56.0
60.0	61.3	99.8	8 400	64.7	99.0	7 900*	67.8	96.7	6 800*	60.0
64.0	59.0	97.3	7 100	62.3	96.5	7 600*	65.4	94.1	6 600*	64.0
68.0	56.5	94.6	5 800	59.8	93.7	7 100	62.8	91.3	6 300*	68.0
72.0	54.0	91.6	4 800	57.3	90.7	6 000	60.2	88.2	6 100*	72.0
76.0	51.4	88.3	3 800	54.6	87.4	4 900	57.5	84.8	5 600	76.0
80.0	48.6	84.7	3 000	51.9	83.8	4 000	54.6	81.0	4 500	80.0
84.0	45.8	80.7	2 200	49.0	79.7	3 100	51.6	76.9	3 600	84.0
88.0				46.0	75.3	2 300	48.5	72.2	2 800	88.0
92.0							45.1	67.0	2 000	92.0