




Liftcrane Boom Capacities

Boom No. 22E With Open Throat Top
67 860 kg Counterweight
360 Degree Rating

Meets
ANSI B30.5
Requirements



999 SERIES 1

LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and do not exceed 75% of a static tipping load. Capacities based on structural competence are denoted by an asterisk (*).

Upper boom point capacity for liftcrane service with single part whip line or combination of two single part lines is 13 380 kg. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of jib, all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves, is considered part of main boom load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.


OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging No. 196151 and Wire Rope Specification chart No. 8391-A. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

MACHINE TRAVEL: Machine to travel on a firm, level and uniformly supporting surface and boom within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specification chart No. 8392-A.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 8 585 mm crawlers, 1 219 mm treads, 3 124 mm retractable gantry, 9 144 mm live mast, 20 part boom hoist reeving, four 35 mm boom pendants and 67 860 kg counterweight.




67 860 kg Crane Counterweight
6 Side Boxes - 1 Center Box

Deduct From Capacities When Jib Is Attached	
Jib Length	Jib No. 123
9.1m	1 130 kg
12.2m	1 410 kg
15.2m	1 680 kg
18.3m	2 000 kg

Consult jib chart for jib capacities.
Upper boom point cannot be used when jib is attached.

Auxiliary Drum Deduct
Deduct 1 810 kg from boom capacities when boom butt is equipped with auxiliary drum.

Boom Catwalks Deduct
Deduct 300 kg from capacities when boom catwalks are attached.



Liftcrane Boom Capacities

Boom No. 22E With Open Throat Top
 67 860 kg Counterweight
 360 Degree Rating

Meets
ANSI B30.5
 Requirements


999 SERIES 1

Maximum Boom And Jib Lengths Lifted Unassisted Without Auxiliary Drum In Boom Butt			
Over End Of Blocked Crawlers		Over Side Of Crawlers	
Boom Length	Jib No. 123	Boom Length	Jib No. 123
(a)(b) 79.2m	—	67.1m	—
(a) 76.2m	—	64.0m	12.2m
73.2m	—	61.0m	18.3m
70.1m	12.2m		
(b) 70.1m	15.2m		
67.1m	18.3m		

Load block, hook and weight ball on ground at start.
 (a) Upper boom point cannot be used on 79.2m and 76.2m boom. Wire rope guide assembly No. 179061 upper and middle sheaves and shafts or assembly No. 92671 upper sheave and shaft must be removed on 79.2m boom when lifted over end of blocked crawlers.
 (b) When boom catwalks are attached, machine must be equipped with optional lowerworks jacking cylinders.

Maximum Boom and Jib Lengths Lifted Unassisted With Auxiliary Drum In Boom Butt			
Over End Of Blocked Crawlers		Over Side Of Crawlers	
Boom Length	Jib No. 123	Boom Length	Jib No. 123
(a) 76.2m	—	67.1m	—
73.2m	—	64.0m	9.1m
70.1m	12.2m	61.0m	18.3m
67.1m	18.3m		

Load block, hook and weight ball on ground at start.
 (a) Upper boom point cannot be used on 76.2m boom.



Liftcrane Boom Capacities

Boom No. 22E With Open Throat Top
67 860 kg Counterweight
360 Degree Rating


Meets
ANSI B30.5
Requirements

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
21.3m (70 Ft.) BOOM			
4.6	81.8	23.6	196 800 *
5.0	80.6	23.5	181 200 *
5.5	79.3	23.4	165 700 *
6.0	77.9	23.3	152 600 *
7.0	75.1	23.1	131 500 *
8.0	72.3	22.8	108 300
9.0	69.5	22.4	89 200
10.0	66.6	22.0	75 600
11.0	63.6	21.6	65 500
12.0	60.6	21.0	57 600
13.0	57.5	20.4	51 300
14.0	54.2	19.8	46 100
15.0	50.8	19.0	41 800
16.0	47.3	18.1	38 100
18.0	39.4	16.0	32 300
20.0	30.0	13.1	27 800
24.4m (80 Ft.) BOOM			
5.2	81.4	26.6	174 900 *
5.5	80.6	26.5	165 400 *
6.0	79.4	26.4	152 300 *
7.0	77.0	26.2	131 200 *
8.0	74.6	26.0	108 400
9.0	72.1	25.7	89 200
10.0	69.7	25.3	75 700
11.0	67.1	24.9	65 500
12.0	64.6	24.5	57 600
13.0	61.9	24.0	51 200
14.0	59.2	23.4	46 000
15.0	56.5	22.8	41 800
16.0	53.6	22.1	38 100
18.0	47.5	20.4	32 200
20.0	40.7	18.4	27 700
22.0	32.9	15.7	24 200
24.0	22.8	11.9	21 300
27.4m (90 Ft.) BOOM			
5.5	81.7	29.6	165 500 *
6.0	80.6	29.5	152 000 *
7.0	78.5	29.3	130 900 *
8.0	76.3	29.1	108 500
9.0	74.2	28.9	89 300
10.0	72.0	28.5	75 600
11.0	69.8	28.2	65 400
12.0	67.5	27.8	57 500
13.0	65.3	27.4	51 100
14.0	62.9	26.9	46 000
15.0	60.6	26.4	41 600
16.0	58.1	25.8	38 000
18.0	53.1	24.4	32 100
20.0	47.7	22.7	27 600
22.0	41.7	20.7	24 100
24.0	35.0	18.2	21 200
26.0	26.8	14.8	18 800

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
30.5m (100 Ft.) BOOM			
5.8	82.0	32.6	157 000 *
6.0	81.6	32.6	151 800 *
7.0	79.7	32.4	130 700 *
8.0	77.7	32.2	108 700
9.0	75.8	32.0	89 300
10.0	73.9	31.7	75 700
11.0	71.9	31.4	65 500
12.0	69.9	31.1	57 500
13.0	67.9	30.7	51 100
14.0	65.8	30.3	46 000
15.0	63.8	29.8	41 600
16.0	61.6	29.3	37 900
18.0	57.3	28.1	32 000
20.0	52.7	26.7	27 600
22.0	47.8	25.0	24 000
24.0	42.5	23.0	21 100
26.0	36.6	20.6	18 700
28.0	29.7	17.6	16 700
30.0	20.9	13.3	15 000
33.5m (110 Ft.) BOOM			
6.7	81.1	35.6	135 900 *
7.0	80.6	35.5	130 500 *
8.0	78.9	35.4	108 700
9.0	77.1	35.1	89 300
10.0	75.4	34.9	75 600
11.0	73.6	34.6	65 300
12.0	71.8	34.3	57 400
13.0	70.0	34.0	51 000
14.0	68.2	33.6	45 800
15.0	66.3	33.2	41 400
16.0	64.4	32.7	37 800
18.0	60.6	31.7	31 900
20.0	56.6	30.4	27 400
22.0	52.4	29.0	23 800
24.0	47.9	27.3	20 900
26.0	43.1	25.4	18 600
28.0	37.8	23.0	16 600
30.0	31.9	20.2	14 800
32.0	24.6	16.4	13 300
36.6m (120 Ft.) BOOM			
6.7	81.9	38.7	135 600 *
7.0	81.4	38.6	130 200 *
8.0	79.8	38.5	108 600
9.0	78.2	38.3	89 200
10.0	76.6	38.0	75 500
11.0	75.0	37.8	65 200
12.0	73.4	37.5	57 200
13.0	71.7	37.2	50 900
14.0	70.1	36.8	45 600
15.0	68.4	36.5	41 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
36.6m (120 Ft.) BOOM			
16.0	66.7	36.0	37 600
18.0	63.2	35.1	31 700
20.0	59.7	34.0	27 200
22.0	56.0	32.8	23 700
24.0	52.1	31.3	20 800
26.0	48.0	29.6	18 400
28.0	43.6	27.7	16 400
30.0	38.9	25.4	14 700
32.0	33.6	22.7	13 200
34.0	27.4	19.3	11 900
36.0	19.5	14.7	10 700
39.6m (130 Ft.) BOOM			
7.3	81.6	41.7	124 300 *
8.0	80.6	41.6	108 700
9.0	79.1	41.4	89 200
10.0	77.6	41.2	75 500
11.0	76.2	40.9	65 200
12.0	74.7	40.7	57 200
13.0	73.2	40.4	50 900
14.0	71.6	40.1	45 600
15.0	70.1	39.7	41 300
16.0	68.6	39.3	37 600
18.0	65.4	38.5	31 700
20.0	62.2	37.5	27 200
22.0	58.9	36.4	23 700
24.0	55.4	35.1	20 800
26.0	51.9	33.6	18 400
28.0	48.1	31.9	16 400
30.0	44.1	30.0	14 700
32.0	39.7	27.8	13 200
34.0	35.0	25.2	11 900
36.0	29.5	22.0	10 700
38.0	23.0	17.9	9 700



Liftcrane Boom Capacities

Boom No. 22E With Open Throat Top
67 860 kg Counterweight
360 Degree Rating


**Meets
ANSI B30.5
Requirements**

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
42.7m (140 Ft.) BOOM			
7.9	81.4	44.6	110 300
8.0	81.3	44.6	108 700
9.0	79.9	44.5	89 100
10.0	78.5	44.3	75 400
11.0	77.2	44.1	65 100
12.0	75.8	43.8	57 100
13.0	74.4	43.6	50 700
14.0	73.0	43.3	45 500
15.0	71.6	42.9	41 100
16.0	70.2	42.6	37 400
18.0	67.3	41.8	31 600
20.0	64.3	40.9	27 100
22.0	61.3	39.9	23 500
24.0	58.2	38.7	20 600
26.0	55.0	37.4	18 200
28.0	51.7	35.9	16 200
30.0	48.1	34.2	14 500
32.0	44.4	32.3	13 100
34.0	40.4	30.1	11 800
36.0	36.1	27.6	10 600
38.0	31.3	24.6	9 600
40.0	25.6	20.9	8 700
42.0	18.5	16.0	7 900
45.7m (150 Ft.) BOOM			
7.9	82.0	47.7	109 000 *
8.0	81.9	47.7	107 600
9.0	80.6	47.6	89 200
10.0	79.3	47.4	75 300
11.0	78.0	47.2	65 000
12.0	76.8	47.0	57 000
13.0	75.5	46.7	50 500
14.0	74.2	46.4	45 300
15.0	72.9	46.1	41 000
16.0	71.5	45.8	37 200
18.0	68.9	45.1	31 400
20.0	66.2	44.3	26 800
22.0	63.4	43.3	23 300
24.0	60.6	42.3	20 400
26.0	57.6	41.1	18 000
28.0	54.6	39.7	16 000
30.0	51.5	38.2	14 300
32.0	48.2	36.5	12 800
34.0	44.7	34.6	11 500
36.0	41.1	32.5	10 400
38.0	37.1	30.0	9 400
40.0	32.7	27.2	8 500
42.0	27.7	23.7	7 600
44.0	21.7	19.4	6 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
48.8m (160 Ft.) BOOM			
8.5	81.7	50.7	97 100
9.0	81.2	50.7	89 200
10.0	80.0	50.5	75 100
11.0	78.8	50.3	64 800
12.0	77.6	50.1	56 800
13.0	76.4	49.9	50 400
14.0	75.2	49.6	45 100
15.0	74.0	49.3	40 800
16.0	72.7	49.0	37 000
18.0	70.3	48.4	31 200
20.0	67.7	47.6	26 600
22.0	65.2	46.7	23 100
24.0	62.6	45.7	20 200
26.0	59.9	44.6	17 800
28.0	57.1	43.4	15 800
30.0	54.3	42.1	14 100
32.0	51.3	40.5	12 700
34.0	48.2	38.8	11 400
36.0	45.0	37.0	10 200
38.0	41.6	34.8	9 200
40.0	37.9	32.4	8 300
42.0	33.9	29.7	7 500
44.0	29.4	26.4	6 700
46.0	24.2	22.5	6 100
51.8m (170 Ft.) BOOM			
9.1	81.5	53.7	86 600
10.0	80.6	53.6	75 100
11.0	79.5	53.4	64 700
12.0	78.3	53.2	56 700
13.0	77.2	53.0	50 300
14.0	76.1	52.8	45 000
15.0	74.9	52.5	40 700
16.0	73.8	52.2	37 000
18.0	71.5	51.6	31 000
20.0	69.1	50.9	26 600
22.0	66.7	50.1	23 000
24.0	64.3	49.1	20 100
26.0	61.8	48.1	17 700
28.0	59.3	47.0	15 700
30.0	56.7	45.7	14 000
32.0	54.0	44.4	12 500
34.0	51.2	42.8	11 200
36.0	48.3	41.1	10 100
38.0	45.3	39.3	9 100
40.0	42.1	37.2	8 200
42.0	38.6	34.8	7 400
44.0	34.9	32.1	6 600
46.0	30.9	29.0	6 000
48.0	26.2	25.4	5 300
50.0	20.7	20.8	4 800

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
54.9m (180 Ft.) BOOM			
9.1	82.0	56.8	86 500
10.0	81.1	56.7	74 900
11.0	80.1	56.5	64 600
12.0	79.0	56.3	56 500
13.0	77.9	56.1	50 100
14.0	76.9	55.9	44 900
15.0	75.8	55.6	40 500
16.0	74.7	55.4	36 800
18.0	72.5	54.8	30 900
20.0	70.3	54.1	26 400
22.0	68.1	53.4	22 800
24.0	65.8	52.5	19 900
26.0	63.5	51.6	17 500
28.0	61.1	50.5	15 500
30.0	58.7	49.4	13 800
32.0	56.3	48.1	12 300
34.0	53.7	46.7	11 000
36.0	51.1	45.1	9 900
38.0	48.3	43.4	8 900
40.0	45.5	41.6	8 000
42.0	42.5	39.5	7 200
44.0	39.3	37.2	6 500
46.0	35.8	34.6	5 800
48.0	32.1	31.6	5 200
50.0	27.9	28.2	4 600
52.0	23.1	24.0	4 100



Liftcrane Boom Capacities

Boom No. 22E With Open Throat Top
67 860 kg Counterweight
360 Degree Rating


**Meets
 ANSI B30.5
 Requirements**

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
57.9m (190 Ft.) BOOM			
9.8	81.8	59.8	77 900
10.0	81.6	59.7	75 000
11.0	80.6	59.6	64 500
12.0	79.6	59.4	56 400
13.0	78.6	59.2	50 000
14.0	77.6	59.0	44 700
15.0	76.5	58.8	40 300
16.0	75.5	58.5	36 600
18.0	73.5	58.0	30 700
20.0	71.4	57.3	26 100
22.0	69.3	56.6	22 600
24.0	67.2	55.8	19 700
26.0	65.0	54.9	17 300
28.0	62.8	54.0	15 300
30.0	60.5	52.9	13 600
32.0	58.2	51.7	12 100
34.0	55.9	50.4	10 800
36.0	53.5	49.0	9 700
38.0	51.0	47.4	8 700
40.0	48.4	45.7	7 800
42.0	45.7	43.9	7 000
44.0	42.8	41.8	6 200
46.0	39.8	39.5	5 600
48.0	36.6	37.0	5 000
50.0	33.2	34.1	4 400
52.0	29.4	30.8	3 900
54.0	25.0	27.0	3 400
56.0	19.8	22.1	2 900
61.0m (200 Ft.) BOOM			
10.4	81.7	62.8	70 600
11.0	81.1	62.7	64 300
12.0	80.1	62.5	56 200
13.0	79.1	62.3	49 800
14.0	78.2	62.1	44 500
15.0	77.2	61.9	40 100
16.0	76.3	61.7	36 400
18.0	74.3	61.2	30 500
20.0	72.4	60.6	26 000
22.0	70.4	59.9	22 400
24.0	68.4	59.1	19 500
26.0	66.3	58.3	17 100
28.0	64.3	57.4	15 100
30.0	62.2	56.4	13 400
32.0	60.0	55.3	11 900
34.0	57.8	54.0	10 600
36.0	55.6	52.7	9 500
38.0	53.2	51.3	8 500
40.0	50.9	49.7	7 500
42.0	48.4	48.0	6 700

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
61.0m (200 Ft.) BOOM			
44.0	45.8	46.2	6 000
46.0	43.1	44.1	5 400
48.0	40.3	41.9	4 800
50.0	37.3	39.4	4 200
52.0	34.1	36.6	3 700
54.0	30.6	33.5	3 200
56.0	26.7	29.8	2 800
58.0	22.1	25.4	2 300
64.0m (210 Ft.) BOOM			
11.0	81.5	65.8	64 400
12.0	80.6	65.6	56 100
13.0	79.7	65.4	49 700
14.0	78.8	65.2	44 400
15.0	77.8	65.0	40 000
16.0	76.9	64.8	36 300
18.0	75.1	64.3	30 300
20.0	73.2	63.7	25 800
22.0	71.3	63.1	22 200
24.0	69.4	62.4	19 300
26.0	67.5	61.6	16 900
28.0	65.6	60.7	14 900
30.0	63.6	59.8	13 200
32.0	61.6	58.7	11 700
34.0	59.5	57.6	10 500
36.0	57.4	56.4	9 300
38.0	55.3	55.1	8 300
40.0	53.1	53.6	7 400
42.0	50.8	52.0	6 600
44.0	48.4	50.3	5 900
46.0	46.0	48.5	5 200
48.0	43.4	46.5	4 600
50.0	40.8	44.3	4 100
52.0	37.9	41.8	3 500
54.0	34.9	39.1	3 100
56.0	31.7	36.1	2 600
58.0	28.1	32.6	2 200

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
67.1m (220 Ft.) BOOM			
11.0	81.9	68.8	64 300
12.0	81.0	68.7	55 900
13.0	80.1	68.5	49 500
14.0	79.3	68.3	44 200
15.0	78.4	68.1	39 800
16.0	77.5	67.9	36 100
18.0	75.8	67.5	30 100
20.0	74.0	66.9	25 600
22.0	72.2	66.3	22 000
24.0	70.4	65.6	19 100
26.0	68.6	64.9	16 700
28.0	66.7	64.1	14 700
30.0	64.9	63.2	13 000
32.0	63.0	62.2	11 500
34.0	61.0	61.1	10 200
36.0	59.1	60.0	9 100
38.0	57.0	58.7	8 100
40.0	55.0	57.4	7 200
42.0	52.9	55.9	6 400
44.0	50.7	54.3	5 700
46.0	48.5	52.6	5 000
48.0	46.1	50.8	4 400
50.0	43.7	48.8	3 800
52.0	41.2	46.6	3 400
54.0	38.5	44.2	2 900
56.0	35.7	41.6	2 400
58.0	32.6	38.6	2 000



Liftcrane Boom Capacities

Boom No. 22E With Open Throat Top
67 860 kg Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

999 SERIES 1

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
70.1m (230 Ft.) BOOM			
11.6	81.8	71.8	59 000
12.0	81.4	71.8	55 900
13.0	80.6	71.6	49 300
14.0	79.7	71.4	44 000
15.0	78.9	71.3	39 600
16.0	78.1	71.1	35 900
18.0	76.4	70.6	30 000
20.0	74.7	70.1	25 400
22.0	73.0	69.5	21 800
24.0	71.3	68.9	18 900
26.0	69.6	68.2	16 500
28.0	67.8	67.4	14 500
30.0	66.0	66.5	12 800
32.0	64.2	65.6	11 300
34.0	62.4	64.6	10 000
36.0	60.5	63.5	8 900
38.0	58.6	62.3	7 800
40.0	56.7	61.1	7 000
42.0	54.7	59.7	6 100
44.0	52.7	58.2	5 400
46.0	50.6	56.6	4 800
48.0	48.5	54.9	4 200
50.0	46.3	53.1	3 600
52.0	43.9	51.1	3 100
54.0	41.5	48.9	2 600
56.0	39.0	46.6	2 200
73.2m (240 Ft.) BOOM			
12.2	81.6	74.8	54 300
13.0	81.0	74.7	49 200
14.0	80.2	74.5	43 900
15.0	79.4	74.4	39 500
16.0	78.6	74.2	35 800
18.0	77.0	73.7	29 800
20.0	75.4	73.2	25 200
22.0	73.7	72.7	21 600
24.0	72.1	72.1	18 700
26.0	70.5	71.4	16 300
28.0	68.8	70.7	14 300
30.0	67.1	69.8	12 600
32.0	65.4	69.0	11 100
34.0	63.6	68.0	9 800
36.0	61.9	67.0	8 700
38.0	60.1	65.9	7 700
40.0	58.3	64.7	6 800
42.0	56.4	63.4	6 000
44.0	54.5	62.0	5 200
46.0	52.6	60.5	4 600
48.0	50.6	59.0	4 000
50.0	48.5	57.2	3 400
52.0	46.4	55.4	2 900
54.0	44.2	53.4	2 400
56.0	41.9	51.3	2 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
76.2m (250 Ft.) BOOM			
12.2	82.0	77.9	50 300 *
13.0	81.3	77.8	49 300
14.0	80.6	77.6	43 700
15.0	79.8	77.5	39 300
16.0	79.0	77.3	35 600
18.0	77.5	76.9	29 600
20.0	76.0	76.4	25 100
22.0	74.4	75.9	21 500
24.0	72.8	75.3	18 500
26.0	71.3	74.6	16 200
28.0	69.7	73.9	14 100
30.0	68.1	73.1	12 400
32.0	66.4	72.3	10 900
34.0	64.8	71.4	9 600
36.0	63.1	70.4	8 500
38.0	61.4	69.4	7 500
40.0	59.7	68.2	6 600
42.0	57.9	67.0	5 800
44.0	56.1	65.7	5 100
46.0	54.3	64.3	4 400
48.0	52.4	62.8	3 800
50.0	50.5	61.3	3 200
52.0	48.5	59.5	2 700
54.0	46.5	57.7	2 300
56.0	44.4	55.7	1 800
79.2m (260 Ft.) BOOM			
12.8	81.8	80.9	45 800 *
13.0	81.7	80.9	45 700 *
14.0	80.9	80.7	43 600
15.0	80.2	80.6	39 100
16.0	79.5	80.4	35 400
18.0	78.0	80.0	29 400
20.0	76.5	79.5	24 900
22.0	75.0	79.0	21 200
24.0	73.5	78.5	18 400
26.0	72.0	77.8	16 000
28.0	70.5	77.2	13 900
30.0	68.9	76.4	12 200
32.0	67.4	75.6	10 700
34.0	65.8	74.7	9 400
36.0	64.2	73.8	8 300
38.0	62.6	72.8	7 300
40.0	61.0	71.7	6 400
42.0	59.3	70.6	5 600
44.0	57.6	69.4	4 800
46.0	55.9	68.1	4 200
48.0	54.1	66.6	3 600
50.0	52.3	65.2	3 000
52.0	50.4	63.6	2 500
54.0	48.5	61.8	2 100