



Liftcrane Boom Capacities

2250 SERIES 1

**Boom No. 44 With Long Reach Top
 76 750 kg Counterweight
 360 Degree Rating**

**Meets
 ANSI B30.5
 Requirements**

LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and do not exceed 75% of a static tipping load. Capacities based on structural competence are denoted by an asterisk (*).

Upper boom point capacity for liftcrane service with single part whip line is 13 610 kg or 27 220 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of jib, all load blocks, hooks, weight ball, slings, hoist lines, etc. beneath boom and jib point sheaves is considered part of main boom load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging **No. 192054**, Wire Rope Specification chart **No. 8033-A**, and Counterweight Arrangement chart **No. 8026-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting

or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

MACHINE TRAVEL: Machine to travel on a firm, level, and uniformly supporting surface and boom within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8028-A**.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 9 373 mm crawlers, 1 219 mm treads, 8 534 mm retractable gantry, 12 part boom hoist reeving, boom support straps, and 76 750 kg counterweight.

Deduct From Capacities When Jib Is Attached	
Jib Length	Jib No. 132
12.2m	2 900 kg
18.3m	3 720 kg
24.3m	4 670 kg
30.5m	5 810 kg
36.6m	6 940 kg

Boom Catwalks Deduct

Deduct 300 kg from capacities when boom catwalks are attached.

Consult jib chart for jib capacities.
 Upper boom point cannot be used when jib is attached.



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

WITHOUT BOOM CATWALKS					
Maximum Boom and Jib Lengths Lifted Unassisted					
Over Front of Blocked Crawlers		Over Rear of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 132	Boom Length	Jib No. 132	Boom Length	Jib No. 132
(a)(b)100.6m	---	94.5m	---	88.4m	---
(a)(b) 97.5m	---	91.4m	---	85.3m	---
94.5m	---	88.4m	---	82.3m	---
91.4m	---	85.3m	12.2m	79.2m	12.2m
88.4m	---	82.3m	18.3m	76.2m	24.4m
85.3m	12.2m	79.2m	24.4m	73.2m	30.5m
(b) 85.3m	18.3m	(b) 79.2m	30.5m	70.1m	36.6m
82.3m	24.4m	76.2m	36.6m		
79.2m	30.5m				
(b) 79.2m	36.6m				

Load block, hook and weight ball on ground at start.
 (a) Upper boom point cannot be used on 100.6m and 97.5m boom.
 (b) Machine must be equipped with optional upperworks jacking cylinders.

WITH BOOM CATWALKS					
Maximum Boom and Jib Lengths Lifted Unassisted					
Over Front of Blocked Crawlers		Over Rear of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 132	Boom Length	Jib No. 132	Boom Length	Jib No. 132
(a)(b) 97.5m	---	(a) 94.5m	---	88.4m	---
94.5m	---	91.4m	---	85.3m	---
91.4m	---	88.4m	---	82.3m	---
88.4m	---	85.3m	---	79.2m	12.2m
85.3m	12.2m	82.3m	18.3m	76.2m	18.3m
82.3m	24.4m	79.2m	24.4m	(b) 76.2m	24.4m
79.2m	30.5m	76.2m	30.5m	73.2m	24.4m
76.2m	36.6m	(b) 76.2m	36.6m	(b) 73.2m	30.5m
				70.1m	36.6m

Load block, hook and weight ball on ground at start.
 (a) Upper boom point cannot be used on 97.5m boom and on 94.5m boom over rear of blocked crawlers.
 (b) Machine must be equipped with optional upperworks jacking cylinders.



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
57.9m (190 Ft.) BOOM			
9.8	82.7	59.8	95 200 *
10.0	82.4	59.8	95 200 *
11.0	81.4	59.6	95 200 *
12.0	80.4	59.5	92 700
13.0	79.4	59.3	83 300
14.0	78.4	59.1	74 600
15.0	77.4	58.9	67 600
16.0	76.4	58.6	61 600
18.0	74.3	58.1	52 100
20.0	72.3	57.5	44 900
22.0	70.2	56.8	39 300
24.0	68.0	56.0	34 700
26.0	65.9	55.1	31 000
28.0	63.7	54.2	27 900
30.0	61.5	53.1	25 200
32.0	59.2	52.0	23 000
34.0	56.8	50.7	21 000
36.0	54.4	49.3	19 200
38.0	51.9	47.8	17 700
40.0	49.4	46.1	16 300
42.0	46.7	44.3	15 100
44.0	43.9	42.3	14 000
46.0	40.9	40.1	13 000
48.0	37.8	37.6	12 000
50.0	34.4	34.8	11 200
52.0	30.7	31.6	10 500

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
61.0m (200 Ft.) BOOM			
9.8	83.0	62.9	95 200 *
10.0	82.8	62.9	95 200 *
11.0	81.9	62.7	95 200 *
12.0	80.9	62.6	92 600
13.0	80.0	62.4	83 000
14.0	79.0	62.2	74 400
15.0	78.0	62.0	67 300
16.0	77.1	61.8	61 300
18.0	75.1	61.3	51 800
20.0	73.2	60.7	44 600
22.0	71.2	60.0	39 000
24.0	69.2	59.3	34 400
26.0	67.2	58.5	30 700
28.0	65.1	57.6	27 600
30.0	63.0	56.6	24 900
32.0	60.9	55.5	22 600
34.0	58.7	54.3	20 600
36.0	56.4	53.0	18 900
38.0	54.2	51.6	17 300
40.0	51.8	50.1	16 000
42.0	49.3	48.4	14 800
44.0	46.8	46.6	13 700
46.0	44.1	44.6	12 600
48.0	41.4	42.4	11 700
50.0	38.4	40.0	10 900
52.0	35.2	37.3	10 100
54.0	31.8	34.2	9 400
56.0	28.0	30.7	8 800

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
64.0m (210 Ft.) BOOM			
10.4	82.8	65.9	95 200 *
11.0	82.3	65.8	95 200 *
12.0	81.3	65.7	92 500
13.0	80.4	65.5	82 900
14.0	79.5	65.3	74 300
15.0	78.6	65.1	67 200
16.0	77.7	64.9	61 100
18.0	75.9	64.4	51 700
20.0	74.0	63.9	44 500
22.0	72.1	63.2	38 800
24.0	70.2	62.5	34 300
26.0	68.3	61.8	30 600
28.0	66.4	60.9	27 500
30.0	64.4	60.0	24 800
32.0	62.4	59.0	22 500
34.0	60.3	57.9	20 600
36.0	58.2	56.7	18 800
38.0	56.1	55.4	17 300
40.0	53.9	53.9	15 900
42.0	51.7	52.4	14 600
44.0	49.3	50.7	13 500
46.0	46.9	48.9	12 500
48.0	44.4	46.9	11 600
50.0	41.7	44.8	10 800
52.0	39.0	42.4	10 000
54.0	36.0	39.7	9 300
56.0	32.8	36.8	8 600
58.0	29.3	33.4	8 000



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
67.1m (220 Ft.) BOOM			
11.0	82.6	68.9	95 200 *
12.0	81.7	68.7	92 300
13.0	80.9	68.6	82 700
14.0	80.0	68.4	74 000
15.0	79.1	68.2	66 900
16.0	78.3	68.0	60 900
18.0	76.5	67.6	51 400
20.0	74.7	67.0	44 200
22.0	73.0	66.4	38 600
24.0	71.2	65.8	34 000
26.0	69.3	65.0	30 300
28.0	67.5	64.2	27 200
30.0	65.6	63.4	24 500
32.0	63.7	62.4	22 200
34.0	61.8	61.4	20 200
36.0	59.9	60.2	18 500
38.0	57.8	59.0	16 900
40.0	55.8	57.7	15 600
42.0	53.7	56.2	14 300
44.0	51.5	54.7	13 200
46.0	49.3	53.0	12 200
48.0	47.0	51.2	11 300
50.0	44.6	49.2	10 500
52.0	42.1	47.1	9 700
54.0	39.5	44.8	9 000
56.0	36.7	42.2	8 300
58.0	33.7	39.3	7 700
60.0	30.4	36.1	7 200
62.0	26.8	32.3	6 700

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
70.1m (230 Ft.) BOOM			
11.0	83.0	72.0	89 000 *
12.0	82.1	71.8	87 500 *
13.0	81.3	71.7	82 800
14.0	80.5	71.5	73 800
15.0	79.6	71.3	66 700
16.0	78.8	71.1	60 600
18.0	77.1	70.7	51 200
20.0	75.4	70.2	44 000
22.0	73.7	69.6	38 300
24.0	72.0	69.0	33 800
26.0	70.3	68.3	30 000
28.0	68.5	67.5	26 900
30.0	66.8	66.7	24 200
32.0	65.0	65.8	22 000
34.0	63.1	64.8	20 000
36.0	61.3	63.7	18 200
38.0	59.4	62.6	16 700
40.0	57.5	61.3	15 300
42.0	55.5	60.0	14 100
44.0	53.5	58.6	13 000
46.0	51.4	57.0	12 000
48.0	49.3	55.3	11 000
50.0	47.1	53.5	10 200
52.0	44.8	51.6	9 500
54.0	42.4	49.4	8 700
56.0	39.9	47.1	8 100
58.0	37.3	44.6	7 500
60.0	34.5	41.8	6 900
62.0	31.4	38.7	6 400
64.0	28.1	35.1	5 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
73.2m (240 Ft.) BOOM			
11.6	82.8	75.0	85 300 *
12.0	82.4	74.9	84 700 *
13.0	81.6	74.8	82 500
14.0	80.9	74.6	73 600
15.0	80.1	74.4	66 400
16.0	79.3	74.2	60 400
18.0	77.7	73.8	50 900
20.0	76.0	73.3	43 700
22.0	74.4	72.8	38 000
24.0	72.8	72.2	33 500
26.0	71.1	71.5	29 700
28.0	69.5	70.8	26 600
30.0	67.8	70.0	23 900
32.0	66.1	69.1	21 600
34.0	64.4	68.2	19 600
36.0	62.6	67.2	17 900
38.0	60.8	66.1	16 400
40.0	59.0	64.9	15 000
42.0	57.1	63.7	13 800
44.0	55.3	62.3	12 700
46.0	53.3	60.9	11 700
48.0	51.3	59.3	10 700
50.0	49.3	57.6	9 900
52.0	47.2	55.8	9 100
54.0	45.0	53.9	8 400
56.0	42.7	51.8	7 700
58.0	40.3	49.5	7 100
60.0	37.8	47.0	6 600
62.0	35.2	44.3	6 100
64.0	32.3	41.2	5 600
66.0	29.2	37.8	5 100



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
76.2m (250 Ft.) BOOM			
12.2	82.6	78.0	81 100 *
13.0	82.0	77.8	79 800
14.0	81.2	77.7	73 500
15.0	80.5	77.5	66 300
16.0	79.7	77.3	60 200
18.0	78.2	76.9	50 700
20.0	76.6	76.5	43 600
22.0	75.1	76.0	37 900
24.0	73.5	75.4	33 300
26.0	71.9	74.8	29 600
28.0	70.3	74.1	26 500
30.0	68.7	73.3	23 800
32.0	67.1	72.5	21 500
34.0	65.4	71.6	19 500
36.0	63.8	70.6	17 700
38.0	62.1	69.6	16 200
40.0	60.4	68.5	14 800
42.0	58.6	67.3	13 600
44.0	56.8	66.0	12 500
46.0	55.0	64.6	11 500
48.0	53.1	63.2	10 600
50.0	51.2	61.6	9 700
52.0	49.3	59.9	9 000
54.0	47.2	58.1	8 300
56.0	45.2	56.2	7 600
58.0	43.0	54.1	7 000
60.0	40.7	51.8	6 400
62.0	38.3	49.4	5 900
64.0	35.8	46.7	5 400
66.0	33.1	43.8	5 000
68.0	30.3	40.5	4 500
70.0	27.1	36.8	4 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
79.2m (260 Ft.) BOOM			
12.2	82.9	81.0	78 200 *
13.0	82.3	80.9	77 400 *
14.0	81.6	80.8	73 200
15.0	80.8	80.6	66 000
16.0	80.1	80.4	60 000
18.0	78.6	80.1	50 500
20.0	77.1	79.6	43 200
22.0	75.7	79.1	37 600
24.0	74.2	78.6	33 000
26.0	72.6	78.0	29 300
28.0	71.1	77.3	26 100
30.0	69.6	76.6	23 500
32.0	68.0	75.8	21 200
34.0	66.5	74.9	19 200
36.0	64.9	74.0	17 500
38.0	63.3	73.0	15 900
40.0	61.6	72.0	14 500
42.0	60.0	70.8	13 300
44.0	58.3	69.6	12 200
46.0	56.5	68.3	11 200
48.0	54.8	67.0	10 300
50.0	53.0	65.5	9 400
52.0	51.1	63.9	8 600
54.0	49.3	62.2	7 900
56.0	47.3	60.4	7 300
58.0	45.3	58.5	6 700
60.0	43.2	56.4	6 100
62.0	41.1	54.2	5 600
64.0	38.8	51.8	5 100
66.0	36.4	49.2	4 600
68.0	33.9	46.3	4 200
70.0	31.2	43.1	3 800
72.0	28.2	39.6	3 400

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
82.3m (270 Ft.) BOOM			
12.8	82.7	84.0	70 000 *
13.0	82.6	84.0	69 900 *
14.0	81.9	83.9	69 300 *
15.0	81.2	83.7	66 200
16.0	80.5	83.5	59 700
18.0	79.1	83.2	50 200
20.0	77.6	82.7	43 000
22.0	76.2	82.3	37 300
24.0	74.8	81.7	32 800
26.0	73.3	81.2	29 000
28.0	71.8	80.5	25 900
30.0	70.4	79.8	23 200
32.0	68.9	79.1	20 900
34.0	67.4	78.3	18 900
36.0	65.9	77.4	17 200
38.0	64.3	76.4	15 600
40.0	62.8	75.4	14 300
42.0	61.2	74.4	13 000
44.0	59.6	73.2	11 900
46.0	57.9	72.0	10 900
48.0	56.3	70.7	10 000
50.0	54.6	69.3	9 100
52.0	52.8	67.8	8 400
54.0	51.1	66.2	7 700
56.0	49.2	64.5	7 000
58.0	47.4	62.7	6 400
60.0	45.4	60.8	5 800
62.0	43.4	58.7	5 300
64.0	41.4	56.5	4 800
66.0	39.2	54.2	4 400
68.0	36.9	51.6	3 900
70.0	34.5	48.8	3 500
72.0	32.0	45.7	3 100
74.0	29.2	42.3	2 800
76.0	26.2	38.4	2 400



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
85.3m (280 Ft.) BOOM			
12.8	83.0	87.1	64 800 *
13.0	82.8	87.1	64 700 *
14.0	82.2	86.9	64 200 *
15.0	81.5	86.8	63 700 *
16.0	80.8	86.6	60 800
18.0	79.4	86.3	50 000
20.0	78.1	85.9	42 700
22.0	76.7	85.4	37 000
24.0	75.3	84.9	32 500
26.0	73.9	84.3	28 700
28.0	72.5	83.7	25 600
30.0	71.1	83.1	22 900
32.0	69.7	82.3	20 600
34.0	68.2	81.6	18 600
36.0	66.8	80.7	16 900
38.0	65.3	79.8	15 300
40.0	63.8	78.8	13 900
42.0	62.3	77.8	12 700
44.0	60.8	76.7	11 600
46.0	59.2	75.6	10 600
48.0	57.6	74.3	9 700
50.0	56.0	73.0	8 800
52.0	54.4	71.6	8 000
54.0	52.7	70.1	7 300
56.0	51.0	68.5	6 700
58.0	49.2	66.8	6 100
60.0	47.4	65.0	5 500
62.0	45.6	63.1	5 000
64.0	43.7	61.1	4 500
66.0	41.7	58.9	4 100
68.0	39.6	56.5	3 600
70.0	37.4	54.0	3 200
72.0	35.1	51.2	2 800
74.0	32.7	48.2	2 500
76.0	30.1	44.9	2 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
88.4m (290 Ft.) BOOM			
13.4	82.8	90.1	60 100 *
14.0	82.4	90.0	59 800 *
15.0	81.8	89.9	59 300 *
16.0	81.1	89.7	57 800
18.0	79.8	89.4	50 100
20.0	78.5	89.0	42 600
22.0	77.2	88.5	36 900
24.0	75.8	88.0	32 300
26.0	74.5	87.5	28 500
28.0	73.1	86.9	25 400
30.0	71.8	86.3	22 700
32.0	70.4	85.6	20 500
34.0	69.0	84.8	18 500
36.0	67.6	84.0	16 700
38.0	66.2	83.2	15 200
40.0	64.8	82.2	13 800
42.0	63.3	81.3	12 500
44.0	61.9	80.2	11 400
46.0	60.4	79.1	10 400
48.0	58.9	77.9	9 500
50.0	57.4	76.7	8 600
52.0	55.8	75.3	7 900
54.0	54.2	73.9	7 200
56.0	52.6	72.4	6 500
58.0	50.9	70.8	5 900
60.0	49.2	69.1	5 400
62.0	47.5	67.3	4 800
64.0	45.7	65.4	4 400
66.0	43.8	63.4	3 900
68.0	41.9	61.2	3 400
70.0	39.9	58.9	3 100
72.0	37.9	56.4	2 600
74.0	35.7	53.7	2 300
76.0	33.4	50.8	1 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
91.4m (300 Ft.) BOOM			
14.0	82.7	93.1	54 300 *
15.0	82.1	92.9	53 800 *
16.0	81.4	92.8	53 200 *
18.0	80.2	92.5	49 300
20.0	78.9	92.1	42 200
22.0	77.6	91.7	36 600
24.0	76.3	91.2	32 000
26.0	75.0	90.7	28 200
28.0	73.7	90.1	25 100
30.0	72.4	89.5	22 400
32.0	71.1	88.8	20 100
34.0	69.7	88.1	18 100
36.0	68.4	87.3	16 400
38.0	67.0	86.5	14 800
40.0	65.7	85.6	13 400
42.0	64.3	84.7	12 200
44.0	62.9	83.7	11 100
46.0	61.5	82.6	10 100
48.0	60.0	81.5	9 100
50.0	58.6	80.3	8 300
52.0	57.1	79.0	7 500
54.0	55.6	77.6	6 800
56.0	54.0	76.2	6 200
58.0	52.5	74.7	5 500
60.0	50.9	73.1	5 000
62.0	49.2	71.4	4 500
64.0	47.5	69.6	4 000
66.0	45.8	67.7	3 500
68.0	44.0	65.7	3 100
70.0	42.2	63.6	2 700
72.0	40.3	61.3	2 300
74.0	38.3	58.8	1 900



Liftcrane Boom Capacities

2250 SERIES 1

Boom No. 44 With Long Reach Top
76 750 kg Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
94.5m (310 Ft.) BOOM			
14.0	82.9	96.2	48 900 *
15.0	82.3	96.0	48 300 *
16.0	81.7	95.9	47 000 *
18.0	80.5	95.6	44 600 *
20.0	79.2	95.2	42 200
22.0	78.0	94.8	36 300
24.0	76.8	94.3	31 700
26.0	75.5	93.8	28 000
28.0	74.3	93.3	24 800
30.0	73.0	92.7	22 100
32.0	71.7	92.0	19 800
34.0	70.4	91.3	17 800
36.0	69.1	90.6	16 100
38.0	67.8	89.8	14 500
40.0	66.5	88.9	13 100
42.0	65.2	88.0	11 900
44.0	63.8	87.1	10 800
46.0	62.5	86.0	9 800
48.0	61.1	85.0	8 900
50.0	59.7	83.8	8 000
52.0	58.3	82.6	7 200
54.0	56.8	81.3	6 500
56.0	55.4	80.0	5 900
58.0	53.9	78.5	5 300
60.0	52.4	77.0	4 700
62.0	50.8	75.4	4 200
64.0	49.2	73.7	3 700
66.0	47.6	71.9	3 200
68.0	45.9	70.0	2 800
70.0	44.2	68.0	2 400
72.0	42.4	65.9	2 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
97.5m (320 Ft.) BOOM			
14.6	82.8	99.2	45 200 *
15.0	82.6	99.1	44 700 *
16.0	82.0	99.0	43 600 *
18.0	80.8	98.7	41 400 *
20.0	79.6	98.3	39 200 *
22.0	78.4	97.9	36 500
24.0	77.2	97.5	31 500
26.0	76.0	97.0	27 800
28.0	74.8	96.4	24 600
30.0	73.5	95.9	21 900
32.0	72.3	95.2	19 600
34.0	71.1	94.6	17 600
36.0	69.8	93.9	15 900
38.0	68.6	93.1	14 300
40.0	67.3	92.3	12 900
42.0	66.0	91.4	11 700
44.0	64.7	90.5	10 600
46.0	63.4	89.5	9 600
48.0	62.1	88.4	8 600
50.0	60.7	87.3	7 800
52.0	59.4	86.2	7 000
54.0	58.0	84.9	6 300
56.0	56.6	83.7	5 700
58.0	55.2	82.3	5 000
60.0	53.7	80.8	4 500
62.0	52.3	79.3	4 000
64.0	50.7	77.7	3 400
66.0	49.2	76.0	3 000
68.0	47.6	74.2	2 600
70.0	46.0	72.3	2 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
100.6m (330 Ft.) BOOM			
14.6	83.0	102.2	39 800 *
15.0	82.8	102.2	39 400 *
16.0	82.2	102.0	38 300 *
18.0	81.1	101.7	36 000 *
20.0	79.9	101.4	34 100 *
22.0	78.7	101.0	32 400 *
24.0	77.6	100.6	30 800 *
26.0	76.4	100.1	28 200
28.0	75.2	99.6	25 000
30.0	74.1	99.0	22 300
32.0	72.9	98.4	20 000
34.0	71.7	97.8	18 000
36.0	70.5	97.1	16 200
38.0	69.2	96.4	14 700
40.0	68.0	95.6	13 300
42.0	66.8	94.7	12 100
44.0	65.5	93.8	10 900
46.0	64.3	92.9	9 900
48.0	63.0	91.9	9 000
50.0	61.7	90.8	8 200
52.0	60.4	89.7	7 400
54.0	59.1	88.5	6 700
56.0	57.7	87.3	6 000
58.0	56.4	86.0	5 400
60.0	55.0	84.6	4 900
62.0	53.6	83.2	4 300
64.0	52.2	81.6	3 900
66.0	50.7	80.0	3 400
68.0	49.2	78.3	3 000
70.0	47.7	76.5	2 600
72.0	46.1	74.7	2 100