



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and do not exceed 75% of a static tipping load. Capacities based on structural competence are denoted by an asterisk (*).

Upper boom point capacity for liftcrane service with single part whip line is 13 610 kg or 27 220 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

76.2m thru 91.4m boom lengths require only the middle three sheaves to be used on lower boom point. All other sheaves must be removed from lower boom point.

Weight of jib, all load blocks, hooks, weight ball, slings, hoist lines, etc. beneath boom and jib point sheaves is considered part of main boom load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging **No. 179809**, Wire Rope Specification chart **No. 8025-A**, and Counterweight Arrangement chart **No. 8026-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

MACHINE TRAVEL: Machine to travel on a firm, level, and uniformly supporting surface and boom within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8027-A**.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 9 373 mm crawlers, 1 219 mm treads, 8 534 mm retractable gantry, 12 part boom hoist reeving, boom support straps, 94 890 kg crane counterweight, and two 13 610 kg carbody counterweights.

Consult chart **No. 8009-AM** for jib capacities. Consult chart **No. 8527-AM** for extended upper boom point capacities.

Deduct From Capacities When Jib Is Attached	
Jib Length	Jib No. 132
12.2m	2 900 kg
18.3m	3 720 kg
24.4m	4 670 kg
30.5m	5 810 kg
36.6m	6 940 kg

Extended Upper Boom Point Deduct

Deduct 2 720 kg from boom capacities when 7.6m extended upper boom point is attached.

Third Line Deduct

Deduct 270 kg from boom capacities when boom is equipped for three line operation.

Boom Catwalks Deduct

Deduct 300 kg from capacities when boom catwalks are attached.

Upper boom point cannot be used when jib or extended upper boom point is attached.
Jib cannot be attached when boom is equipped for three line operation.



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

WITHOUT BOOM CATWALKS								
Maximum Boom and Jib Lengths Lifted Unassisted								
Over Front of Crawlers			Over Rear of Blocked Crawlers			Over Side of Crawlers		
Boom Length	Jib No. 132	7.6m Extended Upper Boom Pt.	Boom Length	Jib No. 132	7.6m Extended Upper Boom Pt.	Boom Length	Jib No. 132	7.6m Extended Upper Boom Pt.
91.4m	—	—	91.4m	—	—	91.4m	—	—
88.4m	—	—	88.4m	—	—	88.4m	—	—
85.3m	—	—	85.3m	—	—	85.3m	—	—
82.3m	—	—	82.3m	—	—	82.3m	—	—
79.2m	24.4m	7.6m	79.2m	24.4m	7.6m	79.2m	24.4m	7.6m
76.2m	36.6m	—	76.2m	36.6m	—	76.2m	30.5m	—
						73.2m	36.6m	—

Load block, hook and weight ball on ground at start.

WITH BOOM CATWALKS								
Maximum Boom and Jib Lengths Lifted Unassisted								
Over Front of Crawlers			Over Rear of Blocked Crawlers			Over Side of Crawlers		
Boom Length	Jib No. 132	7.6m Extended Upper Boom Pt.	Boom Length	Jib No. 132	7.6m Extended Upper Boom Pt.	Boom Length	Jib No. 132	7.6m Extended Upper Boom Pt.
(a) 91.4m	—	—	(a) 91.4m	—	—	(a) 91.4m	—	—
88.4m	—	—	88.4m	—	—	88.4m	—	—
85.3m	—	—	85.3m	—	—	85.3m	—	—
82.3m	—	—	82.3m	—	—	82.3m	—	—
79.2m	24.4m	7.6m	79.2m	24.4m	7.6m	79.2m	24.4m	7.6m
76.2m	30.5m	—	76.2m	30.5m	—	76.2m	30.5m	—
73.2m	30.5m	—	73.2m	36.6m	—	73.2m	30.5m	—
70.1m	36.6m	—				70.1m	36.6m	—

Load block, hook and weight ball on ground at start.
(a) Upper boom point cannot be used on 91.4m boom.



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
21.3m (70 Ft.) BOOM			
5.5	82.9	23.5	272 100 *
6.0	81.5	23.4	256 800 *
6.5	80.2	23.3	243 900 *
7.0	78.8	23.2	229 100 *
7.5	77.4	23.1	214 500 *
8.0	76.0	22.9	201 700 *
8.5	74.6	22.8	190 300 *
9.0	73.2	22.6	180 100 *
10.0	70.3	22.2	155 400
11.0	67.4	21.8	133 700
12.0	64.4	21.3	117 300
13.0	61.3	20.7	104 300
14.0	58.1	20.1	93 800
15.0	54.8	19.4	85 000
16.0	51.4	18.5	77 700
18.0	43.8	16.6	66 100
20.0	34.8	13.9	57 100
24.4m (80 Ft.) BOOM			
6.1	82.4	26.5	238 700 *
6.5	81.4	26.4	237 100 *
7.0	80.2	26.3	228 600 *
7.5	79.0	26.2	214 100 *
8.0	77.8	26.1	201 300 *
8.5	76.6	26.0	189 900 *
9.0	75.4	25.8	179 700 *
10.0	72.9	25.5	155 400
11.0	70.4	25.1	133 600
12.0	67.8	24.7	117 200
13.0	65.2	24.2	104 100
14.0	62.6	23.7	93 600
15.0	59.8	23.1	84 900
16.0	57.0	22.4	77 500
18.0	51.1	20.8	65 900
20.0	44.5	18.9	57 100
22.0	37.0	16.4	50 200
24.0	27.6	13.0	43 500

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
27.4m (90 Ft.) BOOM			
6.4	82.6	29.5	226 100 *
6.5	82.4	29.5	225 700 *
7.0	81.3	29.4	223 400 *
7.5	80.3	29.3	214 400 *
8.0	79.2	29.2	201 100 *
8.5	78.1	29.1	189 600 *
9.0	77.0	29.0	179 400 *
10.0	74.9	28.7	155 400
11.0	72.7	28.4	133 600
12.0	70.4	28.0	117 100
13.0	68.2	27.6	104 100
14.0	65.9	27.1	93 500
15.0	63.5	26.6	84 800
16.0	61.1	26.0	77 500
18.0	56.1	24.7	65 800
20.0	50.8	23.1	57 000
22.0	45.0	21.2	50 100
24.0	38.5	18.8	44 500
30.5m (100 Ft.) BOOM			
6.7	82.8	32.6	217 400 *
7.0	82.2	32.5	216 000 *
7.5	81.2	32.4	212 300 *
8.0	80.3	32.3	200 600 *
8.5	79.3	32.2	189 200 *
9.0	78.4	32.1	179 000 *
10.0	76.4	31.9	155 300
11.0	74.5	31.6	133 400
12.0	72.5	31.2	116 900
13.0	70.5	30.9	103 900
14.0	68.5	30.5	93 400
15.0	66.4	30.0	84 600
16.0	64.3	29.5	77 200
18.0	60.0	28.4	65 600
20.0	55.4	27.0	56 800
22.0	50.6	25.4	49 800
24.0	45.4	23.5	44 300
26.0	39.7	21.2	39 700
28.0	33.1	18.3	35 800

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
33.5m (110 Ft.) BOOM			
7.0	82.9	35.6	169 800 *
7.5	82.0	35.5	167 900 *
8.0	81.2	35.4	166 200 *
8.5	80.3	35.3	164 500 *
9.0	79.4	35.2	162 900 *
10.0	77.7	35.0	156 400
11.0	75.9	34.7	133 300
12.0	74.1	34.4	116 800
13.0	72.3	34.1	103 800
14.0	70.5	33.8	93 200
15.0	68.7	33.3	84 500
16.0	66.8	32.9	77 100
18.0	63.0	31.9	65 400
20.0	59.0	30.7	56 600
22.0	54.9	29.3	49 700
24.0	50.5	27.7	44 100
26.0	45.8	25.8	39 500
28.0	40.6	23.6	35 700
30.0	34.9	20.9	32 400
32.0	28.0	17.4	29 600
36.6m (120 Ft.) BOOM			
7.3	83.0	38.6	164 900 *
7.5	82.7	38.6	164 300 *
8.0	81.9	38.5	162 600 *
8.5	81.1	38.4	161 000 *
9.0	80.3	38.3	159 500 *
10.0	78.7	38.1	154 000
11.0	77.1	37.9	133 100
12.0	75.5	37.6	116 600
13.0	73.9	37.3	103 500
14.0	72.2	37.0	93 000
15.0	70.5	36.6	84 200
16.0	68.9	36.2	76 900
18.0	65.4	35.3	65 200
20.0	61.9	34.3	56 400
22.0	58.2	33.1	49 400
24.0	54.4	31.7	43 800
26.0	50.4	30.0	39 200
28.0	46.1	28.2	35 400
30.0	41.4	26.0	32 100
32.0	36.3	23.4	29 300
34.0	30.3	20.1	26 800



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
39.6m (130 Ft.) BOOM			
7.9	82.7	41.6	159 000 *
8.0	82.6	41.6	158 800 *
8.5	81.8	41.5	157 300 *
9.0	81.1	41.4	155 900 *
10.0	79.6	41.3	151 500
11.0	78.1	41.0	133 100
12.0	76.6	40.8	116 600
13.0	75.1	40.5	103 500
14.0	73.6	40.2	93 000
15.0	72.1	39.9	84 200
16.0	70.6	39.5	76 800
18.0	67.4	38.7	65 200
20.0	64.2	37.7	56 300
22.0	60.9	36.6	49 400
24.0	57.5	35.4	43 800
26.0	54.0	34.0	39 200
28.0	50.3	32.3	35 300
30.0	46.3	30.5	32 100
32.0	42.0	28.3	29 300
34.0	37.4	25.8	26 800
36.0	32.2	22.8	24 700
38.0	25.9	19.0	22 800
42.7m (140 Ft.) BOOM			
8.2	82.8	44.7	155 000 *
8.5	82.4	44.6	154 300 *
9.0	81.7	44.5	152 900 *
10.0	80.4	44.4	149 400
11.0	79.0	44.2	132 900
12.0	77.6	43.9	116 300
13.0	76.2	43.7	103 300
14.0	74.8	43.4	92 700
15.0	73.4	43.1	83 900
16.0	72.0	42.8	76 600
18.0	69.1	42.0	64 900
20.0	66.2	41.1	56 000
22.0	63.2	40.1	49 100
24.0	60.1	39.0	43 500
26.0	56.9	37.7	38 900
28.0	53.6	36.3	35 100
30.0	50.2	34.6	31 800
32.0	46.5	32.8	28 900
34.0	42.6	30.7	26 500
36.0	38.3	28.2	24 400
38.0	33.6	25.3	22 400

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
45.7m (150 Ft.) BOOM			
8.5	82.9	47.7	137 100 *
9.0	82.3	47.6	135 800 *
10.0	81.0	47.5	133 100 *
11.0	79.7	47.3	130 500
12.0	78.5	47.1	116 400
13.0	77.2	46.8	103 100
14.0	75.9	46.6	92 500
15.0	74.6	46.3	83 800
16.0	73.3	46.0	76 400
18.0	70.6	45.3	64 700
20.0	67.9	44.5	55 900
22.0	65.2	43.6	48 900
24.0	62.3	42.5	43 300
26.0	59.4	41.4	38 700
28.0	56.4	40.0	34 800
30.0	53.3	38.6	31 500
32.0	50.1	36.9	28 700
34.0	46.7	35.1	26 300
36.0	43.0	33.0	24 100
38.0	39.1	30.6	22 200
40.0	34.9	27.8	20 600
42.0	30.1	24.6	19 000
48.8m (160 Ft.) BOOM			
8.8	83.0	50.7	132 400 *
9.0	82.8	50.7	132 000 *
10.0	81.6	50.6	129 600 *
11.0	80.4	50.4	127 300
12.0	79.2	50.2	116 500
13.0	78.0	50.0	102 800
14.0	76.8	49.7	92 300
15.0	75.6	49.4	83 500
16.0	74.3	49.2	76 100
18.0	71.9	48.5	64 400
20.0	69.4	47.8	55 500
22.0	66.8	46.9	48 600
24.0	64.2	46.0	43 000
26.0	61.5	44.9	38 400
28.0	58.8	43.7	34 500
30.0	56.0	42.4	31 200
32.0	53.1	40.9	28 400
34.0	50.0	39.2	26 000
36.0	46.8	37.4	23 800
38.0	43.4	35.3	21 900
40.0	39.8	33.0	20 200
42.0	35.9	30.3	18 700
44.0	31.6	27.2	17 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
51.8m (170 Ft.) BOOM			
9.1	83.0	53.8	128 800 *
10.0	82.1	53.6	126 900 *
11.0	81.0	53.5	124 900
12.0	79.8	53.3	116 800
13.0	78.7	53.1	102 800
14.0	77.6	52.9	92 200
15.0	76.4	52.6	83 400
16.0	75.3	52.3	76 000
18.0	73.0	51.7	64 400
20.0	70.6	51.0	55 500
22.0	68.3	50.2	48 500
24.0	65.8	49.4	42 900
26.0	63.4	48.4	38 300
28.0	60.8	47.3	34 500
30.0	58.3	46.0	31 200
32.0	55.6	44.7	28 400
34.0	52.8	43.2	25 900
36.0	50.0	41.5	23 800
38.0	47.0	39.7	21 900
40.0	43.8	37.7	20 100
42.0	40.4	35.4	18 700
44.0	36.8	32.8	17 300
46.0	32.8	29.8	16 000
48.0	28.4	26.3	14 900
54.9m (180 Ft.) BOOM			
9.8	82.8	56.8	124 500 *
10.0	82.5	56.7	124 000 *
11.0	81.5	56.6	122 200 *
12.0	80.4	56.4	116 300
13.0	79.3	56.2	102 600
14.0	78.3	56.0	92 000
15.0	77.2	55.7	83 200
16.0	76.1	55.5	75 800
18.0	74.0	54.9	64 100
20.0	71.8	54.3	55 200
22.0	69.5	53.5	48 200
24.0	67.3	52.7	42 600
26.0	65.0	51.8	38 000
28.0	62.6	50.7	34 200
30.0	60.2	49.6	30 900
32.0	57.8	48.4	28 100
34.0	55.2	47.0	25 600
36.0	52.6	45.5	23 500
38.0	49.9	43.8	21 500
40.0	47.1	42.0	19 900
42.0	44.1	40.0	18 300
44.0	41.0	37.7	17 000
46.0	37.6	35.2	15 700
48.0	33.9	32.3	14 600
50.0	29.9	29.0	13 600



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
57.9m (190 Ft.) BOOM			
10.4	82.6	59.7	109 400 *
11.0	81.9	59.7	108 200 *
12.0	80.9	59.5	106 500 *
13.0	79.9	59.3	103 100
14.0	78.9	59.1	91 800
15.0	77.9	58.9	83 000
16.0	76.9	58.6	75 600
18.0	74.8	58.1	63 900
20.0	72.8	57.5	55 000
22.0	70.7	56.8	48 000
24.0	68.5	56.0	42 400
26.0	66.4	55.1	37 800
28.0	64.2	54.2	33 900
30.0	61.9	53.1	30 600
32.0	59.7	52.0	27 800
34.0	57.3	50.7	25 300
36.0	54.9	49.3	23 200
38.0	52.4	47.8	21 300
40.0	49.9	46.1	19 600
42.0	47.2	44.3	18 100
44.0	44.4	42.3	16 700
46.0	41.4	40.1	15 500
48.0	38.3	37.6	14 300
50.0	34.9	34.8	13 300
52.0	31.2	31.6	12 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
61.0m (200 Ft.) BOOM			
10.4	82.9	62.8	105 800 *
11.0	82.3	62.7	104 800 *
12.0	81.4	62.6	103 200 *
13.0	80.4	62.4	101 000
14.0	79.5	62.2	91 500
15.0	78.5	62.0	82 700
16.0	77.5	61.8	75 300
18.0	75.6	61.3	63 500
20.0	73.6	60.7	54 700
22.0	71.7	60.0	47 700
24.0	69.7	59.3	42 100
26.0	67.6	58.5	37 500
28.0	65.6	57.6	33 600
30.0	63.5	56.6	30 300
32.0	61.3	55.5	27 500
34.0	59.2	54.3	25 000
36.0	56.9	53.0	22 900
38.0	54.6	51.6	21 000
40.0	52.3	50.1	19 300
42.0	49.8	48.4	17 800
44.0	47.3	46.6	16 400
46.0	44.6	44.6	15 200
48.0	41.8	42.4	14 000
50.0	38.9	40.0	13 000
52.0	35.7	37.3	12 000
54.0	32.3	34.2	11 100
56.0	28.5	30.7	10 300

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
64.0m (210 Ft.) BOOM			
11.0	82.7	65.8	102 100 *
12.0	81.8	65.7	100 800 *
13.0	80.9	65.5	98 800 *
14.0	80.0	65.3	91 500
15.0	79.1	65.1	82 600
16.0	78.1	64.9	75 200
18.0	76.3	64.4	63 400
20.0	74.4	63.9	54 600
22.0	72.6	63.2	47 600
24.0	70.7	62.5	42 000
26.0	68.8	61.8	37 400
28.0	66.8	60.9	33 500
30.0	64.8	60.0	30 200
32.0	62.8	59.0	27 400
34.0	60.8	57.9	24 900
36.0	58.7	56.7	22 800
38.0	56.6	55.4	20 900
40.0	54.4	53.9	19 200
42.0	52.1	52.4	17 600
44.0	49.8	50.7	16 300
46.0	47.4	48.9	15 000
48.0	44.8	46.9	13 900
50.0	42.2	44.8	12 900
52.0	39.4	42.4	11 900
54.0	36.4	39.7	11 100
56.0	33.2	36.8	10 200
58.0	29.7	33.4	9 500



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
67.1m (220 Ft.) BOOM			
11.6	82.5	68.8	98 500 *
12.0	82.2	68.7	97 700 *
13.0	81.3	68.6	94 400 *
14.0	80.4	68.4	90 800 *
15.0	79.6	68.2	82 400
16.0	78.7	68.0	74 900
18.0	76.9	67.6	63 200
20.0	75.2	67.0	54 300
22.0	73.4	66.4	47 300
24.0	71.6	65.8	41 700
26.0	69.8	65.1	37 100
28.0	67.9	64.2	33 200
30.0	66.1	63.4	29 900
32.0	64.2	62.4	27 100
34.0	62.2	61.4	24 600
36.0	60.3	60.2	22 500
38.0	58.3	59.0	20 500
40.0	56.2	57.7	18 900
42.0	54.1	56.3	17 300
44.0	52.0	54.7	16 000
46.0	49.7	53.0	14 700
48.0	47.4	51.2	13 600
50.0	45.0	49.3	12 600
52.0	42.5	47.1	11 600
54.0	39.9	44.8	10 700
56.0	37.1	42.2	9 900
58.0	34.1	39.3	9 200
60.0	30.9	36.1	8 500
62.0	27.3	32.4	7 800

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
70.1m (230 Ft.) BOOM			
11.6	82.9	71.9	87 600 *
12.0	82.5	71.8	87 100 *
13.0	81.7	71.7	85 900 *
14.0	80.9	71.5	84 800 *
15.0	80.0	71.3	81 700
16.0	79.2	71.1	75 500
18.0	77.5	70.7	62 900
20.0	75.8	70.2	54 000
22.0	74.1	69.6	47 000
24.0	72.4	69.0	41 400
26.0	70.7	68.3	36 800
28.0	68.9	67.5	32 900
30.0	67.2	66.7	29 600
32.0	65.4	65.8	26 800
34.0	63.6	64.8	24 300
36.0	61.7	63.7	22 200
38.0	59.8	62.6	20 300
40.0	57.9	61.3	18 600
42.0	55.9	60.0	17 100
44.0	53.9	58.6	15 700
46.0	51.8	57.0	14 500
48.0	49.7	55.3	13 300
50.0	47.5	53.5	12 300
52.0	45.2	51.6	11 300
54.0	42.8	49.4	10 500
56.0	40.3	47.1	9 700
58.0	37.7	44.6	8 900
60.0	34.9	41.8	8 200
62.0	31.8	38.7	7 500
64.0	28.5	35.1	6 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
73.2m (240 Ft.) BOOM			
12.2	82.7	74.9	84 200 *
13.0	82.0	74.8	83 300 *
14.0	81.2	74.6	80 900 *
15.0	80.4	74.4	78 300 *
16.0	79.6	74.2	74 300
18.0	78.0	73.8	62 800
20.0	76.4	73.3	53 800
22.0	74.8	72.8	46 800
24.0	73.2	72.2	41 100
26.0	71.5	71.5	36 500
28.0	69.9	70.8	32 700
30.0	68.2	70.0	29 300
32.0	66.5	69.2	26 500
34.0	64.7	68.2	24 100
36.0	63.0	67.2	21 900
38.0	61.2	66.1	20 000
40.0	59.4	64.9	18 300
42.0	57.5	63.7	16 700
44.0	55.6	62.3	15 400
46.0	53.7	60.9	14 100
48.0	51.7	59.3	13 000
50.0	49.7	57.6	12 000
52.0	47.6	55.8	11 000
54.0	45.4	53.9	10 100
56.0	43.1	51.8	9 300
58.0	40.7	49.5	8 600
60.0	38.2	47.0	7 900
62.0	35.6	44.3	7 200
64.0	32.7	41.2	6 600
66.0	29.6	37.8	6 000
68.0	26.2	34.0	5 500



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
76.2m (250 Ft.) BOOM			
12.2	83.0	78.0	81 200 *
13.0	82.4	77.8	80 300 *
14.0	81.6	77.7	77 800 *
15.0	80.8	77.5	75 300 *
16.0	80.1	77.3	72 500
18.0	78.5	76.9	63 500
20.0	77.0	76.5	54 100
22.0	75.4	76.0	47 100
24.0	73.9	75.4	41 500
26.0	72.3	74.8	36 900
28.0	70.7	74.1	33 000
30.0	69.1	73.3	29 700
32.0	67.5	72.5	26 900
34.0	65.8	71.6	24 400
36.0	64.2	70.6	22 300
38.0	62.5	69.6	20 400
40.0	60.7	68.5	18 700
42.0	59.0	67.3	17 200
44.0	57.2	66.0	15 800
46.0	55.4	64.6	14 500
48.0	53.5	63.2	13 400
50.0	51.6	61.6	12 300
52.0	49.6	59.9	11 400
54.0	47.6	58.1	10 500
56.0	45.5	56.2	9 700
58.0	43.4	54.1	9 000
60.0	41.1	51.8	8 300
62.0	38.7	49.4	7 600
64.0	36.2	46.7	7 000
66.0	33.5	43.8	6 400
68.0	30.6	40.5	5 900
70.0	27.5	36.8	5 400

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
79.2m (260 Ft.) BOOM			
12.8	82.8	81.0	76 800 *
13.0	82.7	80.9	76 300 *
14.0	81.9	80.8	73 800 *
15.0	81.2	80.6	71 500 *
16.0	80.5	80.4	69 100 *
18.0	79.0	80.1	62 700
20.0	77.5	79.6	53 900
22.0	76.0	79.1	46 900
24.0	74.5	78.6	41 200
26.0	73.0	78.0	36 600
28.0	71.5	77.3	32 700
30.0	69.9	76.6	29 400
32.0	68.4	75.8	26 600
34.0	66.8	74.9	24 100
36.0	65.2	74.0	22 000
38.0	63.6	73.0	20 000
40.0	62.0	72.0	18 400
42.0	60.3	70.8	16 800
44.0	58.6	69.6	15 500
46.0	56.9	68.3	14 200
48.0	55.1	67.0	13 100
50.0	53.3	65.5	12 000
52.0	51.5	63.9	11 100
54.0	49.6	62.2	10 200
56.0	47.7	60.4	9 400
58.0	45.7	58.5	8 700
60.0	43.6	56.4	8 000
62.0	41.4	54.2	7 300
64.0	39.1	51.8	6 700
66.0	36.8	49.2	6 100
68.0	34.2	46.3	5 600
70.0	31.5	43.1	5 100
72.0	28.6	39.6	4 600

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
82.3m (270 Ft.) BOOM			
13.4	82.6	83.9	69 800 *
14.0	82.2	83.9	68 800 *
15.0	81.5	83.7	66 700 *
16.0	80.8	83.5	64 600 *
18.0	79.4	83.2	60 400 *
20.0	78.0	82.7	53 700
22.0	76.5	82.3	46 600
24.0	75.1	81.7	41 000
26.0	73.7	81.2	36 400
28.0	72.2	80.5	32 500
30.0	70.7	79.8	29 200
32.0	69.2	79.1	26 300
34.0	67.7	78.3	23 800
36.0	66.2	77.4	21 700
38.0	64.7	76.4	19 800
40.0	63.1	75.4	18 100
42.0	61.5	74.4	16 600
44.0	59.9	73.2	15 200
46.0	58.3	72.0	13 900
48.0	56.6	70.7	12 800
50.0	54.9	69.3	11 700
52.0	53.2	67.8	10 800
54.0	51.4	66.2	9 900
56.0	49.6	64.5	9 100
58.0	47.7	62.7	8 400
60.0	45.8	60.8	7 700
62.0	43.8	58.8	7 000
64.0	41.7	56.5	6 400
66.0	39.6	54.2	5 900
68.0	37.3	51.6	5 300
70.0	34.9	48.8	4 800
72.0	32.3	45.7	4 400
74.0	29.6	42.3	3 800
76.0	26.5	38.4	3 000 *



Liftcrane Boom Capacities

2250 SERIES 2

Boom No. 44 With Heavy Lift Top
94 890 kg Crane Counterweight
27 220 kg Carbody Counterweight
360 Degree Rating

**Meets
ANSI B30.5
Requirements**

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
85.3m (280 Ft.) BOOM			
13.4	82.9	87.0	64 700 *
14.0	82.5	86.9	64 400 *
15.0	81.8	86.8	63 400 *
16.0	81.1	86.6	61 200 *
18.0	79.8	86.3	58 500 *
20.0	78.4	85.9	53 700
22.0	77.0	85.4	46 500
24.0	75.6	84.9	40 900
26.0	74.3	84.3	36 300
28.0	72.8	83.7	32 400
30.0	71.4	83.1	29 100
32.0	70.0	82.3	26 300
34.0	68.6	81.6	23 700
36.0	67.1	80.7	21 600
38.0	65.6	79.8	19 700
40.0	64.1	78.9	18 000
42.0	62.6	77.8	16 500
44.0	61.1	76.7	15 100
46.0	59.5	75.6	13 800
48.0	58.0	74.3	12 700
50.0	56.4	73.0	11 700
52.0	54.7	71.6	10 700
54.0	53.0	70.1	9 800
56.0	51.3	68.5	9 000
58.0	49.6	66.8	8 300
60.0	47.8	65.0	7 600
62.0	45.9	63.1	6 900
64.0	44.0	61.1	6 300
66.0	42.0	58.9	5 800
68.0	39.9	56.5	5 200
70.0	37.8	54.0	4 700
72.0	35.5	51.2	4 000 *
74.0	33.1	48.2	3 300 *
76.0	30.5	44.9	2 600 *

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
88.4m (290 Ft.) BOOM			
14.0	82.7	90.0	59 800 *
15.0	82.1	89.9	59 400 *
16.0	81.5	89.7	59 000 *
18.0	80.1	89.4	58 000 *
20.0	78.8	89.0	53 600
22.0	77.5	88.5	46 400
24.0	76.2	88.0	40 700
26.0	74.8	87.5	36 100
28.0	73.5	86.9	32 200
30.0	72.1	86.3	28 900
32.0	70.7	85.6	26 100
34.0	69.3	84.8	23 600
36.0	67.9	84.0	21 400
38.0	66.5	83.2	19 500
40.0	65.1	82.2	17 800
42.0	63.7	81.3	16 300
44.0	62.2	80.2	14 900
46.0	60.7	79.1	13 700
48.0	59.2	77.9	12 500
50.0	57.7	76.7	11 500
52.0	56.1	75.3	10 500
54.0	54.5	73.9	9 600
56.0	52.9	72.4	8 900
58.0	51.3	70.8	8 100
60.0	49.6	69.1	7 400
62.0	47.8	67.3	6 700
64.0	46.0	65.4	6 100
66.0	44.2	63.4	5 600
68.0	42.3	61.2	5 000
70.0	40.3	58.9	4 500
72.0	38.2	56.4	3 900 *
74.0	36.0	53.7	3 200 *
76.0	33.7	50.8	2 600 *

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
91.4m (300 Ft.) BOOM			
14.0	83.0	93.1	55 900 *
15.0	82.4	93.0	55 600 *
16.0	81.7	92.8	55 200 *
18.0	80.5	92.5	53 000 *
20.0	79.2	92.1	50 400
22.0	77.9	91.7	46 500
24.0	76.6	91.2	40 400
26.0	75.3	90.7	35 800
28.0	74.0	90.1	31 900
30.0	72.7	89.5	28 600
32.0	71.4	88.8	25 800
34.0	70.1	88.1	23 300
36.0	68.7	87.3	21 100
38.0	67.4	86.5	19 200
40.0	66.0	85.6	17 500
42.0	64.6	84.7	16 000
44.0	63.2	83.7	14 600
46.0	61.8	82.6	13 300
48.0	60.3	81.5	12 200
50.0	58.9	80.3	11 200
52.0	57.4	79.0	10 200
54.0	55.9	77.6	9 300
56.0	54.3	76.2	8 500
58.0	52.8	74.7	7 800
60.0	51.2	73.1	7 100
62.0	49.5	71.4	6 400
64.0	47.9	69.6	5 800
66.0	46.1	67.7	5 100 *
68.0	44.3	65.7	4 300 *
70.0	42.5	63.6	3 700 *
72.0	40.6	61.3	3 000 *
74.0	38.6	58.8	2 400 *
76.0	36.5	56.1	1 900 *