



# Liftcrane Boom Capacities

**26 100 kg Crane Counterweight**  
**6 500 kg Carbody Counterweight**  
**Extended Position Crawlers**  
**360 Degree Rating**

**Meets  
ASME B30.5  
Requirements**

**8500-1**

## LIFTING CAPACITIES:

- Rated loads included in the charts are the maximum allowable freely suspended loads at a given boom length, boom angle and load radius, and have been determined for the machine standing level on firm supporting surface under ideal operating conditions. The user must limit or de-rate rated loads to allow for adverse conditions (such as soft or uneven ground, out-of-level conditions, wind, side loads, pendulum action, jerking or sudden stopping of loads, inexperience of personnel, and multiple machine lifts).
- Capacities do not exceed 75% of minimum tipping loads. Capacities based on factors other than machine stability such as structural competence are shown by asterisk \* in the charts.
- Attempting to lift more than rated loads may cause machine to tip or collapse. Do not tip machine to determine capacity.
- Do not attempt to lift where no radius on load chart is listed as crane may tip or collapse.
- Weight of hooks, hook blocks, slings and other lifting devices beneath boom and jib point sheaves are part of the total load. Their total weight must be subtracted from the rated load to obtain the weight that can be lifted.
- Load radius is horizontal distance from axis of rotation to center of gravity of the freely suspended load. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of radius. In all cases, operating radius shall govern capacity.
- Least stable position is over the side.
- Boom point elevation is vertical distance from ground level to centerline of boom point shaft.
- Upper boom point capacity for liftcrane service with single part line is 7 700 kg. In all cases, upper boom point capacities cannot exceed those listed for Liftcrane Boom capacity reduced by 200 kg.

- When lifting over boom point with jib or upper boom point, rated loads for the boom must be reduced as shown below:

Jib length (m)	Upper Boom Point	9,1 m	12,2 m	15,2 m	18,3 m
Deduct (kg)	200	1 100	1 500	2 000	2 400

- Lifting capacities listed apply only to the machine as originally manufactured and designed. Modifications to this machine or use of equipment other than that specified can reduce operating capacity.
- Machine travel with load (pick and carry).
  - Travel with crane upperworks in-line with crawlers. Grade in any direction must not exceed 1 percent (0.5 degrees).
  - Travel surface must be firm, level and uniformly supporting. Capacity charts are based on static conditions; therefore judgment must be used to allow for dynamic effects of traveling with load. Carry load as close to ground as possible. Stabilize load with taglines. Travel slowly and smoothly to avoid shock loading boom, jib and rigging.
- To lift the maximum capacity of 80 000 kg, the Upper Boom Point must be used.



## Liftcrane Boom Capacities

26 100 kg Crane Counterweight  
 6 500 kg Carbody Counterweight  
 Extended Position Crawlers  
 360 Degree Rating

Meets  
 ASME B30.5  
 Requirements

# 8500-1

### OPERATING CONDITION:

- The machine must be reeved and set-up as stated in the Operator Manual. If this manual is missing, obtain replacement.
  - Boom backstops are required for all boom lengths.
  - Gantry must be fully raised position for all operation.
  - Crawlers must be fully extended and be locked in position.
  - The crane must be leveled to within 1% on a firm supporting surface.
  - Refer to operator manual for operating guidelines.
- The total load that can be lifted over a jib is limited by the rated jib loads.

- See Operator Manual Section 6 for Wire Rope Specifications.
- Machine equipped with 6 280 mm crawlers, 900 mm treads, 12 parts of boom hoist reeving. 26 100 kg crane counterweight and 6 500 kg carbody counterweight.

Maximum Boom and Jib Lengths Lifted Unassisted			
Over End of Blocked Crawlers		Over End of Crawlers	
Boom Length	Jib Length	Boom Length	Jib Length
61,0 m (a)	—	61,0 m (a)	—
57,9 m	—	57,9 m	—
54,9 m	18,3 m	51,8 m	18,3 m

Load block, hook and weight ball on ground at start.  
 (a) Upper boom point cannot be attached on 61,0 m boom.  
 Jibs can only be mounted on 24,4 m to 54,9 m booms.

Hoist Reeving for Main Boom Loads

No. of Parts of Line	1	2	3	4	5
Maximum Loads (kg)	7 700	15 400	23 100	30 800	38 500

No. of Parts of Line	6	7	8	9	10
Maximum Loads (kg)	46 200	53 900	61 600	69 400	80 000

Hoist Reeving for Upper Boom Point

No. of Parts of Line	1
Maximum Loads (kg)	7 700

**Operation of this equipment in excess of rated loads or disregard of instruction voids the warranty.**



# Liftcrane Boom Capacities

26 100 kg Crane Counterweight  
6 500 kg Carbody Counterweight  
Extended Position Crawlers  
360 Degree Rating

Meets  
ASME B30.5  
Requirements



**8500-1**

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>12,2 m Boom</b>			
3,0	81,70	13,79	80 000 *
3,5	79,59	13,71	76 300 *
4,0	77,18	13,59	69 500 *
4,5	74,75	13,46	62 200 *
5,0	72,29	13,30	56 300 *
5,5	69,79	13,12	51 200 *
6,0	67,25	12,92	45 400
7,0	62,00	12,42	35 900
8,0	56,48	11,80	29 500
9,0	50,56	11,04	25 100
10,0	44,06	10,09	21 700
12,0	27,57	7,22	16 400 *
12,1	25,50	6,82	15 700 *
<b>15,2 m Boom</b>			
3,6	81,10	16,78	75 400 *
4,0	79,78	16,71	69 400 *
4,5	77,86	16,61	62 100 *
5,0	75,93	16,48	56 200 *
5,5	73,97	16,34	51 100 *
6,0	72,00	16,18	45 300
7,0	67,98	15,80	35 800
8,0	63,83	15,34	29 400
9,0	59,53	14,78	25 000
10,0	55,02	14,12	21 600
12,0	45,10	12,40	17 000
14,0	32,93	9,87	13 900 *
15,2	22,70	7,44	12 100 *
<b>18,3 m Boom</b>			
4,0	81,60	19,81	69 300 *
4,5	79,91	19,72	62 000 *
5,0	78,31	19,62	56 100 *
5,5	76,71	19,50	51 100 *
6,0	75,09	19,37	45 200
7,0	71,81	19,06	35 700
8,0	68,46	18,69	29 300
9,0	65,04	18,24	24 800
10,0	61,51	17,73	21 500
12,0	54,04	16,44	16 800
14,0	45,77	14,71	13 800
16,0	36,07	12,36	11 600
18,0	23,10	8,74	10 000 *
18,2	20,60	8,02	9 700 *

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>21,3 m Boom</b>			
4,3	82,00	22,85	65 100 *
4,5	81,37	22,81	61 000 *
5,0	80,01	22,73	56 000 *
5,5	78,64	22,63	51 000 *
6,0	77,26	22,52	45 200
7,0	74,48	22,25	35 700
8,0	71,67	21,94	29 200
9,0	68,81	21,57	24 800
10,0	65,88	21,14	21 400
12,0	59,82	20,09	16 800
14,0	53,34	18,75	13 700
16,0	46,24	17,02	11 500
18,0	38,16	14,78	9 900
19,8	29,30	12,01	8 800
<b>24,4 m Boom</b>			
4,9	81,60	25,84	57 200 *
5,0	81,27	25,82	55 900 *
5,5	80,07	25,73	50 900 *
6,0	78,88	25,64	45 100
7,0	76,47	25,41	35 600
8,0	74,03	25,14	29 200
9,0	71,57	24,82	24 700
10,0	69,06	24,45	21 300
12,0	63,92	23,56	16 700
14,0	58,53	22,44	13 600
16,0	52,81	21,05	11 400
18,0	46,60	19,33	9 800
20,0	39,66	17,16	8 500
22,0	32,49	14,68	7 500
22,8	27,30	12,76	7 200
<b>27,4 m Boom</b>			
5,2	81,90	28,88	53 800 *
5,5	81,19	28,83	50 800 *
6,0	80,13	28,74	45 100
7,0	78,00	28,54	35 600
8,0	75,85	28,30	29 100
9,0	73,68	28,02	24 600
10,0	71,49	27,70	21 300
12,0	67,01	26,92	16 600
14,0	62,37	25,96	13 500
16,0	57,52	24,78	11 300
18,0	52,39	23,36	9 700
20,0	46,87	21,63	8 400
22,0	41,51	19,78	7 400
24,0	34,67	17,19	6 600
25,9	25,70	13,48	6 000

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>30,5 m Boom</b>			
5,7	81,50	31,87	46 100 *
6,0	81,13	31,83	44 600 *
7,0	79,22	31,65	35 500
8,0	77,29	31,44	29 100
9,0	75,35	31,19	24 600
10,0	73,40	30,90	21 200
12,0	69,42	30,22	16 500
14,0	65,34	29,37	13 400
16,0	61,11	28,34	11 200
18,0	56,70	27,12	9 600
20,0	52,06	25,66	8 300
22,0	47,67	24,15	7 300
24,0	42,31	22,12	6 500
26,0	36,33	19,64	5 800
28,0	29,31	16,50	5 300
28,9	24,30	14,63	5 000
<b>33,5 m Boom</b>			
6,0	81,80	34,91	41 900 *
7,0	80,21	34,76	35 500
8,0	78,47	34,56	29 000
9,0	76,71	34,33	24 500
10,0	74,95	34,08	21 200
12,0	71,37	33,46	16 500
14,0	67,71	32,70	13 400
16,0	63,96	31,79	11 200
18,0	60,07	30,71	9 500
20,0	56,03	29,44	8 200
22,0	52,27	28,15	7 200
24,0	47,79	26,45	6 400
26,0	42,96	24,45	5 700
28,0	37,63	22,06	5 200
30,0	31,56	19,13	4 700
32,0	23,20	15,29	4 300



# Liftcrane Boom Capacities

26 100 kg Crane Counterweight  
 6 500 kg Carbody Counterweight  
 Extended Position Crawlers  
 360 Degree Rating

Meets  
**ASME B30.5**  
 Requirements

**8500-1**

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>36,6 m Boom</b>			
6,7	81,50	37,93	36 500 *
7,0	81,03	37,85	34 900 *
8,0	79,44	37,67	29 000
9,0	77,84	37,46	24 500
10,0	76,23	37,23	21 100
12,0	72,98	36,66	16 400
14,0	69,66	35,98	13 300
16,0	66,27	35,15	11 100
18,0	62,79	34,19	9 400
20,0	59,20	33,07	8 200
22,0	55,89	31,92	7 100
24,0	52,00	30,45	6 300
26,0	47,89	28,75	5 600
28,0	43,49	26,78	5 100
30,0	38,69	24,46	4 600
32,0	33,32	21,67	4 200
34,0	27,02	18,19	3 800
35,0	22,20	15,91	3 700
<b>39,6 m Boom</b>			
7,3	81,30	40,88	32 200 *
8,0	80,47	40,77	28 900
9,0	78,99	40,58	24 400
10,0	77,50	40,36	21 000
12,0	74,50	39,85	16 300
14,0	71,44	39,22	13 200
16,0	68,33	38,47	11 000
18,0	65,16	37,59	9 300
20,0	61,89	36,58	8 000
22,0	58,52	35,55	7 000
24,0	55,02	34,25	6 200
26,0	51,37	32,75	5 500
28,0	47,51	31,05	4 900
30,0	43,40	29,10	4 400
32,0	38,94	26,83	4 000
34,0	33,99	24,17	3 700
36,0	28,29	20,93	3 400
38,0	21,20	16,51	3 100

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>42,7 m Boom</b>			
7,3	81,90	43,97	27 900 *
8,0	81,16	43,86	27 400 *
9,0	79,79	43,68	24 400
10,0	78,42	43,48	21 000
12,0	75,64	43,01	16 300
14,0	72,82	42,43	13 200
16,0	69,97	41,74	11 000
18,0	67,05	40,93	9 300
20,0	64,08	40,01	8 000
22,0	61,02	39,08	7 000
24,0	57,87	37,90	6 100
26,0	54,60	36,57	5 400
28,0	51,20	35,06	4 900
30,0	47,62	33,35	4 400
32,0	43,82	31,41	3 900
34,0	39,73	29,20	3 600
36,0	35,25	26,62	3 300
38,0	30,20	23,56	3 000
40,0	24,21	19,78	2 700
41,0	20,50	17,11	2 600
<b>45,7 m Boom</b>			
7,9	81,70	46,96	23 800 *
8,0	80,48	46,95	23 800 *
9,0	79,20	46,78	23 200
10,0	76,62	46,60	20 900
12,0	74,01	46,15	16 200
14,0	71,36	45,61	13 100
16,0	68,68	44,97	10 900
18,0	65,94	44,23	9 200
20,0	63,13	43,38	7 900
22,0	60,26	42,53	6 900
24,0	57,30	41,45	6 100
26,0	54,24	40,24	5 400
28,0	51,05	38,88	4 800
30,0	47,71	37,36	4 300
32,0	44,18	35,65	3 900
34,0	40,41	33,73	3 500
36,0	36,32	31,55	3 200
38,0	31,77	29,05	2 900
40,0	26,54	26,13	2 600
42,6	24,80	21,27	2 400

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>48,8 m Boom</b>			
8,5	81,50	49,95	19 900 *
9,0	81,09	49,87	19 700 *
10,0	79,89	49,70	19 200 *
12,0	77,48	49,28	16 200
14,0	75,04	48,78	13 100
16,0	72,58	48,19	10 900
18,0	70,08	47,50	9 200
20,0	67,54	46,71	7 900
22,0	64,95	45,92	6 900
24,0	62,30	44,93	6 000
26,0	59,59	43,82	5 300
28,0	56,80	42,58	4 700
30,0	53,92	41,20	4 200
32,0	50,92	39,66	3 800
34,0	47,79	37,95	3 400
36,0	44,50	36,04	3 100
38,0	41,00	33,90	2 800
40,0	37,22	31,46	2 600
44,0	28,42	25,36	2 100
45,7	24,00	21,94	1 900
<b>51,8 m Boom</b>			
8,5	82,00	53,03	17 500 *
9,0	81,62	52,96	17 300 *
10,0	80,49	52,80	16 900 *
12,0	78,23	52,41	15 900 *
14,0	75,95	51,93	13 000
16,0	73,64	51,38	10 800
18,0	71,30	50,73	9 100
20,0	68,93	50,00	7 800
22,0	66,53	49,26	6 800
24,0	64,07	48,34	5 900
26,0	61,57	47,31	5 200
28,0	59,00	46,17	4 600
30,0	56,36	44,91	4 100
32,0	53,64	43,51	3 700
34,0	50,81	41,97	3 300
36,0	47,87	40,25	3 000
38,0	44,78	38,35	2 700
40,0	41,51	36,23	2 400
44,0	34,21	31,14	2 000
48,0	25,13	24,25	1 600
48,7	23,30	22,61	1 500



# Liftcrane Boom Capacities

26 100 kg Crane Counterweight  
6 500 kg Carbody Counterweight  
Extended Position Crawlers  
360 Degree Rating

Meets  
ASME B30.5  
Requirements



**8500-1**

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>54,9 m Boom</b>			
9,1	81,80	56,02	15 200 *
10,0	82,17	55,89	14 900 *
12,0	81,11	55,52	14 100 *
14,0	78,99	55,08	12 900 *
16,0	76,85	54,55	10 700
18,0	74,69	53,95	9 000
20,0	72,51	53,26	7 700
22,0	70,31	52,57	6 700
24,0	68,07	51,71	5 800
26,0	65,80	50,75	5 100
28,0	61,12	49,69	4 500
30,0	58,70	48,52	4 000
32,0	56,21	47,24	3 600
34,0	53,66	45,82	3 200
36,0	51,01	44,27	2 900
38,0	48,26	42,56	2 600
40,0	45,39	40,66	2 300
44,0	39,15	36,23	1 800
48,0	31,92	30,59	1 400
52,0	22,60	23,23	1 100

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>57,9 m Boom</b>			
10,0	81,60	58,97	13 200 *
12,0	79,58	58,63	12 500 *
14,0	77,56	58,21	11 900 *
16,0	75,52	57,71	10 700
18,0	73,46	57,14	9 000
20,0	71,39	56,49	7 700
22,0	69,28	55,85	6 700
24,0	67,15	55,04	5 800
26,0	64,98	54,14	5 100
28,0	62,77	53,15	4 500
30,0	60,52	52,06	4 000
32,0	58,21	50,87	3 600
34,0	55,85	49,56	3 200
36,0	53,42	48,13	2 900
38,0	50,90	46,57	2 600
40,0	48,30	44,86	2 300
44,0	42,73	40,90	1 800
48,0	36,49	36,03	1 400
51,7	29,10	30,13	1 100

Load Radius (m)	Boom Angle (deg)	Boom Point Elev. (m)	360° Rated Load (kg)
<b>61,0 m Boom</b>			
10,3	81,40	62,00	11 600 *
12,0	80,10	61,73	11 100 *
14,0	78,19	61,33	10 500 *
16,0	76,26	60,86	9 900 *
18,0	74,31	60,32	8 900 *
20,0	72,35	59,78	7 600
22,0	70,36	59,10	6 600
24,0	68,35	58,34	5 700
26,0	66,31	57,49	5 000
28,0	64,24	56,56	4 400
30,0	62,13	55,55	3 900
32,0	59,98	54,43	3 500
34,0	57,78	53,21	3 100
36,0	55,52	51,89	2 800
38,0	53,20	50,44	2 400
40,0	50,81	48,87	2 100
44,0	45,76	45,28	1 700
48,0	40,22	40,96	1 300
49,0	38,70	40,04	1 200

For Reference