

Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards	
14 m/s Maximum Wind thru 54.5m Boom	
12 m/s with 57.5m and 60.5m Boom	
10 m/s with 63.5m thru 84.5m Boom	

15000 SERIES 4

LIFTING CAPACITIES: Chart supplements boom capacity chart **No. 8604-AM**. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and are calculated to comply with EN 13000, ISO 4305 and include factors based on a 4.0 degree tipping angle. Capacities based on structural competence are denoted by an asterisk (*).

75.5m thru 84.5m boom lengths require only the middle two sheaves in lower boom point. All other sheaves must be removed from lower boom point.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves, is considered part of jib load. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging **No. A07850**, jib assembly **No. A10098** and Wire Rope Specification chart **No. 8608-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to Operator's Manual for operating guidelines.

WIND CONDITIONS: Machine may be operated in winds stated in maximum wind speed table provided crane operator judgment is used to allow for wind effect on lifted load and other considerations noted on capacity chart are followed. Wind will have a considerable effect on load. Loads must be compensated for accordingly by reducing load ratings, reducing operating speeds, or by a combination of both. Recommend stopping operation and lowering boom and jib to no higher than 70 degree boom angle when wind exceeds conditions stated. Lower boom and jib to ground when wind is above 22 m/s.

MACHINE TRAVEL: Machine to travel on a firm, level [up to 1 percent (0.5 degrees) grade] and uniformly supporting surface. *Travel with 100 percent of rated load prohibited.* Travel restricted to 90 percent of rated capacity with speed not to exceed 0.4 m/s. Boom must be within boom angle range

shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8615-A**.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

JIB POINT ELEVATION: Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with 8 585 mm crawlers, 1 219 mm treads, 3 124 mm retractable gantry, 9 144 mm live mast, 20 part boom hoist reeving, boom support straps, 107 680 kg crane counterweight and 52 160 kg carbody counterweight.

Maximum capacity on 26 mm wire rope is 13 380 kg per line (9 070 kg when auxiliary drum is used).

Maximum Wind Speeds		
Boom Lengths	Working Wind	Lower To Ground
27.5m - 54.5m	14 m/s	22 m/s
57.5m - 60.5m	12 m/s	22 m/s
63.5m - 84.5m	10 m/s	22 m/s
Wind speed to be measured at jib point elevation.		

Maximum Boom and Jib Length Raising			
Over End of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 134	Boom Length	Jib No. 134
(a) 87.5m	—	84.5m	—
84.5m	12.2m	81.5m	9.1m
81.5m	21.3m	78.5m	18.3m
78.5m	24.4m	75.5m	24.4m
Load block, hook and weight ball on ground at start. (a) Upper boom point cannot be attached on 87.5m boom.			



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
9.1	79.2	38.3	26 700 *							9.1
10.0	77.8	38.1	26 700 *							10.0
12.0	74.6	37.6	26 700 *	77.1	37.4	26 700*				12.0
14.0	71.3	36.9	26 700 *	73.8	36.7	26 100*	76.2	36.2	20 500*	14.0
16.0	67.9	36.1	26 600 *	70.4	35.9	25 400*	72.8	35.4	19 100*	16.0
18.0	64.5	35.2	26 100 *	66.9	35.0	24 900*	69.3	34.4	18 000*	18.0
20.0	60.9	34.1	25 400 *	63.3	33.9	24 400*	65.6	33.3	17 000*	20.0
22.0	57.2	32.9	24 800 *	59.6	32.6	23 800*	61.8	32.0	16 100*	22.0
24.0	53.4	31.4	24 300 *	55.7	31.1	22 400*	57.8	30.5	15 400*	24.0
26.0	49.3	29.8	23 800 *	51.6	29.5	21 100*	53.6	28.8	14 800*	26.0
28.0	44.9	27.8	23 300 *	47.2	27.5	20 000*	49.1	26.8	14 200*	28.0
30.0	40.2	25.5	22 100 *	42.4	25.2	19 000*	44.1	24.4	13 800*	30.0
32.0	34.9	22.8	20 600 *	37.0	22.4	18 200*				32.0
34.0	28.8	19.5	19 400 *							34.0
30.5m Boom										
9.1	80.0	41.4	26 700 *							9.1
10.0	78.8	41.2	26 700 *							10.0
12.0	75.8	40.7	26 700 *	78.1	40.5	26 700*				12.0
14.0	72.8	40.1	26 700 *	75.1	39.9	26 300*	77.4	39.3	21 000*	14.0
16.0	69.7	39.4	26 700 *	72.0	39.2	25 700*	74.2	38.6	19 700*	16.0
18.0	66.6	38.5	26 400 *	68.8	38.3	25 200*	71.0	37.7	18 600*	18.0
20.0	63.3	37.6	25 800 *	65.6	37.3	24 700*	67.7	36.7	17 600*	20.0
22.0	60.0	36.4	25 200 *	62.2	36.2	24 300*	64.3	35.6	16 700*	22.0
24.0	56.6	35.1	24 600 *	58.7	34.9	23 500*	60.8	34.3	16 000*	24.0
26.0	53.0	33.7	24 200 *	55.1	33.4	22 200*	57.1	32.7	15 300*	26.0
28.0	49.2	32.0	23 700 *	51.3	31.7	21 000*	53.2	31.0	14 700*	28.0
30.0	45.2	30.1	23 400 *	47.3	29.7	20 000*	49.0	29.0	14 200*	30.0
32.0	40.9	27.8	22 200 *	42.9	27.5	19 100*	44.5	26.7	13 800*	32.0
34.0	36.1	25.2	20 900 *	38.0	24.8	18 300*				34.0
36.0	30.7	22.1	19 700 *	32.5	21.6	17 700*				36.0
38.0	24.2	18.0	18 700 *							38.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
9.1	80.7	44.4	26 700 *							9.1
10.0	79.6	44.3	26 700 *							10.0
12.0	76.8	43.8	26 700 *	79.0	43.6	26 700*				12.0
14.0	74.0	43.3	26 700 *	76.2	43.0	26 400*	78.3	42.5	21 400*	14.0
16.0	71.2	42.6	26 700 *	73.3	42.4	25 900*	75.4	41.8	20 200*	16.0
18.0	68.3	41.8	26 700 *	70.4	41.6	25 300*	72.5	41.0	19 100*	18.0
20.0	65.4	40.9	26 100 *	67.4	40.7	24 900*	69.5	40.1	18 100*	20.0
22.0	62.3	39.9	25 500 *	64.4	39.6	24 500*	66.4	39.0	17 200*	22.0
24.0	59.2	38.7	25 000 *	61.3	38.5	24 100*	63.2	37.8	16 500*	24.0
26.0	56.0	37.4	24 500 *	58.0	37.1	23 300*	59.9	36.5	15 800*	26.0
28.0	52.6	35.9	24 000 *	54.6	35.6	22 000*	56.4	35.0	15 200*	28.0
30.0	49.1	34.2	23 700 *	51.1	33.9	21 000*	52.8	33.2	14 700*	30.0
32.0	45.4	32.3	23 400 *	47.3	32.0	20 000*	49.0	31.2	14 200*	32.0
34.0	41.4	30.1	22 500 *	43.3	29.8	19 200*	44.8	29.0	13 800*	34.0
36.0	37.1	27.6	21 100 *	38.9	27.2	18 500*				36.0
38.0	32.2	24.6	20 000 *	33.9	24.1	17 800*				38.0
40.0	26.6	20.9	19 000 *							40.0
36.5m Boom										
10.7	79.4	47.2	26 700 *							10.7
12.0	77.7	46.9	26 700 *							12.0
14.0	75.1	46.4	26 700 *	77.1	46.1	26 600*	79.1	45.6	21 900*	14.0
16.0	72.5	45.8	26 700 *	74.5	45.5	26 000*	76.4	45.0	20 600*	16.0
18.0	69.8	45.1	26 700 *	71.8	44.8	25 500*	73.7	44.2	19 500*	18.0
20.0	67.1	44.2	26 400 *	69.0	44.0	25 100*	70.9	43.4	18 600*	20.0
22.0	64.3	43.3	25 800 *	66.2	43.0	24 700*	68.1	42.4	17 700*	22.0
24.0	61.5	42.2	25 300 *	63.4	41.9	24 300*	65.2	41.3	16 900*	24.0
26.0	58.5	41.0	24 800 *	60.4	40.7	23 900*	62.2	40.1	16 300*	26.0
28.0	55.5	39.7	24 400 *	57.4	39.4	23 100*	59.1	38.7	15 700*	28.0
30.0	52.4	38.2	24 000 *	54.2	37.9	21 900*	55.9	37.2	15 100*	30.0
32.0	49.1	36.5	23 600 *	50.9	36.1	20 900*	52.5	35.4	14 600*	32.0
34.0	45.6	34.6	23 300 *	47.4	34.2	20 000*	48.9	33.5	14 200*	34.0
36.0	41.9	32.4	22 700 *	43.6	32.0	19 300*	45.1	31.2	13 800*	36.0
38.0	37.9	29.9	21 300	39.6	29.5	18 600*				38.0
40.0	33.5	27.0	19 700	35.1	26.6	17 900*				40.0
44.0	22.4	19.2	16 400							44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
10.7	80.1	50.3	26 700 *							10.7
12.0	78.5	50.0	26 700 *							12.0
14.0	76.0	49.5	26 700 *	77.9	49.3	26 600*	79.8	48.7	22 200*	14.0
16.0	73.6	48.9	26 700 *	75.5	48.7	26 200*	77.3	48.1	21 000*	16.0
18.0	71.1	48.3	26 700 *	73.0	48.0	25 700*	74.8	47.4	19 900*	18.0
20.0	68.6	47.5	26 700 *	70.4	47.2	25 200*	72.2	46.6	19 000*	20.0
22.0	66.0	46.6	26 100 *	67.8	46.3	24 800*	69.6	45.8	18 100*	22.0
24.0	63.4	45.6	25 600 *	65.2	45.4	24 500*	66.9	44.8	17 400*	24.0
26.0	60.7	44.5	25 100 *	62.5	44.2	24 100*	64.2	43.6	16 700*	26.0
28.0	57.9	43.3	24 600 *	59.7	43.0	23 700*	61.3	42.4	16 100*	28.0
30.0	55.1	41.9	24 300 *	56.8	41.6	22 800*	58.4	41.0	15 500*	30.0
32.0	52.1	40.4	23 900 *	53.8	40.1	21 800*	55.4	39.4	15 000*	32.0
34.0	49.0	38.7	23 600 *	50.7	38.4	20 900*	52.2	37.7	14 600*	34.0
36.0	45.8	36.8	22 900	47.4	36.5	20 100*	48.9	35.7	14 200*	36.0
38.0	42.3	34.7	21 100	44.0	34.3	19 300*	45.3	33.5	13 800*	38.0
40.0	38.6	32.2	19 500	40.2	31.9	18 700*				40.0
44.0	30.1	26.2	16 800	31.5	25.7	17 000				44.0
42.5m Boom										
10.7	80.7	53.3	26 700 *							10.7
12.0	79.1	53.1	26 700 *							12.0
14.0	76.9	52.6	26 700 *	78.6	52.4	26 700*	80.4	51.8	22 500*	14.0
16.0	74.6	52.1	26 700 *	76.3	51.8	26 300*	78.1	51.2	21 300*	16.0
18.0	72.2	51.4	26 700 *	74.0	51.2	25 800*	75.7	50.6	20 300*	18.0
20.0	69.9	50.7	26 700 *	71.6	50.5	25 400*	73.3	49.9	19 400*	20.0
22.0	67.5	49.9	26 400 *	69.2	49.6	25 000*	70.9	49.0	18 500*	22.0
24.0	65.1	49.0	25 800 *	66.8	48.7	24 600*	68.4	48.1	17 800*	24.0
26.0	62.6	48.0	25 300 *	64.3	47.7	24 300*	65.9	47.1	17 100*	26.0
28.0	60.0	46.8	24 900 *	61.7	46.5	24 000*	63.3	45.9	16 500*	28.0
30.0	57.4	45.6	24 500 *	59.1	45.3	23 600*	60.6	44.6	15 900*	30.0
32.0	54.7	44.2	24 100 *	56.3	43.9	22 600*	57.8	43.2	15 400*	32.0
34.0	51.9	42.6	23 800 *	53.5	42.3	21 700*	55.0	41.6	15 000*	34.0
36.0	49.0	40.9	22 900	50.6	40.6	20 800*	52.0	39.9	14 600*	36.0
38.0	45.9	39.0	20 900	47.5	38.7	20 100*	48.8	37.9	14 200*	38.0
40.0	42.7	36.9	19 400	44.2	36.6	19 300	45.5	35.7	13 900*	40.0
44.0	35.5	31.9	16 700	37.0	31.4	16 800				44.0
48.0	26.7	25.0	14 300							48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
12.2	79.5	56.1	26 700 *							12.2
14.0	77.6	55.7	26 700 *	79.3	55.4	26 700*				14.0
16.0	75.4	55.2	26 700 *	77.1	54.9	26 300*	78.8	54.4	21 700*	16.0
18.0	73.3	54.6	26 700 *	74.9	54.3	25 900*	76.6	53.8	20 600*	18.0
20.0	71.0	53.9	26 700 *	72.7	53.7	25 500*	74.3	53.1	19 700*	20.0
22.0	68.8	53.1	26 500 *	70.4	52.9	25 100*	72.0	52.3	18 900*	22.0
24.0	66.5	52.3	26 000 *	68.1	52.0	24 700*	69.7	51.4	18 100*	24.0
26.0	64.2	51.3	25 600 *	65.8	51.1	24 400*	67.3	50.5	17 500*	26.0
28.0	61.8	50.3	25 100 *	63.4	50.0	24 100*	64.9	49.4	16 800*	28.0
30.0	59.4	49.1	24 700 *	61.0	48.8	23 800*	62.5	48.2	16 300*	30.0
32.0	56.9	47.8	24 400 *	58.5	47.5	23 400*	59.9	46.9	15 800*	32.0
34.0	54.3	46.4	23 900	55.9	46.1	22 500*	57.3	45.4	15 300*	34.0
36.0	51.7	44.9	22 500	53.2	44.6	21 600*	54.6	43.9	14 900*	36.0
38.0	48.9	43.2	20 700	50.4	42.8	20 800*	51.7	42.1	14 500*	38.0
40.0	46.0	41.3	19 100	47.5	40.9	19 300	48.8	40.2	14 200*	40.0
44.0	39.8	36.9	16 400	41.2	36.5	16 500	42.3	35.6	13 600*	44.0
48.0	32.5	31.2	14 100	33.9	30.8	14 200				48.0
48.5m Boom										
12.2	80.1	59.1	26 700 *							12.2
14.0	78.3	58.8	26 700 *	79.9	58.5	26 700*				14.0
16.0	76.2	58.3	26 700 *	77.8	58.0	26 400*	79.4	57.5	22 000*	16.0
18.0	74.2	57.7	26 700 *	75.7	57.5	26 000*	77.3	56.9	21 000*	18.0
20.0	72.1	57.1	26 700 *	73.6	56.8	25 500*	75.2	56.2	20 100*	20.0
22.0	70.0	56.4	26 600 *	71.5	56.1	25 200*	73.0	55.5	19 200*	22.0
24.0	67.8	55.6	26 200 *	69.4	55.3	24 800*	70.9	54.7	18 500*	24.0
26.0	65.6	54.7	25 700 *	67.2	54.4	24 500*	68.6	53.8	17 800*	26.0
28.0	63.4	53.7	25 300 *	64.9	53.4	24 200*	66.4	52.8	17 200*	28.0
30.0	61.2	52.6	24 900 *	62.7	52.3	24 000*	64.1	51.7	16 700*	30.0
32.0	58.8	51.4	24 500 *	60.3	51.1	23 700*	61.7	50.5	16 100*	32.0
34.0	56.5	50.1	24 000	57.9	49.8	23 300*	59.3	49.1	15 700*	34.0
36.0	54.0	48.7	22 300	55.5	48.4	22 300	56.8	47.7	15 300*	36.0
38.0	51.5	47.1	20 400	53.0	46.8	20 700	54.2	46.1	14 800*	38.0
40.0	48.9	45.4	18 900	50.3	45.1	19 100	51.5	44.3	14 500*	40.0
44.0	43.3	41.5	16 200	44.7	41.1	16 300	45.8	40.3	13 900*	44.0
48.0	37.0	36.6	13 900	38.3	36.2	14 100				48.0
52.0	29.6	30.3	12 000							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
12.2	80.6	62.2	26 700 *							12.2
14.0	78.9	61.8	26 700 *	80.4	61.6	26 700*				14.0
16.0	76.9	61.4	26 700 *	78.4	61.1	26 400*	79.9	60.5	22 200*	16.0
18.0	75.0	60.8	26 700 *	76.5	60.6	26 000*	78.0	60.0	21 300*	18.0
20.0	73.0	60.2	26 700 *	74.5	60.0	25 600*	76.0	59.4	20 400*	20.0
22.0	71.0	59.6	26 700 *	72.5	59.3	25 200*	73.9	58.7	19 600*	22.0
24.0	69.0	58.8	26 400 *	70.4	58.5	24 900*	71.9	57.9	18 800*	24.0
26.0	66.9	58.0	25 900 *	68.4	57.7	24 600*	69.8	57.1	18 200*	26.0
28.0	64.8	57.0	25 500 *	66.3	56.8	24 300*	67.7	56.1	17 600*	28.0
30.0	62.7	56.0	25 100 *	64.2	55.7	24 000*	65.5	55.1	17 000*	30.0
32.0	60.6	54.9	24 700 *	62.0	54.6	23 800*	63.3	54.0	16 500*	32.0
34.0	58.3	53.7	24 100	59.8	53.4	23 500	61.1	52.7	16 000*	34.0
36.0	56.1	52.4	22 000	57.5	52.1	22 500	58.8	51.4	15 600*	36.0
38.0	53.7	50.9	20 200	55.1	50.6	20 500	56.4	49.9	15 200*	38.0
40.0	51.3	49.4	18 700	52.7	49.0	18 900	53.9	48.3	14 800*	40.0
44.0	46.3	45.8	15 900	47.6	45.4	16 200	48.7	44.6	14 200*	44.0
48.0	40.7	41.4	13 700	42.0	41.0	13 900	43.0	40.2	13 700*	48.0
52.0	34.4	36.1	11 800	35.6	35.6	11 900				52.0
56.0	26.8	29.1	10 000							56.0
54.5m Boom										
13.7	79.6	64.9	26 700 *							13.7
14.0	79.4	64.9	26 700 *							14.0
16.0	77.5	64.5	26 700 *	79.0	64.2	26 400*				16.0
18.0	75.7	64.0	26 700 *	77.1	63.7	26 000*	78.5	63.1	21 500*	18.0
20.0	73.8	63.4	26 700 *	75.2	63.1	25 600*	76.6	62.5	20 700*	20.0
22.0	71.9	62.7	26 700 *	73.3	62.5	25 300*	74.7	61.9	19 900*	22.0
24.0	70.0	62.0	26 400 *	71.4	61.8	25 000*	72.8	61.2	19 100*	24.0
26.0	68.1	61.2	26 000 *	69.5	61.0	24 700*	70.8	60.4	18 500*	26.0
28.0	66.1	60.4	25 600 *	67.5	60.1	24 400*	68.8	59.5	17 900*	28.0
30.0	64.1	59.4	25 300 *	65.5	59.1	24 100*	66.8	58.5	17 300*	30.0
32.0	62.1	58.4	24 900 *	63.4	58.1	23 900*	64.7	57.4	16 800*	32.0
34.0	60.0	57.2	23 900	61.4	56.9	23 600	62.6	56.3	16 300*	34.0
36.0	57.9	56.0	21 800	59.2	55.7	22 300	60.5	55.0	15 900*	36.0
38.0	55.7	54.6	20 000	57.1	54.3	20 300	58.3	53.6	15 500*	38.0
40.0	53.5	53.2	18 400	54.8	52.9	18 700	56.0	52.2	15 100*	40.0
44.0	48.8	49.9	15 700	50.1	49.5	16 000	51.2	48.8	14 500*	44.0
48.0	43.8	46.0	13 500	45.0	45.6	13 700	46.0	44.8	13 800	48.0
52.0	38.2	41.2	11 600	39.4	40.8	11 800				52.0
56.0	31.8	35.4	10 000	32.9	34.9	10 100				56.0
60.0	23.9	27.6	8 100 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
13.7	80.1	68.0	26 700 *							13.7
14.0	79.9	67.9	26 700 *							14.0
16.0	78.1	67.5	26 700 *	79.5	67.3	26 300*				16.0
18.0	76.3	67.1	26 700 *	77.7	66.8	26 000*	79.1	66.2	21 800*	18.0
20.0	74.6	66.5	26 700 *	75.9	66.3	25 600*	77.3	65.7	21 000*	20.0
22.0	72.8	65.9	26 700 *	74.1	65.6	25 300*	75.5	65.0	20 200*	22.0
24.0	70.9	65.2	26 500 *	72.3	65.0	25 000*	73.6	64.4	19 500*	24.0
26.0	69.1	64.5	26 100 *	70.4	64.2	24 700*	71.7	63.6	18 800*	26.0
28.0	67.2	63.6	25 700 *	68.6	63.4	24 400*	69.9	62.7	18 200*	28.0
30.0	65.4	62.7	25 300 *	66.7	62.5	24 200*	67.9	61.8	17 600*	30.0
32.0	63.4	61.8	25 000 *	64.8	61.5	23 900*	66.0	60.8	17 100*	32.0
34.0	61.5	60.7	23 600	62.8	60.4	23 600	64.0	59.7	16 600*	34.0
36.0	59.5	59.5	21 500	60.8	59.2	21 900	62.0	58.6	16 200*	36.0
38.0	57.5	58.3	19 700	58.8	58.0	20 000	59.9	57.3	15 800*	38.0
40.0	55.4	56.9	18 100	56.7	56.6	18 400	57.8	55.9	15 400*	40.0
44.0	51.1	53.8	15 400	52.3	53.5	15 700	53.4	52.8	14 800*	44.0
48.0	46.4	50.2	13 200	47.7	49.9	13 400	48.7	49.1	13 600	48.0
52.0	41.4	46.0	11 300	42.6	45.6	11 500				52.0
56.0	35.8	40.9	9 700	36.9	40.4	9 800				56.0
60.0	29.3	34.4	8 300							60.0
64.0	21.0	25.7	6 200 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
13.7	80.5	71.0	26 700 *							13.7
14.0	80.3	71.0	26 700 *							14.0
16.0	78.6	70.6	26 700 *	80.0	70.3	26 300*				16.0
18.0	76.9	70.1	26 700 *	78.3	69.9	25 900*	79.6	69.3	22 100*	18.0
20.0	75.2	69.6	26 700 *	76.6	69.4	25 600*	77.8	68.8	21 200*	20.0
22.0	73.5	69.0	26 700 *	74.8	68.8	25 300*	76.1	68.2	20 400*	22.0
24.0	71.8	68.4	26 500 *	73.1	68.1	25 000*	74.4	67.5	19 700*	24.0
26.0	70.1	67.7	26 100 *	71.3	67.4	24 700*	72.6	66.8	19 100*	26.0
28.0	68.3	66.9	25 800 *	69.6	66.6	24 500*	70.8	66.0	18 500*	28.0
30.0	66.5	66.0	25 400 *	67.8	65.8	24 200*	69.0	65.1	18 000*	30.0
32.0	64.7	65.1	25 100 *	65.9	64.8	24 000*	67.1	64.2	17 400*	32.0
34.0	62.8	64.1	23 400	64.1	63.8	23 500	65.3	63.2	16 900*	34.0
36.0	61.0	63.0	21 300	62.2	62.7	21 700	63.4	62.0	16 500*	36.0
38.0	59.0	61.8	19 500	60.3	61.5	19 900	61.4	60.8	16 100*	38.0
40.0	57.1	60.5	17 900	58.3	60.2	18 200	59.4	59.5	15 700*	40.0
44.0	53.0	57.7	15 200	54.2	57.4	15 500	55.3	56.6	15 000*	44.0
48.0	48.8	54.3	13 000	49.9	54.0	13 200	50.9	53.2	13 400	48.0
52.0	44.2	50.5	11 100	45.3	50.1	11 300	46.2	49.3	11 400	52.0
56.0	39.2	45.9	9 500	40.3	45.5	9 700				56.0
60.0	33.5	40.3	8 100	34.6	39.8	8 200				60.0
64.0	26.8	33.3	6 600 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
13.7	80.9	74.1	26 700 *							13.7
14.0	80.7	74.0	26 700 *							14.0
16.0	79.1	73.7	26 700 *	80.4	73.4	26 200*				16.0
18.0	77.5	73.2	26 700 *	78.8	73.0	25 900*	80.0	72.4	22 300*	18.0
20.0	75.9	72.7	26 700 *	77.1	72.5	25 500*	78.4	71.9	21 500*	20.0
22.0	74.2	72.2	26 700 *	75.5	71.9	25 300*	76.7	71.3	20 700*	22.0
24.0	72.6	71.6	26 500 *	73.8	71.3	25 000*	75.0	70.7	20 000*	24.0
26.0	70.9	70.9	26 100 *	72.1	70.6	24 700*	73.4	70.0	19 300*	26.0
28.0	69.2	70.1	25 800 *	70.5	69.9	24 500*	71.6	69.2	18 800*	28.0
30.0	67.5	69.3	25 500 *	68.7	69.0	24 200*	69.9	68.4	18 200*	30.0
32.0	65.8	68.4	25 100 *	67.0	68.1	24 000*	68.2	67.5	17 700*	32.0
34.0	64.0	67.5	23 100	65.3	67.2	23 500	66.4	66.5	17 200*	34.0
36.0	62.3	66.4	21 100	63.5	66.1	21 500	64.6	65.5	16 800*	36.0
38.0	60.5	65.3	19 300	61.7	65.0	19 600	62.8	64.3	16 300*	38.0
40.0	58.6	64.1	17 700	59.8	63.8	18 000	60.9	63.1	16 000*	40.0
44.0	54.8	61.4	15 000	56.0	61.1	15 300	57.0	60.4	15 300*	44.0
48.0	50.8	58.3	12 700	52.0	58.0	13 000	52.9	57.2	13 200	48.0
52.0	46.6	54.7	10 800	47.7	54.4	11 100	48.6	53.6	11 200	52.0
56.0	42.0	50.5	9 300	43.1	50.1	9 400	43.9	49.3	9 600	56.0
60.0	37.0	45.6	7 900	38.0	45.1	8 000				60.0
64.0	31.3	39.5	6 700	32.2	39.0	6 800				64.0
68.0	24.4	31.8	4 900 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
15.2	80.1	76.9	26 700 *							15.2
16.0	79.5	76.7	26 700 *							16.0
18.0	78.0	76.3	26 700 *	79.2	76.0	25 800*				18.0
20.0	76.4	75.8	26 700 *	77.6	75.6	25 500*	78.8	75.0	21 700*	20.0
22.0	74.9	75.3	26 700 *	76.1	75.0	25 200*	77.3	74.4	20 900*	22.0
24.0	73.3	74.7	26 500 *	74.5	74.4	24 900*	75.7	73.8	20 300*	24.0
26.0	71.7	74.1	26 200 *	72.9	73.8	24 700*	74.1	73.2	19 600*	26.0
28.0	70.1	73.3	25 800 *	71.3	73.1	24 400*	72.4	72.5	19 000*	28.0
30.0	68.5	72.6	25 500 *	69.6	72.3	24 200*	70.8	71.7	18 500*	30.0
32.0	66.8	71.7	24 900	68.0	71.4	24 000*	69.1	70.8	18 000*	32.0
34.0	65.2	70.8	22 900	66.3	70.5	23 400	67.4	69.9	17 500*	34.0
36.0	63.5	69.8	20 800	64.6	69.5	21 200	65.7	68.9	17 000*	36.0
38.0	61.7	68.8	19 000	62.9	68.5	19 400	64.0	67.8	16 600*	38.0
40.0	60.0	67.6	17 400	61.1	67.3	17 800	62.2	66.6	16 300*	40.0
44.0	56.4	65.1	14 800	57.5	64.8	15 000	58.6	64.1	15 300	44.0
48.0	52.7	62.2	12 500	53.8	61.8	12 800	54.7	61.1	13 000	48.0
52.0	48.7	58.8	10 600	49.8	58.5	10 800	50.7	57.7	11 000	52.0
56.0	44.5	55.0	9 000	45.6	54.6	9 200	46.4	53.8	9 400	56.0
60.0	40.0	50.5	7 700	41.0	50.1	7 800				60.0
64.0	34.9	45.1	6 500	35.9	44.7	6 600				64.0
68.0	29.1	38.6	5 200 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
15.2	80.5	79.9	26 700 *							15.2
16.0	80.0	79.8	26 700 *							16.0
18.0	78.5	79.4	26 700 *	79.6	79.1	25 700*				18.0
20.0	77.0	78.9	26 700 *	78.1	78.7	25 400*	79.3	78.1	21 900*	20.0
22.0	75.5	78.4	26 700 *	76.6	78.1	25 100*	77.8	77.5	21 200*	22.0
24.0	74.0	77.8	26 500 *	75.1	77.6	24 800*	76.2	77.0	20 500*	24.0
26.0	72.4	77.2	26 100 *	73.6	76.9	24 600*	74.7	76.3	19 900*	26.0
28.0	70.9	76.5	25 800 *	72.0	76.3	24 400*	73.1	75.6	19 300*	28.0
30.0	69.3	75.8	25 500 *	70.5	75.5	24 200*	71.6	74.9	18 700*	30.0
32.0	67.8	75.0	24 300	68.9	74.7	23 900*	70.0	74.1	18 200*	32.0
34.0	66.2	74.1	22 300	67.3	73.8	22 900	68.4	73.2	17 800*	34.0
36.0	64.6	73.2	20 500	65.7	72.9	20 900	66.7	72.2	17 300*	36.0
38.0	62.9	72.2	18 700	64.0	71.9	19 100	65.1	71.2	16 900*	38.0
40.0	61.3	71.1	17 200	62.4	70.8	17 500	63.4	70.1	16 500*	40.0
44.0	57.9	68.7	14 400	59.0	68.4	14 700	59.9	67.7	15 100	44.0
48.0	54.3	65.9	12 200	55.4	65.6	12 500	56.3	64.9	12 700	48.0
52.0	50.6	62.8	10 300	51.7	62.5	10 600	52.6	61.7	10 800	52.0
56.0	46.7	59.2	8 700	47.7	58.8	8 900	48.6	58.0	9 100	56.0
60.0	42.5	55.1	7 300	43.5	54.7	7 500	44.3	53.8	7 700	60.0
64.0	38.0	50.2	6 200	38.9	49.8	6 300				64.0
68.0	32.9	44.5	5 100	33.8	44.0	5 200				68.0
72.0	26.9	37.4	3 500 *							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
15.2	80.9	83.0	26 700 *							15.2
16.0	80.3	82.8	26 700 *							16.0
18.0	78.9	82.4	26 700 *	80.0	82.2	25 600*				18.0
20.0	77.5	82.0	26 700 *	78.6	81.7	25 300*	79.7	81.1	22 100*	20.0
22.0	76.0	81.5	26 600 *	77.1	81.2	25 000*	78.2	80.6	21 400*	22.0
24.0	74.6	81.0	26 400 *	75.7	80.7	24 800*	76.8	80.1	20 700*	24.0
26.0	73.1	80.4	26 000 *	74.2	80.1	24 500*	75.3	79.5	20 100*	26.0
28.0	71.6	79.7	25 700 *	72.7	79.4	24 300*	73.8	78.8	19 500*	28.0
30.0	70.1	79.0	25 400 *	71.2	78.7	24 100*	72.3	78.1	19 000*	30.0
32.0	68.6	78.2	23 800	69.7	77.9	23 900*	70.8	77.3	18 500*	32.0
34.0	67.1	77.4	21 900	68.2	77.1	22 400	69.2	76.5	18 000*	34.0
36.0	65.6	76.5	20 100	66.6	76.2	20 600	67.7	75.6	17 600*	36.0
38.0	64.0	75.5	18 500	65.1	75.2	18 900	66.1	74.6	17 100*	38.0
40.0	62.4	74.5	16 900	63.5	74.2	17 300	64.5	73.5	16 800*	40.0
44.0	59.2	72.2	14 200	60.2	71.9	14 500	61.2	71.2	14 800	44.0
48.0	55.8	69.6	11 900	56.9	69.3	12 200	57.8	68.6	12 500	48.0
52.0	52.3	66.7	10 100	53.4	66.3	10 300	54.3	65.6	10 500	52.0
56.0	48.7	63.3	8 500	49.7	62.9	8 700	50.5	62.2	8 900	56.0
60.0	44.8	59.5	7 100	45.8	59.1	7 300	46.6	58.2	7 400	60.0
64.0	40.6	55.0	5 900	41.6	54.6	6 100	42.3	53.7	6 200	64.0
68.0	36.0	49.9	4 900	36.9	49.4	5 000				68.0
72.0	30.9	43.7	3 600 *							72.0
76.0	24.7	35.9	2 200 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
16.8	80.1	85.7	26 700 *							16.8
18.0	79.3	85.5	26 700 *							18.0
20.0	77.9	85.1	26 700 *	79.0	84.8	25 100*	80.1	84.2	22 300*	20.0
22.0	76.5	84.6	26 500 *	77.6	84.3	24 900*	78.7	83.7	21 600*	22.0
24.0	75.1	84.1	26 200 *	76.2	83.8	24 600*	77.3	83.2	20 900*	24.0
26.0	73.7	83.5	25 900 *	74.8	83.2	24 400*	75.8	82.6	20 300*	26.0
28.0	72.3	82.9	25 500 *	73.4	82.6	24 200*	74.4	82.0	19 800*	28.0
30.0	70.9	82.2	25 300 *	71.9	81.9	24 000*	72.9	81.3	19 200*	30.0
32.0	69.4	81.4	23 600	70.5	81.2	23 800*	71.5	80.5	18 700*	32.0
34.0	68.0	80.6	21 700	69.0	80.4	22 200	70.0	79.7	18 300*	34.0
36.0	66.5	79.8	20 000	67.5	79.5	20 400	68.5	78.9	17 800*	36.0
38.0	65.0	78.9	18 500	66.0	78.6	18 800	67.0	77.9	17 400*	38.0
40.0	63.5	77.9	17 000	64.5	77.6	17 400	65.5	76.9	17 000*	40.0
44.0	60.4	75.7	14 300	61.4	75.4	14 600	62.4	74.7	14 900	44.0
48.0	57.2	73.2	12 000	58.2	72.9	12 300	59.1	72.2	12 600	48.0
52.0	53.9	70.4	10 200	54.9	70.1	10 400	55.8	69.4	10 600	52.0
56.0	50.5	67.3	8 600	51.4	66.9	8 800	52.3	66.2	9 000	56.0
60.0	46.8	63.7	7 200	47.8	63.3	7 400	48.6	62.5	7 500	60.0
64.0	42.9	59.6	6 000	43.9	59.2	6 200	44.6	58.3	6 300	64.0
68.0	38.8	54.9	4 900	39.7	54.5	5 100				68.0
72.0	34.1	49.4	4 000	35.0	48.9	4 100				72.0
76.0	28.9	42.7	2 600 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
16.8	80.5	88.8	26 700 *							16.8
18.0	79.7	88.6	26 700 *							18.0
20.0	78.3	88.2	26 700 *	79.4	87.9	25 000*	80.4	87.3	22 500*	20.0
22.0	77.0	87.7	26 300 *	78.0	87.4	24 700*	79.1	86.8	21 800*	22.0
24.0	75.6	87.2	26 000 *	76.7	86.9	24 500*	77.7	86.3	21 100*	24.0
26.0	74.3	86.6	25 700 *	75.3	86.4	24 300*	76.3	85.8	20 500*	26.0
28.0	72.9	86.0	25 400 *	73.9	85.8	24 100*	75.0	85.1	20 000*	28.0
30.0	71.5	85.4	24 900	72.6	85.1	23 900*	73.6	84.5	19 400*	30.0
32.0	70.2	84.7	23 100	71.2	84.4	23 600	72.2	83.8	18 900*	32.0
34.0	68.8	83.9	21 300	69.8	83.6	21 700	70.7	83.0	18 500*	34.0
36.0	67.3	83.1	19 600	68.3	82.8	20 000	69.3	82.1	18 000*	36.0
38.0	65.9	82.2	18 000	66.9	81.9	18 400	67.9	81.2	17 600*	38.0
40.0	64.5	81.2	16 600	65.5	80.9	17 000	66.4	80.3	17 100	40.0
44.0	61.5	79.1	14 000	62.5	78.8	14 400	63.4	78.2	14 700	44.0
48.0	58.5	76.8	11 800	59.4	76.5	12 100	60.3	75.8	12 400	48.0
52.0	55.3	74.1	9 900	56.3	73.8	10 200	57.2	73.1	10 400	52.0
56.0	52.1	71.1	8 300	53.0	70.8	8 600	53.8	70.1	8 800	56.0
60.0	48.6	67.8	7 000	49.6	67.4	7 200	50.4	66.6	7 300	60.0
64.0	45.0	63.9	5 800	45.9	63.6	5 900	46.7	62.7	6 100	64.0
68.0	41.2	59.6	4 700	42.1	59.2	4 900	42.7	58.3	5 000	68.0
72.0	37.0	54.6	3 800	37.8	54.1	3 900				72.0
76.0	32.3	48.7	2 600 *	33.1	48.2	2 800*				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
16.8	80.8	91.8	26 700 *							16.8
18.0	80.0	91.6	26 600 *							18.0
20.0	78.7	91.2	26 300 *	79.7	91.0	24 700*	80.7	90.4	22 700*	20.0
22.0	77.4	90.8	26 000 *	78.4	90.5	24 500*	79.4	89.9	22 000*	22.0
24.0	76.1	90.3	25 700 *	77.1	90.0	24 300*	78.1	89.4	21 300*	24.0
26.0	74.8	89.8	25 400 *	75.8	89.5	24 100*	76.8	88.9	20 700*	26.0
28.0	73.5	89.2	25 200 *	74.5	88.9	23 800*	75.5	88.3	20 200*	28.0
30.0	72.2	88.5	24 500	73.2	88.3	23 700*	74.1	87.6	19 700*	30.0
32.0	70.8	87.8	22 600	71.8	87.6	23 100	72.8	86.9	19 100*	32.0
34.0	69.5	87.1	20 700	70.5	86.8	21 200	71.4	86.2	18 700*	34.0
36.0	68.1	86.3	19 000	69.1	86.0	19 500	70.0	85.4	18 300*	36.0
38.0	66.8	85.5	17 500	67.7	85.2	17 900	68.7	84.5	17 800*	38.0
40.0	65.4	84.6	16 100	66.3	84.3	16 500	67.2	83.6	17 000	40.0
44.0	62.5	82.6	13 700	63.5	82.3	14 100	64.4	81.6	14 400	44.0
48.0	59.6	80.3	11 500	60.6	80.0	11 800	61.5	79.3	12 100	48.0
52.0	56.6	77.8	9 600	57.6	77.5	9 900	58.4	76.7	10 100	52.0
56.0	53.5	74.9	8 000	54.5	74.6	8 300	55.3	73.9	8 500	56.0
60.0	50.3	71.7	6 700	51.2	71.4	6 800	52.0	70.6	7 000	60.0
64.0	46.9	68.2	5 400	47.8	67.8	5 600	48.5	67.0	5 800	64.0
68.0	43.3	64.1	4 400	44.2	63.7	4 600	44.9	62.8	4 700	68.0
72.0	39.4	59.5	3 500	40.3	59.1	3 600				72.0
76.0	35.2	54.1	2 500	36.0	53.7	2 700				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
84.5m Boom										
18.3	80.2	94.6	26 300 *							18.3
20.0	79.1	94.3	26 000 *	80.1	94.0	24 500*				20.0
22.0	77.8	93.9	25 800 *	78.8	93.6	24 300*	79.8	93.0	22 200*	22.0
24.0	76.6	93.4	25 500 *	77.6	93.1	24 000*	78.5	92.5	21 500*	24.0
26.0	75.3	92.9	25 200 *	76.3	92.6	23 800*	77.2	92.0	20 900*	26.0
28.0	74.0	92.3	24 900 *	75.0	92.0	23 700*	76.0	91.4	20 400*	28.0
30.0	72.8	91.7	24 100	73.7	91.4	23 500*	74.7	90.8	19 900*	30.0
32.0	71.5	91.0	22 100	72.4	90.7	22 600	73.4	90.1	19 400*	32.0
34.0	70.2	90.3	20 200	71.1	90.0	20 700	72.0	89.4	18 900*	34.0
36.0	68.9	89.5	18 600	69.8	89.3	19 000	70.7	88.6	18 500*	36.0
38.0	67.5	88.7	17 100	68.5	88.4	17 500	69.4	87.8	17 900	38.0
40.0	66.2	87.9	15 700	67.1	87.6	16 100	68.0	86.9	16 500	40.0
44.0	63.5	85.9	13 300	64.4	85.6	13 700	65.3	85.0	14 000	44.0
48.0	60.7	83.8	11 300	61.6	83.5	11 600	62.5	82.8	11 900	48.0
52.0	57.8	81.4	9 300	58.8	81.0	9 700	59.6	80.3	9 900	52.0
56.0	54.9	78.6	7 800	55.8	78.3	8 000	56.6	77.6	8 300	56.0
60.0	51.8	75.6	6 400	52.7	75.3	6 600	53.5	74.5	6 800	60.0
64.0	48.6	72.2	5 200	49.5	71.9	5 400	50.2	71.1	5 600	64.0
68.0	45.2	68.4	4 200	46.1	68.1	4 300	46.8	67.2	4 500	68.0
72.0	41.6	64.1	3 200	42.5	63.7	3 400	43.1	62.8	3 500	72.0
76.0	37.8	59.2	2 300 *	38.6	58.8	2 500				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
9.1	80.7	41.4	25 000 *							9.1
10.0	79.5	41.2	24 600 *							10.0
12.0	76.5	40.7	23 700 *							12.0
14.0	73.5	40.1	22 800 *	76.5	39.8	21 200*	79.7	39.1	17 500*	14.0
16.0	70.4	39.4	22 100 *	73.4	39.1	20 700*	76.5	38.4	16 300*	16.0
18.0	67.3	38.6	21 400 *	70.2	38.2	20 200*	73.3	37.5	15 300*	18.0
20.0	64.1	37.6	20 800 *	67.0	37.3	19 800*	69.9	36.5	14 500*	20.0
22.0	60.7	36.5	20 200 *	63.7	36.1	18 900*	66.5	35.4	13 700*	22.0
24.0	57.3	35.2	19 700 *	60.2	34.8	17 600*	63.0	34.0	13 000*	24.0
26.0	53.7	33.7	19 300 *	56.6	33.3	16 500*	59.2	32.5	12 500*	26.0
28.0	49.9	32.0	18 700 *	52.7	31.6	15 500*	55.3	30.8	12 000*	28.0
30.0	45.9	30.1	17 600 *	48.7	29.7	14 700*	51.1	28.7	11 500*	30.0
32.0	41.6	27.9	16 400 *	44.3	27.4	13 900*	46.5	26.4	11 200*	32.0
34.0	36.9	25.3	15 500 *	39.4	24.7	13 300*				34.0
36.0	31.5	22.1	14 600 *	33.9	21.5	12 800*				36.0
38.0	25.0	18.1	13 900 *							38.0
30.5m Boom										
10.7	79.3	44.2	24 400 *							10.7
12.0	77.5	43.9	23 900 *							12.0
14.0	74.7	43.3	23 100 *	77.5	43.0	21 400*	80.4	42.3	17 800*	14.0
16.0	71.9	42.6	22 400 *	74.7	42.3	20 900*	77.5	41.6	16 700*	16.0
18.0	69.0	41.8	21 700 *	71.7	41.5	20 400*	74.6	40.8	15 700*	18.0
20.0	66.0	41.0	21 100 *	68.8	40.6	20 100*	71.5	39.9	14 900*	20.0
22.0	63.0	39.9	20 600 *	65.7	39.6	19 500*	68.4	38.8	14 100*	22.0
24.0	59.9	38.8	20 100 *	62.6	38.4	18 500*	65.2	37.6	13 500*	24.0
26.0	56.7	37.4	19 600 *	59.3	37.1	17 300*	61.9	36.2	12 900*	26.0
28.0	53.3	36.0	19 200 *	56.0	35.6	16 300*	58.4	34.7	12 400*	28.0
30.0	49.8	34.3	18 700 *	52.4	33.9	15 400*	54.8	32.9	11 900*	30.0
32.0	46.1	32.4	17 600 *	48.6	31.9	14 600*	50.9	30.9	11 500*	32.0
34.0	42.1	30.2	16 500 *	44.6	29.7	14 000*	46.7	28.6	11 200*	34.0
36.0	37.8	27.6	15 600 *	40.2	27.1	13 400*				36.0
38.0	32.9	24.6	14 800 *	35.2	24.0	12 900*				38.0
40.0	27.3	20.9	14 100 *							40.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
10.7	80.0	47.2	24 600 *							10.7
12.0	78.3	46.9	24 100 *							12.0
14.0	75.7	46.4	23 300 *	78.4	46.1	21 500*				14.0
16.0	73.1	45.8	22 600 *	75.7	45.5	21 000*	78.4	44.7	17 000*	16.0
18.0	70.4	45.1	22 000 *	73.0	44.7	20 600*	75.7	44.0	16 100*	18.0
20.0	67.7	44.3	21 400 *	70.3	43.9	20 200*	72.9	43.2	15 200*	20.0
22.0	64.9	43.3	20 900 *	67.5	43.0	19 900*	70.0	42.2	14 500*	22.0
24.0	62.1	42.2	20 400 *	64.6	41.9	19 200*	67.1	41.1	13 800*	24.0
26.0	59.2	41.0	19 900 *	61.7	40.7	18 100*	64.1	39.9	13 300*	26.0
28.0	56.1	39.7	19 500 *	58.6	39.3	17 000*	61.0	38.5	12 700*	28.0
30.0	53.0	38.2	19 100 *	55.4	37.8	16 200*	57.7	36.9	12 300*	30.0
32.0	49.7	36.5	18 800 *	52.1	36.1	15 400*	54.3	35.1	11 900*	32.0
34.0	46.2	34.6	17 700 *	48.6	34.1	14 600*	50.7	33.2	11 500*	34.0
36.0	42.6	32.4	16 600 *	44.9	32.0	14 000*	46.8	30.9	11 200*	36.0
38.0	38.6	30.0	15 800 *	40.8	29.4	13 400*				38.0
40.0	34.2	27.1	15 000 *	36.3	26.5	13 000*				40.0
44.0	23.1	19.3	13 700 *							44.0
36.5m Boom										
10.7	80.6	50.3	24 700 *							10.7
12.0	79.0	50.0	24 200 *							12.0
14.0	76.6	49.5	23 500 *	79.1	49.2	21 600*				14.0
16.0	74.2	49.0	22 800 *	76.6	48.6	21 200*	79.2	47.9	17 300*	16.0
18.0	71.7	48.3	22 200 *	74.1	47.9	20 800*	76.6	47.2	16 400*	18.0
20.0	69.2	47.5	21 700 *	71.6	47.2	20 400*	74.0	46.4	15 600*	20.0
22.0	66.6	46.6	21 100 *	69.0	46.3	20 000*	71.4	45.5	14 800*	22.0
24.0	64.0	45.7	20 600 *	66.4	45.3	19 700*	68.7	44.5	14 200*	24.0
26.0	61.3	44.6	20 200 *	63.6	44.2	18 900*	65.9	43.4	13 600*	26.0
28.0	58.5	43.3	19 800 *	60.9	42.9	17 800*	63.1	42.1	13 100*	28.0
30.0	55.7	42.0	19 400 *	58.0	41.6	16 800*	60.2	40.7	12 600*	30.0
32.0	52.7	40.4	19 100 *	55.0	40.0	16 100*	57.1	39.1	12 200*	32.0
34.0	49.6	38.7	18 700 *	51.9	38.3	15 300*	53.9	37.4	11 800*	34.0
36.0	46.4	36.8	17 700 *	48.6	36.4	14 700*	50.5	35.4	11 500*	36.0
38.0	42.9	34.7	16 700 *	45.1	34.2	14 000*	46.9	33.1	11 200*	38.0
40.0	39.2	32.3	15 900 *	41.3	31.8	13 500*				40.0
44.0	30.7	26.2	14 500 *	32.6	25.6	12 600*				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	79.5	53.0	24 200 *							12.2
14.0	77.4	52.6	23 600 *	79.8	52.3	21 700*				14.0
16.0	75.1	52.1	23 000 *	77.4	51.7	21 300*	79.8	51.0	17 600*	16.0
18.0	72.8	51.5	22 400 *	75.1	51.1	20 900*	77.5	50.4	16 700*	18.0
20.0	70.4	50.7	21 900 *	72.7	50.4	20 500*	75.0	49.6	15 800*	20.0
22.0	68.0	49.9	21 400 *	70.3	49.6	20 200*	72.6	48.8	15 100*	22.0
24.0	65.6	49.0	20 900 *	67.9	48.6	19 900*	70.1	47.9	14 500*	24.0
26.0	63.1	48.0	20 400 *	65.3	47.6	19 600*	67.5	46.8	13 900*	26.0
28.0	60.6	46.9	20 100 *	62.8	46.5	18 500*	64.9	45.6	13 400*	28.0
30.0	57.9	45.6	19 700 *	60.1	45.2	17 600*	62.2	44.3	12 900*	30.0
32.0	55.2	44.2	19 400 *	57.4	43.8	16 700*	59.4	42.9	12 500*	32.0
34.0	52.4	42.7	19 000 *	54.6	42.2	15 900*	56.5	41.3	12 100*	34.0
36.0	49.5	41.0	18 600 *	51.6	40.5	15 200*	53.5	39.6	11 800*	36.0
38.0	46.5	39.1	17 700 *	48.5	38.6	14 600*	50.4	37.6	11 500*	38.0
40.0	43.3	37.0	16 800 *	45.3	36.5	14 100*	47.0	35.4	11 200*	40.0
44.0	36.1	31.9	15 300 *	38.0	31.3	13 100*				44.0
48.0	27.3	25.1	14 100 *							48.0
42.5m Boom										
12.2	80.1	56.1	24 300 *							12.2
14.0	78.1	55.7	23 800 *	80.3	55.4	21 800*				14.0
16.0	76.0	55.2	23 100 *	78.2	54.9	21 300*				16.0
18.0	73.8	54.6	22 600 *	76.0	54.3	21 000*	78.2	53.5	16 900*	18.0
20.0	71.6	53.9	22 000 *	73.7	53.6	20 600*	75.9	52.8	16 200*	20.0
22.0	69.3	53.2	21 600 *	71.5	52.8	20 300*	73.6	52.0	15 400*	22.0
24.0	67.0	52.3	21 100 *	69.2	52.0	20 000*	71.3	51.2	14 800*	24.0
26.0	64.7	51.4	20 700 *	66.8	51.0	19 700*	68.9	50.2	14 200*	26.0
28.0	62.3	50.3	20 300 *	64.5	49.9	19 300*	66.5	49.1	13 700*	28.0
30.0	59.9	49.2	19 900 *	62.0	48.8	18 200*	64.0	47.9	13 200*	30.0
32.0	57.4	47.9	19 600 *	59.5	47.5	17 300*	61.4	46.6	12 800*	32.0
34.0	54.9	46.5	19 300 *	56.9	46.0	16 600*	58.8	45.1	12 400*	34.0
36.0	52.2	44.9	19 000 *	54.2	44.5	15 900*	56.1	43.5	12 100*	36.0
38.0	49.5	43.2	18 700 *	51.4	42.8	15 200*	53.2	41.8	11 800*	38.0
40.0	46.6	41.3	17 700 *	48.5	40.9	14 600*	50.2	39.8	11 500*	40.0
44.0	40.3	36.9	16 100 *	42.2	36.4	13 600*	43.7	35.2	11 000*	44.0
48.0	33.1	31.3	14 700	34.8	30.6	12 800*				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
12.2	80.6	59.2	24 400 *							12.2
14.0	78.8	58.8	23 800 *							14.0
16.0	76.7	58.3	23 200 *	78.8	58.0	21 400 *				16.0
18.0	74.6	57.7	22 700 *	76.7	57.4	21 000 *	78.8	56.6	17 200 *	18.0
20.0	72.6	57.1	22 200 *	74.6	56.8	20 700 *	76.7	56.0	16 400 *	20.0
22.0	70.4	56.4	21 700 *	72.5	56.0	20 400 *	74.6	55.2	15 700 *	22.0
24.0	68.3	55.6	21 300 *	70.3	55.2	20 100 *	72.4	54.4	15 100 *	24.0
26.0	66.1	54.7	20 900 *	68.1	54.3	19 900 *	70.1	53.5	14 500 *	26.0
28.0	63.9	53.7	20 500 *	65.9	53.3	19 600 *	67.9	52.5	14 000 *	28.0
30.0	61.7	52.6	20 100 *	63.6	52.2	18 900 *	65.6	51.4	13 500 *	30.0
32.0	59.3	51.4	19 800 *	61.3	51.0	18 000 *	63.2	50.2	13 100 *	32.0
34.0	57.0	50.1	19 500 *	58.9	49.7	17 100 *	60.7	48.8	12 700 *	34.0
36.0	54.5	48.7	19 200 *	56.5	48.3	16 400 *	58.2	47.4	12 300 *	36.0
38.0	52.0	47.2	18 900 *	53.9	46.7	15 800 *	55.6	45.8	12 000 *	38.0
40.0	49.4	45.4	18 600 *	51.3	45.0	15 200 *	52.9	44.0	11 700 *	40.0
44.0	43.8	41.5	16 700	45.6	41.0	14 100 *	47.1	39.9	11 200 *	44.0
48.0	37.5	36.6	14 400	39.3	36.1	13 300 *				48.0
52.0	30.2	30.4	12 500							52.0
48.5m Boom										
13.7	79.6	61.9	23 900 *							13.7
14.0	79.3	61.9	23 900 *							14.0
16.0	77.4	61.4	23 300 *	79.4	61.0	21 500 *				16.0
18.0	75.4	60.9	22 800 *	77.4	60.5	21 100 *	79.4	59.7	17 400 *	18.0
20.0	73.5	60.3	22 300 *	75.4	59.9	20 800 *	77.4	59.1	16 700 *	20.0
22.0	71.5	59.6	21 900 *	73.4	59.2	20 500 *	75.4	58.4	16 000 *	22.0
24.0	69.4	58.8	21 400 *	71.4	58.5	20 200 *	73.3	57.7	15 300 *	24.0
26.0	67.4	58.0	21 100 *	69.3	57.6	19 900 *	71.2	56.8	14 800 *	26.0
28.0	65.3	57.1	20 700 *	67.2	56.7	19 700 *	69.1	55.9	14 300 *	28.0
30.0	63.2	56.1	20 300 *	65.1	55.7	19 400 *	66.9	54.8	13 800 *	30.0
32.0	61.0	54.9	20 000 *	62.9	54.5	18 500 *	64.7	53.7	13 400 *	32.0
34.0	58.8	53.7	19 700 *	60.7	53.3	17 700 *	62.4	52.4	13 000 *	34.0
36.0	56.6	52.4	19 400 *	58.4	52.0	17 000 *	60.1	51.1	12 600 *	36.0
38.0	54.2	51.0	19 100 *	56.0	50.5	16 300 *	57.7	49.6	12 300 *	38.0
40.0	51.8	49.4	18 800	53.6	48.9	15 700 *	55.3	48.0	12 000 *	40.0
44.0	46.7	45.8	16 500	48.5	45.3	14 600 *	50.0	44.3	11 400 *	44.0
48.0	41.2	41.5	14 200	42.9	40.9	13 700 *	44.2	39.8	11 000 *	48.0
52.0	34.9	36.1	12 300	36.5	35.5	12 500				52.0
56.0	27.3	29.2	10 600							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
13.7	80.1	65.0	23 900 *							13.7
14.0	79.8	64.9	23 900 *							14.0
16.0	78.0	64.5	23 400 *	79.9	64.1	21 500*				16.0
18.0	76.1	64.0	22 900 *	78.0	63.6	21 100*				18.0
20.0	74.3	63.4	22 400 *	76.1	63.0	20 800*	78.0	62.3	16 800*	20.0
22.0	72.4	62.8	22 000 *	74.2	62.4	20 500*	76.1	61.6	16 200*	22.0
24.0	70.5	62.0	21 600 *	72.3	61.7	20 300*	74.2	60.9	15 600*	24.0
26.0	68.5	61.3	21 200 *	70.4	60.9	20 000*	72.2	60.1	15 000*	26.0
28.0	66.6	60.4	20 800 *	68.4	60.0	19 800*	70.2	59.2	14 500*	28.0
30.0	64.6	59.4	20 500 *	66.4	59.0	19 600*	68.1	58.2	14 100*	30.0
32.0	62.5	58.4	20 100 *	64.3	58.0	19 100*	66.1	57.1	13 600*	32.0
34.0	60.5	57.2	19 800 *	62.2	56.8	18 300*	63.9	56.0	13 200*	34.0
36.0	58.3	56.0	19 600 *	60.1	55.6	17 500*	61.8	54.7	12 900*	36.0
38.0	56.2	54.7	19 300 *	57.9	54.2	16 900*	59.6	53.3	12 500*	38.0
40.0	53.9	53.2	18 900	55.7	52.8	16 200*	57.3	51.8	12 200*	40.0
44.0	49.3	49.9	16 300	51.0	49.4	15 100*	52.5	48.4	11 700*	44.0
48.0	44.2	46.0	14 000	45.9	45.5	14 100	47.2	44.4	11 200*	48.0
52.0	38.7	41.3	12 100	40.2	40.7	12 300				52.0
56.0	32.3	35.4	10 500	33.7	34.8	10 700				56.0
60.0	24.4	27.7	8 600 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
13.7	80.5	68.0	23 900 *							13.7
14.0	80.3	68.0	23 900 *							14.0
16.0	78.5	67.6	23 400 *	80.3	67.2	21 400*				16.0
18.0	76.8	67.1	22 900 *	78.6	66.7	21 100*				18.0
20.0	75.0	66.5	22 500 *	76.8	66.2	20 800*	78.6	65.4	17 100*	20.0
22.0	73.2	65.9	22 000 *	75.0	65.6	20 600*	76.8	64.8	16 400*	22.0
24.0	71.4	65.2	21 700 *	73.1	64.9	20 400*	74.9	64.1	15 800*	24.0
26.0	69.5	64.5	21 300 *	71.3	64.1	20 100*	73.1	63.3	15 300*	26.0
28.0	67.7	63.7	20 900 *	69.4	63.3	19 900*	71.2	62.5	14 800*	28.0
30.0	65.8	62.8	20 600 *	67.5	62.4	19 700*	69.2	61.5	14 300*	30.0
32.0	63.9	61.8	20 300 *	65.6	61.4	19 500*	67.3	60.5	13 900*	32.0
34.0	61.9	60.7	20 000 *	63.6	60.3	18 900*	65.3	59.4	13 500*	34.0
36.0	59.9	59.5	19 700 *	61.6	59.1	18 100*	63.2	58.2	13 100*	36.0
38.0	57.9	58.3	19 500 *	59.6	57.9	17 400*	61.2	57.0	12 800*	38.0
40.0	55.8	56.9	18 800	57.5	56.5	16 700*	59.0	55.6	12 500*	40.0
44.0	51.5	53.9	16 000	53.1	53.4	15 600*	54.6	52.4	11 900*	44.0
48.0	46.9	50.3	13 800	48.5	49.8	14 100	49.8	48.7	11 400*	48.0
52.0	41.9	46.0	11 900	43.4	45.5	12 100				52.0
56.0	36.3	40.9	10 300	37.7	40.3	10 500				56.0
60.0	29.8	34.5	8 900							60.0
64.0	21.5	25.7	6 800 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
13.7	81.0	71.1	23 900 *							13.7
14.0	80.7	71.0	23 800 *							14.0
16.0	79.0	70.6	23 400 *							16.0
18.0	77.4	70.2	22 900 *	79.1	69.8	21 100*				18.0
20.0	75.7	69.7	22 500 *	77.4	69.3	20 800*	79.1	68.5	17 300*	20.0
22.0	73.9	69.1	22 100 *	75.6	68.7	20 600*	77.4	67.9	16 600*	22.0
24.0	72.2	68.4	21 700 *	73.9	68.1	20 400*	75.6	67.2	16 000*	24.0
26.0	70.5	67.7	21 400 *	72.2	67.3	20 100*	73.8	66.5	15 500*	26.0
28.0	68.7	66.9	21 000 *	70.4	66.5	19 900*	72.0	65.7	15 000*	28.0
30.0	66.9	66.1	20 700 *	68.6	65.7	19 700*	70.2	64.8	14 500*	30.0
32.0	65.1	65.1	20 400 *	66.7	64.7	19 500*	68.4	63.9	14 100*	32.0
34.0	63.2	64.1	20 100 *	64.9	63.7	19 300*	66.5	62.9	13 700*	34.0
36.0	61.4	63.0	19 800 *	63.0	62.6	18 600*	64.6	61.7	13 300*	36.0
38.0	59.5	61.8	19 600 *	61.1	61.4	17 900*	62.6	60.5	13 000*	38.0
40.0	57.5	60.6	18 500	59.1	60.1	17 200*	60.6	59.2	12 700*	40.0
44.0	53.5	57.7	15 700	55.0	57.3	16 000	56.5	56.3	12 100*	44.0
48.0	49.2	54.4	13 500	50.7	53.9	13 800	52.1	52.9	11 600*	48.0
52.0	44.6	50.5	11 600	46.1	50.0	11 800	47.3	48.9	11 200*	52.0
56.0	39.6	45.9	10 000	41.0	45.3	10 200				56.0
60.0	34.0	40.3	8 600	35.3	39.7	8 700				60.0
64.0	27.3	33.3	7 200							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
15.2	80.1	73.8	23 500 *							15.2
16.0	79.5	73.7	23 300 *							16.0
18.0	77.9	73.3	22 900 *	79.5	72.9	21 100*				18.0
20.0	76.3	72.8	22 500 *	77.9	72.4	20 800*	79.6	71.6	17 400*	20.0
22.0	74.6	72.2	22 100 *	76.3	71.8	20 600*	77.9	71.0	16 800*	22.0
24.0	73.0	71.6	21 800 *	74.6	71.2	20 400*	76.2	70.4	16 200*	24.0
26.0	71.3	70.9	21 400 *	72.9	70.5	20 200*	74.6	69.7	15 700*	26.0
28.0	69.6	70.2	21 100 *	71.2	69.8	20 000*	72.8	68.9	15 200*	28.0
30.0	67.9	69.3	20 800 *	69.5	68.9	19 800*	71.1	68.1	14 800*	30.0
32.0	66.2	68.4	20 500 *	67.8	68.1	19 600*	69.3	67.2	14 300*	32.0
34.0	64.4	67.5	20 200 *	66.0	67.1	19 500*	67.6	66.2	13 900*	34.0
36.0	62.7	66.4	20 000 *	64.2	66.0	19 100*	65.7	65.2	13 600*	36.0
38.0	60.9	65.3	19 700 *	62.4	64.9	18 400*	63.9	64.0	13 200*	38.0
40.0	59.0	64.1	18 200	60.6	63.7	17 700*	62.0	62.8	12 900*	40.0
44.0	55.2	61.4	15 500	56.7	61.0	15 900	58.1	60.0	12 300*	44.0
48.0	51.2	58.3	13 300	52.7	57.9	13 600	54.0	56.9	11 800*	48.0
52.0	47.0	54.8	11 400	48.4	54.3	11 600	49.7	53.2	11 400	52.0
56.0	42.4	50.6	9 800	43.8	50.0	10 000	45.0	48.9	10 200	56.0
60.0	37.4	45.6	8 400	38.7	45.0	8 600				60.0
64.0	31.7	39.6	7 200	32.9	38.9	7 300				64.0
68.0	24.8	31.8	5 500 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
15.2	80.5	76.9	23 400 *							15.2
16.0	79.9	76.7	23 200 *							16.0
18.0	78.4	76.3	22 900 *	80.0	76.0	21 100*				18.0
20.0	76.8	75.9	22 500 *	78.4	75.5	20 800*	80.0	74.7	17 600*	20.0
22.0	75.2	75.3	22 100 *	76.8	75.0	20 600*	78.4	74.1	17 000*	22.0
24.0	73.7	74.7	21 800 *	75.2	74.4	20 400*	76.8	73.5	16 400*	24.0
26.0	72.1	74.1	21 400 *	73.6	73.7	20 200*	75.2	72.9	15 900*	26.0
28.0	70.5	73.4	21 100 *	72.0	73.0	20 000*	73.6	72.1	15 400*	28.0
30.0	68.8	72.6	20 800 *	70.4	72.2	19 800*	71.9	71.4	15 000*	30.0
32.0	67.2	71.7	20 500 *	68.7	71.3	19 600*	70.2	70.5	14 600*	32.0
34.0	65.5	70.8	20 300 *	67.1	70.4	19 500*	68.5	69.6	14 100*	34.0
36.0	63.8	69.8	20 000 *	65.4	69.4	19 300*	66.8	68.6	13 800*	36.0
38.0	62.1	68.8	19 500	63.6	68.4	18 900*	65.1	67.5	13 400*	38.0
40.0	60.4	67.6	18 000	61.9	67.2	18 100	63.3	66.3	13 100*	40.0
44.0	56.8	65.1	15 300	58.3	64.7	15 600	59.6	63.7	12 500*	44.0
48.0	53.1	62.2	13 000	54.5	61.7	13 300	55.8	60.7	12 000*	48.0
52.0	49.1	58.8	11 200	50.5	58.4	11 400	51.7	57.3	11 600	52.0
56.0	44.9	55.0	9 500	46.3	54.5	9 800	47.4	53.3	10 000	56.0
60.0	40.3	50.5	8 200	41.7	49.9	8 300				60.0
64.0	35.3	45.2	6 900	36.5	44.5	7 100				64.0
68.0	29.5	38.6	5 800 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
15.2	80.9	79.9	23 300 *							15.2
16.0	80.3	79.8	23 200 *							16.0
18.0	78.8	79.4	22 800 *							18.0
20.0	77.3	78.9	22 500 *	78.9	78.6	20 800*	80.4	77.8	17 800*	20.0
22.0	75.8	78.4	22 100 *	77.3	78.1	20 600*	78.9	77.3	17 200*	22.0
24.0	74.3	77.9	21 800 *	75.8	77.5	20 400*	77.4	76.7	16 600*	24.0
26.0	72.8	77.2	21 500 *	74.3	76.9	20 200*	75.8	76.0	16 100*	26.0
28.0	71.2	76.6	21 100 *	72.7	76.2	20 000*	74.2	75.3	15 600*	28.0
30.0	69.7	75.8	20 900 *	71.2	75.4	19 800*	72.7	74.6	15 200*	30.0
32.0	68.1	75.0	20 600 *	69.6	74.6	19 600*	71.1	73.8	14 700*	32.0
34.0	66.5	74.1	20 400 *	68.0	73.7	19 500*	69.4	72.9	14 400*	34.0
36.0	64.9	73.2	20 100 *	66.4	72.8	19 400*	67.8	71.9	14 000*	36.0
38.0	63.3	72.2	19 300	64.7	71.8	19 200*	66.1	70.9	13 700*	38.0
40.0	61.6	71.1	17 800	63.1	70.7	18 300	64.4	69.8	13 300*	40.0
44.0	58.2	68.7	15 000	59.7	68.3	15 400	61.0	67.3	12 700*	44.0
48.0	54.7	66.0	12 800	56.1	65.5	13 100	57.4	64.5	12 200*	48.0
52.0	51.0	62.8	10 900	52.4	62.3	11 200	53.6	61.3	11 400	52.0
56.0	47.1	59.2	9 300	48.4	58.7	9 600	49.6	57.6	9 800	56.0
60.0	42.9	55.1	7 900	44.2	54.6	8 200	45.2	53.4	8 300	60.0
64.0	38.3	50.3	6 700	39.6	49.7	6 900				64.0
68.0	33.2	44.5	5 700	34.4	43.9	5 800				68.0
72.0	27.3	37.4	4 300 *							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	80.1	82.7	22 900 *							16.8
18.0	79.2	82.5	22 700 *							18.0
20.0	77.8	82.0	22 400 *	79.3	81.7	20 700*	80.8	80.8	17 900*	20.0
22.0	76.4	81.5	22 000 *	77.8	81.2	20 500*	79.3	80.3	17 400*	22.0
24.0	74.9	81.0	21 700 *	76.4	80.6	20 300*	77.8	79.8	16 800*	24.0
26.0	73.4	80.4	21 400 *	74.9	80.0	20 100*	76.4	79.2	16 300*	26.0
28.0	72.0	79.7	21 100 *	73.4	79.4	19 900*	74.9	78.5	15 800*	28.0
30.0	70.5	79.0	20 800 *	71.9	78.6	19 800*	73.3	77.8	15 400*	30.0
32.0	69.0	78.2	20 600 *	70.4	77.9	19 600*	71.8	77.0	14 900*	32.0
34.0	67.4	77.4	20 400 *	68.9	77.0	19 500*	70.3	76.2	14 600*	34.0
36.0	65.9	76.5	20 100 *	67.3	76.1	19 300*	68.7	75.2	14 200*	36.0
38.0	64.3	75.5	19 100	65.8	75.1	19 200*	67.1	74.3	13 800*	38.0
40.0	62.8	74.5	17 500	64.2	74.1	18 000	65.5	73.2	13 500*	40.0
44.0	59.5	72.2	14 700	60.9	71.8	15 100	62.2	70.9	12 900*	44.0
48.0	56.2	69.6	12 500	57.5	69.2	12 800	58.8	68.2	12 400*	48.0
52.0	52.7	66.7	10 600	54.0	66.2	10 900	55.2	65.2	11 200	52.0
56.0	49.0	63.3	9 000	50.3	62.8	9 300	51.5	61.8	9 500	56.0
60.0	45.1	59.5	7 600	46.4	59.0	7 800	47.5	57.8	8 000	60.0
64.0	41.0	55.1	6 400	42.2	54.5	6 600	43.2	53.3	6 800	64.0
68.0	36.4	49.9	5 300	37.6	49.3	5 500				68.0
72.0	31.2	43.7	4 200 *							72.0
76.0	25.1	36.0	2 800 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
16.8	80.5	85.8	22 800 *							16.8
18.0	79.6	85.5	22 600 *							18.0
20.0	78.2	85.1	22 300 *	79.7	84.7	20 600*				20.0
22.0	76.9	84.6	21 900 *	78.3	84.3	20 400*	79.7	83.4	17 500*	22.0
24.0	75.5	84.1	21 600 *	76.9	83.7	20 300*	78.3	82.9	17 000*	24.0
26.0	74.0	83.5	21 300 *	75.4	83.1	20 100*	76.9	82.3	16 400*	26.0
28.0	72.6	82.9	21 100 *	74.0	82.5	19 900*	75.4	81.7	16 000*	28.0
30.0	71.2	82.2	20 800 *	72.6	81.8	19 700*	74.0	81.0	15 500*	30.0
32.0	69.7	81.5	20 600 *	71.1	81.1	19 600*	72.5	80.2	15 100*	32.0
34.0	68.3	80.7	20 400 *	69.7	80.3	19 400*	71.0	79.4	14 700*	34.0
36.0	66.8	79.8	20 000	68.2	79.4	19 300*	69.5	78.5	14 400*	36.0
38.0	65.3	78.9	18 700	66.7	78.5	19 200	68.0	77.6	14 000*	38.0
40.0	63.8	77.9	17 200	65.2	77.5	17 700	66.5	76.6	13 700*	40.0
44.0	60.7	75.7	14 500	62.1	75.3	14 900	63.3	74.4	13 100*	44.0
48.0	57.6	73.2	12 300	58.9	72.8	12 600	60.1	71.9	12 600*	48.0
52.0	54.2	70.5	10 300	55.5	70.0	10 700	56.7	69.0	11 000	52.0
56.0	50.8	67.3	8 800	52.1	66.8	9 000	53.2	65.8	9 300	56.0
60.0	47.2	63.7	7 400	48.4	63.2	7 600	49.5	62.1	7 800	60.0
64.0	43.3	59.6	6 200	44.5	59.1	6 400	45.5	57.9	6 500	64.0
68.0	39.1	54.9	5 100	40.3	54.3	5 300				68.0
72.0	34.5	49.4	4 200	35.6	48.7	4 300				72.0
76.0	29.2	42.7	2 800 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
16.8	80.8	88.8	22 600 *							16.8
18.0	80.0	88.6	22 400 *							18.0
20.0	78.7	88.2	22 100 *	80.0	87.8	20 500*				20.0
22.0	77.3	87.7	21 800 *	78.7	87.3	20 300*	80.1	86.5	17 700*	22.0
24.0	76.0	87.2	21 500 *	77.3	86.8	20 100*	78.7	86.0	17 100*	24.0
26.0	74.6	86.7	21 300 *	76.0	86.3	20 000*	77.3	85.4	16 600*	26.0
28.0	73.2	86.1	21 000 *	74.6	85.7	19 800*	75.9	84.8	16 100*	28.0
30.0	71.9	85.4	20 700 *	73.2	85.0	19 700*	74.5	84.2	15 700*	30.0
32.0	70.5	84.7	20 500 *	71.8	84.3	19 500*	73.1	83.4	15 300*	32.0
34.0	69.1	83.9	20 300 *	70.4	83.5	19 400*	71.7	82.7	14 900*	34.0
36.0	67.7	83.1	19 900	69.0	82.7	19 300*	70.3	81.8	14 600*	36.0
38.0	66.2	82.2	18 600	67.5	81.8	19 100	68.8	80.9	14 200*	38.0
40.0	64.8	81.3	17 200	66.1	80.8	17 700	67.4	80.0	13 900*	40.0
44.0	61.8	79.2	14 500	63.1	78.7	15 000	64.4	77.8	13 300*	44.0
48.0	58.8	76.8	12 300	60.1	76.4	12 700	61.3	75.4	12 800	48.0
52.0	55.7	74.2	10 400	56.9	73.7	10 800	58.1	72.7	11 100	52.0
56.0	52.4	71.2	8 800	53.6	70.7	9 100	54.7	69.7	9 300	56.0
60.0	49.0	67.8	7 400	50.2	67.3	7 700	51.2	66.2	7 900	60.0
64.0	45.4	64.0	6 300	46.5	63.5	6 400	47.5	62.3	6 600	64.0
68.0	41.5	59.6	5 200	42.6	59.1	5 400	43.5	57.8	5 500	68.0
72.0	37.3	54.6	4 300	38.4	54.0	4 400				72.0
76.0	32.7	48.7	3 200 *	33.7	48.0	3 500				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
18.3	80.1	91.6	22 200 *							18.3
20.0	79.0	91.2	22 000 *	80.4	90.9	20 400*				20.0
22.0	77.7	90.8	21 700 *	79.1	90.4	20 200*	80.4	89.6	17 800*	22.0
24.0	76.4	90.3	21 400 *	77.8	89.9	20 000*	79.1	89.1	17 300*	24.0
26.0	75.1	89.8	21 100 *	76.4	89.4	19 900*	77.8	88.6	16 800*	26.0
28.0	73.8	89.2	20 900 *	75.1	88.8	19 700*	76.4	88.0	16 300*	28.0
30.0	72.5	88.6	20 600 *	73.8	88.2	19 600*	75.1	87.3	15 900*	30.0
32.0	71.1	87.9	20 400 *	72.4	87.5	19 500*	73.7	86.6	15 500*	32.0
34.0	69.8	87.1	20 200 *	71.1	86.7	19 300*	72.4	85.9	15 100*	34.0
36.0	68.4	86.3	19 600	69.7	85.9	19 200*	71.0	85.1	14 700*	36.0
38.0	67.1	85.5	18 200	68.3	85.1	18 700	69.6	84.2	14 400*	38.0
40.0	65.7	84.6	16 800	67.0	84.2	17 300	68.2	83.3	14 100*	40.0
44.0	62.9	82.6	14 300	64.1	82.2	14 800	65.3	81.3	13 500*	44.0
48.0	60.0	80.3	12 100	61.2	79.9	12 500	62.4	79.0	12 800	48.0
52.0	57.0	77.8	10 200	58.2	77.4	10 500	59.3	76.4	10 800	52.0
56.0	53.9	75.0	8 600	55.1	74.5	8 900	56.1	73.5	9 200	56.0
60.0	50.6	71.8	7 200	51.8	71.3	7 500	52.8	70.2	7 700	60.0
64.0	47.2	68.2	6 000	48.4	67.7	6 200	49.4	66.6	6 400	64.0
68.0	43.6	64.1	4 900	44.8	63.6	5 100	45.7	62.4	5 300	68.0
72.0	39.8	59.5	4 000	40.9	58.9	4 200				72.0
76.0	35.6	54.2	3 200	36.6	53.5	3 300				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
18.3	80.5	94.6	22 000 *							18.3
20.0	79.4	94.3	21 700 *	80.7	93.9	20 200*				20.0
22.0	78.1	93.9	21 500 *	79.4	93.5	20 000*				22.0
24.0	76.9	93.4	21 200 *	78.2	93.0	19 900*	79.5	92.2	17 400*	24.0
26.0	75.6	92.9	20 900 *	76.9	92.5	19 700*	78.2	91.7	16 900*	26.0
28.0	74.3	92.3	20 700 *	75.6	91.9	19 600*	76.9	91.1	16 500*	28.0
30.0	73.1	91.7	20 500 *	74.3	91.3	19 400*	75.6	90.5	16 000*	30.0
32.0	71.8	91.0	20 300 *	73.0	90.7	19 300*	74.3	89.8	15 600*	32.0
34.0	70.5	90.3	20 000	71.7	89.9	19 200*	73.0	89.1	15 200*	34.0
36.0	69.2	89.6	19 300	70.4	89.2	19 000*	71.6	88.3	14 900*	36.0
38.0	67.8	88.8	17 700	69.1	88.3	18 200	70.3	87.5	14 600*	38.0
40.0	66.5	87.9	16 300	67.7	87.5	16 800	68.9	86.6	14 200*	40.0
44.0	63.8	86.0	13 900	65.0	85.5	14 300	66.2	84.6	13 600*	44.0
48.0	61.0	83.8	11 800	62.2	83.4	12 200	63.4	82.4	12 600	48.0
52.0	58.2	81.4	9 900	59.3	80.9	10 300	60.4	80.0	10 600	52.0
56.0	55.2	78.7	8 300	56.4	78.2	8 600	57.4	77.2	8 900	56.0
60.0	52.1	75.6	6 900	53.3	75.2	7 200	54.3	74.1	7 400	60.0
64.0	48.9	72.3	5 700	50.1	71.8	5 900	51.0	70.7	6 200	64.0
68.0	45.6	68.5	4 600	46.7	67.9	4 800	47.6	66.8	5 000	68.0
72.0	42.0	64.2	3 700	43.0	63.6	3 900				72.0
76.0	38.1	59.3	2 800	39.1	58.7	3 000				76.0
80.0				34.8	52.9	2 000*				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
84.5m Boom										
18.3	80.8	97.7	21 800 *							18.3
20.0	79.7	97.4	21 500 *							20.0
22.0	78.5	97.0	21 300 *	79.8	96.6	19 900*				22.0
24.0	77.3	96.5	21 000 *	78.5	96.1	19 700*	79.8	95.3	17 600*	24.0
26.0	76.1	96.0	20 800 *	77.3	95.6	19 600*	78.6	94.8	17 100*	26.0
28.0	74.8	95.4	20 500 *	76.1	95.1	19 400*	77.3	94.2	16 600*	28.0
30.0	73.6	94.9	20 300 *	74.8	94.5	19 300*	76.1	93.6	16 200*	30.0
32.0	72.4	94.2	20 100 *	73.6	93.8	19 200*	74.8	93.0	15 800*	32.0
34.0	71.1	93.5	19 800	72.3	93.1	19 100*	73.5	92.3	15 400*	34.0
36.0	69.8	92.8	18 800	71.1	92.4	18 900	72.2	91.5	15 100*	36.0
38.0	68.6	92.0	17 200	69.8	91.6	17 800	71.0	90.7	14 700*	38.0
40.0	67.3	91.2	15 900	68.5	90.8	16 400	69.6	89.9	14 400*	40.0
44.0	64.7	89.3	13 500	65.9	88.9	13 900	67.0	88.0	13 800*	44.0
48.0	62.0	87.2	11 500	63.2	86.8	11 900	64.3	85.9	12 300	48.0
52.0	59.3	84.9	9 600	60.4	84.5	10 000	61.5	83.5	10 300	52.0
56.0	56.4	82.3	8 000	57.6	81.9	8 400	58.6	80.9	8 700	56.0
60.0	53.5	79.5	6 700	54.6	79.0	6 900	55.6	78.0	7 200	60.0
64.0	50.5	76.2	5 400	51.6	75.8	5 700	52.5	74.7	5 900	64.0
68.0	47.3	72.7	4 400	48.4	72.1	4 600	49.3	71.0	4 800	68.0
72.0	43.9	68.6	3 500	45.0	68.1	3 600	45.8	66.9	3 800	72.0
76.0	40.3	64.1	2 600	41.4	63.5	2 800				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
10.7	79.6	44.2	20 500 *							10.7
12.0	77.8	43.9	20 000 *							12.0
14.0	75.0	43.3	19 300 *	78.6	43.0	17 900*				14.0
16.0	72.2	42.7	18 600 *	75.7	42.3	17 300*	79.4	41.5	14 400*	16.0
18.0	69.3	41.9	18 000 *	72.8	41.5	16 800*	76.4	40.7	13 400*	18.0
20.0	66.4	41.0	17 400 *	69.9	40.6	16 300*	73.4	39.8	12 500*	20.0
22.0	63.4	40.0	16 800 *	66.8	39.6	15 700*	70.3	38.7	11 700*	22.0
24.0	60.2	38.8	16 200 *	63.7	38.4	14 600*	67.1	37.5	11 100*	24.0
26.0	57.0	37.5	15 700 *	60.4	37.1	13 700*	63.7	36.2	10 500*	26.0
28.0	53.7	36.0	15 200 *	57.1	35.6	12 800*	60.2	34.6	10 000*	28.0
30.0	50.2	34.3	14 700 *	53.5	33.9	12 100*	56.6	32.9	9 600*	30.0
32.0	46.5	32.4	13 800 *	49.7	31.9	11 500*	52.7	30.9	9 200*	32.0
34.0	42.5	30.2	13 000 *	45.7	29.7	10 900*	48.5	28.5	8 900*	34.0
36.0	38.2	27.7	12 200 *	41.3	27.1	10 400*				36.0
38.0	33.4	24.7	11 500 *	36.3	24.1	10 000*				38.0
40.0	27.7	21.0	11 000 *							40.0
30.5m Boom										
10.7	80.3	47.3	20 600 *							10.7
12.0	78.6	47.0	20 200 *							12.0
14.0	76.0	46.5	19 500 *	79.4	46.1	18 000*				14.0
16.0	73.4	45.9	18 800 *	76.7	45.5	17 500*				16.0
18.0	70.7	45.1	18 300 *	74.0	44.8	16 900*	77.4	43.9	13 600*	18.0
20.0	68.0	44.3	17 700 *	71.3	43.9	16 500*	74.6	43.1	12 800*	20.0
22.0	65.3	43.4	17 100 *	68.5	43.0	16 100*	71.8	42.1	12 100*	22.0
24.0	62.4	42.3	16 600 *	65.6	41.9	15 300*	68.8	41.0	11 400*	24.0
26.0	59.5	41.1	16 100 *	62.7	40.7	14 300*	65.8	39.8	10 900*	26.0
28.0	56.5	39.8	15 600 *	59.6	39.3	13 500*	62.7	38.4	10 400*	28.0
30.0	53.3	38.3	15 200 *	56.5	37.8	12 700*	59.4	36.8	9 900*	30.0
32.0	50.1	36.6	14 700 *	53.1	36.1	12 100*	56.0	35.1	9 500*	32.0
34.0	46.6	34.7	13 900 *	49.6	34.2	11 500*	52.3	33.1	9 200*	34.0
36.0	42.9	32.5	13 000 *	45.9	32.0	10 900*	48.5	30.8	8 900*	36.0
38.0	38.9	30.0	12 300 *	41.8	29.5	10 500*	44.2	28.2	8 600*	38.0
40.0	34.6	27.2	11 700 *	37.3	26.5	10 100*				40.0
44.0	23.6	19.4	10 600 *							44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
10.7	80.9	50.3	20 800 *							10.7
12.0	79.3	50.1	20 300 *							12.0
14.0	76.9	49.6	19 600 *	80.1	49.2	18 100*				14.0
16.0	74.5	49.0	19 000 *	77.6	48.6	17 600*				16.0
18.0	72.0	48.3	18 500 *	75.1	47.9	17 100*	78.2	47.1	14 000*	18.0
20.0	69.5	47.6	18 000 *	72.6	47.2	16 600*	75.7	46.3	13 100*	20.0
22.0	66.9	46.7	17 400 *	70.0	46.3	16 200*	73.0	45.4	12 400*	22.0
24.0	64.3	45.7	16 900 *	67.3	45.3	15 800*	70.3	44.4	11 800*	24.0
26.0	61.6	44.6	16 400 *	64.6	44.2	14 900*	67.5	43.3	11 200*	26.0
28.0	58.8	43.4	15 900 *	61.8	42.9	14 000*	64.7	42.0	10 700*	28.0
30.0	56.0	42.0	15 500 *	58.9	41.6	13 300*	61.7	40.6	10 300*	30.0
32.0	53.0	40.5	15 100 *	55.9	40.0	12 600*	58.7	39.0	9 800*	32.0
34.0	49.9	38.8	14 700 *	52.8	38.3	12 000*	55.4	37.2	9 500*	34.0
36.0	46.7	36.9	13 900 *	49.5	36.4	11 400*	52.1	35.3	9 100*	36.0
38.0	43.3	34.8	13 100 *	46.0	34.2	10 900*	48.4	33.0	8 900*	38.0
40.0	39.6	32.4	12 400 *	42.3	31.8	10 500*				40.0
44.0	31.1	26.3	11 200 *	33.6	25.6	9 800*				44.0
36.5m Boom										
12.2	79.7	53.1	20 300 *							12.2
14.0	77.7	52.7	19 800 *	80.7	52.3	18 200*				14.0
16.0	75.4	52.1	19 200 *	78.3	51.7	17 700*				16.0
18.0	73.1	51.5	18 700 *	76.0	51.1	17 300*	79.0	50.3	14 200*	18.0
20.0	70.7	50.8	18 100 *	73.6	50.4	16 800*	76.6	49.5	13 400*	20.0
22.0	68.3	50.0	17 700 *	71.2	49.6	16 400*	74.1	48.7	12 700*	22.0
24.0	65.9	49.1	17 200 *	68.8	48.6	16 000*	71.6	47.7	12 100*	24.0
26.0	63.4	48.0	16 700 *	66.2	47.6	15 500*	69.0	46.7	11 500*	26.0
28.0	60.9	46.9	16 200 *	63.7	46.5	14 600*	66.4	45.5	11 000*	28.0
30.0	58.2	45.7	15 800 *	61.0	45.2	13 800*	63.7	44.2	10 500*	30.0
32.0	55.5	44.3	15 400 *	58.3	43.8	13 100*	60.9	42.8	10 100*	32.0
34.0	52.7	42.7	15 100 *	55.5	42.3	12 500*	58.0	41.2	9 800*	34.0
36.0	49.8	41.0	14 600 *	52.5	40.5	11 900*	55.0	39.4	9 400*	36.0
38.0	46.8	39.1	13 900 *	49.4	38.6	11 400*	51.8	37.5	9 100*	38.0
40.0	43.6	37.0	13 200 *	46.2	36.5	11 000*	48.4	35.2	8 900*	40.0
44.0	36.4	32.0	11 900 *	38.9	31.3	10 200*				44.0
48.0	27.7	25.2	10 900 *							48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	80.3	56.1	20 400 *							12.2
14.0	78.4	55.8	19 900 *							14.0
16.0	76.2	55.2	19 300 *	79.0	54.9	17 800*				16.0
18.0	74.0	54.7	18 800 *	76.8	54.3	17 400*	79.6	53.4	14 400*	18.0
20.0	71.8	54.0	18 300 *	74.6	53.6	17 000*	77.4	52.7	13 600*	20.0
22.0	69.6	53.2	17 900 *	72.3	52.8	16 600*	75.1	51.9	12 900*	22.0
24.0	67.3	52.4	17 400 *	70.0	51.9	16 200*	72.7	51.0	12 300*	24.0
26.0	65.0	51.4	16 900 *	67.7	51.0	15 800*	70.3	50.1	11 800*	26.0
28.0	62.6	50.4	16 500 *	65.3	49.9	15 200*	67.9	49.0	11 300*	28.0
30.0	60.2	49.2	16 100 *	62.9	48.8	14 300*	65.4	47.8	10 800*	30.0
32.0	57.7	47.9	15 700 *	60.3	47.5	13 600*	62.8	46.5	10 400*	32.0
34.0	55.1	46.5	15 300 *	57.8	46.0	13 000*	60.2	45.0	10 000*	34.0
36.0	52.5	45.0	15 000 *	55.1	44.5	12 400*	57.4	43.4	9 700*	36.0
38.0	49.7	43.3	14 700 *	52.3	42.8	11 900*	54.6	41.6	9 400*	38.0
40.0	46.9	41.4	13 900 *	49.4	40.8	11 400*	51.6	39.7	9 100*	40.0
44.0	40.6	37.0	12 600 *	43.0	36.4	10 600*	45.0	35.0	8 700*	44.0
48.0	33.4	31.4	11 500 *	35.7	30.6	10 000*				48.0
42.5m Boom										
12.2	80.8	59.2	20 500 *							12.2
14.0	79.0	58.8	20 000 *							14.0
16.0	77.0	58.4	19 400 *	79.6	58.0	17 900*				16.0
18.0	74.9	57.8	18 900 *	77.5	57.4	17 500*				18.0
20.0	72.8	57.2	18 500 *	75.4	56.8	17 100*	78.1	55.9	13 900*	20.0
22.0	70.7	56.4	18 000 *	73.3	56.0	16 700*	75.9	55.1	13 200*	22.0
24.0	68.6	55.6	17 600 *	71.1	55.2	16 300*	73.7	54.3	12 600*	24.0
26.0	66.4	54.8	17 200 *	69.0	54.3	16 000*	71.5	53.4	12 000*	26.0
28.0	64.2	53.8	16 700 *	66.7	53.3	15 600*	69.2	52.4	11 500*	28.0
30.0	61.9	52.7	16 300 *	64.4	52.2	14 900*	66.9	51.3	11 100*	30.0
32.0	59.6	51.5	16 000 *	62.1	51.0	14 100*	64.5	50.0	10 700*	32.0
34.0	57.2	50.2	15 600 *	59.7	49.7	13 500*	62.1	48.7	10 300*	34.0
36.0	54.8	48.8	15 300 *	57.3	48.3	12 900*	59.5	47.2	9 900*	36.0
38.0	52.3	47.2	15 000 *	54.7	46.7	12 400*	56.9	45.6	9 600*	38.0
40.0	49.7	45.5	14 600 *	52.1	45.0	11 800*	54.2	43.8	9 400*	40.0
44.0	44.1	41.6	13 300 *	46.4	41.0	11 000*	48.4	39.7	8 900*	44.0
48.0	37.8	36.7	12 100 *	40.1	36.0	10 300*				48.0
52.0	30.5	30.5	11 200 *							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	79.8	62.0	20 100 *							13.7
14.0	79.5	61.9	20 000 *							14.0
16.0	77.6	61.4	19 500 *	80.1	61.0	17 900 *				16.0
18.0	75.7	60.9	19 000 *	78.2	60.5	17 600 *				18.0
20.0	73.7	60.3	18 600 *	76.2	59.9	17 200 *	78.7	59.0	14 100 *	20.0
22.0	71.7	59.6	18 100 *	74.2	59.2	16 800 *	76.7	58.3	13 400 *	22.0
24.0	69.7	58.9	17 700 *	72.1	58.5	16 500 *	74.6	57.5	12 800 *	24.0
26.0	67.6	58.0	17 400 *	70.1	57.6	16 200 *	72.5	56.7	12 300 *	26.0
28.0	65.5	57.1	17 000 *	68.0	56.7	15 900 *	70.4	55.7	11 800 *	28.0
30.0	63.4	56.1	16 600 *	65.8	55.7	15 400 *	68.2	54.7	11 300 *	30.0
32.0	61.3	55.0	16 200 *	63.7	54.5	14 600 *	66.0	53.5	10 900 *	32.0
34.0	59.1	53.8	15 800 *	61.4	53.3	13 900 *	63.7	52.3	10 500 *	34.0
36.0	56.8	52.5	15 500 *	59.2	52.0	13 300 *	61.4	50.9	10 200 *	36.0
38.0	54.5	51.0	15 200 *	56.8	50.5	12 800 *	59.0	49.4	9 900 *	38.0
40.0	52.1	49.4	14 900 *	54.4	48.9	12 300 *	56.5	47.8	9 600 *	40.0
44.0	47.0	45.9	13 900 *	49.3	45.3	11 400 *	51.2	44.1	9 100 *	44.0
48.0	41.5	41.5	12 800 *	43.6	40.9	10 700 *	45.4	39.6	8 700 *	48.0
52.0	35.2	36.2	11 700 *	37.2	35.5	10 000 *				52.0
56.0	27.6	29.3	10 900 *							56.0
48.5m Boom										
13.7	80.3	65.0	20 100 *							13.7
14.0	80.0	65.0	20 100 *							14.0
16.0	78.2	64.5	19 600 *							16.0
18.0	76.3	64.0	19 100 *	78.7	63.6	17 600 *				18.0
20.0	74.5	63.5	18 700 *	76.9	63.0	17 300 *	79.3	62.1	14 300 *	20.0
22.0	72.6	62.8	18 300 *	75.0	62.4	16 900 *	77.3	61.5	13 600 *	22.0
24.0	70.7	62.1	17 900 *	73.0	61.7	16 600 *	75.4	60.7	13 000 *	24.0
26.0	68.7	61.3	17 500 *	71.1	60.9	16 300 *	73.4	59.9	12 500 *	26.0
28.0	66.8	60.4	17 200 *	69.1	60.0	16 000 *	71.4	59.0	12 000 *	28.0
30.0	64.8	59.5	16 800 *	67.1	59.0	15 700 *	69.3	58.1	11 600 *	30.0
32.0	62.8	58.4	16 400 *	65.1	58.0	15 100 *	67.3	57.0	11 200 *	32.0
34.0	60.7	57.3	16 100 *	63.0	56.8	14 400 *	65.1	55.8	10 700 *	34.0
36.0	58.6	56.1	15 700 *	60.8	55.6	13 800 *	63.0	54.5	10 400 *	36.0
38.0	56.4	54.7	15 400 *	58.6	54.2	13 200 *	60.7	53.2	10 100 *	38.0
40.0	54.2	53.3	15 100 *	56.4	52.8	12 700 *	58.4	51.7	9 800 *	40.0
44.0	49.5	50.0	14 600 *	51.7	49.4	11 800 *	53.6	48.3	9 300 *	44.0
48.0	44.5	46.1	13 400 *	46.6	45.5	11 000 *	48.4	44.2	8 900 *	48.0
52.0	38.9	41.4	12 300 *	41.0	40.7	10 400 *				52.0
56.0	32.6	35.5	11 000 *	34.5	34.7	9 800 *				56.0
60.0	24.7	27.8	9 200 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
13.7	80.7	68.1	20 100 *							13.7
14.0	80.5	68.0	20 100 *							14.0
16.0	78.7	67.6	19 600 *							16.0
18.0	77.0	67.1	19 100 *	79.3	66.7	17 700*				18.0
20.0	75.2	66.6	18 700 *	77.5	66.2	17 400*	79.8	65.2	14 500*	20.0
22.0	73.4	66.0	18 400 *	75.7	65.5	17 000*	77.9	64.6	13 800*	22.0
24.0	71.6	65.3	18 000 *	73.8	64.9	16 700*	76.1	63.9	13 200*	24.0
26.0	69.8	64.5	17 600 *	72.0	64.1	16 400*	74.2	63.2	12 700*	26.0
28.0	67.9	63.7	17 300 *	70.1	63.3	16 100*	72.3	62.3	12 200*	28.0
30.0	66.0	62.8	17 000 *	68.2	62.4	15 900*	70.4	61.4	11 800*	30.0
32.0	64.1	61.8	16 600 *	66.3	61.4	15 500*	68.4	60.4	11 400*	32.0
34.0	62.1	60.8	16 200 *	64.3	60.3	14 800*	66.4	59.3	11 000*	34.0
36.0	60.2	59.6	15 900 *	62.3	59.1	14 200*	64.4	58.1	10 600*	36.0
38.0	58.1	58.3	15 600 *	60.3	57.9	13 600*	62.3	56.8	10 300*	38.0
40.0	56.1	57.0	15 300 *	58.2	56.5	13 100*	60.2	55.4	10 000*	40.0
44.0	51.7	53.9	14 800 *	53.8	53.4	12 200*	55.7	52.2	9 500*	44.0
48.0	47.1	50.3	14 000 *	49.1	49.8	11 400*	50.9	48.5	9 100*	48.0
52.0	42.1	46.1	12 400	44.1	45.5	10 700*	45.7	44.1	8 700*	52.0
56.0	36.5	41.0	10 800	38.4	40.3	10 200*				56.0
60.0	30.0	34.6	9 400							60.0
64.0	21.8	25.9	7 300 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	79.9	70.8	19 800 *							15.2
16.0	79.2	70.7	19 600 *							16.0
18.0	77.6	70.2	19 200 *	79.7	69.8	17 700*				18.0
20.0	75.9	69.7	18 800 *	78.0	69.3	17 400*	80.2	68.4	14 700*	20.0
22.0	74.1	69.1	18 400 *	76.3	68.7	17 100*	78.5	67.8	14 000*	22.0
24.0	72.4	68.5	18 100 *	74.6	68.0	16 800*	76.7	67.1	13 400*	24.0
26.0	70.7	67.8	17 700 *	72.8	67.3	16 500*	74.9	66.4	12 900*	26.0
28.0	68.9	67.0	17 400 *	71.0	66.5	16 200*	73.1	65.6	12 400*	28.0
30.0	67.1	66.1	17 100 *	69.2	65.7	16 000*	71.3	64.7	12 000*	30.0
32.0	65.3	65.2	16 800 *	67.4	64.7	15 700*	69.4	63.7	11 600*	32.0
34.0	63.5	64.2	16 400 *	65.6	63.7	15 300*	67.6	62.7	11 200*	34.0
36.0	61.6	63.1	16 100 *	63.7	62.6	14 600*	65.6	61.6	10 800*	36.0
38.0	59.7	61.9	15 800 *	61.7	61.4	14 000*	63.7	60.4	10 500*	38.0
40.0	57.7	60.6	15 500 *	59.8	60.1	13 500*	61.7	59.0	10 200*	40.0
44.0	53.7	57.8	15 000 *	55.7	57.2	12 600*	57.5	56.1	9 700*	44.0
48.0	49.4	54.4	14 100	51.4	53.9	11 700*	53.1	52.7	9 200*	48.0
52.0	44.8	50.6	12 200	46.7	50.0	11 000*	48.4	48.7	8 900*	52.0
56.0	39.8	46.0	10 600	41.7	45.3	10 400*	43.1	43.9	8 600*	56.0
60.0	34.2	40.4	9 100	35.9	39.7	9 300				60.0
64.0	27.6	33.4	7 800							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
15.2	80.3	73.9	19 800 *							15.2
16.0	79.7	73.7	19 600 *							16.0
18.0	78.1	73.3	19 200 *							18.0
20.0	76.5	72.8	18 800 *	78.5	72.4	17 400*	80.7	71.4	14 800*	20.0
22.0	74.8	72.3	18 500 *	76.9	71.8	17 200*	79.0	70.9	14 200*	22.0
24.0	73.2	71.6	18 100 *	75.2	71.2	16 800*	77.3	70.2	13 600*	24.0
26.0	71.5	70.9	17 800 *	73.6	70.5	16 600*	75.6	69.5	13 100*	26.0
28.0	69.8	70.2	17 500 *	71.9	69.8	16 300*	73.9	68.8	12 600*	28.0
30.0	68.1	69.4	17 200 *	70.2	68.9	16 100*	72.1	68.0	12 200*	30.0
32.0	66.4	68.5	16 900 *	68.4	68.0	15 800*	70.4	67.0	11 800*	32.0
34.0	64.6	67.5	16 600 *	66.7	67.1	15 600*	68.6	66.1	11 400*	34.0
36.0	62.9	66.5	16 300 *	64.9	66.0	15 000*	66.8	65.0	11 100*	36.0
38.0	61.1	65.4	16 000 *	63.0	64.9	14 400*	64.9	63.9	10 700*	38.0
40.0	59.2	64.2	15 700 *	61.2	63.7	13 900*	63.0	62.6	10 400*	40.0
44.0	55.4	61.5	15 200 *	57.4	61.0	12 900*	59.1	59.9	9 900*	44.0
48.0	51.4	58.4	13 700	53.3	57.9	12 100*	55.0	56.7	9 400*	48.0
52.0	47.2	54.8	11 800	49.1	54.2	11 400*	50.7	53.0	9 100*	52.0
56.0	42.6	50.6	10 200	44.5	50.0	10 500	45.9	48.6	8 700*	56.0
60.0	37.6	45.7	8 800	39.4	45.0	9 100				60.0
64.0	31.9	39.7	7 700	33.6	38.9	7 800				64.0
68.0	25.1	31.9	6 100 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
15.2	80.7	76.9	19 700 *							15.2
16.0	80.1	76.8	19 600 *							16.0
18.0	78.6	76.4	19 200 *							18.0
20.0	77.0	75.9	18 800 *	79.0	75.5	17 400*				20.0
22.0	75.4	75.4	18 500 *	77.4	74.9	17 200*	79.4	74.0	14 400*	22.0
24.0	73.9	74.8	18 200 *	75.8	74.3	16 900*	77.8	73.4	13 800*	24.0
26.0	72.3	74.1	17 900 *	74.2	73.7	16 600*	76.2	72.7	13 300*	26.0
28.0	70.7	73.4	17 600 *	72.6	73.0	16 400*	74.6	72.0	12 800*	28.0
30.0	69.0	72.6	17 300 *	71.0	72.2	16 100*	72.9	71.2	12 400*	30.0
32.0	67.4	71.8	17 000 *	69.3	71.3	15 900*	71.2	70.3	12 000*	32.0
34.0	65.7	70.9	16 700 *	67.7	70.4	15 700*	69.5	69.4	11 600*	34.0
36.0	64.0	69.9	16 500 *	66.0	69.4	15 300*	67.8	68.4	11 300*	36.0
38.0	62.3	68.8	16 200 *	64.2	68.3	14 800*	66.1	67.3	10 900*	38.0
40.0	60.6	67.7	15 900 *	62.5	67.2	14 200*	64.3	66.1	10 600*	40.0
44.0	57.0	65.2	15 400 *	58.9	64.6	13 200*	60.6	63.5	10 100*	44.0
48.0	53.3	62.2	13 500	55.1	61.7	12 400*	56.8	60.6	9 600*	48.0
52.0	49.3	58.9	11 600	51.1	58.3	11 700	52.7	57.1	9 200*	52.0
56.0	45.1	55.1	10 000	46.9	54.4	10 300	48.3	53.1	8 900*	56.0
60.0	40.6	50.6	8 600	42.3	49.9	8 800				60.0
64.0	35.5	45.2	7 400	37.1	44.5	7 600				64.0
68.0	29.7	38.7	6 300							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	79.9	79.7	19 400 *							16.8
18.0	79.0	79.4	19 100 *							18.0
20.0	77.5	79.0	18 800 *	79.4	78.6	17 400*				20.0
22.0	76.0	78.5	18 500 *	77.9	78.0	17 200*	79.9	77.1	14 500*	22.0
24.0	74.5	77.9	18 200 *	76.4	77.5	17 000*	78.3	76.5	14 000*	24.0
26.0	73.0	77.3	17 900 *	74.9	76.8	16 700*	76.8	75.9	13 400*	26.0
28.0	71.4	76.6	17 600 *	73.3	76.2	16 400*	75.2	75.2	13 000*	28.0
30.0	69.9	75.9	17 300 *	71.8	75.4	16 200*	73.6	74.4	12 600*	30.0
32.0	68.3	75.1	17 100 *	70.2	74.6	16 000*	72.0	73.6	12 200*	32.0
34.0	66.7	74.2	16 800 *	68.6	73.7	15 700*	70.4	72.7	11 800*	34.0
36.0	65.1	73.2	16 500 *	67.0	72.8	15 500*	68.8	71.7	11 400*	36.0
38.0	63.5	72.2	16 300 *	65.3	71.7	15 200*	67.1	70.7	11 100*	38.0
40.0	61.8	71.1	16 000 *	63.7	70.7	14 600*	65.4	69.6	10 800*	40.0
44.0	58.4	68.7	15 400	60.2	68.2	13 600*	61.9	67.1	10 300*	44.0
48.0	54.9	66.0	13 300	56.7	65.5	12 800*	58.3	64.3	9 800*	48.0
52.0	51.2	62.9	11 400	52.9	62.3	11 700	54.5	61.1	9 400*	52.0
56.0	47.3	59.3	9 800	49.0	58.7	10 100	50.5	57.4	9 000*	56.0
60.0	43.1	55.2	8 400	44.8	54.5	8 600	46.1	53.1	8 700	60.0
64.0	38.5	50.4	7 200	40.1	49.7	7 400				64.0
68.0	33.5	44.6	6 100	35.0	43.8	6 300				68.0
72.0	27.5	37.5	4 700 *							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
16.8	80.3	82.8	19 300 *							16.8
18.0	79.4	82.5	19 100 *							18.0
20.0	78.0	82.1	18 800 *	79.8	81.6	17 400*				20.0
22.0	76.5	81.6	18 500 *	78.4	81.1	17 200*	80.3	80.2	14 700*	22.0
24.0	75.1	81.0	18 200 *	76.9	80.6	17 000*	78.8	79.6	14 100*	24.0
26.0	73.6	80.4	17 900 *	75.5	80.0	16 700*	77.3	79.0	13 600*	26.0
28.0	72.1	79.8	17 600 *	74.0	79.3	16 500*	75.8	78.4	13 200*	28.0
30.0	70.6	79.1	17 400 *	72.5	78.6	16 200*	74.3	77.6	12 700*	30.0
32.0	69.1	78.3	17 100 *	71.0	77.8	16 000*	72.7	76.8	12 300*	32.0
34.0	67.6	77.5	16 900 *	69.4	77.0	15 800*	71.2	76.0	12 000*	34.0
36.0	66.1	76.6	16 600 *	67.9	76.1	15 600*	69.6	75.1	11 600*	36.0
38.0	64.5	75.6	16 400 *	66.3	75.1	15 400*	68.0	74.1	11 300*	38.0
40.0	63.0	74.6	16 100 *	64.7	74.1	15 000*	66.4	73.0	11 000*	40.0
44.0	59.7	72.3	15 300	61.5	71.8	14 000*	63.1	70.7	10 400*	44.0
48.0	56.4	69.7	13 000	58.1	69.2	13 100*	59.7	68.0	10 000*	48.0
52.0	52.9	66.7	11 100	54.6	66.2	11 500	56.1	65.0	9 500*	52.0
56.0	49.2	63.4	9 500	50.9	62.8	9 800	52.3	61.6	9 200*	56.0
60.0	45.3	59.6	8 200	47.0	58.9	8 400	48.3	57.6	8 700	60.0
64.0	41.2	55.1	6 900	42.7	54.5	7 200	44.0	53.0	7 300	64.0
68.0	36.6	50.0	5 900	38.1	49.3	6 100				68.0
72.0	31.4	43.8	4 900 *	32.9	43.0	5 100				72.0
76.0	25.3	36.1	3 400 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	80.6	85.8	19 200 *							16.8
18.0	79.8	85.6	19 000 *							18.0
20.0	78.4	85.2	18 700 *	80.2	84.7	17 300*				20.0
22.0	77.0	84.7	18 400 *	78.8	84.2	17 100*				22.0
24.0	75.6	84.2	18 200 *	77.4	83.7	16 900*	79.2	82.7	14 300*	24.0
26.0	74.2	83.6	17 900 *	76.0	83.1	16 700*	77.8	82.2	13 800*	26.0
28.0	72.8	82.9	17 600 *	74.6	82.5	16 500*	76.3	81.5	13 300*	28.0
30.0	71.4	82.3	17 300 *	73.1	81.8	16 300*	74.9	80.8	12 900*	30.0
32.0	69.9	81.5	17 100 *	71.7	81.1	16 100*	73.4	80.1	12 500*	32.0
34.0	68.5	80.7	16 900 *	70.2	80.3	15 900*	71.9	79.2	12 100*	34.0
36.0	67.0	79.9	16 600 *	68.7	79.4	15 600*	70.4	78.4	11 800*	36.0
38.0	65.5	78.9	16 400 *	67.2	78.5	15 500*	68.9	77.4	11 400*	38.0
40.0	64.0	77.9	16 200 *	65.7	77.5	15 300*	67.3	76.4	11 100*	40.0
44.0	60.9	75.8	15 000	62.6	75.3	14 300*	64.2	74.2	10 600*	44.0
48.0	57.7	73.3	12 700	59.4	72.8	13 200	60.9	71.7	10 100*	48.0
52.0	54.4	70.5	10 800	56.1	70.0	11 200	57.6	68.8	9 700*	52.0
56.0	51.0	67.4	9 200	52.6	66.8	9 600	54.0	65.6	9 300*	56.0
60.0	47.3	63.8	7 800	48.9	63.2	8 100	50.3	61.9	8 400	60.0
64.0	43.5	59.7	6 600	45.0	59.0	6 900	46.3	57.6	7 100	64.0
68.0	39.3	55.0	5 600	40.8	54.3	5 800				68.0
72.0	34.7	49.5	4 600	36.1	48.7	4 800				72.0
76.0	29.5	42.8	3 400 *							76.0
80.0	23.1	34.4	2 000 *							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
16.8	81.0	88.9	19 100 *							16.8
18.0	80.1	88.6	19 000 *							18.0
20.0	78.8	88.2	18 700 *	80.6	87.8	17 300*				20.0
22.0	77.5	87.8	18 400 *	79.2	87.3	17 100*				22.0
24.0	76.1	87.3	18 100 *	77.9	86.8	16 900*	79.6	85.8	14 400*	24.0
26.0	74.8	86.7	17 900 *	76.5	86.3	16 700*	78.2	85.3	13 900*	26.0
28.0	73.4	86.1	17 600 *	75.1	85.6	16 500*	76.8	84.7	13 500*	28.0
30.0	72.0	85.4	17 300 *	73.7	85.0	16 300*	75.4	84.0	13 100*	30.0
32.0	70.6	84.7	17 100 *	72.3	84.3	16 100*	74.0	83.3	12 700*	32.0
34.0	69.2	84.0	16 900 *	70.9	83.5	15 900*	72.6	82.5	12 300*	34.0
36.0	67.8	83.1	16 700 *	69.5	82.7	15 700*	71.1	81.6	11 900*	36.0
38.0	66.4	82.2	16 400 *	68.1	81.8	15 500*	69.7	80.7	11 600*	38.0
40.0	65.0	81.3	16 200 *	66.6	80.8	15 300*	68.2	79.8	11 300*	40.0
44.0	62.0	79.2	14 800	63.7	78.7	14 600*	65.2	77.6	10 800*	44.0
48.0	59.0	76.9	12 500	60.6	76.3	12 900	62.1	75.2	10 300*	48.0
52.0	55.8	74.2	10 600	57.4	73.7	11 000	58.9	72.5	9 900*	52.0
56.0	52.6	71.2	9 000	54.2	70.7	9 300	55.6	69.5	9 500*	56.0
60.0	49.2	67.9	7 600	50.7	67.3	7 900	52.0	66.0	8 200	60.0
64.0	45.5	64.0	6 400	47.1	63.4	6 700	48.3	62.1	6 900	64.0
68.0	41.7	59.7	5 300	43.2	59.0	5 500	44.3	57.6	5 700	68.0
72.0	37.5	54.7	4 400	38.9	54.0	4 600				72.0
76.0	32.9	48.8	3 400	34.2	48.0	3 700				76.0
80.0	27.5	41.6	2 100 *							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
18.3	80.3	91.6	18 800 *							18.3
20.0	79.2	91.3	18 500 *	80.9	90.8	17 200*				20.0
22.0	77.9	90.8	18 300 *	79.6	90.4	17 000*				22.0
24.0	76.6	90.4	18 000 *	78.3	89.9	16 800*	79.9	88.9	14 600*	24.0
26.0	75.3	89.8	17 800 *	77.0	89.4	16 600*	78.6	88.4	14 100*	26.0
28.0	74.0	89.2	17 500 *	75.6	88.8	16 500*	77.3	87.8	13 600*	28.0
30.0	72.6	88.6	17 300 *	74.3	88.1	16 300*	75.9	87.1	13 200*	30.0
32.0	71.3	87.9	17 100 *	73.0	87.5	16 100*	74.6	86.4	12 800*	32.0
34.0	70.0	87.2	16 800 *	71.6	86.7	15 900*	73.2	85.7	12 400*	34.0
36.0	68.6	86.4	16 600 *	70.2	85.9	15 700*	71.8	84.9	12 100*	36.0
38.0	67.2	85.5	16 400 *	68.8	85.1	15 600*	70.4	84.0	11 800*	38.0
40.0	65.8	84.6	16 200 *	67.5	84.1	15 400*	69.0	83.1	11 500*	40.0
44.0	63.0	82.6	14 800	64.6	82.1	14 900*	66.1	81.1	10 900*	44.0
48.0	60.1	80.4	12 500	61.7	79.9	13 000	63.2	78.8	10 400*	48.0
52.0	57.1	77.8	10 600	58.7	77.3	11 000	60.1	76.2	10 000*	52.0
56.0	54.0	75.0	9 000	55.6	74.5	9 400	56.9	73.3	9 600	56.0
60.0	50.8	71.8	7 700	52.3	71.2	8 000	53.6	70.0	8 200	60.0
64.0	47.4	68.2	6 400	48.9	67.6	6 700	50.1	66.3	6 900	64.0
68.0	43.8	64.2	5 400	45.3	63.5	5 600	46.4	62.1	5 800	68.0
72.0	40.0	59.6	4 400	41.4	58.9	4 600				72.0
76.0	35.7	54.3	3 600	37.1	53.5	3 800				76.0
80.0	31.0	48.0	2 500 *	32.3	47.1	2 700*				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
18.3	80.6	94.7	18 700 *							18.3
20.0	79.5	94.4	18 400 *							20.0
22.0	78.3	93.9	18 200 *	79.9	93.5	16 900*				22.0
24.0	77.0	93.5	17 900 *	78.7	93.0	16 700*	80.3	92.0	14 700*	24.0
26.0	75.8	92.9	17 700 *	77.4	92.5	16 600*	79.0	91.5	14 200*	26.0
28.0	74.5	92.4	17 400 *	76.1	91.9	16 400*	77.7	90.9	13 800*	28.0
30.0	73.2	91.8	17 200 *	74.8	91.3	16 300*	76.4	90.3	13 300*	30.0
32.0	71.9	91.1	17 000 *	73.5	90.6	16 100*	75.1	89.6	13 000*	32.0
34.0	70.6	90.4	16 800 *	72.2	89.9	15 900*	73.8	88.9	12 600*	34.0
36.0	69.3	89.6	16 600 *	70.9	89.1	15 700*	72.4	88.1	12 300*	36.0
38.0	68.0	88.8	16 400 *	69.6	88.3	15 600*	71.1	87.3	11 900*	38.0
40.0	66.7	87.9	16 200 *	68.2	87.4	15 400*	69.7	86.4	11 600*	40.0
44.0	64.0	86.0	14 500	65.5	85.5	15 000	67.0	84.4	11 100*	44.0
48.0	61.2	83.9	12 300	62.7	83.3	12 800	64.1	82.2	10 600*	48.0
52.0	58.3	81.4	10 400	59.8	80.9	10 800	61.2	79.8	10 200*	52.0
56.0	55.4	78.7	8 800	56.9	78.2	9 200	58.2	77.0	9 500	56.0
60.0	52.3	75.7	7 400	53.8	75.1	7 700	55.1	73.9	8 000	60.0
64.0	49.1	72.3	6 200	50.5	71.7	6 500	51.8	70.4	6 800	64.0
68.0	45.7	68.5	5 100	47.1	67.9	5 400	48.3	66.5	5 600	68.0
72.0	42.1	64.2	4 200	43.5	63.6	4 400	44.6	62.1	4 600	72.0
76.0	38.3	59.4	3 300	39.6	58.6	3 500				76.0
80.0	34.0	53.7	2 400 *	35.3	52.9	2 700				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
18.3	80.9	97.7	18 500 *							18.3
20.0	79.9	97.4	18 300 *							20.0
22.0	78.7	97.0	18 000 *	80.2	96.5	16 800*				22.0
24.0	77.4	96.5	17 800 *	79.0	96.1	16 600*				24.0
26.0	76.2	96.0	17 500 *	77.8	95.6	16 500*	79.4	94.6	14 300*	26.0
28.0	75.0	95.5	17 400 *	76.6	95.0	16 300*	78.1	94.0	13 900*	28.0
30.0	73.8	94.9	17 100 *	75.3	94.4	16 200*	76.8	93.4	13 500*	30.0
32.0	72.5	94.3	16 900 *	74.1	93.8	16 100*	75.6	92.8	13 100*	32.0
34.0	71.3	93.6	16 700 *	72.8	93.1	15 900*	74.3	92.1	12 700*	34.0
36.0	70.0	92.8	16 500 *	71.5	92.4	15 700*	73.0	91.3	12 400*	36.0
38.0	68.7	92.0	16 300 *	70.2	91.6	15 600*	71.7	90.5	12 100*	38.0
40.0	67.4	91.2	16 100	69.0	90.7	15 400*	70.4	89.7	11 800*	40.0
44.0	64.8	89.4	14 000	66.3	88.9	14 600	67.8	87.8	11 200*	44.0
48.0	62.2	87.3	12 000	63.6	86.8	12 500	65.0	85.7	10 700*	48.0
52.0	59.4	85.0	10 100	60.9	84.5	10 500	62.3	83.3	10 300*	52.0
56.0	56.6	82.4	8 500	58.1	81.8	8 900	59.4	80.7	9 300	56.0
60.0	53.7	79.5	7 100	55.1	78.9	7 400	56.4	77.7	7 800	60.0
64.0	50.6	76.3	5 900	52.0	75.7	6 200	53.3	74.5	6 500	64.0
68.0	47.5	72.7	4 800	48.8	72.1	5 100	50.0	70.8	5 300	68.0
72.0	44.1	68.7	3 900	45.5	68.1	4 100	46.5	66.6	4 300	72.0
76.0	40.5	64.2	3 000	41.8	63.5	3 300	42.8	62.0	3 400	76.0
80.0	36.6	59.0	2 200 *	37.9	58.2	2 500				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
10.7	80.4	47.3	17 600 *							10.7
12.0	78.7	47.0	17 200 *							12.0
14.0	76.1	46.5	16 600 *	80.2	46.2	13 300*				14.0
16.0	73.5	45.9	15 900 *	77.5	45.5	13 300*				16.0
18.0	70.8	45.2	15 300 *	74.8	44.8	13 300*	78.9	44.0	12 200*	18.0
20.0	68.1	44.4	14 700 *	72.1	44.0	13 300*	76.2	43.1	11 400*	20.0
22.0	65.3	43.4	14 200 *	69.3	43.0	13 100*	73.3	42.1	10 600*	22.0
24.0	62.5	42.4	13 700 *	66.4	42.0	12 800*	70.4	41.0	10 000*	24.0
26.0	59.6	41.2	13 200 *	63.5	40.7	12 400*	67.3	39.8	9 500*	26.0
28.0	56.6	39.8	12 800 *	60.4	39.4	11 700*	64.2	38.4	8 900*	28.0
30.0	53.4	38.3	12 400 *	57.3	37.9	11 000*	61.0	36.8	8 500*	30.0
32.0	50.2	36.6	12 000 *	54.0	36.2	10 300*	57.5	35.1	8 100*	32.0
34.0	46.7	34.7	11 400 *	50.5	34.2	9 800*	53.9	33.1	7 800*	34.0
36.0	43.0	32.6	10 700 *	46.7	32.1	9 300*	50.0	30.8	7 400*	36.0
38.0	39.1	30.1	10 000 *	42.7	29.6	8 800*	45.8	28.2	7 200*	38.0
40.0	34.7	27.3	9 500 *	38.2	26.6	8 500*				40.0
44.0	23.8	19.5	8 600 *							44.0
30.5m Boom										
10.7	81.0	50.4	17 700 *							10.7
12.0	79.4	50.1	17 300 *							12.0
14.0	77.0	49.6	16 700 *							14.0
16.0	74.5	49.1	16 100 *	78.3	48.7	13 300*				16.0
18.0	72.1	48.4	15 500 *	75.8	48.0	13 300*				18.0
20.0	69.5	47.6	15 000 *	73.3	47.2	13 300*	77.1	46.3	11 700*	20.0
22.0	67.0	46.8	14 500 *	70.7	46.3	13 300*	74.5	45.4	10 900*	22.0
24.0	64.4	45.8	14 000 *	68.1	45.4	13 000*	71.8	44.4	10 300*	24.0
26.0	61.7	44.7	13 500 *	65.3	44.2	12 600*	69.0	43.3	9 700*	26.0
28.0	58.9	43.4	13 100 *	62.6	43.0	12 200*	66.1	42.0	9 200*	28.0
30.0	56.1	42.1	12 700 *	59.7	41.6	11 500*	63.2	40.6	8 800*	30.0
32.0	53.1	40.6	12 300 *	56.7	40.1	10 800*	60.1	39.0	8 400*	32.0
34.0	50.1	38.9	12 000 *	53.6	38.4	10 300*	56.9	37.3	8 000*	34.0
36.0	46.8	37.0	11 400 *	50.3	36.5	9 700*	53.5	35.3	7 700*	36.0
38.0	43.4	34.9	10 700 *	46.8	34.3	9 300*	49.9	33.0	7 400*	38.0
40.0	39.7	32.5	10 100 *	43.1	31.9	8 900*	46.0	30.5	7 200*	40.0
44.0	31.2	26.5	9 100 *	34.4	25.7	8 200*				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	79.8	53.1	17 400 *							12.2
14.0	77.7	52.7	16 800 *							14.0
16.0	75.5	52.2	16 300 *	79.0	51.8	13 300*				16.0
18.0	73.1	51.6	15 700 *	76.7	51.2	13 300*				18.0
20.0	70.8	50.8	15 200 *	74.3	50.4	13 300*	77.9	49.5	11 900*	20.0
22.0	68.4	50.0	14 700 *	71.9	49.6	13 300*	75.5	48.7	11 200*	22.0
24.0	66.0	49.1	14 200 *	69.5	48.7	13 100*	73.0	47.7	10 500*	24.0
26.0	63.5	48.1	13 800 *	66.9	47.7	12 800*	70.4	46.7	10 000*	26.0
28.0	60.9	47.0	13 400 *	64.4	46.5	12 500*	67.8	45.5	9 500*	28.0
30.0	58.3	45.7	13 000 *	61.7	45.3	12 000*	65.1	44.2	9 100*	30.0
32.0	55.6	44.3	12 600 *	59.0	43.9	11 300*	62.3	42.8	8 700*	32.0
34.0	52.8	42.8	12 200 *	56.2	42.3	10 800*	59.4	41.2	8 300*	34.0
36.0	49.9	41.1	11 900 *	53.3	40.6	10 200*	56.3	39.4	8 000*	36.0
38.0	46.9	39.2	11 400 *	50.2	38.7	9 700*	53.2	37.5	7 700*	38.0
40.0	43.7	37.1	10 800 *	46.9	36.6	9 300*	49.8	35.2	7 400*	40.0
44.0	36.6	32.1	9 700 *	39.6	31.4	8 600*	42.2	29.9	7 000*	44.0
48.0	27.8	25.3	8 800 *							48.0
36.5m Boom										
12.2	80.4	56.2	17 500 *							12.2
14.0	78.4	55.8	17 000 *							14.0
16.0	76.3	55.3	16 500 *	79.7	54.9	13 300*				16.0
18.0	74.1	54.7	16 000 *	77.5	54.3	13 300*				18.0
20.0	71.9	54.0	15 400 *	75.2	53.6	13 300*	78.6	52.7	12 100*	20.0
22.0	69.6	53.3	14 900 *	73.0	52.9	13 300*	76.3	51.9	11 400*	22.0
24.0	67.4	52.4	14 500 *	70.7	52.0	13 200*	74.0	51.0	10 800*	24.0
26.0	65.1	51.5	14 000 *	68.3	51.0	13 000*	71.6	50.1	10 200*	26.0
28.0	62.7	50.4	13 600 *	66.0	50.0	12 700*	69.2	49.0	9 700*	28.0
30.0	60.3	49.3	13 200 *	63.5	48.8	12 400*	66.7	47.8	9 300*	30.0
32.0	57.8	48.0	12 900 *	61.0	47.5	11 800*	64.1	46.5	8 900*	32.0
34.0	55.2	46.6	12 600 *	58.4	46.1	11 200*	61.5	45.0	8 500*	34.0
36.0	52.6	45.0	12 200 *	55.7	44.5	10 600*	58.7	43.4	8 200*	36.0
38.0	49.8	43.3	11 900 *	53.0	42.8	10 100*	55.8	41.6	7 900*	38.0
40.0	47.0	41.5	11 400 *	50.1	40.9	9 700*	52.8	39.7	7 700*	40.0
44.0	40.7	37.1	10 300 *	43.7	36.4	8 900*	46.3	35.0	7 200*	44.0
48.0	33.5	31.5	9 400 *	36.4	30.7	8 300*				48.0
52.0	24.4	23.7	8 600 *							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	80.9	59.3	17 500 *							12.2
14.0	79.0	58.9	17 000 *							14.0
16.0	77.0	58.4	16 600 *							16.0
18.0	74.9	57.9	16 100 *	78.1	57.4	13 300 *				18.0
20.0	72.9	57.2	15 600 *	76.0	56.8	13 300 *	79.3	55.8	12 300 *	20.0
22.0	70.8	56.5	15 100 *	73.9	56.1	13 300 *	77.1	55.1	11 700 *	22.0
24.0	68.6	55.7	14 600 *	71.8	55.3	13 300 *	74.9	54.3	11 000 *	24.0
26.0	66.5	54.8	14 200 *	69.6	54.4	13 100 *	72.7	53.4	10 500 *	26.0
28.0	64.2	53.8	13 900 *	67.3	53.4	12 800 *	70.4	52.4	10 000 *	28.0
30.0	62.0	52.7	13 500 *	65.1	52.3	12 500 *	68.1	51.2	9 500 *	30.0
32.0	59.7	51.6	13 100 *	62.7	51.1	12 300 *	65.7	50.0	9 200 *	32.0
34.0	57.3	50.3	12 800 *	60.3	49.8	11 600 *	63.3	48.7	8 800 *	34.0
36.0	54.9	48.8	12 500 *	57.9	48.3	11 100 *	60.7	47.2	8 400 *	36.0
38.0	52.4	47.3	12 200 *	55.3	46.8	10 600 *	58.1	45.6	8 100 *	38.0
40.0	49.8	45.6	11 900 *	52.7	45.0	10 100 *	55.4	43.8	7 900 *	40.0
44.0	44.2	41.6	10 800 *	47.1	41.0	9 300 *	49.6	39.7	7 400 *	44.0
48.0	38.0	36.8	9 900 *	40.7	36.1	8 600 *	43.0	34.5	7 000 *	48.0
52.0	30.6	30.6	9 100 *	33.2	29.7	8 100 *				52.0
42.5m Boom										
13.7	79.9	62.0	17 200 *							13.7
14.0	79.6	62.0	17 100 *							14.0
16.0	77.7	61.5	16 600 *							16.0
18.0	75.7	61.0	16 200 *	78.7	60.6	13 300 *				18.0
20.0	73.7	60.4	15 700 *	76.8	59.9	13 300 *	79.8	59.0	12 500 *	20.0
22.0	71.8	59.7	15 300 *	74.8	59.3	13 300 *	77.8	58.3	11 800 *	22.0
24.0	69.7	58.9	14 900 *	72.7	58.5	13 300 *	75.7	57.5	11 200 *	24.0
26.0	67.7	58.1	14 400 *	70.7	57.7	13 200 *	73.6	56.6	10 700 *	26.0
28.0	65.6	57.2	14 000 *	68.6	56.7	12 900 *	71.5	55.7	10 200 *	28.0
30.0	63.5	56.2	13 700 *	66.4	55.7	12 700 *	69.3	54.7	9 800 *	30.0
32.0	61.3	55.1	13 300 *	64.3	54.6	12 400 *	67.1	53.5	9 400 *	32.0
34.0	59.1	53.8	13 000 *	62.0	53.4	12 100 *	64.8	52.3	9 000 *	34.0
36.0	56.9	52.5	12 700 *	59.8	52.0	11 500 *	62.5	50.9	8 700 *	36.0
38.0	54.6	51.1	12 400 *	57.4	50.6	11 000 *	60.1	49.4	8 400 *	38.0
40.0	52.2	49.5	12 100 *	55.0	49.0	10 500 *	57.6	47.8	8 100 *	40.0
44.0	47.1	45.9	11 400 *	49.9	45.4	9 700 *	52.3	44.1	7 600 *	44.0
48.0	41.6	41.6	10 400 *	44.2	41.0	9 000 *	46.5	39.5	7 200 *	48.0
52.0	35.3	36.3	9 500 *	37.8	35.6	8 400 *				52.0
56.0	27.8	29.4	8 800 *							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	80.4	65.1	17 200 *							13.7
14.0	80.1	65.0	17 100 *							14.0
16.0	78.3	64.6	16 700 *							16.0
18.0	76.4	64.1	16 300 *	79.3	63.7	13 300 *				18.0
20.0	74.5	63.5	15 900 *	77.4	63.1	13 300 *	80.3	62.1	12 700 *	20.0
22.0	72.6	62.9	15 400 *	75.5	62.4	13 300 *	78.4	61.4	12 000 *	22.0
24.0	70.7	62.2	15 000 *	73.6	61.7	13 300 *	76.5	60.7	11 400 *	24.0
26.0	68.8	61.4	14 600 *	71.6	60.9	13 300 *	74.5	59.9	10 900 *	26.0
28.0	66.8	60.5	14 200 *	69.7	60.0	13 100 *	72.5	59.0	10 400 *	28.0
30.0	64.9	59.5	13 900 *	67.7	59.1	12 800 *	70.4	58.0	10 000 *	30.0
32.0	62.8	58.5	13 500 *	65.6	58.0	12 600 *	68.3	56.9	9 600 *	32.0
34.0	60.8	57.4	13 200 *	63.5	56.9	12 300 *	66.2	55.8	9 200 *	34.0
36.0	58.6	56.1	12 900 *	61.4	55.6	11 900 *	64.0	54.5	8 900 *	36.0
38.0	56.5	54.8	12 600 *	59.2	54.3	11 400 *	61.8	53.1	8 600 *	38.0
40.0	54.3	53.3	12 300 *	57.0	52.8	10 900 *	59.5	51.6	8 300 *	40.0
44.0	49.6	50.0	11 800 *	52.3	49.5	10 000 *	54.7	48.2	7 800 *	44.0
48.0	44.6	46.1	10 900 *	47.2	45.5	9 300 *	49.4	44.1	7 400 *	48.0
52.0	39.0	41.5	10 000 *	41.5	40.8	8 700 *	43.6	39.2	7 100 *	52.0
56.0	32.7	35.6	9 300 *	35.1	34.8	8 200 *				56.0
60.0	24.9	27.9	8 600 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
13.7	80.8	68.1	17 200 *							13.7
14.0	80.5	68.1	17 200 *							14.0
16.0	78.8	67.7	16 800 *							16.0
18.0	77.0	67.2	16 300 *							18.0
20.0	75.2	66.6	16 000 *	78.0	66.2	13 300*				20.0
22.0	73.5	66.0	15 600 *	76.2	65.6	13 300*	79.0	64.6	12 200*	22.0
24.0	71.6	65.4	15 100 *	74.4	64.9	13 300*	77.1	63.9	11 600*	24.0
26.0	69.8	64.6	14 800 *	72.5	64.1	13 300*	75.2	63.1	11 100*	26.0
28.0	68.0	63.8	14 400 *	70.7	63.3	13 200*	73.3	62.3	10 600*	28.0
30.0	66.1	62.9	14 100 *	68.8	62.4	12 900*	71.4	61.3	10 200*	30.0
32.0	64.2	61.9	13 700 *	66.8	61.4	12 700*	69.4	60.3	9 800*	32.0
34.0	62.2	60.8	13 400 *	64.9	60.3	12 500*	67.4	59.2	9 400*	34.0
36.0	60.2	59.7	13 100 *	62.9	59.2	12 200*	65.4	58.0	9 100*	36.0
38.0	58.2	58.4	12 800 *	60.8	57.9	11 800*	63.3	56.7	8 800*	38.0
40.0	56.1	57.1	12 600 *	58.7	56.5	11 200*	61.2	55.3	8 500*	40.0
44.0	51.8	54.0	12 000 *	54.4	53.4	10 400*	56.7	52.2	8 000*	44.0
48.0	47.2	50.4	11 400 *	49.7	49.8	9 700*	51.9	48.5	7 600*	48.0
52.0	42.2	46.2	10 500 *	44.6	45.5	9 000*	46.7	44.0	7 200*	52.0
56.0	36.6	41.1	9 700 *	39.0	40.3	8 500*				56.0
60.0	30.2	34.7	9 000 *	32.4	33.8	8 100*				60.0
64.0	22.0	26.0	7 800 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	79.9	70.9	16 900 *							15.2
16.0	79.3	70.7	16 800 *							16.0
18.0	77.6	70.3	16 400 *							18.0
20.0	75.9	69.8	16 000 *	78.5	69.3	13 300*				20.0
22.0	74.2	69.2	15 700 *	76.8	68.7	13 300*	79.5	67.7	12 400*	22.0
24.0	72.5	68.5	15 300 *	75.1	68.1	13 300*	77.7	67.0	11 800*	24.0
26.0	70.7	67.8	14 900 *	73.3	67.4	13 300*	75.9	66.3	11 300*	26.0
28.0	69.0	67.0	14 500 *	71.5	66.6	13 300*	74.1	65.5	10 800*	28.0
30.0	67.2	66.2	14 200 *	69.7	65.7	13 000*	72.3	64.6	10 400*	30.0
32.0	65.4	65.2	13 900 *	67.9	64.8	12 800*	70.4	63.7	10 000*	32.0
34.0	63.5	64.2	13 500 *	66.1	63.7	12 500*	68.5	62.6	9 600*	34.0
36.0	61.6	63.1	13 300 *	64.2	62.6	12 300*	66.6	61.5	9 300*	36.0
38.0	59.7	62.0	13 000 *	62.2	61.4	12 100*	64.7	60.3	9 000*	38.0
40.0	57.8	60.7	12 700 *	60.3	60.2	11 600*	62.7	59.0	8 700*	40.0
44.0	53.8	57.8	12 200 *	56.2	57.3	10 700*	58.5	56.0	8 200*	44.0
48.0	49.5	54.5	11 700 *	51.9	53.9	10 000*	54.1	52.6	7 800*	48.0
52.0	44.9	50.6	11 000 *	47.3	50.0	9 300*	49.3	48.6	7 400*	52.0
56.0	39.9	46.1	10 100 *	42.2	45.4	8 800*	44.1	43.8	7 100*	56.0
60.0	34.3	40.5	9 400	36.5	39.7	8 300*				60.0
64.0	27.7	33.5	8 200							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.3	73.9	16 900 *							15.2
16.0	79.7	73.8	16 800 *							16.0
18.0	78.1	73.4	16 400 *							18.0
20.0	76.5	72.9	16 100 *	79.0	72.4	13 300 *				20.0
22.0	74.9	72.3	15 700 *	77.4	71.9	13 300 *	79.9	70.8	12 500 *	22.0
24.0	73.2	71.7	15 400 *	75.7	71.2	13 300 *	78.2	70.2	12 000 *	24.0
26.0	71.5	71.0	15 000 *	74.0	70.5	13 300 *	76.5	69.5	11 400 *	26.0
28.0	69.9	70.3	14 600 *	72.4	69.8	13 300 *	74.8	68.7	11 000 *	28.0
30.0	68.2	69.4	14 300 *	70.6	69.0	13 100 *	73.1	67.9	10 600 *	30.0
32.0	66.4	68.6	14 000 *	68.9	68.1	12 900 *	71.3	67.0	10 200 *	32.0
34.0	64.7	67.6	13 700 *	67.1	67.1	12 600 *	69.5	66.0	9 800 *	34.0
36.0	62.9	66.6	13 400 *	65.4	66.1	12 500 *	67.7	64.9	9 500 *	36.0
38.0	61.1	65.4	13 200 *	63.5	64.9	12 200 *	65.9	63.8	9 200 *	38.0
40.0	59.3	64.2	12 900 *	61.7	63.7	12 000 *	64.0	62.6	8 900 *	40.0
44.0	55.5	61.6	12 400 *	57.9	61.0	11 100 *	60.1	59.8	8 400 *	44.0
48.0	51.5	58.5	12 000 *	53.8	57.9	10 300 *	56.0	56.6	7 900 *	48.0
52.0	47.3	54.9	11 400 *	49.6	54.3	9 600 *	51.6	52.9	7 600 *	52.0
56.0	42.7	50.7	10 600 *	45.0	50.1	9 000 *	46.8	48.5	7 200 *	56.0
60.0	37.7	45.8	9 300	39.9	45.1	8 500 *				60.0
64.0	32.0	39.8	8 200	34.1	38.9	8 100 *				64.0
68.0	25.2	32.1	6 600 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
15.2	80.7	77.0	16 900 *							15.2
16.0	80.1	76.9	16 700 *							16.0
18.0	78.6	76.4	16 400 *							18.0
20.0	77.0	76.0	16 100 *	79.5	75.5	13 300 *				20.0
22.0	75.5	75.4	15 800 *	77.9	75.0	13 300 *				22.0
24.0	73.9	74.8	15 400 *	76.3	74.4	13 300 *	78.7	73.3	12 100 *	24.0
26.0	72.3	74.2	15 100 *	74.7	73.7	13 300 *	77.1	72.7	11 600 *	26.0
28.0	70.7	73.5	14 700 *	73.1	73.0	13 300 *	75.5	71.9	11 200 *	28.0
30.0	69.1	72.7	14 400 *	71.5	72.2	13 200 *	73.8	71.1	10 700 *	30.0
32.0	67.4	71.9	14 100 *	69.8	71.4	13 000 *	72.1	70.3	10 300 *	32.0
34.0	65.8	70.9	13 800 *	68.1	70.4	12 700 *	70.4	69.3	10 000 *	34.0
36.0	64.1	70.0	13 600 *	66.4	69.5	12 500 *	68.7	68.3	9 600 *	36.0
38.0	62.4	68.9	13 300 *	64.7	68.4	12 300 *	67.0	67.2	9 400 *	38.0
40.0	60.6	67.8	13 000 *	63.0	67.2	12 200 *	65.2	66.1	9 100 *	40.0
44.0	57.1	65.2	12 500 *	59.3	64.7	11 400 *	61.5	63.5	8 500 *	44.0
48.0	53.3	62.3	12 100 *	55.6	61.8	10 600 *	57.6	60.5	8 100 *	48.0
52.0	49.4	59.0	11 700	51.6	58.4	9 900 *	53.6	57.0	7 700 *	52.0
56.0	45.2	55.1	10 400	47.3	54.5	9 300 *	49.2	53.0	7 400 *	56.0
60.0	40.6	50.7	9 100	42.7	50.0	8 800 *	44.5	48.4	7 100 *	60.0
64.0	35.6	45.3	7 800	37.6	44.6	8 100				64.0
68.0	29.8	38.8	6 700	31.7	37.9	6 900				68.0
72.0	22.7	30.3	5 100 *							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.0	79.8	16 600 *							16.8
18.0	79.0	79.5	16 400 *							18.0
20.0	77.5	79.1	16 100 *	79.9	78.6	13 300*				20.0
22.0	76.0	78.5	15 800 *	78.4	78.1	13 300*				22.0
24.0	74.5	78.0	15 500 *	76.9	77.5	13 300*	79.2	76.4	12 300*	24.0
26.0	73.0	77.3	15 200 *	75.3	76.9	13 300*	77.6	75.8	11 800*	26.0
28.0	71.5	76.7	14 800 *	73.8	76.2	13 300*	76.1	75.1	11 300*	28.0
30.0	69.9	75.9	14 500 *	72.2	75.4	13 200*	74.5	74.3	10 900*	30.0
32.0	68.3	75.1	14 200 *	70.6	74.6	13 000*	72.9	73.5	10 500*	32.0
34.0	66.8	74.2	13 900 *	69.0	73.7	12 800*	71.3	72.6	10 200*	34.0
36.0	65.2	73.3	13 700 *	67.4	72.8	12 600*	69.6	71.7	9 800*	36.0
38.0	63.5	72.3	13 400 *	65.8	71.8	12 400*	67.9	70.6	9 500*	38.0
40.0	61.9	71.2	13 100 *	64.1	70.7	12 300*	66.3	69.5	9 200*	40.0
44.0	58.5	68.8	12 700 *	60.7	68.3	11 700*	62.8	67.1	8 700*	44.0
48.0	55.0	66.1	12 300 *	57.1	65.5	10 900*	59.1	64.3	8 300*	48.0
52.0	51.3	62.9	11 800	53.4	62.4	10 200*	55.3	61.0	7 900*	52.0
56.0	47.4	59.4	10 200	49.5	58.7	9 600*	51.3	57.3	7 500*	56.0
60.0	43.2	55.3	8 800	45.2	54.6	9 100	46.9	53.0	7 200*	60.0
64.0	38.6	50.4	7 600	40.6	49.7	7 900	42.2	48.0	7 000*	64.0
68.0	33.5	44.7	6 600	35.4	43.9	6 800				68.0
72.0	27.6	37.7	5 300 *							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.3	82.8	16 600 *							16.8
18.0	79.4	82.6	16 400 *							18.0
20.0	78.0	82.1	16 100 *	80.3	81.7	13 300*				20.0
22.0	76.6	81.6	15 800 *	78.8	81.2	13 300*				22.0
24.0	75.1	81.1	15 500 *	77.4	80.6	13 300*	79.6	79.6	12 400*	24.0
26.0	73.7	80.5	15 200 *	75.9	80.0	13 300*	78.1	78.9	11 900*	26.0
28.0	72.2	79.8	14 900 *	74.4	79.4	13 300*	76.6	78.3	11 500*	28.0
30.0	70.7	79.1	14 600 *	72.9	78.6	13 200*	75.1	77.5	11 000*	30.0
32.0	69.2	78.4	14 300 *	71.4	77.9	13 100*	73.6	76.8	10 700*	32.0
34.0	67.7	77.5	14 000 *	69.9	77.0	12 900*	72.0	75.9	10 300*	34.0
36.0	66.1	76.6	13 800 *	68.3	76.1	12 700*	70.4	75.0	10 000*	36.0
38.0	64.6	75.7	13 500 *	66.7	75.2	12 500*	68.9	74.0	9 700*	38.0
40.0	63.0	74.6	13 300 *	65.2	74.1	12 300*	67.2	72.9	9 400*	40.0
44.0	59.8	72.3	12 800 *	61.9	71.8	12 000*	63.9	70.6	8 900*	44.0
48.0	56.4	69.8	12 400 *	58.5	69.2	11 200*	60.5	67.9	8 400*	48.0
52.0	52.9	66.8	11 500	55.0	66.2	10 500*	56.9	64.9	8 000*	52.0
56.0	49.3	63.5	9 900	51.3	62.8	9 800*	53.1	61.5	7 700*	56.0
60.0	45.4	59.6	8 600	47.4	59.0	8 900	49.1	57.5	7 400*	60.0
64.0	41.2	55.2	7 300	43.2	54.5	7 700	44.8	52.9	7 100*	64.0
68.0	36.7	50.1	6 300	38.6	49.3	6 500				68.0
72.0	31.5	43.9	5 300	33.3	43.0	5 600				72.0
76.0	25.4	36.2	3 900 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
16.8	80.7	85.9	16 500 *							16.8
18.0	79.8	85.6	16 300 *							18.0
20.0	78.4	85.2	16 000 *	80.6	84.7	13 300*				20.0
22.0	77.1	84.7	15 700 *	79.2	84.3	13 300*				22.0
24.0	75.7	84.2	15 500 *	77.8	83.7	13 300*	80.0	82.7	12 600*	24.0
26.0	74.3	83.6	15 200 *	76.4	83.2	13 300*	78.6	82.1	12 000*	26.0
28.0	72.8	83.0	14 900 *	75.0	82.5	13 300*	77.1	81.4	11 600*	28.0
30.0	71.4	82.3	14 700 *	73.5	81.8	13 200*	75.7	80.7	11 200*	30.0
32.0	70.0	81.6	14 400 *	72.1	81.1	13 100*	74.2	80.0	10 800*	32.0
34.0	68.5	80.8	14 100 *	70.6	80.3	12 900*	72.7	79.2	10 400*	34.0
36.0	67.0	79.9	13 900 *	69.1	79.4	12 700*	71.2	78.3	10 100*	36.0
38.0	65.5	79.0	13 600 *	67.6	78.5	12 600*	69.7	77.3	9 800*	38.0
40.0	64.0	78.0	13 400 *	66.1	77.5	12 400*	68.1	76.3	9 500*	40.0
44.0	61.0	75.8	12 900 *	63.0	75.3	12 100*	65.0	74.1	9 000*	44.0
48.0	57.8	73.4	12 500 *	59.8	72.8	11 500*	61.7	71.6	8 600*	48.0
52.0	54.5	70.6	11 300	56.5	70.0	10 800*	58.4	68.7	8 100*	52.0
56.0	51.0	67.4	9 700	53.0	66.8	10 100	54.8	65.5	7 800*	56.0
60.0	47.4	63.8	8 300	49.4	63.2	8 700	51.1	61.8	7 500*	60.0
64.0	43.6	59.8	7 100	45.5	59.1	7 400	47.0	57.5	7 300*	64.0
68.0	39.4	55.1	6 100	41.2	54.3	6 400	42.7	52.6	6 600	68.0
72.0	34.8	49.6	5 100	36.6	48.7	5 300				72.0
76.0	29.6	43.0	4 000 *	31.2	42.0	4 400				76.0
80.0	23.2	34.5	2 600 *							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	81.0	88.9	16 400 *							16.8
18.0	80.2	88.7	16 200 *							18.0
20.0	78.8	88.3	16 000 *							20.0
22.0	77.5	87.8	15 700 *	79.6	87.3	13 300*				22.0
24.0	76.2	87.3	15 500 *	78.2	86.8	13 300*				24.0
26.0	74.8	86.8	15 200 *	76.9	86.3	13 300*	79.0	85.2	12 200*	26.0
28.0	73.4	86.2	14 900 *	75.5	85.7	13 300*	77.6	84.6	11 800*	28.0
30.0	72.1	85.5	14 700 *	74.1	85.0	13 200*	76.2	83.9	11 300*	30.0
32.0	70.7	84.8	14 500 *	72.7	84.3	13 100*	74.8	83.2	11 000*	32.0
34.0	69.3	84.0	14 200 *	71.3	83.5	12 900*	73.3	82.4	10 600*	34.0
36.0	67.9	83.2	13 900 *	69.9	82.7	12 800*	71.9	81.6	10 300*	36.0
38.0	66.4	82.3	13 700 *	68.5	81.8	12 600*	70.4	80.6	10 000*	38.0
40.0	65.0	81.4	13 500 *	67.0	80.8	12 500*	69.0	79.7	9 700*	40.0
44.0	62.1	79.3	13 000 *	64.1	78.8	12 200*	66.0	77.6	9 200*	44.0
48.0	59.0	76.9	12 600	61.0	76.4	11 800*	62.9	75.1	8 700*	48.0
52.0	55.9	74.3	11 000	57.8	73.7	11 000*	59.7	72.4	8 300*	52.0
56.0	52.6	71.3	9 400	54.6	70.7	9 900	56.3	69.4	8 000*	56.0
60.0	49.2	67.9	8 000	51.1	67.3	8 400	52.8	65.9	7 600*	60.0
64.0	45.6	64.1	6 800	47.5	63.5	7 200	49.1	62.0	7 300*	64.0
68.0	41.8	59.8	5 800	43.6	59.1	6 000	45.1	57.4	6 300	68.0
72.0	37.6	54.8	4 800	39.3	54.0	5 100				72.0
76.0	32.9	48.9	3 900	34.6	48.0	4 200				76.0
80.0	27.6	41.8	2 600 *							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
18.3	80.3	91.7	16 100 *							18.3
20.0	79.2	91.3	15 900 *							20.0
22.0	77.9	90.9	15 700 *	80.0	90.4	13 300*				22.0
24.0	76.6	90.4	15 400 *	78.6	89.9	13 300*				24.0
26.0	75.3	89.9	15 200 *	77.3	89.4	13 300*	79.4	88.3	12 300*	26.0
28.0	74.0	89.3	14 900 *	76.0	88.8	13 300*	78.0	87.7	11 900*	28.0
30.0	72.7	88.7	14 700 *	74.7	88.2	13 200*	76.7	87.1	11 500*	30.0
32.0	71.3	88.0	14 500 *	73.3	87.5	13 000*	75.3	86.4	11 100*	32.0
34.0	70.0	87.2	14 200 *	72.0	86.7	12 900*	73.9	85.6	10 800*	34.0
36.0	68.6	86.4	14 000 *	70.6	85.9	12 800*	72.6	84.8	10 400*	36.0
38.0	67.3	85.6	13 800 *	69.2	85.1	12 700*	71.2	83.9	10 100*	38.0
40.0	65.9	84.7	13 500 *	67.8	84.2	12 500*	69.7	83.0	9 800*	40.0
44.0	63.1	82.7	13 100 *	65.0	82.2	12 200*	66.9	81.0	9 300*	44.0
48.0	60.2	80.4	12 600	62.1	79.9	11 900*	63.9	78.7	8 800*	48.0
52.0	57.2	77.9	10 800	59.1	77.4	11 300	60.8	76.1	8 500*	52.0
56.0	54.1	75.1	9 200	56.0	74.5	9 600	57.7	73.2	8 100*	56.0
60.0	50.9	71.9	7 800	52.7	71.3	8 200	54.3	69.9	7 800*	60.0
64.0	47.5	68.3	6 600	49.3	67.7	6 900	50.9	66.2	7 300	64.0
68.0	43.9	64.3	5 500	45.7	63.6	5 800	47.1	62.0	6 100	68.0
72.0	40.0	59.7	4 500	41.8	58.9	4 900	43.1	57.2	5 100	72.0
76.0	35.8	54.4	3 700	37.5	53.5	4 000				76.0
80.0	31.1	48.1	2 600 *	32.7	47.1	3 000*				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
18.3	80.6	94.7	16 100 *							18.3
20.0	79.6	94.4	15 800 *							20.0
22.0	78.3	94.0	15 600 *	80.3	93.5	13 300*				22.0
24.0	77.1	93.5	15 400 *	79.0	93.0	13 300*				24.0
26.0	75.8	93.0	15 100 *	77.8	92.5	13 300*	79.7	91.4	12 500*	26.0
28.0	74.5	92.4	14 900 *	76.5	91.9	13 300*	78.4	90.8	12 000*	28.0
30.0	73.3	91.8	14 700 *	75.2	91.3	13 100*	77.1	90.2	11 600*	30.0
32.0	72.0	91.2	14 500 *	73.9	90.7	13 000*	75.8	89.5	11 200*	32.0
34.0	70.7	90.4	14 200 *	72.6	89.9	12 900*	74.5	88.8	10 900*	34.0
36.0	69.4	89.7	14 000 *	71.3	89.2	12 800*	73.2	88.0	10 600*	36.0
38.0	68.0	88.9	13 800 *	69.9	88.3	12 700*	71.8	87.2	10 300*	38.0
40.0	66.7	88.0	13 600 *	68.6	87.5	12 500*	70.5	86.3	10 000*	40.0
44.0	64.0	86.1	13 200 *	65.9	85.5	12 300*	67.7	84.4	9 500*	44.0
48.0	61.2	83.9	12 600	63.1	83.4	12 000*	64.9	82.1	9 000*	48.0
52.0	58.4	81.5	10 800	60.2	80.9	11 400	61.9	79.7	8 600*	52.0
56.0	55.4	78.8	9 200	57.2	78.2	9 700	58.9	76.9	8 200*	56.0
60.0	52.4	75.8	7 800	54.1	75.2	8 200	55.8	73.8	7 900*	60.0
64.0	49.2	72.4	6 600	50.9	71.8	7 000	52.5	70.3	7 300	64.0
68.0	45.8	68.6	5 500	47.5	67.9	5 900	49.0	66.4	6 100	68.0
72.0	42.2	64.3	4 600	43.9	63.6	4 900	45.3	62.0	5 100	72.0
76.0	38.3	59.4	3 800	40.0	58.7	4 000				76.0
80.0	34.1	53.8	2 900 *	35.7	52.9	3 200				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
18.3	80.9	97.8	16 000 *							18.3
20.0	79.9	97.5	15 800 *							20.0
22.0	78.7	97.1	15 500 *							22.0
24.0	77.5	96.6	15 300 *	79.4	96.1	13 300*				24.0
26.0	76.3	96.1	15 100 *	78.1	95.6	13 300*	80.1	94.5	12 500*	26.0
28.0	75.0	95.6	14 900 *	76.9	95.1	13 200*	78.8	93.9	12 100*	28.0
30.0	73.8	95.0	14 700 *	75.7	94.5	13 100*	77.5	93.3	11 700*	30.0
32.0	72.5	94.3	14 500 *	74.4	93.8	13 000*	76.3	92.7	11 400*	32.0
34.0	71.3	93.6	14 200 *	73.2	93.1	12 800*	75.0	92.0	11 000*	34.0
36.0	70.0	92.9	14 000 *	71.9	92.4	12 800*	73.7	91.2	10 700*	36.0
38.0	68.8	92.1	13 800 *	70.6	91.6	12 700*	72.4	90.4	10 400*	38.0
40.0	67.5	91.3	13 600 *	69.3	90.8	12 500*	71.1	89.6	10 100*	40.0
44.0	64.9	89.4	13 200 *	66.7	88.9	12 300*	68.5	87.7	9 600*	44.0
48.0	62.2	87.4	12 500	64.0	86.8	12 000*	65.7	85.6	9 100*	48.0
52.0	59.5	85.0	10 500	61.3	84.5	11 100	62.9	83.2	8 700*	52.0
56.0	56.6	82.5	8 900	58.4	81.9	9 400	60.1	80.6	8 300*	56.0
60.0	53.7	79.6	7 600	55.5	79.0	8 000	57.1	77.6	8 000*	60.0
64.0	50.7	76.4	6 300	52.4	75.8	6 800	53.9	74.3	7 100	64.0
68.0	47.5	72.8	5 300	49.2	72.1	5 700	50.7	70.7	6 000	68.0
72.0	44.2	68.8	4 400	45.8	68.1	4 700	47.2	66.5	4 900	72.0
76.0	40.6	64.3	3 500	42.2	63.5	3 800	43.5	61.8	4 000	76.0
80.0	36.7	59.1	2 700	38.3	58.3	3 000				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
19.8	80.3	100.6	15 500 *							19.8
20.0	80.2	100.5	15 400 *							20.0
22.0	79.0	100.1	15 300 *							22.0
24.0	77.9	99.7	15 100 *	79.7	99.2	13 300*				24.0
26.0	76.7	99.2	14 900 *	78.5	98.7	13 200*	80.4	97.6	12 500*	26.0
28.0	75.5	98.7	14 700 *	77.3	98.2	13 100*	79.2	97.1	12 300*	28.0
30.0	74.3	98.1	14 600 *	76.1	97.6	13 000*	77.9	96.5	11 800*	30.0
32.0	73.1	97.5	14 300 *	74.9	97.0	12 900*	76.7	95.8	11 500*	32.0
34.0	71.9	96.8	14 200 *	73.7	96.3	12 800*	75.5	95.2	11 100*	34.0
36.0	70.7	96.1	14 000 *	72.5	95.6	12 700*	74.2	94.4	10 800*	36.0
38.0	69.4	95.3	13 800 *	71.2	94.8	12 600*	73.0	93.7	10 500*	38.0
40.0	68.2	94.5	13 600 *	70.0	94.0	12 500*	71.7	92.8	10 200*	40.0
44.0	65.7	92.8	13 200 *	67.5	92.2	12 300*	69.2	91.0	9 700*	44.0
48.0	63.1	90.8	12 000	64.9	90.2	12 000*	66.6	89.0	9 200*	48.0
52.0	60.5	88.5	10 300	62.2	88.0	10 800	63.9	86.7	8 800*	52.0
56.0	57.8	86.1	8 600	59.5	85.5	9 200	61.1	84.2	8 500*	56.0
60.0	55.0	83.3	7 200	56.7	82.7	7 700	58.3	81.4	8 100	60.0
64.0	52.1	80.3	6 000	53.8	79.6	6 500	55.3	78.3	6 800	64.0
68.0	49.1	76.9	5 000	50.8	76.2	5 400	52.2	74.8	5 700	68.0
72.0	45.9	73.1	4 000	47.6	72.4	4 400	48.9	70.9	4 700	72.0
76.0	42.6	68.9	3 200	44.2	68.1	3 500	45.5	66.5	3 700	76.0
80.0	39.0	64.1	2 400	40.6	63.3	2 700				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
12.2	79.3	50.2	13 300 *							12.2
14.0	76.8	49.7	13 100 *							14.0
16.0	74.3	49.1	12 700 *	78.8	48.8	12 200*				16.0
18.0	71.9	48.5	12 400 *	76.3	48.1	11 800*				18.0
20.0	69.3	47.7	12 000 *	73.8	47.3	11 400*	78.3	46.4	10 200*	20.0
22.0	66.8	46.8	11 700 *	71.2	46.4	11 100*	75.7	45.5	9 500*	22.0
24.0	64.2	45.8	11 300 *	68.5	45.5	10 700*	73.0	44.5	8 900*	24.0
26.0	61.5	44.7	10 900 *	65.8	44.4	10 400*	70.2	43.4	8 400*	26.0
28.0	58.7	43.5	10 600 *	63.1	43.1	10 100*	67.4	42.1	7 900*	28.0
30.0	55.9	42.2	10 200 *	60.2	41.7	9 800*	64.4	40.7	7 500*	30.0
32.0	53.0	40.6	9 900 *	57.2	40.2	9 200*	61.4	39.1	7 100*	32.0
34.0	49.9	39.0	9 600 *	54.1	38.5	8 700*	58.2	37.4	6 800*	34.0
36.0	46.7	37.1	9 300 *	50.8	36.6	8 200*	54.8	35.4	6 500*	36.0
38.0	43.2	35.0	9 000 *	47.4	34.4	7 800*	51.2	33.2	6 200*	38.0
40.0	39.6	32.6	8 800 *	43.7	32.0	7 400*	47.3	30.6	5 900*	40.0
44.0	31.1	26.6	7 800 *	35.0	25.9	6 800*				44.0
30.5m Boom										
12.2	79.9	53.3	13 300 *							12.2
14.0	77.6	52.8	13 200 *							14.0
16.0	75.3	52.3	12 800 *	79.5	51.9	12 300*				16.0
18.0	72.9	51.6	12 500 *	77.1	51.3	11 900*				18.0
20.0	70.6	50.9	12 100 *	74.8	50.5	11 500*	79.0	49.6	10 500*	20.0
22.0	68.2	50.1	11 800 *	72.4	49.7	11 200*	76.6	48.8	9 800*	22.0
24.0	65.8	49.2	11 400 *	69.9	48.8	10 900*	74.1	47.8	9 100*	24.0
26.0	63.3	48.2	11 100 *	67.4	47.8	10 600*	71.5	46.8	8 600*	26.0
28.0	60.8	47.1	10 800 *	64.8	46.6	10 300*	68.9	45.6	8 100*	28.0
30.0	58.2	45.8	10 500 *	62.2	45.4	10 000*	66.2	44.3	7 700*	30.0
32.0	55.5	44.4	10 200 *	59.5	44.0	9 700*	63.4	42.9	7 300*	32.0
34.0	52.7	42.9	9 900 *	56.7	42.4	9 100*	60.5	41.3	7 000*	34.0
36.0	49.8	41.2	9 600 *	53.8	40.7	8 600*	57.5	39.6	6 700*	36.0
38.0	46.8	39.3	9 300 *	50.7	38.8	8 200*	54.4	37.6	6 400*	38.0
40.0	43.6	37.2	9 100 *	47.4	36.7	7 800*	51.0	35.4	6 200*	40.0
44.0	36.5	32.2	8 400 *	40.2	31.6	7 100*	43.4	30.0	5 800*	44.0
48.0	27.8	25.4	7 600 *	31.3	24.6	6 600*				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	80.5	56.3	13 300 *			12 000*			10 600*	12.2
14.0	78.2	55.9	13 200 *							14.0
16.0	76.1	55.4	12 800 *							16.0
18.0	73.9	54.8	12 500 *							18.0
20.0	71.7	54.1	12 200 *							20.0
22.0	69.5	53.4	11 900 *	73.4	53.0	11 300*	77.4	52.0	9 900*	22.0
24.0	67.2	52.5	11 500 *	71.1	52.1	11 000*	75.1	51.1	9 400*	24.0
26.0	64.9	51.6	11 200 *	68.8	51.1	10 700*	72.7	50.1	8 800*	26.0
28.0	62.5	50.5	10 900 *	66.4	50.1	10 400*	70.3	49.1	8 400*	28.0
30.0	60.1	49.3	10 600 *	64.0	48.9	10 200*	67.8	47.9	7 900*	30.0
32.0	57.6	48.1	10 300 *	61.5	47.6	9 900*	65.2	46.5	7 600*	32.0
34.0	55.1	46.7	10 100 *	58.9	46.2	9 500*	62.6	45.1	7 200*	34.0
36.0	52.4	45.1	9 800 *	56.2	44.7	9 000*	59.8	43.5	6 900*	36.0
38.0	49.7	43.4	9 500 *	53.4	42.9	8 500*	57.0	41.7	6 600*	38.0
40.0	46.8	41.6	9 300 *	50.5	41.0	8 200*	54.0	39.8	6 400*	40.0
44.0	40.6	37.2	8 800 *	44.2	36.6	7 500*	47.4	35.1	6 000*	44.0
48.0	33.5	31.6	8 100 *	36.9	30.9	6 900*				48.0
52.0	24.4	23.9	7 400 *							52.0
36.5m Boom										
12.2	81.0	59.4	13 300 *			12 100*			10 800*	12.2
14.0	78.9	59.0	13 200 *							14.0
16.0	76.8	58.5	12 800 *							16.0
18.0	74.8	57.9	12 500 *							18.0
20.0	72.7	57.3	12 200 *							20.0
22.0	70.6	56.6	12 000 *	74.3	56.2	11 400*	78.1	55.2	10 100*	22.0
24.0	68.5	55.8	11 600 *	72.2	55.4	11 100*	75.9	54.4	9 600*	24.0
26.0	66.3	54.9	11 300 *	70.0	54.5	10 900*	73.7	53.4	9 000*	26.0
28.0	64.1	53.9	11 000 *	67.8	53.5	10 600*	71.4	52.4	8 600*	28.0
30.0	61.8	52.8	10 800 *	65.5	52.4	10 300*	69.1	51.3	8 200*	30.0
32.0	59.5	51.6	10 500 *	63.2	51.2	10 100*	66.7	50.1	7 800*	32.0
34.0	57.2	50.3	10 200 *	60.8	49.9	9 800*	64.3	48.8	7 400*	34.0
36.0	54.7	48.9	10 000 *	58.3	48.4	9 400*	61.8	47.3	7 200*	36.0
38.0	52.2	47.4	9 800 *	55.8	46.9	8 900*	59.2	45.7	6 900*	38.0
40.0	49.6	45.7	9 500 *	53.1	45.2	8 500*	56.5	43.9	6 600*	40.0
44.0	44.1	41.7	9 000 *	47.5	41.2	7 800*	50.6	39.8	6 100*	44.0
48.0	37.9	36.9	8 600 *	41.2	36.3	7 200*	44.1	34.7	5 800*	48.0
52.0	30.5	30.7	7 800 *	33.7	29.9	6 700*				52.0
56.0	20.9	21.9	7 100 *							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
13.7	80.0	62.1	13 200 *							13.7
14.0	79.4	62.0	13 200 *							14.0
16.0	77.5	61.6	12 800 *							16.0
18.0	75.5	61.0	12 500 *							18.0
20.0	73.6	60.4	12 300 *							20.0
22.0	71.6	59.8	12 000 *	75.1	59.4	11 500*	78.8	58.3	10 300*	22.0
24.0	69.6	59.0	11 700 *	73.1	58.6	11 300*	76.7	57.6	9 800*	24.0
26.0	67.5	58.2	11 400 *	71.0	57.7	11 000*	74.6	56.7	9 200*	26.0
28.0	65.5	57.3	11 100 *	69.0	56.8	10 700*	72.5	55.8	8 800*	28.0
30.0	63.4	56.2	10 800 *	66.8	55.8	10 500*	70.3	54.7	8 400*	30.0
32.0	61.2	55.1	10 600 *	64.7	54.7	10 200*	68.1	53.6	8 000*	32.0
34.0	59.0	53.9	10 300 *	62.4	53.5	10 000*	65.8	52.3	7 600*	34.0
36.0	56.7	52.6	10 100 *	60.2	52.1	9 700*	63.5	51.0	7 300*	36.0
38.0	54.4	51.2	9 900 *	57.8	50.7	9 300*	61.1	49.5	7 000*	38.0
40.0	52.0	49.6	9 700 *	55.4	49.1	8 900*	58.6	47.9	6 800*	40.0
44.0	47.0	46.0	9 200 *	50.3	45.5	8 100*	53.3	44.1	6 300*	44.0
48.0	41.4	41.7	8 800 *	44.7	41.1	7 500*	47.5	39.6	6 000*	48.0
52.0	35.2	36.4	8 200 *	38.3	35.7	7 000*				52.0
56.0	27.7	29.6	7 600 *	30.6	28.7	6 500*				56.0
42.5m Boom										
13.7	80.4	65.2	13 100 *							13.7
14.0	79.9	65.1	13 100 *							14.0
16.0	78.1	64.7	12 800 *							16.0
18.0	76.2	64.2	12 500 *							18.0
20.0	74.4	63.6	12 300 *							20.0
22.0	72.5	62.9	12 000 *	75.9	62.5	11 600*	79.3	61.5	10 500*	22.0
24.0	70.6	62.2	11 800 *	73.9	61.8	11 300*	77.4	60.8	9 900*	24.0
26.0	68.7	61.4	11 500 *	72.0	61.0	11 100*	75.4	60.0	9 400*	26.0
28.0	66.7	60.6	11 200 *	70.0	60.1	10 800*	73.4	59.1	9 000*	28.0
30.0	64.7	59.6	10 900 *	68.0	59.2	10 600*	71.3	58.1	8 600*	30.0
32.0	62.7	58.6	10 700 *	66.0	58.1	10 400*	69.3	57.0	8 200*	32.0
34.0	60.6	57.4	10 400 *	63.9	57.0	10 100*	67.1	55.8	7 900*	34.0
36.0	58.5	56.2	10 200 *	61.8	55.7	9 900*	65.0	54.6	7 500*	36.0
38.0	56.4	54.9	10 000 *	59.6	54.4	9 700*	62.7	53.2	7 300*	38.0
40.0	54.1	53.4	9 800 *	57.4	52.9	9 200*	60.4	51.7	7 000*	40.0
44.0	49.5	50.1	9 400 *	52.7	49.6	8 400*	55.6	48.3	6 500*	44.0
48.0	44.5	46.2	9 000 *	47.6	45.7	7 800*	50.4	44.2	6 100*	48.0
52.0	38.9	41.6	8 600 *	42.0	40.9	7 200*	44.5	39.3	5 800*	52.0
56.0	32.6	35.8	8 000 *	35.5	35.0	6 800*				56.0
60.0	24.8	28.1	7 400 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	80.9	68.2	13 100 *							13.7
14.0	80.4	68.1	13 100 *							14.0
16.0	78.6	67.7	12 800 *							16.0
18.0	76.9	67.3	12 500 *							18.0
20.0	75.1	66.7	12 300 *	78.3	66.3	12 000 *				20.0
22.0	73.3	66.1	12 000 *	76.5	65.7	11 700 *	79.8	64.6	10 600 *	22.0
24.0	71.5	65.4	11 700 *	74.7	65.0	11 400 *	78.0	63.9	10 100 *	24.0
26.0	69.7	64.7	11 500 *	72.9	64.2	11 100 *	76.1	63.2	9 600 *	26.0
28.0	67.8	63.9	11 200 *	71.0	63.4	10 900 *	74.2	62.3	9 100 *	28.0
30.0	65.9	62.9	11 000 *	69.1	62.5	10 700 *	72.3	61.4	8 700 *	30.0
32.0	64.0	62.0	10 700 *	67.2	61.5	10 500 *	70.3	60.4	8 300 *	32.0
34.0	62.1	60.9	10 500 *	65.2	60.4	10 200 *	68.3	59.3	8 000 *	34.0
36.0	60.1	59.7	10 300 *	63.2	59.3	10 000 *	66.3	58.1	7 700 *	36.0
38.0	58.1	58.5	10 000 *	61.2	58.0	9 800 *	64.2	56.8	7 400 *	38.0
40.0	56.0	57.1	9 900 *	59.1	56.6	9 500 *	62.1	55.4	7 200 *	40.0
44.0	51.7	54.1	9 400 *	54.7	53.6	8 700 *	57.6	52.3	6 700 *	44.0
48.0	47.1	50.5	9 100 *	50.1	49.9	8 100 *	52.8	48.5	6 300 *	48.0
52.0	42.1	46.3	8 700 *	45.0	45.7	7 500 *	47.6	44.1	6 000 *	52.0
56.0	36.6	41.2	8 400 *	39.4	40.5	7 000 *	41.7	38.7	5 700 *	56.0
60.0	30.1	34.8	7 800 *	32.8	34.0	6 600 *				60.0
64.0	22.0	26.2	7 200 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
15.2	80.0	71.0	12 900 *							15.2
16.0	79.1	70.8	12 800 *							16.0
18.0	77.5	70.3	12 500 *							18.0
20.0	75.8	69.8	12 300 *	78.9	69.4	11 900*				20.0
22.0	74.0	69.2	12 000 *	77.1	68.8	11 700*				22.0
24.0	72.3	68.6	11 800 *	75.4	68.2	11 500*	78.5	67.1	10 300*	24.0
26.0	70.6	67.9	11 600 *	73.6	67.4	11 200*	76.8	66.4	9 800*	26.0
28.0	68.8	67.1	11 300 *	71.9	66.7	11 000*	74.9	65.6	9 300*	28.0
30.0	67.0	66.2	11 000 *	70.1	65.8	10 800*	73.1	64.7	8 900*	30.0
32.0	65.2	65.3	10 800 *	68.3	64.9	10 600*	71.3	63.7	8 500*	32.0
34.0	63.4	64.3	10 600 *	66.4	63.8	10 400*	69.4	62.7	8 200*	34.0
36.0	61.5	63.2	10 300 *	64.5	62.7	10 200*	67.5	61.6	7 900*	36.0
38.0	59.6	62.0	10 100 *	62.6	61.5	10 000*	65.5	60.3	7 600*	38.0
40.0	57.7	60.8	9 900 *	60.6	60.3	9 800*	63.5	59.0	7 300*	40.0
44.0	53.6	57.9	9 500 *	56.6	57.4	9 100*	59.3	56.1	6 900*	44.0
48.0	49.4	54.6	9 200 *	52.3	54.0	8 400*	54.9	52.7	6 500*	48.0
52.0	44.8	50.7	8 900 *	47.6	50.1	7 800*	50.2	48.6	6 100*	52.0
56.0	39.8	46.2	8 600 *	42.6	45.5	7 300*	44.9	43.9	5 800*	56.0
60.0	34.2	40.7	8 100 *	36.9	39.9	6 900*				60.0
64.0	27.6	33.7	7 500 *	30.1	32.7	6 500*				64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	80.4	74.1	12 800 *							15.2
16.0	79.6	73.9	12 700 *							16.0
18.0	78.0	73.4	12 400 *							18.0
20.0	76.4	72.9	12 200 *	79.3	72.5	11 900*				20.0
22.0	74.7	72.4	12 000 *	77.7	71.9	11 700*				22.0
24.0	73.1	71.8	11 700 *	76.0	71.3	11 500*	79.0	70.2	10 400*	24.0
26.0	71.4	71.1	11 500 *	74.4	70.6	11 300*	77.3	69.5	9 900*	26.0
28.0	69.7	70.3	11 300 *	72.7	69.9	11 100*	75.6	68.8	9 500*	28.0
30.0	68.0	69.5	11 000 *	71.0	69.1	10 900*	73.9	67.9	9 100*	30.0
32.0	66.3	68.6	10 800 *	69.2	68.2	10 700*	72.1	67.0	8 700*	32.0
34.0	64.6	67.7	10 600 *	67.5	67.2	10 500*	70.3	66.0	8 400*	34.0
36.0	62.8	66.6	10 400 *	65.7	66.2	10 300*	68.5	65.0	8 100*	36.0
38.0	61.0	65.5	10 200 *	63.9	65.0	10 100*	66.7	63.8	7 800*	38.0
40.0	59.2	64.3	9 900 *	62.0	63.8	9 900*	64.8	62.6	7 500*	40.0
44.0	55.4	61.6	9 600 *	58.2	61.1	9 400*	60.9	59.8	7 000*	44.0
48.0	51.4	58.6	9 300 *	54.2	58.0	8 700*	56.8	56.7	6 600*	48.0
52.0	47.2	55.0	9 000 *	49.9	54.4	8 000*	52.4	52.9	6 300*	52.0
56.0	42.6	50.8	8 600 *	45.3	50.2	7 500*	47.6	48.6	6 000*	56.0
60.0	37.6	45.9	8 400 *	40.3	45.2	7 100*	42.4	43.4	5 700*	60.0
64.0	32.0	39.9	7 900 *	34.5	39.1	6 700*				64.0
68.0	25.2	32.2	7 200 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.8	77.1	12 700 *							15.2
16.0	80.0	76.9	12 700 *							16.0
18.0	78.5	76.5	12 400 *							18.0
20.0	76.9	76.0	12 200 *	79.8	75.6	11 800 *				20.0
22.0	75.3	75.5	11 900 *	78.2	75.1	11 600 *				22.0
24.0	73.8	74.9	11 700 *	76.6	74.5	11 500 *	79.5	73.4	10 500 *	24.0
26.0	72.2	74.3	11 500 *	75.0	73.8	11 200 *	77.9	72.7	10 000 *	26.0
28.0	70.6	73.5	11 300 *	73.4	73.1	11 100 *	76.2	72.0	9 600 *	28.0
30.0	69.0	72.8	11 100 *	71.8	72.3	10 900 *	74.6	71.2	9 200 *	30.0
32.0	67.3	71.9	10 800 *	70.1	71.5	10 700 *	72.9	70.3	8 800 *	32.0
34.0	65.7	71.0	10 600 *	68.4	70.5	10 600 *	71.2	69.4	8 500 *	34.0
36.0	64.0	70.0	10 400 *	66.7	69.5	10 400 *	69.5	68.4	8 200 *	36.0
38.0	62.3	69.0	10 200 *	65.0	68.5	10 200 *	67.7	67.3	7 900 *	38.0
40.0	60.5	67.8	10 000 *	63.3	67.3	10 000 *	65.9	66.1	7 700 *	40.0
44.0	56.9	65.3	9 700 *	59.7	64.8	9 600 *	62.3	63.5	7 200 *	44.0
48.0	53.2	62.4	9 400 *	55.9	61.9	8 900 *	58.4	60.5	6 800 *	48.0
52.0	49.3	59.1	9 100 *	51.9	58.5	8 300 *	54.3	57.1	6 400 *	52.0
56.0	45.1	55.2	8 700 *	47.7	54.6	7 800 *	50.0	53.1	6 100 *	56.0
60.0	40.6	50.8	8 500 *	43.1	50.1	7 300 *	45.2	48.4	5 900 *	60.0
64.0	35.5	45.5	8 200 *	38.0	44.7	6 900 *				64.0
68.0	29.8	39.0	7 200	32.1	38.1	6 600 *				68.0
72.0	22.7	30.5	5 600 *							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
16.8	80.0	79.9	12 500 *							16.8
18.0	78.9	79.6	12 300 *							18.0
20.0	77.4	79.1	12 100 *	80.2	78.7	11 700*				20.0
22.0	75.9	78.6	11 900 *	78.7	78.2	11 500*				22.0
24.0	74.4	78.0	11 700 *	77.1	77.6	11 400*	79.9	76.5	10 600*	24.0
26.0	72.9	77.4	11 500 *	75.6	77.0	11 200*	78.4	75.8	10 200*	26.0
28.0	71.3	76.7	11 300 *	74.1	76.3	11 000*	76.8	75.1	9 800*	28.0
30.0	69.8	76.0	11 100 *	72.5	75.5	10 900*	75.2	74.4	9 400*	30.0
32.0	68.2	75.2	10 800 *	70.9	74.7	10 700*	73.6	73.6	9 000*	32.0
34.0	66.6	74.3	10 600 *	69.3	73.8	10 500*	72.0	72.7	8 700*	34.0
36.0	65.0	73.4	10 400 *	67.7	72.9	10 400*	70.3	71.7	8 400*	36.0
38.0	63.4	72.4	10 200 *	66.1	71.9	10 300*	68.7	70.7	8 100*	38.0
40.0	61.8	71.3	10 000 *	64.4	70.8	10 100*	67.0	69.6	7 800*	40.0
44.0	58.4	68.9	9 700 *	61.0	68.4	9 800*	63.5	67.1	7 300*	44.0
48.0	54.8	66.2	9 400 *	57.4	65.6	9 200*	59.9	64.3	6 900*	48.0
52.0	51.2	63.0	9 100 *	53.7	62.5	8 600*	56.1	61.1	6 600*	52.0
56.0	47.3	59.5	8 800 *	49.8	58.9	8 000*	52.0	57.4	6 200*	56.0
60.0	43.1	55.4	8 500 *	45.6	54.7	7 600*	47.7	53.1	5 900*	60.0
64.0	38.6	50.6	8 000	41.0	49.8	7 200*	42.9	48.1	5 800*	64.0
68.0	33.5	44.9	7 000	35.8	44.0	6 800*				68.0
72.0	27.6	37.8	5 900 *							72.0
76.0	20.1	28.3	4 300 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.4	82.9	12 400 *							16.8
18.0	79.3	82.6	12 200 *							18.0
20.0	77.9	82.2	12 000 *	80.5	81.7	11 700*				20.0
22.0	76.4	81.7	11 800 *	79.1	81.3	11 500*				22.0
24.0	75.0	81.2	11 600 *	77.6	80.7	11 300*				24.0
26.0	73.5	80.6	11 400 *	76.2	80.1	11 100*	78.8	79.0	10 300*	26.0
28.0	72.1	79.9	11 200 *	74.7	79.4	11 000*	77.3	78.3	9 900*	28.0
30.0	70.6	79.2	11 100 *	73.2	78.7	10 800*	75.8	77.6	9 500*	30.0
32.0	69.1	78.4	10 800 *	71.7	77.9	10 700*	74.3	76.8	9 200*	32.0
34.0	67.6	77.6	10 600 *	70.1	77.1	10 500*	72.7	75.9	8 800*	34.0
36.0	66.0	76.7	10 400 *	68.6	76.2	10 400*	71.1	75.0	8 500*	36.0
38.0	64.5	75.7	10 300 *	67.0	75.2	10 300*	69.6	74.0	8 200*	38.0
40.0	62.9	74.7	10 100 *	65.4	74.2	10 100*	67.9	73.0	8 000*	40.0
44.0	59.7	72.4	9 700 *	62.2	71.9	9 800*	64.6	70.6	7 500*	44.0
48.0	56.3	69.8	9 400 *	58.8	69.3	9 500*	61.2	68.0	7 000*	48.0
52.0	52.9	66.9	9 100 *	55.3	66.3	8 900*	57.6	64.9	6 700*	52.0
56.0	49.2	63.5	8 900 *	51.6	62.9	8 300*	53.9	61.5	6 400*	56.0
60.0	45.3	59.7	8 600 *	47.7	59.1	7 800*	49.8	57.5	6 100*	60.0
64.0	41.2	55.3	7 800	43.5	54.6	7 400*	45.5	52.9	5 800*	64.0
68.0	36.6	50.2	6 700	38.9	49.4	6 900				68.0
72.0	31.5	44.1	5 800	33.7	43.2	6 000				72.0
76.0	25.4	36.4	4 500 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.7	86.0	12 200 *							16.8
18.0	79.7	85.7	12 100 *							18.0
20.0	78.3	85.3	11 900 *							20.0
22.0	76.9	84.8	11 700 *	79.5	84.3	11 400 *				22.0
24.0	75.5	84.3	11 600 *	78.1	83.8	11 300 *				24.0
26.0	74.1	83.7	11 300 *	76.7	83.2	11 100 *	79.2	82.1	10 500 *	26.0
28.0	72.7	83.1	11 200 *	75.2	82.6	10 900 *	77.8	81.5	10 000 *	28.0
30.0	71.3	82.4	11 000 *	73.8	81.9	10 800 *	76.3	80.8	9 600 *	30.0
32.0	69.8	81.7	10 800 *	72.4	81.2	10 700 *	74.9	80.0	9 300 *	32.0
34.0	68.4	80.9	10 600 *	70.9	80.4	10 500 *	73.4	79.2	8 900 *	34.0
36.0	66.9	80.0	10 400 *	69.4	79.5	10 400 *	71.9	78.3	8 700 *	36.0
38.0	65.4	79.1	10 200 *	67.9	78.6	10 300 *	70.4	77.4	8 400 *	38.0
40.0	63.9	78.1	10 000 *	66.4	77.6	10 100 *	68.8	76.4	8 100 *	40.0
44.0	60.9	75.9	9 700 *	63.3	75.4	9 800 *	65.7	74.1	7 600 *	44.0
48.0	57.7	73.4	9 400 *	60.1	72.9	9 600 *	62.4	71.6	7 200 *	48.0
52.0	54.4	70.7	9 100 *	56.8	70.1	9 100 *	59.0	68.7	6 800 *	52.0
56.0	50.9	67.5	8 900 *	53.3	66.9	8 500 *	55.5	65.5	6 500 *	56.0
60.0	47.3	63.9	8 600	49.7	63.3	8 000 *	51.7	61.8	6 200 *	60.0
64.0	43.5	59.9	7 500	45.8	59.2	7 600 *	47.7	57.6	6 000 *	64.0
68.0	39.3	55.2	6 500	41.5	54.5	6 800	43.4	52.7	5 700 *	68.0
72.0	34.7	49.7	5 500	36.9	48.9	5 800				72.0
76.0	29.5	43.1	4 500 *	31.6	42.1	4 900				76.0
80.0	23.2	34.7	3 200 *							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
18.3	80.1	88.8	12 600 *							18.3
20.0	78.7	88.4	12 400 *							20.0
22.0	77.4	87.9	12 200 *	79.9	87.4	11 800*				22.0
24.0	76.0	87.4	12 000 *	78.5	86.9	11 700*				24.0
26.0	74.7	86.8	11 800 *	77.1	86.4	11 500*	79.6	85.2	10 600*	26.0
28.0	73.3	86.2	11 600 *	75.8	85.8	11 300*	78.2	84.6	10 100*	28.0
30.0	72.0	85.6	11 400 *	74.4	85.1	11 100*	76.8	83.9	9 800*	30.0
32.0	70.6	84.9	11 200 *	73.0	84.4	11 000*	75.4	83.2	9 400*	32.0
34.0	69.2	84.1	11 000 *	71.6	83.6	10 800*	74.0	82.4	9 100*	34.0
36.0	67.8	83.3	10 800 *	70.2	82.8	10 600*	72.6	81.6	8 800*	36.0
38.0	66.3	82.4	10 600 *	68.7	81.9	10 500*	71.1	80.7	8 500*	38.0
40.0	64.9	81.4	10 400 *	67.3	80.9	10 300*	69.6	79.7	8 200*	40.0
44.0	62.0	79.4	10 000 *	64.3	78.8	10 000*	66.6	77.6	7 800*	44.0
48.0	58.9	77.0	9 700 *	61.3	76.5	9 700*	63.5	75.2	7 300*	48.0
52.0	55.8	74.4	9 300 *	58.1	73.8	9 400*	60.3	72.5	7 000*	52.0
56.0	52.5	71.4	9 000 *	54.8	70.8	8 800*	57.0	69.4	6 600*	56.0
60.0	49.1	68.0	8 600	51.4	67.4	8 300*	53.4	65.9	6 300*	60.0
64.0	45.5	64.2	7 300	47.8	63.6	7 700	49.7	62.0	6 100*	64.0
68.0	41.7	59.9	6 300	43.9	59.2	6 500	45.7	57.5	5 900*	68.0
72.0	37.5	54.9	5 300	39.6	54.1	5 600				72.0
76.0	32.9	49.0	4 500	34.9	48.2	4 700				76.0
80.0	27.6	41.9	3 200 *							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
18.3	80.4	91.8	12 400 *							18.3
20.0	79.1	91.4	12 200 *							20.0
22.0	77.8	91.0	12 000 *	80.2	90.5	11 700*				22.0
24.0	76.5	90.5	11 800 *	78.9	90.0	11 600*				24.0
26.0	75.2	90.0	11 600 *	77.6	89.5	11 400*	80.0	88.3	10 600*	26.0
28.0	73.9	89.4	11 500 *	76.3	88.9	11 300*	78.7	87.7	10 300*	28.0
30.0	72.6	88.7	11 300 *	74.9	88.2	11 100*	77.3	87.1	9 900*	30.0
32.0	71.2	88.0	11 200 *	73.6	87.6	11 000*	75.9	86.4	9 500*	32.0
34.0	69.9	87.3	11 000 *	72.2	86.8	10 800*	74.6	85.6	9 200*	34.0
36.0	68.5	86.5	10 800 *	70.9	86.0	10 700*	73.2	84.8	8 900*	36.0
38.0	67.2	85.7	10 600 *	69.5	85.2	10 500*	71.8	83.9	8 600*	38.0
40.0	65.8	84.8	10 400 *	68.1	84.3	10 400*	70.4	83.0	8 300*	40.0
44.0	63.0	82.8	10 000 *	65.3	82.2	10 100*	67.5	81.0	7 900*	44.0
48.0	60.1	80.5	9 700 *	62.3	80.0	9 800*	64.5	78.7	7 500*	48.0
52.0	57.1	78.0	9 400 *	59.3	77.4	9 500*	61.5	76.1	7 100*	52.0
56.0	54.0	75.2	9 000 *	56.2	74.6	9 000*	58.3	73.2	6 700*	56.0
60.0	50.8	72.0	8 200	53.0	71.4	8 400	55.0	69.9	6 400*	60.0
64.0	47.4	68.4	7 000	49.6	67.8	7 300	51.5	66.2	6 200*	64.0
68.0	43.8	64.4	5 900	45.9	63.7	6 300	47.8	62.0	6 000*	68.0
72.0	40.0	59.8	5 000	42.0	59.1	5 300	43.8	57.3	5 500	72.0
76.0	35.8	54.5	4 200	37.8	53.7	4 400				76.0
80.0	31.1	48.2	3 100 *	33.0	47.3	3 500				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
18.3	80.7	94.9	12 300 *							18.3
20.0	79.5	94.5	12 100 *							20.0
22.0	78.2	94.1	11 900 *							22.0
24.0	77.0	93.6	11 700 *	79.3	93.1	11 500 *				24.0
26.0	75.7	93.1	11 600 *	78.0	92.6	11 300 *	80.3	91.4	10 600 *	26.0
28.0	74.4	92.5	11 400 *	76.7	92.0	11 200 *	79.0	90.8	10 400 *	28.0
30.0	73.2	91.9	11 200 *	75.4	91.4	11 000 *	77.7	90.2	10 000 *	30.0
32.0	71.9	91.2	11 100 *	74.1	90.7	10 900 *	76.4	89.5	9 700 *	32.0
34.0	70.6	90.5	10 900 *	72.8	90.0	10 800 *	75.1	88.8	9 300 *	34.0
36.0	69.3	89.8	10 800 *	71.5	89.2	10 600 *	73.8	88.0	9 000 *	36.0
38.0	67.9	88.9	10 600 *	70.2	88.4	10 500 *	72.4	87.2	8 800 *	38.0
40.0	66.6	88.1	10 400 *	68.9	87.6	10 400 *	71.1	86.3	8 500 *	40.0
44.0	63.9	86.1	10 100 *	66.1	85.6	10 100 *	68.3	84.4	8 000 *	44.0
48.0	61.1	84.0	9 700 *	63.3	83.5	9 800 *	65.5	82.2	7 600 *	48.0
52.0	58.3	81.6	9 400 *	60.5	81.0	9 600 *	62.5	79.7	7 200 *	52.0
56.0	55.3	78.9	9 100 *	57.5	78.3	9 200 *	59.5	76.9	6 900 *	56.0
60.0	52.3	75.9	7 900	54.4	75.3	8 400	56.4	73.8	6 600 *	60.0
64.0	49.1	72.5	6 800	51.2	71.9	7 100	53.1	70.3	6 300 *	64.0
68.0	45.7	68.7	5 700	47.8	68.0	6 000	49.6	66.4	6 100 *	68.0
72.0	42.1	64.4	4 700	44.2	63.7	5 000	45.9	62.0	5 300	72.0
76.0	38.3	59.6	3 900	40.3	58.8	4 200	41.9	56.9	4 400	76.0
80.0	34.1	53.9	3 100	36.0	53.1	3 300				80.0
84.0				31.1	46.2	2 300 *				84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
18.3	81.0	97.9	12 100 *							18.3
20.0	79.8	97.5	12 000 *							20.0
22.0	78.6	97.1	11 800 *							22.0
24.0	77.4	96.7	11 600 *	79.6	96.2	11 400*				24.0
26.0	76.2	96.2	11 400 *	78.4	95.7	11 200*	80.6	94.5	10 500*	26.0
28.0	74.9	95.6	11 300 *	77.1	95.1	11 100*	79.4	94.0	10 400*	28.0
30.0	73.7	95.0	11 100 *	75.9	94.5	10 900*	78.1	93.4	10 100*	30.0
32.0	72.4	94.4	11 000 *	74.7	93.9	10 800*	76.9	92.7	9 700*	32.0
34.0	71.2	93.7	10 800 *	73.4	93.2	10 700*	75.6	92.0	9 500*	34.0
36.0	69.9	93.0	10 700 *	72.1	92.5	10 600*	74.3	91.3	9 200*	36.0
38.0	68.7	92.2	10 500 *	70.8	91.7	10 400*	73.0	90.4	8 900*	38.0
40.0	67.4	91.3	10 300 *	69.6	90.8	10 300*	71.7	89.6	8 600*	40.0
44.0	64.8	89.5	10 000 *	66.9	89.0	10 100*	69.0	87.7	8 100*	44.0
48.0	62.1	87.4	9 700 *	64.3	86.9	9 800*	66.3	85.6	7 700*	48.0
52.0	59.4	85.1	9 400 *	61.5	84.6	9 600*	63.5	83.2	7 300*	52.0
56.0	56.6	82.5	9 100 *	58.7	82.0	9 400*	60.6	80.6	7 000*	56.0
60.0	53.6	79.7	8 000	55.7	79.1	8 400	57.7	77.6	6 700*	60.0
64.0	50.6	76.5	6 800	52.7	75.8	7 200	54.5	74.4	6 400*	64.0
68.0	47.4	72.9	5 700	49.5	72.2	6 100	51.3	70.7	6 200*	68.0
72.0	44.1	68.9	4 800	46.1	68.2	5 100	47.8	66.5	5 300	72.0
76.0	40.5	64.4	3 900	42.5	63.6	4 200	44.1	61.8	4 400	76.0
80.0	36.7	59.2	3 200	38.6	58.4	3 400				80.0
84.0	32.4	53.2	2 200 *	34.2	52.3	2 600*				84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
19.8	80.4	100.7	11 800 *							19.8
20.0	80.1	100.6	11 800 *							20.0
22.0	78.9	100.2	11 600 *							22.0
24.0	77.8	99.8	11 500 *	79.9	99.3	11 200*				24.0
26.0	76.6	99.3	11 300 *	78.7	98.8	11 100*				26.0
28.0	75.4	98.7	11 100 *	77.5	98.2	10 900*	79.7	97.1	10 400*	28.0
30.0	74.2	98.2	11 000 *	76.3	97.7	10 800*	78.5	96.5	10 200*	30.0
32.0	73.0	97.5	10 800 *	75.1	97.1	10 700*	77.3	95.9	9 900*	32.0
34.0	71.8	96.9	10 700 *	73.9	96.4	10 600*	76.1	95.2	9 500*	34.0
36.0	70.6	96.2	10 600 *	72.7	95.7	10 500*	74.8	94.4	9 200*	36.0
38.0	69.3	95.4	10 400 *	71.5	94.9	10 300*	73.6	93.7	9 000*	38.0
40.0	68.1	94.6	10 300 *	70.2	94.1	10 200*	72.3	92.8	8 700*	40.0
44.0	65.6	92.8	9 900 *	67.7	92.3	10 000*	69.7	91.0	8 200*	44.0
48.0	63.0	90.8	9 700 *	65.1	90.3	9 800*	67.1	89.0	7 800*	48.0
52.0	60.4	88.6	9 400 *	62.5	88.1	9 600*	64.4	86.7	7 500*	52.0
56.0	57.7	86.1	9 000	59.7	85.6	9 400*	61.7	84.2	7 100*	56.0
60.0	54.9	83.4	7 700	56.9	82.8	8 200	58.8	81.4	6 800*	60.0
64.0	52.0	80.3	6 500	54.0	79.7	6 900	55.9	78.3	6 500*	64.0
68.0	49.0	77.0	5 500	51.0	76.3	5 800	52.8	74.8	6 200	68.0
72.0	45.9	73.2	4 500	47.8	72.5	4 900	49.5	70.9	5 200	72.0
76.0	42.5	69.0	3 700	44.4	68.2	4 000	46.1	66.5	4 300	76.0
80.0	38.9	64.2	2 900	40.8	63.4	3 200	42.3	61.5	3 400	80.0
84.0	35.1	58.7	2 100 *	36.9	57.9	2 500				84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
19.8	80.7	103.7	11 600 *							19.8
20.0	80.4	103.6	11 600 *							20.0
22.0	79.3	103.3	11 400 *							22.0
24.0	78.1	102.8	11 300 *							24.0
26.0	77.0	102.4	11 100 *	79.1	101.9	10 900*				26.0
28.0	75.8	101.8	11 000 *	77.9	101.4	10 800*	80.0	100.2	10 400*	28.0
30.0	74.7	101.3	10 800 *	76.8	100.8	10 700*	78.9	99.6	10 300*	30.0
32.0	73.5	100.7	10 700 *	75.6	100.2	10 600*	77.7	99.0	10 000*	32.0
34.0	72.3	100.1	10 600 *	74.4	99.5	10 400*	76.5	98.3	9 700*	34.0
36.0	71.2	99.4	10 400 *	73.2	98.9	10 300*	75.3	97.6	9 400*	36.0
38.0	70.0	98.6	10 300 *	72.0	98.1	10 200*	74.1	96.9	9 100*	38.0
40.0	68.8	97.8	10 100 *	70.8	97.3	10 100*	72.9	96.1	8 800*	40.0
44.0	66.3	96.1	9 900 *	68.4	95.6	9 900*	70.4	94.3	8 400*	44.0
48.0	63.9	94.2	9 600 *	65.9	93.7	9 700*	67.9	92.4	7 900*	48.0
52.0	61.3	92.1	9 300 *	63.4	91.5	9 500*	65.3	90.2	7 600*	52.0
56.0	58.8	89.7	8 800	60.8	89.1	9 300	62.6	87.8	7 200*	56.0
60.0	56.1	87.1	7 400	58.1	86.5	7 900	59.9	85.1	6 900*	60.0
64.0	53.3	84.2	6 200	55.3	83.6	6 700	57.1	82.1	6 600*	64.0
68.0	50.5	80.9	5 100	52.4	80.3	5 500	54.1	78.8	5 900	68.0
72.0	47.5	77.4	4 200	49.4	76.7	4 600	51.1	75.1	4 900	72.0
76.0	44.3	73.4	3 300	46.2	72.7	3 700	47.8	71.0	4 000	76.0
80.0	41.0	68.9	2 600	42.8	68.2	2 900	44.4	66.4	3 100	80.0
84.0				39.2	63.1	2 200*				84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
12.2	79.5	53.3	10 600 *							12.2
14.0	77.1	52.9	10 300 *							14.0
16.0	74.8	52.3	10 000 *	79.7	52.0	9 900*				16.0
18.0	72.5	51.7	9 700 *	77.3	51.4	9 600*				18.0
20.0	70.2	51.0	9 400 *	75.0	50.7	9 300*	80.0	49.8	8 900*	20.0
22.0	67.8	50.2	9 100 *	72.6	49.8	9 000*	77.5	48.9	8 600*	22.0
24.0	65.4	49.3	8 900 *	70.1	48.9	8 700*	75.0	48.0	8 200*	24.0
26.0	62.9	48.2	8 600 *	67.6	47.9	8 500*	72.5	47.0	7 600*	26.0
28.0	60.4	47.1	8 300 *	65.1	46.8	8 200*	69.9	45.8	7 200*	28.0
30.0	57.8	45.9	8 100 *	62.5	45.5	8 000*	67.2	44.5	6 700*	30.0
32.0	55.1	44.5	7 800 *	59.8	44.1	7 700*	64.4	43.1	6 400*	32.0
34.0	52.3	43.0	7 600 *	57.0	42.6	7 500*	61.5	41.5	6 000*	34.0
36.0	49.4	41.3	7 300 *	54.0	40.9	7 300*	58.5	39.8	5 800*	36.0
38.0	46.4	39.4	7 100 *	51.0	39.0	7 000*	55.4	37.8	5 500*	38.0
40.0	43.2	37.3	6 900 *	47.7	36.9	6 600*	52.0	35.6	5 300*	40.0
44.0	36.1	32.3	6 500 *	40.5	31.8	6 000*	44.5	30.3	4 900*	44.0
48.0	27.5	25.6	6 200 *	31.7	24.9	5 500*				48.0
30.5m Boom										
12.2	80.1	56.4	10 600 *							12.2
14.0	77.8	55.9	10 300 *							14.0
16.0	75.7	55.4	10 100 *							16.0
18.0	73.5	54.9	9 800 *	78.1	54.5	9 600*				18.0
20.0	71.3	54.2	9 500 *	75.8	53.8	9 300*				20.0
22.0	69.1	53.4	9 200 *	73.6	53.1	9 100*	78.3	52.1	8 700*	22.0
24.0	66.8	52.6	9 000 *	71.3	52.2	8 800*	75.9	51.3	8 300*	24.0
26.0	64.5	51.6	8 700 *	69.0	51.3	8 600*	73.6	50.3	7 800*	26.0
28.0	62.1	50.6	8 500 *	66.6	50.2	8 300*	71.2	49.2	7 400*	28.0
30.0	59.7	49.4	8 200 *	64.2	49.0	8 100*	68.7	48.0	6 900*	30.0
32.0	57.3	48.2	8 000 *	61.7	47.8	7 800*	66.1	46.7	6 600*	32.0
34.0	54.7	46.8	7 700 *	59.1	46.3	7 700*	63.5	45.3	6 300*	34.0
36.0	52.1	45.2	7 500 *	56.5	44.8	7 400*	60.8	43.7	6 000*	36.0
38.0	49.3	43.5	7 300 *	53.7	43.1	7 200*	57.9	41.9	5 700*	38.0
40.0	46.5	41.6	7 100 *	50.8	41.2	7 000*	54.9	40.0	5 400*	40.0
44.0	40.3	37.3	6 700 *	44.5	36.8	6 300*	48.4	35.4	5 000*	44.0
48.0	33.1	31.7	6 400 *	37.3	31.1	5 800*	40.8	29.4	4 700*	48.0
52.0	24.1	24.1	6 100 *							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	80.6	59.4	10 600 *							12.2
14.0	78.5	59.0	10 300 *							14.0
16.0	76.4	58.5	10 100 *							16.0
18.0	74.4	58.0	9 800 *	78.7	57.6	9 600*				18.0
20.0	72.3	57.4	9 500 *	76.6	57.0	9 400*				20.0
22.0	70.2	56.6	9 300 *	74.5	56.3	9 100*	78.9	55.3	8 700*	22.0
24.0	68.1	55.8	9 000 *	72.4	55.5	8 900*	76.8	54.5	8 500*	24.0
26.0	65.9	55.0	8 800 *	70.2	54.6	8 600*	74.5	53.6	8 000*	26.0
28.0	63.7	54.0	8 600 *	68.0	53.6	8 400*	72.3	52.6	7 500*	28.0
30.0	61.5	52.9	8 300 *	65.7	52.5	8 200*	70.0	51.5	7 200*	30.0
32.0	59.2	51.7	8 100 *	63.4	51.3	8 000*	67.6	50.3	6 800*	32.0
34.0	56.8	50.4	7 800 *	61.0	50.0	7 800*	65.2	48.9	6 500*	34.0
36.0	54.4	49.0	7 600 *	58.6	48.6	7 600*	62.6	47.5	6 200*	36.0
38.0	51.9	47.4	7 400 *	56.0	47.0	7 400*	60.1	45.9	5 900*	38.0
40.0	49.3	45.8	7 200 *	53.4	45.3	7 200*	57.4	44.1	5 700*	40.0
44.0	43.7	41.8	6 800 *	47.8	41.3	6 700*	51.6	40.0	5 200*	44.0
48.0	37.5	37.0	6 500 *	41.5	36.4	6 100*	45.0	34.9	4 900*	48.0
52.0	30.3	30.8	6 200 *	34.1	30.2	5 600*				52.0
56.0	20.7	22.1	6 000 *							56.0
36.5m Boom										
13.7	79.6	62.2	10 400 *							13.7
14.0	79.1	62.1	10 400 *							14.0
16.0	77.1	61.6	10 100 *							16.0
18.0	75.2	61.1	10 000 *	79.3	60.8	9 700*				18.0
20.0	73.2	60.5	9 600 *	77.3	60.1	9 400*				20.0
22.0	71.2	59.8	9 300 *	75.3	59.5	9 200*	79.5	58.5	8 700*	22.0
24.0	69.2	59.1	9 200 *	73.3	58.7	8 900*	77.5	57.7	8 600*	24.0
26.0	67.2	58.2	8 900 *	71.2	57.9	8 700*	75.4	56.9	8 200*	26.0
28.0	65.1	57.3	8 600 *	69.2	56.9	8 500*	73.2	55.9	7 800*	28.0
30.0	63.0	56.3	8 400 *	67.0	55.9	8 300*	71.1	54.9	7 300*	30.0
32.0	60.9	55.2	8 200 *	64.9	54.8	8 100*	68.9	53.7	7 000*	32.0
34.0	58.7	54.0	8 000 *	62.6	53.6	7 900*	66.6	52.5	6 600*	34.0
36.0	56.4	52.7	7 800 *	60.4	52.3	7 700*	64.3	51.1	6 300*	36.0
38.0	54.1	51.3	7 500 *	58.0	50.8	7 500*	61.9	49.6	6 100*	38.0
40.0	51.7	49.7	7 300 *	55.6	49.2	7 300*	59.4	48.0	5 800*	40.0
44.0	46.7	46.1	7 000 *	50.5	45.6	7 000*	54.2	44.3	5 400*	44.0
48.0	41.1	41.8	6 600 *	44.9	41.3	6 400*	48.4	39.8	5 000*	48.0
52.0	34.9	36.6	6 300 *	38.6	35.9	5 900*	41.8	34.2	4 700*	52.0
56.0	27.4	29.7	6 100 *	31.0	28.9	5 500*				56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
13.7	80.1	65.3	10 400 *							13.7
14.0	79.6	65.2	10 400 *							14.0
16.0	77.7	64.7	10 200 *							16.0
18.0	75.9	64.2	9 900 *							18.0
20.0	74.0	63.7	9 800 *	77.9	63.3	9 500*				20.0
22.0	72.1	63.0	9 400 *	76.0	62.6	9 200*	80.1	61.6	8 700*	22.0
24.0	70.2	62.3	9 200 *	74.1	61.9	9 000*	78.1	60.9	8 600*	24.0
26.0	68.3	61.5	8 900 *	72.2	61.1	8 700*	76.1	60.1	8 400*	26.0
28.0	66.4	60.6	8 700 *	70.2	60.2	8 600*	74.1	59.2	7 900*	28.0
30.0	64.4	59.7	8 500 *	68.2	59.3	8 400*	72.1	58.2	7 500*	30.0
32.0	62.4	58.6	8 300 *	66.2	58.2	8 200*	70.0	57.1	7 200*	32.0
34.0	60.3	57.5	8 100 *	64.1	57.1	8 000*	67.9	56.0	6 800*	34.0
36.0	58.2	56.3	7 800 *	62.0	55.9	7 800*	65.7	54.7	6 500*	36.0
38.0	56.0	54.9	7 600 *	59.8	54.5	7 600*	63.5	53.3	6 300*	38.0
40.0	53.8	53.5	7 400 *	57.6	53.0	7 400*	61.2	51.8	6 000*	40.0
44.0	49.2	50.2	7 100 *	52.9	49.7	7 100*	56.4	48.4	5 600*	44.0
48.0	44.2	46.3	6 700 *	47.8	45.8	6 700*	51.2	44.4	5 200*	48.0
52.0	38.7	41.7	6 500 *	42.2	41.1	6 100*	45.4	39.5	4 900*	52.0
56.0	32.3	35.9	6 200 *	35.8	35.2	5 700*				56.0
60.0	24.6	28.2	6 000 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.5m Boom										
13.7	80.5	68.3	10 400 *							13.7
14.0	80.1	68.2	10 400 *							14.0
16.0	78.3	67.8	10 200 *							16.0
18.0	76.5	67.3	9 900 *							18.0
20.0	74.8	66.8	9 700 *	78.5	66.4	9 500 *				20.0
22.0	73.0	66.2	9 400 *	76.7	65.8	9 200 *				22.0
24.0	71.2	65.5	9 200 *	74.9	65.1	9 000 *	78.7	64.1	8 600 *	24.0
26.0	69.3	64.7	9 000 *	73.0	64.3	8 800 *	76.8	63.3	8 400 *	26.0
28.0	67.5	63.9	8 800 *	71.2	63.5	8 600 *	74.9	62.4	8 100 *	28.0
30.0	65.6	63.0	8 600 *	69.3	62.6	8 400 *	73.0	61.5	7 700 *	30.0
32.0	63.7	62.0	8 300 *	67.4	61.6	8 300 *	71.0	60.5	7 300 *	32.0
34.0	61.8	61.0	8 200 *	65.4	60.6	8 100 *	69.0	59.4	7 000 *	34.0
36.0	59.8	59.8	8 000 *	63.4	59.4	7 800 *	67.0	58.2	6 700 *	36.0
38.0	57.8	58.6	7 800 *	61.4	58.1	7 700 *	64.9	56.9	6 400 *	38.0
40.0	55.7	57.2	7 600 *	59.3	56.8	7 500 *	62.8	55.5	6 200 *	40.0
44.0	51.4	54.2	7 200 *	54.9	53.7	7 200 *	58.3	52.4	5 700 *	44.0
48.0	46.8	50.6	6 900 *	50.3	50.1	6 900 *	53.6	48.7	5 400 *	48.0
52.0	41.8	46.4	6 600 *	45.3	45.8	6 400 *	48.4	44.3	5 000 *	52.0
56.0	36.3	41.3	6 300 *	39.7	40.7	6 000 *	42.5	38.9	4 800 *	56.0
60.0	29.9	35.0	6 100 *	33.1	34.2	5 600 *				60.0
64.0	21.8	26.4	5 900 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	81.0	71.4	10 300 *							13.7
14.0	80.5	71.3	10 300 *							14.0
16.0	78.8	70.9	10 100 *							16.0
18.0	77.1	70.4	9 900 *							18.0
20.0	75.4	69.9	9 700 *	79.0	69.5	9 500 *				20.0
22.0	73.7	69.3	9 500 *	77.3	68.9	9 200 *				22.0
24.0	72.0	68.7	9 300 *	75.6	68.3	9 000 *	79.2	67.2	8 600 *	24.0
26.0	70.3	68.0	9 100 *	73.8	67.6	8 800 *	77.4	66.5	8 400 *	26.0
28.0	68.5	67.2	8 800 *	72.0	66.8	8 700 *	75.6	65.7	8 200 *	28.0
30.0	66.7	66.3	8 600 *	70.2	65.9	8 500 *	73.8	64.8	7 800 *	30.0
32.0	64.9	65.4	8 400 *	68.4	65.0	8 300 *	71.9	63.8	7 500 *	32.0
34.0	63.1	64.4	8 200 *	66.6	64.0	8 100 *	70.1	62.8	7 200 *	34.0
36.0	61.2	63.3	8 000 *	64.7	62.9	7 900 *	68.1	61.7	6 900 *	36.0
38.0	59.3	62.1	7 900 *	62.8	61.7	7 800 *	66.2	60.5	6 600 *	38.0
40.0	57.4	60.8	7 700 *	60.8	60.4	7 600 *	64.2	59.2	6 300 *	40.0
44.0	53.3	58.0	7 300 *	56.8	57.5	7 300 *	60.0	56.2	5 900 *	44.0
48.0	49.1	54.7	7 000 *	52.5	54.2	7 000 *	55.6	52.8	5 500 *	48.0
52.0	44.5	50.8	6 700 *	47.9	50.3	6 600 *	50.9	48.8	5 200 *	52.0
56.0	39.6	46.3	6 400 *	42.8	45.7	6 200 *	45.7	44.0	4 900 *	56.0
60.0	34.0	40.8	6 200 *	37.2	40.1	5 800 *				60.0
64.0	27.4	33.8	6 000 *	30.4	33.0	5 400 *				64.0
68.0	18.8	24.1	5 800 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
15.2	80.1	74.1	10 200 *							15.2
16.0	79.3	73.9	10 100 *							16.0
18.0	77.7	73.5	10 000 *							18.0
20.0	76.1	73.0	9 700 *	79.5	72.6	9 500*				20.0
22.0	74.4	72.4	9 500 *	77.8	72.0	9 300*				22.0
24.0	72.8	71.8	9 300 *	76.2	71.4	9 100*	79.7	70.3	8 600*	24.0
26.0	71.1	71.2	9 100 *	74.5	70.7	8 900*	78.0	69.6	8 500*	26.0
28.0	69.4	70.4	8 900 *	72.8	70.0	8 600*	76.3	68.9	8 300*	28.0
30.0	67.7	69.6	8 700 *	71.1	69.2	8 500*	74.5	68.0	8 000*	30.0
32.0	66.0	68.7	8 500 *	69.4	68.3	8 300*	72.8	67.1	7 700*	32.0
34.0	64.3	67.7	8 300 *	67.6	67.3	8 200*	71.0	66.2	7 300*	34.0
36.0	62.5	66.7	8 100 *	65.9	66.3	8 000*	69.2	65.1	7 000*	36.0
38.0	60.7	65.6	7 900 *	64.0	65.2	7 900*	67.3	64.0	6 700*	38.0
40.0	58.9	64.4	7 700 *	62.2	63.9	7 700*	65.4	62.7	6 500*	40.0
44.0	55.1	61.7	7 400 *	58.4	61.3	7 400*	61.5	60.0	6 000*	44.0
48.0	51.1	58.6	7 100 *	54.4	58.1	7 100*	57.5	56.8	5 600*	48.0
52.0	46.9	55.1	6 800 *	50.1	54.5	6 800*	53.1	53.1	5 300*	52.0
56.0	42.4	50.9	6 500 *	45.5	50.3	6 400*	48.4	48.8	5 000*	56.0
60.0	37.4	46.0	6 300 *	40.5	45.4	6 000*	43.1	43.6	4 800*	60.0
64.0	31.7	40.0	6 100 *	34.7	39.3	5 700*				64.0
68.0	25.0	32.4	5 900 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	80.5	77.2	10 200 *							15.2
16.0	79.7	77.0	10 100 *							16.0
18.0	78.2	76.6	10 000 *							18.0
20.0	76.6	76.1	9 700 *	79.9	75.7	9 400*				20.0
22.0	75.1	75.6	9 500 *	78.3	75.2	9 200*				22.0
24.0	73.5	75.0	9 300 *	76.8	74.6	9 100*				24.0
26.0	71.9	74.3	9 100 *	75.2	73.9	8 900*	78.5	72.8	8 400*	26.0
28.0	70.3	73.6	8 900 *	73.5	73.2	8 700*	76.9	72.1	8 300*	28.0
30.0	68.7	72.8	8 700 *	71.9	72.4	8 500*	75.2	71.3	8 100*	30.0
32.0	67.0	72.0	8 500 *	70.3	71.6	8 300*	73.5	70.4	7 800*	32.0
34.0	65.4	71.1	8 300 *	68.6	70.6	8 200*	71.8	69.5	7 400*	34.0
36.0	63.7	70.1	8 100 *	66.9	69.7	8 000*	70.1	68.5	7 200*	36.0
38.0	62.0	69.0	7 900 *	65.2	68.6	7 900*	68.3	67.4	6 900*	38.0
40.0	60.2	67.9	7 800 *	63.4	67.4	7 700*	66.6	66.2	6 600*	40.0
44.0	56.7	65.4	7 500 *	59.8	64.9	7 400*	62.9	63.6	6 200*	44.0
48.0	52.9	62.5	7 100 *	56.1	62.0	7 200*	59.1	60.6	5 800*	48.0
52.0	49.0	59.2	6 800 *	52.1	58.6	6 900*	55.0	57.2	5 500*	52.0
56.0	44.8	55.3	6 600 *	47.9	54.8	6 700*	50.7	53.2	5 200*	56.0
60.0	40.3	50.9	6 300 *	43.3	50.2	6 200*	45.9	48.6	4 900*	60.0
64.0	35.3	45.6	6 100 *	38.2	44.9	5 800*	40.6	43.0	4 700*	64.0
68.0	29.6	39.1	6 000 *	32.4	38.3	5 500*				68.0
72.0	22.5	30.7	5 800 *							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.9	80.2	10 100 *							15.2
16.0	80.1	80.0	10 100 *							16.0
18.0	78.6	79.6	9 900 *							18.0
20.0	77.1	79.2	9 700 *	80.3	78.8	9 400 *				20.0
22.0	75.6	78.7	9 500 *	78.8	78.3	9 200 *				22.0
24.0	74.1	78.1	9 300 *	77.3	77.7	9 100 *				24.0
26.0	72.6	77.5	9 100 *	75.7	77.1	8 900 *	79.0	75.9	8 400 *	26.0
28.0	71.1	76.8	8 900 *	74.2	76.4	8 700 *	77.4	75.2	8 300 *	28.0
30.0	69.5	76.1	8 700 *	72.6	75.6	8 500 *	75.8	74.5	8 200 *	30.0
32.0	68.0	75.3	8 500 *	71.1	74.8	8 400 *	74.2	73.7	7 900 *	32.0
34.0	66.4	74.4	8 300 *	69.5	73.9	8 200 *	72.6	72.8	7 600 *	34.0
36.0	64.8	73.5	8 200 *	67.9	73.0	8 100 *	70.9	71.8	7 300 *	36.0
38.0	63.1	72.4	8 000 *	66.2	72.0	7 900 *	69.3	70.8	7 000 *	38.0
40.0	61.5	71.4	7 900 *	64.6	70.9	7 800 *	67.6	69.7	6 800 *	40.0
44.0	58.1	69.0	7 500 *	61.2	68.5	7 500 *	64.1	67.2	6 300 *	44.0
48.0	54.6	66.2	7 200 *	57.6	65.7	7 300 *	60.5	64.4	5 900 *	48.0
52.0	50.9	63.1	6 900 *	53.9	62.6	7 000 *	56.7	61.2	5 600 *	52.0
56.0	47.0	59.6	6 700 *	50.0	59.0	6 800 *	52.7	57.5	5 300 *	56.0
60.0	42.8	55.5	6 400 *	45.8	54.9	6 500 *	48.3	53.2	5 000 *	60.0
64.0	38.3	50.7	6 200 *	41.2	50.0	6 100 *	43.6	48.2	4 800 *	64.0
68.0	33.3	45.0	6 000 *	36.0	44.2	5 700 *				68.0
72.0	27.4	38.0	5 900 *	30.0	37.1	5 400 *				72.0
76.0	20.0	28.5	4 700 *							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
16.8	80.1	83.0	10 000 *							16.8
18.0	79.0	82.7	9 900 *							18.0
20.0	77.6	82.3	9 700 *	80.7	81.9	9 400*				20.0
22.0	76.2	81.8	9 500 *	79.2	81.4	9 200*				22.0
24.0	74.7	81.2	9 300 *	77.8	80.8	9 000*				24.0
26.0	73.3	80.6	9 100 *	76.3	80.2	8 800*	79.4	79.1	8 400*	26.0
28.0	71.8	80.0	8 900 *	74.8	79.6	8 700*	77.9	78.4	8 300*	28.0
30.0	70.3	79.3	8 700 *	73.3	78.8	8 500*	76.4	77.7	8 200*	30.0
32.0	68.8	78.5	8 600 *	71.8	78.1	8 400*	74.8	76.9	8 100*	32.0
34.0	67.3	77.7	8 400 *	70.3	77.2	8 200*	73.3	76.0	7 700*	34.0
36.0	65.8	76.8	8 200 *	68.7	76.3	8 100*	71.7	75.1	7 400*	36.0
38.0	64.2	75.8	8 000 *	67.2	75.4	7 900*	70.1	74.1	7 200*	38.0
40.0	62.6	74.8	7 900 *	65.6	74.3	7 800*	68.5	73.1	6 900*	40.0
44.0	59.4	72.5	7 600 *	62.4	72.0	7 600*	65.2	70.8	6 500*	44.0
48.0	56.1	69.9	7 300 *	59.0	69.4	7 300*	61.8	68.1	6 000*	48.0
52.0	52.6	67.0	7 000 *	55.5	66.5	7 100*	58.2	65.1	5 700*	52.0
56.0	49.0	63.6	6 700 *	51.8	63.1	6 800*	54.5	61.6	5 400*	56.0
60.0	45.1	59.8	6 500 *	47.9	59.2	6 600*	50.5	57.7	5 100*	60.0
64.0	40.9	55.4	6 300 *	43.7	54.8	6 300*	46.1	53.1	4 900*	64.0
68.0	36.4	50.3	6 100 *	39.1	49.6	5 900*	41.3	47.7	4 700*	68.0
72.0	31.3	44.2	5 900 *	33.9	43.4	5 600*				72.0
76.0	25.2	36.6	4 900 *	27.7	35.6	5 200*				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.5	86.1	9 900 *							16.8
18.0	79.4	85.8	9 900 *							18.0
20.0	78.1	85.3	9 700 *							20.0
22.0	76.7	84.9	9 600 *	79.6	84.4	9 200 *				22.0
24.0	75.3	84.4	9 300 *	78.2	83.9	9 000 *				24.0
26.0	73.9	83.8	9 100 *	76.8	83.3	8 800 *	79.8	82.2	8 400 *	26.0
28.0	72.5	83.1	9 000 *	75.4	82.7	8 700 *	78.3	81.6	8 300 *	28.0
30.0	71.0	82.5	8 800 *	73.9	82.0	8 500 *	76.9	80.9	8 200 *	30.0
32.0	69.6	81.7	8 600 *	72.5	81.3	8 400 *	75.4	80.1	8 100 *	32.0
34.0	68.1	80.9	8 400 *	71.0	80.5	8 300 *	73.9	79.3	7 900 *	34.0
36.0	66.7	80.1	8 300 *	69.6	79.6	8 100 *	72.4	78.4	7 600 *	36.0
38.0	65.2	79.1	8 100 *	68.1	78.7	8 000 *	70.9	77.5	7 300 *	38.0
40.0	63.7	78.2	7 900 *	66.5	77.7	7 900 *	69.4	76.5	7 000 *	40.0
44.0	60.6	76.0	7 600 *	63.5	75.5	7 600 *	66.2	74.2	6 600 *	44.0
48.0	57.4	73.5	7 300 *	60.3	73.0	7 300 *	63.0	71.7	6 200 *	48.0
52.0	54.2	70.7	7 100 *	56.9	70.2	7 100 *	59.6	68.9	5 800 *	52.0
56.0	50.7	67.6	6 800 *	53.5	67.1	6 900 *	56.1	65.6	5 500 *	56.0
60.0	47.1	64.0	6 600 *	49.8	63.5	6 700 *	52.3	61.9	5 300 *	60.0
64.0	43.2	60.0	6 300 *	45.9	59.4	6 500 *	48.3	57.7	5 000 *	64.0
68.0	39.1	55.3	6 200 *	41.7	54.6	6 100 *	44.0	52.8	4 800 *	68.0
72.0	34.5	49.8	5 900	37.1	49.1	5 800 *				72.0
76.0	29.3	43.2	4 900	31.8	42.4	5 300				76.0
80.0	23.1	34.9	3 600 *							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.8	89.1	9 900 *							16.8
18.0	79.8	88.8	9 800 *							18.0
20.0	78.5	88.4	9 700 *							20.0
22.0	77.1	88.0	9 500 *	80.0	87.5	9 100*				22.0
24.0	75.8	87.5	9 300 *	78.6	87.0	9 000*				24.0
26.0	74.4	86.9	9 100 *	77.3	86.5	8 800*	80.2	85.3	8 300*	26.0
28.0	73.1	86.3	9 000 *	75.9	85.9	8 700*	78.8	84.7	8 300*	28.0
30.0	71.7	85.6	8 800 *	74.5	85.2	8 500*	77.4	84.0	8 100*	30.0
32.0	70.3	84.9	8 600 *	73.1	84.5	8 400*	76.0	83.3	8 000*	32.0
34.0	68.9	84.2	8 400 *	71.7	83.7	8 200*	74.5	82.5	7 900*	34.0
36.0	67.5	83.3	8 300 *	70.3	82.9	8 100*	73.1	81.7	7 700*	36.0
38.0	66.1	82.5	8 100 *	68.9	82.0	8 000*	71.6	80.8	7 400*	38.0
40.0	64.6	81.5	7 900 *	67.4	81.0	7 900*	70.2	79.8	7 200*	40.0
44.0	61.7	79.4	7 600 *	64.5	79.0	7 600*	67.2	77.7	6 700*	44.0
48.0	58.7	77.1	7 300 *	61.4	76.6	7 400*	64.1	75.3	6 300*	48.0
52.0	55.6	74.4	7 100 *	58.3	73.9	7 200*	60.9	72.6	6 000*	52.0
56.0	52.3	71.5	6 900 *	55.0	70.9	7 000*	57.5	69.5	5 600*	56.0
60.0	48.9	68.1	6 600 *	51.6	67.5	6 700*	54.0	66.0	5 400*	60.0
64.0	45.3	64.3	6 400 *	47.9	63.7	6 600*	50.3	62.1	5 100*	64.0
68.0	41.5	60.0	6 200 *	44.1	59.3	6 300*	46.3	57.6	4 900*	68.0
72.0	37.3	55.0	5 700	39.8	54.3	5 900	41.9	52.4	4 700*	72.0
76.0	32.7	49.2	4 800	35.2	48.4	5 100				76.0
80.0	27.4	42.1	3 700 *	29.7	41.1	4 100*				80.0
84.0	20.8	32.9	2 400 *							84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
18.3	80.1	91.9	9 700 *							18.3
20.0	78.9	91.5	9 600 *							20.0
22.0	77.6	91.0	9 500 *	80.3	90.6	9 400*				22.0
24.0	76.3	90.6	9 300 *	79.0	90.1	9 200*				24.0
26.0	75.0	90.0	9 100 *	77.7	89.6	9 100*	80.5	88.4	8 600*	26.0
28.0	73.7	89.4	9 000 *	76.4	89.0	8 900*	79.2	87.8	8 400*	28.0
30.0	72.3	88.8	8 800 *	75.1	88.4	8 700*	77.8	87.2	8 300*	30.0
32.0	71.0	88.1	8 700 *	73.7	87.7	8 600*	76.5	86.5	8 200*	32.0
34.0	69.7	87.4	8 500 *	72.4	86.9	8 400*	75.1	85.7	8 100*	34.0
36.0	68.3	86.6	8 300 *	71.0	86.1	8 300*	73.7	84.9	7 800*	36.0
38.0	66.9	85.7	8 100 *	69.6	85.3	8 100*	72.3	84.0	7 500*	38.0
40.0	65.5	84.8	8 000 *	68.2	84.4	8 000*	70.9	83.1	7 300*	40.0
44.0	62.7	82.8	7 700 *	65.4	82.4	7 700*	68.0	81.1	6 800*	44.0
48.0	59.8	80.6	7 400 *	62.5	80.1	7 500*	65.1	78.8	6 400*	48.0
52.0	56.9	78.1	7 200 *	59.5	77.6	7 200*	62.0	76.2	6 100*	52.0
56.0	53.8	75.2	6 900 *	56.4	74.7	7 000*	58.8	73.3	5 800*	56.0
60.0	50.6	72.1	6 700 *	53.1	71.5	6 800*	55.5	70.0	5 500*	60.0
64.0	47.2	68.5	6 500 *	49.7	67.9	6 600*	52.0	66.3	5 300*	64.0
68.0	43.6	64.5	6 200	46.1	63.9	6 400*	48.3	62.2	5 000*	68.0
72.0	39.8	59.9	5 400	42.2	59.2	5 700	44.3	57.4	4 800*	72.0
76.0	35.6	54.6	4 600	38.0	53.9	4 800	39.9	51.8	4 700*	76.0
80.0	30.9	48.4	3 600 *	33.2	47.5	4 000				80.0
84.0	25.4	40.7	2 500 *							84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
18.3	80.5	94.9	9 700 *							18.3
20.0	79.2	94.5	9 600 *							20.0
22.0	78.0	94.1	9 500 *							22.0
24.0	76.7	93.7	9 300 *	79.4	93.2	9 200*				24.0
26.0	75.5	93.1	9 100 *	78.1	92.7	9 100*				26.0
28.0	74.2	92.6	9 000 *	76.8	92.1	8 900*	79.5	90.9	8 400*	28.0
30.0	72.9	92.0	8 800 *	75.6	91.5	8 700*	78.2	90.3	8 300*	30.0
32.0	71.6	91.3	8 700 *	74.3	90.8	8 600*	76.9	89.6	8 200*	32.0
34.0	70.3	90.6	8 500 *	73.0	90.1	8 400*	75.6	88.9	8 100*	34.0
36.0	69.0	89.8	8 300 *	71.6	89.4	8 300*	74.3	88.1	7 900*	36.0
38.0	67.7	89.0	8 200 *	70.3	88.5	8 200*	72.9	87.3	7 700*	38.0
40.0	66.4	88.1	8 000 *	69.0	87.7	8 000*	71.6	86.4	7 400*	40.0
44.0	63.7	86.2	7 700 *	66.3	85.7	7 800*	68.8	84.5	7 000*	44.0
48.0	60.9	84.1	7 400 *	63.5	83.6	7 500*	66.0	82.3	6 600*	48.0
52.0	58.1	81.7	7 200 *	60.6	81.2	7 200*	63.0	79.8	6 200*	52.0
56.0	55.1	79.0	7 000 *	57.6	78.4	7 000*	60.0	77.0	5 900*	56.0
60.0	52.1	76.0	6 700 *	54.6	75.4	6 900*	56.9	73.9	5 600*	60.0
64.0	48.9	72.6	6 500 *	51.3	72.0	6 700*	53.6	70.5	5 300*	64.0
68.0	45.5	68.8	6 100	48.0	68.2	6 400	50.1	66.6	5 100*	68.0
72.0	41.9	64.5	5 100	44.3	63.9	5 400	46.4	62.1	4 900*	72.0
76.0	38.1	59.7	4 300	40.5	59.0	4 600	42.4	57.0	4 800*	76.0
80.0	33.9	54.0	3 500	36.2	53.3	3 800				80.0
84.0	29.1	47.4	2 300 *	31.4	46.5	2 800*				84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
18.3	80.8	98.0	9 600 *							18.3
20.0	79.6	97.6	9 600 *							20.0
22.0	78.4	97.2	9 400 *							22.0
24.0	77.1	96.7	9 300 *	79.7	96.3	9 200 *				24.0
26.0	75.9	96.2	9 200 *	78.5	95.8	9 000 *				26.0
28.0	74.7	95.7	9 000 *	77.3	95.2	8 900 *	79.9	94.0	8 400 *	28.0
30.0	73.5	95.1	8 800 *	76.0	94.6	8 700 *	78.6	93.4	8 300 *	30.0
32.0	72.2	94.5	8 700 *	74.8	94.0	8 600 *	77.3	92.8	8 200 *	32.0
34.0	71.0	93.8	8 500 *	73.5	93.3	8 400 *	76.1	92.1	8 100 *	34.0
36.0	69.7	93.0	8 300 *	72.2	92.6	8 300 *	74.8	91.3	8 000 *	36.0
38.0	68.4	92.3	8 200 *	71.0	91.8	8 200 *	73.5	90.5	7 800 *	38.0
40.0	67.2	91.4	8 000 *	69.7	90.9	8 000 *	72.2	89.7	7 500 *	40.0
44.0	64.6	89.6	7 800 *	67.1	89.1	7 800 *	69.5	87.8	7 000 *	44.0
48.0	61.9	87.5	7 500 *	64.4	87.0	7 500 *	66.8	85.7	6 700 *	48.0
52.0	59.2	85.2	7 200 *	61.6	84.7	7 300 *	64.0	83.3	6 300 *	52.0
56.0	56.3	82.6	7 000 *	58.8	82.1	7 100 *	61.1	80.7	6 000 *	56.0
60.0	53.4	79.7	6 800 *	55.9	79.2	6 900 *	58.1	77.7	5 700 *	60.0
64.0	50.4	76.5	6 600 *	52.8	76.0	6 700 *	55.0	74.5	5 400 *	64.0
68.0	47.2	73.0	5 800	49.6	72.4	6 200	51.8	70.8	5 200 *	68.0
72.0	43.9	69.0	4 800	46.2	68.3	5 200	48.3	66.6	5 000 *	72.0
76.0	40.3	64.5	4 000	42.6	63.8	4 300	44.6	62.0	4 600	76.0
80.0	36.5	59.3	3 300	38.7	58.6	3 500	40.6	56.6	3 800	80.0
84.0	32.2	53.3	2 300 *	34.4	52.5	2 800 *				84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
19.8	80.2	100.7	9 500 *							19.8
20.0	79.9	100.7	9 500 *							20.0
22.0	78.7	100.3	9 300 *							22.0
24.0	77.5	99.8	9 200 *	80.0	99.4	9 100*				24.0
26.0	76.4	99.3	9 100 *	78.8	98.9	9 000*				26.0
28.0	75.2	98.8	8 900 *	77.7	98.4	8 800*	80.2	97.1	8 400*	28.0
30.0	74.0	98.2	8 800 *	76.5	97.8	8 700*	79.0	96.6	8 300*	30.0
32.0	72.8	97.6	8 600 *	75.2	97.2	8 600*	77.8	95.9	8 200*	32.0
34.0	71.6	97.0	8 500 *	74.0	96.5	8 400*	76.5	95.3	8 100*	34.0
36.0	70.3	96.2	8 400 *	72.8	95.8	8 300*	75.3	94.5	8 000*	36.0
38.0	69.1	95.5	8 200 *	71.6	95.0	8 200*	74.0	93.8	7 800*	38.0
40.0	67.9	94.7	8 000 *	70.3	94.2	8 000*	72.8	92.9	7 600*	40.0
44.0	65.4	92.9	7 800 *	67.8	92.4	7 800*	70.2	91.1	7 200*	44.0
48.0	62.8	90.9	7 500 *	65.2	90.4	7 500*	67.6	89.1	6 800*	48.0
52.0	60.2	88.7	7 300 *	62.6	88.2	7 300*	64.9	86.8	6 400*	52.0
56.0	57.5	86.2	7 000 *	59.9	85.7	7 100*	62.2	84.3	6 100*	56.0
60.0	54.7	83.5	6 800 *	57.1	82.9	6 900*	59.3	81.5	5 800*	60.0
64.0	51.8	80.4	6 600 *	54.2	79.9	6 800*	56.3	78.4	5 500*	64.0
68.0	48.8	77.0	5 800	51.1	76.5	6 300	53.3	74.9	5 300*	68.0
72.0	45.7	73.3	4 900	48.0	72.7	5 200	50.0	71.0	5 100*	72.0
76.0	42.3	69.1	4 000	44.6	68.4	4 300	46.5	66.6	4 700	76.0
80.0	38.8	64.3	3 300	41.0	63.6	3 600	42.8	61.7	3 800	80.0
84.0	34.9	58.8	2 500 *	37.1	58.1	2 800				84.0
88.0				32.7	51.6	1 900*				88.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
107 680 kg Crane Counterweight
52 160 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 84.5m Boom

15000 SERIES 4

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
19.8	80.4	103.8	9 400 *							19.8
20.0	80.2	103.7	9 400 *							20.0
22.0	79.0	103.3	9 300 *							22.0
24.0	77.9	102.9	9 200 *							24.0
26.0	76.8	102.4	9 100 *	79.2	102.0	8 900*				26.0
28.0	75.6	101.9	8 900 *	78.0	101.5	8 800*	80.5	100.2	8 300*	28.0
30.0	74.5	101.4	8 800 *	76.9	100.9	8 600*	79.3	99.7	8 200*	30.0
32.0	73.3	100.8	8 600 *	75.7	100.3	8 500*	78.1	99.1	8 200*	32.0
34.0	72.1	100.1	8 500 *	74.5	99.7	8 400*	76.9	98.4	8 100*	34.0
36.0	70.9	99.4	8 300 *	73.3	99.0	8 300*	75.7	97.7	8 000*	36.0
38.0	69.8	98.7	8 200 *	72.1	98.2	8 200*	74.5	97.0	7 800*	38.0
40.0	68.6	97.9	8 000 *	70.9	97.4	8 000*	73.3	96.2	7 800*	40.0
44.0	66.1	96.2	7 800 *	68.5	95.7	7 800*	70.8	94.4	7 300*	44.0
48.0	63.7	94.3	7 500 *	66.0	93.8	7 600*	68.3	92.5	6 900*	48.0
52.0	61.1	92.2	7 300 *	63.5	91.6	7 300*	65.7	90.3	6 500*	52.0
56.0	58.6	89.8	7 100 *	60.9	89.3	7 100*	63.1	87.9	6 200*	56.0
60.0	55.9	87.2	6 800 *	58.2	86.6	7 000*	60.4	85.2	5 900*	60.0
64.0	53.1	84.2	6 600	55.4	83.7	6 800*	57.6	82.2	5 700*	64.0
68.0	50.3	81.0	5 500	52.5	80.4	6 000	54.6	78.9	5 400*	68.0
72.0	47.3	77.5	4 600	49.5	76.8	5 000	51.5	75.2	5 200	72.0
76.0	44.2	73.5	3 800	46.4	72.8	4 100	48.3	71.1	4 400	76.0
80.0	40.8	69.0	3 000	43.0	68.4	3 300	44.8	66.5	3 600	80.0
84.0	37.2	64.0	2 300	39.4	63.3	2 600	41.1	61.3	2 900	84.0
88.0				35.4	57.4	1 900				88.0