



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating**

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

LIFTING CAPACITIES: Chart supplements boom capacity chart **No. 8605-AM**. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and are calculated to comply with EN 13000, ISO 4305 and include factors based on a 4.0 degree tipping angle. Capacities based on structural competence are denoted by an asterisk (*).

75.5m thru 81.5m boom lengths require only the middle two sheaves in lower boom point. All other sheaves must be removed from lower boom point.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves, is considered part of jib load. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging **No. A07850**, jib assembly **No. A10098** and Wire Rope Specification chart **No. 8608-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to Operator's Manual for operating guidelines.

WIND CONDITIONS: Machine may be operated in winds stated in maximum wind speed table provided crane operator judgment is used to allow for wind effect on lifted load and other considerations noted on capacity chart are followed. Wind will have a considerable effect on load. Loads must be compensated for accordingly by reducing load ratings, reducing operating speeds, or by a combination of both. Recommend stopping operation and lowering boom and jib to no higher than 70 degree boom angle when wind exceeds conditions stated. Lower boom and jib to ground when wind is above 22 m/s.

MACHINE TRAVEL: Machine to travel on a firm, level [up to 1 percent (0.5 degrees) grade] and uniformly supporting surface. *Travel with 100 percent of rated load prohibited.* Travel restricted to 90 percent of rated capacity with speed not to exceed 0.4 m/s. Boom must be within boom angle range

shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8615-A**.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

JIB POINT ELEVATION: Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with 8 585 mm crawlers, 1 219 mm treads, 3 124 mm retractable gantry, 9 144 mm live mast, 20 part boom hoist reeving, boom support straps, 99 740 kg crane counterweight and 36 290 kg carbody counterweight.

Maximum capacity on 26 mm wire rope is 13 380 kg per line (9 070 kg when auxiliary drum is used).

Maximum Wind Speeds		
Boom Lengths	Working Wind	Lower To Ground
27.5m - 54.5m	14 m/s	22 m/s
57.5m - 60.5m	12 m/s	22 m/s
63.5m - 81.5m	10 m/s	22 m/s
Wind speed to be measured at jib point elevation.		

Maximum Boom and Jib Length Raising			
Over End of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 134	Boom Length	Jib No. 134
(a) 87.5m	—	78.5m	—
84.5m	—	75.5m	12.2m
81.5m	15.2m	72.5m	18.3m
78.5m	24.4m	69.5m	24.4m
Load block, hook and weight ball on ground at start. (a) Upper boom point cannot be attached on 87.5m boom.			



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
9.1	79.2	38.3	26 700 *							9.1
10.0	77.8	38.1	26 700 *							10.0
12.0	74.6	37.6	26 700 *	77.1	37.4	26 700*				12.0
14.0	71.3	36.9	26 700 *	73.8	36.7	26 100*	76.2	36.2	20 500*	14.0
16.0	67.9	36.1	26 600 *	70.4	35.9	25 400*	72.8	35.4	19 100*	16.0
18.0	64.5	35.2	26 100 *	66.9	35.0	24 900*	69.3	34.4	18 000*	18.0
20.0	60.9	34.1	25 400 *	63.3	33.9	24 400*	65.6	33.3	17 000*	20.0
22.0	57.2	32.9	24 800 *	59.6	32.6	23 800*	61.8	32.0	16 100*	22.0
24.0	53.4	31.4	24 300 *	55.7	31.1	22 400*	57.8	30.5	15 400*	24.0
26.0	49.3	29.8	23 800 *	51.6	29.5	21 100*	53.6	28.8	14 800*	26.0
28.0	44.9	27.8	23 300 *	47.2	27.5	20 000*	49.1	26.8	14 200*	28.0
30.0	40.2	25.5	22 100 *	42.4	25.2	19 000*	44.1	24.4	13 800*	30.0
32.0	34.9	22.8	20 600 *	37.0	22.4	18 200*				32.0
34.0	28.8	19.5	19 400 *							34.0
30.5m Boom										
9.1	80.0	41.4	26 700 *							9.1
10.0	78.8	41.2	26 700 *							10.0
12.0	75.8	40.7	26 700 *	78.1	40.5	26 700*				12.0
14.0	72.8	40.1	26 700 *	75.1	39.9	26 300*	77.4	39.3	21 000*	14.0
16.0	69.7	39.4	26 700 *	72.0	39.2	25 700*	74.2	38.6	19 700*	16.0
18.0	66.6	38.5	26 400 *	68.8	38.3	25 200*	71.0	37.7	18 600*	18.0
20.0	63.3	37.6	25 800 *	65.6	37.3	24 700*	67.7	36.7	17 600*	20.0
22.0	60.0	36.4	25 200 *	62.2	36.2	24 300*	64.3	35.6	16 700*	22.0
24.0	56.6	35.1	24 600 *	58.7	34.9	23 500*	60.8	34.3	16 000*	24.0
26.0	53.0	33.7	24 200 *	55.1	33.4	22 200*	57.1	32.7	15 300*	26.0
28.0	49.2	32.0	23 700 *	51.3	31.7	21 000*	53.2	31.0	14 700*	28.0
30.0	45.2	30.1	23 400 *	47.3	29.7	20 000*	49.0	29.0	14 200*	30.0
32.0	40.9	27.8	22 200 *	42.9	27.5	19 100*	44.5	26.7	13 800*	32.0
34.0	36.1	25.2	20 900 *	38.0	24.8	18 300*				34.0
36.0	30.7	22.1	19 700 *	32.5	21.6	17 700*				36.0
38.0	24.2	18.0	18 700 *							38.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
9.1	80.7	44.4	26 700 *							9.1
10.0	79.6	44.3	26 700 *							10.0
12.0	76.8	43.8	26 700 *	79.0	43.6	26 700*				12.0
14.0	74.0	43.3	26 700 *	76.2	43.0	26 400*	78.3	42.5	21 400*	14.0
16.0	71.2	42.6	26 700 *	73.3	42.4	25 900*	75.4	41.8	20 200*	16.0
18.0	68.3	41.8	26 700 *	70.4	41.6	25 300*	72.5	41.0	19 100*	18.0
20.0	65.4	40.9	26 100 *	67.4	40.7	24 900*	69.5	40.1	18 100*	20.0
22.0	62.3	39.9	25 500 *	64.4	39.6	24 500*	66.4	39.0	17 200*	22.0
24.0	59.2	38.7	25 000 *	61.3	38.5	24 100*	63.2	37.8	16 500*	24.0
26.0	56.0	37.4	24 500 *	58.0	37.1	23 300*	59.9	36.5	15 800*	26.0
28.0	52.6	35.9	24 000 *	54.6	35.6	22 000*	56.4	35.0	15 200*	28.0
30.0	49.1	34.2	23 700 *	51.1	33.9	21 000*	52.8	33.2	14 700*	30.0
32.0	45.4	32.3	23 400 *	47.3	32.0	20 000*	49.0	31.2	14 200*	32.0
34.0	41.4	30.1	22 400	43.3	29.8	19 200*	44.8	29.0	13 800*	34.0
36.0	37.1	27.6	20 600	38.9	27.2	18 500*				36.0
38.0	32.2	24.6	19 000	33.9	24.1	17 800*				38.0
40.0	26.6	20.9	17 500							40.0
36.5m Boom										
10.7	79.4	47.2	26 700 *							10.7
12.0	77.7	46.9	26 700 *							12.0
14.0	75.1	46.4	26 700 *	77.1	46.1	26 600*	79.1	45.6	21 900*	14.0
16.0	72.5	45.8	26 700 *	74.5	45.5	26 000*	76.4	45.0	20 600*	16.0
18.0	69.8	45.1	26 700 *	71.8	44.8	25 500*	73.7	44.2	19 500*	18.0
20.0	67.1	44.2	26 400 *	69.0	44.0	25 100*	70.9	43.4	18 600*	20.0
22.0	64.3	43.3	25 800 *	66.2	43.0	24 700*	68.1	42.4	17 700*	22.0
24.0	61.5	42.2	25 300 *	63.4	41.9	24 300*	65.2	41.3	16 900*	24.0
26.0	58.5	41.0	24 800 *	60.4	40.7	23 900*	62.2	40.1	16 300*	26.0
28.0	55.5	39.7	24 400 *	57.4	39.4	23 100*	59.1	38.7	15 700*	28.0
30.0	52.4	38.2	24 000 *	54.2	37.9	21 900*	55.9	37.2	15 100*	30.0
32.0	49.1	36.5	23 600 *	50.9	36.1	20 900*	52.5	35.4	14 600*	32.0
34.0	45.6	34.6	22 400	47.4	34.2	20 000*	48.9	33.5	14 200*	34.0
36.0	41.9	32.4	20 500	43.6	32.0	19 300*	45.1	31.2	13 800*	36.0
38.0	37.9	29.9	18 800	39.6	29.5	18 600*				38.0
40.0	33.5	27.0	17 400	35.1	26.6	17 500				40.0
44.0	22.4	19.2	14 900							44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
10.7	80.1	50.3	26 700 *							10.7
12.0	78.5	50.0	26 700 *							12.0
14.0	76.0	49.5	26 700 *	77.9	49.3	26 600*	79.8	48.7	22 200*	14.0
16.0	73.6	48.9	26 700 *	75.5	48.7	26 200*	77.3	48.1	21 000*	16.0
18.0	71.1	48.3	26 700 *	73.0	48.0	25 700*	74.8	47.4	19 900*	18.0
20.0	68.6	47.5	26 700 *	70.4	47.2	25 200*	72.2	46.6	19 000*	20.0
22.0	66.0	46.6	26 100 *	67.8	46.3	24 800*	69.6	45.8	18 100*	22.0
24.0	63.4	45.6	25 600 *	65.2	45.4	24 500*	66.9	44.8	17 400*	24.0
26.0	60.7	44.5	25 100 *	62.5	44.2	24 100*	64.2	43.6	16 700*	26.0
28.0	57.9	43.3	24 600 *	59.7	43.0	23 700*	61.3	42.4	16 100*	28.0
30.0	55.1	41.9	24 300 *	56.8	41.6	22 800*	58.4	41.0	15 500*	30.0
32.0	52.1	40.4	23 900 *	53.8	40.1	21 800*	55.4	39.4	15 000*	32.0
34.0	49.0	38.7	22 200	50.7	38.4	20 900*	52.2	37.7	14 600*	34.0
36.0	45.8	36.8	20 300	47.4	36.5	20 100*	48.9	35.7	14 200*	36.0
38.0	42.3	34.7	18 700	44.0	34.3	18 900	45.3	33.5	13 800*	38.0
40.0	38.6	32.2	17 200	40.2	31.9	17 400				40.0
44.0	30.1	26.2	14 700	31.5	25.7	14 800				44.0
42.5m Boom										
10.7	80.7	53.3	26 700 *							10.7
12.0	79.1	53.1	26 700 *							12.0
14.0	76.9	52.6	26 700 *	78.6	52.4	26 700*	80.4	51.8	22 500*	14.0
16.0	74.6	52.1	26 700 *	76.3	51.8	26 300*	78.1	51.2	21 300*	16.0
18.0	72.2	51.4	26 700 *	74.0	51.2	25 800*	75.7	50.6	20 300*	18.0
20.0	69.9	50.7	26 700 *	71.6	50.5	25 400*	73.3	49.9	19 400*	20.0
22.0	67.5	49.9	26 400 *	69.2	49.6	25 000*	70.9	49.0	18 500*	22.0
24.0	65.1	49.0	25 800 *	66.8	48.7	24 600*	68.4	48.1	17 800*	24.0
26.0	62.6	48.0	25 300 *	64.3	47.7	24 300*	65.9	47.1	17 100*	26.0
28.0	60.0	46.8	24 900 *	61.7	46.5	24 000*	63.3	45.9	16 500*	28.0
30.0	57.4	45.6	24 500 *	59.1	45.3	23 600*	60.6	44.6	15 900*	30.0
32.0	54.7	44.2	24 000	56.3	43.9	22 600*	57.8	43.2	15 400*	32.0
34.0	51.9	42.6	21 900	53.5	42.3	21 700	55.0	41.6	15 000*	34.0
36.0	49.0	40.9	20 100	50.6	40.6	20 400	52.0	39.9	14 600*	36.0
38.0	45.9	39.0	18 500	47.5	38.7	18 700	48.8	37.9	14 200*	38.0
40.0	42.7	36.9	17 000	44.2	36.6	17 200	45.5	35.7	13 900*	40.0
44.0	35.5	31.9	14 500	37.0	31.4	14 700				44.0
48.0	26.7	25.0	12 500							48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
12.2	79.5	56.1	26 700 *							12.2
14.0	77.6	55.7	26 700 *	79.3	55.4	26 700*				14.0
16.0	75.4	55.2	26 700 *	77.1	54.9	26 300*	78.8	54.4	21 700*	16.0
18.0	73.3	54.6	26 700 *	74.9	54.3	25 900*	76.6	53.8	20 600*	18.0
20.0	71.0	53.9	26 700 *	72.7	53.7	25 500*	74.3	53.1	19 700*	20.0
22.0	68.8	53.1	26 500 *	70.4	52.9	25 100*	72.0	52.3	18 900*	22.0
24.0	66.5	52.3	26 000 *	68.1	52.0	24 700*	69.7	51.4	18 100*	24.0
26.0	64.2	51.3	25 600 *	65.8	51.1	24 400*	67.3	50.5	17 500*	26.0
28.0	61.8	50.3	25 100 *	63.4	50.0	24 100*	64.9	49.4	16 800*	28.0
30.0	59.4	49.1	24 700 *	61.0	48.8	23 800*	62.5	48.2	16 300*	30.0
32.0	56.9	47.8	23 700	58.5	47.5	23 400*	59.9	46.9	15 800*	32.0
34.0	54.3	46.4	21 600	55.9	46.1	22 000	57.3	45.4	15 300*	34.0
36.0	51.7	44.9	19 800	53.2	44.6	20 000	54.6	43.9	14 900*	36.0
38.0	48.9	43.2	18 200	50.4	42.8	18 400	51.7	42.1	14 500*	38.0
40.0	46.0	41.3	16 700	47.5	40.9	16 900	48.8	40.2	14 200*	40.0
44.0	39.8	36.9	14 200	41.2	36.5	14 400	42.3	35.6	13 600*	44.0
48.0	32.5	31.2	12 200	33.9	30.8	12 300				48.0
48.5m Boom										
12.2	80.1	59.1	26 700 *							12.2
14.0	78.3	58.8	26 700 *	79.9	58.5	26 700*				14.0
16.0	76.2	58.3	26 700 *	77.8	58.0	26 400*	79.4	57.5	22 000*	16.0
18.0	74.2	57.7	26 700 *	75.7	57.5	26 000*	77.3	56.9	21 000*	18.0
20.0	72.1	57.1	26 700 *	73.6	56.8	25 500*	75.2	56.2	20 100*	20.0
22.0	70.0	56.4	26 600 *	71.5	56.1	25 200*	73.0	55.5	19 200*	22.0
24.0	67.8	55.6	26 200 *	69.4	55.3	24 800*	70.9	54.7	18 500*	24.0
26.0	65.6	54.7	25 700 *	67.2	54.4	24 500*	68.6	53.8	17 800*	26.0
28.0	63.4	53.7	25 300 *	64.9	53.4	24 200*	66.4	52.8	17 200*	28.0
30.0	61.2	52.6	24 900 *	62.7	52.3	24 000*	64.1	51.7	16 700*	30.0
32.0	58.8	51.4	23 500	60.3	51.1	23 700*	61.7	50.5	16 100*	32.0
34.0	56.5	50.1	21 400	57.9	49.8	21 800	59.3	49.1	15 700*	34.0
36.0	54.0	48.7	19 600	55.5	48.4	19 900	56.8	47.7	15 300*	36.0
38.0	51.5	47.1	18 000	53.0	46.8	18 200	54.2	46.1	14 800*	38.0
40.0	48.9	45.4	16 500	50.3	45.1	16 700	51.5	44.3	14 500*	40.0
44.0	43.3	41.5	14 000	44.7	41.1	14 200	45.8	40.3	13 900*	44.0
48.0	37.0	36.6	12 000	38.3	36.2	12 100				48.0
52.0	29.6	30.3	10 300							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
12.2	80.6	62.2	26 700 *							12.2
14.0	78.9	61.8	26 700 *	80.4	61.6	26 700*				14.0
16.0	76.9	61.4	26 700 *	78.4	61.1	26 400*	79.9	60.5	22 200*	16.0
18.0	75.0	60.8	26 700 *	76.5	60.6	26 000*	78.0	60.0	21 300*	18.0
20.0	73.0	60.2	26 700 *	74.5	60.0	25 600*	76.0	59.4	20 400*	20.0
22.0	71.0	59.6	26 700 *	72.5	59.3	25 200*	73.9	58.7	19 600*	22.0
24.0	69.0	58.8	26 400 *	70.4	58.5	24 900*	71.9	57.9	18 800*	24.0
26.0	66.9	58.0	25 900 *	68.4	57.7	24 600*	69.8	57.1	18 200*	26.0
28.0	64.8	57.0	25 500 *	66.3	56.8	24 300*	67.7	56.1	17 600*	28.0
30.0	62.7	56.0	25 100 *	64.2	55.7	24 000*	65.5	55.1	17 000*	30.0
32.0	60.6	54.9	23 300	62.0	54.6	23 700	63.3	54.0	16 500*	32.0
34.0	58.3	53.7	21 200	59.8	53.4	21 600	61.1	52.7	16 000*	34.0
36.0	56.1	52.4	19 400	57.5	52.1	19 700	58.8	51.4	15 600*	36.0
38.0	53.7	50.9	17 800	55.1	50.6	18 000	56.4	49.9	15 200*	38.0
40.0	51.3	49.4	16 300	52.7	49.0	16 600	53.9	48.3	14 800*	40.0
44.0	46.3	45.8	13 800	47.6	45.4	14 000	48.7	44.6	14 100	44.0
48.0	40.7	41.4	11 800	42.0	41.0	11 900	43.0	40.2	12 100	48.0
52.0	34.4	36.1	10 000	35.6	35.6	10 200				52.0
56.0	26.8	29.1	8 600							56.0
54.5m Boom										
13.7	79.6	64.9	26 700 *							13.7
14.0	79.4	64.9	26 700 *							14.0
16.0	77.5	64.5	26 700 *	79.0	64.2	26 400*				16.0
18.0	75.7	64.0	26 700 *	77.1	63.7	26 000*	78.5	63.1	21 500*	18.0
20.0	73.8	63.4	26 700 *	75.2	63.1	25 600*	76.6	62.5	20 700*	20.0
22.0	71.9	62.7	26 700 *	73.3	62.5	25 300*	74.7	61.9	19 900*	22.0
24.0	70.0	62.0	26 400 *	71.4	61.8	25 000*	72.8	61.2	19 100*	24.0
26.0	68.1	61.2	26 000 *	69.5	61.0	24 700*	70.8	60.4	18 500*	26.0
28.0	66.1	60.4	25 600 *	67.5	60.1	24 400*	68.8	59.5	17 900*	28.0
30.0	64.1	59.4	25 100	65.5	59.1	24 100*	66.8	58.5	17 300*	30.0
32.0	62.1	58.4	23 100	63.4	58.1	23 400	64.7	57.4	16 800*	32.0
34.0	60.0	57.2	21 000	61.4	56.9	21 300	62.6	56.3	16 300*	34.0
36.0	57.9	56.0	19 200	59.2	55.7	19 500	60.5	55.0	15 900*	36.0
38.0	55.7	54.6	17 500	57.1	54.3	17 900	58.3	53.6	15 500*	38.0
40.0	53.5	53.2	16 100	54.8	52.9	16 400	56.0	52.2	15 100*	40.0
44.0	48.8	49.9	13 600	50.1	49.5	13 800	51.2	48.8	14 100	44.0
48.0	43.8	46.0	11 600	45.0	45.6	11 700	46.0	44.8	11 900	48.0
52.0	38.2	41.2	9 900	39.4	40.8	10 000				52.0
56.0	31.8	35.4	8 400	32.9	34.9	8 500				56.0
60.0	23.9	27.6	7 100							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
13.7	80.1	68.0	26 700 *							13.7
14.0	79.9	67.9	26 700 *							14.0
16.0	78.1	67.5	26 700 *	79.5	67.3	26 300*				16.0
18.0	76.3	67.1	26 700 *	77.7	66.8	26 000*	79.1	66.2	21 800*	18.0
20.0	74.6	66.5	26 700 *	75.9	66.3	25 600*	77.3	65.7	21 000*	20.0
22.0	72.8	65.9	26 700 *	74.1	65.6	25 300*	75.5	65.0	20 200*	22.0
24.0	70.9	65.2	26 500 *	72.3	65.0	25 000*	73.6	64.4	19 500*	24.0
26.0	69.1	64.5	26 100 *	70.4	64.2	24 700*	71.7	63.6	18 800*	26.0
28.0	67.2	63.6	25 700 *	68.6	63.4	24 400*	69.9	62.7	18 200*	28.0
30.0	65.4	62.7	25 000	66.7	62.5	24 200*	67.9	61.8	17 600*	30.0
32.0	63.4	61.8	22 800	64.8	61.5	23 200	66.0	60.8	17 100*	32.0
34.0	61.5	60.7	20 700	62.8	60.4	21 100	64.0	59.7	16 600*	34.0
36.0	59.5	59.5	18 900	60.8	59.2	19 200	62.0	58.6	16 200*	36.0
38.0	57.5	58.3	17 300	58.8	58.0	17 600	59.9	57.3	15 800*	38.0
40.0	55.4	56.9	15 800	56.7	56.6	16 100	57.8	55.9	15 400*	40.0
44.0	51.1	53.8	13 300	52.3	53.5	13 500	53.4	52.8	13 800	44.0
48.0	46.4	50.2	11 300	47.7	49.9	11 500	48.7	49.1	11 600	48.0
52.0	41.4	46.0	9 500	42.6	45.6	9 700				52.0
56.0	35.8	40.9	8 100	36.9	40.4	8 200				56.0
60.0	29.3	34.4	6 800							60.0
64.0	21.0	25.7	5 700							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
13.7	80.5	71.0	26 700 *							13.7
14.0	80.3	71.0	26 700 *							14.0
16.0	78.6	70.6	26 700 *	80.0	70.3	26 300*				16.0
18.0	76.9	70.1	26 700 *	78.3	69.9	25 900*	79.6	69.3	22 100*	18.0
20.0	75.2	69.6	26 700 *	76.6	69.4	25 600*	77.8	68.8	21 200*	20.0
22.0	73.5	69.0	26 700 *	74.8	68.8	25 300*	76.1	68.2	20 400*	22.0
24.0	71.8	68.4	26 500 *	73.1	68.1	25 000*	74.4	67.5	19 700*	24.0
26.0	70.1	67.7	26 100 *	71.3	67.4	24 700*	72.6	66.8	19 100*	26.0
28.0	68.3	66.9	25 800 *	69.6	66.6	24 500*	70.8	66.0	18 500*	28.0
30.0	66.5	66.0	24 800	67.8	65.8	24 200*	69.0	65.1	18 000*	30.0
32.0	64.7	65.1	22 600	65.9	64.8	23 000	67.1	64.2	17 400*	32.0
34.0	62.8	64.1	20 500	64.1	63.8	20 900	65.3	63.2	16 900*	34.0
36.0	61.0	63.0	18 600	62.2	62.7	19 000	63.4	62.0	16 500*	36.0
38.0	59.0	61.8	17 000	60.3	61.5	17 400	61.4	60.8	16 100*	38.0
40.0	57.1	60.5	15 600	58.3	60.2	15 900	59.4	59.5	15 700	40.0
44.0	53.0	57.7	13 100	54.2	57.4	13 400	55.3	56.6	13 600	44.0
48.0	48.8	54.3	11 000	49.9	54.0	11 200	50.9	53.2	11 500	48.0
52.0	44.2	50.5	9 300	45.3	50.1	9 500	46.2	49.3	9 700	52.0
56.0	39.2	45.9	7 900	40.3	45.5	8 000				56.0
60.0	33.5	40.3	6 600	34.6	39.8	6 700				60.0
64.0	26.8	33.3	5 500							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
13.7	80.9	74.1	26 700 *							13.7
14.0	80.7	74.0	26 700 *							14.0
16.0	79.1	73.7	26 700 *	80.4	73.4	26 200*				16.0
18.0	77.5	73.2	26 700 *	78.8	73.0	25 900*	80.0	72.4	22 300*	18.0
20.0	75.9	72.7	26 700 *	77.1	72.5	25 500*	78.4	71.9	21 500*	20.0
22.0	74.2	72.2	26 700 *	75.5	71.9	25 300*	76.7	71.3	20 700*	22.0
24.0	72.6	71.6	26 500 *	73.8	71.3	25 000*	75.0	70.7	20 000*	24.0
26.0	70.9	70.9	26 100 *	72.1	70.6	24 700*	73.4	70.0	19 300*	26.0
28.0	69.2	70.1	25 800	70.5	69.9	24 500*	71.6	69.2	18 800*	28.0
30.0	67.5	69.3	24 500	68.7	69.0	24 200*	69.9	68.4	18 200*	30.0
32.0	65.8	68.4	22 300	67.0	68.1	22 700	68.2	67.5	17 700*	32.0
34.0	64.0	67.5	20 300	65.3	67.2	20 700	66.4	66.5	17 200*	34.0
36.0	62.3	66.4	18 400	63.5	66.1	18 800	64.6	65.5	16 800*	36.0
38.0	60.5	65.3	16 800	61.7	65.0	17 100	62.8	64.3	16 300*	38.0
40.0	58.6	64.1	15 300	59.8	63.8	15 700	60.9	63.1	15 900	40.0
44.0	54.8	61.4	12 800	56.0	61.1	13 100	57.0	60.4	13 400	44.0
48.0	50.8	58.3	10 800	52.0	58.0	11 100	52.9	57.2	11 200	48.0
52.0	46.6	54.7	9 100	47.7	54.4	9 300	48.6	53.6	9 400	52.0
56.0	42.0	50.5	7 600	43.1	50.1	7 800	43.9	49.3	7 900	56.0
60.0	37.0	45.6	6 400	38.0	45.1	6 500				60.0
64.0	31.3	39.5	5 300	32.2	39.0	5 300				64.0
68.0	24.4	31.8	4 300							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
15.2	80.1	76.9	26 700 *							15.2
16.0	79.5	76.7	26 700 *							16.0
18.0	78.0	76.3	26 700 *	79.2	76.0	25 800*				18.0
20.0	76.4	75.8	26 700 *	77.6	75.6	25 500*	78.8	75.0	21 700*	20.0
22.0	74.9	75.3	26 700 *	76.1	75.0	25 200*	77.3	74.4	20 900*	22.0
24.0	73.3	74.7	26 500 *	74.5	74.4	24 900*	75.7	73.8	20 300*	24.0
26.0	71.7	74.1	26 200 *	72.9	73.8	24 700*	74.1	73.2	19 600*	26.0
28.0	70.1	73.3	25 700	71.3	73.1	24 400*	72.4	72.5	19 000*	28.0
30.0	68.5	72.6	23 900	69.6	72.3	24 000	70.8	71.7	18 500*	30.0
32.0	66.8	71.7	21 800	68.0	71.4	22 200	69.1	70.8	18 000*	32.0
34.0	65.2	70.8	19 900	66.3	70.5	20 400	67.4	69.9	17 500*	34.0
36.0	63.5	69.8	18 200	64.6	69.5	18 600	65.7	68.9	17 000*	36.0
38.0	61.7	68.8	16 500	62.9	68.5	16 900	64.0	67.8	16 600*	38.0
40.0	60.0	67.6	15 100	61.1	67.3	15 400	62.2	66.6	15 800	40.0
44.0	56.4	65.1	12 600	57.5	64.8	12 900	58.6	64.1	13 200	44.0
48.0	52.7	62.2	10 600	53.8	61.8	10 800	54.7	61.1	11 100	48.0
52.0	48.7	58.8	8 900	49.8	58.5	9 100	50.7	57.7	9 300	52.0
56.0	44.5	55.0	7 400	45.6	54.6	7 600	46.4	53.8	7 700	56.0
60.0	40.0	50.5	6 100	41.0	50.1	6 300				60.0
64.0	34.9	45.1	5 000	35.9	44.7	5 200				64.0
68.0	29.1	38.6	4 100							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
15.2	80.5	79.9	26 700 *							15.2
16.0	80.0	79.8	26 700 *							16.0
18.0	78.5	79.4	26 700 *	79.6	79.1	25 700*				18.0
20.0	77.0	78.9	26 700 *	78.1	78.7	25 400*	79.3	78.1	21 900*	20.0
22.0	75.5	78.4	26 700 *	76.6	78.1	25 100*	77.8	77.5	21 200*	22.0
24.0	74.0	77.8	26 500 *	75.1	77.6	24 800*	76.2	77.0	20 500*	24.0
26.0	72.4	77.2	26 100 *	73.6	76.9	24 600*	74.7	76.3	19 900*	26.0
28.0	70.9	76.5	25 400	72.0	76.3	24 400*	73.1	75.6	19 300*	28.0
30.0	69.3	75.8	23 200	70.5	75.5	23 600	71.6	74.9	18 700*	30.0
32.0	67.8	75.0	21 200	68.9	74.7	21 700	70.0	74.1	18 200*	32.0
34.0	66.2	74.1	19 400	67.3	73.8	19 900	68.4	73.2	17 800*	34.0
36.0	64.6	73.2	17 800	65.7	72.9	18 200	66.7	72.2	17 300*	36.0
38.0	62.9	72.2	16 300	64.0	71.9	16 600	65.1	71.2	16 900*	38.0
40.0	61.3	71.1	14 800	62.4	70.8	15 200	63.4	70.1	15 500	40.0
44.0	57.9	68.7	12 300	59.0	68.4	12 600	59.9	67.7	12 900	44.0
48.0	54.3	65.9	10 300	55.4	65.6	10 500	56.3	64.9	10 800	48.0
52.0	50.6	62.8	8 500	51.7	62.5	8 800	52.6	61.7	9 000	52.0
56.0	46.7	59.2	7 100	47.7	58.8	7 300	48.6	58.0	7 400	56.0
60.0	42.5	55.1	5 800	43.5	54.7	6 000	44.3	53.8	6 100	60.0
64.0	38.0	50.2	4 700	38.9	49.8	4 900				64.0
68.0	32.9	44.5	3 800	33.8	44.0	3 800				68.0
72.0	26.9	37.4	2 900							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
15.2	80.9	83.0	26 700 *							15.2
16.0	80.3	82.8	26 700 *							16.0
18.0	78.9	82.4	26 700 *	80.0	82.2	25 600*				18.0
20.0	77.5	82.0	26 700 *	78.6	81.7	25 300*	79.7	81.1	22 100*	20.0
22.0	76.0	81.5	26 600 *	77.1	81.2	25 000*	78.2	80.6	21 400*	22.0
24.0	74.6	81.0	26 400 *	75.7	80.7	24 800*	76.8	80.1	20 700*	24.0
26.0	73.1	80.4	26 000	74.2	80.1	24 500*	75.3	79.5	20 100*	26.0
28.0	71.6	79.7	25 100	72.7	79.4	24 300*	73.8	78.8	19 500*	28.0
30.0	70.1	79.0	22 700	71.2	78.7	23 300	72.3	78.1	19 000*	30.0
32.0	68.6	78.2	20 700	69.7	77.9	21 200	70.8	77.3	18 500*	32.0
34.0	67.1	77.4	19 000	68.2	77.1	19 400	69.2	76.5	18 000*	34.0
36.0	65.6	76.5	17 400	66.6	76.2	17 800	67.7	75.6	17 600*	36.0
38.0	64.0	75.5	15 900	65.1	75.2	16 300	66.1	74.6	16 700	38.0
40.0	62.4	74.5	14 600	63.5	74.2	14 900	64.5	73.5	15 300	40.0
44.0	59.2	72.2	12 100	60.2	71.9	12 400	61.2	71.2	12 700	44.0
48.0	55.8	69.6	10 000	56.9	69.3	10 300	57.8	68.6	10 600	48.0
52.0	52.3	66.7	8 300	53.4	66.3	8 500	54.3	65.6	8 800	52.0
56.0	48.7	63.3	6 800	49.7	62.9	7 100	50.5	62.2	7 300	56.0
60.0	44.8	59.5	5 600	45.8	59.1	5 800	46.6	58.2	5 900	60.0
64.0	40.6	55.0	4 500	41.6	54.6	4 600	42.3	53.7	4 800	64.0
68.0	36.0	49.9	3 500	36.9	49.4	3 600				68.0
72.0	30.9	43.7	2 700							72.0
76.0	24.7	35.9	1 900							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
16.8	80.1	85.7	26 700 *							16.8
18.0	79.3	85.5	26 700 *							18.0
20.0	77.9	85.1	26 700 *	79.0	84.8	25 100*	80.1	84.2	22 300*	20.0
22.0	76.5	84.6	26 500 *	77.6	84.3	24 900*	78.7	83.7	21 600*	22.0
24.0	75.1	84.1	26 200 *	76.2	83.8	24 600*	77.3	83.2	20 900*	24.0
26.0	73.7	83.5	25 900	74.8	83.2	24 400*	75.8	82.6	20 300*	26.0
28.0	72.3	82.9	24 900	73.4	82.6	24 200*	74.4	82.0	19 800*	28.0
30.0	70.9	82.2	22 600	71.9	81.9	23 200	72.9	81.3	19 200*	30.0
32.0	69.4	81.4	20 600	70.5	81.2	21 100	71.5	80.5	18 700*	32.0
34.0	68.0	80.6	18 800	69.0	80.4	19 300	70.0	79.7	18 300*	34.0
36.0	66.5	79.8	17 300	67.5	79.5	17 700	68.5	78.9	17 800*	36.0
38.0	65.0	78.9	15 900	66.0	78.6	16 300	67.0	77.9	16 700	38.0
40.0	63.5	77.9	14 600	64.5	77.6	15 000	65.5	76.9	15 300	40.0
44.0	60.4	75.7	12 200	61.4	75.4	12 500	62.4	74.7	12 800	44.0
48.0	57.2	73.2	10 100	58.2	72.9	10 400	59.1	72.2	10 700	48.0
52.0	53.9	70.4	8 400	54.9	70.1	8 600	55.8	69.4	8 900	52.0
56.0	50.5	67.3	6 900	51.4	66.9	7 100	52.3	66.2	7 300	56.0
60.0	46.8	63.7	5 700	47.8	63.3	5 900	48.6	62.5	6 000	60.0
64.0	42.9	59.6	4 600	43.9	59.2	4 700	44.6	58.3	4 900	64.0
68.0	38.8	54.9	3 600	39.7	54.5	3 700				68.0
72.0	34.1	49.4	2 700	35.0	48.9	2 900				72.0
76.0	28.9	42.7	2 000							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
16.8	80.5	88.8	26 700 *							16.8
18.0	79.7	88.6	26 700 *							18.0
20.0	78.3	88.2	26 700 *	79.4	87.9	25 000*	80.4	87.3	22 500*	20.0
22.0	77.0	87.7	26 300 *	78.0	87.4	24 700*	79.1	86.8	21 800*	22.0
24.0	75.6	87.2	26 000 *	76.7	86.9	24 500*	77.7	86.3	21 100*	24.0
26.0	74.3	86.6	25 700	75.3	86.4	24 300*	76.3	85.8	20 500*	26.0
28.0	72.9	86.0	24 400	73.9	85.8	24 000	75.0	85.1	20 000*	28.0
30.0	71.5	85.4	22 100	72.6	85.1	22 700	73.6	84.5	19 400*	30.0
32.0	70.2	84.7	20 100	71.2	84.4	20 600	72.2	83.8	18 900*	32.0
34.0	68.8	83.9	18 400	69.8	83.6	18 800	70.7	83.0	18 500*	34.0
36.0	67.3	83.1	16 800	68.3	82.8	17 300	69.3	82.1	17 700	36.0
38.0	65.9	82.2	15 400	66.9	81.9	15 800	67.9	81.2	16 200	38.0
40.0	64.5	81.2	14 100	65.5	80.9	14 500	66.4	80.3	14 900	40.0
44.0	61.5	79.1	11 900	62.5	78.8	12 300	63.4	78.2	12 600	44.0
48.0	58.5	76.8	9 900	59.4	76.5	10 200	60.3	75.8	10 400	48.0
52.0	55.3	74.1	8 100	56.3	73.8	8 400	57.2	73.1	8 600	52.0
56.0	52.1	71.1	6 700	53.0	70.8	6 900	53.8	70.1	7 100	56.0
60.0	48.6	67.8	5 500	49.6	67.4	5 600	50.4	66.6	5 800	60.0
64.0	45.0	63.9	4 400	45.9	63.6	4 500	46.7	62.7	4 600	64.0
68.0	41.2	59.6	3 400	42.1	59.2	3 500	42.7	58.3	3 600	68.0
72.0	37.0	54.6	2 500	37.8	54.1	2 600				72.0
76.0				33.1	48.2	1 800				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
16.8	80.8	91.8	26 700 *							16.8
18.0	80.0	91.6	26 600 *							18.0
20.0	78.7	91.2	26 300 *	79.7	91.0	24 700*	80.7	90.4	22 700*	20.0
22.0	77.4	90.8	26 000 *	78.4	90.5	24 500*	79.4	89.9	22 000*	22.0
24.0	76.1	90.3	25 700 *	77.1	90.0	24 300*	78.1	89.4	21 300*	24.0
26.0	74.8	89.8	25 400	75.8	89.5	24 100*	76.8	88.9	20 700*	26.0
28.0	73.5	89.2	23 700	74.5	88.9	23 700	75.5	88.3	20 200*	28.0
30.0	72.2	88.5	21 500	73.2	88.3	22 200	74.1	87.6	19 700*	30.0
32.0	70.8	87.8	19 600	71.8	87.6	20 100	72.8	86.9	19 100*	32.0
34.0	69.5	87.1	17 800	70.5	86.8	18 300	71.4	86.2	18 600	34.0
36.0	68.1	86.3	16 300	69.1	86.0	16 800	70.0	85.4	17 300	36.0
38.0	66.8	85.5	14 900	67.7	85.2	15 300	68.7	84.5	15 800	38.0
40.0	65.4	84.6	13 700	66.3	84.3	14 100	67.2	83.6	14 500	40.0
44.0	62.5	82.6	11 500	63.5	82.3	11 800	64.4	81.6	12 100	44.0
48.0	59.6	80.3	9 600	60.6	80.0	9 900	61.5	79.3	10 200	48.0
52.0	56.6	77.8	7 900	57.6	77.5	8 100	58.4	76.7	8 400	52.0
56.0	53.5	74.9	6 400	54.5	74.6	6 600	55.3	73.9	6 800	56.0
60.0	50.3	71.7	5 100	51.2	71.4	5 300	52.0	70.6	5 500	60.0
64.0	46.9	68.2	4 000	47.8	67.8	4 200	48.5	67.0	4 400	64.0
68.0	43.3	64.1	3 100	44.2	63.7	3 200	44.9	62.8	3 400	68.0
72.0	39.4	59.5	2 200	40.3	59.1	2 300				72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
9.1	80.7	41.4	25 000 *							9.1
10.0	79.5	41.2	24 600 *							10.0
12.0	76.5	40.7	23 700 *							12.0
14.0	73.5	40.1	22 800 *	76.5	39.8	21 200*	79.7	39.1	17 500*	14.0
16.0	70.4	39.4	22 100 *	73.4	39.1	20 700*	76.5	38.4	16 300*	16.0
18.0	67.3	38.6	21 400 *	70.2	38.2	20 200*	73.3	37.5	15 300*	18.0
20.0	64.1	37.6	20 800 *	67.0	37.3	19 800*	69.9	36.5	14 500*	20.0
22.0	60.7	36.5	20 200 *	63.7	36.1	18 900*	66.5	35.4	13 700*	22.0
24.0	57.3	35.2	19 700 *	60.2	34.8	17 600*	63.0	34.0	13 000*	24.0
26.0	53.7	33.7	19 300 *	56.6	33.3	16 500*	59.2	32.5	12 500*	26.0
28.0	49.9	32.0	18 700 *	52.7	31.6	15 500*	55.3	30.8	12 000*	28.0
30.0	45.9	30.1	17 600 *	48.7	29.7	14 700*	51.1	28.7	11 500*	30.0
32.0	41.6	27.9	16 400 *	44.3	27.4	13 900*	46.5	26.4	11 200*	32.0
34.0	36.9	25.3	15 500 *	39.4	24.7	13 300*				34.0
36.0	31.5	22.1	14 600 *	33.9	21.5	12 800*				36.0
38.0	25.0	18.1	13 900 *							38.0
30.5m Boom										
10.7	79.3	44.2	24 400 *							10.7
12.0	77.5	43.9	23 900 *							12.0
14.0	74.7	43.3	23 100 *	77.5	43.0	21 400*	80.4	42.3	17 800*	14.0
16.0	71.9	42.6	22 400 *	74.7	42.3	20 900*	77.5	41.6	16 700*	16.0
18.0	69.0	41.8	21 700 *	71.7	41.5	20 400*	74.6	40.8	15 700*	18.0
20.0	66.0	41.0	21 100 *	68.8	40.6	20 100*	71.5	39.9	14 900*	20.0
22.0	63.0	39.9	20 600 *	65.7	39.6	19 500*	68.4	38.8	14 100*	22.0
24.0	59.9	38.8	20 100 *	62.6	38.4	18 500*	65.2	37.6	13 500*	24.0
26.0	56.7	37.4	19 600 *	59.3	37.1	17 300*	61.9	36.2	12 900*	26.0
28.0	53.3	36.0	19 200 *	56.0	35.6	16 300*	58.4	34.7	12 400*	28.0
30.0	49.8	34.3	18 700 *	52.4	33.9	15 400*	54.8	32.9	11 900*	30.0
32.0	46.1	32.4	17 600 *	48.6	31.9	14 600*	50.9	30.9	11 500*	32.0
34.0	42.1	30.2	16 500 *	44.6	29.7	14 000*	46.7	28.6	11 200*	34.0
36.0	37.8	27.6	15 600 *	40.2	27.1	13 400*				36.0
38.0	32.9	24.6	14 800 *	35.2	24.0	12 900*				38.0
40.0	27.3	20.9	14 100 *							40.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
10.7	80.0	47.2	24 600 *							10.7
12.0	78.3	46.9	24 100 *							12.0
14.0	75.7	46.4	23 300 *	78.4	46.1	21 500*				14.0
16.0	73.1	45.8	22 600 *	75.7	45.5	21 000*	78.4	44.7	17 000*	16.0
18.0	70.4	45.1	22 000 *	73.0	44.7	20 600*	75.7	44.0	16 100*	18.0
20.0	67.7	44.3	21 400 *	70.3	43.9	20 200*	72.9	43.2	15 200*	20.0
22.0	64.9	43.3	20 900 *	67.5	43.0	19 900*	70.0	42.2	14 500*	22.0
24.0	62.1	42.2	20 400 *	64.6	41.9	19 200*	67.1	41.1	13 800*	24.0
26.0	59.2	41.0	19 900 *	61.7	40.7	18 100*	64.1	39.9	13 300*	26.0
28.0	56.1	39.7	19 500 *	58.6	39.3	17 000*	61.0	38.5	12 700*	28.0
30.0	53.0	38.2	19 100 *	55.4	37.8	16 200*	57.7	36.9	12 300*	30.0
32.0	49.7	36.5	18 800 *	52.1	36.1	15 400*	54.3	35.1	11 900*	32.0
34.0	46.2	34.6	17 700 *	48.6	34.1	14 600*	50.7	33.2	11 500*	34.0
36.0	42.6	32.4	16 600 *	44.9	32.0	14 000*	46.8	30.9	11 200*	36.0
38.0	38.6	30.0	15 800 *	40.8	29.4	13 400*				38.0
40.0	34.2	27.1	15 000 *	36.3	26.5	13 000*				40.0
44.0	23.1	19.3	13 700 *							44.0
36.5m Boom										
10.7	80.6	50.3	24 700 *							10.7
12.0	79.0	50.0	24 200 *							12.0
14.0	76.6	49.5	23 500 *	79.1	49.2	21 600*				14.0
16.0	74.2	49.0	22 800 *	76.6	48.6	21 200*	79.2	47.9	17 300*	16.0
18.0	71.7	48.3	22 200 *	74.1	47.9	20 800*	76.6	47.2	16 400*	18.0
20.0	69.2	47.5	21 700 *	71.6	47.2	20 400*	74.0	46.4	15 600*	20.0
22.0	66.6	46.6	21 100 *	69.0	46.3	20 000*	71.4	45.5	14 800*	22.0
24.0	64.0	45.7	20 600 *	66.4	45.3	19 700*	68.7	44.5	14 200*	24.0
26.0	61.3	44.6	20 200 *	63.6	44.2	18 900*	65.9	43.4	13 600*	26.0
28.0	58.5	43.3	19 800 *	60.9	42.9	17 800*	63.1	42.1	13 100*	28.0
30.0	55.7	42.0	19 400 *	58.0	41.6	16 800*	60.2	40.7	12 600*	30.0
32.0	52.7	40.4	19 100 *	55.0	40.0	16 100*	57.1	39.1	12 200*	32.0
34.0	49.6	38.7	18 700 *	51.9	38.3	15 300*	53.9	37.4	11 800*	34.0
36.0	46.4	36.8	17 700 *	48.6	36.4	14 700*	50.5	35.4	11 500*	36.0
38.0	42.9	34.7	16 700 *	45.1	34.2	14 000*	46.9	33.1	11 200*	38.0
40.0	39.2	32.3	15 900 *	41.3	31.8	13 500*				40.0
44.0	30.7	26.2	14 500 *	32.6	25.6	12 600*				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	79.5	53.0	24 200 *							12.2
14.0	77.4	52.6	23 600 *	79.8	52.3	21 700*				14.0
16.0	75.1	52.1	23 000 *	77.4	51.7	21 300*	79.8	51.0	17 600*	16.0
18.0	72.8	51.5	22 400 *	75.1	51.1	20 900*	77.5	50.4	16 700*	18.0
20.0	70.4	50.7	21 900 *	72.7	50.4	20 500*	75.0	49.6	15 800*	20.0
22.0	68.0	49.9	21 400 *	70.3	49.6	20 200*	72.6	48.8	15 100*	22.0
24.0	65.6	49.0	20 900 *	67.9	48.6	19 900*	70.1	47.9	14 500*	24.0
26.0	63.1	48.0	20 400 *	65.3	47.6	19 600*	67.5	46.8	13 900*	26.0
28.0	60.6	46.9	20 100 *	62.8	46.5	18 500*	64.9	45.6	13 400*	28.0
30.0	57.9	45.6	19 700 *	60.1	45.2	17 600*	62.2	44.3	12 900*	30.0
32.0	55.2	44.2	19 400 *	57.4	43.8	16 700*	59.4	42.9	12 500*	32.0
34.0	52.4	42.7	19 000 *	54.6	42.2	15 900*	56.5	41.3	12 100*	34.0
36.0	49.5	41.0	18 600 *	51.6	40.5	15 200*	53.5	39.6	11 800*	36.0
38.0	46.5	39.1	17 700 *	48.5	38.6	14 600*	50.4	37.6	11 500*	38.0
40.0	43.3	37.0	16 800 *	45.3	36.5	14 100*	47.0	35.4	11 200*	40.0
44.0	36.1	31.9	15 000	38.0	31.3	13 100*				44.0
48.0	27.3	25.1	13 000							48.0
42.5m Boom										
12.2	80.1	56.1	24 300 *							12.2
14.0	78.1	55.7	23 800 *	80.3	55.4	21 800*				14.0
16.0	76.0	55.2	23 100 *	78.2	54.9	21 300*				16.0
18.0	73.8	54.6	22 600 *	76.0	54.3	21 000*	78.2	53.5	16 900*	18.0
20.0	71.6	53.9	22 000 *	73.7	53.6	20 600*	75.9	52.8	16 200*	20.0
22.0	69.3	53.2	21 600 *	71.5	52.8	20 300*	73.6	52.0	15 400*	22.0
24.0	67.0	52.3	21 100 *	69.2	52.0	20 000*	71.3	51.2	14 800*	24.0
26.0	64.7	51.4	20 700 *	66.8	51.0	19 700*	68.9	50.2	14 200*	26.0
28.0	62.3	50.3	20 300 *	64.5	49.9	19 300*	66.5	49.1	13 700*	28.0
30.0	59.9	49.2	19 900 *	62.0	48.8	18 200*	64.0	47.9	13 200*	30.0
32.0	57.4	47.9	19 600 *	59.5	47.5	17 300*	61.4	46.6	12 800*	32.0
34.0	54.9	46.5	19 300 *	56.9	46.0	16 600*	58.8	45.1	12 400*	34.0
36.0	52.2	44.9	19 000 *	54.2	44.5	15 900*	56.1	43.5	12 100*	36.0
38.0	49.5	43.2	18 700 *	51.4	42.8	15 200*	53.2	41.8	11 800*	38.0
40.0	46.6	41.3	17 400	48.5	40.9	14 600*	50.2	39.8	11 500*	40.0
44.0	40.3	36.9	14 900	42.2	36.4	13 600*	43.7	35.2	11 000*	44.0
48.0	33.1	31.3	12 800	34.8	30.6	12 800				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
12.2	80.6	59.2	24 400 *							12.2
14.0	78.8	58.8	23 800 *							14.0
16.0	76.7	58.3	23 200 *	78.8	58.0	21 400*				16.0
18.0	74.6	57.7	22 700 *	76.7	57.4	21 000*	78.8	56.6	17 200*	18.0
20.0	72.6	57.1	22 200 *	74.6	56.8	20 700*	76.7	56.0	16 400*	20.0
22.0	70.4	56.4	21 700 *	72.5	56.0	20 400*	74.6	55.2	15 700*	22.0
24.0	68.3	55.6	21 300 *	70.3	55.2	20 100*	72.4	54.4	15 100*	24.0
26.0	66.1	54.7	20 900 *	68.1	54.3	19 900*	70.1	53.5	14 500*	26.0
28.0	63.9	53.7	20 500 *	65.9	53.3	19 600*	67.9	52.5	14 000*	28.0
30.0	61.7	52.6	20 100 *	63.6	52.2	18 900*	65.6	51.4	13 500*	30.0
32.0	59.3	51.4	19 800 *	61.3	51.0	18 000*	63.2	50.2	13 100*	32.0
34.0	57.0	50.1	19 500 *	58.9	49.7	17 100*	60.7	48.8	12 700*	34.0
36.0	54.5	48.7	19 200 *	56.5	48.3	16 400*	58.2	47.4	12 300*	36.0
38.0	52.0	47.2	18 500	53.9	46.7	15 800*	55.6	45.8	12 000*	38.0
40.0	49.4	45.4	17 100	51.3	45.0	15 200*	52.9	44.0	11 700*	40.0
44.0	43.8	41.5	14 600	45.6	41.0	14 100*	47.1	39.9	11 200*	44.0
48.0	37.5	36.6	12 500	39.3	36.1	12 700				48.0
52.0	30.2	30.4	10 800							52.0
48.5m Boom										
13.7	79.6	61.9	23 900 *							13.7
14.0	79.3	61.9	23 900 *							14.0
16.0	77.4	61.4	23 300 *	79.4	61.0	21 500*				16.0
18.0	75.4	60.9	22 800 *	77.4	60.5	21 100*	79.4	59.7	17 400*	18.0
20.0	73.5	60.3	22 300 *	75.4	59.9	20 800*	77.4	59.1	16 700*	20.0
22.0	71.5	59.6	21 900 *	73.4	59.2	20 500*	75.4	58.4	16 000*	22.0
24.0	69.4	58.8	21 400 *	71.4	58.5	20 200*	73.3	57.7	15 300*	24.0
26.0	67.4	58.0	21 100 *	69.3	57.6	19 900*	71.2	56.8	14 800*	26.0
28.0	65.3	57.1	20 700 *	67.2	56.7	19 700*	69.1	55.9	14 300*	28.0
30.0	63.2	56.1	20 300 *	65.1	55.7	19 400*	66.9	54.8	13 800*	30.0
32.0	61.0	54.9	20 000 *	62.9	54.5	18 500*	64.7	53.7	13 400*	32.0
34.0	58.8	53.7	19 700 *	60.7	53.3	17 700*	62.4	52.4	13 000*	34.0
36.0	56.6	52.4	19 400 *	58.4	52.0	17 000*	60.1	51.1	12 600*	36.0
38.0	54.2	51.0	18 300	56.0	50.5	16 300*	57.7	49.6	12 300*	38.0
40.0	51.8	49.4	16 800	53.6	48.9	15 700*	55.3	48.0	12 000*	40.0
44.0	46.7	45.8	14 400	48.5	45.3	14 600	50.0	44.3	11 400*	44.0
48.0	41.2	41.5	12 300	42.9	40.9	12 500	44.2	39.8	11 000*	48.0
52.0	34.9	36.1	10 600	36.5	35.5	10 700				52.0
56.0	27.3	29.2	9 100							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
13.7	80.1	65.0	23 900 *							13.7
14.0	79.8	64.9	23 900 *							14.0
16.0	78.0	64.5	23 400 *	79.9	64.1	21 500*				16.0
18.0	76.1	64.0	22 900 *	78.0	63.6	21 100*				18.0
20.0	74.3	63.4	22 400 *	76.1	63.0	20 800*	78.0	62.3	16 800*	20.0
22.0	72.4	62.8	22 000 *	74.2	62.4	20 500*	76.1	61.6	16 200*	22.0
24.0	70.5	62.0	21 600 *	72.3	61.7	20 300*	74.2	60.9	15 600*	24.0
26.0	68.5	61.3	21 200 *	70.4	60.9	20 000*	72.2	60.1	15 000*	26.0
28.0	66.6	60.4	20 800 *	68.4	60.0	19 800*	70.2	59.2	14 500*	28.0
30.0	64.6	59.4	20 500 *	66.4	59.0	19 600*	68.1	58.2	14 100*	30.0
32.0	62.5	58.4	20 100 *	64.3	58.0	19 100*	66.1	57.1	13 600*	32.0
34.0	60.5	57.2	19 800 *	62.2	56.8	18 300*	63.9	56.0	13 200*	34.0
36.0	58.3	56.0	19 400	60.1	55.6	17 500*	61.8	54.7	12 900*	36.0
38.0	56.2	54.7	18 100	57.9	54.2	16 900*	59.6	53.3	12 500*	38.0
40.0	53.9	53.2	16 600	55.7	52.8	16 200*	57.3	51.8	12 200*	40.0
44.0	49.3	49.9	14 100	51.0	49.4	14 400	52.5	48.4	11 700*	44.0
48.0	44.2	46.0	12 100	45.9	45.5	12 300	47.2	44.4	11 200*	48.0
52.0	38.7	41.3	10 400	40.2	40.7	10 500				52.0
56.0	32.3	35.4	8 900	33.7	34.8	9 000				56.0
60.0	24.4	27.7	7 600							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
13.7	80.5	68.0	23 900 *							13.7
14.0	80.3	68.0	23 900 *							14.0
16.0	78.5	67.6	23 400 *	80.3	67.2	21 400*				16.0
18.0	76.8	67.1	22 900 *	78.6	66.7	21 100*				18.0
20.0	75.0	66.5	22 500 *	76.8	66.2	20 800*	78.6	65.4	17 100*	20.0
22.0	73.2	65.9	22 000 *	75.0	65.6	20 600*	76.8	64.8	16 400*	22.0
24.0	71.4	65.2	21 700 *	73.1	64.9	20 400*	74.9	64.1	15 800*	24.0
26.0	69.5	64.5	21 300 *	71.3	64.1	20 100*	73.1	63.3	15 300*	26.0
28.0	67.7	63.7	20 900 *	69.4	63.3	19 900*	71.2	62.5	14 800*	28.0
30.0	65.8	62.8	20 600 *	67.5	62.4	19 700*	69.2	61.5	14 300*	30.0
32.0	63.9	61.8	20 300 *	65.6	61.4	19 500*	67.3	60.5	13 900*	32.0
34.0	61.9	60.7	20 000 *	63.6	60.3	18 900*	65.3	59.4	13 500*	34.0
36.0	59.9	59.5	19 400	61.6	59.1	18 100*	63.2	58.2	13 100*	36.0
38.0	57.9	58.3	17 900	59.6	57.9	17 400*	61.2	57.0	12 800*	38.0
40.0	55.8	56.9	16 400	57.5	56.5	16 600	59.0	55.6	12 500*	40.0
44.0	51.5	53.9	13 900	53.1	53.4	14 200	54.6	52.4	11 900*	44.0
48.0	46.9	50.3	11 900	48.5	49.8	12 100	49.8	48.7	11 400*	48.0
52.0	41.9	46.0	10 100	43.4	45.5	10 400				52.0
56.0	36.3	40.9	8 700	37.7	40.3	8 800				56.0
60.0	29.8	34.5	7 400							60.0
64.0	21.5	25.7	6 300							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
13.7	81.0	71.1	23 900 *							13.7
14.0	80.7	71.0	23 800 *							14.0
16.0	79.0	70.6	23 400 *							16.0
18.0	77.4	70.2	22 900 *	79.1	69.8	21 100*				18.0
20.0	75.7	69.7	22 500 *	77.4	69.3	20 800*	79.1	68.5	17 300*	20.0
22.0	73.9	69.1	22 100 *	75.6	68.7	20 600*	77.4	67.9	16 600*	22.0
24.0	72.2	68.4	21 700 *	73.9	68.1	20 400*	75.6	67.2	16 000*	24.0
26.0	70.5	67.7	21 400 *	72.2	67.3	20 100*	73.8	66.5	15 500*	26.0
28.0	68.7	66.9	21 000 *	70.4	66.5	19 900*	72.0	65.7	15 000*	28.0
30.0	66.9	66.1	20 700 *	68.6	65.7	19 700*	70.2	64.8	14 500*	30.0
32.0	65.1	65.1	20 400 *	66.7	64.7	19 500*	68.4	63.9	14 100*	32.0
34.0	63.2	64.1	20 100 *	64.9	63.7	19 300*	66.5	62.9	13 700*	34.0
36.0	61.4	63.0	19 300	63.0	62.6	18 600*	64.6	61.7	13 300*	36.0
38.0	59.5	61.8	17 600	61.1	61.4	17 900*	62.6	60.5	13 000*	38.0
40.0	57.5	60.6	16 100	59.1	60.1	16 500	60.6	59.2	12 700*	40.0
44.0	53.5	57.7	13 600	55.0	57.3	13 900	56.5	56.3	12 100*	44.0
48.0	49.2	54.4	11 600	50.7	53.9	11 800	52.1	52.9	11 600*	48.0
52.0	44.6	50.5	9 900	46.1	50.0	10 100	47.3	48.9	10 300	52.0
56.0	39.6	45.9	8 400	41.0	45.3	8 600				56.0
60.0	34.0	40.3	7 100	35.3	39.7	7 200				60.0
64.0	27.3	33.3	6 000							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
15.2	80.1	73.8	23 500 *							15.2
16.0	79.5	73.7	23 300 *							16.0
18.0	77.9	73.3	22 900 *	79.5	72.9	21 100*				18.0
20.0	76.3	72.8	22 500 *	77.9	72.4	20 800*	79.6	71.6	17 400*	20.0
22.0	74.6	72.2	22 100 *	76.3	71.8	20 600*	77.9	71.0	16 800*	22.0
24.0	73.0	71.6	21 800 *	74.6	71.2	20 400*	76.2	70.4	16 200*	24.0
26.0	71.3	70.9	21 400 *	72.9	70.5	20 200*	74.6	69.7	15 700*	26.0
28.0	69.6	70.2	21 100 *	71.2	69.8	20 000*	72.8	68.9	15 200*	28.0
30.0	67.9	69.3	20 800 *	69.5	68.9	19 800*	71.1	68.1	14 800*	30.0
32.0	66.2	68.4	20 500 *	67.8	68.1	19 600*	69.3	67.2	14 300*	32.0
34.0	64.4	67.5	20 200	66.0	67.1	19 500*	67.6	66.2	13 900*	34.0
36.0	62.7	66.4	19 100	64.2	66.0	19 100*	65.7	65.2	13 600*	36.0
38.0	60.9	65.3	17 400	62.4	64.9	17 800	63.9	64.0	13 200*	38.0
40.0	59.0	64.1	15 900	60.6	63.7	16 300	62.0	62.8	12 900*	40.0
44.0	55.2	61.4	13 400	56.7	61.0	13 700	58.1	60.0	12 300*	44.0
48.0	51.2	58.3	11 300	52.7	57.9	11 600	54.0	56.9	11 800	48.0
52.0	47.0	54.8	9 600	48.4	54.3	9 900	49.7	53.2	10 100	52.0
56.0	42.4	50.6	8 100	43.8	50.0	8 300	45.0	48.9	8 500	56.0
60.0	37.4	45.6	6 900	38.7	45.0	7 000				60.0
64.0	31.7	39.6	5 800	32.9	38.9	5 900				64.0
68.0	24.8	31.8	4 800							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
15.2	80.5	76.9	23 400 *							15.2
16.0	79.9	76.7	23 200 *							16.0
18.0	78.4	76.3	22 900 *	80.0	76.0	21 100*				18.0
20.0	76.8	75.9	22 500 *	78.4	75.5	20 800*	80.0	74.7	17 600*	20.0
22.0	75.2	75.3	22 100 *	76.8	75.0	20 600*	78.4	74.1	17 000*	22.0
24.0	73.7	74.7	21 800 *	75.2	74.4	20 400*	76.8	73.5	16 400*	24.0
26.0	72.1	74.1	21 400 *	73.6	73.7	20 200*	75.2	72.9	15 900*	26.0
28.0	70.5	73.4	21 100 *	72.0	73.0	20 000*	73.6	72.1	15 400*	28.0
30.0	68.8	72.6	20 800 *	70.4	72.2	19 800*	71.9	71.4	15 000*	30.0
32.0	67.2	71.7	20 500 *	68.7	71.3	19 600*	70.2	70.5	14 600*	32.0
34.0	65.5	70.8	20 200	67.1	70.4	19 500*	68.5	69.6	14 100*	34.0
36.0	63.8	69.8	18 800	65.4	69.4	19 100	66.8	68.6	13 800*	36.0
38.0	62.1	68.8	17 100	63.6	68.4	17 600	65.1	67.5	13 400*	38.0
40.0	60.4	67.6	15 700	61.9	67.2	16 100	63.3	66.3	13 100*	40.0
44.0	56.8	65.1	13 200	58.3	64.7	13 500	59.6	63.7	12 500*	44.0
48.0	53.1	62.2	11 100	54.5	61.7	11 400	55.8	60.7	11 800	48.0
52.0	49.1	58.8	9 400	50.5	58.4	9 600	51.7	57.3	9 900	52.0
56.0	44.9	55.0	7 900	46.3	54.5	8 100	47.4	53.3	8 300	56.0
60.0	40.3	50.5	6 600	41.7	49.9	6 800				60.0
64.0	35.3	45.2	5 500	36.5	44.5	5 700				64.0
68.0	29.5	38.6	4 500							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
15.2	80.9	79.9	23 300 *							15.2
16.0	80.3	79.8	23 200 *							16.0
18.0	78.8	79.4	22 800 *							18.0
20.0	77.3	78.9	22 500 *	78.9	78.6	20 800*	80.4	77.8	17 800*	20.0
22.0	75.8	78.4	22 100 *	77.3	78.1	20 600*	78.9	77.3	17 200*	22.0
24.0	74.3	77.9	21 800 *	75.8	77.5	20 400*	77.4	76.7	16 600*	24.0
26.0	72.8	77.2	21 500 *	74.3	76.9	20 200*	75.8	76.0	16 100*	26.0
28.0	71.2	76.6	21 100 *	72.7	76.2	20 000*	74.2	75.3	15 600*	28.0
30.0	69.7	75.8	20 900 *	71.2	75.4	19 800*	72.7	74.6	15 200*	30.0
32.0	68.1	75.0	20 600 *	69.6	74.6	19 600*	71.1	73.8	14 700*	32.0
34.0	66.5	74.1	20 200	68.0	73.7	19 500*	69.4	72.9	14 400*	34.0
36.0	64.9	73.2	18 500	66.4	72.8	19 000	67.8	71.9	14 000*	36.0
38.0	63.3	72.2	16 900	64.7	71.8	17 400	66.1	70.9	13 700*	38.0
40.0	61.6	71.1	15 400	63.1	70.7	15 900	64.4	69.8	13 300*	40.0
44.0	58.2	68.7	12 900	59.7	68.3	13 300	61.0	67.3	12 700*	44.0
48.0	54.7	66.0	10 900	56.1	65.5	11 200	57.4	64.5	11 500	48.0
52.0	51.0	62.8	9 100	52.4	62.3	9 400	53.6	61.3	9 700	52.0
56.0	47.1	59.2	7 700	48.4	58.7	7 900	49.6	57.6	8 100	56.0
60.0	42.9	55.1	6 400	44.2	54.6	6 600	45.2	53.4	6 800	60.0
64.0	38.3	50.3	5 300	39.6	49.7	5 500				64.0
68.0	33.2	44.5	4 300	34.4	43.9	4 400				68.0
72.0	27.3	37.4	3 500							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	80.1	82.7	22 900 *							16.8
18.0	79.2	82.5	22 700 *							18.0
20.0	77.8	82.0	22 400 *	79.3	81.7	20 700*	80.8	80.8	17 900*	20.0
22.0	76.4	81.5	22 000 *	77.8	81.2	20 500*	79.3	80.3	17 400*	22.0
24.0	74.9	81.0	21 700 *	76.4	80.6	20 300*	77.8	79.8	16 800*	24.0
26.0	73.4	80.4	21 400 *	74.9	80.0	20 100*	76.4	79.2	16 300*	26.0
28.0	72.0	79.7	21 100 *	73.4	79.4	19 900*	74.9	78.5	15 800*	28.0
30.0	70.5	79.0	20 800 *	71.9	78.6	19 800*	73.3	77.8	15 400*	30.0
32.0	69.0	78.2	20 600 *	70.4	77.9	19 600*	71.8	77.0	14 900*	32.0
34.0	67.4	77.4	19 700	68.9	77.0	19 400	70.3	76.2	14 600*	34.0
36.0	65.9	76.5	18 000	67.3	76.1	18 700	68.7	75.2	14 200*	36.0
38.0	64.3	75.5	16 500	65.8	75.1	17 000	67.1	74.3	13 800*	38.0
40.0	62.8	74.5	15 100	64.2	74.1	15 600	65.5	73.2	13 500*	40.0
44.0	59.5	72.2	12 600	60.9	71.8	13 000	62.2	70.9	12 900*	44.0
48.0	56.2	69.6	10 600	57.5	69.2	10 900	58.8	68.2	11 200	48.0
52.0	52.7	66.7	8 800	54.0	66.2	9 100	55.2	65.2	9 400	52.0
56.0	49.0	63.3	7 300	50.3	62.8	7 600	51.5	61.8	7 800	56.0
60.0	45.1	59.5	6 100	46.4	59.0	6 300	47.5	57.8	6 500	60.0
64.0	41.0	55.1	5 000	42.2	54.5	5 200	43.2	53.3	5 300	64.0
68.0	36.4	49.9	4 000	37.6	49.3	4 200				68.0
72.0	31.2	43.7	3 100							72.0
76.0	25.1	36.0	2 400							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
16.8	80.5	85.8	22 800 *							16.8
18.0	79.6	85.5	22 600 *							18.0
20.0	78.2	85.1	22 300 *	79.7	84.7	20 600*				20.0
22.0	76.9	84.6	21 900 *	78.3	84.3	20 400*	79.7	83.4	17 500*	22.0
24.0	75.5	84.1	21 600 *	76.9	83.7	20 300*	78.3	82.9	17 000*	24.0
26.0	74.0	83.5	21 300 *	75.4	83.1	20 100*	76.9	82.3	16 400*	26.0
28.0	72.6	82.9	21 100 *	74.0	82.5	19 900*	75.4	81.7	16 000*	28.0
30.0	71.2	82.2	20 800 *	72.6	81.8	19 700*	74.0	81.0	15 500*	30.0
32.0	69.7	81.5	20 600 *	71.1	81.1	19 600*	72.5	80.2	15 100*	32.0
34.0	68.3	80.7	19 100	69.7	80.3	19 300	71.0	79.4	14 700*	34.0
36.0	66.8	79.8	17 500	68.2	79.4	18 100	69.5	78.5	14 400*	36.0
38.0	65.3	78.9	16 100	66.7	78.5	16 600	68.0	77.6	14 000*	38.0
40.0	63.8	77.9	14 800	65.2	77.5	15 300	66.5	76.6	13 700*	40.0
44.0	60.7	75.7	12 400	62.1	75.3	12 800	63.3	74.4	13 100	44.0
48.0	57.6	73.2	10 300	58.9	72.8	10 700	60.1	71.9	11 000	48.0
52.0	54.2	70.5	8 600	55.5	70.0	8 900	56.7	69.0	9 200	52.0
56.0	50.8	67.3	7 100	52.1	66.8	7 400	53.2	65.8	7 600	56.0
60.0	47.2	63.7	5 900	48.4	63.2	6 100	49.5	62.1	6 300	60.0
64.0	43.3	59.6	4 800	44.5	59.1	4 900	45.5	57.9	5 100	64.0
68.0	39.1	54.9	3 800	40.3	54.3	3 900				68.0
72.0	34.5	49.4	2 900	35.6	48.7	3 000				72.0
76.0	29.2	42.7	2 100							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
16.8	80.8	88.8	22 600 *							16.8
18.0	80.0	88.6	22 400 *							18.0
20.0	78.7	88.2	22 100 *	80.0	87.8	20 500*				20.0
22.0	77.3	87.7	21 800 *	78.7	87.3	20 300*	80.1	86.5	17 700*	22.0
24.0	76.0	87.2	21 500 *	77.3	86.8	20 100*	78.7	86.0	17 100*	24.0
26.0	74.6	86.7	21 300 *	76.0	86.3	20 000*	77.3	85.4	16 600*	26.0
28.0	73.2	86.1	21 000 *	74.6	85.7	19 800*	75.9	84.8	16 100*	28.0
30.0	71.9	85.4	20 700 *	73.2	85.0	19 700*	74.5	84.2	15 700*	30.0
32.0	70.5	84.7	20 500 *	71.8	84.3	19 500*	73.1	83.4	15 300*	32.0
34.0	69.1	83.9	19 000	70.4	83.5	19 300	71.7	82.7	14 900*	34.0
36.0	67.7	83.1	17 400	69.0	82.7	18 100	70.3	81.8	14 600*	36.0
38.0	66.2	82.2	16 000	67.5	81.8	16 500	68.8	80.9	14 200*	38.0
40.0	64.8	81.3	14 700	66.1	80.8	15 200	67.4	80.0	13 900*	40.0
44.0	61.8	79.2	12 400	63.1	78.7	12 900	64.4	77.8	13 200	44.0
48.0	58.8	76.8	10 400	60.1	76.4	10 700	61.3	75.4	11 100	48.0
52.0	55.7	74.2	8 600	56.9	73.7	9 000	58.1	72.7	9 300	52.0
56.0	52.4	71.2	7 200	53.6	70.7	7 500	54.7	69.7	7 700	56.0
60.0	49.0	67.8	5 900	50.2	67.3	6 200	51.2	66.2	6 400	60.0
64.0	45.4	64.0	4 800	46.5	63.5	5 000	47.5	62.3	5 200	64.0
68.0	41.5	59.6	3 900	42.6	59.1	4 000	43.5	57.8	4 200	68.0
72.0	37.3	54.6	3 000	38.4	54.0	3 100				72.0
76.0	32.7	48.7	2 200	33.7	48.0	2 300				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
18.3	80.1	91.6	22 200 *							18.3
20.0	79.0	91.2	22 000 *	80.4	90.9	20 400*				20.0
22.0	77.7	90.8	21 700 *	79.1	90.4	20 200*	80.4	89.6	17 800*	22.0
24.0	76.4	90.3	21 400 *	77.8	89.9	20 000*	79.1	89.1	17 300*	24.0
26.0	75.1	89.8	21 100 *	76.4	89.4	19 900*	77.8	88.6	16 800*	26.0
28.0	73.8	89.2	20 900 *	75.1	88.8	19 700*	76.4	88.0	16 300*	28.0
30.0	72.5	88.6	20 600 *	73.8	88.2	19 600*	75.1	87.3	15 900*	30.0
32.0	71.1	87.9	20 300	72.4	87.5	19 500*	73.7	86.6	15 500*	32.0
34.0	69.8	87.1	18 500	71.1	86.7	19 100	72.4	85.9	15 100*	34.0
36.0	68.4	86.3	17 000	69.7	85.9	17 600	71.0	85.1	14 700*	36.0
38.0	67.1	85.5	15 600	68.3	85.1	16 100	69.6	84.2	14 400*	38.0
40.0	65.7	84.6	14 300	67.0	84.2	14 800	68.2	83.3	14 100*	40.0
44.0	62.9	82.6	12 100	64.1	82.2	12 600	65.3	81.3	13 000	44.0
48.0	60.0	80.3	10 200	61.2	79.9	10 500	62.4	79.0	10 900	48.0
52.0	57.0	77.8	8 400	58.2	77.4	8 800	59.3	76.4	9 100	52.0
56.0	53.9	75.0	6 900	55.1	74.5	7 300	56.1	73.5	7 500	56.0
60.0	50.6	71.8	5 700	51.8	71.3	5 900	52.8	70.2	6 200	60.0
64.0	47.2	68.2	4 600	48.4	67.7	4 800	49.4	66.6	5 000	64.0
68.0	43.6	64.1	3 600	44.8	63.6	3 800	45.7	62.4	4 000	68.0
72.0	39.8	59.5	2 700	40.9	58.9	2 900				72.0
76.0	35.6	54.2	2 000	36.6	53.5	2 100				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
18.3	80.5	94.6	22 000 *							18.3
20.0	79.4	94.3	21 700 *	80.7	93.9	20 200*				20.0
22.0	78.1	93.9	21 500 *	79.4	93.5	20 000*				22.0
24.0	76.9	93.4	21 200 *	78.2	93.0	19 900*	79.5	92.2	17 400*	24.0
26.0	75.6	92.9	20 900 *	76.9	92.5	19 700*	78.2	91.7	16 900*	26.0
28.0	74.3	92.3	20 700 *	75.6	91.9	19 600*	76.9	91.1	16 500*	28.0
30.0	73.1	91.7	20 500 *	74.3	91.3	19 400*	75.6	90.5	16 000*	30.0
32.0	71.8	91.0	19 700	73.0	90.7	19 300*	74.3	89.8	15 600*	32.0
34.0	70.5	90.3	18 000	71.7	89.9	18 800	73.0	89.1	15 200*	34.0
36.0	69.2	89.6	16 500	70.4	89.2	17 100	71.6	88.3	14 900*	36.0
38.0	67.8	88.8	15 100	69.1	88.3	15 700	70.3	87.5	14 600*	38.0
40.0	66.5	87.9	13 800	67.7	87.5	14 400	68.9	86.6	14 200*	40.0
44.0	63.8	86.0	11 700	65.0	85.5	12 100	66.2	84.6	12 500	44.0
48.0	61.0	83.8	9 800	62.2	83.4	10 200	63.4	82.4	10 600	48.0
52.0	58.2	81.4	8 100	59.3	80.9	8 400	60.4	80.0	8 800	52.0
56.0	55.2	78.7	6 600	56.4	78.2	6 900	57.4	77.2	7 300	56.0
60.0	52.1	75.6	5 400	53.3	75.2	5 600	54.3	74.1	5 900	60.0
64.0	48.9	72.3	4 300	50.1	71.8	4 500	51.0	70.7	4 700	64.0
68.0	45.6	68.5	3 300	46.7	67.9	3 500	47.6	66.8	3 700	68.0
72.0	42.0	64.2	2 400	43.0	63.6	2 600				72.0
76.0				39.1	58.7	1 800				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
10.7	79.6	44.2	20 500 *							10.7
12.0	77.8	43.9	20 000 *							12.0
14.0	75.0	43.3	19 300 *	78.6	43.0	17 900*				14.0
16.0	72.2	42.7	18 600 *	75.7	42.3	17 300*	79.4	41.5	14 400*	16.0
18.0	69.3	41.9	18 000 *	72.8	41.5	16 800*	76.4	40.7	13 400*	18.0
20.0	66.4	41.0	17 400 *	69.9	40.6	16 300*	73.4	39.8	12 500*	20.0
22.0	63.4	40.0	16 800 *	66.8	39.6	15 700*	70.3	38.7	11 700*	22.0
24.0	60.2	38.8	16 200 *	63.7	38.4	14 600*	67.1	37.5	11 100*	24.0
26.0	57.0	37.5	15 700 *	60.4	37.1	13 700*	63.7	36.2	10 500*	26.0
28.0	53.7	36.0	15 200 *	57.1	35.6	12 800*	60.2	34.6	10 000*	28.0
30.0	50.2	34.3	14 700 *	53.5	33.9	12 100*	56.6	32.9	9 600*	30.0
32.0	46.5	32.4	13 800 *	49.7	31.9	11 500*	52.7	30.9	9 200*	32.0
34.0	42.5	30.2	13 000 *	45.7	29.7	10 900*	48.5	28.5	8 900*	34.0
36.0	38.2	27.7	12 200 *	41.3	27.1	10 400*				36.0
38.0	33.4	24.7	11 500 *	36.3	24.1	10 000*				38.0
40.0	27.7	21.0	11 000 *							40.0
30.5m Boom										
10.7	80.3	47.3	20 600 *							10.7
12.0	78.6	47.0	20 200 *							12.0
14.0	76.0	46.5	19 500 *	79.4	46.1	18 000*				14.0
16.0	73.4	45.9	18 800 *	76.7	45.5	17 500*				16.0
18.0	70.7	45.1	18 300 *	74.0	44.8	16 900*	77.4	43.9	13 600*	18.0
20.0	68.0	44.3	17 700 *	71.3	43.9	16 500*	74.6	43.1	12 800*	20.0
22.0	65.3	43.4	17 100 *	68.5	43.0	16 100*	71.8	42.1	12 100*	22.0
24.0	62.4	42.3	16 600 *	65.6	41.9	15 300*	68.8	41.0	11 400*	24.0
26.0	59.5	41.1	16 100 *	62.7	40.7	14 300*	65.8	39.8	10 900*	26.0
28.0	56.5	39.8	15 600 *	59.6	39.3	13 500*	62.7	38.4	10 400*	28.0
30.0	53.3	38.3	15 200 *	56.5	37.8	12 700*	59.4	36.8	9 900*	30.0
32.0	50.1	36.6	14 700 *	53.1	36.1	12 100*	56.0	35.1	9 500*	32.0
34.0	46.6	34.7	13 900 *	49.6	34.2	11 500*	52.3	33.1	9 200*	34.0
36.0	42.9	32.5	13 000 *	45.9	32.0	10 900*	48.5	30.8	8 900*	36.0
38.0	38.9	30.0	12 300 *	41.8	29.5	10 500*	44.2	28.2	8 600*	38.0
40.0	34.6	27.2	11 700 *	37.3	26.5	10 100*				40.0
44.0	23.6	19.4	10 600 *							44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
10.7	80.9	50.3	20 800 *							10.7
12.0	79.3	50.1	20 300 *							12.0
14.0	76.9	49.6	19 600 *	80.1	49.2	18 100*				14.0
16.0	74.5	49.0	19 000 *	77.6	48.6	17 600*				16.0
18.0	72.0	48.3	18 500 *	75.1	47.9	17 100*	78.2	47.1	14 000*	18.0
20.0	69.5	47.6	18 000 *	72.6	47.2	16 600*	75.7	46.3	13 100*	20.0
22.0	66.9	46.7	17 400 *	70.0	46.3	16 200*	73.0	45.4	12 400*	22.0
24.0	64.3	45.7	16 900 *	67.3	45.3	15 800*	70.3	44.4	11 800*	24.0
26.0	61.6	44.6	16 400 *	64.6	44.2	14 900*	67.5	43.3	11 200*	26.0
28.0	58.8	43.4	15 900 *	61.8	42.9	14 000*	64.7	42.0	10 700*	28.0
30.0	56.0	42.0	15 500 *	58.9	41.6	13 300*	61.7	40.6	10 300*	30.0
32.0	53.0	40.5	15 100 *	55.9	40.0	12 600*	58.7	39.0	9 800*	32.0
34.0	49.9	38.8	14 700 *	52.8	38.3	12 000*	55.4	37.2	9 500*	34.0
36.0	46.7	36.9	13 900 *	49.5	36.4	11 400*	52.1	35.3	9 100*	36.0
38.0	43.3	34.8	13 100 *	46.0	34.2	10 900*	48.4	33.0	8 900*	38.0
40.0	39.6	32.4	12 400 *	42.3	31.8	10 500*				40.0
44.0	31.1	26.3	11 200 *	33.6	25.6	9 800*				44.0
36.5m Boom										
12.2	79.7	53.1	20 300 *							12.2
14.0	77.7	52.7	19 800 *	80.7	52.3	18 200*				14.0
16.0	75.4	52.1	19 200 *	78.3	51.7	17 700*				16.0
18.0	73.1	51.5	18 700 *	76.0	51.1	17 300*	79.0	50.3	14 200*	18.0
20.0	70.7	50.8	18 100 *	73.6	50.4	16 800*	76.6	49.5	13 400*	20.0
22.0	68.3	50.0	17 700 *	71.2	49.6	16 400*	74.1	48.7	12 700*	22.0
24.0	65.9	49.1	17 200 *	68.8	48.6	16 000*	71.6	47.7	12 100*	24.0
26.0	63.4	48.0	16 700 *	66.2	47.6	15 500*	69.0	46.7	11 500*	26.0
28.0	60.9	46.9	16 200 *	63.7	46.5	14 600*	66.4	45.5	11 000*	28.0
30.0	58.2	45.7	15 800 *	61.0	45.2	13 800*	63.7	44.2	10 500*	30.0
32.0	55.5	44.3	15 400 *	58.3	43.8	13 100*	60.9	42.8	10 100*	32.0
34.0	52.7	42.7	15 100 *	55.5	42.3	12 500*	58.0	41.2	9 800*	34.0
36.0	49.8	41.0	14 600 *	52.5	40.5	11 900*	55.0	39.4	9 400*	36.0
38.0	46.8	39.1	13 900 *	49.4	38.6	11 400*	51.8	37.5	9 100*	38.0
40.0	43.6	37.0	13 200 *	46.2	36.5	11 000*	48.4	35.2	8 900*	40.0
44.0	36.4	32.0	11 900 *	38.9	31.3	10 200*				44.0
48.0	27.7	25.2	10 900 *							48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	80.3	56.1	20 400 *							12.2
14.0	78.4	55.8	19 900 *							14.0
16.0	76.2	55.2	19 300 *	79.0	54.9	17 800*				16.0
18.0	74.0	54.7	18 800 *	76.8	54.3	17 400*	79.6	53.4	14 400*	18.0
20.0	71.8	54.0	18 300 *	74.6	53.6	17 000*	77.4	52.7	13 600*	20.0
22.0	69.6	53.2	17 900 *	72.3	52.8	16 600*	75.1	51.9	12 900*	22.0
24.0	67.3	52.4	17 400 *	70.0	51.9	16 200*	72.7	51.0	12 300*	24.0
26.0	65.0	51.4	16 900 *	67.7	51.0	15 800*	70.3	50.1	11 800*	26.0
28.0	62.6	50.4	16 500 *	65.3	49.9	15 200*	67.9	49.0	11 300*	28.0
30.0	60.2	49.2	16 100 *	62.9	48.8	14 300*	65.4	47.8	10 800*	30.0
32.0	57.7	47.9	15 700 *	60.3	47.5	13 600*	62.8	46.5	10 400*	32.0
34.0	55.1	46.5	15 300 *	57.8	46.0	13 000*	60.2	45.0	10 000*	34.0
36.0	52.5	45.0	15 000 *	55.1	44.5	12 400*	57.4	43.4	9 700*	36.0
38.0	49.7	43.3	14 700 *	52.3	42.8	11 900*	54.6	41.6	9 400*	38.0
40.0	46.9	41.4	13 900 *	49.4	40.8	11 400*	51.6	39.7	9 100*	40.0
44.0	40.6	37.0	12 600 *	43.0	36.4	10 600*	45.0	35.0	8 700*	44.0
48.0	33.4	31.4	11 500 *	35.7	30.6	10 000*				48.0
42.5m Boom										
12.2	80.8	59.2	20 500 *							12.2
14.0	79.0	58.8	20 000 *							14.0
16.0	77.0	58.4	19 400 *	79.6	58.0	17 900*				16.0
18.0	74.9	57.8	18 900 *	77.5	57.4	17 500*				18.0
20.0	72.8	57.2	18 500 *	75.4	56.8	17 100*	78.1	55.9	13 900*	20.0
22.0	70.7	56.4	18 000 *	73.3	56.0	16 700*	75.9	55.1	13 200*	22.0
24.0	68.6	55.6	17 600 *	71.1	55.2	16 300*	73.7	54.3	12 600*	24.0
26.0	66.4	54.8	17 200 *	69.0	54.3	16 000*	71.5	53.4	12 000*	26.0
28.0	64.2	53.8	16 700 *	66.7	53.3	15 600*	69.2	52.4	11 500*	28.0
30.0	61.9	52.7	16 300 *	64.4	52.2	14 900*	66.9	51.3	11 100*	30.0
32.0	59.6	51.5	16 000 *	62.1	51.0	14 100*	64.5	50.0	10 700*	32.0
34.0	57.2	50.2	15 600 *	59.7	49.7	13 500*	62.1	48.7	10 300*	34.0
36.0	54.8	48.8	15 300 *	57.3	48.3	12 900*	59.5	47.2	9 900*	36.0
38.0	52.3	47.2	15 000 *	54.7	46.7	12 400*	56.9	45.6	9 600*	38.0
40.0	49.7	45.5	14 600 *	52.1	45.0	11 800*	54.2	43.8	9 400*	40.0
44.0	44.1	41.6	13 300 *	46.4	41.0	11 000*	48.4	39.7	8 900*	44.0
48.0	37.8	36.7	12 100 *	40.1	36.0	10 300*				48.0
52.0	30.5	30.5	11 200							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	79.8	62.0	20 100 *							13.7
14.0	79.5	61.9	20 000 *							14.0
16.0	77.6	61.4	19 500 *	80.1	61.0	17 900*				16.0
18.0	75.7	60.9	19 000 *	78.2	60.5	17 600*				18.0
20.0	73.7	60.3	18 600 *	76.2	59.9	17 200*	78.7	59.0	14 100*	20.0
22.0	71.7	59.6	18 100 *	74.2	59.2	16 800*	76.7	58.3	13 400*	22.0
24.0	69.7	58.9	17 700 *	72.1	58.5	16 500*	74.6	57.5	12 800*	24.0
26.0	67.6	58.0	17 400 *	70.1	57.6	16 200*	72.5	56.7	12 300*	26.0
28.0	65.5	57.1	17 000 *	68.0	56.7	15 900*	70.4	55.7	11 800*	28.0
30.0	63.4	56.1	16 600 *	65.8	55.7	15 400*	68.2	54.7	11 300*	30.0
32.0	61.3	55.0	16 200 *	63.7	54.5	14 600*	66.0	53.5	10 900*	32.0
34.0	59.1	53.8	15 800 *	61.4	53.3	13 900*	63.7	52.3	10 500*	34.0
36.0	56.8	52.5	15 500 *	59.2	52.0	13 300*	61.4	50.9	10 200*	36.0
38.0	54.5	51.0	15 200 *	56.8	50.5	12 800*	59.0	49.4	9 900*	38.0
40.0	52.1	49.4	14 900 *	54.4	48.9	12 300*	56.5	47.8	9 600*	40.0
44.0	47.0	45.9	13 900 *	49.3	45.3	11 400*	51.2	44.1	9 100*	44.0
48.0	41.5	41.5	12 700	43.6	40.9	10 700*	45.4	39.6	8 700*	48.0
52.0	35.2	36.2	11 000	37.2	35.5	10 000*				52.0
56.0	27.6	29.3	9 500							56.0
48.5m Boom										
13.7	80.3	65.0	20 100 *							13.7
14.0	80.0	65.0	20 100 *							14.0
16.0	78.2	64.5	19 600 *							16.0
18.0	76.3	64.0	19 100 *	78.7	63.6	17 600 *				18.0
20.0	74.5	63.5	18 700 *	76.9	63.0	17 300*	79.3	62.1	14 300*	20.0
22.0	72.6	62.8	18 300 *	75.0	62.4	16 900*	77.3	61.5	13 600*	22.0
24.0	70.7	62.1	17 900 *	73.0	61.7	16 600*	75.4	60.7	13 000*	24.0
26.0	68.7	61.3	17 500 *	71.1	60.9	16 300*	73.4	59.9	12 500*	26.0
28.0	66.8	60.4	17 200 *	69.1	60.0	16 000*	71.4	59.0	12 000*	28.0
30.0	64.8	59.5	16 800 *	67.1	59.0	15 700*	69.3	58.1	11 600*	30.0
32.0	62.8	58.4	16 400 *	65.1	58.0	15 100*	67.3	57.0	11 200*	32.0
34.0	60.7	57.3	16 100 *	63.0	56.8	14 400*	65.1	55.8	10 700*	34.0
36.0	58.6	56.1	15 700 *	60.8	55.6	13 800*	63.0	54.5	10 400*	36.0
38.0	56.4	54.7	15 400 *	58.6	54.2	13 200*	60.7	53.2	10 100*	38.0
40.0	54.2	53.3	15 100 *	56.4	52.8	12 700*	58.4	51.7	9 800*	40.0
44.0	49.5	50.0	14 600	51.7	49.4	11 800*	53.6	48.3	9 300*	44.0
48.0	44.5	46.1	12 600	46.6	45.5	11 000*	48.4	44.2	8 900*	48.0
52.0	38.9	41.4	10 800	41.0	40.7	10 400*				52.0
56.0	32.6	35.5	9 300	34.5	34.7	9 500				56.0
60.0	24.7	27.8	8 100							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
13.7	80.7	68.1	20 100 *							13.7
14.0	80.5	68.0	20 100 *							14.0
16.0	78.7	67.6	19 600 *							16.0
18.0	77.0	67.1	19 100 *	79.3	66.7	17 700*				18.0
20.0	75.2	66.6	18 700 *	77.5	66.2	17 400*	79.8	65.2	14 500*	20.0
22.0	73.4	66.0	18 400 *	75.7	65.5	17 000*	77.9	64.6	13 800*	22.0
24.0	71.6	65.3	18 000 *	73.8	64.9	16 700*	76.1	63.9	13 200*	24.0
26.0	69.8	64.5	17 600 *	72.0	64.1	16 400*	74.2	63.2	12 700*	26.0
28.0	67.9	63.7	17 300 *	70.1	63.3	16 100*	72.3	62.3	12 200*	28.0
30.0	66.0	62.8	17 000 *	68.2	62.4	15 900*	70.4	61.4	11 800*	30.0
32.0	64.1	61.8	16 600 *	66.3	61.4	15 500*	68.4	60.4	11 400*	32.0
34.0	62.1	60.8	16 200 *	64.3	60.3	14 800*	66.4	59.3	11 000*	34.0
36.0	60.2	59.6	15 900 *	62.3	59.1	14 200*	64.4	58.1	10 600*	36.0
38.0	58.1	58.3	15 600 *	60.3	57.9	13 600*	62.3	56.8	10 300*	38.0
40.0	56.1	57.0	15 300 *	58.2	56.5	13 100*	60.2	55.4	10 000*	40.0
44.0	51.7	53.9	14 400	53.8	53.4	12 200*	55.7	52.2	9 500*	44.0
48.0	47.1	50.3	12 300	49.1	49.8	11 400*	50.9	48.5	9 100*	48.0
52.0	42.1	46.1	10 600	44.1	45.5	10 700	45.7	44.1	8 700*	52.0
56.0	36.5	41.0	9 100	38.4	40.3	9 300				56.0
60.0	30.0	34.6	7 900							60.0
64.0	21.8	25.9	6 700							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	79.9	70.8	19 800 *							15.2
16.0	79.2	70.7	19 600 *							16.0
18.0	77.6	70.2	19 200 *	79.7	69.8	17 700 *				18.0
20.0	75.9	69.7	18 800 *	78.0	69.3	17 400 *	80.2	68.4	14 700 *	20.0
22.0	74.1	69.1	18 400 *	76.3	68.7	17 100 *	78.5	67.8	14 000 *	22.0
24.0	72.4	68.5	18 100 *	74.6	68.0	16 800 *	76.7	67.1	13 400 *	24.0
26.0	70.7	67.8	17 700 *	72.8	67.3	16 500 *	74.9	66.4	12 900 *	26.0
28.0	68.9	67.0	17 400 *	71.0	66.5	16 200 *	73.1	65.6	12 400 *	28.0
30.0	67.1	66.1	17 100 *	69.2	65.7	16 000 *	71.3	64.7	12 000 *	30.0
32.0	65.3	65.2	16 800 *	67.4	64.7	15 700 *	69.4	63.7	11 600 *	32.0
34.0	63.5	64.2	16 400 *	65.6	63.7	15 300 *	67.6	62.7	11 200 *	34.0
36.0	61.6	63.1	16 100 *	63.7	62.6	14 600 *	65.6	61.6	10 800 *	36.0
38.0	59.7	61.9	15 800 *	61.7	61.4	14 000 *	63.7	60.4	10 500 *	38.0
40.0	57.7	60.6	15 500 *	59.8	60.1	13 500 *	61.7	59.0	10 200 *	40.0
44.0	53.7	57.8	14 200	55.7	57.2	12 600 *	57.5	56.1	9 700 *	44.0
48.0	49.4	54.4	12 100	51.4	53.9	11 700 *	53.1	52.7	9 200 *	48.0
52.0	44.8	50.6	10 400	46.7	50.0	10 700	48.4	48.7	8 900 *	52.0
56.0	39.8	46.0	8 900	41.7	45.3	9 100	43.1	43.9	8 600 *	56.0
60.0	34.2	40.4	7 600	35.9	39.7	7 800				60.0
64.0	27.6	33.4	6 500							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
15.2	80.3	73.9	19 800 *							15.2
16.0	79.7	73.7	19 600 *							16.0
18.0	78.1	73.3	19 200 *							18.0
20.0	76.5	72.8	18 800 *	78.5	72.4	17 400*	80.7	71.4	14 800*	20.0
22.0	74.8	72.3	18 500 *	76.9	71.8	17 200*	79.0	70.9	14 200*	22.0
24.0	73.2	71.6	18 100 *	75.2	71.2	16 800*	77.3	70.2	13 600*	24.0
26.0	71.5	70.9	17 800 *	73.6	70.5	16 600*	75.6	69.5	13 100*	26.0
28.0	69.8	70.2	17 500 *	71.9	69.8	16 300*	73.9	68.8	12 600*	28.0
30.0	68.1	69.4	17 200 *	70.2	68.9	16 100*	72.1	68.0	12 200*	30.0
32.0	66.4	68.5	16 900 *	68.4	68.0	15 800*	70.4	67.0	11 800*	32.0
34.0	64.6	67.5	16 600 *	66.7	67.1	15 600*	68.6	66.1	11 400*	34.0
36.0	62.9	66.5	16 300 *	64.9	66.0	15 000*	66.8	65.0	11 100*	36.0
38.0	61.1	65.4	16 000 *	63.0	64.9	14 400*	64.9	63.9	10 700*	38.0
40.0	59.2	64.2	15 700 *	61.2	63.7	13 900*	63.0	62.6	10 400*	40.0
44.0	55.4	61.5	13 900	57.4	61.0	12 900*	59.1	59.9	9 900*	44.0
48.0	51.4	58.4	11 800	53.3	57.9	12 000	55.0	56.7	9 400*	48.0
52.0	47.2	54.8	10 100	49.1	54.2	10 400	50.7	53.0	9 100*	52.0
56.0	42.6	50.6	8 600	44.5	50.0	8 800	45.9	48.6	8 700*	56.0
60.0	37.6	45.7	7 300	39.4	45.0	7 500				60.0
64.0	31.9	39.7	6 200	33.6	38.9	6 300				64.0
68.0	25.1	31.9	5 200							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
15.2	80.7	76.9	19 700 *							15.2
16.0	80.1	76.8	19 600 *							16.0
18.0	78.6	76.4	19 200 *							18.0
20.0	77.0	75.9	18 800 *	79.0	75.5	17 400*				20.0
22.0	75.4	75.4	18 500 *	77.4	74.9	17 200*	79.4	74.0	14 400*	22.0
24.0	73.9	74.8	18 200 *	75.8	74.3	16 900*	77.8	73.4	13 800*	24.0
26.0	72.3	74.1	17 900 *	74.2	73.7	16 600*	76.2	72.7	13 300*	26.0
28.0	70.7	73.4	17 600 *	72.6	73.0	16 400*	74.6	72.0	12 800*	28.0
30.0	69.0	72.6	17 300 *	71.0	72.2	16 100*	72.9	71.2	12 400*	30.0
32.0	67.4	71.8	17 000 *	69.3	71.3	15 900*	71.2	70.3	12 000*	32.0
34.0	65.7	70.9	16 700 *	67.7	70.4	15 700*	69.5	69.4	11 600*	34.0
36.0	64.0	69.9	16 500 *	66.0	69.4	15 300*	67.8	68.4	11 300*	36.0
38.0	62.3	68.8	16 200 *	64.2	68.3	14 800*	66.1	67.3	10 900*	38.0
40.0	60.6	67.7	15 800	62.5	67.2	14 200*	64.3	66.1	10 600*	40.0
44.0	57.0	65.2	13 600	58.9	64.6	13 200*	60.6	63.5	10 100*	44.0
48.0	53.3	62.2	11 600	55.1	61.7	12 000	56.8	60.6	9 600*	48.0
52.0	49.3	58.9	9 900	51.1	58.3	10 200	52.7	57.1	9 200*	52.0
56.0	45.1	55.1	8 400	46.9	54.4	8 700	48.3	53.1	8 800	56.0
60.0	40.6	50.6	7 100	42.3	49.9	7 300				60.0
64.0	35.5	45.2	6 000	37.1	44.5	6 200				64.0
68.0	29.7	38.7	5 000							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	79.9	79.7	19 400 *							16.8
18.0	79.0	79.4	19 100 *							18.0
20.0	77.5	79.0	18 800 *	79.4	78.6	17 400*				20.0
22.0	76.0	78.5	18 500 *	77.9	78.0	17 200*	79.9	77.1	14 500*	22.0
24.0	74.5	77.9	18 200 *	76.4	77.5	17 000*	78.3	76.5	14 000*	24.0
26.0	73.0	77.3	17 900 *	74.9	76.8	16 700*	76.8	75.9	13 400*	26.0
28.0	71.4	76.6	17 600 *	73.3	76.2	16 400*	75.2	75.2	13 000*	28.0
30.0	69.9	75.9	17 300 *	71.8	75.4	16 200*	73.6	74.4	12 600*	30.0
32.0	68.3	75.1	17 100 *	70.2	74.6	16 000*	72.0	73.6	12 200*	32.0
34.0	66.7	74.2	16 800 *	68.6	73.7	15 700*	70.4	72.7	11 800*	34.0
36.0	65.1	73.2	16 500 *	67.0	72.8	15 500*	68.8	71.7	11 400*	36.0
38.0	63.5	72.2	16 300 *	65.3	71.7	15 200*	67.1	70.7	11 100*	38.0
40.0	61.8	71.1	15 900	63.7	70.7	14 600*	65.4	69.6	10 800*	40.0
44.0	58.4	68.7	13 400	60.2	68.2	13 600*	61.9	67.1	10 300*	44.0
48.0	54.9	66.0	11 300	56.7	65.5	11 700	58.3	64.3	9 800*	48.0
52.0	51.2	62.9	9 600	52.9	62.3	9 900	54.5	61.1	9 400*	52.0
56.0	47.3	59.3	8 100	49.0	58.7	8 400	50.5	57.4	8 700	56.0
60.0	43.1	55.2	6 900	44.8	54.5	7 100	46.1	53.1	7 300	60.0
64.0	38.5	50.4	5 800	40.1	49.7	5 900				64.0
68.0	33.5	44.6	4 800	35.0	43.8	4 900				68.0
72.0	27.5	37.5	3 900							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
16.8	80.3	82.8	19 300 *							16.8
18.0	79.4	82.5	19 100 *							18.0
20.0	78.0	82.1	18 800 *	79.8	81.6	17 400*				20.0
22.0	76.5	81.6	18 500 *	78.4	81.1	17 200*	80.3	80.2	14 700*	22.0
24.0	75.1	81.0	18 200 *	76.9	80.6	17 000*	78.8	79.6	14 100*	24.0
26.0	73.6	80.4	17 900 *	75.5	80.0	16 700*	77.3	79.0	13 600*	26.0
28.0	72.1	79.8	17 600 *	74.0	79.3	16 500*	75.8	78.4	13 200*	28.0
30.0	70.6	79.1	17 400 *	72.5	78.6	16 200*	74.3	77.6	12 700*	30.0
32.0	69.1	78.3	17 100 *	71.0	77.8	16 000*	72.7	76.8	12 300*	32.0
34.0	67.6	77.5	16 900 *	69.4	77.0	15 800*	71.2	76.0	12 000*	34.0
36.0	66.1	76.6	16 600 *	67.9	76.1	15 600*	69.6	75.1	11 600*	36.0
38.0	64.5	75.6	16 400 *	66.3	75.1	15 400*	68.0	74.1	11 300*	38.0
40.0	63.0	74.6	15 700	64.7	74.1	15 000*	66.4	73.0	11 000*	40.0
44.0	59.7	72.3	13 200	61.5	71.8	13 600	63.1	70.7	10 400*	44.0
48.0	56.4	69.7	11 100	58.1	69.2	11 500	59.7	68.0	10 000*	48.0
52.0	52.9	66.7	9 400	54.6	66.2	9 700	56.1	65.0	9 500*	52.0
56.0	49.2	63.4	7 900	50.9	62.8	8 200	52.3	61.6	8 500	56.0
60.0	45.3	59.6	6 600	47.0	58.9	6 900	48.3	57.6	7 100	60.0
64.0	41.2	55.1	5 500	42.7	54.5	5 800	44.0	53.0	5 900	64.0
68.0	36.6	50.0	4 500	38.1	49.3	4 700				68.0
72.0	31.4	43.8	3 700	32.9	43.0	3 800				72.0
76.0	25.3	36.1	2 900							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	80.6	85.8	19 200 *							16.8
18.0	79.8	85.6	19 000 *							18.0
20.0	78.4	85.2	18 700 *	80.2	84.7	17 300*				20.0
22.0	77.0	84.7	18 400 *	78.8	84.2	17 100*				22.0
24.0	75.6	84.2	18 200 *	77.4	83.7	16 900*	79.2	82.7	14 300*	24.0
26.0	74.2	83.6	17 900 *	76.0	83.1	16 700*	77.8	82.2	13 800*	26.0
28.0	72.8	82.9	17 600 *	74.6	82.5	16 500*	76.3	81.5	13 300*	28.0
30.0	71.4	82.3	17 300 *	73.1	81.8	16 300*	74.9	80.8	12 900*	30.0
32.0	69.9	81.5	17 100 *	71.7	81.1	16 100*	73.4	80.1	12 500*	32.0
34.0	68.5	80.7	16 900 *	70.2	80.3	15 900*	71.9	79.2	12 100*	34.0
36.0	67.0	79.9	16 600 *	68.7	79.4	15 600*	70.4	78.4	11 800*	36.0
38.0	65.5	78.9	16 400 *	67.2	78.5	15 500*	68.9	77.4	11 400*	38.0
40.0	64.0	77.9	15 400	65.7	77.5	15 300*	67.3	76.4	11 100*	40.0
44.0	60.9	75.8	12 800	62.6	75.3	13 400	64.2	74.2	10 600*	44.0
48.0	57.7	73.3	10 800	59.4	72.8	11 200	60.9	71.7	10 100*	48.0
52.0	54.4	70.5	9 000	56.1	70.0	9 400	57.6	68.8	9 700	52.0
56.0	51.0	67.4	7 600	52.6	66.8	7 900	54.0	65.6	8 200	56.0
60.0	47.3	63.8	6 300	48.9	63.2	6 600	50.3	61.9	6 900	60.0
64.0	43.5	59.7	5 200	45.0	59.0	5 400	46.3	57.6	5 700	64.0
68.0	39.3	55.0	4 200	40.8	54.3	4 400				68.0
72.0	34.7	49.5	3 400	36.1	48.7	3 500				72.0
76.0	29.5	42.8	2 600							76.0
80.0	23.1	34.4	1 900							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
16.8	81.0	88.9	19 100 *							16.8
18.0	80.1	88.6	19 000 *							18.0
20.0	78.8	88.2	18 700 *	80.6	87.8	17 300*				20.0
22.0	77.5	87.8	18 400 *	79.2	87.3	17 100*				22.0
24.0	76.1	87.3	18 100 *	77.9	86.8	16 900*	79.6	85.8	14 400*	24.0
26.0	74.8	86.7	17 900 *	76.5	86.3	16 700*	78.2	85.3	13 900*	26.0
28.0	73.4	86.1	17 600 *	75.1	85.6	16 500*	76.8	84.7	13 500*	28.0
30.0	72.0	85.4	17 300 *	73.7	85.0	16 300*	75.4	84.0	13 100*	30.0
32.0	70.6	84.7	17 100 *	72.3	84.3	16 100*	74.0	83.3	12 700*	32.0
34.0	69.2	84.0	16 900 *	70.9	83.5	15 900*	72.6	82.5	12 300*	34.0
36.0	67.8	83.1	16 700 *	69.5	82.7	15 700*	71.1	81.6	11 900*	36.0
38.0	66.4	82.2	16 200	68.1	81.8	15 500*	69.7	80.7	11 600*	38.0
40.0	65.0	81.3	14 900	66.6	80.8	15 300	68.2	79.8	11 300*	40.0
44.0	62.0	79.2	12 600	63.7	78.7	13 100	65.2	77.6	10 800*	44.0
48.0	59.0	76.9	10 500	60.6	76.3	11 000	62.1	75.2	10 300*	48.0
52.0	55.8	74.2	8 800	57.4	73.7	9 200	58.9	72.5	9 600	52.0
56.0	52.6	71.2	7 300	54.2	70.7	7 700	55.6	69.5	8 000	56.0
60.0	49.2	67.9	6 100	50.7	67.3	6 400	52.0	66.0	6 700	60.0
64.0	45.5	64.0	4 900	47.1	63.4	5 200	48.3	62.1	5 400	64.0
68.0	41.7	59.7	4 000	43.2	59.0	4 200	44.3	57.6	4 400	68.0
72.0	37.5	54.7	3 100	38.9	54.0	3 300				72.0
76.0	32.9	48.8	2 300	34.2	48.0	2 500				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
18.3	80.3	91.6	18 800 *							18.3
20.0	79.2	91.3	18 500 *	80.9	90.8	17 200*				20.0
22.0	77.9	90.8	18 300 *	79.6	90.4	17 000*				22.0
24.0	76.6	90.4	18 000 *	78.3	89.9	16 800*	79.9	88.9	14 600*	24.0
26.0	75.3	89.8	17 800 *	77.0	89.4	16 600*	78.6	88.4	14 100*	26.0
28.0	74.0	89.2	17 500 *	75.6	88.8	16 500*	77.3	87.8	13 600*	28.0
30.0	72.6	88.6	17 300 *	74.3	88.1	16 300*	75.9	87.1	13 200*	30.0
32.0	71.3	87.9	17 100 *	73.0	87.5	16 100*	74.6	86.4	12 800*	32.0
34.0	70.0	87.2	16 800 *	71.6	86.7	15 900*	73.2	85.7	12 400*	34.0
36.0	68.6	86.4	16 600 *	70.2	85.9	15 700*	71.8	84.9	12 100*	36.0
38.0	67.2	85.5	16 100	68.8	85.1	15 600*	70.4	84.0	11 800*	38.0
40.0	65.8	84.6	14 800	67.5	84.1	15 300	69.0	83.1	11 500*	40.0
44.0	63.0	82.6	12 600	64.6	82.1	13 200	66.1	81.1	10 900*	44.0
48.0	60.1	80.4	10 600	61.7	79.9	11 100	63.2	78.8	10 400*	48.0
52.0	57.1	77.8	8 900	58.7	77.3	9 300	60.1	76.2	9 700	52.0
56.0	54.0	75.0	7 400	55.6	74.5	7 700	56.9	73.3	8 100	56.0
60.0	50.8	71.8	6 100	52.3	71.2	6 400	53.6	70.0	6 700	60.0
64.0	47.4	68.2	5 000	48.9	67.6	5 300	50.1	66.3	5 500	64.0
68.0	43.8	64.2	4 000	45.3	63.5	4 300	46.4	62.1	4 500	68.0
72.0	40.0	59.6	3 200	41.4	58.9	3 400				72.0
76.0	35.7	54.3	2 400	37.1	53.5	2 600				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
18.3	80.6	94.7	18 700 *							18.3
20.0	79.5	94.4	18 400 *							20.0
22.0	78.3	93.9	18 200 *	79.9	93.5	16 900*				22.0
24.0	77.0	93.5	17 900 *	78.7	93.0	16 700*	80.3	92.0	14 700*	24.0
26.0	75.8	92.9	17 700 *	77.4	92.5	16 600*	79.0	91.5	14 200*	26.0
28.0	74.5	92.4	17 400 *	76.1	91.9	16 400*	77.7	90.9	13 800*	28.0
30.0	73.2	91.8	17 200 *	74.8	91.3	16 300*	76.4	90.3	13 300*	30.0
32.0	71.9	91.1	17 000 *	73.5	90.6	16 100*	75.1	89.6	13 000*	32.0
34.0	70.6	90.4	16 800 *	72.2	89.9	15 900*	73.8	88.9	12 600*	34.0
36.0	69.3	89.6	16 600 *	70.9	89.1	15 700*	72.4	88.1	12 300*	36.0
38.0	68.0	88.8	15 700	69.6	88.3	15 600*	71.1	87.3	11 900*	38.0
40.0	66.7	87.9	14 400	68.2	87.4	15 100	69.7	86.4	11 600*	40.0
44.0	64.0	86.0	12 200	65.5	85.5	12 800	67.0	84.4	11 100*	44.0
48.0	61.2	83.9	10 300	62.7	83.3	10 800	64.1	82.2	10 600*	48.0
52.0	58.3	81.4	8 600	59.8	80.9	9 000	61.2	79.8	9 400	52.0
56.0	55.4	78.7	7 100	56.9	78.2	7 500	58.2	77.0	7 900	56.0
60.0	52.3	75.7	5 900	53.8	75.1	6 200	55.1	73.9	6 500	60.0
64.0	49.1	72.3	4 800	50.5	71.7	5 100	51.8	70.4	5 300	64.0
68.0	45.7	68.5	3 800	47.1	67.9	4 100	48.3	66.5	4 300	68.0
72.0	42.1	64.2	3 000	43.5	63.6	3 100	44.6	62.1	3 300	72.0
76.0	38.3	59.4	2 200	39.6	58.6	2 400				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
81.5m Boom										
18.3	80.9	97.7	18 500 *							18.3
20.0	79.9	97.4	18 300 *							20.0
22.0	78.7	97.0	18 000 *	80.2	96.5	16 800*				22.0
24.0	77.4	96.5	17 800 *	79.0	96.1	16 600*				24.0
26.0	76.2	96.0	17 500 *	77.8	95.6	16 500*	79.4	94.6	14 300*	26.0
28.0	75.0	95.5	17 400 *	76.6	95.0	16 300*	78.1	94.0	13 900*	28.0
30.0	73.8	94.9	17 100 *	75.3	94.4	16 200*	76.8	93.4	13 500*	30.0
32.0	72.5	94.3	16 900 *	74.1	93.8	16 100*	75.6	92.8	13 100*	32.0
34.0	71.3	93.6	16 700 *	72.8	93.1	15 900*	74.3	92.1	12 700*	34.0
36.0	70.0	92.8	16 300	71.5	92.4	15 700*	73.0	91.3	12 400*	36.0
38.0	68.7	92.0	15 200	70.2	91.6	15 600*	71.7	90.5	12 100*	38.0
40.0	67.4	91.2	14 000	69.0	90.7	14 600	70.4	89.7	11 800*	40.0
44.0	64.8	89.4	11 700	66.3	88.9	12 300	67.8	87.8	11 200*	44.0
48.0	62.2	87.3	9 900	63.6	86.8	10 400	65.0	85.7	10 700	48.0
52.0	59.4	85.0	8 300	60.9	84.5	8 800	62.3	83.3	9 200	52.0
56.0	56.6	82.4	6 800	58.1	81.8	7 300	59.4	80.7	7 600	56.0
60.0	53.7	79.5	5 600	55.1	78.9	5 900	56.4	77.7	6 300	60.0
64.0	50.6	76.3	4 400	52.0	75.7	4 800	53.3	74.5	5 000	64.0
68.0	47.5	72.7	3 500	48.8	72.1	3 800	50.0	70.8	4 000	68.0
72.0	44.1	68.7	2 600	45.5	68.1	2 900	46.5	66.6	3 000	72.0
76.0	40.5	64.2	1 800	41.8	63.5	2 100	42.8	62.0	2 200	76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
10.7	80.4	47.3	17 600 *							10.7
12.0	78.7	47.0	17 200 *							12.0
14.0	76.1	46.5	16 600 *	80.5	46.2	13 300*				14.0
16.0	73.5	45.9	15 900 *	77.9	45.6	13 300*				16.0
18.0	70.8	45.2	15 300 *	75.2	44.9	13 300*	79.3	44.1	12 200*	18.0
20.0	68.1	44.4	14 700 *	72.5	44.1	13 300*	76.5	43.2	11 400*	20.0
22.0	65.3	43.4	14 200 *	69.7	43.2	13 100*	73.7	42.3	10 600*	22.0
24.0	62.5	42.4	13 700 *	66.8	42.1	12 800*	70.8	41.2	10 000*	24.0
26.0	59.6	41.2	13 200 *	63.9	40.9	12 400*	67.8	40.0	9 500*	26.0
28.0	56.6	39.8	12 800 *	60.9	39.6	11 700*	64.7	38.6	8 900*	28.0
30.0	53.4	38.3	12 400 *	57.7	38.1	11 000*	61.4	37.1	8 500*	30.0
32.0	50.2	36.6	12 000 *	54.4	36.4	10 300*	58.0	35.3	8 100*	32.0
34.0	46.7	34.7	11 400 *	51.0	34.5	9 800*	54.4	33.4	7 800*	34.0
36.0	43.0	32.6	10 700 *	47.3	32.4	9 300*	50.6	31.2	7 400*	36.0
38.0	39.1	30.1	10 000 *	43.3	29.9	8 800*	46.4	28.6	7 200*	38.0
40.0	34.7	27.3	9 500 *	38.9	27.1	8 500*				40.0
44.0	23.8	19.5	8 600 *							44.0
30.5m Boom										
10.7	81.0	50.4	17 700 *							10.7
12.0	79.4	50.1	17 300 *							12.0
14.0	77.0	49.6	16 700 *							14.0
16.0	74.5	49.1	16 100 *	78.7	48.8	13 300*				16.0
18.0	72.1	48.4	15 500 *	76.2	48.1	13 300*				18.0
20.0	69.5	47.6	15 000 *	73.6	47.3	13 300*	77.5	46.4	11 700*	20.0
22.0	67.0	46.8	14 500 *	71.1	46.5	13 300*	74.8	45.6	10 900*	22.0
24.0	64.4	45.8	14 000 *	68.4	45.5	13 000*	72.1	44.6	10 300*	24.0
26.0	61.7	44.7	13 500 *	65.7	44.4	12 600*	69.4	43.5	9 700*	26.0
28.0	58.9	43.4	13 100 *	63.0	43.2	12 200*	66.5	42.2	9 200*	28.0
30.0	56.1	42.1	12 700 *	60.1	41.8	11 500*	63.6	40.8	8 800*	30.0
32.0	53.1	40.6	12 300 *	57.1	40.3	10 800*	60.6	39.3	8 400*	32.0
34.0	50.1	38.9	12 000 *	54.0	38.6	10 300*	57.4	37.5	8 000*	34.0
36.0	46.8	37.0	11 400 *	50.8	36.7	9 700*	54.0	35.6	7 700*	36.0
38.0	43.4	34.9	10 700 *	47.3	34.6	9 300*	50.4	33.4	7 400*	38.0
40.0	39.7	32.5	10 100 *	43.6	32.2	8 900*	46.5	30.9	7 200*	40.0
44.0	31.2	26.5	9 100 *	35.1	26.2	8 200*				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	79.8	53.1	17 400 *							12.2
14.0	77.7	52.7	16 800 *							14.0
16.0	75.5	52.2	16 300 *	79.4	51.9	13 300*				16.0
18.0	73.1	51.6	15 700 *	77.0	51.3	13 300*				18.0
20.0	70.8	50.8	15 200 *	74.7	50.5	13 300*	78.3	49.6	11 900*	20.0
22.0	68.4	50.0	14 700 *	72.2	49.7	13 300*	75.8	48.8	11 200*	22.0
24.0	66.0	49.1	14 200 *	69.8	48.8	13 100*	73.3	47.9	10 500*	24.0
26.0	63.5	48.1	13 800 *	67.3	47.8	12 800*	70.8	46.9	10 000*	26.0
28.0	60.9	47.0	13 400 *	64.7	46.7	12 500*	68.1	45.7	9 500*	28.0
30.0	58.3	45.7	13 000 *	62.1	45.5	12 000*	65.4	44.4	9 100*	30.0
32.0	55.6	44.3	12 600 *	59.4	44.1	11 300*	62.7	43.0	8 700*	32.0
34.0	52.8	42.8	12 200 *	56.6	42.5	10 800*	59.8	41.4	8 300*	34.0
36.0	49.9	41.1	11 900 *	53.7	40.8	10 200*	56.8	39.7	8 000*	36.0
38.0	46.9	39.2	11 400 *	50.6	39.0	9 700*	53.6	37.8	7 700*	38.0
40.0	43.7	37.1	10 800 *	47.4	36.9	9 300*	50.3	35.6	7 400*	40.0
44.0	36.6	32.1	9 700 *	40.2	31.8	8 600*	42.7	30.3	7 000*	44.0
48.0	27.8	25.3	8 800 *							48.0
36.5m Boom										
12.2	80.4	56.2	17 500 *							12.2
14.0	78.4	55.8	17 000 *							14.0
16.0	76.3	55.3	16 500 *	80.0	55.0	13 300*				16.0
18.0	74.1	54.7	16 000 *	77.8	54.4	13 300*				18.0
20.0	71.9	54.0	15 400 *	75.5	53.7	13 300*	79.0	52.8	12 100*	20.0
22.0	69.6	53.3	14 900 *	73.3	53.0	13 300*	76.7	52.0	11 400*	22.0
24.0	67.4	52.4	14 500 *	71.0	52.1	13 200*	74.3	51.2	10 800*	24.0
26.0	65.1	51.5	14 000 *	68.7	51.2	13 000*	71.9	50.2	10 200*	26.0
28.0	62.7	50.4	13 600 *	66.3	50.1	12 700*	69.5	49.1	9 700*	28.0
30.0	60.3	49.3	13 200 *	63.9	49.0	12 400*	67.0	47.9	9 300*	30.0
32.0	57.8	48.0	12 900 *	61.4	47.7	11 800*	64.5	46.6	8 900*	32.0
34.0	55.2	46.6	12 600 *	58.8	46.3	11 200*	61.8	45.2	8 500*	34.0
36.0	52.6	45.0	12 200 *	56.1	44.8	10 600*	59.1	43.6	8 200*	36.0
38.0	49.8	43.3	11 900 *	53.4	43.1	10 100*	56.3	41.9	7 900*	38.0
40.0	47.0	41.5	11 400 *	50.5	41.2	9 700*	53.3	39.9	7 700*	40.0
44.0	40.7	37.1	10 300 *	44.2	36.8	8 900*	46.8	35.4	7 200*	44.0
48.0	33.5	31.5	9 400 *	36.9	31.2	8 300*				48.0
52.0	24.4	23.7	8 600 *							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	80.9	59.3	17 500 *							12.2
14.0	79.0	58.9	17 000 *							14.0
16.0	77.0	58.4	16 600 *							16.0
18.0	74.9	57.9	16 100 *	78.4	57.5	13 300 *				18.0
20.0	72.9	57.2	15 600 *	76.3	56.9	13 300 *	79.6	55.9	12 300 *	20.0
22.0	70.8	56.5	15 100 *	74.2	56.2	13 300 *	77.4	55.2	11 700 *	22.0
24.0	68.6	55.7	14 600 *	72.1	55.4	13 300 *	75.2	54.4	11 000 *	24.0
26.0	66.5	54.8	14 200 *	69.9	54.5	13 100 *	73.0	53.5	10 500 *	26.0
28.0	64.2	53.8	13 900 *	67.7	53.5	12 800 *	70.7	52.5	10 000 *	28.0
30.0	62.0	52.7	13 500 *	65.4	52.4	12 500 *	68.4	51.4	9 500 *	30.0
32.0	59.7	51.6	13 100 *	63.1	51.3	12 300 *	66.0	50.2	9 200 *	32.0
34.0	57.3	50.3	12 800 *	60.7	50.0	11 600 *	63.6	48.9	8 800 *	34.0
36.0	54.9	48.8	12 500 *	58.2	48.5	11 100 *	61.1	47.4	8 400 *	36.0
38.0	52.4	47.3	12 200 *	55.7	47.0	10 600 *	58.5	45.8	8 100 *	38.0
40.0	49.8	45.6	11 900 *	53.1	45.3	10 100 *	55.8	44.1	7 900 *	40.0
44.0	44.2	41.6	10 800 *	47.5	41.4	9 300 *	50.0	40.0	7 400 *	44.0
48.0	38.0	36.8	9 900 *	41.2	36.5	8 600 *	43.5	35.0	7 000 *	48.0
52.0	30.6	30.6	9 100 *	33.8	30.3	8 100 *				52.0
42.5m Boom										
13.7	79.9	62.0	17 200 *							13.7
14.0	79.6	62.0	17 100 *							14.0
16.0	77.7	61.5	16 600 *							16.0
18.0	75.7	61.0	16 200 *	79.0	60.6	13 300 *				18.0
20.0	73.7	60.4	15 700 *	77.0	60.0	13 300 *	80.1	59.1	12 500 *	20.0
22.0	71.8	59.7	15 300 *	75.0	59.4	13 300 *	78.1	58.4	11 800 *	22.0
24.0	69.7	58.9	14 900 *	73.0	58.6	13 300 *	76.0	57.6	11 200 *	24.0
26.0	67.7	58.1	14 400 *	71.0	57.8	13 200 *	73.9	56.8	10 700 *	26.0
28.0	65.6	57.2	14 000 *	68.9	56.9	12 900 *	71.8	55.8	10 200 *	28.0
30.0	63.5	56.2	13 700 *	66.7	55.9	12 700 *	69.6	54.8	9 800 *	30.0
32.0	61.3	55.1	13 300 *	64.6	54.7	12 400 *	67.4	53.7	9 400 *	32.0
34.0	59.1	53.8	13 000 *	62.3	53.5	12 100 *	65.1	52.4	9 000 *	34.0
36.0	56.9	52.5	12 700 *	60.1	52.2	11 500 *	62.8	51.1	8 700 *	36.0
38.0	54.6	51.1	12 400 *	57.7	50.8	11 000 *	60.4	49.6	8 400 *	38.0
40.0	52.2	49.5	12 100 *	55.3	49.2	10 500 *	58.0	48.0	8 100 *	40.0
44.0	47.1	45.9	11 400 *	50.2	45.6	9 700 *	52.7	44.3	7 600 *	44.0
48.0	41.6	41.6	10 400 *	44.6	41.3	9 000 *	46.9	39.9	7 200 *	48.0
52.0	35.3	36.3	9 500 *	38.3	36.0	8 400 *				52.0
56.0	27.8	29.4	8 800 *							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	80.4	65.1	17 200 *							13.7
14.0	80.1	65.0	17 100 *							14.0
16.0	78.3	64.6	16 700 *							16.0
18.0	76.4	64.1	16 300 *	79.6	63.7	13 300 *				18.0
20.0	74.5	63.5	15 900 *	77.7	63.2	13 300 *	80.6	62.2	12 700 *	20.0
22.0	72.6	62.9	15 400 *	75.8	62.5	13 300 *	78.7	61.5	12 000 *	22.0
24.0	70.7	62.2	15 000 *	73.9	61.8	13 300 *	76.7	60.8	11 400 *	24.0
26.0	68.8	61.4	14 600 *	71.9	61.0	13 300 *	74.8	60.0	10 900 *	26.0
28.0	66.8	60.5	14 200 *	69.9	60.2	13 100 *	72.7	59.1	10 400 *	28.0
30.0	64.9	59.5	13 900 *	67.9	59.2	12 800 *	70.7	58.2	10 000 *	30.0
32.0	62.8	58.5	13 500 *	65.9	58.2	12 600 *	68.6	57.1	9 600 *	32.0
34.0	60.8	57.4	13 200 *	63.8	57.0	12 300 *	66.5	55.9	9 200 *	34.0
36.0	58.6	56.1	12 900 *	61.7	55.8	11 900 *	64.3	54.7	8 900 *	36.0
38.0	56.5	54.8	12 600 *	59.5	54.5	11 400 *	62.1	53.3	8 600 *	38.0
40.0	54.3	53.3	12 300 *	57.3	53.0	10 900 *	59.8	51.8	8 300 *	40.0
44.0	49.6	50.0	11 800 *	52.6	49.7	10 000 *	55.0	48.5	7 800 *	44.0
48.0	44.6	46.1	10 900 *	47.5	45.8	9 300 *	49.8	44.4	7 400 *	48.0
52.0	39.0	41.5	10 000 *	42.0	41.1	8 700 *	44.0	39.6	7 100 *	52.0
56.0	32.7	35.6	9 300 *	35.6	35.3	8 200 *				56.0
60.0	24.9	27.9	8 500							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
13.7	80.8	68.1	17 200 *							13.7
14.0	80.5	68.1	17 200 *							14.0
16.0	78.8	67.7	16 800 *							16.0
18.0	77.0	67.2	16 300 *							18.0
20.0	75.2	66.6	16 000 *	78.3	66.3	13 300*				20.0
22.0	73.5	66.0	15 600 *	76.4	65.7	13 300*	79.2	64.7	12 200*	22.0
24.0	71.6	65.4	15 100 *	74.6	65.0	13 300*	77.4	64.0	11 600*	24.0
26.0	69.8	64.6	14 800 *	72.8	64.3	13 300*	75.5	63.2	11 100*	26.0
28.0	68.0	63.8	14 400 *	70.9	63.4	13 200*	73.6	62.4	10 600*	28.0
30.0	66.1	62.9	14 100 *	69.0	62.5	12 900*	71.7	61.5	10 200*	30.0
32.0	64.2	61.9	13 700 *	67.1	61.6	12 700*	69.7	60.5	9 800*	32.0
34.0	62.2	60.8	13 400 *	65.1	60.5	12 500*	67.7	59.4	9 400*	34.0
36.0	60.2	59.7	13 100 *	63.1	59.3	12 200*	65.7	58.2	9 100*	36.0
38.0	58.2	58.4	12 800 *	61.1	58.1	11 800*	63.6	56.9	8 800*	38.0
40.0	56.1	57.1	12 600 *	59.0	56.7	11 200*	61.5	55.5	8 500*	40.0
44.0	51.8	54.0	12 000 *	54.7	53.7	10 400*	57.0	52.4	8 000*	44.0
48.0	47.2	50.4	11 400 *	50.0	50.1	9 700*	52.3	48.8	7 600*	48.0
52.0	42.2	46.2	10 500 *	45.0	45.9	9 000*	47.1	44.4	7 200*	52.0
56.0	36.6	41.1	9 600	39.4	40.7	8 500*				56.0
60.0	30.2	34.7	8 300	32.9	34.3	8 100*				60.0
64.0	22.0	26.0	7 200							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	79.9	70.9	16 900 *							15.2
16.0	79.3	70.7	16 800 *							16.0
18.0	77.6	70.3	16 400 *							18.0
20.0	75.9	69.8	16 000 *	78.8	69.4	13 300*				20.0
22.0	74.2	69.2	15 700 *	77.1	68.8	13 300*	79.7	67.8	12 400*	22.0
24.0	72.5	68.5	15 300 *	75.3	68.2	13 300*	78.0	67.1	11 800*	24.0
26.0	70.7	67.8	14 900 *	73.6	67.5	13 300*	76.2	66.4	11 300*	26.0
28.0	69.0	67.0	14 500 *	71.8	66.7	13 300*	74.4	65.6	10 800*	28.0
30.0	67.2	66.2	14 200 *	70.0	65.8	13 000*	72.5	64.8	10 400*	30.0
32.0	65.4	65.2	13 900 *	68.2	64.9	12 800*	70.7	63.8	10 000*	32.0
34.0	63.5	64.2	13 500 *	66.3	63.9	12 500*	68.8	62.8	9 600*	34.0
36.0	61.6	63.1	13 300 *	64.4	62.8	12 300*	66.9	61.7	9 300*	36.0
38.0	59.7	62.0	13 000 *	62.5	61.6	12 100*	64.9	60.5	9 000*	38.0
40.0	57.8	60.7	12 700 *	60.6	60.3	11 600*	62.9	59.2	8 700*	40.0
44.0	53.8	57.8	12 200 *	56.5	57.5	10 700*	58.8	56.3	8 200*	44.0
48.0	49.5	54.5	11 700 *	52.2	54.2	10 000*	54.4	52.9	7 800*	48.0
52.0	44.9	50.6	10 800	47.6	50.3	9 300*	49.7	48.9	7 400*	52.0
56.0	39.9	46.1	9 300	42.6	45.7	8 800*	44.5	44.1	7 100*	56.0
60.0	34.3	40.5	8 000	36.9	40.2	8 200				60.0
64.0	27.7	33.5	6 900							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.3	73.9	16 900 *							15.2
16.0	79.7	73.8	16 800 *							16.0
18.0	78.1	73.4	16 400 *							18.0
20.0	76.5	72.9	16 100 *	79.3	72.5	13 300 *				20.0
22.0	74.9	72.3	15 700 *	77.6	71.9	13 300 *	80.2	70.9	12 500 *	22.0
24.0	73.2	71.7	15 400 *	76.0	71.3	13 300 *	78.5	70.3	12 000 *	24.0
26.0	71.5	71.0	15 000 *	74.3	70.6	13 300 *	76.8	69.6	11 400 *	26.0
28.0	69.9	70.3	14 600 *	72.6	69.9	13 300 *	75.1	68.8	11 000 *	28.0
30.0	68.2	69.4	14 300 *	70.9	69.1	13 100 *	73.3	68.0	10 600 *	30.0
32.0	66.4	68.6	14 000 *	69.1	68.2	12 900 *	71.6	67.1	10 200 *	32.0
34.0	64.7	67.6	13 700 *	67.4	67.3	12 600 *	69.8	66.1	9 800 *	34.0
36.0	62.9	66.6	13 400 *	65.6	66.2	12 500 *	68.0	65.1	9 500 *	36.0
38.0	61.1	65.4	13 200 *	63.8	65.1	12 200 *	66.1	64.0	9 200 *	38.0
40.0	59.3	64.2	12 900 *	61.9	63.9	12 000 *	64.2	62.7	8 900 *	40.0
44.0	55.5	61.6	12 400 *	58.1	61.2	11 100 *	60.4	60.0	8 400 *	44.0
48.0	51.5	58.5	12 000 *	54.1	58.1	10 300 *	56.3	56.8	7 900 *	48.0
52.0	47.3	54.9	10 600	49.9	54.6	9 600 *	51.9	53.2	7 600 *	52.0
56.0	42.7	50.7	9 100	45.3	50.4	9 000 *	47.2	48.9	7 200 *	56.0
60.0	37.7	45.8	7 800	40.3	45.4	8 100				60.0
64.0	32.0	39.8	6 700	34.5	39.4	6 900				64.0
68.0	25.2	32.1	5 700							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
15.2	80.7	77.0	16 900 *							15.2
16.0	80.1	76.9	16 700 *							16.0
18.0	78.6	76.4	16 400 *							18.0
20.0	77.0	76.0	16 100 *	79.7	75.6	13 300 *				20.0
22.0	75.5	75.4	15 800 *	78.1	75.0	13 300 *				22.0
24.0	73.9	74.8	15 400 *	76.5	74.5	13 300 *	79.0	73.4	12 100 *	24.0
26.0	72.3	74.2	15 100 *	74.9	73.8	13 300 *	77.3	72.8	11 600 *	26.0
28.0	70.7	73.5	14 700 *	73.3	73.1	13 300 *	75.7	72.0	11 200 *	28.0
30.0	69.1	72.7	14 400 *	71.7	72.3	13 200 *	74.1	71.2	10 700 *	30.0
32.0	67.4	71.9	14 100 *	70.0	71.5	13 000 *	72.4	70.4	10 300 *	32.0
34.0	65.8	70.9	13 800 *	68.4	70.6	12 700 *	70.7	69.5	10 000 *	34.0
36.0	64.1	70.0	13 600 *	66.7	69.6	12 500 *	69.0	68.5	9 600 *	36.0
38.0	62.4	68.9	13 300 *	65.0	68.5	12 300 *	67.2	67.4	9 400 *	38.0
40.0	60.6	67.8	13 000 *	63.2	67.4	12 200 *	65.4	66.2	9 100 *	40.0
44.0	57.1	65.2	12 500 *	59.6	64.9	11 400 *	61.8	63.7	8 500 *	44.0
48.0	53.3	62.3	12 000	55.8	62.0	10 600 *	57.9	60.7	8 100 *	48.0
52.0	49.4	59.0	10 300	51.9	58.6	9 900 *	53.9	57.3	7 700 *	52.0
56.0	45.2	55.1	8 800	47.7	54.8	9 200	49.5	53.3	7 400 *	56.0
60.0	40.6	50.7	7 500	43.1	50.3	7 800	44.8	48.7	7 100 *	60.0
64.0	35.6	45.3	6 400	38.0	45.0	6 700				64.0
68.0	29.8	38.8	5 400	32.2	38.4	5 600				68.0
72.0	22.7	30.3	4 500							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.0	79.8	16 600 *							16.8
18.0	79.0	79.5	16 400 *							18.0
20.0	77.5	79.1	16 100 *	80.1	78.7	13 300*				20.0
22.0	76.0	78.5	15 800 *	78.6	78.1	13 300*				22.0
24.0	74.5	78.0	15 500 *	77.1	77.6	13 300*	79.4	76.5	12 300*	24.0
26.0	73.0	77.3	15 200 *	75.5	77.0	13 300*	77.9	75.9	11 800*	26.0
28.0	71.5	76.7	14 800 *	74.0	76.3	13 300*	76.3	75.2	11 300*	28.0
30.0	69.9	75.9	14 500 *	72.4	75.5	13 200*	74.7	74.5	10 900*	30.0
32.0	68.3	75.1	14 200 *	70.9	74.7	13 000*	73.1	73.6	10 500*	32.0
34.0	66.8	74.2	13 900 *	69.3	73.9	12 800*	71.5	72.8	10 200*	34.0
36.0	65.2	73.3	13 700 *	67.6	72.9	12 600*	69.8	71.8	9 800*	36.0
38.0	63.5	72.3	13 400 *	66.0	71.9	12 400*	68.2	70.8	9 500*	38.0
40.0	61.9	71.2	13 100 *	64.3	70.9	12 300*	66.5	69.7	9 200*	40.0
44.0	58.5	68.8	12 700 *	60.9	68.5	11 700*	63.0	67.3	8 700*	44.0
48.0	55.0	66.1	11 800	57.4	65.7	10 900*	59.4	64.5	8 300*	48.0
52.0	51.3	62.9	10 000	53.7	62.6	10 200	55.6	61.3	7 900*	52.0
56.0	47.4	59.4	8 600	49.7	59.0	8 900	51.6	57.6	7 500*	56.0
60.0	43.2	55.3	7 300	45.5	54.9	7 600	47.3	53.4	7 200*	60.0
64.0	38.6	50.4	6 200	41.0	50.1	6 500	42.5	48.4	6 700	64.0
68.0	33.5	44.7	5 200	35.8	44.3	5 400				68.0
72.0	27.6	37.7	4 300							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.3	82.8	16 600 *							16.8
18.0	79.4	82.6	16 400 *							18.0
20.0	78.0	82.1	16 100 *	80.5	81.7	13 300*				20.0
22.0	76.6	81.6	15 800 *	79.0	81.2	13 300*				22.0
24.0	75.1	81.1	15 500 *	77.6	80.7	13 300*	79.8	79.6	12 400*	24.0
26.0	73.7	80.5	15 200 *	76.1	80.1	13 300*	78.3	79.0	11 900*	26.0
28.0	72.2	79.8	14 900 *	74.6	79.5	13 300*	76.8	78.4	11 500*	28.0
30.0	70.7	79.1	14 600 *	73.1	78.7	13 200*	75.3	77.7	11 000*	30.0
32.0	69.2	78.4	14 300 *	71.6	78.0	13 100*	73.8	76.9	10 700*	32.0
34.0	67.7	77.5	14 000 *	70.1	77.1	12 900*	72.2	76.0	10 300*	34.0
36.0	66.1	76.6	13 800 *	68.5	76.3	12 700*	70.7	75.1	10 000*	36.0
38.0	64.6	75.7	13 500 *	67.0	75.3	12 500*	69.1	74.1	9 700*	38.0
40.0	63.0	74.6	13 300 *	65.4	74.3	12 300*	67.5	73.1	9 400*	40.0
44.0	59.8	72.3	12 800 *	62.1	72.0	12 000*	64.2	70.8	8 900*	44.0
48.0	56.4	69.8	11 500	58.8	69.4	11 200*	60.7	68.1	8 400*	48.0
52.0	52.9	66.8	9 800	55.3	66.4	10 300	57.2	65.1	8 000*	52.0
56.0	49.3	63.5	8 300	51.6	63.1	8 700	53.4	61.7	7 700*	56.0
60.0	45.4	59.6	7 000	47.7	59.3	7 400	49.4	57.8	7 400*	60.0
64.0	41.2	55.2	5 900	43.5	54.9	6 300	45.1	53.3	6 500	64.0
68.0	36.7	50.1	4 900	38.9	49.7	5 200				68.0
72.0	31.5	43.9	4 100	33.7	43.5	4 300				72.0
76.0	25.4	36.2	3 300							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
16.8	80.7	85.9	16 500 *							16.8
18.0	79.8	85.6	16 300 *							18.0
20.0	78.4	85.2	16 000 *	80.8	84.8	13 300*				20.0
22.0	77.1	84.7	15 700 *	79.4	84.3	13 300*				22.0
24.0	75.7	84.2	15 500 *	78.0	83.8	13 300*	80.2	82.7	12 600*	24.0
26.0	74.3	83.6	15 200 *	76.6	83.2	13 300*	78.8	82.2	12 000*	26.0
28.0	72.8	83.0	14 900 *	75.2	82.6	13 300*	77.3	81.5	11 600*	28.0
30.0	71.4	82.3	14 700 *	73.7	81.9	13 200*	75.9	80.8	11 200*	30.0
32.0	70.0	81.6	14 400 *	72.3	81.2	13 100*	74.4	80.1	10 800*	32.0
34.0	68.5	80.8	14 100 *	70.8	80.4	12 900*	72.9	79.3	10 400*	34.0
36.0	67.0	79.9	13 900 *	69.4	79.5	12 700*	71.4	78.4	10 100*	36.0
38.0	65.5	79.0	13 600 *	67.9	78.6	12 600*	69.9	77.5	9 800*	38.0
40.0	64.0	78.0	13 400 *	66.3	77.6	12 400*	68.4	76.5	9 500*	40.0
44.0	61.0	75.8	12 900 *	63.2	75.5	12 100*	65.2	74.3	9 000*	44.0
48.0	57.8	73.4	11 300	60.1	73.0	11 500*	62.0	71.8	8 600*	48.0
52.0	54.5	70.6	9 500	56.7	70.2	10 000	58.6	68.9	8 100*	52.0
56.0	51.0	67.4	8 100	53.3	67.1	8 500	55.1	65.7	7 800*	56.0
60.0	47.4	63.8	6 800	49.6	63.5	7 200	51.3	62.0	7 400	60.0
64.0	43.6	59.8	5 700	45.7	59.4	6 000	47.3	57.9	6 300	64.0
68.0	39.4	55.1	4 700	41.5	54.7	5 000	43.0	53.0	5 200	68.0
72.0	34.8	49.6	3 900	36.9	49.2	4 100				72.0
76.0	29.6	43.0	3 100	31.6	42.5	3 300				76.0
80.0	23.2	34.5	2 400							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	81.0	88.9	16 400 *							16.8
18.0	80.2	88.7	16 200 *							18.0
20.0	78.8	88.3	16 000 *							20.0
22.0	77.5	87.8	15 700 *	79.8	87.4	13 300 *				22.0
24.0	76.2	87.3	15 500 *	78.4	86.9	13 300 *				24.0
26.0	74.8	86.8	15 200 *	77.1	86.4	13 300 *	79.2	85.3	12 200 *	26.0
28.0	73.4	86.2	14 900 *	75.7	85.8	13 300 *	77.8	84.7	11 800 *	28.0
30.0	72.1	85.5	14 700 *	74.3	85.1	13 200 *	76.4	84.0	11 300 *	30.0
32.0	70.7	84.8	14 500 *	72.9	84.4	13 100 *	75.0	83.3	11 000 *	32.0
34.0	69.3	84.0	14 200 *	71.5	83.6	12 900 *	73.5	82.5	10 600 *	34.0
36.0	67.9	83.2	13 900 *	70.1	82.8	12 800 *	72.1	81.7	10 300 *	36.0
38.0	66.4	82.3	13 700 *	68.7	81.9	12 600 *	70.7	80.8	10 000 *	38.0
40.0	65.0	81.4	13 500 *	67.2	81.0	12 500 *	69.2	79.8	9 700 *	40.0
44.0	62.1	79.3	13 000	64.3	78.9	12 200 *	66.2	77.7	9 200 *	44.0
48.0	59.0	76.9	11 000	61.2	76.6	11 600	63.1	75.3	8 700 *	48.0
52.0	55.9	74.3	9 200	58.1	73.9	9 800	59.9	72.6	8 300 *	52.0
56.0	52.6	71.3	7 800	54.8	70.9	8 200	56.5	69.6	8 000 *	56.0
60.0	49.2	67.9	6 500	51.4	67.6	6 900	53.0	66.2	7 200	60.0
64.0	45.6	64.1	5 400	47.7	63.7	5 800	49.3	62.2	6 000	64.0
68.0	41.8	59.8	4 400	43.9	59.4	4 700	45.3	57.8	4 900	68.0
72.0	37.6	54.8	3 500	39.6	54.4	3 800				72.0
76.0	32.9	48.9	2 800	35.0	48.5	3 000				76.0
80.0	27.6	41.8	2 100							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
18.3	80.3	91.7	16 100 *							18.3
20.0	79.2	91.3	15 900 *							20.0
22.0	77.9	90.9	15 700 *	80.1	90.5	13 300*				22.0
24.0	76.6	90.4	15 400 *	78.8	90.0	13 300*				24.0
26.0	75.3	89.9	15 200 *	77.5	89.5	13 300*	79.6	88.4	12 300*	26.0
28.0	74.0	89.3	14 900 *	76.2	88.9	13 300*	78.2	87.8	11 900*	28.0
30.0	72.7	88.7	14 700 *	74.9	88.3	13 200*	76.9	87.2	11 500*	30.0
32.0	71.3	88.0	14 500 *	73.5	87.6	13 000*	75.5	86.5	11 100*	32.0
34.0	70.0	87.2	14 200 *	72.2	86.8	12 900*	74.1	85.7	10 800*	34.0
36.0	68.6	86.4	14 000 *	70.8	86.1	12 800*	72.8	84.9	10 400*	36.0
38.0	67.3	85.6	13 800 *	69.4	85.2	12 700*	71.4	84.1	10 100*	38.0
40.0	65.9	84.7	13 500 *	68.0	84.3	12 500*	69.9	83.1	9 800*	40.0
44.0	63.1	82.7	12 700	65.2	82.3	12 200*	67.1	81.1	9 300*	44.0
48.0	60.2	80.4	10 700	62.3	80.1	11 400	64.1	78.8	8 800*	48.0
52.0	57.2	77.9	9 000	59.3	77.5	9 500	61.1	76.3	8 500*	52.0
56.0	54.1	75.1	7 500	56.2	74.7	8 000	57.9	73.4	8 100*	56.0
60.0	50.9	71.9	6 200	52.9	71.5	6 700	54.6	70.1	7 000	60.0
64.0	47.5	68.3	5 100	49.5	67.9	5 500	51.1	66.5	5 800	64.0
68.0	43.9	64.3	4 200	45.9	63.9	4 500	47.4	62.3	4 800	68.0
72.0	40.0	59.7	3 300	42.0	59.3	3 600	43.4	57.6	3 800	72.0
76.0	35.8	54.4	2 500	37.8	53.9	2 800				76.0
80.0				33.1	47.6	2 000				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
18.3	80.6	94.7	16 100 *							18.3
20.0	79.6	94.4	15 800 *							20.0
22.0	78.3	94.0	15 600 *	80.5	93.6	13 300*				22.0
24.0	77.1	93.5	15 400 *	79.2	93.1	13 300*				24.0
26.0	75.8	93.0	15 100 *	77.9	92.6	13 300*	79.9	91.5	12 500*	26.0
28.0	74.5	92.4	14 900 *	76.7	92.0	13 300*	78.6	90.9	12 000*	28.0
30.0	73.3	91.8	14 700 *	75.4	91.4	13 100*	77.3	90.3	11 600*	30.0
32.0	72.0	91.2	14 500 *	74.1	90.8	13 000*	76.0	89.6	11 200*	32.0
34.0	70.7	90.4	14 200 *	72.8	90.0	12 900*	74.7	88.9	10 900*	34.0
36.0	69.4	89.7	14 000 *	71.5	89.3	12 800*	73.3	88.1	10 600*	36.0
38.0	68.0	88.9	13 800 *	70.1	88.5	12 700*	72.0	87.3	10 300*	38.0
40.0	66.7	88.0	13 600 *	68.8	87.6	12 500*	70.6	86.4	10 000*	40.0
44.0	64.0	86.1	12 700	66.1	85.7	12 300*	67.9	84.5	9 500*	44.0
48.0	61.2	83.9	10 700	63.3	83.5	11 400	65.1	82.3	9 000*	48.0
52.0	58.4	81.5	9 000	60.4	81.1	9 600	62.1	79.9	8 600*	52.0
56.0	55.4	78.8	7 500	57.4	78.4	8 000	59.1	77.1	8 200*	56.0
60.0	52.4	75.8	6 300	54.4	75.4	6 700	56.0	74.0	7 100	60.0
64.0	49.2	72.4	5 200	51.2	72.0	5 600	52.7	70.6	5 800	64.0
68.0	45.8	68.6	4 200	47.8	68.2	4 500	49.2	66.7	4 800	68.0
72.0	42.2	64.3	3 300	44.2	63.9	3 600	45.5	62.3	3 900	72.0
76.0	38.3	59.4	2 600	40.3	59.0	2 800				76.0
80.0	34.1	53.8	1 900	36.0	53.4	2 100				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
18.3	80.9	97.8	16 000 *							18.3
20.0	79.9	97.5	15 800 *							20.0
22.0	78.7	97.1	15 500 *							22.0
24.0	77.5	96.6	15 300 *	79.5	96.2	13 300*				24.0
26.0	76.3	96.1	15 100 *	78.3	95.7	13 300*	80.2	94.6	12 500*	26.0
28.0	75.0	95.6	14 900 *	77.1	95.1	13 200*	79.0	94.0	12 100*	28.0
30.0	73.8	95.0	14 700 *	75.8	94.6	13 100*	77.7	93.4	11 700*	30.0
32.0	72.5	94.3	14 500 *	74.6	93.9	13 000*	76.5	92.8	11 400*	32.0
34.0	71.3	93.6	14 200 *	73.3	93.2	12 800*	75.2	92.1	11 000*	34.0
36.0	70.0	92.9	14 000 *	72.1	92.5	12 800*	73.9	91.4	10 700*	36.0
38.0	68.8	92.1	13 800 *	70.8	91.7	12 700*	72.6	90.6	10 400*	38.0
40.0	67.5	91.3	13 600 *	69.5	90.9	12 500*	71.3	89.7	10 100*	40.0
44.0	64.9	89.4	12 300	66.9	89.0	12 300*	68.6	87.8	9 600*	44.0
48.0	62.2	87.4	10 400	64.2	87.0	11 100	65.9	85.7	9 100*	48.0
52.0	59.5	85.0	8 800	61.5	84.7	9 400	63.1	83.4	8 700*	52.0
56.0	56.6	82.5	7 300	58.6	82.1	7 800	60.3	80.8	8 200	56.0
60.0	53.7	79.6	6 000	55.7	79.2	6 500	57.3	77.9	6 900	60.0
64.0	50.7	76.4	4 900	52.6	76.0	5 300	54.2	74.6	5 700	64.0
68.0	47.5	72.8	3 900	49.4	72.4	4 300	50.9	70.9	4 600	68.0
72.0	44.2	68.8	3 100	46.1	68.4	3 400	47.5	66.8	3 700	72.0
76.0	40.6	64.3	2 300	42.5	63.9	2 600	43.8	62.2	2 800	76.0
80.0				38.6	58.7	1 900				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
12.2	79.3	50.2	13 300 *							12.2
14.0	77.1	49.8	13 100 *							14.0
16.0	74.7	49.2	12 700 *	79.1	48.9	12 200*				16.0
18.0	72.2	48.6	12 400 *	76.6	48.2	11 800*				18.0
20.0	69.7	47.8	12 000 *	74.1	47.4	11 400*	78.7	46.6	10 200*	20.0
22.0	67.1	46.9	11 700 *	71.5	46.6	11 100*	76.0	45.7	9 500*	22.0
24.0	64.5	46.0	11 300 *	68.9	45.6	10 700*	73.4	44.7	8 900*	24.0
26.0	61.9	44.9	10 900 *	66.2	44.5	10 400*	70.6	43.6	8 400*	26.0
28.0	59.1	43.7	10 600 *	63.5	43.3	10 100*	67.8	42.3	7 900*	28.0
30.0	56.3	42.4	10 200 *	60.6	41.9	9 800*	64.9	40.9	7 500*	30.0
32.0	53.4	40.9	9 900 *	57.6	40.4	9 200*	61.8	39.4	7 100*	32.0
34.0	50.3	39.2	9 600 *	54.6	38.8	8 700*	58.6	37.6	6 800*	34.0
36.0	47.1	37.4	9 300 *	51.3	36.9	8 200*	55.3	35.7	6 500*	36.0
38.0	43.7	35.3	9 000 *	47.9	34.8	7 800*	51.7	33.5	6 200*	38.0
40.0	40.1	32.9	8 800 *	44.2	32.4	7 400*	47.9	31.0	5 900*	40.0
44.0	31.8	27.1	7 800 *	35.7	26.4	6 800*				44.0
30.5m Boom										
12.2	79.9	53.3	13 300 *							12.2
14.0	77.9	52.9	13 200 *							14.0
16.0	75.6	52.3	12 800 *	79.8	52.0	12 300*				16.0
18.0	73.3	51.7	12 500 *	77.5	51.4	11 900*				18.0
20.0	70.9	51.0	12 100 *	75.1	50.6	11 500*	79.4	49.7	10 500*	20.0
22.0	68.6	50.2	11 800 *	72.7	49.8	11 200*	76.9	48.9	9 800*	22.0
24.0	66.1	49.3	11 400 *	70.3	48.9	10 900*	74.4	48.0	9 100*	24.0
26.0	63.7	48.3	11 100 *	67.8	47.9	10 600*	71.9	47.0	8 600*	26.0
28.0	61.1	47.2	10 800 *	65.2	46.8	10 300*	69.3	45.8	8 100*	28.0
30.0	58.5	46.0	10 500 *	62.6	45.6	10 000*	66.6	44.5	7 700*	30.0
32.0	55.9	44.6	10 200 *	59.9	44.2	9 700*	63.8	43.1	7 300*	32.0
34.0	53.1	43.1	9 900 *	57.1	42.7	9 100*	61.0	41.6	7 000*	34.0
36.0	50.2	41.4	9 600 *	54.2	41.0	8 600*	58.0	39.8	6 700*	36.0
38.0	47.2	39.6	9 300 *	51.1	39.1	8 200*	54.8	37.9	6 400*	38.0
40.0	44.0	37.5	9 100 *	47.9	37.0	7 800*	51.5	35.7	6 200*	40.0
44.0	37.0	32.6	8 400 *	40.7	32.0	7 100*	44.0	30.5	5 800*	44.0
48.0	28.5	26.0	7 600 *	32.0	25.2	6 600*				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	80.5	56.3	13 300 *							12.2
14.0	78.5	55.9	13 200 *							14.0
16.0	76.4	55.5	12 800 *							16.0
18.0	74.2	54.9	12 500 *	78.2	54.5	12 000*				18.0
20.0	72.0	54.2	12 200 *	76.0	53.8	11 700*	80.0	52.9	10 600*	20.0
22.0	69.8	53.5	11 900 *	73.7	53.1	11 300*	77.7	52.1	9 900*	22.0
24.0	67.5	52.6	11 500 *	71.4	52.2	11 000*	75.4	51.2	9 400*	24.0
26.0	65.2	51.7	11 200 *	69.1	51.3	10 700*	73.0	50.3	8 800*	26.0
28.0	62.9	50.7	10 900 *	66.7	50.2	10 400*	70.6	49.2	8 400*	28.0
30.0	60.5	49.5	10 600 *	64.3	49.1	10 200*	68.1	48.0	7 900*	30.0
32.0	58.0	48.3	10 300 *	61.8	47.8	9 900*	65.6	46.7	7 600*	32.0
34.0	55.4	46.9	10 100 *	59.2	46.4	9 500*	62.9	45.3	7 200*	34.0
36.0	52.8	45.4	9 800 *	56.6	44.9	9 000*	60.2	43.7	6 900*	36.0
38.0	50.1	43.7	9 500 *	53.8	43.2	8 500*	57.4	42.0	6 600*	38.0
40.0	47.2	41.8	9 300 *	50.9	41.3	8 200*	54.4	40.1	6 400*	40.0
44.0	41.1	37.5	8 800 *	44.7	36.9	7 500*	47.9	35.5	6 000*	44.0
48.0	34.0	32.0	8 100 *	37.5	31.3	6 900*				48.0
52.0	25.1	24.6	7 400 *							52.0
36.5m Boom										
12.2	81.0	59.4	13 300 *							12.2
14.0	79.2	59.0	13 200 *							14.0
16.0	77.1	58.6	12 800 *							16.0
18.0	75.1	58.0	12 500 *	78.8	57.6	12 100*				18.0
20.0	73.0	57.4	12 200 *	76.7	57.0	11 800*	80.6	56.0	10 800*	20.0
22.0	70.9	56.7	12 000 *	74.6	56.3	11 400*	78.4	55.3	10 100*	22.0
24.0	68.8	55.9	11 600 *	72.5	55.5	11 100*	76.2	54.5	9 600*	24.0
26.0	66.6	55.0	11 300 *	70.3	54.6	10 900*	74.0	53.6	9 000*	26.0
28.0	64.4	54.0	11 000 *	68.1	53.6	10 600*	71.7	52.6	8 600*	28.0
30.0	62.1	53.0	10 800 *	65.8	52.5	10 300*	69.4	51.5	8 200*	30.0
32.0	59.9	51.8	10 500 *	63.5	51.4	10 100*	67.1	50.3	7 800*	32.0
34.0	57.5	50.5	10 200 *	61.1	50.1	9 800*	64.6	49.0	7 400*	34.0
36.0	55.1	49.1	10 000 *	58.7	48.7	9 400*	62.1	47.5	7 200*	36.0
38.0	52.6	47.6	9 800 *	56.1	47.1	8 900*	59.5	45.9	6 900*	38.0
40.0	50.0	45.9	9 500 *	53.5	45.4	8 500*	56.8	44.2	6 600*	40.0
44.0	44.5	42.0	9 000 *	47.9	41.5	7 800*	51.1	40.1	6 100*	44.0
48.0	38.3	37.3	8 600 *	41.7	36.6	7 200*	44.6	35.1	5 800*	48.0
52.0	31.1	31.2	7 800 *	34.3	30.4	6 700*				52.0
56.0	21.8	22.7	7 100 *							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
13.7	80.0	62.1	13 200 *							13.7
14.0	79.7	62.1	13 200 *							14.0
16.0	77.8	61.6	12 800 *							16.0
18.0	75.8	61.1	12 500 *	79.4	60.7	12 100*				18.0
20.0	73.9	60.5	12 300 *	77.4	60.1	11 800*				20.0
22.0	71.9	59.9	12 000 *	75.4	59.5	11 500*	79.0	58.4	10 300*	22.0
24.0	69.9	59.1	11 700 *	73.4	58.7	11 300*	77.0	57.7	9 800*	24.0
26.0	67.8	58.3	11 400 *	71.3	57.9	11 000*	74.9	56.8	9 200*	26.0
28.0	65.8	57.4	11 100 *	69.2	57.0	10 700*	72.8	55.9	8 800*	28.0
30.0	63.6	56.4	10 800 *	67.1	55.9	10 500*	70.6	54.9	8 400*	30.0
32.0	61.5	55.3	10 600 *	65.0	54.8	10 200*	68.4	53.7	8 000*	32.0
34.0	59.3	54.1	10 300 *	62.7	53.6	10 000*	66.1	52.5	7 600*	34.0
36.0	57.1	52.8	10 100 *	60.5	52.3	9 700*	63.8	51.2	7 300*	36.0
38.0	54.7	51.4	9 900 *	58.1	50.9	9 300*	61.4	49.7	7 000*	38.0
40.0	52.4	49.8	9 700 *	55.7	49.3	8 900*	58.9	48.1	6 800*	40.0
44.0	47.3	46.3	9 200 *	50.7	45.8	8 100*	53.7	44.4	6 300*	44.0
48.0	41.9	42.1	8 800 *	45.1	41.5	7 500*	47.9	40.0	6 000*	48.0
52.0	35.7	36.9	8 200 *	38.8	36.2	7 000*				52.0
56.0	28.3	30.1	7 600 *	31.2	29.2	6 500*				56.0
42.5m Boom										
13.7	80.4	65.2	13 100 *							13.7
14.0	80.2	65.1	13 100 *							14.0
16.0	78.4	64.7	12 800 *							16.0
18.0	76.5	64.2	12 500 *							18.0
20.0	74.6	63.7	12 300 *	78.0	63.3	11 900*				20.0
22.0	72.8	63.0	12 000 *	76.1	62.6	11 600*	79.6	61.6	10 500*	22.0
24.0	70.9	62.3	11 800 *	74.2	61.9	11 300*	77.6	60.9	9 900*	24.0
26.0	68.9	61.6	11 500 *	72.3	61.1	11 100*	75.7	60.1	9 400*	26.0
28.0	67.0	60.7	11 200 *	70.3	60.3	10 800*	73.7	59.2	9 000*	28.0
30.0	65.0	59.8	10 900 *	68.3	59.3	10 600*	71.6	58.2	8 600*	30.0
32.0	63.0	58.7	10 700 *	66.3	58.3	10 400*	69.5	57.2	8 200*	32.0
34.0	60.9	57.6	10 400 *	64.2	57.1	10 100*	67.4	56.0	7 900*	34.0
36.0	58.8	56.4	10 200 *	62.1	55.9	9 900*	65.3	54.8	7 500*	36.0
38.0	56.7	55.1	10 000 *	59.9	54.6	9 700*	63.0	53.4	7 300*	38.0
40.0	54.4	53.6	9 800 *	57.7	53.1	9 200*	60.8	51.9	7 000*	40.0
44.0	49.8	50.4	9 400 *	53.0	49.8	8 400*	56.0	48.5	6 500*	44.0
48.0	44.8	46.5	9 000 *	48.0	46.0	7 800*	50.8	44.5	6 100*	48.0
52.0	39.4	41.9	8 600 *	42.4	41.3	7 200*	45.0	39.7	5 800*	52.0
56.0	33.1	36.2	8 000 *	36.0	35.4	6 800*				56.0
60.0	25.5	28.7	7 400 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	80.9	68.2	13 100 *							13.7
14.0	80.6	68.2	13 100 *							14.0
16.0	78.9	67.8	12 800 *							16.0
18.0	77.1	67.3	12 500 *							18.0
20.0	75.3	66.8	12 300 *	78.6	66.4	12 000*				20.0
22.0	73.6	66.2	12 000 *	76.8	65.8	11 700*	80.1	64.7	10 600*	22.0
24.0	71.8	65.5	11 700 *	75.0	65.1	11 400*	78.2	64.0	10 100*	24.0
26.0	69.9	64.8	11 500 *	73.1	64.3	11 100*	76.4	63.3	9 600*	26.0
28.0	68.1	64.0	11 200 *	71.3	63.5	10 900*	74.5	62.4	9 100*	28.0
30.0	66.2	63.1	11 000 *	69.4	62.6	10 700*	72.5	61.5	8 700*	30.0
32.0	64.3	62.1	10 700 *	67.4	61.6	10 500*	70.6	60.5	8 300*	32.0
34.0	62.3	61.1	10 500 *	65.5	60.6	10 200*	68.6	59.4	8 000*	34.0
36.0	60.4	59.9	10 300 *	63.5	59.4	10 000*	66.6	58.3	7 700*	36.0
38.0	58.4	58.7	10 000 *	61.5	58.2	9 800*	64.5	57.0	7 400*	38.0
40.0	56.3	57.3	9 900 *	59.4	56.8	9 500*	62.4	55.6	7 200*	40.0
44.0	52.0	54.3	9 400 *	55.0	53.8	8 700*	57.9	52.5	6 700*	44.0
48.0	47.4	50.8	9 100 *	50.4	50.2	8 100*	53.2	48.8	6 300*	48.0
52.0	42.5	46.6	8 700 *	45.4	46.0	7 500*	48.0	44.5	6 000*	52.0
56.0	37.0	41.6	8 400 *	39.8	40.9	7 000*	42.1	39.1	5 700*	56.0
60.0	30.6	35.3	7 800 *	33.3	34.5	6 600*				60.0
64.0	22.6	26.9	7 200 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
15.2	80.0	71.0	12 900 *							15.2
16.0	79.4	70.9	12 800 *							16.0
18.0	77.7	70.4	12 500 *							18.0
20.0	76.0	69.9	12 300 *	79.1	69.5	11 900*				20.0
22.0	74.3	69.3	12 000 *	77.4	68.9	11 700*				22.0
24.0	72.6	68.7	11 800 *	75.6	68.3	11 500*	78.8	67.2	10 300*	24.0
26.0	70.8	68.0	11 600 *	73.9	67.5	11 200*	77.0	66.5	9 800*	26.0
28.0	69.1	67.2	11 300 *	72.1	66.8	11 000*	75.2	65.7	9 300*	28.0
30.0	67.3	66.4	11 000 *	70.3	65.9	10 800*	73.4	64.8	8 900*	30.0
32.0	65.5	65.5	10 800 *	68.5	65.0	10 600*	71.5	63.9	8 500*	32.0
34.0	63.6	64.5	10 600 *	66.7	64.0	10 400*	69.6	62.8	8 200*	34.0
36.0	61.8	63.4	10 300 *	64.8	62.9	10 200*	67.7	61.7	7 900*	36.0
38.0	59.9	62.2	10 100 *	62.9	61.7	10 000*	65.8	60.5	7 600*	38.0
40.0	57.9	60.9	9 900 *	60.9	60.4	9 800*	63.8	59.2	7 300*	40.0
44.0	53.9	58.1	9 500 *	56.9	57.6	9 100*	59.6	56.3	6 900*	44.0
48.0	49.7	54.9	9 200 *	52.6	54.3	8 400*	55.2	52.9	6 500*	48.0
52.0	45.1	51.0	8 900 *	48.0	50.4	7 800*	50.5	49.0	6 100*	52.0
56.0	40.2	46.5	8 600 *	43.0	45.9	7 300*	45.3	44.2	5 800*	56.0
60.0	34.7	41.1	8 100 *	37.3	40.3	6 900*				60.0
64.0	28.1	34.2	7 400	30.7	33.3	6 500*				64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	80.4	74.1	12 800 *							15.2
16.0	79.8	73.9	12 700 *							16.0
18.0	78.2	73.5	12 400 *							18.0
20.0	76.6	73.0	12 200 *	79.6	72.6	11 900 *				20.0
22.0	75.0	72.5	12 000 *	77.9	72.0	11 700 *				22.0
24.0	73.3	71.9	11 700 *	76.3	71.4	11 500 *	79.3	70.3	10 400 *	24.0
26.0	71.7	71.2	11 500 *	74.6	70.7	11 300 *	77.6	69.6	9 900 *	26.0
28.0	70.0	70.4	11 300 *	72.9	70.0	11 100 *	75.9	68.9	9 500 *	28.0
30.0	68.3	69.6	11 000 *	71.2	69.2	10 900 *	74.1	68.1	9 100 *	30.0
32.0	66.6	68.8	10 800 *	69.5	68.3	10 700 *	72.4	67.2	8 700 *	32.0
34.0	64.8	67.8	10 600 *	67.7	67.3	10 500 *	70.6	66.2	8 400 *	34.0
36.0	63.1	66.8	10 400 *	65.9	66.3	10 300 *	68.8	65.1	8 100 *	36.0
38.0	61.3	65.7	10 200 *	64.1	65.2	10 100 *	66.9	64.0	7 800 *	38.0
40.0	59.4	64.5	9 900 *	62.3	64.0	9 900 *	65.0	62.8	7 500 *	40.0
44.0	55.6	61.8	9 600 *	58.5	61.3	9 400 *	61.2	60.1	7 000 *	44.0
48.0	51.7	58.8	9 300 *	54.5	58.2	8 700 *	57.1	56.9	6 600 *	48.0
52.0	47.5	55.3	9 000 *	50.2	54.7	8 000 *	52.7	53.2	6 300 *	52.0
56.0	43.0	51.1	8 600 *	45.7	50.5	7 500 *	48.0	48.9	6 000 *	56.0
60.0	38.0	46.3	8 300	40.6	45.6	7 100 *	42.8	43.8	5 700 *	60.0
64.0	32.4	40.4	7 100	34.9	39.6	6 700 *				64.0
68.0	25.7	32.9	6 200							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.8	77.1	12 700 *							15.2
16.0	80.2	77.0	12 700 *							16.0
18.0	78.7	76.6	12 400 *							18.0
20.0	77.1	76.1	12 200 *	80.0	75.7	11 800 *				20.0
22.0	75.6	75.6	11 900 *	78.4	75.1	11 600 *				22.0
24.0	74.0	75.0	11 700 *	76.8	74.5	11 500 *	79.7	73.4	10 500 *	24.0
26.0	72.4	74.4	11 500 *	75.2	73.9	11 200 *	78.1	72.8	10 000 *	26.0
28.0	70.8	73.6	11 300 *	73.6	73.2	11 100 *	76.5	72.1	9 600 *	28.0
30.0	69.2	72.9	11 100 *	72.0	72.4	10 900 *	74.8	71.3	9 200 *	30.0
32.0	67.5	72.0	10 800 *	70.3	71.6	10 700 *	73.1	70.4	8 800 *	32.0
34.0	65.9	71.1	10 600 *	68.7	70.7	10 600 *	71.4	69.5	8 500 *	34.0
36.0	64.2	70.2	10 400 *	67.0	69.7	10 400 *	69.7	68.5	8 200 *	36.0
38.0	62.5	69.1	10 200 *	65.3	68.6	10 200 *	68.0	67.4	7 900 *	38.0
40.0	60.8	68.0	10 000 *	63.5	67.5	10 000 *	66.2	66.3	7 700 *	40.0
44.0	57.2	65.5	9 700 *	59.9	65.0	9 600 *	62.5	63.7	7 200 *	44.0
48.0	53.5	62.6	9 400 *	56.2	62.1	8 900 *	58.7	60.7	6 800 *	48.0
52.0	49.6	59.3	9 100 *	52.2	58.7	8 300 *	54.6	57.3	6 400 *	52.0
56.0	45.4	55.5	8 700 *	48.0	54.9	7 800 *	50.3	53.4	6 100 *	56.0
60.0	40.9	51.1	8 000	43.4	50.4	7 300 *	45.6	48.8	5 900 *	60.0
64.0	35.9	45.9	6 900	38.4	45.1	6 900 *				64.0
68.0	30.2	39.5	5 900	32.6	38.6	6 100				68.0
72.0	23.2	31.2	5 000							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
16.8	80.0	79.9	12 500 *							16.8
18.0	79.1	79.6	12 300 *							18.0
20.0	77.6	79.2	12 100 *	80.4	78.7	11 700*				20.0
22.0	76.1	78.7	11 900 *	78.9	78.2	11 500*				22.0
24.0	74.6	78.1	11 700 *	77.4	77.7	11 400*	80.1	76.6	10 600*	24.0
26.0	73.1	77.5	11 500 *	75.8	77.0	11 200*	78.6	75.9	10 200*	26.0
28.0	71.6	76.8	11 300 *	74.3	76.4	11 000*	77.0	75.2	9 800*	28.0
30.0	70.0	76.1	11 100 *	72.7	75.6	10 900*	75.4	74.5	9 400*	30.0
32.0	68.5	75.3	10 800 *	71.1	74.8	10 700*	73.8	73.7	9 000*	32.0
34.0	66.9	74.4	10 600 *	69.6	74.0	10 500*	72.2	72.8	8 700*	34.0
36.0	65.3	73.5	10 400 *	67.9	73.0	10 400*	70.6	71.8	8 400*	36.0
38.0	63.6	72.5	10 200 *	66.3	72.0	10 300*	68.9	70.8	8 100*	38.0
40.0	62.0	71.4	10 000 *	64.6	70.9	10 100*	67.2	69.7	7 800*	40.0
44.0	58.6	69.1	9 700 *	61.2	68.6	9 800*	63.8	67.3	7 300*	44.0
48.0	55.1	66.4	9 400 *	57.7	65.8	9 200*	60.1	64.5	6 900*	48.0
52.0	51.4	63.3	9 100 *	54.0	62.7	8 600*	56.3	61.3	6 600*	52.0
56.0	47.5	59.7	8 800 *	50.1	59.1	8 000*	52.3	57.6	6 200*	56.0
60.0	43.4	55.7	7 700	45.9	55.0	7 600*	48.0	53.4	5 900*	60.0
64.0	38.9	50.9	6 600	41.3	50.2	6 900	43.3	48.4	5 800*	64.0
68.0	33.9	45.3	5 600	36.2	44.5	5 800				68.0
72.0	28.0	38.4	4 800							72.0
76.0	20.7	29.1	4 000							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.4	82.9	12 400 *							16.8
18.0	79.5	82.7	12 200 *							18.0
20.0	78.1	82.3	12 000 *	80.7	81.8	11 700*				20.0
22.0	76.6	81.8	11 800 *	79.3	81.3	11 500*				22.0
24.0	75.2	81.2	11 600 *	77.8	80.8	11 300*				24.0
26.0	73.7	80.7	11 400 *	76.4	80.2	11 100*	79.0	79.1	10 300*	26.0
28.0	72.3	80.0	11 200 *	74.9	79.5	11 000*	77.5	78.4	9 900*	28.0
30.0	70.8	79.3	11 100 *	73.4	78.8	10 800*	76.0	77.7	9 500*	30.0
32.0	69.3	78.5	10 800 *	71.9	78.1	10 700*	74.5	76.9	9 200*	32.0
34.0	67.8	77.7	10 600 *	70.4	77.2	10 500*	72.9	76.1	8 800*	34.0
36.0	66.2	76.8	10 400 *	68.8	76.3	10 400*	71.4	75.2	8 500*	36.0
38.0	64.7	75.9	10 300 *	67.3	75.4	10 300*	69.8	74.2	8 200*	38.0
40.0	63.1	74.9	10 100 *	65.7	74.3	10 100*	68.2	73.1	8 000*	40.0
44.0	59.9	72.6	9 700 *	62.4	72.1	9 800*	64.9	70.8	7 500*	44.0
48.0	56.6	70.0	9 400 *	59.1	69.5	9 500*	61.5	68.2	7 000*	48.0
52.0	53.1	67.1	9 100 *	55.6	66.5	8 900*	57.9	65.2	6 700*	52.0
56.0	49.5	63.8	8 700	51.9	63.2	8 300*	54.1	61.8	6 400*	56.0
60.0	45.6	60.0	7 500	48.0	59.4	7 700	50.1	57.8	6 100*	60.0
64.0	41.5	55.7	6 300	43.8	55.0	6 700	45.8	53.3	5 800*	64.0
68.0	36.9	50.6	5 400	39.2	49.8	5 600				68.0
72.0	31.9	44.5	4 500	34.1	43.7	4 700				72.0
76.0	25.9	37.0	3 700							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.7	86.0	12 200 *							16.8
18.0	79.9	85.8	12 100 *							18.0
20.0	78.5	85.3	11 900 *							20.0
22.0	77.1	84.9	11 700 *	79.7	84.4	11 400*				22.0
24.0	75.7	84.4	11 600 *	78.3	83.9	11 300*				24.0
26.0	74.3	83.8	11 300 *	76.9	83.3	11 100*	79.4	82.2	10 500*	26.0
28.0	72.9	83.2	11 200 *	75.4	82.7	10 900*	78.0	81.5	10 000*	28.0
30.0	71.5	82.5	11 000 *	74.0	82.0	10 800*	76.5	80.9	9 600*	30.0
32.0	70.1	81.8	10 800 *	72.6	81.3	10 700*	75.1	80.1	9 300*	32.0
34.0	68.6	81.0	10 600 *	71.1	80.5	10 500*	73.6	79.3	8 900*	34.0
36.0	67.1	80.1	10 400 *	69.6	79.6	10 400*	72.1	78.4	8 700*	36.0
38.0	65.6	79.2	10 200 *	68.1	78.7	10 300*	70.6	77.5	8 400*	38.0
40.0	64.1	78.2	10 000 *	66.6	77.7	10 100*	69.0	76.5	8 100*	40.0
44.0	61.1	76.1	9 700 *	63.5	75.6	9 800*	65.9	74.3	7 600*	44.0
48.0	57.9	73.6	9 400 *	60.3	73.1	9 600*	62.6	71.8	7 200*	48.0
52.0	54.6	70.9	9 100 *	57.0	70.3	9 100*	59.3	68.9	6 800*	52.0
56.0	51.2	67.7	8 500	53.6	67.2	8 500*	55.7	65.7	6 500*	56.0
60.0	47.6	64.2	7 200	49.9	63.6	7 600	52.0	62.1	6 200*	60.0
64.0	43.7	60.2	6 100	46.0	59.5	6 400	48.0	57.9	6 000*	64.0
68.0	39.6	55.5	5 100	41.9	54.8	5 400	43.7	53.0	5 700	68.0
72.0	35.1	50.1	4 300	37.2	49.3	4 500				72.0
76.0	29.9	43.6	3 500	32.0	42.7	3 700				76.0
80.0	23.7	35.4	2 800							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
18.3	80.1	88.8	12 600 *							18.3
20.0	78.9	88.4	12 400 *							20.0
22.0	77.6	88.0	12 200 *	80.0	87.5	11 800*				22.0
24.0	76.2	87.5	12 000 *	78.7	87.0	11 700*				24.0
26.0	74.9	86.9	11 800 *	77.3	86.4	11 500*	79.8	85.3	10 600*	26.0
28.0	73.5	86.3	11 600 *	76.0	85.8	11 300*	78.4	84.7	10 100*	28.0
30.0	72.1	85.7	11 400 *	74.6	85.2	11 100*	77.0	84.0	9 800*	30.0
32.0	70.8	85.0	11 200 *	73.2	84.5	11 000*	75.6	83.3	9 400*	32.0
34.0	69.4	84.2	11 000 *	71.8	83.7	10 800*	74.2	82.5	9 100*	34.0
36.0	68.0	83.4	10 800 *	70.4	82.9	10 600*	72.8	81.7	8 800*	36.0
38.0	66.5	82.5	10 600 *	68.9	82.0	10 500*	71.3	80.8	8 500*	38.0
40.0	65.1	81.6	10 400 *	67.5	81.1	10 300*	69.8	79.8	8 200*	40.0
44.0	62.2	79.5	10 000 *	64.5	79.0	10 000*	66.8	77.7	7 800*	44.0
48.0	59.1	77.2	9 700 *	61.5	76.6	9 700*	63.7	75.3	7 300*	48.0
52.0	56.0	74.6	9 300 *	58.3	74.0	9 400*	60.5	72.7	7 000*	52.0
56.0	52.8	71.6	8 200	55.1	71.0	8 700	57.2	69.6	6 600*	56.0
60.0	49.4	68.3	7 000	51.6	67.7	7 400	53.7	66.2	6 300*	60.0
64.0	45.8	64.5	5 900	48.0	63.9	6 200	50.0	62.3	6 100*	64.0
68.0	42.0	60.2	4 900	44.2	59.5	5 200	46.0	57.8	5 500	68.0
72.0	37.8	55.3	4 000	40.0	54.5	4 300				72.0
76.0	33.2	49.5	3 300	35.3	48.6	3 500				76.0
80.0	28.0	42.5	2 600							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
18.3	80.4	91.8	12 400 *							18.3
20.0	79.3	91.5	12 200 *							20.0
22.0	78.0	91.0	12 000 *	80.4	90.6	11 700*				22.0
24.0	76.7	90.6	11 800 *	79.1	90.1	11 600*				24.0
26.0	75.4	90.0	11 600 *	77.8	89.6	11 400*	80.2	88.4	10 600*	26.0
28.0	74.1	89.5	11 500 *	76.4	89.0	11 300*	78.8	87.8	10 300*	28.0
30.0	72.8	88.8	11 300 *	75.1	88.3	11 100*	77.5	87.2	9 900*	30.0
32.0	71.4	88.1	11 200 *	73.8	87.7	11 000*	76.1	86.5	9 500*	32.0
34.0	70.1	87.4	11 000 *	72.4	86.9	10 800*	74.8	85.7	9 200*	34.0
36.0	68.7	86.6	10 800 *	71.1	86.1	10 700*	73.4	84.9	8 900*	36.0
38.0	67.4	85.8	10 600 *	69.7	85.3	10 500*	72.0	84.1	8 600*	38.0
40.0	66.0	84.9	10 400 *	68.3	84.4	10 400*	70.6	83.2	8 300*	40.0
44.0	63.2	82.9	10 000 *	65.5	82.4	10 100*	67.7	81.1	7 900*	44.0
48.0	60.3	80.7	9 700 *	62.6	80.2	9 800*	64.7	78.9	7 500*	48.0
52.0	57.3	78.2	9 300	59.6	77.6	9 500*	61.7	76.3	7 100*	52.0
56.0	54.2	75.4	7 900	56.4	74.8	8 400	58.5	73.4	6 700*	56.0
60.0	51.0	72.2	6 700	53.2	71.6	7 100	55.2	70.2	6 400*	60.0
64.0	47.6	68.7	5 600	49.8	68.0	5 900	51.7	66.5	6 200*	64.0
68.0	44.1	64.7	4 600	46.2	64.0	4 900	48.0	62.4	5 200	68.0
72.0	40.2	60.1	3 700	42.3	59.4	4 000	44.1	57.6	4 300	72.0
76.0	36.1	54.9	2 900	38.1	54.1	3 200				76.0
80.0	31.4	48.7	2 300	33.4	47.8	2 400				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
18.3	80.7	94.9	12 300 *							18.3
20.0	79.6	94.5	12 100 *							20.0
22.0	78.4	94.1	11 900 *							22.0
24.0	77.1	93.7	11 700 *	79.4	93.2	11 500 *				24.0
26.0	75.9	93.1	11 600 *	78.2	92.7	11 300 *	80.5	91.5	10 600 *	26.0
28.0	74.6	92.6	11 400 *	76.9	92.1	11 200 *	79.2	90.9	10 400 *	28.0
30.0	73.3	92.0	11 200 *	75.6	91.5	11 000 *	77.9	90.3	10 000 *	30.0
32.0	72.0	91.3	11 100 *	74.3	90.8	10 900 *	76.6	89.6	9 700 *	32.0
34.0	70.7	90.6	10 900 *	73.0	90.1	10 800 *	75.3	88.9	9 300 *	34.0
36.0	69.4	89.9	10 800 *	71.7	89.4	10 600 *	74.0	88.2	9 000 *	36.0
38.0	68.1	89.1	10 600 *	70.4	88.5	10 500 *	72.6	87.3	8 800 *	38.0
40.0	66.8	88.2	10 400 *	69.0	87.7	10 400 *	71.3	86.4	8 500 *	40.0
44.0	64.1	86.3	10 100 *	66.3	85.8	10 100 *	68.5	84.5	8 000 *	44.0
48.0	61.3	84.2	9 700 *	63.5	83.6	9 800 *	65.7	82.3	7 600 *	48.0
52.0	58.5	81.8	9 100	60.7	81.2	9 600	62.7	79.9	7 200 *	52.0
56.0	55.5	79.1	7 700	57.7	78.5	8 200	59.7	77.1	6 900 *	56.0
60.0	52.5	76.1	6 400	54.6	75.5	6 900	56.6	74.1	6 600 *	60.0
64.0	49.3	72.7	5 300	51.4	72.1	5 700	53.3	70.6	6 100	64.0
68.0	45.9	69.0	4 400	48.0	68.3	4 700	49.9	66.7	5 000	68.0
72.0	42.4	64.7	3 500	44.4	64.0	3 800	46.2	62.3	4 000	72.0
76.0	38.6	59.9	2 700	40.6	59.2	3 000	42.2	57.3	3 200	76.0
80.0	34.4	54.3	2 000	36.3	53.5	2 200				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
18.3	81.0	97.9	12 100 *							18.3
20.0	80.0	97.6	12 000 *							20.0
22.0	78.8	97.2	11 800 *							22.0
24.0	77.5	96.7	11 600 *	79.8	96.3	11 400 *				24.0
26.0	76.3	96.2	11 400 *	78.5	95.8	11 200 *	80.8	94.6	10 500 *	26.0
28.0	75.1	95.7	11 300 *	77.3	95.2	11 100 *	79.6	94.0	10 400 *	28.0
30.0	73.9	95.1	11 100 *	76.1	94.6	10 900 *	78.3	93.4	10 100 *	30.0
32.0	72.6	94.5	11 000 *	74.8	94.0	10 800 *	77.0	92.8	9 700 *	32.0
34.0	71.4	93.8	10 800 *	73.6	93.3	10 700 *	75.8	92.1	9 500 *	34.0
36.0	70.1	93.1	10 700 *	72.3	92.6	10 600 *	74.5	91.4	9 200 *	36.0
38.0	68.8	92.3	10 500 *	71.0	91.8	10 400 *	73.2	90.6	8 900 *	38.0
40.0	67.6	91.5	10 300 *	69.7	90.9	10 300 *	71.9	89.7	8 600 *	40.0
44.0	65.0	89.6	10 000 *	67.1	89.1	10 100 *	69.2	87.9	8 100 *	44.0
48.0	62.3	87.6	9 700 *	64.4	87.0	9 800 *	66.5	85.8	7 700 *	48.0
52.0	59.6	85.3	9 200	61.7	84.7	9 600	63.7	83.4	7 300 *	52.0
56.0	56.8	82.7	7 700	58.9	82.2	8 200	60.8	80.8	7 000 *	56.0
60.0	53.8	79.9	6 400	55.9	79.3	6 900	57.9	77.9	6 700 *	60.0
64.0	50.8	76.7	5 300	52.9	76.1	5 800	54.8	74.6	6 100	64.0
68.0	47.7	73.2	4 400	49.7	72.5	4 700	51.5	70.9	5 000	68.0
72.0	44.3	69.2	3 500	46.3	68.5	3 800	48.0	66.8	4 100	72.0
76.0	40.8	64.7	2 800	42.7	64.0	3 000	44.4	62.2	3 300	76.0
80.0	36.9	59.6	2 000	38.8	58.8	2 300				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
19.8	80.4	100.7	11 800 *							19.8
20.0	80.3	100.6	11 800 *							20.0
22.0	79.1	100.3	11 600 *							22.0
24.0	77.9	99.8	11 500 *	80.1	99.3	11 200*				24.0
26.0	76.7	99.3	11 300 *	78.9	98.8	11 100*				26.0
28.0	75.6	98.8	11 100 *	77.7	98.3	10 900*	79.9	97.1	10 400*	28.0
30.0	74.4	98.2	11 000 *	76.5	97.8	10 800*	78.7	96.6	10 200*	30.0
32.0	73.2	97.6	10 800 *	75.3	97.1	10 700*	77.5	95.9	9 900*	32.0
34.0	72.0	97.0	10 700 *	74.1	96.5	10 600*	76.2	95.3	9 500*	34.0
36.0	70.7	96.3	10 600 *	72.9	95.8	10 500*	75.0	94.6	9 200*	36.0
38.0	69.5	95.5	10 400 *	71.6	95.0	10 300*	73.7	93.8	9 000*	38.0
40.0	68.3	94.7	10 300 *	70.4	94.2	10 200*	72.5	93.0	8 700*	40.0
44.0	65.8	93.0	9 900 *	67.9	92.4	10 000*	69.9	91.2	8 200*	44.0
48.0	63.2	91.0	9 700 *	65.3	90.4	9 800*	67.3	89.2	7 800*	48.0
52.0	60.6	88.8	8 900	62.7	88.2	9 600	64.6	86.9	7 500*	52.0
56.0	57.9	86.3	7 500	59.9	85.8	8 000	61.9	84.4	7 100*	56.0
60.0	55.1	83.6	6 200	57.1	83.0	6 700	59.0	81.6	6 800*	60.0
64.0	52.2	80.6	5 100	54.2	80.0	5 500	56.1	78.5	5 900	64.0
68.0	49.2	77.2	4 100	51.2	76.6	4 500	53.0	75.0	4 800	68.0
72.0	46.1	73.5	3 200	48.0	72.8	3 600	49.7	71.2	3 900	72.0
76.0	42.8	69.3	2 500	44.7	68.6	2 800	46.3	66.8	3 000	76.0
80.0				41.1	63.8	2 100	42.6	61.9	2 300	80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
12.2	79.5	53.3	10 600 *							12.2
14.0	77.4	52.9	10 300 *							14.0
16.0	75.2	52.4	10 000 *	80.0	52.1	9 900*				16.0
18.0	72.8	51.8	9 700 *	77.7	51.5	9 600*				18.0
20.0	70.5	51.1	9 400 *	75.3	50.8	9 300*	80.3	49.9	8 900*	20.0
22.0	68.1	50.3	9 100 *	72.9	50.0	9 000*	77.9	49.1	8 600*	22.0
24.0	65.7	49.4	8 900 *	70.5	49.1	8 700*	75.4	48.1	8 200*	24.0
26.0	63.2	48.4	8 600 *	68.0	48.1	8 500*	72.8	47.1	7 600*	26.0
28.0	60.7	47.3	8 300 *	65.4	46.9	8 200*	70.2	46.0	7 200*	28.0
30.0	58.1	46.1	8 100 *	62.8	45.7	8 000*	67.6	44.7	6 700*	30.0
32.0	55.5	44.7	7 800 *	60.1	44.3	7 700*	64.8	43.3	6 400*	32.0
34.0	52.7	43.2	7 600 *	57.4	42.8	7 500*	62.0	41.7	6 000*	34.0
36.0	49.8	41.5	7 300 *	54.4	41.1	7 300*	59.0	40.0	5 800*	36.0
38.0	46.8	39.7	7 100 *	51.4	39.2	7 000*	55.8	38.1	5 500*	38.0
40.0	43.6	37.6	6 900 *	48.2	37.2	6 600*	52.5	35.9	5 300*	40.0
44.0	36.6	32.7	6 500 *	41.1	32.2	6 000*	45.1	30.7	4 900*	44.0
48.0	28.1	26.1	6 200 *	32.4	25.5	5 500*				48.0
30.5m Boom										
12.2	80.1	56.4	10 600 *							12.2
14.0	78.1	56.0	10 300 *							14.0
16.0	76.0	55.5	10 100 *							16.0
18.0	73.8	54.9	9 800 *	78.4	54.6	9 600*				18.0
20.0	71.6	54.3	9 500 *	76.2	53.9	9 300*				20.0
22.0	69.4	53.5	9 200 *	73.9	53.2	9 100*	78.6	52.3	8 700*	22.0
24.0	67.1	52.7	9 000 *	71.6	52.3	8 800*	76.3	51.4	8 300*	24.0
26.0	64.8	51.8	8 700 *	69.3	51.4	8 600*	73.9	50.4	7 800*	26.0
28.0	62.5	50.7	8 500 *	67.0	50.4	8 300*	71.5	49.4	7 400*	28.0
30.0	60.1	49.6	8 200 *	64.5	49.2	8 100*	69.0	48.2	6 900*	30.0
32.0	57.6	48.3	8 000 *	62.0	47.9	7 800*	66.5	46.9	6 600*	32.0
34.0	55.1	47.0	7 700 *	59.5	46.6	7 700*	63.9	45.5	6 300*	34.0
36.0	52.5	45.4	7 500 *	56.8	45.0	7 400*	61.1	43.9	6 000*	36.0
38.0	49.7	43.8	7 300 *	54.1	43.3	7 200*	58.3	42.2	5 700*	38.0
40.0	46.9	41.9	7 100 *	51.2	41.5	7 000*	55.4	40.3	5 400*	40.0
44.0	40.7	37.6	6 700 *	45.0	37.1	6 300*	48.9	35.7	5 000*	44.0
48.0	33.7	32.1	6 400 *	37.8	31.5	5 800*	41.4	29.9	4 700*	48.0
52.0	24.9	24.7	6 100 *							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	80.6	59.4	10 600 *							12.2
14.0	78.8	59.1	10 300 *							14.0
16.0	76.7	58.6	10 100 *							16.0
18.0	74.7	58.1	9 800 *	79.0	57.7	9 600 *				18.0
20.0	72.6	57.5	9 500 *	76.9	57.1	9 400 *				20.0
22.0	70.5	56.7	9 300 *	74.8	56.4	9 100 *	79.2	55.4	8 700 *	22.0
24.0	68.4	56.0	9 000 *	72.7	55.6	8 900 *	77.1	54.6	8 500 *	24.0
26.0	66.2	55.1	8 800 *	70.5	54.7	8 600 *	74.8	53.7	8 000 *	26.0
28.0	64.0	54.1	8 600 *	68.3	53.7	8 400 *	72.6	52.7	7 500 *	28.0
30.0	61.8	53.1	8 300 *	66.0	52.7	8 200 *	70.3	51.6	7 200 *	30.0
32.0	59.5	51.9	8 100 *	63.7	51.5	8 000 *	67.9	50.4	6 800 *	32.0
34.0	57.1	50.6	7 800 *	61.3	50.2	7 800 *	65.5	49.1	6 500 *	34.0
36.0	54.7	49.2	7 600 *	58.9	48.8	7 600 *	63.0	47.7	6 200 *	36.0
38.0	52.2	47.7	7 400 *	56.4	47.2	7 400 *	60.4	46.1	5 900 *	38.0
40.0	49.6	46.0	7 200 *	53.8	45.6	7 200 *	57.7	44.3	5 700 *	40.0
44.0	44.1	42.1	6 800 *	48.2	41.6	6 700 *	52.0	40.3	5 200 *	44.0
48.0	38.0	37.4	6 500 *	42.0	36.8	6 100 *	45.5	35.3	4 900 *	48.0
52.0	30.8	31.3	6 200 *	34.6	30.7	5 600 *				52.0
56.0	21.5	22.9	6 000 *							56.0
36.5m Boom										
13.7	79.6	62.2	10 400 *							13.7
14.0	79.3	62.1	10 400 *							14.0
16.0	77.4	61.7	10 100 *							16.0
18.0	75.5	61.2	10 000 *	79.6	60.8	9 700 *				18.0
20.0	73.5	60.6	9 600 *	77.6	60.2	9 400 *				20.0
22.0	71.5	59.9	9 300 *	75.6	59.6	9 200 *	79.8	58.6	8 700 *	22.0
24.0	69.5	59.2	9 200 *	73.6	58.8	8 900 *	77.8	57.8	8 600 *	24.0
26.0	67.5	58.4	8 900 *	71.5	58.0	8 700 *	75.7	57.0	8 200 *	26.0
28.0	65.4	57.5	8 600 *	69.4	57.1	8 500 *	73.5	56.0	7 800 *	28.0
30.0	63.3	56.5	8 400 *	67.3	56.1	8 300 *	71.4	55.0	7 300 *	30.0
32.0	61.2	55.4	8 200 *	65.2	55.0	8 100 *	69.2	53.9	7 000 *	32.0
34.0	59.0	54.2	8 000 *	63.0	53.8	7 900 *	66.9	52.7	6 600 *	34.0
36.0	56.7	52.9	7 800 *	60.7	52.5	7 700 *	64.6	51.3	6 300 *	36.0
38.0	54.4	51.5	7 500 *	58.4	51.0	7 500 *	62.2	49.9	6 100 *	38.0
40.0	52.0	49.9	7 300 *	56.0	49.5	7 300 *	59.8	48.3	5 800 *	40.0
44.0	47.0	46.4	7 000 *	50.9	45.9	7 000 *	54.6	44.6	5 400 *	44.0
48.0	41.5	42.2	6 600 *	45.4	41.6	6 400 *	48.8	40.2	5 000 *	48.0
52.0	35.4	37.0	6 300 *	39.1	36.3	5 900 *	42.3	34.7	4 700 *	52.0
56.0	28.0	30.3	6 100 *	31.6	29.5	5 500 *				56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
13.7	80.1	65.3	10 400 *							13.7
14.0	79.8	65.2	10 400 *							14.0
16.0	78.0	64.8	10 200 *							16.0
18.0	76.2	64.3	9 900 *							18.0
20.0	74.3	63.7	9 800 *	78.2	63.4	9 500 *				20.0
22.0	72.4	63.1	9 400 *	76.3	62.7	9 200 *	80.3	61.7	8 700 *	22.0
24.0	70.5	62.4	9 200 *	74.4	62.0	9 000 *	78.4	61.0	8 600 *	24.0
26.0	68.6	61.6	8 900 *	72.5	61.2	8 700 *	76.4	60.2	8 400 *	26.0
28.0	66.6	60.8	8 700 *	70.5	60.4	8 600 *	74.4	59.3	7 900 *	28.0
30.0	64.7	59.8	8 500 *	68.5	59.4	8 400 *	72.4	58.4	7 500 *	30.0
32.0	62.6	58.8	8 300 *	66.5	58.4	8 200 *	70.3	57.3	7 200 *	32.0
34.0	60.6	57.7	8 100 *	64.4	57.3	8 000 *	68.2	56.1	6 800 *	34.0
36.0	58.5	56.5	7 800 *	62.3	56.0	7 800 *	66.0	54.9	6 500 *	36.0
38.0	56.3	55.1	7 600 *	60.1	54.7	7 600 *	63.8	53.5	6 300 *	38.0
40.0	54.1	53.7	7 400 *	57.9	53.3	7 400 *	61.5	52.1	6 000 *	40.0
44.0	49.5	50.5	7 100 *	53.2	50.0	7 100 *	56.8	48.7	5 600 *	44.0
48.0	44.5	46.6	6 700 *	48.2	46.1	6 700 *	51.6	44.7	5 200 *	48.0
52.0	39.1	42.0	6 500 *	42.7	41.4	6 100 *	45.8	39.9	4 900 *	52.0
56.0	32.8	36.3	6 200 *	36.3	35.6	5 700 *				56.0
60.0	25.2	28.9	6 000 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.5m Boom										
13.7	80.5	68.3	10 400 *							13.7
14.0	80.3	68.3	10 400 *							14.0
16.0	78.6	67.9	10 200 *							16.0
18.0	76.8	67.4	9 900 *							18.0
20.0	75.0	66.9	9 700 *	78.7	66.5	9 500*				20.0
22.0	73.2	66.3	9 400 *	76.9	65.9	9 200*				22.0
24.0	71.4	65.6	9 200 *	75.1	65.2	9 000*	78.9	64.2	8 600*	24.0
26.0	69.6	64.9	9 000 *	73.3	64.5	8 800*	77.1	63.4	8 400*	26.0
28.0	67.7	64.0	8 800 *	71.4	63.6	8 600*	75.2	62.6	8 100*	28.0
30.0	65.9	63.2	8 600 *	69.5	62.7	8 400*	73.3	61.7	7 700*	30.0
32.0	64.0	62.2	8 300 *	67.6	61.8	8 300*	71.3	60.7	7 300*	32.0
34.0	62.0	61.1	8 200 *	65.7	60.7	8 100*	69.3	59.6	7 000*	34.0
36.0	60.1	60.0	8 000 *	63.7	59.6	7 800*	67.3	58.4	6 700*	36.0
38.0	58.0	58.7	7 800 *	61.7	58.3	7 700*	65.2	57.1	6 400*	38.0
40.0	56.0	57.4	7 600 *	59.6	57.0	7 500*	63.1	55.8	6 200*	40.0
44.0	51.7	54.4	7 200 *	55.3	53.9	7 200*	58.7	52.6	5 700*	44.0
48.0	47.1	50.9	6 900 *	50.6	50.4	6 900*	53.9	49.0	5 400*	48.0
52.0	42.2	46.7	6 600 *	45.6	46.1	6 400*	48.8	44.6	5 000*	52.0
56.0	36.7	41.7	6 300 *	40.1	41.1	6 000*	43.0	39.3	4 800*	56.0
60.0	30.4	35.5	6 100 *	33.6	34.7	5 600*				60.0
64.0	22.4	27.1	5 900 *							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	81.0	71.4	10 300 *							13.7
14.0	80.7	71.3	10 300 *							14.0
16.0	79.0	70.9	10 100 *							16.0
18.0	77.4	70.5	9 900 *							18.0
20.0	75.7	70.0	9 700 *	79.2	69.6	9 500 *				20.0
22.0	74.0	69.4	9 500 *	77.5	69.0	9 200 *				22.0
24.0	72.3	68.8	9 300 *	75.8	68.4	9 000 *	79.5	67.3	8 600 *	24.0
26.0	70.5	68.1	9 100 *	74.1	67.7	8 800 *	77.7	66.6	8 400 *	26.0
28.0	68.8	67.3	8 800 *	72.3	66.9	8 700 *	75.9	65.8	8 200 *	28.0
30.0	67.0	66.4	8 600 *	70.5	66.0	8 500 *	74.1	64.9	7 800 *	30.0
32.0	65.2	65.5	8 400 *	68.7	65.1	8 300 *	72.2	64.0	7 500 *	32.0
34.0	63.3	64.5	8 200 *	66.8	64.1	8 100 *	70.3	63.0	7 200 *	34.0
36.0	61.5	63.4	8 000 *	65.0	63.0	7 900 *	68.4	61.9	6 900 *	36.0
38.0	59.6	62.3	7 900 *	63.0	61.8	7 800 *	66.5	60.7	6 600 *	38.0
40.0	57.6	61.0	7 700 *	61.1	60.6	7 600 *	64.5	59.4	6 300 *	40.0
44.0	53.6	58.2	7 300 *	57.1	57.7	7 300 *	60.3	56.5	5 900 *	44.0
48.0	49.4	54.9	7 000 *	52.8	54.4	7 000 *	56.0	53.1	5 500 *	48.0
52.0	44.9	51.1	6 700 *	48.2	50.6	6 600 *	51.2	49.1	5 200 *	52.0
56.0	39.9	46.6	6 400 *	43.2	46.0	6 200 *	46.1	44.4	4 900 *	56.0
60.0	34.4	41.2	6 200 *	37.6	40.5	5 800 *				60.0
64.0	27.9	34.4	6 000 *	31.0	33.5	5 400 *				64.0
68.0	19.5	24.9	5 800 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
15.2	80.1	74.1	10 200 *							15.2
16.0	79.5	74.0	10 100 *							16.0
18.0	77.9	73.6	10 000 *							18.0
20.0	76.3	73.1	9 700 *	79.7	72.7	9 500*				20.0
22.0	74.7	72.5	9 500 *	78.1	72.1	9 300*				22.0
24.0	73.0	71.9	9 300 *	76.4	71.5	9 100*	79.9	70.4	8 600*	24.0
26.0	71.4	71.2	9 100 *	74.7	70.8	8 900*	78.2	69.7	8 500*	26.0
28.0	69.7	70.5	8 900 *	73.1	70.1	8 600*	76.5	69.0	8 300*	28.0
30.0	68.0	69.7	8 700 *	71.4	69.3	8 500*	74.8	68.2	8 000*	30.0
32.0	66.3	68.8	8 500 *	69.6	68.4	8 300*	73.0	67.3	7 700*	32.0
34.0	64.5	67.9	8 300 *	67.9	67.5	8 200*	71.2	66.3	7 300*	34.0
36.0	62.8	66.9	8 100 *	66.1	66.4	8 000*	69.4	65.3	7 000*	36.0
38.0	61.0	65.8	7 900 *	64.3	65.3	7 900*	67.6	64.1	6 700*	38.0
40.0	59.1	64.6	7 700 *	62.5	64.1	7 700*	65.7	62.9	6 500*	40.0
44.0	55.4	61.9	7 400 *	58.7	61.5	7 400*	61.8	60.2	6 000*	44.0
48.0	51.4	58.9	7 100 *	54.7	58.4	7 100*	57.7	57.0	5 600*	48.0
52.0	47.2	55.3	6 800 *	50.4	54.8	6 800*	53.4	53.4	5 300*	52.0
56.0	42.7	51.2	6 500 *	45.9	50.7	6 400*	48.7	49.1	5 000*	56.0
60.0	37.8	46.4	6 300 *	40.9	45.7	6 000*	43.5	44.0	4 800*	60.0
64.0	32.2	40.5	6 100 *	35.2	39.8	5 700*				64.0
68.0	25.5	33.0	5 900 *							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	80.5	77.2	10 200 *							15.2
16.0	79.9	77.0	10 100 *							16.0
18.0	78.4	76.6	10 000 *							18.0
20.0	76.8	76.2	9 700 *	80.1	75.8	9 400*				20.0
22.0	75.3	75.6	9 500 *	78.6	75.2	9 200*				22.0
24.0	73.7	75.1	9 300 *	77.0	74.7	9 100*				24.0
26.0	72.1	74.4	9 100 *	75.4	74.0	8 900*	78.7	72.9	8 400*	26.0
28.0	70.5	73.7	8 900 *	73.8	73.3	8 700*	77.1	72.2	8 300*	28.0
30.0	68.9	72.9	8 700 *	72.1	72.5	8 500*	75.4	71.4	8 100*	30.0
32.0	67.3	72.1	8 500 *	70.5	71.7	8 300*	73.8	70.5	7 800*	32.0
34.0	65.6	71.2	8 300 *	68.8	70.8	8 200*	72.1	69.6	7 400*	34.0
36.0	63.9	70.2	8 100 *	67.1	69.8	8 000*	70.3	68.6	7 200*	36.0
38.0	62.2	69.2	7 900 *	65.4	68.7	7 900*	68.6	67.5	6 900*	38.0
40.0	60.5	68.1	7 800 *	63.7	67.6	7 700*	66.8	66.4	6 600*	40.0
44.0	56.9	65.6	7 500 *	60.1	65.1	7 400*	63.2	63.8	6 200*	44.0
48.0	53.2	62.7	7 100 *	56.3	62.2	7 200*	59.3	60.9	5 800*	48.0
52.0	49.3	59.4	6 800 *	52.4	58.9	6 900*	55.3	57.5	5 500*	52.0
56.0	45.1	55.6	6 600 *	48.2	55.1	6 700*	51.0	53.5	5 200*	56.0
60.0	40.6	51.2	6 300 *	43.6	50.6	6 200*	46.3	48.9	4 900*	60.0
64.0	35.7	46.0	6 100 *	38.6	45.3	5 800*	41.0	43.4	4 700*	64.0
68.0	30.0	39.6	6 000 *	32.8	38.8	5 500*				68.0
72.0	23.1	31.3	5 400							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.9	80.2	10 100 *							15.2
16.0	80.3	80.1	10 100 *							16.0
18.0	78.8	79.7	9 900 *							18.0
20.0	77.3	79.3	9 700 *	80.5	78.8	9 400 *				20.0
22.0	75.8	78.8	9 500 *	79.0	78.3	9 200 *				22.0
24.0	74.3	78.2	9 300 *	77.5	77.8	9 100 *				24.0
26.0	72.8	77.6	9 100 *	76.0	77.2	8 900 *	79.2	76.0	8 400 *	26.0
28.0	71.3	76.9	8 900 *	74.4	76.5	8 700 *	77.6	75.3	8 300 *	28.0
30.0	69.7	76.2	8 700 *	72.9	75.7	8 500 *	76.0	74.6	8 200 *	30.0
32.0	68.2	75.4	8 500 *	71.3	74.9	8 400 *	74.4	73.8	7 900 *	32.0
34.0	66.6	74.5	8 300 *	69.7	74.1	8 200 *	72.8	72.9	7 600 *	34.0
36.0	65.0	73.6	8 200 *	68.1	73.1	8 100 *	71.2	72.0	7 300 *	36.0
38.0	63.4	72.6	8 000 *	66.5	72.1	7 900 *	69.5	70.9	7 000 *	38.0
40.0	61.7	71.5	7 900 *	64.8	71.1	7 800 *	67.8	69.8	6 800 *	40.0
44.0	58.3	69.2	7 500 *	61.4	68.7	7 500 *	64.4	67.4	6 300 *	44.0
48.0	54.8	66.4	7 200 *	57.9	65.9	7 300 *	60.8	64.6	5 900 *	48.0
52.0	51.2	63.4	6 900 *	54.2	62.8	7 000 *	57.0	61.4	5 600 *	52.0
56.0	47.3	59.8	6 700 *	50.3	59.3	6 800 *	53.0	57.8	5 300 *	56.0
60.0	43.2	55.8	6 400 *	46.1	55.2	6 500 *	48.7	53.6	5 000 *	60.0
64.0	38.7	51.0	6 200 *	41.5	50.4	6 100 *	43.9	48.6	4 800 *	64.0
68.0	33.6	45.4	6 000	36.4	44.7	5 700 *				68.0
72.0	27.8	38.5	5 200	30.5	37.6	5 400				72.0
76.0	20.6	29.3	4 400							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
16.8	80.1	83.0	10 000 *							16.8
18.0	79.2	82.8	9 900 *							18.0
20.0	77.8	82.3	9 700 *	80.9	81.9	9 400*				20.0
22.0	76.4	81.9	9 500 *	79.4	81.4	9 200*				22.0
24.0	74.9	81.3	9 300 *	78.0	80.9	9 000*				24.0
26.0	73.5	80.7	9 100 *	76.5	80.3	8 800*	79.6	79.2	8 400*	26.0
28.0	72.0	80.1	8 900 *	75.0	79.6	8 700*	78.1	78.5	8 300*	28.0
30.0	70.5	79.4	8 700 *	73.5	78.9	8 500*	76.6	77.8	8 200*	30.0
32.0	69.0	78.6	8 600 *	72.0	78.2	8 400*	75.1	77.0	8 100*	32.0
34.0	67.5	77.8	8 400 *	70.5	77.3	8 200*	73.5	76.2	7 700*	34.0
36.0	66.0	76.9	8 200 *	69.0	76.5	8 100*	71.9	75.3	7 400*	36.0
38.0	64.4	75.9	8 000 *	67.4	75.5	7 900*	70.4	74.3	7 200*	38.0
40.0	62.9	74.9	7 900 *	65.8	74.5	7 800*	68.8	73.2	6 900*	40.0
44.0	59.6	72.7	7 600 *	62.6	72.2	7 600*	65.5	70.9	6 500*	44.0
48.0	56.3	70.1	7 300 *	59.2	69.6	7 300*	62.0	68.3	6 000*	48.0
52.0	52.9	67.2	7 000 *	55.7	66.7	7 100*	58.5	65.3	5 700*	52.0
56.0	49.2	63.9	6 700 *	52.1	63.3	6 800*	54.7	61.9	5 400*	56.0
60.0	45.4	60.1	6 500 *	48.2	59.5	6 600*	50.7	58.0	5 100*	60.0
64.0	41.2	55.8	6 300 *	44.0	55.1	6 300*	46.4	53.4	4 900*	64.0
68.0	36.7	50.7	5 800	39.4	50.0	5 900*	41.7	48.1	4 700*	68.0
72.0	31.7	44.7	4 900	34.3	43.9	5 100				72.0
76.0	25.7	37.2	4 100	28.2	36.2	4 300				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.5	86.1	9 900 *							16.8
18.0	79.6	85.8	9 900 *							18.0
20.0	78.3	85.4	9 700 *							20.0
22.0	76.9	84.9	9 600 *	79.8	84.5	9 200*				22.0
24.0	75.5	84.4	9 300 *	78.4	84.0	9 000*				24.0
26.0	74.1	83.9	9 100 *	77.0	83.4	8 800*	80.0	82.3	8 400*	26.0
28.0	72.7	83.2	9 000 *	75.6	82.8	8 700*	78.5	81.6	8 300*	28.0
30.0	71.2	82.6	8 800 *	74.1	82.1	8 500*	77.1	81.0	8 200*	30.0
32.0	69.8	81.8	8 600 *	72.7	81.4	8 400*	75.6	80.2	8 100*	32.0
34.0	68.3	81.0	8 400 *	71.2	80.6	8 300*	74.1	79.4	7 900*	34.0
36.0	66.9	80.2	8 300 *	69.8	79.7	8 100*	72.6	78.5	7 600*	36.0
38.0	65.4	79.3	8 100 *	68.3	78.8	8 000*	71.1	77.6	7 300*	38.0
40.0	63.9	78.3	7 900 *	66.8	77.8	7 900*	69.6	76.6	7 000*	40.0
44.0	60.8	76.2	7 600 *	63.7	75.7	7 600*	66.5	74.4	6 600*	44.0
48.0	57.7	73.7	7 300 *	60.5	73.2	7 300*	63.2	71.9	6 200*	48.0
52.0	54.4	71.0	7 100 *	57.2	70.4	7 100*	59.8	69.1	5 800*	52.0
56.0	51.0	67.8	6 800 *	53.7	67.3	6 900*	56.3	65.8	5 500*	56.0
60.0	47.4	64.3	6 600 *	50.1	63.7	6 700*	52.6	62.2	5 300*	60.0
64.0	43.5	60.3	6 300 *	46.2	59.7	6 500*	48.6	58.0	5 000*	64.0
68.0	39.4	55.6	5 500	42.1	55.0	5 800	44.3	53.2	4 800*	68.0
72.0	34.9	50.2	4 600	37.4	49.5	4 900				72.0
76.0	29.7	43.7	3 900	32.2	42.9	4 100				76.0
80.0	23.5	35.5	3 200							80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.8	89.1	9 900 *							16.8
18.0	80.0	88.9	9 800 *							18.0
20.0	78.7	88.5	9 700 *							20.0
22.0	77.3	88.0	9 500 *	80.2	87.6	9 100*				22.0
24.0	76.0	87.5	9 300 *	78.8	87.1	9 000*				24.0
26.0	74.6	87.0	9 100 *	77.5	86.5	8 800*	80.3	85.4	8 300*	26.0
28.0	73.3	86.4	9 000 *	76.1	85.9	8 700*	79.0	84.8	8 300*	28.0
30.0	71.9	85.7	8 800 *	74.7	85.3	8 500*	77.6	84.1	8 100*	30.0
32.0	70.5	85.0	8 600 *	73.3	84.6	8 400*	76.2	83.4	8 000*	32.0
34.0	69.1	84.3	8 400 *	71.9	83.8	8 200*	74.7	82.6	7 900*	34.0
36.0	67.7	83.5	8 300 *	70.5	83.0	8 100*	73.3	81.8	7 700*	36.0
38.0	66.3	82.6	8 100 *	69.1	82.1	8 000*	71.8	80.9	7 400*	38.0
40.0	64.9	81.6	7 900 *	67.6	81.2	7 900*	70.4	79.9	7 200*	40.0
44.0	61.9	79.6	7 600 *	64.7	79.1	7 600*	67.4	77.8	6 700*	44.0
48.0	58.9	77.3	7 300 *	61.6	76.8	7 400*	64.3	75.4	6 300*	48.0
52.0	55.8	74.6	7 100 *	58.5	74.1	7 200*	61.1	72.8	6 000*	52.0
56.0	52.5	71.7	6 900 *	55.2	71.1	7 000*	57.7	69.7	5 600*	56.0
60.0	49.1	68.4	6 600 *	51.8	67.8	6 700*	54.3	66.3	5 400*	60.0
64.0	45.6	64.6	6 200	48.2	64.0	6 600*	50.5	62.4	5 100*	64.0
68.0	41.7	60.3	5 300	44.3	59.7	5 600	46.6	57.9	4 900*	68.0
72.0	37.6	55.4	4 400	40.1	54.7	4 700	42.2	52.8	4 700*	72.0
76.0	33.0	49.6	3 600	35.5	48.8	3 800				76.0
80.0	27.8	42.6	2 900	30.1	41.7	3 100				80.0
84.0	21.4	33.6	2 300							84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
18.3	80.1	91.9	9 700 *							18.3
20.0	79.0	91.5	9 600 *							20.0
22.0	77.8	91.1	9 500 *	80.5	90.7	9 400*				22.0
24.0	76.5	90.6	9 300 *	79.2	90.2	9 200*				24.0
26.0	75.2	90.1	9 100 *	77.9	89.7	9 100*	80.7	88.5	8 600*	26.0
28.0	73.8	89.5	9 000 *	76.6	89.1	8 900*	79.3	87.9	8 400*	28.0
30.0	72.5	88.9	8 800 *	75.2	88.5	8 700*	78.0	87.3	8 300*	30.0
32.0	71.2	88.2	8 700 *	73.9	87.8	8 600*	76.6	86.6	8 200*	32.0
34.0	69.8	87.5	8 500 *	72.6	87.0	8 400*	75.3	85.8	8 100*	34.0
36.0	68.5	86.7	8 300 *	71.2	86.2	8 300*	73.9	85.0	7 800*	36.0
38.0	67.1	85.9	8 100 *	69.8	85.4	8 100*	72.5	84.2	7 500*	38.0
40.0	65.7	85.0	8 000 *	68.4	84.5	8 000*	71.1	83.2	7 300*	40.0
44.0	62.9	83.0	7 700 *	65.6	82.5	7 700*	68.2	81.2	6 800*	44.0
48.0	60.0	80.8	7 400 *	62.7	80.3	7 500*	65.3	79.0	6 400*	48.0
52.0	57.1	78.3	7 200 *	59.7	77.8	7 200*	62.2	76.4	6 100*	52.0
56.0	54.0	75.5	6 900 *	56.6	74.9	7 000*	59.1	73.5	5 800*	56.0
60.0	50.8	72.3	6 700 *	53.4	71.8	6 800*	55.8	70.3	5 500*	60.0
64.0	47.4	68.8	6 000	50.0	68.2	6 400	52.3	66.6	5 300*	64.0
68.0	43.8	64.8	5 000	46.4	64.2	5 300	48.6	62.5	5 000*	68.0
72.0	40.0	60.2	4 100	42.5	59.6	4 400	44.6	57.8	4 800	72.0
76.0	35.9	55.0	3 400	38.3	54.3	3 700	40.3	52.3	3 900	76.0
80.0	31.2	48.8	2 700	33.6	48.0	2 900				80.0
84.0	25.9	41.3	2 100							84.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
18.3	80.5	94.9	9 700 *							18.3
20.0	79.4	94.6	9 600 *							20.0
22.0	78.2	94.2	9 500 *							22.0
24.0	76.9	93.7	9 300 *	79.6	93.3	9 200*				24.0
26.0	75.6	93.2	9 100 *	78.3	92.8	9 100*				26.0
28.0	74.4	92.7	9 000 *	77.0	92.2	8 900*	79.7	91.0	8 400*	28.0
30.0	73.1	92.0	8 800 *	75.7	91.6	8 700*	78.4	90.4	8 300*	30.0
32.0	71.8	91.4	8 700 *	74.4	90.9	8 600*	77.1	89.7	8 200*	32.0
34.0	70.5	90.7	8 500 *	73.1	90.2	8 400*	75.8	89.0	8 100*	34.0
36.0	69.2	89.9	8 300 *	71.8	89.5	8 300*	74.5	88.2	7 900*	36.0
38.0	67.9	89.1	8 200 *	70.5	88.7	8 200*	73.1	87.4	7 700*	38.0
40.0	66.6	88.3	8 000 *	69.2	87.8	8 000*	71.8	86.5	7 400*	40.0
44.0	63.9	86.4	7 700 *	66.5	85.9	7 800*	69.0	84.6	7 000*	44.0
48.0	61.1	84.2	7 400 *	63.7	83.7	7 500*	66.2	82.4	6 600*	48.0
52.0	58.3	81.8	7 200 *	60.8	81.3	7 200*	63.3	80.0	6 200*	52.0
56.0	55.3	79.2	7 000 *	57.8	78.6	7 000*	60.2	77.2	5 900*	56.0
60.0	52.3	76.2	6 700	54.8	75.6	6 900*	57.1	74.2	5 600*	60.0
64.0	49.1	72.8	5 700	51.6	72.3	6 100	53.8	70.7	5 300*	64.0
68.0	45.7	69.1	4 700	48.2	68.5	5 100	50.4	66.8	5 100*	68.0
72.0	42.2	64.8	3 800	44.6	64.2	4 200	46.7	62.5	4 500	72.0
76.0	38.4	60.0	3 100	40.7	59.3	3 300	42.7	57.4	3 600	76.0
80.0	34.2	54.5	2 400	36.5	53.7	2 600				80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
18.3	80.8	98.0	9 600 *							18.3
20.0	79.7	97.7	9 600 *							20.0
22.0	78.5	97.3	9 400 *							22.0
24.0	77.3	96.8	9 300 *	79.9	96.4	9 200*				24.0
26.0	76.1	96.3	9 200 *	78.7	95.9	9 000*				26.0
28.0	74.9	95.8	9 000 *	77.4	95.3	8 900*	80.0	94.1	8 400*	28.0
30.0	73.6	95.2	8 800 *	76.2	94.7	8 700*	78.8	93.5	8 300*	30.0
32.0	72.4	94.6	8 700 *	74.9	94.1	8 600*	77.5	92.9	8 200*	32.0
34.0	71.1	93.9	8 500 *	73.7	93.4	8 400*	76.3	92.2	8 100*	34.0
36.0	69.9	93.1	8 300 *	72.4	92.7	8 300*	75.0	91.4	8 000*	36.0
38.0	68.6	92.4	8 200 *	71.1	91.9	8 200*	73.7	90.6	7 800*	38.0
40.0	67.3	91.5	8 000 *	69.9	91.1	8 000*	72.4	89.8	7 500*	40.0
44.0	64.7	89.7	7 800 *	67.2	89.2	7 800*	69.7	87.9	7 000*	44.0
48.0	62.1	87.7	7 500 *	64.6	87.2	7 500*	67.0	85.8	6 700*	48.0
52.0	59.4	85.4	7 200 *	61.8	84.9	7 300*	64.2	83.5	6 300*	52.0
56.0	56.5	82.8	7 000 *	59.0	82.3	7 100*	61.3	80.9	6 000*	56.0
60.0	53.6	80.0	6 500	56.1	79.4	6 900	58.4	78.0	5 700*	60.0
64.0	50.6	76.8	5 400	53.0	76.2	5 800	55.3	74.7	5 400*	64.0
68.0	47.5	73.2	4 400	49.9	72.6	4 800	52.0	71.0	5 200	68.0
72.0	44.1	69.3	3 600	46.5	68.6	4 000	48.6	66.9	4 300	72.0
76.0	40.6	64.8	2 800	42.9	64.1	3 100	44.9	62.3	3 400	76.0
80.0	36.7	59.7	2 100	39.0	59.0	2 400	40.9	57.0	2 600	80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
75.5m Boom										
19.8	80.2	100.7	9 500 *							19.8
20.0	80.0	100.7	9 500 *							20.0
22.0	78.9	100.3	9 300 *							22.0
24.0	77.7	99.9	9 200 *	80.2	99.4	9 100*				24.0
26.0	76.5	99.4	9 100 *	79.0	99.0	9 000*				26.0
28.0	75.3	98.9	8 900 *	77.8	98.4	8 800*	80.4	97.2	8 400*	28.0
30.0	74.1	98.3	8 800 *	76.6	97.9	8 700*	79.1	96.6	8 300*	30.0
32.0	72.9	97.7	8 600 *	75.4	97.2	8 600*	77.9	96.0	8 200*	32.0
34.0	71.7	97.0	8 500 *	74.2	96.6	8 400*	76.7	95.4	8 100*	34.0
36.0	70.5	96.3	8 400 *	73.0	95.9	8 300*	75.5	94.6	8 000*	36.0
38.0	69.3	95.6	8 200 *	71.7	95.1	8 200*	74.2	93.9	7 800*	38.0
40.0	68.1	94.8	8 000 *	70.5	94.3	8 000*	72.9	93.0	7 600*	40.0
44.0	65.6	93.0	7 800 *	68.0	92.5	7 800*	70.4	91.3	7 200*	44.0
48.0	63.0	91.1	7 500 *	65.4	90.6	7 500*	67.8	89.2	6 800*	48.0
52.0	60.4	88.9	7 300 *	62.8	88.3	7 300*	65.1	87.0	6 400*	52.0
56.0	57.7	86.4	7 000 *	60.1	85.9	7 100*	62.4	84.5	6 100*	56.0
60.0	54.9	83.7	6 500	57.3	83.1	6 900	59.5	81.7	5 800*	60.0
64.0	52.0	80.7	5 400	54.4	80.1	5 900	56.6	78.6	5 500*	64.0
68.0	49.0	77.3	4 400	51.4	76.7	4 900	53.5	75.1	5 300	68.0
72.0	45.9	73.6	3 600	48.2	72.9	4 000	50.2	71.3	4 300	72.0
76.0	42.6	69.4	2 800	44.8	68.7	3 200	46.8	66.9	3 500	76.0
80.0	39.0	64.6	2 100	41.3	63.9	2 400	43.1	62.0	2 700	80.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
99 740 kg Crane Counterweight
36 290 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 81.5m Boom

15000 SERIES 3

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
78.5m Boom										
19.8	80.4	103.8	9 400 *							19.8
20.0	80.3	103.8	9 400 *							20.0
22.0	79.2	103.4	9 300 *							22.0
24.0	78.1	103.0	9 200 *							24.0
26.0	76.9	102.5	9 100 *	79.3	102.0	8 900 *				26.0
28.0	75.8	102.0	8 900 *	78.2	101.5	8 800 *	80.7	100.3	8 300 *	28.0
30.0	74.6	101.4	8 800 *	77.0	101.0	8 600 *	79.5	99.8	8 200 *	30.0
32.0	73.5	100.9	8 600 *	75.9	100.4	8 500 *	78.3	99.2	8 200 *	32.0
34.0	72.3	100.2	8 500 *	74.7	99.7	8 400 *	77.1	98.5	8 100 *	34.0
36.0	71.1	99.5	8 300 *	73.5	99.1	8 300 *	75.9	97.8	8 000 *	36.0
38.0	69.9	98.8	8 200 *	72.3	98.3	8 200 *	74.7	97.1	7 800 *	38.0
40.0	68.7	98.0	8 000 *	71.1	97.6	8 000 *	73.5	96.3	7 800 *	40.0
44.0	66.3	96.3	7 800 *	68.7	95.8	7 800 *	71.0	94.6	7 300 *	44.0
48.0	63.8	94.4	7 500 *	66.2	93.9	7 600 *	68.5	92.6	6 900 *	48.0
52.0	61.3	92.3	7 300 *	63.7	91.8	7 300 *	65.9	90.4	6 500 *	52.0
56.0	58.7	90.0	7 100 *	61.1	89.4	7 100 *	63.3	88.0	6 200 *	56.0
60.0	56.1	87.3	6 300	58.4	86.8	6 900	60.6	85.4	5 900 *	60.0
64.0	53.3	84.5	5 200	55.6	83.9	5 700	57.8	82.4	5 700 *	64.0
68.0	50.5	81.3	4 200	52.8	80.7	4 600	54.8	79.1	5 100	68.0
72.0	47.5	77.7	3 300	49.8	77.1	3 700	51.8	75.5	4 100	72.0
76.0	44.4	73.8	2 600	46.6	73.1	2 900	48.5	71.4	3 300	76.0
80.0	41.1	69.4	1 900	43.2	68.7	2 200	45.1	66.8	2 500	80.0