

Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**

European Standards	
14 m/s Maximum Wind thru 54.5m Boom	
12 m/s with 57.5m and 60.5m Boom	
10 m/s with 63.5m thru 75.5m Boom	

15000 SERIES 2

LIFTING CAPACITIES: Chart supplements boom capacity chart **No. 8606-AM**. Lifting capacities for various boom lengths, jib lengths and jib operating radii are for freely suspended loads and are calculated to comply with EN 13000, ISO 4305 and include factors based on a 4.0 degree tipping angle. Capacities based on structural competence are denoted by an asterisk (*).

75.5m boom length requires only the middle two sheaves in lower boom point. All other sheaves must be removed from lower boom point.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves, is considered part of jib load. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up. Refer to boom rigging **No. A07850**, jib assembly **No. A10098** and Wire Rope Specification chart **No. 8608-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to Operator's Manual for operating guidelines.

WIND CONDITIONS: Machine may be operated in winds stated in maximum wind speed table provided crane operator judgment is used to allow for wind effect on lifted load and other considerations noted on capacity chart are followed. Wind will have a considerable effect on load. Loads must be compensated for accordingly by reducing load ratings, reducing operating speeds, or by a combination of both. Recommend stopping operation and lowering boom and jib to no higher than 70 degree boom angle when wind exceeds conditions stated. Lower boom and jib to ground when wind is above 22 m/s.

MACHINE TRAVEL: Machine to travel on a firm, level [up to 1 percent (0.5 degrees) grade] and uniformly supporting surface. *Travel with 100 percent of rated load prohibited.* Travel restricted to 90 percent of rated capacity with speed not

to exceed 0.4 m/s. Boom must be within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8615-A**.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.


JIB POINT ELEVATION: Jib point elevation is vertical distance from ground level to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with 8 585 mm crawlers, 1 219 mm treads, 3 124 mm retractable gantry, 9 144 mm live mast, 20 part boom hoist reeving, boom support straps, 83 870 kg crane counterweight and 19 960 kg carbody counterweight.

Maximum capacity on 26 mm wire rope is 13 380 kg per line (9 070 kg when auxiliary drum is used).

Maximum Wind Speeds		
Boom Lengths	Working Wind	Lower To Ground
27.5m - 54.5m	14 m/s	22 m/s
57.5m - 60.5m	12 m/s	22 m/s
63.5m - 75.5m	10 m/s	22 m/s
Wind speed to be measured at jib point elevation.		

Maximum Boom and Jib Length Raising			
Over End of Blocked Crawlers		Over Side of Crawlers	
Boom Length	Jib No. 134	Boom Length	Jib No. 134
78.5m	—	69.5m	—
75.5m	9.1m	66.5m	12.2m
72.5m	15.2m	63.5m	21.3m
69.5m	24.4m	60.5m	24.4m
Load block, hook and weight ball on ground at start.			



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
9.1	79.2	38.3	26 700 *							9.1
10.0	77.8	38.1	26 700 *							10.0
12.0	74.6	37.6	26 700 *	77.1	37.4	26 700*				12.0
14.0	71.3	36.9	26 700 *	73.8	36.7	26 100*	76.2	36.2	20 500*	14.0
16.0	67.9	36.1	26 600 *	70.4	35.9	25 400*	72.8	35.4	19 100*	16.0
18.0	64.5	35.2	26 100 *	66.9	35.0	24 900*	69.3	34.4	18 000*	18.0
20.0	60.9	34.1	25 400 *	63.3	33.9	24 400*	65.6	33.3	17 000*	20.0
22.0	57.2	32.9	24 800 *	59.6	32.6	23 800*	61.8	32.0	16 100*	22.0
24.0	53.4	31.4	24 300 *	55.7	31.1	22 400*	57.8	30.5	15 400*	24.0
26.0	49.3	29.8	23 800 *	51.6	29.5	21 100*	53.6	28.8	14 800*	26.0
28.0	44.9	27.8	23 300 *	47.2	27.5	20 000*	49.1	26.8	14 200*	28.0
30.0	40.2	25.5	22 100 *	42.4	25.2	19 000*	44.1	24.4	13 800*	30.0
32.0	34.9	22.8	20 200	37.0	22.4	18 200*				32.0
34.0	28.8	19.5	18 400							34.0
30.5m Boom										
9.1	80.0	41.4	26 700 *							9.1
10.0	78.8	41.2	26 700 *							10.0
12.0	75.8	40.7	26 700 *	78.1	40.5	26 700*				12.0
14.0	72.8	40.1	26 700 *	75.1	39.9	26 300*	77.4	39.3	21 000*	14.0
16.0	69.7	39.4	26 700 *	72.0	39.2	25 700*	74.2	38.6	19 700*	16.0
18.0	66.6	38.5	26 400 *	68.8	38.3	25 200*	71.0	37.7	18 600*	18.0
20.0	63.3	37.6	25 800 *	65.6	37.3	24 700*	67.7	36.7	17 600*	20.0
22.0	60.0	36.4	25 200 *	62.2	36.2	24 300*	64.3	35.6	16 700*	22.0
24.0	56.6	35.1	24 600 *	58.7	34.9	23 500*	60.8	34.3	16 000*	24.0
26.0	53.0	33.7	24 200 *	55.1	33.4	22 200*	57.1	32.7	15 300*	26.0
28.0	49.2	32.0	23 700	51.3	31.7	21 000*	53.2	31.0	14 700*	28.0
30.0	45.2	30.1	22 300	47.3	29.7	20 000*	49.0	29.0	14 200*	30.0
32.0	40.9	27.8	20 100	42.9	27.5	19 100*	44.5	26.7	13 800*	32.0
34.0	36.1	25.2	18 300	38.0	24.8	18 300				34.0
36.0	30.7	22.1	16 700	32.5	21.6	16 900				36.0
38.0	24.2	18.0	15 300							38.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
9.1	80.7	44.4	26 700 *							9.1
10.0	79.6	44.3	26 700 *							10.0
12.0	76.8	43.8	26 700 *	79.0	43.6	26 700*				12.0
14.0	74.0	43.3	26 700 *	76.2	43.0	26 400*	78.3	42.5	21 400*	14.0
16.0	71.2	42.6	26 700 *	73.3	42.4	25 900*	75.4	41.8	20 200*	16.0
18.0	68.3	41.8	26 700 *	70.4	41.6	25 300*	72.5	41.0	19 100*	18.0
20.0	65.4	40.9	26 100 *	67.4	40.7	24 900*	69.5	40.1	18 100*	20.0
22.0	62.3	39.9	25 500 *	64.4	39.6	24 500*	66.4	39.0	17 200*	22.0
24.0	59.2	38.7	25 000 *	61.3	38.5	24 100*	63.2	37.8	16 500*	24.0
26.0	56.0	37.4	24 500 *	58.0	37.1	23 300*	59.9	36.5	15 800*	26.0
28.0	52.6	35.9	23 800	54.6	35.6	22 000*	56.4	35.0	15 200*	28.0
30.0	49.1	34.2	21 900	51.1	33.9	21 000*	52.8	33.2	14 700*	30.0
32.0	45.4	32.3	19 800	47.3	32.0	20 000*	49.0	31.2	14 200*	32.0
34.0	41.4	30.1	18 000	43.3	29.8	18 200	44.8	29.0	13 800*	34.0
36.0	37.1	27.6	16 500	38.9	27.2	16 600				36.0
38.0	32.2	24.6	15 100	33.9	24.1	15 200				38.0
40.0	26.6	20.9	13 800							40.0
36.5m Boom										
10.7	79.4	47.2	26 700 *							10.7
12.0	77.7	46.9	26 700 *							12.0
14.0	75.1	46.4	26 700 *	77.1	46.1	26 600*	79.1	45.6	21 900*	14.0
16.0	72.5	45.8	26 700 *	74.5	45.5	26 000*	76.4	45.0	20 600*	16.0
18.0	69.8	45.1	26 700 *	71.8	44.8	25 500*	73.7	44.2	19 500*	18.0
20.0	67.1	44.2	26 400 *	69.0	44.0	25 100*	70.9	43.4	18 600*	20.0
22.0	64.3	43.3	25 800 *	66.2	43.0	24 700*	68.1	42.4	17 700*	22.0
24.0	61.5	42.2	25 300 *	63.4	41.9	24 300*	65.2	41.3	16 900*	24.0
26.0	58.5	41.0	24 800 *	60.4	40.7	23 900*	62.2	40.1	16 300*	26.0
28.0	55.5	39.7	24 000	57.4	39.4	23 100*	59.1	38.7	15 700*	28.0
30.0	52.4	38.2	21 700	54.2	37.9	21 800	55.9	37.2	15 100*	30.0
32.0	49.1	36.5	19 600	50.9	36.1	19 900	52.5	35.4	14 600*	32.0
34.0	45.6	34.6	17 900	47.4	34.2	18 100	48.9	33.5	14 200*	34.0
36.0	41.9	32.4	16 300	43.6	32.0	16 500	45.1	31.2	13 800*	36.0
38.0	37.9	29.9	14 900	39.6	29.5	15 100				38.0
40.0	33.5	27.0	13 700	35.1	26.6	13 800				40.0
44.0	22.4	19.2	11 500							44.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
10.7	80.1	50.3	26 700 *							10.7
12.0	78.5	50.0	26 700 *							12.0
14.0	76.0	49.5	26 700 *	77.9	49.3	26 600*	79.8	48.7	22 200*	14.0
16.0	73.6	48.9	26 700 *	75.5	48.7	26 200*	77.3	48.1	21 000*	16.0
18.0	71.1	48.3	26 700 *	73.0	48.0	25 700*	74.8	47.4	19 900*	18.0
20.0	68.6	47.5	26 700 *	70.4	47.2	25 200*	72.2	46.6	19 000*	20.0
22.0	66.0	46.6	26 100 *	67.8	46.3	24 800*	69.6	45.8	18 100*	22.0
24.0	63.4	45.6	25 600 *	65.2	45.4	24 500*	66.9	44.8	17 400*	24.0
26.0	60.7	44.5	25 100	62.5	44.2	24 100*	64.2	43.6	16 700*	26.0
28.0	57.9	43.3	24 100	59.7	43.0	23 700	61.3	42.4	16 100*	28.0
30.0	55.1	41.9	21 500	56.8	41.6	22 000	58.4	41.0	15 500*	30.0
32.0	52.1	40.4	19 500	53.8	40.1	19 800	55.4	39.4	15 000*	32.0
34.0	49.0	38.7	17 700	50.7	38.4	18 000	52.2	37.7	14 600*	34.0
36.0	45.8	36.8	16 200	47.4	36.5	16 400	48.9	35.7	14 200*	36.0
38.0	42.3	34.7	14 800	44.0	34.3	14 900	45.3	33.5	13 800*	38.0
40.0	38.6	32.2	13 500	40.2	31.9	13 700				40.0
44.0	30.1	26.2	11 400	31.5	25.7	11 500				44.0
42.5m Boom										
10.7	80.7	53.3	26 700 *							10.7
12.0	79.1	53.1	26 700 *							12.0
14.0	76.9	52.6	26 700 *	78.6	52.4	26 700*	80.4	51.8	22 500*	14.0
16.0	74.6	52.1	26 700 *	76.3	51.8	26 300*	78.1	51.2	21 300*	16.0
18.0	72.2	51.4	26 700 *	74.0	51.2	25 800*	75.7	50.6	20 300*	18.0
20.0	69.9	50.7	26 700 *	71.6	50.5	25 400*	73.3	49.9	19 400*	20.0
22.0	67.5	49.9	26 400 *	69.2	49.6	25 000*	70.9	49.0	18 500*	22.0
24.0	65.1	49.0	25 800 *	66.8	48.7	24 600*	68.4	48.1	17 800*	24.0
26.0	62.6	48.0	25 300	64.3	47.7	24 300*	65.9	47.1	17 100*	26.0
28.0	60.0	46.8	23 900	61.7	46.5	23 700	63.3	45.9	16 500*	28.0
30.0	57.4	45.6	21 300	59.1	45.3	21 800	60.6	44.6	15 900*	30.0
32.0	54.7	44.2	19 300	56.3	43.9	19 600	57.8	43.2	15 400*	32.0
34.0	51.9	42.6	17 500	53.5	42.3	17 800	55.0	41.6	15 000*	34.0
36.0	49.0	40.9	16 000	50.6	40.6	16 200	52.0	39.9	14 600*	36.0
38.0	45.9	39.0	14 600	47.5	38.7	14 800	48.8	37.9	14 200*	38.0
40.0	42.7	36.9	13 300	44.2	36.6	13 500	45.5	35.7	13 800	40.0
44.0	35.5	31.9	11 200	37.0	31.4	11 300				44.0
48.0	26.7	25.0	9 400							48.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
12.2	79.5	56.1	26 700 *							12.2
14.0	77.6	55.7	26 700 *	79.3	55.4	26 700*				14.0
16.0	75.4	55.2	26 700 *	77.1	54.9	26 300*	78.8	54.4	21 700*	16.0
18.0	73.3	54.6	26 700 *	74.9	54.3	25 900*	76.6	53.8	20 600*	18.0
20.0	71.0	53.9	26 700 *	72.7	53.7	25 500*	74.3	53.1	19 700*	20.0
22.0	68.8	53.1	26 500 *	70.4	52.9	25 100*	72.0	52.3	18 900*	22.0
24.0	66.5	52.3	26 000 *	68.1	52.0	24 700*	69.7	51.4	18 100*	24.0
26.0	64.2	51.3	25 500	65.8	51.1	24 400*	67.3	50.5	17 500*	26.0
28.0	61.8	50.3	23 500	63.4	50.0	23 800	64.9	49.4	16 800*	28.0
30.0	59.4	49.1	21 000	61.0	48.8	21 400	62.5	48.2	16 300*	30.0
32.0	56.9	47.8	19 000	58.5	47.5	19 300	59.9	46.9	15 800*	32.0
34.0	54.3	46.4	17 200	55.9	46.1	17 500	57.3	45.4	15 300*	34.0
36.0	51.7	44.9	15 700	53.2	44.6	15 900	54.6	43.9	14 900*	36.0
38.0	48.9	43.2	14 300	50.4	42.8	14 500	51.7	42.1	14 500*	38.0
40.0	46.0	41.3	13 000	47.5	40.9	13 200	48.8	40.2	13 400	40.0
44.0	39.8	36.9	10 900	41.2	36.5	11 100	42.3	35.6	11 200	44.0
48.0	32.5	31.2	9 100	33.9	30.8	9 200				48.0
48.5m Boom										
12.2	80.1	59.1	26 700 *							12.2
14.0	78.3	58.8	26 700 *	79.9	58.5	26 700*				14.0
16.0	76.2	58.3	26 700 *	77.8	58.0	26 400*	79.4	57.5	22 000*	16.0
18.0	74.2	57.7	26 700 *	75.7	57.5	26 000*	77.3	56.9	21 000*	18.0
20.0	72.1	57.1	26 700 *	73.6	56.8	25 500*	75.2	56.2	20 100*	20.0
22.0	70.0	56.4	26 600 *	71.5	56.1	25 200*	73.0	55.5	19 200*	22.0
24.0	67.8	55.6	26 200 *	69.4	55.3	24 800*	70.9	54.7	18 500*	24.0
26.0	65.6	54.7	25 700	67.2	54.4	24 500*	68.6	53.8	17 800*	26.0
28.0	63.4	53.7	23 200	64.9	53.4	23 800	66.4	52.8	17 200*	28.0
30.0	61.2	52.6	20 800	62.7	52.3	21 200	64.1	51.7	16 700*	30.0
32.0	58.8	51.4	18 800	60.3	51.1	19 100	61.7	50.5	16 100*	32.0
34.0	56.5	50.1	17 000	57.9	49.8	17 300	59.3	49.1	15 700*	34.0
36.0	54.0	48.7	15 500	55.5	48.4	15 700	56.8	47.7	15 300*	36.0
38.0	51.5	47.1	14 100	53.0	46.8	14 300	54.2	46.1	14 600	38.0
40.0	48.9	45.4	12 800	50.3	45.1	13 100	51.5	44.3	13 300	40.0
44.0	43.3	41.5	10 700	44.7	41.1	10 900	45.8	40.3	11 100	44.0
48.0	37.0	36.6	8 900	38.3	36.2	9 100				48.0
52.0	29.6	30.3	7 500							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
12.2	80.6	62.2	26 700 *							12.2
14.0	78.9	61.8	26 700 *	80.4	61.6	26 700 *				14.0
16.0	76.9	61.4	26 700 *	78.4	61.1	26 400 *	79.9	60.5	22 200 *	16.0
18.0	75.0	60.8	26 700 *	76.5	60.6	26 000 *	78.0	60.0	21 300 *	18.0
20.0	73.0	60.2	26 700 *	74.5	60.0	25 600 *	76.0	59.4	20 400 *	20.0
22.0	71.0	59.6	26 700 *	72.5	59.3	25 200 *	73.9	58.7	19 600 *	22.0
24.0	69.0	58.8	26 400 *	70.4	58.5	24 900 *	71.9	57.9	18 800 *	24.0
26.0	66.9	58.0	25 600	68.4	57.7	24 600	69.8	57.1	18 200 *	26.0
28.0	64.8	57.0	23 000	66.3	56.8	23 600	67.7	56.1	17 600 *	28.0
30.0	62.7	56.0	20 600	64.2	55.7	21 000	65.5	55.1	17 000 *	30.0
32.0	60.6	54.9	18 600	62.0	54.6	19 000	63.3	54.0	16 500 *	32.0
34.0	58.3	53.7	16 800	59.8	53.4	17 100	61.1	52.7	16 000 *	34.0
36.0	56.1	52.4	15 200	57.5	52.1	15 500	58.8	51.4	15 500	36.0
38.0	53.7	50.9	13 900	55.1	50.6	14 100	56.4	49.9	14 400	38.0
40.0	51.3	49.4	12 600	52.7	49.0	12 900	53.9	48.3	13 100	40.0
44.0	46.3	45.8	10 500	47.6	45.4	10 700	48.7	44.6	10 900	44.0
48.0	40.7	41.4	8 800	42.0	41.0	8 900	43.0	40.2	9 000	48.0
52.0	34.4	36.1	7 300	35.6	35.6	7 400				52.0
56.0	26.8	29.1	6 000							56.0
54.5m Boom										
13.7	79.6	64.9	26 700 *							13.7
14.0	79.4	64.9	26 700 *							14.0
16.0	77.5	64.5	26 700 *	79.0	64.2	26 400 *				16.0
18.0	75.7	64.0	26 700 *	77.1	63.7	26 000 *	78.5	63.1	21 500 *	18.0
20.0	73.8	63.4	26 700 *	75.2	63.1	25 600 *	76.6	62.5	20 700 *	20.0
22.0	71.9	62.7	26 700 *	73.3	62.5	25 300 *	74.7	61.9	19 900 *	22.0
24.0	70.0	62.0	26 400 *	71.4	61.8	25 000 *	72.8	61.2	19 100 *	24.0
26.0	68.1	61.2	25 100	69.5	61.0	24 600	70.8	60.4	18 500 *	26.0
28.0	66.1	60.4	22 700	67.5	60.1	23 300	68.8	59.5	17 900 *	28.0
30.0	64.1	59.4	20 400	65.5	59.1	20 900	66.8	58.5	17 300 *	30.0
32.0	62.1	58.4	18 400	63.4	58.1	18 800	64.7	57.4	16 800 *	32.0
34.0	60.0	57.2	16 600	61.4	56.9	17 000	62.6	56.3	16 300 *	34.0
36.0	57.9	56.0	15 000	59.2	55.7	15 400	60.5	55.0	15 600	36.0
38.0	55.7	54.6	13 600	57.1	54.3	13 900	58.3	53.6	14 200	38.0
40.0	53.5	53.2	12 400	54.8	52.9	12 700	56.0	52.2	12 900	40.0
44.0	48.8	49.9	10 300	50.1	49.5	10 500	51.2	48.8	10 700	44.0
48.0	43.8	46.0	8 500	45.0	45.6	8 700	46.0	44.8	8 900	48.0
52.0	38.2	41.2	7 100	39.4	40.8	7 200				52.0
56.0	31.8	35.4	5 800	32.9	34.9	5 900				56.0
60.0	23.9	27.6	4 700							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
13.7	80.1	68.0	26 700 *							13.7
14.0	79.9	67.9	26 700 *							14.0
16.0	78.1	67.5	26 700 *	79.5	67.3	26 300*				16.0
18.0	76.3	67.1	26 700 *	77.7	66.8	26 000*	79.1	66.2	21 800*	18.0
20.0	74.6	66.5	26 700 *	75.9	66.3	25 600*	77.3	65.7	21 000*	20.0
22.0	72.8	65.9	26 700 *	74.1	65.6	25 300*	75.5	65.0	20 200*	22.0
24.0	70.9	65.2	26 500 *	72.3	65.0	25 000*	73.6	64.4	19 500*	24.0
26.0	69.1	64.5	24 500	70.4	64.2	24 700	71.7	63.6	18 800*	26.0
28.0	67.2	63.6	22 100	68.6	63.4	22 700	69.9	62.7	18 200*	28.0
30.0	65.4	62.7	20 000	66.7	62.5	20 500	67.9	61.8	17 600*	30.0
32.0	63.4	61.8	18 100	64.8	61.5	18 500	66.0	60.8	17 100*	32.0
34.0	61.5	60.7	16 300	62.8	60.4	16 700	64.0	59.7	16 600	34.0
36.0	59.5	59.5	14 700	60.8	59.2	15 100	62.0	58.6	15 500	36.0
38.0	57.5	58.3	13 400	58.8	58.0	13 700	59.9	57.3	13 900	38.0
40.0	55.4	56.9	12 100	56.7	56.6	12 400	57.8	55.9	12 600	40.0
44.0	51.1	53.8	10 000	52.3	53.5	10 200	53.4	52.8	10 400	44.0
48.0	46.4	50.2	8 200	47.7	49.9	8 400	48.7	49.1	8 600	48.0
52.0	41.4	46.0	6 800	42.6	45.6	6 900				52.0
56.0	35.8	40.9	5 500	36.9	40.4	5 600				56.0
60.0	29.3	34.4	4 400							60.0
64.0	21.0	25.7	3 400							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
13.7	80.5	71.0	26 700 *							13.7
14.0	80.3	71.0	26 700 *							14.0
16.0	78.6	70.6	26 700 *	80.0	70.3	26 300*				16.0
18.0	76.9	70.1	26 700 *	78.3	69.9	25 900*	79.6	69.3	22 100*	18.0
20.0	75.2	69.6	26 700 *	76.6	69.4	25 600*	77.8	68.8	21 200*	20.0
22.0	73.5	69.0	26 700 *	74.8	68.8	25 300*	76.1	68.2	20 400*	22.0
24.0	71.8	68.4	26 200	73.1	68.1	25 000*	74.4	67.5	19 700*	24.0
26.0	70.1	67.7	23 900	71.3	67.4	24 500	72.6	66.8	19 100*	26.0
28.0	68.3	66.9	21 600	69.6	66.6	22 100	70.8	66.0	18 500*	28.0
30.0	66.5	66.0	19 600	67.8	65.8	20 000	69.0	65.1	18 000*	30.0
32.0	64.7	65.1	17 800	65.9	64.8	18 200	67.1	64.2	17 400*	32.0
34.0	62.8	64.1	16 100	64.1	63.8	16 500	65.3	63.2	16 800	34.0
36.0	61.0	63.0	14 500	62.2	62.7	14 900	63.4	62.0	15 200	36.0
38.0	59.0	61.8	13 100	60.3	61.5	13 400	61.4	60.8	13 800	38.0
40.0	57.1	60.5	11 900	58.3	60.2	12 200	59.4	59.5	12 500	40.0
44.0	53.0	57.7	9 800	54.2	57.4	10 000	55.3	56.6	10 200	44.0
48.0	48.8	54.3	8 000	49.9	54.0	8 200	50.9	53.2	8 400	48.0
52.0	44.2	50.5	6 600	45.3	50.1	6 700	46.2	49.3	6 900	52.0
56.0	39.2	45.9	5 300	40.3	45.5	5 400				56.0
60.0	33.5	40.3	4 200	34.6	39.8	4 300				60.0
64.0	26.8	33.3	3 300							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
13.7	80.9	74.1	26 700 *							13.7
14.0	80.7	74.0	26 700 *							14.0
16.0	79.1	73.7	26 700 *	80.4	73.4	26 200*				16.0
18.0	77.5	73.2	26 700 *	78.8	73.0	25 900*	80.0	72.4	22 300*	18.0
20.0	75.9	72.7	26 700 *	77.1	72.5	25 500*	78.4	71.9	21 500*	20.0
22.0	74.2	72.2	26 700 *	75.5	71.9	25 300*	76.7	71.3	20 700*	22.0
24.0	72.6	71.6	25 800	73.8	71.3	25 000*	75.0	70.7	20 000*	24.0
26.0	70.9	70.9	23 400	72.1	70.6	24 000	73.4	70.0	19 300*	26.0
28.0	69.2	70.1	21 100	70.5	69.9	21 600	71.6	69.2	18 800*	28.0
30.0	67.5	69.3	19 100	68.7	69.0	19 600	69.9	68.4	18 200*	30.0
32.0	65.8	68.4	17 400	67.0	68.1	17 800	68.2	67.5	17 700*	32.0
34.0	64.0	67.5	15 800	65.3	67.2	16 200	66.4	66.5	16 600	34.0
36.0	62.3	66.4	14 300	63.5	66.1	14 700	64.6	65.5	15 000	36.0
38.0	60.5	65.3	12 900	61.7	65.0	13 200	62.8	64.3	13 600	38.0
40.0	58.6	64.1	11 700	59.8	63.8	12 000	60.9	63.1	12 300	40.0
44.0	54.8	61.4	9 500	56.0	61.1	9 800	57.0	60.4	10 000	44.0
48.0	50.8	58.3	7 800	52.0	58.0	8 000	52.9	57.2	8 200	48.0
52.0	46.6	54.7	6 300	47.7	54.4	6 500	48.6	53.6	6 600	52.0
56.0	42.0	50.5	5 100	43.1	50.1	5 200	43.9	49.3	5 300	56.0
60.0	37.0	45.6	4 000	38.0	45.1	4 100				60.0
64.0	31.3	39.5	3 000	32.2	39.0	3 100				64.0
68.0	24.4	31.8	2 200							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
15.2	80.1	76.9	26 700 *							15.2
16.0	79.5	76.7	26 700 *							16.0
18.0	78.0	76.3	26 700 *	79.2	76.0	25 800*				18.0
20.0	76.4	75.8	26 700 *	77.6	75.6	25 500*	78.8	75.0	21 700*	20.0
22.0	74.9	75.3	26 700 *	76.1	75.0	25 200*	77.3	74.4	20 900*	22.0
24.0	73.3	74.7	25 400	74.5	74.4	24 900*	75.7	73.8	20 300*	24.0
26.0	71.7	74.1	22 800	72.9	73.8	23 400	74.1	73.2	19 600*	26.0
28.0	70.1	73.3	20 600	71.3	73.1	21 100	72.4	72.5	19 000*	28.0
30.0	68.5	72.6	18 700	69.6	72.3	19 100	70.8	71.7	18 500*	30.0
32.0	66.8	71.7	16 900	68.0	71.4	17 400	69.1	70.8	17 800	32.0
34.0	65.2	70.8	15 400	66.3	70.5	15 800	67.4	69.9	16 200	34.0
36.0	63.5	69.8	14 000	64.6	69.5	14 400	65.7	68.9	14 800	36.0
38.0	61.7	68.8	12 700	62.9	68.5	13 000	64.0	67.8	13 400	38.0
40.0	60.0	67.6	11 400	61.1	67.3	11 700	62.2	66.6	12 100	40.0
44.0	56.4	65.1	9 300	57.5	64.8	9 600	58.6	64.1	9 800	44.0
48.0	52.7	62.2	7 500	53.8	61.8	7 800	54.7	61.1	8 000	48.0
52.0	48.7	58.8	6 100	49.8	58.5	6 300	50.7	57.7	6 500	52.0
56.0	44.5	55.0	4 800	45.6	54.6	5 000	46.4	53.8	5 100	56.0
60.0	40.0	50.5	3 800	41.0	50.1	3 900				60.0
64.0	34.9	45.1	2 800	35.9	44.7	2 900				64.0
68.0	29.1	38.6	2 000							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
15.2	80.5	79.9	26 700 *							15.2
16.0	80.0	79.8	26 700 *							16.0
18.0	78.5	79.4	26 700 *	79.6	79.1	25 700*				18.0
20.0	77.0	78.9	26 700 *	78.1	78.7	25 400*	79.3	78.1	21 900*	20.0
22.0	75.5	78.4	26 600	76.6	78.1	25 100*	77.8	77.5	21 200*	22.0
24.0	74.0	77.8	25 000	75.1	77.6	24 800*	76.2	77.0	20 500*	24.0
26.0	72.4	77.2	22 200	73.6	76.9	22 800	74.7	76.3	19 900*	26.0
28.0	70.9	76.5	20 000	72.0	76.3	20 600	73.1	75.6	19 300*	28.0
30.0	69.3	75.8	18 100	70.5	75.5	18 600	71.6	74.9	18 700*	30.0
32.0	67.8	75.0	16 400	68.9	74.7	16 900	70.0	74.1	17 300	32.0
34.0	66.2	74.1	14 800	67.3	73.8	15 300	68.4	73.2	15 700	34.0
36.0	64.6	73.2	13 500	65.7	72.9	13 900	66.7	72.2	14 300	36.0
38.0	62.9	72.2	12 300	64.0	71.9	12 600	65.1	71.2	13 000	38.0
40.0	61.3	71.1	11 100	62.4	70.8	11 500	63.4	70.1	11 800	40.0
44.0	57.9	68.7	9 000	59.0	68.4	9 300	59.9	67.7	9 600	44.0
48.0	54.3	65.9	7 200	55.4	65.6	7 500	56.3	64.9	7 700	48.0
52.0	50.6	62.8	5 800	51.7	62.5	6 000	52.6	61.7	6 200	52.0
56.0	46.7	59.2	4 500	47.7	58.8	4 700	48.6	58.0	4 900	56.0
60.0	42.5	55.1	3 400	43.5	54.7	3 600	44.3	53.8	3 700	60.0
64.0	38.0	50.2	2 500	38.9	49.8	2 600				64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

9.1m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
72.5m Boom										
15.2	80.9	83.0	26 700 *							15.2
16.0	80.3	82.8	26 700 *							16.0
18.0	78.9	82.4	26 700 *	80.0	82.2	25 600*				18.0
20.0	77.5	82.0	26 700 *	78.6	81.7	25 300*	79.7	81.1	22 100*	20.0
22.0	76.0	81.5	26 300	77.1	81.2	25 000*	78.2	80.6	21 400*	22.0
24.0	74.6	81.0	24 400	75.7	80.7	24 500	76.8	80.1	20 700*	24.0
26.0	73.1	80.4	21 700	74.2	80.1	22 300	75.3	79.5	20 100*	26.0
28.0	71.6	79.7	19 500	72.7	79.4	20 100	73.8	78.8	19 500*	28.0
30.0	70.1	79.0	17 600	71.2	78.7	18 200	72.3	78.1	18 600	30.0
32.0	68.6	78.2	15 900	69.7	77.9	16 400	70.8	77.3	16 900	32.0
34.0	67.1	77.4	14 400	68.2	77.1	14 900	69.2	76.5	15 300	34.0
36.0	65.6	76.5	13 100	66.6	76.2	13 500	67.7	75.6	13 900	36.0
38.0	64.0	75.5	11 800	65.1	75.2	12 200	66.1	74.6	12 600	38.0
40.0	62.4	74.5	10 700	63.5	74.2	11 100	64.5	73.5	11 400	40.0
44.0	59.2	72.2	8 700	60.2	71.9	9 100	61.2	71.2	9 400	44.0
48.0	55.8	69.6	7 000	56.9	69.3	7 300	57.8	68.6	7 500	48.0
52.0	52.3	66.7	5 500	53.4	66.3	5 800	54.3	65.6	6 000	52.0
56.0	48.7	63.3	4 300	49.7	62.9	4 500	50.5	62.2	4 700	56.0
60.0	44.8	59.5	3 200	45.8	59.1	3 400	46.6	58.2	3 500	60.0
64.0	40.6	55.0	2 300	41.6	54.6	2 400	42.3	53.7	2 500	64.0
75.5m Boom										
16.8	80.1	85.7	26 700 *							16.8
18.0	79.3	85.5	26 700 *							18.0
20.0	77.9	85.1	26 700 *	79.0	84.8	25 100*	80.1	84.2	22 300*	20.0
22.0	76.5	84.6	26 300	77.6	84.3	24 900*	78.7	83.7	21 600*	22.0
24.0	75.1	84.1	24 100	76.2	83.8	24 400	77.3	83.2	20 900*	24.0
26.0	73.7	83.5	21 600	74.8	83.2	22 200	75.8	82.6	20 300*	26.0
28.0	72.3	82.9	19 400	73.4	82.6	19 900	74.4	82.0	19 800*	28.0
30.0	70.9	82.2	17 500	71.9	81.9	18 000	72.9	81.3	18 600	30.0
32.0	69.4	81.4	15 800	70.5	81.2	16 300	71.5	80.5	16 800	32.0
34.0	68.0	80.6	14 300	69.0	80.4	14 800	70.0	79.7	15 200	34.0
36.0	66.5	79.8	13 000	67.5	79.5	13 400	68.5	78.9	13 800	36.0
38.0	65.0	78.9	11 800	66.0	78.6	12 200	67.0	77.9	12 600	38.0
40.0	63.5	77.9	10 700	64.5	77.6	11 000	65.5	76.9	11 400	40.0
44.0	60.4	75.7	8 800	61.4	75.4	9 100	62.4	74.7	9 400	44.0
48.0	57.2	73.2	7 100	58.2	72.9	7 300	59.1	72.2	7 600	48.0
52.0	53.9	70.4	5 600	54.9	70.1	5 800	55.8	69.4	6 100	52.0
56.0	50.5	67.3	4 400	51.4	66.9	4 600	52.3	66.2	4 700	56.0
60.0	46.8	63.7	3 300	47.8	63.3	3 500	48.6	62.5	3 600	60.0
64.0	42.9	59.6	2 400	43.9	59.2	2 500	44.6	58.3	2 600	64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
9.1	80.7	41.4	25 000 *							9.1
10.0	79.5	41.2	24 600 *							10.0
12.0	76.5	40.7	23 700 *							12.0
14.0	73.5	40.1	22 800 *	76.5	39.8	21 200*	79.7	39.1	17 500*	14.0
16.0	70.4	39.4	22 100 *	73.4	39.1	20 700*	76.5	38.4	16 300*	16.0
18.0	67.3	38.6	21 400 *	70.2	38.2	20 200*	73.3	37.5	15 300*	18.0
20.0	64.1	37.6	20 800 *	67.0	37.3	19 800*	69.9	36.5	14 500*	20.0
22.0	60.7	36.5	20 200 *	63.7	36.1	18 900*	66.5	35.4	13 700*	22.0
24.0	57.3	35.2	19 700 *	60.2	34.8	17 600*	63.0	34.0	13 000*	24.0
26.0	53.7	33.7	19 300 *	56.6	33.3	16 500*	59.2	32.5	12 500*	26.0
28.0	49.9	32.0	18 700 *	52.7	31.6	15 500*	55.3	30.8	12 000*	28.0
30.0	45.9	30.1	17 600 *	48.7	29.7	14 700*	51.1	28.7	11 500*	30.0
32.0	41.6	27.9	16 400 *	44.3	27.4	13 900*	46.5	26.4	11 200*	32.0
34.0	36.9	25.3	15 500 *	39.4	24.7	13 300*				34.0
36.0	31.5	22.1	14 600 *	33.9	21.5	12 800*				36.0
38.0	25.0	18.1	13 900 *							38.0
30.5m Boom										
10.7	79.3	44.2	24 400 *							10.7
12.0	77.5	43.9	23 900 *							12.0
14.0	74.7	43.3	23 100 *	77.5	43.0	21 400*	80.4	42.3	17 800*	14.0
16.0	71.9	42.6	22 400 *	74.7	42.3	20 900*	77.5	41.6	16 700*	16.0
18.0	69.0	41.8	21 700 *	71.7	41.5	20 400*	74.6	40.8	15 700*	18.0
20.0	66.0	41.0	21 100 *	68.8	40.6	20 100*	71.5	39.9	14 900*	20.0
22.0	63.0	39.9	20 600 *	65.7	39.6	19 500*	68.4	38.8	14 100*	22.0
24.0	59.9	38.8	20 100 *	62.6	38.4	18 500*	65.2	37.6	13 500*	24.0
26.0	56.7	37.4	19 600 *	59.3	37.1	17 300*	61.9	36.2	12 900*	26.0
28.0	53.3	36.0	19 200 *	56.0	35.6	16 300*	58.4	34.7	12 400*	28.0
30.0	49.8	34.3	18 700 *	52.4	33.9	15 400*	54.8	32.9	11 900*	30.0
32.0	46.1	32.4	17 600 *	48.6	31.9	14 600*	50.9	30.9	11 500*	32.0
34.0	42.1	30.2	16 500 *	44.6	29.7	14 000*	46.7	28.6	11 200*	34.0
36.0	37.8	27.6	15 600 *	40.2	27.1	13 400*				36.0
38.0	32.9	24.6	14 800 *	35.2	24.0	12 900*				38.0
40.0	27.3	20.9	14 100 *							40.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
10.7	80.0	47.2	24 600 *							10.7
12.0	78.3	46.9	24 100 *							12.0
14.0	75.7	46.4	23 300 *	78.4	46.1	21 500*				14.0
16.0	73.1	45.8	22 600 *	75.7	45.5	21 000*	78.4	44.7	17 000*	16.0
18.0	70.4	45.1	22 000 *	73.0	44.7	20 600*	75.7	44.0	16 100*	18.0
20.0	67.7	44.3	21 400 *	70.3	43.9	20 200*	72.9	43.2	15 200*	20.0
22.0	64.9	43.3	20 900 *	67.5	43.0	19 900*	70.0	42.2	14 500*	22.0
24.0	62.1	42.2	20 400 *	64.6	41.9	19 200*	67.1	41.1	13 800*	24.0
26.0	59.2	41.0	19 900 *	61.7	40.7	18 100*	64.1	39.9	13 300*	26.0
28.0	56.1	39.7	19 500 *	58.6	39.3	17 000*	61.0	38.5	12 700*	28.0
30.0	53.0	38.2	19 100 *	55.4	37.8	16 200*	57.7	36.9	12 300*	30.0
32.0	49.7	36.5	18 800 *	52.1	36.1	15 400*	54.3	35.1	11 900*	32.0
34.0	46.2	34.6	17 700 *	48.6	34.1	14 600*	50.7	33.2	11 500*	34.0
36.0	42.6	32.4	16 600 *	44.9	32.0	14 000*	46.8	30.9	11 200*	36.0
38.0	38.6	30.0	15 500	40.8	29.4	13 400*				38.0
40.0	34.2	27.1	14 200	36.3	26.5	13 000*				40.0
44.0	23.1	19.3	12 000							44.0
36.5m Boom										
10.7	80.6	50.3	24 700 *							10.7
12.0	79.0	50.0	24 200 *							12.0
14.0	76.6	49.5	23 500 *	79.1	49.2	21 600*				14.0
16.0	74.2	49.0	22 800 *	76.6	48.6	21 200*	79.2	47.9	17 300*	16.0
18.0	71.7	48.3	22 200 *	74.1	47.9	20 800*	76.6	47.2	16 400*	18.0
20.0	69.2	47.5	21 700 *	71.6	47.2	20 400*	74.0	46.4	15 600*	20.0
22.0	66.6	46.6	21 100 *	69.0	46.3	20 000*	71.4	45.5	14 800*	22.0
24.0	64.0	45.7	20 600 *	66.4	45.3	19 700*	68.7	44.5	14 200*	24.0
26.0	61.3	44.6	20 200 *	63.6	44.2	18 900*	65.9	43.4	13 600*	26.0
28.0	58.5	43.3	19 800 *	60.9	42.9	17 800*	63.1	42.1	13 100*	28.0
30.0	55.7	42.0	19 400 *	58.0	41.6	16 800*	60.2	40.7	12 600*	30.0
32.0	52.7	40.4	19 100 *	55.0	40.0	16 100*	57.1	39.1	12 200*	32.0
34.0	49.6	38.7	18 400	51.9	38.3	15 300*	53.9	37.4	11 800*	34.0
36.0	46.4	36.8	16 700	48.6	36.4	14 700*	50.5	35.4	11 500*	36.0
38.0	42.9	34.7	15 300	45.1	34.2	14 000*	46.9	33.1	11 200*	38.0
40.0	39.2	32.3	14 100	41.3	31.8	13 500*				40.0
44.0	30.7	26.2	11 900	32.6	25.6	12 000				44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	79.5	53.0	24 200 *							12.2
14.0	77.4	52.6	23 600 *	79.8	52.3	21 700*				14.0
16.0	75.1	52.1	23 000 *	77.4	51.7	21 300*	79.8	51.0	17 600*	16.0
18.0	72.8	51.5	22 400 *	75.1	51.1	20 900*	77.5	50.4	16 700*	18.0
20.0	70.4	50.7	21 900 *	72.7	50.4	20 500*	75.0	49.6	15 800*	20.0
22.0	68.0	49.9	21 400 *	70.3	49.6	20 200*	72.6	48.8	15 100*	22.0
24.0	65.6	49.0	20 900 *	67.9	48.6	19 900*	70.1	47.9	14 500*	24.0
26.0	63.1	48.0	20 400 *	65.3	47.6	19 600*	67.5	46.8	13 900*	26.0
28.0	60.6	46.9	20 100 *	62.8	46.5	18 500*	64.9	45.6	13 400*	28.0
30.0	57.9	45.6	19 700 *	60.1	45.2	17 600*	62.2	44.3	12 900*	30.0
32.0	55.2	44.2	19 400 *	57.4	43.8	16 700*	59.4	42.9	12 500*	32.0
34.0	52.4	42.7	18 100	54.6	42.2	15 900*	56.5	41.3	12 100*	34.0
36.0	49.5	41.0	16 500	51.6	40.5	15 200*	53.5	39.6	11 800*	36.0
38.0	46.5	39.1	15 100	48.5	38.6	14 600*	50.4	37.6	11 500*	38.0
40.0	43.3	37.0	13 800	45.3	36.5	14 000	47.0	35.4	11 200*	40.0
44.0	36.1	31.9	11 700	38.0	31.3	11 900				44.0
48.0	27.3	25.1	9 900							48.0
42.5m Boom										
12.2	80.1	56.1	24 300 *							12.2
14.0	78.1	55.7	23 800 *	80.3	55.4	21 800*				14.0
16.0	76.0	55.2	23 100 *	78.2	54.9	21 300*				16.0
18.0	73.8	54.6	22 600 *	76.0	54.3	21 000*	78.2	53.5	16 900*	18.0
20.0	71.6	53.9	22 000 *	73.7	53.6	20 600*	75.9	52.8	16 200*	20.0
22.0	69.3	53.2	21 600 *	71.5	52.8	20 300*	73.6	52.0	15 400*	22.0
24.0	67.0	52.3	21 100 *	69.2	52.0	20 000*	71.3	51.2	14 800*	24.0
26.0	64.7	51.4	20 700 *	66.8	51.0	19 700*	68.9	50.2	14 200*	26.0
28.0	62.3	50.3	20 300 *	64.5	49.9	19 300*	66.5	49.1	13 700*	28.0
30.0	59.9	49.2	19 900 *	62.0	48.8	18 200*	64.0	47.9	13 200*	30.0
32.0	57.4	47.9	19 600 *	59.5	47.5	17 300*	61.4	46.6	12 800*	32.0
34.0	54.9	46.5	17 900	56.9	46.0	16 600*	58.8	45.1	12 400*	34.0
36.0	52.2	44.9	16 300	54.2	44.5	15 900*	56.1	43.5	12 100*	36.0
38.0	49.5	43.2	14 900	51.4	42.8	15 200	53.2	41.8	11 800*	38.0
40.0	46.6	41.3	13 700	48.5	40.9	13 900	50.2	39.8	11 500*	40.0
44.0	40.3	36.9	11 500	42.2	36.4	11 700	43.7	35.2	11 000*	44.0
48.0	33.1	31.3	9 800	34.8	30.6	9 900				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
12.2	80.6	59.2	24 400 *							12.2
14.0	78.8	58.8	23 800 *							14.0
16.0	76.7	58.3	23 200 *	78.8	58.0	21 400*				16.0
18.0	74.6	57.7	22 700 *	76.7	57.4	21 000*	78.8	56.6	17 200*	18.0
20.0	72.6	57.1	22 200 *	74.6	56.8	20 700*	76.7	56.0	16 400*	20.0
22.0	70.4	56.4	21 700 *	72.5	56.0	20 400*	74.6	55.2	15 700*	22.0
24.0	68.3	55.6	21 300 *	70.3	55.2	20 100*	72.4	54.4	15 100*	24.0
26.0	66.1	54.7	20 900 *	68.1	54.3	19 900*	70.1	53.5	14 500*	26.0
28.0	63.9	53.7	20 500 *	65.9	53.3	19 600*	67.9	52.5	14 000*	28.0
30.0	61.7	52.6	20 100 *	63.6	52.2	18 900*	65.6	51.4	13 500*	30.0
32.0	59.3	51.4	19 400	61.3	51.0	18 000*	63.2	50.2	13 100*	32.0
34.0	57.0	50.1	17 600	58.9	49.7	17 100*	60.7	48.8	12 700*	34.0
36.0	54.5	48.7	16 000	56.5	48.3	16 300	58.2	47.4	12 300*	36.0
38.0	52.0	47.2	14 600	53.9	46.7	14 900	55.6	45.8	12 000*	38.0
40.0	49.4	45.4	13 400	51.3	45.0	13 600	52.9	44.0	11 700*	40.0
44.0	43.8	41.5	11 200	45.6	41.0	11 500	47.1	39.9	11 200*	44.0
48.0	37.5	36.6	9 500	39.3	36.1	9 700				48.0
52.0	30.2	30.4	8 000							52.0
48.5m Boom										
13.7	79.6	61.9	23 900 *							13.7
14.0	79.3	61.9	23 900 *							14.0
16.0	77.4	61.4	23 300 *	79.4	61.0	21 500*				16.0
18.0	75.4	60.9	22 800 *	77.4	60.5	21 100*	79.4	59.7	17 400*	18.0
20.0	73.5	60.3	22 300 *	75.4	59.9	20 800*	77.4	59.1	16 700*	20.0
22.0	71.5	59.6	21 900 *	73.4	59.2	20 500*	75.4	58.4	16 000*	22.0
24.0	69.4	58.8	21 400 *	71.4	58.5	20 200*	73.3	57.7	15 300*	24.0
26.0	67.4	58.0	21 100 *	69.3	57.6	19 900*	71.2	56.8	14 800*	26.0
28.0	65.3	57.1	20 700 *	67.2	56.7	19 700*	69.1	55.9	14 300*	28.0
30.0	63.2	56.1	20 300 *	65.1	55.7	19 400*	66.9	54.8	13 800*	30.0
32.0	61.0	54.9	19 100	62.9	54.5	18 500*	64.7	53.7	13 400*	32.0
34.0	58.8	53.7	17 400	60.7	53.3	17 600	62.4	52.4	13 000*	34.0
36.0	56.6	52.4	15 800	58.4	52.0	16 200	60.1	51.1	12 600*	36.0
38.0	54.2	51.0	14 400	56.0	50.5	14 800	57.7	49.6	12 300*	38.0
40.0	51.8	49.4	13 200	53.6	48.9	13 500	55.3	48.0	12 000*	40.0
44.0	46.7	45.8	11 000	48.5	45.3	11 300	50.0	44.3	11 400*	44.0
48.0	41.2	41.5	9 300	42.9	40.9	9 500	44.2	39.8	9 600	48.0
52.0	34.9	36.1	7 800	36.5	35.5	8 000				52.0
56.0	27.3	29.2	6 500							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
13.7	80.1	65.0	23 900 *							13.7
14.0	79.8	64.9	23 900 *							14.0
16.0	78.0	64.5	23 400 *	79.9	64.1	21 500*				16.0
18.0	76.1	64.0	22 900 *	78.0	63.6	21 100*				18.0
20.0	74.3	63.4	22 400 *	76.1	63.0	20 800*	78.0	62.3	16 800*	20.0
22.0	72.4	62.8	22 000 *	74.2	62.4	20 500*	76.1	61.6	16 200*	22.0
24.0	70.5	62.0	21 600 *	72.3	61.7	20 300*	74.2	60.9	15 600*	24.0
26.0	68.5	61.3	21 200 *	70.4	60.9	20 000*	72.2	60.1	15 000*	26.0
28.0	66.6	60.4	20 800 *	68.4	60.0	19 800*	70.2	59.2	14 500*	28.0
30.0	64.6	59.4	20 500 *	66.4	59.0	19 600*	68.1	58.2	14 100*	30.0
32.0	62.5	58.4	18 900	64.3	58.0	19 100*	66.1	57.1	13 600*	32.0
34.0	60.5	57.2	17 100	62.2	56.8	17 600	63.9	56.0	13 200*	34.0
36.0	58.3	56.0	15 600	60.1	55.6	16 000	61.8	54.7	12 900*	36.0
38.0	56.2	54.7	14 200	57.9	54.2	14 500	59.6	53.3	12 500*	38.0
40.0	53.9	53.2	12 900	55.7	52.8	13 300	57.3	51.8	12 200*	40.0
44.0	49.3	49.9	10 800	51.0	49.4	11 100	52.5	48.4	11 300	44.0
48.0	44.2	46.0	9 000	45.9	45.5	9 300	47.2	44.4	9 500	48.0
52.0	38.7	41.3	7 600	40.2	40.7	7 700				52.0
56.0	32.3	35.4	6 300	33.7	34.8	6 400				56.0
60.0	24.4	27.7	5 200							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
13.7	80.5	68.0	23 900 *							13.7
14.0	80.3	68.0	23 900 *							14.0
16.0	78.5	67.6	23 400 *	80.3	67.2	21 400*				16.0
18.0	76.8	67.1	22 900 *	78.6	66.7	21 100*				18.0
20.0	75.0	66.5	22 500 *	76.8	66.2	20 800*	78.6	65.4	17 100*	20.0
22.0	73.2	65.9	22 000 *	75.0	65.6	20 600*	76.8	64.8	16 400*	22.0
24.0	71.4	65.2	21 700 *	73.1	64.9	20 400*	74.9	64.1	15 800*	24.0
26.0	69.5	64.5	21 300 *	71.3	64.1	20 100*	73.1	63.3	15 300*	26.0
28.0	67.7	63.7	20 900 *	69.4	63.3	19 900*	71.2	62.5	14 800*	28.0
30.0	65.8	62.8	20 500	67.5	62.4	19 700*	69.2	61.5	14 300*	30.0
32.0	63.9	61.8	18 700	65.6	61.4	19 200	67.3	60.5	13 900*	32.0
34.0	61.9	60.7	16 900	63.6	60.3	17 400	65.3	59.4	13 500*	34.0
36.0	59.9	59.5	15 400	61.6	59.1	15 800	63.2	58.2	13 100*	36.0
38.0	57.9	58.3	13 900	59.6	57.9	14 400	61.2	57.0	12 800*	38.0
40.0	55.8	56.9	12 700	57.5	56.5	13 100	59.0	55.6	12 500*	40.0
44.0	51.5	53.9	10 600	53.1	53.4	10 900	54.6	52.4	11 200	44.0
48.0	46.9	50.3	8 800	48.5	49.8	9 100	49.8	48.7	9 300	48.0
52.0	41.9	46.0	7 400	43.4	45.5	7 600				52.0
56.0	36.3	40.9	6 100	37.7	40.3	6 200				56.0
60.0	29.8	34.5	5 000							60.0
64.0	21.5	25.7	4 000							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
13.7	81.0	71.1	23 900 *							13.7
14.0	80.7	71.0	23 800 *							14.0
16.0	79.0	70.6	23 400 *							16.0
18.0	77.4	70.2	22 900 *	79.1	69.8	21 100*				18.0
20.0	75.7	69.7	22 500 *	77.4	69.3	20 800*	79.1	68.5	17 300*	20.0
22.0	73.9	69.1	22 100 *	75.6	68.7	20 600*	77.4	67.9	16 600*	22.0
24.0	72.2	68.4	21 700 *	73.9	68.1	20 400*	75.6	67.2	16 000*	24.0
26.0	70.5	67.7	21 400 *	72.2	67.3	20 100*	73.8	66.5	15 500*	26.0
28.0	68.7	66.9	21 000 *	70.4	66.5	19 900*	72.0	65.7	15 000*	28.0
30.0	66.9	66.1	20 200	68.6	65.7	19 700*	70.2	64.8	14 500*	30.0
32.0	65.1	65.1	18 400	66.7	64.7	19 000	68.4	63.9	14 100*	32.0
34.0	63.2	64.1	16 600	64.9	63.7	17 100	66.5	62.9	13 700*	34.0
36.0	61.4	63.0	15 100	63.0	62.6	15 500	64.6	61.7	13 300*	36.0
38.0	59.5	61.8	13 700	61.1	61.4	14 100	62.6	60.5	13 000*	38.0
40.0	57.5	60.6	12 400	59.1	60.1	12 800	60.6	59.2	12 700	40.0
44.0	53.5	57.7	10 300	55.0	57.3	10 600	56.5	56.3	10 900	44.0
48.0	49.2	54.4	8 500	50.7	53.9	8 800	52.1	52.9	9 000	48.0
52.0	44.6	50.5	7 100	46.1	50.0	7 300	47.3	48.9	7 500	52.0
56.0	39.6	45.9	5 800	41.0	45.3	6 000				56.0
60.0	34.0	40.3	4 700	35.3	39.7	4 800				60.0
64.0	27.3	33.3	3 700							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
15.2	80.1	73.8	23 500 *							15.2
16.0	79.5	73.7	23 300 *							16.0
18.0	77.9	73.3	22 900 *	79.5	72.9	21 100*				18.0
20.0	76.3	72.8	22 500 *	77.9	72.4	20 800*	79.6	71.6	17 400*	20.0
22.0	74.6	72.2	22 100 *	76.3	71.8	20 600*	77.9	71.0	16 800*	22.0
24.0	73.0	71.6	21 800 *	74.6	71.2	20 400*	76.2	70.4	16 200*	24.0
26.0	71.3	70.9	21 400 *	72.9	70.5	20 200*	74.6	69.7	15 700*	26.0
28.0	69.6	70.2	21 100	71.2	69.8	20 000*	72.8	68.9	15 200*	28.0
30.0	67.9	69.3	19 900	69.5	68.9	19 800*	71.1	68.1	14 800*	30.0
32.0	66.2	68.4	18 000	67.8	68.1	18 600	69.3	67.2	14 300*	32.0
34.0	64.4	67.5	16 400	66.0	67.1	16 900	67.6	66.2	13 900*	34.0
36.0	62.7	66.4	14 800	64.2	66.0	15 300	65.7	65.2	13 600*	36.0
38.0	60.9	65.3	13 400	62.4	64.9	13 900	63.9	64.0	13 200*	38.0
40.0	59.0	64.1	12 200	60.6	63.7	12 600	62.0	62.8	12 800	40.0
44.0	55.2	61.4	10 100	56.7	61.0	10 400	58.1	60.0	10 700	44.0
48.0	51.2	58.3	8 300	52.7	57.9	8 600	54.0	56.9	8 900	48.0
52.0	47.0	54.8	6 800	48.4	54.3	7 100	49.7	53.2	7 300	52.0
56.0	42.4	50.6	5 500	43.8	50.0	5 800	45.0	48.9	5 900	56.0
60.0	37.4	45.6	4 500	38.7	45.0	4 700				60.0
64.0	31.7	39.6	3 500	32.9	38.9	3 600				64.0
68.0	24.8	31.8	2 700							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
15.2	80.5	76.9	23 400 *							15.2
16.0	79.9	76.7	23 200 *							16.0
18.0	78.4	76.3	22 900 *	80.0	76.0	21 100*				18.0
20.0	76.8	75.9	22 500 *	78.4	75.5	20 800*	80.0	74.7	17 600*	20.0
22.0	75.2	75.3	22 100 *	76.8	75.0	20 600*	78.4	74.1	17 000*	22.0
24.0	73.7	74.7	21 800 *	75.2	74.4	20 400*	76.8	73.5	16 400*	24.0
26.0	72.1	74.1	21 400 *	73.6	73.7	20 200*	75.2	72.9	15 900*	26.0
28.0	70.5	73.4	21 000	72.0	73.0	20 000*	73.6	72.1	15 400*	28.0
30.0	68.8	72.6	19 400	70.4	72.2	19 600	71.9	71.4	15 000*	30.0
32.0	67.2	71.7	17 600	68.7	71.3	18 100	70.2	70.5	14 600*	32.0
34.0	65.5	70.8	16 000	67.1	70.4	16 500	68.5	69.6	14 100*	34.0
36.0	63.8	69.8	14 600	65.4	69.4	15 100	66.8	68.6	13 800*	36.0
38.0	62.1	68.8	13 200	63.6	68.4	13 700	65.1	67.5	13 400*	38.0
40.0	60.4	67.6	12 000	61.9	67.2	12 400	63.3	66.3	12 800	40.0
44.0	56.8	65.1	9 800	58.3	64.7	10 200	59.6	63.7	10 500	44.0
48.0	53.1	62.2	8 100	54.5	61.7	8 400	55.8	60.7	8 700	48.0
52.0	49.1	58.8	6 600	50.5	58.4	6 900	51.7	57.3	7 100	52.0
56.0	44.9	55.0	5 300	46.3	54.5	5 500	47.4	53.3	5 700	56.0
60.0	40.3	50.5	4 200	41.7	49.9	4 400				60.0
64.0	35.3	45.2	3 300	36.5	44.5	3 400				64.0
68.0	29.5	38.6	2 500							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
15.2	80.9	79.9	23 300 *							15.2
16.0	80.3	79.8	23 200 *							16.0
18.0	78.8	79.4	22 800 *							18.0
20.0	77.3	78.9	22 500 *	78.9	78.6	20 800*	80.4	77.8	17 800*	20.0
22.0	75.8	78.4	22 100 *	77.3	78.1	20 600*	78.9	77.3	17 200*	22.0
24.0	74.3	77.9	21 800 *	75.8	77.5	20 400*	77.4	76.7	16 600*	24.0
26.0	72.8	77.2	21 500 *	74.3	76.9	20 200*	75.8	76.0	16 100*	26.0
28.0	71.2	76.6	20 800	72.7	76.2	20 000*	74.2	75.3	15 600*	28.0
30.0	69.7	75.8	18 800	71.2	75.4	19 400	72.7	74.6	15 200*	30.0
32.0	68.1	75.0	17 100	69.6	74.6	17 700	71.1	73.8	14 700*	32.0
34.0	66.5	74.1	15 600	68.0	73.7	16 100	69.4	72.9	14 400*	34.0
36.0	64.9	73.2	14 200	66.4	72.8	14 700	67.8	71.9	14 000*	36.0
38.0	63.3	72.2	12 900	64.7	71.8	13 400	66.1	70.9	13 700*	38.0
40.0	61.6	71.1	11 700	63.1	70.7	12 200	64.4	69.8	12 600	40.0
44.0	58.2	68.7	9 600	59.7	68.3	10 000	61.0	67.3	10 300	44.0
48.0	54.7	66.0	7 800	56.1	65.5	8 200	57.4	64.5	8 500	48.0
52.0	51.0	62.8	6 400	52.4	62.3	6 600	53.6	61.3	6 900	52.0
56.0	47.1	59.2	5 100	48.4	58.7	5 300	49.6	57.6	5 500	56.0
60.0	42.9	55.1	4 000	44.2	54.6	4 200	45.2	53.4	4 400	60.0
64.0	38.3	50.3	3 100	39.6	49.7	3 200				64.0
68.0	33.2	44.5	2 200	34.4	43.9	2 300				68.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

12.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	80.1	82.7	22 900 *							16.8
18.0	79.2	82.5	22 700 *							18.0
20.0	77.8	82.0	22 400 *	79.3	81.7	20 700*	80.8	80.8	17 900*	20.0
22.0	76.4	81.5	22 000 *	77.8	81.2	20 500*	79.3	80.3	17 400*	22.0
24.0	74.9	81.0	21 700 *	76.4	80.6	20 300*	77.8	79.8	16 800*	24.0
26.0	73.4	80.4	21 400	74.9	80.0	20 100*	76.4	79.2	16 300*	26.0
28.0	72.0	79.7	20 300	73.4	79.4	19 900*	74.9	78.5	15 800*	28.0
30.0	70.5	79.0	18 200	71.9	78.6	19 100	73.3	77.8	15 400*	30.0
32.0	69.0	78.2	16 600	70.4	77.9	17 200	71.8	77.0	14 900*	32.0
34.0	67.4	77.4	15 000	68.9	77.0	15 600	70.3	76.2	14 600*	34.0
36.0	65.9	76.5	13 700	67.3	76.1	14 200	68.7	75.2	14 200*	36.0
38.0	64.3	75.5	12 400	65.8	75.1	12 900	67.1	74.3	13 400	38.0
40.0	62.8	74.5	11 300	64.2	74.1	11 800	65.5	73.2	12 300	40.0
44.0	59.5	72.2	9 300	60.9	71.8	9 700	62.2	70.9	10 100	44.0
48.0	56.2	69.6	7 500	57.5	69.2	7 900	58.8	68.2	8 200	48.0
52.0	52.7	66.7	6 100	54.0	66.2	6 300	55.2	65.2	6 600	52.0
56.0	49.0	63.3	4 800	50.3	62.8	5 100	51.5	61.8	5 300	56.0
60.0	45.1	59.5	3 700	46.4	59.0	3 900	47.5	57.8	4 100	60.0
64.0	41.0	55.1	2 800	42.2	54.5	2 900	43.2	53.3	3 100	64.0
68.0	36.4	49.9	1 900	37.6	49.3	2 100				68.0
72.5m Boom										
16.8	80.5	85.8	22 800 *							16.8
18.0	79.6	85.5	22 600 *							18.0
20.0	78.2	85.1	22 300 *	79.7	84.7	20 600*				20.0
22.0	76.9	84.6	21 900 *	78.3	84.3	20 400*	79.7	83.4	17 500*	22.0
24.0	75.5	84.1	21 600 *	76.9	83.7	20 300*	78.3	82.9	17 000*	24.0
26.0	74.0	83.5	21 300	75.4	83.1	20 100*	76.9	82.3	16 400*	26.0
28.0	72.6	82.9	19 800	74.0	82.5	19 800	75.4	81.7	16 000*	28.0
30.0	71.2	82.2	17 800	72.6	81.8	18 600	74.0	81.0	15 500*	30.0
32.0	69.7	81.5	16 100	71.1	81.1	16 700	72.5	80.2	15 100*	32.0
34.0	68.3	80.7	14 600	69.7	80.3	15 200	71.0	79.4	14 700*	34.0
36.0	66.8	79.8	13 200	68.2	79.4	13 800	69.5	78.5	14 200	36.0
38.0	65.3	78.9	12 000	66.7	78.5	12 500	68.0	77.6	13 100	38.0
40.0	63.8	77.9	11 000	65.2	77.5	11 400	66.5	76.6	11 900	40.0
44.0	60.7	75.7	9 000	62.1	75.3	9 400	63.3	74.4	9 800	44.0
48.0	57.6	73.2	7 300	58.9	72.8	7 700	60.1	71.9	8 000	48.0
52.0	54.2	70.5	5 800	55.5	70.0	6 100	56.7	69.0	6 400	52.0
56.0	50.8	67.3	4 600	52.1	66.8	4 800	53.2	65.8	5 100	56.0
60.0	47.2	63.7	3 500	48.4	63.2	3 700	49.5	62.1	3 900	60.0
64.0	43.3	59.6	2 500	44.5	59.1	2 700	45.5	57.9	2 900	64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
10.7	79.6	44.2	20 500 *							10.7
12.0	77.8	43.9	20 000 *							12.0
14.0	75.0	43.3	19 300 *	78.6	43.0	17 900*				14.0
16.0	72.2	42.7	18 600 *	75.7	42.3	17 300*	79.4	41.5	14 400*	16.0
18.0	69.3	41.9	18 000 *	72.8	41.5	16 800*	76.4	40.7	13 400*	18.0
20.0	66.4	41.0	17 400 *	69.9	40.6	16 300*	73.4	39.8	12 500*	20.0
22.0	63.4	40.0	16 800 *	66.8	39.6	15 700*	70.3	38.7	11 700*	22.0
24.0	60.2	38.8	16 200 *	63.7	38.4	14 600*	67.1	37.5	11 100*	24.0
26.0	57.0	37.5	15 700 *	60.4	37.1	13 700*	63.7	36.2	10 500*	26.0
28.0	53.7	36.0	15 200 *	57.1	35.6	12 800*	60.2	34.6	10 000*	28.0
30.0	50.2	34.3	14 700 *	53.5	33.9	12 100*	56.6	32.9	9 600*	30.0
32.0	46.5	32.4	13 800 *	49.7	31.9	11 500*	52.7	30.9	9 200*	32.0
34.0	42.5	30.2	13 000 *	45.7	29.7	10 900*	48.5	28.5	8 900*	34.0
36.0	38.2	27.7	12 200 *	41.3	27.1	10 400*				36.0
38.0	33.4	24.7	11 500 *	36.3	24.1	10 000*				38.0
40.0	27.7	21.0	11 000 *							40.0
30.5m Boom										
10.7	80.3	47.3	20 600 *							10.7
12.0	78.6	47.0	20 200 *							12.0
14.0	76.0	46.5	19 500 *	79.4	46.1	18 000*				14.0
16.0	73.4	45.9	18 800 *	76.7	45.5	17 500*				16.0
18.0	70.7	45.1	18 300 *	74.0	44.8	16 900*	77.4	43.9	13 600*	18.0
20.0	68.0	44.3	17 700 *	71.3	43.9	16 500*	74.6	43.1	12 800*	20.0
22.0	65.3	43.4	17 100 *	68.5	43.0	16 100*	71.8	42.1	12 100*	22.0
24.0	62.4	42.3	16 600 *	65.6	41.9	15 300*	68.8	41.0	11 400*	24.0
26.0	59.5	41.1	16 100 *	62.7	40.7	14 300*	65.8	39.8	10 900*	26.0
28.0	56.5	39.8	15 600 *	59.6	39.3	13 500*	62.7	38.4	10 400*	28.0
30.0	53.3	38.3	15 200 *	56.5	37.8	12 700*	59.4	36.8	9 900*	30.0
32.0	50.1	36.6	14 700 *	53.1	36.1	12 100*	56.0	35.1	9 500*	32.0
34.0	46.6	34.7	13 900 *	49.6	34.2	11 500*	52.3	33.1	9 200*	34.0
36.0	42.9	32.5	13 000 *	45.9	32.0	10 900*	48.5	30.8	8 900*	36.0
38.0	38.9	30.0	12 300 *	41.8	29.5	10 500*	44.2	28.2	8 600*	38.0
40.0	34.6	27.2	11 700 *	37.3	26.5	10 100*				40.0
44.0	23.6	19.4	10 600 *							44.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
10.7	80.9	50.3	20 800 *							10.7
12.0	79.3	50.1	20 300 *							12.0
14.0	76.9	49.6	19 600 *	80.1	49.2	18 100*				14.0
16.0	74.5	49.0	19 000 *	77.6	48.6	17 600*				16.0
18.0	72.0	48.3	18 500 *	75.1	47.9	17 100*	78.2	47.1	14 000*	18.0
20.0	69.5	47.6	18 000 *	72.6	47.2	16 600*	75.7	46.3	13 100*	20.0
22.0	66.9	46.7	17 400 *	70.0	46.3	16 200*	73.0	45.4	12 400*	22.0
24.0	64.3	45.7	16 900 *	67.3	45.3	15 800*	70.3	44.4	11 800*	24.0
26.0	61.6	44.6	16 400 *	64.6	44.2	14 900*	67.5	43.3	11 200*	26.0
28.0	58.8	43.4	15 900 *	61.8	42.9	14 000*	64.7	42.0	10 700*	28.0
30.0	56.0	42.0	15 500 *	58.9	41.6	13 300*	61.7	40.6	10 300*	30.0
32.0	53.0	40.5	15 100 *	55.9	40.0	12 600*	58.7	39.0	9 800*	32.0
34.0	49.9	38.8	14 700 *	52.8	38.3	12 000*	55.4	37.2	9 500*	34.0
36.0	46.7	36.9	13 900 *	49.5	36.4	11 400*	52.1	35.3	9 100*	36.0
38.0	43.3	34.8	13 100 *	46.0	34.2	10 900*	48.4	33.0	8 900*	38.0
40.0	39.6	32.4	12 400 *	42.3	31.8	10 500*				40.0
44.0	31.1	26.3	11 200 *	33.6	25.6	9 800*				44.0
36.5m Boom										
12.2	79.7	53.1	20 300 *							12.2
14.0	77.7	52.7	19 800 *	80.7	52.3	18 200*				14.0
16.0	75.4	52.1	19 200 *	78.3	51.7	17 700*				16.0
18.0	73.1	51.5	18 700 *	76.0	51.1	17 300*	79.0	50.3	14 200*	18.0
20.0	70.7	50.8	18 100 *	73.6	50.4	16 800*	76.6	49.5	13 400*	20.0
22.0	68.3	50.0	17 700 *	71.2	49.6	16 400*	74.1	48.7	12 700*	22.0
24.0	65.9	49.1	17 200 *	68.8	48.6	16 000*	71.6	47.7	12 100*	24.0
26.0	63.4	48.0	16 700 *	66.2	47.6	15 500*	69.0	46.7	11 500*	26.0
28.0	60.9	46.9	16 200 *	63.7	46.5	14 600*	66.4	45.5	11 000*	28.0
30.0	58.2	45.7	15 800 *	61.0	45.2	13 800*	63.7	44.2	10 500*	30.0
32.0	55.5	44.3	15 400 *	58.3	43.8	13 100*	60.9	42.8	10 100*	32.0
34.0	52.7	42.7	15 100 *	55.5	42.3	12 500*	58.0	41.2	9 800*	34.0
36.0	49.8	41.0	14 600 *	52.5	40.5	11 900*	55.0	39.4	9 400*	36.0
38.0	46.8	39.1	13 900 *	49.4	38.6	11 400*	51.8	37.5	9 100*	38.0
40.0	43.6	37.0	13 200 *	46.2	36.5	11 000*	48.4	35.2	8 900*	40.0
44.0	36.4	32.0	11 900 *	38.9	31.3	10 200*				44.0
48.0	27.7	25.2	10 400							48.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	80.3	56.1	20 400 *							12.2
14.0	78.4	55.8	19 900 *							14.0
16.0	76.2	55.2	19 300 *	79.0	54.9	17 800*				16.0
18.0	74.0	54.7	18 800 *	76.8	54.3	17 400*	79.6	53.4	14 400*	18.0
20.0	71.8	54.0	18 300 *	74.6	53.6	17 000*	77.4	52.7	13 600*	20.0
22.0	69.6	53.2	17 900 *	72.3	52.8	16 600*	75.1	51.9	12 900*	22.0
24.0	67.3	52.4	17 400 *	70.0	51.9	16 200*	72.7	51.0	12 300*	24.0
26.0	65.0	51.4	16 900 *	67.7	51.0	15 800*	70.3	50.1	11 800*	26.0
28.0	62.6	50.4	16 500 *	65.3	49.9	15 200*	67.9	49.0	11 300*	28.0
30.0	60.2	49.2	16 100 *	62.9	48.8	14 300*	65.4	47.8	10 800*	30.0
32.0	57.7	47.9	15 700 *	60.3	47.5	13 600*	62.8	46.5	10 400*	32.0
34.0	55.1	46.5	15 300 *	57.8	46.0	13 000*	60.2	45.0	10 000*	34.0
36.0	52.5	45.0	15 000 *	55.1	44.5	12 400*	57.4	43.4	9 700*	36.0
38.0	49.7	43.3	14 700 *	52.3	42.8	11 900*	54.6	41.6	9 400*	38.0
40.0	46.9	41.4	13 900	49.4	40.8	11 400*	51.6	39.7	9 100*	40.0
44.0	40.6	37.0	12 000	43.0	36.4	10 600*	45.0	35.0	8 700*	44.0
48.0	33.4	31.4	10 200	35.7	30.6	10 000*				48.0
42.5m Boom										
12.2	80.8	59.2	20 500 *							12.2
14.0	79.0	58.8	20 000 *							14.0
16.0	77.0	58.4	19 400 *	79.6	58.0	17 900*				16.0
18.0	74.9	57.8	18 900 *	77.5	57.4	17 500*				18.0
20.0	72.8	57.2	18 500 *	75.4	56.8	17 100*	78.1	55.9	13 900*	20.0
22.0	70.7	56.4	18 000 *	73.3	56.0	16 700*	75.9	55.1	13 200*	22.0
24.0	68.6	55.6	17 600 *	71.1	55.2	16 300*	73.7	54.3	12 600*	24.0
26.0	66.4	54.8	17 200 *	69.0	54.3	16 000*	71.5	53.4	12 000*	26.0
28.0	64.2	53.8	16 700 *	66.7	53.3	15 600*	69.2	52.4	11 500*	28.0
30.0	61.9	52.7	16 300 *	64.4	52.2	14 900*	66.9	51.3	11 100*	30.0
32.0	59.6	51.5	16 000 *	62.1	51.0	14 100*	64.5	50.0	10 700*	32.0
34.0	57.2	50.2	15 600 *	59.7	49.7	13 500*	62.1	48.7	10 300*	34.0
36.0	54.8	48.8	15 300 *	57.3	48.3	12 900*	59.5	47.2	9 900*	36.0
38.0	52.3	47.2	15 000 *	54.7	46.7	12 400*	56.9	45.6	9 600*	38.0
40.0	49.7	45.5	13 900	52.1	45.0	11 800*	54.2	43.8	9 400*	40.0
44.0	44.1	41.6	11 800	46.4	41.0	11 000*	48.4	39.7	8 900*	44.0
48.0	37.8	36.7	10 000	40.1	36.0	10 200				48.0
52.0	30.5	30.5	8 600							52.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	79.8	62.0	20 100 *							13.7
14.0	79.5	61.9	20 000 *							14.0
16.0	77.6	61.4	19 500 *	80.1	61.0	17 900*				16.0
18.0	75.7	60.9	19 000 *	78.2	60.5	17 600*				18.0
20.0	73.7	60.3	18 600 *	76.2	59.9	17 200*	78.7	59.0	14 100*	20.0
22.0	71.7	59.6	18 100 *	74.2	59.2	16 800*	76.7	58.3	13 400*	22.0
24.0	69.7	58.9	17 700 *	72.1	58.5	16 500*	74.6	57.5	12 800*	24.0
26.0	67.6	58.0	17 400 *	70.1	57.6	16 200*	72.5	56.7	12 300*	26.0
28.0	65.5	57.1	17 000 *	68.0	56.7	15 900*	70.4	55.7	11 800*	28.0
30.0	63.4	56.1	16 600 *	65.8	55.7	15 400*	68.2	54.7	11 300*	30.0
32.0	61.3	55.0	16 200 *	63.7	54.5	14 600*	66.0	53.5	10 900*	32.0
34.0	59.1	53.8	15 800 *	61.4	53.3	13 900*	63.7	52.3	10 500*	34.0
36.0	56.8	52.5	15 500 *	59.2	52.0	13 300*	61.4	50.9	10 200*	36.0
38.0	54.5	51.0	14 900	56.8	50.5	12 800*	59.0	49.4	9 900*	38.0
40.0	52.1	49.4	13 600	54.4	48.9	12 300*	56.5	47.8	9 600*	40.0
44.0	47.0	45.9	11 500	49.3	45.3	11 400*	51.2	44.1	9 100*	44.0
48.0	41.5	41.5	9 700	43.6	40.9	10 000	45.4	39.6	8 700*	48.0
52.0	35.2	36.2	8 200	37.2	35.5	8 500				52.0
56.0	27.6	29.3	7 000							56.0
48.5m Boom										
13.7	80.3	65.0	20 100 *							13.7
14.0	80.0	65.0	20 100 *							14.0
16.0	78.2	64.5	19 600 *							16.0
18.0	76.3	64.0	19 100 *	78.7	63.6	17 600*				18.0
20.0	74.5	63.5	18 700 *	76.9	63.0	17 300*	79.3	62.1	14 300*	20.0
22.0	72.6	62.8	18 300 *	75.0	62.4	16 900*	77.3	61.5	13 600*	22.0
24.0	70.7	62.1	17 900 *	73.0	61.7	16 600*	75.4	60.7	13 000*	24.0
26.0	68.7	61.3	17 500 *	71.1	60.9	16 300*	73.4	59.9	12 500*	26.0
28.0	66.8	60.4	17 200 *	69.1	60.0	16 000*	71.4	59.0	12 000*	28.0
30.0	64.8	59.5	16 800 *	67.1	59.0	15 700*	69.3	58.1	11 600*	30.0
32.0	62.8	58.4	16 400 *	65.1	58.0	15 100*	67.3	57.0	11 200*	32.0
34.0	60.7	57.3	16 100 *	63.0	56.8	14 400*	65.1	55.8	10 700*	34.0
36.0	58.6	56.1	15 700 *	60.8	55.6	13 800*	63.0	54.5	10 400*	36.0
38.0	56.4	54.7	14 700	58.6	54.2	13 200*	60.7	53.2	10 100*	38.0
40.0	54.2	53.3	13 400	56.4	52.8	12 700*	58.4	51.7	9 800*	40.0
44.0	49.5	50.0	11 300	51.7	49.4	11 600	53.6	48.3	9 300*	44.0
48.0	44.5	46.1	9 500	46.6	45.5	9 800	48.4	44.2	8 900*	48.0
52.0	38.9	41.4	8 000	41.0	40.7	8 300				52.0
56.0	32.6	35.5	6 800	34.5	34.7	6 900				56.0
60.0	24.7	27.8	5 700							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
13.7	80.7	68.1	20 100 *							13.7
14.0	80.5	68.0	20 100 *							14.0
16.0	78.7	67.6	19 600 *							16.0
18.0	77.0	67.1	19 100 *	79.3	66.7	17 700*				18.0
20.0	75.2	66.6	18 700 *	77.5	66.2	17 400*	79.8	65.2	14 500*	20.0
22.0	73.4	66.0	18 400 *	75.7	65.5	17 000*	77.9	64.6	13 800*	22.0
24.0	71.6	65.3	18 000 *	73.8	64.9	16 700*	76.1	63.9	13 200*	24.0
26.0	69.8	64.5	17 600 *	72.0	64.1	16 400*	74.2	63.2	12 700*	26.0
28.0	67.9	63.7	17 300 *	70.1	63.3	16 100*	72.3	62.3	12 200*	28.0
30.0	66.0	62.8	17 000 *	68.2	62.4	15 900*	70.4	61.4	11 800*	30.0
32.0	64.1	61.8	16 600 *	66.3	61.4	15 500*	68.4	60.4	11 400*	32.0
34.0	62.1	60.8	16 200 *	64.3	60.3	14 800*	66.4	59.3	11 000*	34.0
36.0	60.2	59.6	15 700	62.3	59.1	14 200*	64.4	58.1	10 600*	36.0
38.0	58.1	58.3	14 500	60.3	57.9	13 600*	62.3	56.8	10 300*	38.0
40.0	56.1	57.0	13 200	58.2	56.5	13 100*	60.2	55.4	10 000*	40.0
44.0	51.7	53.9	11 100	53.8	53.4	11 400	55.7	52.2	9 500*	44.0
48.0	47.1	50.3	9 300	49.1	49.8	9 600	50.9	48.5	9 100*	48.0
52.0	42.1	46.1	7 800	44.1	45.5	8 100	45.7	44.1	8 300	52.0
56.0	36.5	41.0	6 600	38.4	40.3	6 700				56.0
60.0	30.0	34.6	5 400							60.0
64.0	21.8	25.9	4 500							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	79.9	70.8	19 800 *							15.2
16.0	79.2	70.7	19 600 *							16.0
18.0	77.6	70.2	19 200 *	79.7	69.8	17 700*				18.0
20.0	75.9	69.7	18 800 *	78.0	69.3	17 400*	80.2	68.4	14 700*	20.0
22.0	74.1	69.1	18 400 *	76.3	68.7	17 100*	78.5	67.8	14 000*	22.0
24.0	72.4	68.5	18 100 *	74.6	68.0	16 800*	76.7	67.1	13 400*	24.0
26.0	70.7	67.8	17 700 *	72.8	67.3	16 500*	74.9	66.4	12 900*	26.0
28.0	68.9	67.0	17 400 *	71.0	66.5	16 200*	73.1	65.6	12 400*	28.0
30.0	67.1	66.1	17 100 *	69.2	65.7	16 000*	71.3	64.7	12 000*	30.0
32.0	65.3	65.2	16 800 *	67.4	64.7	15 700*	69.4	63.7	11 600*	32.0
34.0	63.5	64.2	16 400 *	65.6	63.7	15 300*	67.6	62.7	11 200*	34.0
36.0	61.6	63.1	15 700	63.7	62.6	14 600*	65.6	61.6	10 800*	36.0
38.0	59.7	61.9	14 200	61.7	61.4	14 000*	63.7	60.4	10 500*	38.0
40.0	57.7	60.6	13 000	59.8	60.1	13 400	61.7	59.0	10 200*	40.0
44.0	53.7	57.8	10 800	55.7	57.2	11 200	57.5	56.1	9 700*	44.0
48.0	49.4	54.4	9 100	51.4	53.9	9 400	53.1	52.7	9 200*	48.0
52.0	44.8	50.6	7 600	46.7	50.0	7 900	48.4	48.7	8 100	52.0
56.0	39.8	46.0	6 300	41.7	45.3	6 500	43.1	43.9	6 700	56.0
60.0	34.2	40.4	5 200	35.9	39.7	5 400				60.0
64.0	27.6	33.4	4 300							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
15.2	80.3	73.9	19 800 *							15.2
16.0	79.7	73.7	19 600 *							16.0
18.0	78.1	73.3	19 200 *							18.0
20.0	76.5	72.8	18 800 *	78.5	72.4	17 400*	80.7	71.4	14 800*	20.0
22.0	74.8	72.3	18 500 *	76.9	71.8	17 200*	79.0	70.9	14 200*	22.0
24.0	73.2	71.6	18 100 *	75.2	71.2	16 800*	77.3	70.2	13 600*	24.0
26.0	71.5	70.9	17 800 *	73.6	70.5	16 600*	75.6	69.5	13 100*	26.0
28.0	69.8	70.2	17 500 *	71.9	69.8	16 300*	73.9	68.8	12 600*	28.0
30.0	68.1	69.4	17 200 *	70.2	68.9	16 100*	72.1	68.0	12 200*	30.0
32.0	66.4	68.5	16 900 *	68.4	68.0	15 800*	70.4	67.0	11 800*	32.0
34.0	64.6	67.5	16 500	66.7	67.1	15 600*	68.6	66.1	11 400*	34.0
36.0	62.9	66.5	15 400	64.9	66.0	15 000*	66.8	65.0	11 100*	36.0
38.0	61.1	65.4	13 900	63.0	64.9	14 400*	64.9	63.9	10 700*	38.0
40.0	59.2	64.2	12 700	61.2	63.7	13 100	63.0	62.6	10 400*	40.0
44.0	55.4	61.5	10 500	57.4	61.0	10 900	59.1	59.9	9 900*	44.0
48.0	51.4	58.4	8 800	53.3	57.9	9 100	55.0	56.7	9 300	48.0
52.0	47.2	54.8	7 300	49.1	54.2	7 600	50.7	53.0	7 900	52.0
56.0	42.6	50.6	6 000	44.5	50.0	6 300	45.9	48.6	6 500	56.0
60.0	37.6	45.7	4 900	39.4	45.0	5 200				60.0
64.0	31.9	39.7	4 000	33.6	38.9	4 100				64.0
68.0	25.1	31.9	3 100							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
15.2	80.7	76.9	19 700 *							15.2
16.0	80.1	76.8	19 600 *							16.0
18.0	78.6	76.4	19 200 *							18.0
20.0	77.0	75.9	18 800 *	79.0	75.5	17 400*				20.0
22.0	75.4	75.4	18 500 *	77.4	74.9	17 200*	79.4	74.0	14 400*	22.0
24.0	73.9	74.8	18 200 *	75.8	74.3	16 900*	77.8	73.4	13 800*	24.0
26.0	72.3	74.1	17 900 *	74.2	73.7	16 600*	76.2	72.7	13 300*	26.0
28.0	70.7	73.4	17 600 *	72.6	73.0	16 400*	74.6	72.0	12 800*	28.0
30.0	69.0	72.6	17 300 *	71.0	72.2	16 100*	72.9	71.2	12 400*	30.0
32.0	67.4	71.8	17 000 *	69.3	71.3	15 900*	71.2	70.3	12 000*	32.0
34.0	65.7	70.9	16 600	67.7	70.4	15 700*	69.5	69.4	11 600*	34.0
36.0	64.0	69.9	15 100	66.0	69.4	15 300*	67.8	68.4	11 300*	36.0
38.0	62.3	68.8	13 700	64.2	68.3	14 200	66.1	67.3	10 900*	38.0
40.0	60.6	67.7	12 400	62.5	67.2	12 900	64.3	66.1	10 600*	40.0
44.0	57.0	65.2	10 300	58.9	64.6	10 800	60.6	63.5	10 100*	44.0
48.0	53.3	62.2	8 500	55.1	61.7	8 900	56.8	60.6	9 300	48.0
52.0	49.3	58.9	7 100	51.1	58.3	7 400	52.7	57.1	7 600	52.0
56.0	45.1	55.1	5 800	46.9	54.4	6 100	48.3	53.1	6 300	56.0
60.0	40.6	50.6	4 700	42.3	49.9	4 900				60.0
64.0	35.5	45.2	3 800	37.1	44.5	3 900				64.0
68.0	29.7	38.7	2 900							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	79.9	79.7	19 400 *							16.8
18.0	79.0	79.4	19 100 *							18.0
20.0	77.5	79.0	18 800 *	79.4	78.6	17 400 *				20.0
22.0	76.0	78.5	18 500 *	77.9	78.0	17 200 *	79.9	77.1	14 500 *	22.0
24.0	74.5	77.9	18 200 *	76.4	77.5	17 000 *	78.3	76.5	14 000 *	24.0
26.0	73.0	77.3	17 900 *	74.9	76.8	16 700 *	76.8	75.9	13 400 *	26.0
28.0	71.4	76.6	17 600 *	73.3	76.2	16 400 *	75.2	75.2	13 000 *	28.0
30.0	69.9	75.9	17 300 *	71.8	75.4	16 200 *	73.6	74.4	12 600 *	30.0
32.0	68.3	75.1	17 100 *	70.2	74.6	16 000 *	72.0	73.6	12 200 *	32.0
34.0	66.7	74.2	16 100	68.6	73.7	15 700 *	70.4	72.7	11 800 *	34.0
36.0	65.1	73.2	14 700	67.0	72.8	15 300	68.8	71.7	11 400 *	36.0
38.0	63.5	72.2	13 400	65.3	71.7	14 000	67.1	70.7	11 100 *	38.0
40.0	61.8	71.1	12 200	63.7	70.7	12 700	65.4	69.6	10 800 *	40.0
44.0	58.4	68.7	10 100	60.2	68.2	10 500	61.9	67.1	10 300 *	44.0
48.0	54.9	66.0	8 300	56.7	65.5	8 700	58.3	64.3	9 000	48.0
52.0	51.2	62.9	6 800	52.9	62.3	7 100	54.5	61.1	7 500	52.0
56.0	47.3	59.3	5 600	49.0	58.7	5 800	50.5	57.4	6 100	56.0
60.0	43.1	55.2	4 500	44.8	54.5	4 700	46.1	53.1	4 900	60.0
64.0	38.5	50.4	3 500	40.1	49.7	3 700				64.0
68.0	33.5	44.6	2 700	35.0	43.8	2 800				68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
16.8	80.3	82.8	19 300 *							16.8
18.0	79.4	82.5	19 100 *							18.0
20.0	78.0	82.1	18 800 *	79.8	81.6	17 400*				20.0
22.0	76.5	81.6	18 500 *	78.4	81.1	17 200*	80.3	80.2	14 700*	22.0
24.0	75.1	81.0	18 200 *	76.9	80.6	17 000*	78.8	79.6	14 100*	24.0
26.0	73.6	80.4	17 900 *	75.5	80.0	16 700*	77.3	79.0	13 600*	26.0
28.0	72.1	79.8	17 600 *	74.0	79.3	16 500*	75.8	78.4	13 200*	28.0
30.0	70.6	79.1	17 400 *	72.5	78.6	16 200*	74.3	77.6	12 700*	30.0
32.0	69.1	78.3	17 100 *	71.0	77.8	16 000*	72.7	76.8	12 300*	32.0
34.0	67.6	77.5	15 700	69.4	77.0	15 800	71.2	76.0	12 000*	34.0
36.0	66.1	76.6	14 300	67.9	76.1	15 000	69.6	75.1	11 600*	36.0
38.0	64.5	75.6	13 100	66.3	75.1	13 700	68.0	74.1	11 300*	38.0
40.0	63.0	74.6	11 900	64.7	74.1	12 500	66.4	73.0	11 000*	40.0
44.0	59.7	72.3	9 800	61.5	71.8	10 300	63.1	70.7	10 400*	44.0
48.0	56.4	69.7	8 100	58.1	69.2	8 500	59.7	68.0	8 900	48.0
52.0	52.9	66.7	6 600	54.6	66.2	6 900	56.1	65.0	7 300	52.0
56.0	49.2	63.4	5 300	50.9	62.8	5 600	52.3	61.6	5 900	56.0
60.0	45.3	59.6	4 200	47.0	58.9	4 500	48.3	57.6	4 700	60.0
64.0	41.2	55.1	3 300	42.7	54.5	3 500	44.0	53.0	3 700	64.0
68.0	36.6	50.0	2 400	38.1	49.3	2 600				68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

15.2m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	80.6	85.8	19 200 *							16.8
18.0	79.8	85.6	19 000 *							18.0
20.0	78.4	85.2	18 700 *	80.2	84.7	17 300*				20.0
22.0	77.0	84.7	18 400 *	78.8	84.2	17 100*				22.0
24.0	75.6	84.2	18 200 *	77.4	83.7	16 900*	79.2	82.7	14 300*	24.0
26.0	74.2	83.6	17 900 *	76.0	83.1	16 700*	77.8	82.2	13 800*	26.0
28.0	72.8	82.9	17 600 *	74.6	82.5	16 500*	76.3	81.5	13 300*	28.0
30.0	71.4	82.3	17 300 *	73.1	81.8	16 300*	74.9	80.8	12 900*	30.0
32.0	69.9	81.5	16 600	71.7	81.1	16 100*	73.4	80.1	12 500*	32.0
34.0	68.5	80.7	15 200	70.2	80.3	15 700	71.9	79.2	12 100*	34.0
36.0	67.0	79.9	13 800	68.7	79.4	14 500	70.4	78.4	11 800*	36.0
38.0	65.5	78.9	12 600	67.2	78.5	13 200	68.9	77.4	11 400*	38.0
40.0	64.0	77.9	11 500	65.7	77.5	12 000	67.3	76.4	11 100*	40.0
44.0	60.9	75.8	9 500	62.6	75.3	10 000	64.2	74.2	10 400	44.0
48.0	57.7	73.3	7 800	59.4	72.8	8 200	60.9	71.7	8 600	48.0
52.0	54.4	70.5	6 300	56.1	70.0	6 600	57.6	68.8	7 000	52.0
56.0	51.0	67.4	5 000	52.6	66.8	5 300	54.0	65.6	5 700	56.0
60.0	47.3	63.8	3 900	48.9	63.2	4 200	50.3	61.9	4 500	60.0
64.0	43.5	59.7	2 900	45.0	59.0	3 200	46.3	57.6	3 400	64.0
68.0	39.3	55.0	2 100	40.8	54.3	2 300				68.0
72.5m Boom										
16.8	81.0	88.9	19 100 *							16.8
18.0	80.1	88.6	19 000 *							18.0
20.0	78.8	88.2	18 700 *	80.6	87.8	17 300*				20.0
22.0	77.5	87.8	18 400 *	79.2	87.3	17 100*				22.0
24.0	76.1	87.3	18 100 *	77.9	86.8	16 900*	79.6	85.8	14 400*	24.0
26.0	74.8	86.7	17 900 *	76.5	86.3	16 700*	78.2	85.3	13 900*	26.0
28.0	73.4	86.1	17 600 *	75.1	85.6	16 500*	76.8	84.7	13 500*	28.0
30.0	72.0	85.4	17 300 *	73.7	85.0	16 300*	75.4	84.0	13 100*	30.0
32.0	70.6	84.7	16 200	72.3	84.3	16 100*	74.0	83.3	12 700*	32.0
34.0	69.2	84.0	14 700	70.9	83.5	15 500	72.6	82.5	12 300*	34.0
36.0	67.8	83.1	13 400	69.5	82.7	14 100	71.1	81.6	11 900*	36.0
38.0	66.4	82.2	12 200	68.1	81.8	12 800	69.7	80.7	11 600*	38.0
40.0	65.0	81.3	11 000	66.6	80.8	11 700	68.2	79.8	11 300*	40.0
44.0	62.0	79.2	9 200	63.7	78.7	9 700	65.2	77.6	10 200	44.0
48.0	59.0	76.9	7 500	60.6	76.3	8 000	62.1	75.2	8 400	48.0
52.0	55.8	74.2	6 000	57.4	73.7	6 400	58.9	72.5	6 800	52.0
56.0	52.6	71.2	4 800	54.2	70.7	5 100	55.6	69.5	5 400	56.0
60.0	49.2	67.9	3 700	50.7	67.3	4 000	52.0	66.0	4 200	60.0
64.0	45.5	64.0	2 700	47.1	63.4	3 000	48.3	62.1	3 200	64.0
68.0	41.7	59.7	1 900	43.2	59.0	2 100	44.3	57.6	2 300	68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
10.7	80.4	47.3	17 600 *							10.7
12.0	78.7	47.0	17 200 *							12.0
14.0	76.1	46.5	16 600 *	80.5	46.2	13 300*				14.0
16.0	73.5	45.9	15 900 *	77.9	45.6	13 300*				16.0
18.0	70.8	45.2	15 300 *	75.2	44.9	13 300*	79.3	44.1	12 200*	18.0
20.0	68.1	44.4	14 700 *	72.5	44.1	13 300*	76.5	43.2	11 400*	20.0
22.0	65.3	43.4	14 200 *	69.7	43.2	13 100*	73.7	42.3	10 600*	22.0
24.0	62.5	42.4	13 700 *	66.8	42.1	12 800*	70.8	41.2	10 000*	24.0
26.0	59.6	41.2	13 200 *	63.9	40.9	12 400*	67.8	40.0	9 500*	26.0
28.0	56.6	39.8	12 800 *	60.9	39.6	11 700*	64.7	38.6	8 900*	28.0
30.0	53.4	38.3	12 400 *	57.7	38.1	11 000*	61.4	37.1	8 500*	30.0
32.0	50.2	36.6	12 000 *	54.4	36.4	10 300*	58.0	35.3	8 100*	32.0
34.0	46.7	34.7	11 400 *	51.0	34.5	9 800*	54.4	33.4	7 800*	34.0
36.0	43.0	32.6	10 700 *	47.3	32.4	9 300*	50.6	31.2	7 400*	36.0
38.0	39.1	30.1	10 000 *	43.3	29.9	8 800*	46.4	28.6	7 200*	38.0
40.0	34.7	27.3	9 500 *	38.9	27.1	8 500*				40.0
44.0	23.8	19.5	8 600 *							44.0
30.5m Boom										
10.7	81.0	50.4	17 700 *							10.7
12.0	79.4	50.1	17 300 *							12.0
14.0	77.0	49.6	16 700 *							14.0
16.0	74.5	49.1	16 100 *	78.7	48.8	13 300*				16.0
18.0	72.1	48.4	15 500 *	76.2	48.1	13 300*				18.0
20.0	69.5	47.6	15 000 *	73.6	47.3	13 300*	77.5	46.4	11 700*	20.0
22.0	67.0	46.8	14 500 *	71.1	46.5	13 300*	74.8	45.6	10 900*	22.0
24.0	64.4	45.8	14 000 *	68.4	45.5	13 000*	72.1	44.6	10 300*	24.0
26.0	61.7	44.7	13 500 *	65.7	44.4	12 600*	69.4	43.5	9 700*	26.0
28.0	58.9	43.4	13 100 *	63.0	43.2	12 200*	66.5	42.2	9 200*	28.0
30.0	56.1	42.1	12 700 *	60.1	41.8	11 500*	63.6	40.8	8 800*	30.0
32.0	53.1	40.6	12 300 *	57.1	40.3	10 800*	60.6	39.3	8 400*	32.0
34.0	50.1	38.9	12 000 *	54.0	38.6	10 300*	57.4	37.5	8 000*	34.0
36.0	46.8	37.0	11 400 *	50.8	36.7	9 700*	54.0	35.6	7 700*	36.0
38.0	43.4	34.9	10 700 *	47.3	34.6	9 300*	50.4	33.4	7 400*	38.0
40.0	39.7	32.5	10 100 *	43.6	32.2	8 900*	46.5	30.9	7 200*	40.0
44.0	31.2	26.5	9 100 *	35.1	26.2	8 200*				44.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	79.8	53.1	17 400 *							12.2
14.0	77.7	52.7	16 800 *							14.0
16.0	75.5	52.2	16 300 *	79.4	51.9	13 300*				16.0
18.0	73.1	51.6	15 700 *	77.0	51.3	13 300*				18.0
20.0	70.8	50.8	15 200 *	74.7	50.5	13 300*	78.3	49.6	11 900*	20.0
22.0	68.4	50.0	14 700 *	72.2	49.7	13 300*	75.8	48.8	11 200*	22.0
24.0	66.0	49.1	14 200 *	69.8	48.8	13 100*	73.3	47.9	10 500*	24.0
26.0	63.5	48.1	13 800 *	67.3	47.8	12 800*	70.8	46.9	10 000*	26.0
28.0	60.9	47.0	13 400 *	64.7	46.7	12 500*	68.1	45.7	9 500*	28.0
30.0	58.3	45.7	13 000 *	62.1	45.5	12 000*	65.4	44.4	9 100*	30.0
32.0	55.6	44.3	12 600 *	59.4	44.1	11 300*	62.7	43.0	8 700*	32.0
34.0	52.8	42.8	12 200 *	56.6	42.5	10 800*	59.8	41.4	8 300*	34.0
36.0	49.9	41.1	11 900 *	53.7	40.8	10 200*	56.8	39.7	8 000*	36.0
38.0	46.9	39.2	11 400 *	50.6	39.0	9 700*	53.6	37.8	7 700*	38.0
40.0	43.7	37.1	10 800 *	47.4	36.9	9 300*	50.3	35.6	7 400*	40.0
44.0	36.6	32.1	9 700 *	40.2	31.8	8 600*	42.7	30.3	7 000*	44.0
48.0	27.8	25.3	8 800 *							48.0
36.5m Boom										
12.2	80.4	56.2	17 500 *							12.2
14.0	78.4	55.8	17 000 *							14.0
16.0	76.3	55.3	16 500 *	80.0	55.0	13 300*				16.0
18.0	74.1	54.7	16 000 *	77.8	54.4	13 300*				18.0
20.0	71.9	54.0	15 400 *	75.5	53.7	13 300*	79.0	52.8	12 100*	20.0
22.0	69.6	53.3	14 900 *	73.3	53.0	13 300*	76.7	52.0	11 400*	22.0
24.0	67.4	52.4	14 500 *	71.0	52.1	13 200*	74.3	51.2	10 800*	24.0
26.0	65.1	51.5	14 000 *	68.7	51.2	13 000*	71.9	50.2	10 200*	26.0
28.0	62.7	50.4	13 600 *	66.3	50.1	12 700*	69.5	49.1	9 700*	28.0
30.0	60.3	49.3	13 200 *	63.9	49.0	12 400*	67.0	47.9	9 300*	30.0
32.0	57.8	48.0	12 900 *	61.4	47.7	11 800*	64.5	46.6	8 900*	32.0
34.0	55.2	46.6	12 600 *	58.8	46.3	11 200*	61.8	45.2	8 500*	34.0
36.0	52.6	45.0	12 200 *	56.1	44.8	10 600*	59.1	43.6	8 200*	36.0
38.0	49.8	43.3	11 900 *	53.4	43.1	10 100*	56.3	41.9	7 900*	38.0
40.0	47.0	41.5	11 400 *	50.5	41.2	9 700*	53.3	39.9	7 700*	40.0
44.0	40.7	37.1	10 300 *	44.2	36.8	8 900*	46.8	35.4	7 200*	44.0
48.0	33.5	31.5	9 400 *	36.9	31.2	8 300*				48.0
52.0	24.4	23.7	8 600 *							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
12.2	80.9	59.3	17 500 *							12.2
14.0	79.0	58.9	17 000 *							14.0
16.0	77.0	58.4	16 600 *							16.0
18.0	74.9	57.9	16 100 *	78.4	57.5	13 300*				18.0
20.0	72.9	57.2	15 600 *	76.3	56.9	13 300*	79.6	55.9	12 300*	20.0
22.0	70.8	56.5	15 100 *	74.2	56.2	13 300*	77.4	55.2	11 700*	22.0
24.0	68.6	55.7	14 600 *	72.1	55.4	13 300*	75.2	54.4	11 000*	24.0
26.0	66.5	54.8	14 200 *	69.9	54.5	13 100*	73.0	53.5	10 500*	26.0
28.0	64.2	53.8	13 900 *	67.7	53.5	12 800*	70.7	52.5	10 000*	28.0
30.0	62.0	52.7	13 500 *	65.4	52.4	12 500*	68.4	51.4	9 500*	30.0
32.0	59.7	51.6	13 100 *	63.1	51.3	12 300*	66.0	50.2	9 200*	32.0
34.0	57.3	50.3	12 800 *	60.7	50.0	11 600*	63.6	48.9	8 800*	34.0
36.0	54.9	48.8	12 500 *	58.2	48.5	11 100*	61.1	47.4	8 400*	36.0
38.0	52.4	47.3	12 200 *	55.7	47.0	10 600*	58.5	45.8	8 100*	38.0
40.0	49.8	45.6	11 900 *	53.1	45.3	10 100*	55.8	44.1	7 900*	40.0
44.0	44.2	41.6	10 800 *	47.5	41.4	9 300*	50.0	40.0	7 400*	44.0
48.0	38.0	36.8	9 900 *	41.2	36.5	8 600*	43.5	35.0	7 000*	48.0
52.0	30.6	30.6	9 000	33.8	30.3	8 100*				52.0
42.5m Boom										
13.7	79.9	62.0	17 200 *							13.7
14.0	79.6	62.0	17 100 *							14.0
16.0	77.7	61.5	16 600 *							16.0
18.0	75.7	61.0	16 200 *	79.0	60.6	13 300*				18.0
20.0	73.7	60.4	15 700 *	77.0	60.0	13 300*	80.1	59.1	12 500*	20.0
22.0	71.8	59.7	15 300 *	75.0	59.4	13 300*	78.1	58.4	11 800*	22.0
24.0	69.7	58.9	14 900 *	73.0	58.6	13 300*	76.0	57.6	11 200*	24.0
26.0	67.7	58.1	14 400 *	71.0	57.8	13 200*	73.9	56.8	10 700*	26.0
28.0	65.6	57.2	14 000 *	68.9	56.9	12 900*	71.8	55.8	10 200*	28.0
30.0	63.5	56.2	13 700 *	66.7	55.9	12 700*	69.6	54.8	9 800*	30.0
32.0	61.3	55.1	13 300 *	64.6	54.7	12 400*	67.4	53.7	9 400*	32.0
34.0	59.1	53.8	13 000 *	62.3	53.5	12 100*	65.1	52.4	9 000*	34.0
36.0	56.9	52.5	12 700 *	60.1	52.2	11 500*	62.8	51.1	8 700*	36.0
38.0	54.6	51.1	12 400 *	57.7	50.8	11 000*	60.4	49.6	8 400*	38.0
40.0	52.2	49.5	12 100 *	55.3	49.2	10 500*	58.0	48.0	8 100*	40.0
44.0	47.1	45.9	11 400 *	50.2	45.6	9 700*	52.7	44.3	7 600*	44.0
48.0	41.6	41.6	10 300	44.6	41.3	9 000*	46.9	39.9	7 200*	48.0
52.0	35.3	36.3	8 800	38.3	36.0	8 400*				52.0
56.0	27.8	29.4	7 500							56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	80.4	65.1	17 200 *							13.7
14.0	80.1	65.0	17 100 *							14.0
16.0	78.3	64.6	16 700 *							16.0
18.0	76.4	64.1	16 300 *	79.6	63.7	13 300*				18.0
20.0	74.5	63.5	15 900 *	77.7	63.2	13 300*	80.6	62.2	12 700*	20.0
22.0	72.6	62.9	15 400 *	75.8	62.5	13 300*	78.7	61.5	12 000*	22.0
24.0	70.7	62.2	15 000 *	73.9	61.8	13 300*	76.7	60.8	11 400*	24.0
26.0	68.8	61.4	14 600 *	71.9	61.0	13 300*	74.8	60.0	10 900*	26.0
28.0	66.8	60.5	14 200 *	69.9	60.2	13 100*	72.7	59.1	10 400*	28.0
30.0	64.9	59.5	13 900 *	67.9	59.2	12 800*	70.7	58.2	10 000*	30.0
32.0	62.8	58.5	13 500 *	65.9	58.2	12 600*	68.6	57.1	9 600*	32.0
34.0	60.8	57.4	13 200 *	63.8	57.0	12 300*	66.5	55.9	9 200*	34.0
36.0	58.6	56.1	12 900 *	61.7	55.8	11 900*	64.3	54.7	8 900*	36.0
38.0	56.5	54.8	12 600 *	59.5	54.5	11 400*	62.1	53.3	8 600*	38.0
40.0	54.3	53.3	12 300 *	57.3	53.0	10 900*	59.8	51.8	8 300*	40.0
44.0	49.6	50.0	11 700	52.6	49.7	10 000*	55.0	48.5	7 800*	44.0
48.0	44.6	46.1	9 900	47.5	45.8	9 300*	49.8	44.4	7 400*	48.0
52.0	39.0	41.5	8 500	42.0	41.1	8 700	44.0	39.6	7 100*	52.0
56.0	32.7	35.6	7 200	35.6	35.3	7 400				56.0
60.0	24.9	27.9	6 100							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
13.7	80.8	68.1	17 200 *							13.7
14.0	80.5	68.1	17 200 *							14.0
16.0	78.8	67.7	16 800 *							16.0
18.0	77.0	67.2	16 300 *							18.0
20.0	75.2	66.6	16 000 *	78.3	66.3	13 300*				20.0
22.0	73.5	66.0	15 600 *	76.4	65.7	13 300*	79.2	64.7	12 200*	22.0
24.0	71.6	65.4	15 100 *	74.6	65.0	13 300*	77.4	64.0	11 600*	24.0
26.0	69.8	64.6	14 800 *	72.8	64.3	13 300*	75.5	63.2	11 100*	26.0
28.0	68.0	63.8	14 400 *	70.9	63.4	13 200*	73.6	62.4	10 600*	28.0
30.0	66.1	62.9	14 100 *	69.0	62.5	12 900*	71.7	61.5	10 200*	30.0
32.0	64.2	61.9	13 700 *	67.1	61.6	12 700*	69.7	60.5	9 800*	32.0
34.0	62.2	60.8	13 400 *	65.1	60.5	12 500*	67.7	59.4	9 400*	34.0
36.0	60.2	59.7	13 100 *	63.1	59.3	12 200*	65.7	58.2	9 100*	36.0
38.0	58.2	58.4	12 800 *	61.1	58.1	11 800*	63.6	56.9	8 800*	38.0
40.0	56.1	57.1	12 600 *	59.0	56.7	11 200*	61.5	55.5	8 500*	40.0
44.0	51.8	54.0	11 500	54.7	53.7	10 400*	57.0	52.4	8 000*	44.0
48.0	47.2	50.4	9 700	50.0	50.1	9 700*	52.3	48.8	7 600*	48.0
52.0	42.2	46.2	8 200	45.0	45.9	8 600	47.1	44.4	7 200*	52.0
56.0	36.6	41.1	7 000	39.4	40.7	7 200				56.0
60.0	30.2	34.7	5 900	32.9	34.3	6 100				60.0
64.0	22.0	26.0	4 900							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	79.9	70.9	16 900 *							15.2
16.0	79.3	70.7	16 800 *							16.0
18.0	77.6	70.3	16 400 *							18.0
20.0	75.9	69.8	16 000 *	78.8	69.4	13 300*				20.0
22.0	74.2	69.2	15 700 *	77.1	68.8	13 300*	79.7	67.8	12 400*	22.0
24.0	72.5	68.5	15 300 *	75.3	68.2	13 300*	78.0	67.1	11 800*	24.0
26.0	70.7	67.8	14 900 *	73.6	67.5	13 300*	76.2	66.4	11 300*	26.0
28.0	69.0	67.0	14 500 *	71.8	66.7	13 300*	74.4	65.6	10 800*	28.0
30.0	67.2	66.2	14 200 *	70.0	65.8	13 000*	72.5	64.8	10 400*	30.0
32.0	65.4	65.2	13 900 *	68.2	64.9	12 800*	70.7	63.8	10 000*	32.0
34.0	63.5	64.2	13 500 *	66.3	63.9	12 500*	68.8	62.8	9 600*	34.0
36.0	61.6	63.1	13 300 *	64.4	62.8	12 300*	66.9	61.7	9 300*	36.0
38.0	59.7	62.0	13 000 *	62.5	61.6	12 100*	64.9	60.5	9 000*	38.0
40.0	57.8	60.7	12 700 *	60.6	60.3	11 600*	62.9	59.2	8 700*	40.0
44.0	53.8	57.8	11 200	56.5	57.5	10 700*	58.8	56.3	8 200*	44.0
48.0	49.5	54.5	9 500	52.2	54.2	9 900	54.4	52.9	7 800*	48.0
52.0	44.9	50.6	8 000	47.6	50.3	8 400	49.7	48.9	7 400*	52.0
56.0	39.9	46.1	6 700	42.6	45.7	7 000	44.5	44.1	7 100*	56.0
60.0	34.3	40.5	5 700	36.9	40.2	5 900				60.0
64.0	27.7	33.5	4 700							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.3	73.9	16 900 *							15.2
16.0	79.7	73.8	16 800 *							16.0
18.0	78.1	73.4	16 400 *							18.0
20.0	76.5	72.9	16 100 *	79.3	72.5	13 300*				20.0
22.0	74.9	72.3	15 700 *	77.6	71.9	13 300*	80.2	70.9	12 500*	22.0
24.0	73.2	71.7	15 400 *	76.0	71.3	13 300*	78.5	70.3	12 000*	24.0
26.0	71.5	71.0	15 000 *	74.3	70.6	13 300*	76.8	69.6	11 400*	26.0
28.0	69.9	70.3	14 600 *	72.6	69.9	13 300*	75.1	68.8	11 000*	28.0
30.0	68.2	69.4	14 300 *	70.9	69.1	13 100*	73.3	68.0	10 600*	30.0
32.0	66.4	68.6	14 000 *	69.1	68.2	12 900*	71.6	67.1	10 200*	32.0
34.0	64.7	67.6	13 700 *	67.4	67.3	12 600*	69.8	66.1	9 800*	34.0
36.0	62.9	66.6	13 400 *	65.6	66.2	12 500*	68.0	65.1	9 500*	36.0
38.0	61.1	65.4	13 200 *	63.8	65.1	12 200*	66.1	64.0	9 200*	38.0
40.0	59.3	64.2	12 800	61.9	63.9	12 000*	64.2	62.7	8 900*	40.0
44.0	55.5	61.6	11 000	58.1	61.2	11 100*	60.4	60.0	8 400*	44.0
48.0	51.5	58.5	9 300	54.1	58.1	9 700	56.3	56.8	7 900*	48.0
52.0	47.3	54.9	7 800	49.9	54.6	8 200	51.9	53.2	7 600*	52.0
56.0	42.7	50.7	6 500	45.3	50.4	6 900	47.2	48.9	7 100	56.0
60.0	37.7	45.8	5 400	40.3	45.4	5 700				60.0
64.0	32.0	39.8	4 500	34.5	39.4	4 700				64.0
68.0	25.2	32.1	3 600							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
15.2	80.7	77.0	16 900 *							15.2
16.0	80.1	76.9	16 700 *							16.0
18.0	78.6	76.4	16 400 *							18.0
20.0	77.0	76.0	16 100 *	79.7	75.6	13 300 *				20.0
22.0	75.5	75.4	15 800 *	78.1	75.0	13 300 *				22.0
24.0	73.9	74.8	15 400 *	76.5	74.5	13 300 *	79.0	73.4	12 100 *	24.0
26.0	72.3	74.2	15 100 *	74.9	73.8	13 300 *	77.3	72.8	11 600 *	26.0
28.0	70.7	73.5	14 700 *	73.3	73.1	13 300 *	75.7	72.0	11 200 *	28.0
30.0	69.1	72.7	14 400 *	71.7	72.3	13 200 *	74.1	71.2	10 700 *	30.0
32.0	67.4	71.9	14 100 *	70.0	71.5	13 000 *	72.4	70.4	10 300 *	32.0
34.0	65.8	70.9	13 800 *	68.4	70.6	12 700 *	70.7	69.5	10 000 *	34.0
36.0	64.1	70.0	13 600 *	66.7	69.6	12 500 *	69.0	68.5	9 600 *	36.0
38.0	62.4	68.9	13 300 *	65.0	68.5	12 300 *	67.2	67.4	9 400 *	38.0
40.0	60.6	67.8	12 900	63.2	67.4	12 200 *	65.4	66.2	9 100 *	40.0
44.0	57.1	65.2	10 700	59.6	64.9	11 200	61.8	63.7	8 500 *	44.0
48.0	53.3	62.3	8 900	55.8	62.0	9 400	57.9	60.7	8 100 *	48.0
52.0	49.4	59.0	7 500	51.9	58.6	7 900	53.9	57.3	7 700 *	52.0
56.0	45.2	55.1	6 200	47.7	54.8	6 600	49.5	53.3	6 900	56.0
60.0	40.6	50.7	5 100	43.1	50.3	5 400	44.8	48.7	5 600	60.0
64.0	35.6	45.3	4 200	38.0	45.0	4 400				64.0
68.0	29.8	38.8	3 300	32.2	38.4	3 500				68.0
72.0	22.7	30.3	2 600							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.0	79.8	16 600 *							16.8
18.0	79.0	79.5	16 400 *							18.0
20.0	77.5	79.1	16 100 *	80.1	78.7	13 300*				20.0
22.0	76.0	78.5	15 800 *	78.6	78.1	13 300*				22.0
24.0	74.5	78.0	15 500 *	77.1	77.6	13 300*	79.4	76.5	12 300*	24.0
26.0	73.0	77.3	15 200 *	75.5	77.0	13 300*	77.9	75.9	11 800*	26.0
28.0	71.5	76.7	14 800 *	74.0	76.3	13 300*	76.3	75.2	11 300*	28.0
30.0	69.9	75.9	14 500 *	72.4	75.5	13 200*	74.7	74.5	10 900*	30.0
32.0	68.3	75.1	14 200 *	70.9	74.7	13 000*	73.1	73.6	10 500*	32.0
34.0	66.8	74.2	13 900 *	69.3	73.9	12 800*	71.5	72.8	10 200*	34.0
36.0	65.2	73.3	13 700 *	67.6	72.9	12 600*	69.8	71.8	9 800*	36.0
38.0	63.5	72.3	13 400 *	66.0	71.9	12 400*	68.2	70.8	9 500*	38.0
40.0	61.9	71.2	12 600	64.3	70.9	12 300*	66.5	69.7	9 200*	40.0
44.0	58.5	68.8	10 500	60.9	68.5	11 100	63.0	67.3	8 700*	44.0
48.0	55.0	66.1	8 700	57.4	65.7	9 200	59.4	64.5	8 300*	48.0
52.0	51.3	62.9	7 200	53.7	62.6	7 700	55.6	61.3	7 900	52.0
56.0	47.4	59.4	6 000	49.7	59.0	6 400	51.6	57.6	6 600	56.0
60.0	43.2	55.3	4 900	45.5	54.9	5 200	47.3	53.4	5 500	60.0
64.0	38.6	50.4	3 900	41.0	50.1	4 200	42.5	48.4	4 400	64.0
68.0	33.5	44.7	3 100	35.8	44.3	3 300				68.0
72.0	27.6	37.7	2 300							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.3	82.8	16 600 *							16.8
18.0	79.4	82.6	16 400 *							18.0
20.0	78.0	82.1	16 100 *	80.5	81.7	13 300*				20.0
22.0	76.6	81.6	15 800 *	79.0	81.2	13 300*				22.0
24.0	75.1	81.1	15 500 *	77.6	80.7	13 300*	79.8	79.6	12 400*	24.0
26.0	73.7	80.5	15 200 *	76.1	80.1	13 300*	78.3	79.0	11 900*	26.0
28.0	72.2	79.8	14 900 *	74.6	79.5	13 300*	76.8	78.4	11 500*	28.0
30.0	70.7	79.1	14 600 *	73.1	78.7	13 200*	75.3	77.7	11 000*	30.0
32.0	69.2	78.4	14 300 *	71.6	78.0	13 100*	73.8	76.9	10 700*	32.0
34.0	67.7	77.5	14 000 *	70.1	77.1	12 900*	72.2	76.0	10 300*	34.0
36.0	66.1	76.6	13 800 *	68.5	76.3	12 700*	70.7	75.1	10 000*	36.0
38.0	64.6	75.7	13 500	67.0	75.3	12 500*	69.1	74.1	9 700*	38.0
40.0	63.0	74.6	12 400	65.4	74.3	12 300*	67.5	73.1	9 400*	40.0
44.0	59.8	72.3	10 200	62.1	72.0	10 800	64.2	70.8	8 900*	44.0
48.0	56.4	69.8	8 500	58.8	69.4	9 000	60.7	68.1	8 400*	48.0
52.0	52.9	66.8	7 000	55.3	66.4	7 500	57.2	65.1	7 900	52.0
56.0	49.3	63.5	5 700	51.6	63.1	6 100	53.4	61.7	6 500	56.0
60.0	45.4	59.6	4 700	47.7	59.3	5 000	49.4	57.8	5 300	60.0
64.0	41.2	55.2	3 700	43.5	54.9	4 000	45.1	53.3	4 200	64.0
68.0	36.7	50.1	2 900	38.9	49.7	3 100				68.0
72.0	31.5	43.9	2 100	33.7	43.5	2 300				72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
16.8	80.7	85.9	16 500 *							16.8
18.0	79.8	85.6	16 300 *							18.0
20.0	78.4	85.2	16 000 *	80.8	84.8	13 300*				20.0
22.0	77.1	84.7	15 700 *	79.4	84.3	13 300*				22.0
24.0	75.7	84.2	15 500 *	78.0	83.8	13 300*	80.2	82.7	12 600*	24.0
26.0	74.3	83.6	15 200 *	76.6	83.2	13 300*	78.8	82.2	12 000*	26.0
28.0	72.8	83.0	14 900 *	75.2	82.6	13 300*	77.3	81.5	11 600*	28.0
30.0	71.4	82.3	14 700 *	73.7	81.9	13 200*	75.9	80.8	11 200*	30.0
32.0	70.0	81.6	14 400 *	72.3	81.2	13 100*	74.4	80.1	10 800*	32.0
34.0	68.5	80.8	14 100 *	70.8	80.4	12 900*	72.9	79.3	10 400*	34.0
36.0	67.0	79.9	13 900 *	69.4	79.5	12 700*	71.4	78.4	10 100*	36.0
38.0	65.5	79.0	13 100	67.9	78.6	12 600*	69.9	77.5	9 800*	38.0
40.0	64.0	78.0	12 000	66.3	77.6	12 400	68.4	76.5	9 500*	40.0
44.0	61.0	75.8	10 000	63.2	75.5	10 600	65.2	74.3	9 000*	44.0
48.0	57.8	73.4	8 200	60.1	73.0	8 800	62.0	71.8	8 600*	48.0
52.0	54.5	70.6	6 700	56.7	70.2	7 200	58.6	68.9	7 700	52.0
56.0	51.0	67.4	5 500	53.3	67.1	5 900	55.1	65.7	6 300	56.0
60.0	47.4	63.8	4 400	49.6	63.5	4 800	51.3	62.0	5 100	60.0
64.0	43.6	59.8	3 400	45.7	59.4	3 800	47.3	57.9	4 000	64.0
68.0	39.4	55.1	2 600	41.5	54.7	2 900	43.0	53.0	3 100	68.0
72.0				36.9	49.2	2 100				72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

18.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
16.8	81.0	88.9	16 400 *							16.8
18.0	80.2	88.7	16 200 *							18.0
20.0	78.8	88.3	16 000 *							20.0
22.0	77.5	87.8	15 700 *	79.8	87.4	13 300*				22.0
24.0	76.2	87.3	15 500 *	78.4	86.9	13 300*				24.0
26.0	74.8	86.8	15 200 *	77.1	86.4	13 300*	79.2	85.3	12 200*	26.0
28.0	73.4	86.2	14 900 *	75.7	85.8	13 300*	77.8	84.7	11 800*	28.0
30.0	72.1	85.5	14 700 *	74.3	85.1	13 200*	76.4	84.0	11 300*	30.0
32.0	70.7	84.8	14 500 *	72.9	84.4	13 100*	75.0	83.3	11 000*	32.0
34.0	69.3	84.0	14 200 *	71.5	83.6	12 900*	73.5	82.5	10 600*	34.0
36.0	67.9	83.2	13 700	70.1	82.8	12 800*	72.1	81.7	10 300*	36.0
38.0	66.4	82.3	12 600	68.7	81.9	12 600*	70.7	80.8	10 000*	38.0
40.0	65.0	81.4	11 500	67.2	81.0	12 300	69.2	79.8	9 700*	40.0
44.0	62.1	79.3	9 600	64.3	78.9	10 300	66.2	77.7	9 200*	44.0
48.0	59.0	76.9	7 900	61.2	76.6	8 500	63.1	75.3	8 700*	48.0
52.0	55.9	74.3	6 400	58.1	73.9	7 000	59.9	72.6	7 400	52.0
56.0	52.6	71.3	5 200	54.8	70.9	5 600	56.5	69.6	6 000	56.0
60.0	49.2	67.9	4 100	51.4	67.6	4 500	53.0	66.2	4 800	60.0
64.0	45.6	64.1	3 100	47.7	63.7	3 500	49.3	62.2	3 800	64.0
68.0	41.8	59.8	2 300	43.9	59.4	2 600	45.3	57.8	2 800	68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
12.2	79.3	50.2	13 300 *							12.2
14.0	77.1	49.8	13 100 *							14.0
16.0	74.7	49.2	12 700 *	79.1	48.9	12 200*				16.0
18.0	72.2	48.6	12 400 *	76.6	48.2	11 800*				18.0
20.0	69.7	47.8	12 000 *	74.1	47.4	11 400*	78.7	46.6	10 200*	20.0
22.0	67.1	46.9	11 700 *	71.5	46.6	11 100*	76.0	45.7	9 500*	22.0
24.0	64.5	46.0	11 300 *	68.9	45.6	10 700*	73.4	44.7	8 900*	24.0
26.0	61.9	44.9	10 900 *	66.2	44.5	10 400*	70.6	43.6	8 400*	26.0
28.0	59.1	43.7	10 600 *	63.5	43.3	10 100*	67.8	42.3	7 900*	28.0
30.0	56.3	42.4	10 200 *	60.6	41.9	9 800*	64.9	40.9	7 500*	30.0
32.0	53.4	40.9	9 900 *	57.6	40.4	9 200*	61.8	39.4	7 100*	32.0
34.0	50.3	39.2	9 600 *	54.6	38.8	8 700*	58.6	37.6	6 800*	34.0
36.0	47.1	37.4	9 300 *	51.3	36.9	8 200*	55.3	35.7	6 500*	36.0
38.0	43.7	35.3	9 000 *	47.9	34.8	7 800*	51.7	33.5	6 200*	38.0
40.0	40.1	32.9	8 800 *	44.2	32.4	7 400*	47.9	31.0	5 900*	40.0
44.0	31.8	27.1	7 800 *	35.7	26.4	6 800*				44.0
30.5m Boom										
12.2	79.9	53.3	13 300 *							12.2
14.0	77.9	52.9	13 200 *							14.0
16.0	75.6	52.3	12 800 *	79.8	52.0	12 300*				16.0
18.0	73.3	51.7	12 500 *	77.5	51.4	11 900*				18.0
20.0	70.9	51.0	12 100 *	75.1	50.6	11 500*	79.4	49.7	10 500*	20.0
22.0	68.6	50.2	11 800 *	72.7	49.8	11 200*	76.9	48.9	9 800*	22.0
24.0	66.1	49.3	11 400 *	70.3	48.9	10 900*	74.4	48.0	9 100*	24.0
26.0	63.7	48.3	11 100 *	67.8	47.9	10 600*	71.9	47.0	8 600*	26.0
28.0	61.1	47.2	10 800 *	65.2	46.8	10 300*	69.3	45.8	8 100*	28.0
30.0	58.5	46.0	10 500 *	62.6	45.6	10 000*	66.6	44.5	7 700*	30.0
32.0	55.9	44.6	10 200 *	59.9	44.2	9 700*	63.8	43.1	7 300*	32.0
34.0	53.1	43.1	9 900 *	57.1	42.7	9 100*	61.0	41.6	7 000*	34.0
36.0	50.2	41.4	9 600 *	54.2	41.0	8 600*	58.0	39.8	6 700*	36.0
38.0	47.2	39.6	9 300 *	51.1	39.1	8 200*	54.8	37.9	6 400*	38.0
40.0	44.0	37.5	9 100 *	47.9	37.0	7 800*	51.5	35.7	6 200*	40.0
44.0	37.0	32.6	8 400 *	40.7	32.0	7 100*	44.0	30.5	5 800*	44.0
48.0	28.5	26.0	7 600 *	32.0	25.2	6 600*				48.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	80.5	56.3	13 300 *							12.2
14.0	78.5	55.9	13 200 *							14.0
16.0	76.4	55.5	12 800 *							16.0
18.0	74.2	54.9	12 500 *	78.2	54.5	12 000*				18.0
20.0	72.0	54.2	12 200 *	76.0	53.8	11 700*	80.0	52.9	10 600*	20.0
22.0	69.8	53.5	11 900 *	73.7	53.1	11 300*	77.7	52.1	9 900*	22.0
24.0	67.5	52.6	11 500 *	71.4	52.2	11 000*	75.4	51.2	9 400*	24.0
26.0	65.2	51.7	11 200 *	69.1	51.3	10 700*	73.0	50.3	8 800*	26.0
28.0	62.9	50.7	10 900 *	66.7	50.2	10 400*	70.6	49.2	8 400*	28.0
30.0	60.5	49.5	10 600 *	64.3	49.1	10 200*	68.1	48.0	7 900*	30.0
32.0	58.0	48.3	10 300 *	61.8	47.8	9 900*	65.6	46.7	7 600*	32.0
34.0	55.4	46.9	10 100 *	59.2	46.4	9 500*	62.9	45.3	7 200*	34.0
36.0	52.8	45.4	9 800 *	56.6	44.9	9 000*	60.2	43.7	6 900*	36.0
38.0	50.1	43.7	9 500 *	53.8	43.2	8 500*	57.4	42.0	6 600*	38.0
40.0	47.2	41.8	9 300 *	50.9	41.3	8 200*	54.4	40.1	6 400*	40.0
44.0	41.1	37.5	8 800 *	44.7	36.9	7 500*	47.9	35.5	6 000*	44.0
48.0	34.0	32.0	8 100 *	37.5	31.3	6 900*				48.0
52.0	25.1	24.6	7 400 *							52.0
36.5m Boom										
12.2	81.0	59.4	13 300 *							12.2
14.0	79.2	59.0	13 200 *							14.0
16.0	77.1	58.6	12 800 *							16.0
18.0	75.1	58.0	12 500 *	78.8	57.6	12 100*				18.0
20.0	73.0	57.4	12 200 *	76.7	57.0	11 800*	80.6	56.0	10 800*	20.0
22.0	70.9	56.7	12 000 *	74.6	56.3	11 400*	78.4	55.3	10 100*	22.0
24.0	68.8	55.9	11 600 *	72.5	55.5	11 100*	76.2	54.5	9 600*	24.0
26.0	66.6	55.0	11 300 *	70.3	54.6	10 900*	74.0	53.6	9 000*	26.0
28.0	64.4	54.0	11 000 *	68.1	53.6	10 600*	71.7	52.6	8 600*	28.0
30.0	62.1	53.0	10 800 *	65.8	52.5	10 300*	69.4	51.5	8 200*	30.0
32.0	59.9	51.8	10 500 *	63.5	51.4	10 100*	67.1	50.3	7 800*	32.0
34.0	57.5	50.5	10 200 *	61.1	50.1	9 800*	64.6	49.0	7 400*	34.0
36.0	55.1	49.1	10 000 *	58.7	48.7	9 400*	62.1	47.5	7 200*	36.0
38.0	52.6	47.6	9 800 *	56.1	47.1	8 900*	59.5	45.9	6 900*	38.0
40.0	50.0	45.9	9 500 *	53.5	45.4	8 500*	56.8	44.2	6 600*	40.0
44.0	44.5	42.0	9 000 *	47.9	41.5	7 800*	51.1	40.1	6 100*	44.0
48.0	38.3	37.3	8 600 *	41.7	36.6	7 200*	44.6	35.1	5 800*	48.0
52.0	31.1	31.2	7 800 *	34.3	30.4	6 700*				52.0
56.0	21.8	22.7	7 100 *							56.0



Liftcrane Jib Capacities

**Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating**


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
13.7	80.0	62.1	13 200 *							13.7
14.0	79.7	62.1	13 200 *							14.0
16.0	77.8	61.6	12 800 *							16.0
18.0	75.8	61.1	12 500 *	79.4	60.7	12 100*				18.0
20.0	73.9	60.5	12 300 *	77.4	60.1	11 800*				20.0
22.0	71.9	59.9	12 000 *	75.4	59.5	11 500*	79.0	58.4	10 300*	22.0
24.0	69.9	59.1	11 700 *	73.4	58.7	11 300*	77.0	57.7	9 800*	24.0
26.0	67.8	58.3	11 400 *	71.3	57.9	11 000*	74.9	56.8	9 200*	26.0
28.0	65.8	57.4	11 100 *	69.2	57.0	10 700*	72.8	55.9	8 800*	28.0
30.0	63.6	56.4	10 800 *	67.1	55.9	10 500*	70.6	54.9	8 400*	30.0
32.0	61.5	55.3	10 600 *	65.0	54.8	10 200*	68.4	53.7	8 000*	32.0
34.0	59.3	54.1	10 300 *	62.7	53.6	10 000*	66.1	52.5	7 600*	34.0
36.0	57.1	52.8	10 100 *	60.5	52.3	9 700*	63.8	51.2	7 300*	36.0
38.0	54.7	51.4	9 900 *	58.1	50.9	9 300*	61.4	49.7	7 000*	38.0
40.0	52.4	49.8	9 700 *	55.7	49.3	8 900*	58.9	48.1	6 800*	40.0
44.0	47.3	46.3	9 200 *	50.7	45.8	8 100*	53.7	44.4	6 300*	44.0
48.0	41.9	42.1	8 800 *	45.1	41.5	7 500*	47.9	40.0	6 000*	48.0
52.0	35.7	36.9	8 200 *	38.8	36.2	7 000*				52.0
56.0	28.3	30.1	7 600 *	31.2	29.2	6 500*				56.0
42.5m Boom										
13.7	80.4	65.2	13 100 *							13.7
14.0	80.2	65.1	13 100 *							14.0
16.0	78.4	64.7	12 800 *							16.0
18.0	76.5	64.2	12 500 *							18.0
20.0	74.6	63.7	12 300 *	78.0	63.3	11 900*				20.0
22.0	72.8	63.0	12 000 *	76.1	62.6	11 600*	79.6	61.6	10 500*	22.0
24.0	70.9	62.3	11 800 *	74.2	61.9	11 300*	77.6	60.9	9 900*	24.0
26.0	68.9	61.6	11 500 *	72.3	61.1	11 100*	75.7	60.1	9 400*	26.0
28.0	67.0	60.7	11 200 *	70.3	60.3	10 800*	73.7	59.2	9 000*	28.0
30.0	65.0	59.8	10 900 *	68.3	59.3	10 600*	71.6	58.2	8 600*	30.0
32.0	63.0	58.7	10 700 *	66.3	58.3	10 400*	69.5	57.2	8 200*	32.0
34.0	60.9	57.6	10 400 *	64.2	57.1	10 100*	67.4	56.0	7 900*	34.0
36.0	58.8	56.4	10 200 *	62.1	55.9	9 900*	65.3	54.8	7 500*	36.0
38.0	56.7	55.1	10 000 *	59.9	54.6	9 700*	63.0	53.4	7 300*	38.0
40.0	54.4	53.6	9 800 *	57.7	53.1	9 200*	60.8	51.9	7 000*	40.0
44.0	49.8	50.4	9 400 *	53.0	49.8	8 400*	56.0	48.5	6 500*	44.0
48.0	44.8	46.5	9 000 *	48.0	46.0	7 800*	50.8	44.5	6 100*	48.0
52.0	39.4	41.9	8 600 *	42.4	41.3	7 200*	45.0	39.7	5 800*	52.0
56.0	33.1	36.2	7 700	36.0	35.4	6 800*				56.0
60.0	25.5	28.7	6 600							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	80.9	68.2	13 100 *							13.7
14.0	80.6	68.2	13 100 *							14.0
16.0	78.9	67.8	12 800 *							16.0
18.0	77.1	67.3	12 500 *							18.0
20.0	75.3	66.8	12 300 *	78.6	66.4	12 000 *				20.0
22.0	73.6	66.2	12 000 *	76.8	65.8	11 700 *	80.1	64.7	10 600 *	22.0
24.0	71.8	65.5	11 700 *	75.0	65.1	11 400 *	78.2	64.0	10 100 *	24.0
26.0	69.9	64.8	11 500 *	73.1	64.3	11 100 *	76.4	63.3	9 600 *	26.0
28.0	68.1	64.0	11 200 *	71.3	63.5	10 900 *	74.5	62.4	9 100 *	28.0
30.0	66.2	63.1	11 000 *	69.4	62.6	10 700 *	72.5	61.5	8 700 *	30.0
32.0	64.3	62.1	10 700 *	67.4	61.6	10 500 *	70.6	60.5	8 300 *	32.0
34.0	62.3	61.1	10 500 *	65.5	60.6	10 200 *	68.6	59.4	8 000 *	34.0
36.0	60.4	59.9	10 300 *	63.5	59.4	10 000 *	66.6	58.3	7 700 *	36.0
38.0	58.4	58.7	10 000 *	61.5	58.2	9 800 *	64.5	57.0	7 400 *	38.0
40.0	56.3	57.3	9 900 *	59.4	56.8	9 500 *	62.4	55.6	7 200 *	40.0
44.0	52.0	54.3	9 400 *	55.0	53.8	8 700 *	57.9	52.5	6 700 *	44.0
48.0	47.4	50.8	9 100 *	50.4	50.2	8 100 *	53.2	48.8	6 300 *	48.0
52.0	42.5	46.6	8 700	45.4	46.0	7 500 *	48.0	44.5	6 000 *	52.0
56.0	37.0	41.6	7 400	39.8	40.9	7 000 *	42.1	39.1	5 700 *	56.0
60.0	30.6	35.3	6 300	33.3	34.5	6 500				60.0
64.0	22.6	26.9	5 300							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
15.2	80.0	71.0	12 900 *							15.2
16.0	79.4	70.9	12 800 *							16.0
18.0	77.7	70.4	12 500 *							18.0
20.0	76.0	69.9	12 300 *	79.1	69.5	11 900*				20.0
22.0	74.3	69.3	12 000 *	77.4	68.9	11 700*				22.0
24.0	72.6	68.7	11 800 *	75.6	68.3	11 500*	78.8	67.2	10 300*	24.0
26.0	70.8	68.0	11 600 *	73.9	67.5	11 200*	77.0	66.5	9 800*	26.0
28.0	69.1	67.2	11 300 *	72.1	66.8	11 000*	75.2	65.7	9 300*	28.0
30.0	67.3	66.4	11 000 *	70.3	65.9	10 800*	73.4	64.8	8 900*	30.0
32.0	65.5	65.5	10 800 *	68.5	65.0	10 600*	71.5	63.9	8 500*	32.0
34.0	63.6	64.5	10 600 *	66.7	64.0	10 400*	69.6	62.8	8 200*	34.0
36.0	61.8	63.4	10 300 *	64.8	62.9	10 200*	67.7	61.7	7 900*	36.0
38.0	59.9	62.2	10 100 *	62.9	61.7	10 000*	65.8	60.5	7 600*	38.0
40.0	57.9	60.9	9 900 *	60.9	60.4	9 800*	63.8	59.2	7 300*	40.0
44.0	53.9	58.1	9 500 *	56.9	57.6	9 100*	59.6	56.3	6 900*	44.0
48.0	49.7	54.9	9 200 *	52.6	54.3	8 400*	55.2	52.9	6 500*	48.0
52.0	45.1	51.0	8 400	48.0	50.4	7 800*	50.5	49.0	6 100*	52.0
56.0	40.2	46.5	7 200	43.0	45.9	7 300*	45.3	44.2	5 800*	56.0
60.0	34.7	41.1	6 100	37.3	40.3	6 300				60.0
64.0	28.1	34.2	5 100	30.7	33.3	5 300				64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	80.4	74.1	12 800 *							15.2
16.0	79.8	73.9	12 700 *							16.0
18.0	78.2	73.5	12 400 *							18.0
20.0	76.6	73.0	12 200 *	79.6	72.6	11 900*				20.0
22.0	75.0	72.5	12 000 *	77.9	72.0	11 700*				22.0
24.0	73.3	71.9	11 700 *	76.3	71.4	11 500*	79.3	70.3	10 400*	24.0
26.0	71.7	71.2	11 500 *	74.6	70.7	11 300*	77.6	69.6	9 900*	26.0
28.0	70.0	70.4	11 300 *	72.9	70.0	11 100*	75.9	68.9	9 500*	28.0
30.0	68.3	69.6	11 000 *	71.2	69.2	10 900*	74.1	68.1	9 100*	30.0
32.0	66.6	68.8	10 800 *	69.5	68.3	10 700*	72.4	67.2	8 700*	32.0
34.0	64.8	67.8	10 600 *	67.7	67.3	10 500*	70.6	66.2	8 400*	34.0
36.0	63.1	66.8	10 400 *	65.9	66.3	10 300*	68.8	65.1	8 100*	36.0
38.0	61.3	65.7	10 200 *	64.1	65.2	10 100*	66.9	64.0	7 800*	38.0
40.0	59.4	64.5	9 900 *	62.3	64.0	9 900*	65.0	62.8	7 500*	40.0
44.0	55.6	61.8	9 600 *	58.5	61.3	9 400*	61.2	60.1	7 000*	44.0
48.0	51.7	58.8	9 300 *	54.5	58.2	8 700*	57.1	56.9	6 600*	48.0
52.0	47.5	55.3	8 200	50.2	54.7	8 000*	52.7	53.2	6 300*	52.0
56.0	43.0	51.1	6 900	45.7	50.5	7 300	48.0	48.9	6 000*	56.0
60.0	38.0	46.3	5 800	40.6	45.6	6 100	42.8	43.8	5 700*	60.0
64.0	32.4	40.4	4 900	34.9	39.6	5 100				64.0
68.0	25.7	32.9	4 100							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.8	77.1	12 700 *							15.2
16.0	80.2	77.0	12 700 *							16.0
18.0	78.7	76.6	12 400 *							18.0
20.0	77.1	76.1	12 200 *	80.0	75.7	11 800*				20.0
22.0	75.6	75.6	11 900 *	78.4	75.1	11 600*				22.0
24.0	74.0	75.0	11 700 *	76.8	74.5	11 500*	79.7	73.4	10 500*	24.0
26.0	72.4	74.4	11 500 *	75.2	73.9	11 200*	78.1	72.8	10 000*	26.0
28.0	70.8	73.6	11 300 *	73.6	73.2	11 100*	76.5	72.1	9 600*	28.0
30.0	69.2	72.9	11 100 *	72.0	72.4	10 900*	74.8	71.3	9 200*	30.0
32.0	67.5	72.0	10 800 *	70.3	71.6	10 700*	73.1	70.4	8 800*	32.0
34.0	65.9	71.1	10 600 *	68.7	70.7	10 600*	71.4	69.5	8 500*	34.0
36.0	64.2	70.2	10 400 *	67.0	69.7	10 400*	69.7	68.5	8 200*	36.0
38.0	62.5	69.1	10 200 *	65.3	68.6	10 200*	68.0	67.4	7 900*	38.0
40.0	60.8	68.0	10 000 *	63.5	67.5	10 000*	66.2	66.3	7 700*	40.0
44.0	57.2	65.5	9 700 *	59.9	65.0	9 600*	62.5	63.7	7 200*	44.0
48.0	53.5	62.6	9 300	56.2	62.1	8 900*	58.7	60.7	6 800*	48.0
52.0	49.6	59.3	8 000	52.2	58.7	8 300	54.6	57.3	6 400*	52.0
56.0	45.4	55.5	6 700	48.0	54.9	7 100	50.3	53.4	6 100*	56.0
60.0	40.9	51.1	5 600	43.4	50.4	5 900	45.6	48.8	5 900*	60.0
64.0	35.9	45.9	4 700	38.4	45.1	4 900				64.0
68.0	30.2	39.5	3 800	32.6	38.6	4 000				68.0
72.0	23.2	31.2	3 100							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
16.8	80.0	79.9	12 500 *							16.8
18.0	79.1	79.6	12 300 *							18.0
20.0	77.6	79.2	12 100 *	80.4	78.7	11 700*				20.0
22.0	76.1	78.7	11 900 *	78.9	78.2	11 500*				22.0
24.0	74.6	78.1	11 700 *	77.4	77.7	11 400*	80.1	76.6	10 600*	24.0
26.0	73.1	77.5	11 500 *	75.8	77.0	11 200*	78.6	75.9	10 200*	26.0
28.0	71.6	76.8	11 300 *	74.3	76.4	11 000*	77.0	75.2	9 800*	28.0
30.0	70.0	76.1	11 100 *	72.7	75.6	10 900*	75.4	74.5	9 400*	30.0
32.0	68.5	75.3	10 800 *	71.1	74.8	10 700*	73.8	73.7	9 000*	32.0
34.0	66.9	74.4	10 600 *	69.6	74.0	10 500*	72.2	72.8	8 700*	34.0
36.0	65.3	73.5	10 400 *	67.9	73.0	10 400*	70.6	71.8	8 400*	36.0
38.0	63.6	72.5	10 200 *	66.3	72.0	10 300*	68.9	70.8	8 100*	38.0
40.0	62.0	71.4	10 000 *	64.6	70.9	10 100*	67.2	69.7	7 800*	40.0
44.0	58.6	69.1	9 700 *	61.2	68.6	9 800*	63.8	67.3	7 300*	44.0
48.0	55.1	66.4	9 200	57.7	65.8	9 200*	60.1	64.5	6 900*	48.0
52.0	51.4	63.3	7 600	54.0	62.7	8 100	56.3	61.3	6 600*	52.0
56.0	47.5	59.7	6 400	50.1	59.1	6 800	52.3	57.6	6 200*	56.0
60.0	43.4	55.7	5 300	45.9	55.0	5 700	48.0	53.4	5 900	60.0
64.0	38.9	50.9	4 400	41.3	50.2	4 600	43.3	48.4	4 900	64.0
68.0	33.9	45.3	3 500	36.2	44.5	3 700				68.0
72.0	28.0	38.4	2 800							72.0
76.0	20.7	29.1	2 100							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.4	82.9	12 400 *							16.8
18.0	79.5	82.7	12 200 *							18.0
20.0	78.1	82.3	12 000 *	80.7	81.8	11 700*				20.0
22.0	76.6	81.8	11 800 *	79.3	81.3	11 500*				22.0
24.0	75.2	81.2	11 600 *	77.8	80.8	11 300*				24.0
26.0	73.7	80.7	11 400 *	76.4	80.2	11 100*	79.0	79.1	10 300*	26.0
28.0	72.3	80.0	11 200 *	74.9	79.5	11 000*	77.5	78.4	9 900*	28.0
30.0	70.8	79.3	11 100 *	73.4	78.8	10 800*	76.0	77.7	9 500*	30.0
32.0	69.3	78.5	10 800 *	71.9	78.1	10 700*	74.5	76.9	9 200*	32.0
34.0	67.8	77.7	10 600 *	70.4	77.2	10 500*	72.9	76.1	8 800*	34.0
36.0	66.2	76.8	10 400 *	68.8	76.3	10 400*	71.4	75.2	8 500*	36.0
38.0	64.7	75.9	10 300 *	67.3	75.4	10 300*	69.8	74.2	8 200*	38.0
40.0	63.1	74.9	10 100 *	65.7	74.3	10 100*	68.2	73.1	8 000*	40.0
44.0	59.9	72.6	9 700 *	62.4	72.1	9 800*	64.9	70.8	7 500*	44.0
48.0	56.6	70.0	8 900	59.1	69.5	9 400	61.5	68.2	7 000*	48.0
52.0	53.1	67.1	7 400	55.6	66.5	7 900	57.9	65.2	6 700*	52.0
56.0	49.5	63.8	6 100	51.9	63.2	6 600	54.1	61.8	6 400*	56.0
60.0	45.6	60.0	5 100	48.0	59.4	5 400	50.1	57.8	5 700	60.0
64.0	41.5	55.7	4 100	43.8	55.0	4 400	45.8	53.3	4 700	64.0
68.0	36.9	50.6	3 300	39.2	49.8	3 600				68.0
72.0	31.9	44.5	2 600	34.1	43.7	2 700				72.0
76.0	25.9	37.0	1 900							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.7	86.0	12 200 *							16.8
18.0	79.9	85.8	12 100 *							18.0
20.0	78.5	85.3	11 900 *							20.0
22.0	77.1	84.9	11 700 *	79.7	84.4	11 400*				22.0
24.0	75.7	84.4	11 600 *	78.3	83.9	11 300*				24.0
26.0	74.3	83.8	11 300 *	76.9	83.3	11 100*	79.4	82.2	10 500*	26.0
28.0	72.9	83.2	11 200 *	75.4	82.7	10 900*	78.0	81.5	10 000*	28.0
30.0	71.5	82.5	11 000 *	74.0	82.0	10 800*	76.5	80.9	9 600*	30.0
32.0	70.1	81.8	10 800 *	72.6	81.3	10 700*	75.1	80.1	9 300*	32.0
34.0	68.6	81.0	10 600 *	71.1	80.5	10 500*	73.6	79.3	8 900*	34.0
36.0	67.1	80.1	10 400 *	69.6	79.6	10 400*	72.1	78.4	8 700*	36.0
38.0	65.6	79.2	10 200 *	68.1	78.7	10 300*	70.6	77.5	8 400*	38.0
40.0	64.1	78.2	10 000 *	66.6	77.7	10 100*	69.0	76.5	8 100*	40.0
44.0	61.1	76.1	9 700 *	63.5	75.6	9 800*	65.9	74.3	7 600*	44.0
48.0	57.9	73.6	8 600	60.3	73.1	9 300	62.6	71.8	7 200*	48.0
52.0	54.6	70.9	7 100	57.0	70.3	7 600	59.3	68.9	6 800*	52.0
56.0	51.2	67.7	5 900	53.6	67.2	6 300	55.7	65.7	6 500*	56.0
60.0	47.6	64.2	4 800	49.9	63.6	5 200	52.0	62.1	5 600	60.0
64.0	43.7	60.2	3 900	46.0	59.5	4 200	48.0	57.9	4 500	64.0
68.0	39.6	55.5	3 000	41.9	54.8	3 300	43.7	53.0	3 600	68.0
72.0	35.1	50.1	2 300	37.2	49.3	2 500				72.0
76.0				32.0	42.7	1 800				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
18.3	80.1	88.8	12 600 *							18.3
20.0	78.9	88.4	12 400 *							20.0
22.0	77.6	88.0	12 200 *	80.0	87.5	11 800*				22.0
24.0	76.2	87.5	12 000 *	78.7	87.0	11 700*				24.0
26.0	74.9	86.9	11 800 *	77.3	86.4	11 500*	79.8	85.3	10 600*	26.0
28.0	73.5	86.3	11 600 *	76.0	85.8	11 300*	78.4	84.7	10 100*	28.0
30.0	72.1	85.7	11 400 *	74.6	85.2	11 100*	77.0	84.0	9 800*	30.0
32.0	70.8	85.0	11 200 *	73.2	84.5	11 000*	75.6	83.3	9 400*	32.0
34.0	69.4	84.2	11 000 *	71.8	83.7	10 800*	74.2	82.5	9 100*	34.0
36.0	68.0	83.4	10 800 *	70.4	82.9	10 600*	72.8	81.7	8 800*	36.0
38.0	66.5	82.5	10 600 *	68.9	82.0	10 500*	71.3	80.8	8 500*	38.0
40.0	65.1	81.6	10 400 *	67.5	81.1	10 300*	69.8	79.8	8 200*	40.0
44.0	62.2	79.5	10 000 *	64.5	79.0	10 000*	66.8	77.7	7 800*	44.0
48.0	59.1	77.2	8 400	61.5	76.6	9 000	63.7	75.3	7 300*	48.0
52.0	56.0	74.6	6 900	58.3	74.0	7 500	60.5	72.7	7 000*	52.0
56.0	52.8	71.6	5 700	55.1	71.0	6 100	57.2	69.6	6 500	56.0
60.0	49.4	68.3	4 600	51.6	67.7	5 000	53.7	66.2	5 400	60.0
64.0	45.8	64.5	3 600	48.0	63.9	4 000	50.0	62.3	4 300	64.0
68.0	42.0	60.2	2 800	44.2	59.5	3 100	46.0	57.8	3 400	68.0
72.0	37.8	55.3	2 100	40.0	54.5	2 300				72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

21.3m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
18.3	80.4	91.8	12 400 *							18.3
20.0	79.3	91.5	12 200 *							20.0
22.0	78.0	91.0	12 000 *	80.4	90.6	11 700*				22.0
24.0	76.7	90.6	11 800 *	79.1	90.1	11 600*				24.0
26.0	75.4	90.0	11 600 *	77.8	89.6	11 400*	80.2	88.4	10 600*	26.0
28.0	74.1	89.5	11 500 *	76.4	89.0	11 300*	78.8	87.8	10 300*	28.0
30.0	72.8	88.8	11 300 *	75.1	88.3	11 100*	77.5	87.2	9 900*	30.0
32.0	71.4	88.1	11 200 *	73.8	87.7	11 000*	76.1	86.5	9 500*	32.0
34.0	70.1	87.4	11 000 *	72.4	86.9	10 800*	74.8	85.7	9 200*	34.0
36.0	68.7	86.6	10 800 *	71.1	86.1	10 700*	73.4	84.9	8 900*	36.0
38.0	67.4	85.8	10 600 *	69.7	85.3	10 500*	72.0	84.1	8 600*	38.0
40.0	66.0	84.9	10 400 *	68.3	84.4	10 400*	70.6	83.2	8 300*	40.0
44.0	63.2	82.9	9 700	65.5	82.4	10 100*	67.7	81.1	7 900*	44.0
48.0	60.3	80.7	8 100	62.6	80.2	8 700	64.7	78.9	7 500*	48.0
52.0	57.3	78.2	6 600	59.6	77.6	7 200	61.7	76.3	7 100*	52.0
56.0	54.2	75.4	5 400	56.4	74.8	5 800	58.5	73.4	6 300	56.0
60.0	51.0	72.2	4 300	53.2	71.6	4 700	55.2	70.2	5 100	60.0
64.0	47.6	68.7	3 300	49.8	68.0	3 700	51.7	66.5	4 000	64.0
68.0	44.1	64.7	2 500	46.2	64.0	2 800	48.0	62.4	3 100	68.0
72.0				42.3	59.4	2 000	44.1	57.6	2 300	72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
27.5m Boom										
12.2	79.5	53.3	10 600 *							12.2
14.0	77.4	52.9	10 300 *							14.0
16.0	75.2	52.4	10 000 *	80.0	52.1	9 900*				16.0
18.0	72.8	51.8	9 700 *	77.7	51.5	9 600*				18.0
20.0	70.5	51.1	9 400 *	75.3	50.8	9 300*	80.3	49.9	8 900*	20.0
22.0	68.1	50.3	9 100 *	72.9	50.0	9 000*	77.9	49.1	8 600*	22.0
24.0	65.7	49.4	8 900 *	70.5	49.1	8 700*	75.4	48.1	8 200*	24.0
26.0	63.2	48.4	8 600 *	68.0	48.1	8 500*	72.8	47.1	7 600*	26.0
28.0	60.7	47.3	8 300 *	65.4	46.9	8 200*	70.2	46.0	7 200*	28.0
30.0	58.1	46.1	8 100 *	62.8	45.7	8 000*	67.6	44.7	6 700*	30.0
32.0	55.5	44.7	7 800 *	60.1	44.3	7 700*	64.8	43.3	6 400*	32.0
34.0	52.7	43.2	7 600 *	57.4	42.8	7 500*	62.0	41.7	6 000*	34.0
36.0	49.8	41.5	7 300 *	54.4	41.1	7 300*	59.0	40.0	5 800*	36.0
38.0	46.8	39.7	7 100 *	51.4	39.2	7 000*	55.8	38.1	5 500*	38.0
40.0	43.6	37.6	6 900 *	48.2	37.2	6 600*	52.5	35.9	5 300*	40.0
44.0	36.6	32.7	6 500 *	41.1	32.2	6 000*	45.1	30.7	4 900*	44.0
48.0	28.1	26.1	6 200 *	32.4	25.5	5 500*				48.0
30.5m Boom										
12.2	80.1	56.4	10 600 *							12.2
14.0	78.1	56.0	10 300 *							14.0
16.0	76.0	55.5	10 100 *							16.0
18.0	73.8	54.9	9 800 *	78.4	54.6	9 600*				18.0
20.0	71.6	54.3	9 500 *	76.2	53.9	9 300*				20.0
22.0	69.4	53.5	9 200 *	73.9	53.2	9 100*	78.6	52.3	8 700*	22.0
24.0	67.1	52.7	9 000 *	71.6	52.3	8 800*	76.3	51.4	8 300*	24.0
26.0	64.8	51.8	8 700 *	69.3	51.4	8 600*	73.9	50.4	7 800*	26.0
28.0	62.5	50.7	8 500 *	67.0	50.4	8 300*	71.5	49.4	7 400*	28.0
30.0	60.1	49.6	8 200 *	64.5	49.2	8 100*	69.0	48.2	6 900*	30.0
32.0	57.6	48.3	8 000 *	62.0	47.9	7 800*	66.5	46.9	6 600*	32.0
34.0	55.1	47.0	7 700 *	59.5	46.6	7 700*	63.9	45.5	6 300*	34.0
36.0	52.5	45.4	7 500 *	56.8	45.0	7 400*	61.1	43.9	6 000*	36.0
38.0	49.7	43.8	7 300 *	54.1	43.3	7 200*	58.3	42.2	5 700*	38.0
40.0	46.9	41.9	7 100 *	51.2	41.5	7 000*	55.4	40.3	5 400*	40.0
44.0	40.7	37.6	6 700 *	45.0	37.1	6 300*	48.9	35.7	5 000*	44.0
48.0	33.7	32.1	6 400 *	37.8	31.5	5 800*	41.4	29.9	4 700*	48.0
52.0	24.9	24.7	6 100 *							52.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
33.5m Boom										
12.2	80.6	59.4	10 600 *							12.2
14.0	78.8	59.1	10 300 *							14.0
16.0	76.7	58.6	10 100 *							16.0
18.0	74.7	58.1	9 800 *	79.0	57.7	9 600 *				18.0
20.0	72.6	57.5	9 500 *	76.9	57.1	9 400 *				20.0
22.0	70.5	56.7	9 300 *	74.8	56.4	9 100 *	79.2	55.4	8 700 *	22.0
24.0	68.4	56.0	9 000 *	72.7	55.6	8 900 *	77.1	54.6	8 500 *	24.0
26.0	66.2	55.1	8 800 *	70.5	54.7	8 600 *	74.8	53.7	8 000 *	26.0
28.0	64.0	54.1	8 600 *	68.3	53.7	8 400 *	72.6	52.7	7 500 *	28.0
30.0	61.8	53.1	8 300 *	66.0	52.7	8 200 *	70.3	51.6	7 200 *	30.0
32.0	59.5	51.9	8 100 *	63.7	51.5	8 000 *	67.9	50.4	6 800 *	32.0
34.0	57.1	50.6	7 800 *	61.3	50.2	7 800 *	65.5	49.1	6 500 *	34.0
36.0	54.7	49.2	7 600 *	58.9	48.8	7 600 *	63.0	47.7	6 200 *	36.0
38.0	52.2	47.7	7 400 *	56.4	47.2	7 400 *	60.4	46.1	5 900 *	38.0
40.0	49.6	46.0	7 200 *	53.8	45.6	7 200 *	57.7	44.3	5 700 *	40.0
44.0	44.1	42.1	6 800 *	48.2	41.6	6 700 *	52.0	40.3	5 200 *	44.0
48.0	38.0	37.4	6 500 *	42.0	36.8	6 100 *	45.5	35.3	4 900 *	48.0
52.0	30.8	31.3	6 200 *	34.6	30.7	5 600 *				52.0
56.0	21.5	22.9	6 000 *							56.0
36.5m Boom										
13.7	79.6	62.2	10 400 *							13.7
14.0	79.3	62.1	10 400 *							14.0
16.0	77.4	61.7	10 100 *							16.0
18.0	75.5	61.2	10 000 *	79.6	60.8	9 700 *				18.0
20.0	73.5	60.6	9 600 *	77.6	60.2	9 400 *				20.0
22.0	71.5	59.9	9 300 *	75.6	59.6	9 200 *	79.8	58.6	8 700 *	22.0
24.0	69.5	59.2	9 200 *	73.6	58.8	8 900 *	77.8	57.8	8 600 *	24.0
26.0	67.5	58.4	8 900 *	71.5	58.0	8 700 *	75.7	57.0	8 200 *	26.0
28.0	65.4	57.5	8 600 *	69.4	57.1	8 500 *	73.5	56.0	7 800 *	28.0
30.0	63.3	56.5	8 400 *	67.3	56.1	8 300 *	71.4	55.0	7 300 *	30.0
32.0	61.2	55.4	8 200 *	65.2	55.0	8 100 *	69.2	53.9	7 000 *	32.0
34.0	59.0	54.2	8 000 *	63.0	53.8	7 900 *	66.9	52.7	6 600 *	34.0
36.0	56.7	52.9	7 800 *	60.7	52.5	7 700 *	64.6	51.3	6 300 *	36.0
38.0	54.4	51.5	7 500 *	58.4	51.0	7 500 *	62.2	49.9	6 100 *	38.0
40.0	52.0	49.9	7 300 *	56.0	49.5	7 300 *	59.8	48.3	5 800 *	40.0
44.0	47.0	46.4	7 000 *	50.9	45.9	7 000 *	54.6	44.6	5 400 *	44.0
48.0	41.5	42.2	6 600 *	45.4	41.6	6 400 *	48.8	40.2	5 000 *	48.0
52.0	35.4	37.0	6 300 *	39.1	36.3	5 900 *	42.3	34.7	4 700 *	52.0
56.0	28.0	30.3	6 100 *	31.6	29.5	5 500 *				56.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
39.5m Boom										
13.7	80.1	65.3	10 400 *							13.7
14.0	79.8	65.2	10 400 *							14.0
16.0	78.0	64.8	10 200 *							16.0
18.0	76.2	64.3	9 900 *							18.0
20.0	74.3	63.7	9 800 *	78.2	63.4	9 500*				20.0
22.0	72.4	63.1	9 400 *	76.3	62.7	9 200*	80.3	61.7	8 700*	22.0
24.0	70.5	62.4	9 200 *	74.4	62.0	9 000*	78.4	61.0	8 600*	24.0
26.0	68.6	61.6	8 900 *	72.5	61.2	8 700*	76.4	60.2	8 400*	26.0
28.0	66.6	60.8	8 700 *	70.5	60.4	8 600*	74.4	59.3	7 900*	28.0
30.0	64.7	59.8	8 500 *	68.5	59.4	8 400*	72.4	58.4	7 500*	30.0
32.0	62.6	58.8	8 300 *	66.5	58.4	8 200*	70.3	57.3	7 200*	32.0
34.0	60.6	57.7	8 100 *	64.4	57.3	8 000*	68.2	56.1	6 800*	34.0
36.0	58.5	56.5	7 800 *	62.3	56.0	7 800*	66.0	54.9	6 500*	36.0
38.0	56.3	55.1	7 600 *	60.1	54.7	7 600*	63.8	53.5	6 300*	38.0
40.0	54.1	53.7	7 400 *	57.9	53.3	7 400*	61.5	52.1	6 000*	40.0
44.0	49.5	50.5	7 100 *	53.2	50.0	7 100*	56.8	48.7	5 600*	44.0
48.0	44.5	46.6	6 700 *	48.2	46.1	6 700*	51.6	44.7	5 200*	48.0
52.0	39.1	42.0	6 500 *	42.7	41.4	6 100*	45.8	39.9	4 900*	52.0
56.0	32.8	36.3	6 200 *	36.3	35.6	5 700*				56.0
60.0	25.2	28.9	6 000 *							60.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
42.5m Boom										
13.7	80.5	68.3	10 400 *							13.7
14.0	80.3	68.3	10 400 *							14.0
16.0	78.6	67.9	10 200 *							16.0
18.0	76.8	67.4	9 900 *							18.0
20.0	75.0	66.9	9 700 *	78.7	66.5	9 500*				20.0
22.0	73.2	66.3	9 400 *	76.9	65.9	9 200*				22.0
24.0	71.4	65.6	9 200 *	75.1	65.2	9 000*	78.9	64.2	8 600*	24.0
26.0	69.6	64.9	9 000 *	73.3	64.5	8 800*	77.1	63.4	8 400*	26.0
28.0	67.7	64.0	8 800 *	71.4	63.6	8 600*	75.2	62.6	8 100*	28.0
30.0	65.9	63.2	8 600 *	69.5	62.7	8 400*	73.3	61.7	7 700*	30.0
32.0	64.0	62.2	8 300 *	67.6	61.8	8 300*	71.3	60.7	7 300*	32.0
34.0	62.0	61.1	8 200 *	65.7	60.7	8 100*	69.3	59.6	7 000*	34.0
36.0	60.1	60.0	8 000 *	63.7	59.6	7 800*	67.3	58.4	6 700*	36.0
38.0	58.0	58.7	7 800 *	61.7	58.3	7 700*	65.2	57.1	6 400*	38.0
40.0	56.0	57.4	7 600 *	59.6	57.0	7 500*	63.1	55.8	6 200*	40.0
44.0	51.7	54.4	7 200 *	55.3	53.9	7 200*	58.7	52.6	5 700*	44.0
48.0	47.1	50.9	6 900 *	50.6	50.4	6 900*	53.9	49.0	5 400*	48.0
52.0	42.2	46.7	6 600 *	45.6	46.1	6 400*	48.8	44.6	5 000*	52.0
56.0	36.7	41.7	6 300 *	40.1	41.1	6 000*	43.0	39.3	4 800*	56.0
60.0	30.4	35.5	6 100 *	33.6	34.7	5 600*				60.0
64.0	22.4	27.1	5 800							64.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
45.5m Boom										
13.7	81.0	71.4	10 300 *							13.7
14.0	80.7	71.3	10 300 *							14.0
16.0	79.0	70.9	10 100 *							16.0
18.0	77.4	70.5	9 900 *							18.0
20.0	75.7	70.0	9 700 *	79.2	69.6	9 500 *				20.0
22.0	74.0	69.4	9 500 *	77.5	69.0	9 200 *				22.0
24.0	72.3	68.8	9 300 *	75.8	68.4	9 000 *	79.5	67.3	8 600 *	24.0
26.0	70.5	68.1	9 100 *	74.1	67.7	8 800 *	77.7	66.6	8 400 *	26.0
28.0	68.8	67.3	8 800 *	72.3	66.9	8 700 *	75.9	65.8	8 200 *	28.0
30.0	67.0	66.4	8 600 *	70.5	66.0	8 500 *	74.1	64.9	7 800 *	30.0
32.0	65.2	65.5	8 400 *	68.7	65.1	8 300 *	72.2	64.0	7 500 *	32.0
34.0	63.3	64.5	8 200 *	66.8	64.1	8 100 *	70.3	63.0	7 200 *	34.0
36.0	61.5	63.4	8 000 *	65.0	63.0	7 900 *	68.4	61.9	6 900 *	36.0
38.0	59.6	62.3	7 900 *	63.0	61.8	7 800 *	66.5	60.7	6 600 *	38.0
40.0	57.6	61.0	7 700 *	61.1	60.6	7 600 *	64.5	59.4	6 300 *	40.0
44.0	53.6	58.2	7 300 *	57.1	57.7	7 300 *	60.3	56.5	5 900 *	44.0
48.0	49.4	54.9	7 000 *	52.8	54.4	7 000 *	56.0	53.1	5 500 *	48.0
52.0	44.9	51.1	6 700 *	48.2	50.6	6 600 *	51.2	49.1	5 200 *	52.0
56.0	39.9	46.6	6 400 *	43.2	46.0	6 200 *	46.1	44.4	4 900 *	56.0
60.0	34.4	41.2	6 200 *	37.6	40.5	5 800 *				60.0
64.0	27.9	34.4	5 500	31.0	33.5	5 400 *				64.0
68.0	19.5	24.9	4 700							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
48.5m Boom										
15.2	80.1	74.1	10 200 *							15.2
16.0	79.5	74.0	10 100 *							16.0
18.0	77.9	73.6	10 000 *							18.0
20.0	76.3	73.1	9 700 *	79.7	72.7	9 500*				20.0
22.0	74.7	72.5	9 500 *	78.1	72.1	9 300*				22.0
24.0	73.0	71.9	9 300 *	76.4	71.5	9 100*	79.9	70.4	8 600*	24.0
26.0	71.4	71.2	9 100 *	74.7	70.8	8 900*	78.2	69.7	8 500*	26.0
28.0	69.7	70.5	8 900 *	73.1	70.1	8 600*	76.5	69.0	8 300*	28.0
30.0	68.0	69.7	8 700 *	71.4	69.3	8 500*	74.8	68.2	8 000*	30.0
32.0	66.3	68.8	8 500 *	69.6	68.4	8 300*	73.0	67.3	7 700*	32.0
34.0	64.5	67.9	8 300 *	67.9	67.5	8 200*	71.2	66.3	7 300*	34.0
36.0	62.8	66.9	8 100 *	66.1	66.4	8 000*	69.4	65.3	7 000*	36.0
38.0	61.0	65.8	7 900 *	64.3	65.3	7 900*	67.6	64.1	6 700*	38.0
40.0	59.1	64.6	7 700 *	62.5	64.1	7 700*	65.7	62.9	6 500*	40.0
44.0	55.4	61.9	7 400 *	58.7	61.5	7 400*	61.8	60.2	6 000*	44.0
48.0	51.4	58.9	7 100 *	54.7	58.4	7 100*	57.7	57.0	5 600*	48.0
52.0	47.2	55.3	6 800 *	50.4	54.8	6 800*	53.4	53.4	5 300*	52.0
56.0	42.7	51.2	6 500 *	45.9	50.7	6 400*	48.7	49.1	5 000*	56.0
60.0	37.8	46.4	6 200	40.9	45.7	6 000*	43.5	44.0	4 800*	60.0
64.0	32.2	40.5	5 300	35.2	39.8	5 500				64.0
68.0	25.5	33.0	4 400							68.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
51.5m Boom										
15.2	80.5	77.2	10 200 *							15.2
16.0	79.9	77.0	10 100 *							16.0
18.0	78.4	76.6	10 000 *							18.0
20.0	76.8	76.2	9 700 *	80.1	75.8	9 400*				20.0
22.0	75.3	75.6	9 500 *	78.6	75.2	9 200*				22.0
24.0	73.7	75.1	9 300 *	77.0	74.7	9 100*				24.0
26.0	72.1	74.4	9 100 *	75.4	74.0	8 900*	78.7	72.9	8 400*	26.0
28.0	70.5	73.7	8 900 *	73.8	73.3	8 700*	77.1	72.2	8 300*	28.0
30.0	68.9	72.9	8 700 *	72.1	72.5	8 500*	75.4	71.4	8 100*	30.0
32.0	67.3	72.1	8 500 *	70.5	71.7	8 300*	73.8	70.5	7 800*	32.0
34.0	65.6	71.2	8 300 *	68.8	70.8	8 200*	72.1	69.6	7 400*	34.0
36.0	63.9	70.2	8 100 *	67.1	69.8	8 000*	70.3	68.6	7 200*	36.0
38.0	62.2	69.2	7 900 *	65.4	68.7	7 900*	68.6	67.5	6 900*	38.0
40.0	60.5	68.1	7 800 *	63.7	67.6	7 700*	66.8	66.4	6 600*	40.0
44.0	56.9	65.6	7 500 *	60.1	65.1	7 400*	63.2	63.8	6 200*	44.0
48.0	53.2	62.7	7 100 *	56.3	62.2	7 200*	59.3	60.9	5 800*	48.0
52.0	49.3	59.4	6 800 *	52.4	58.9	6 900*	55.3	57.5	5 500*	52.0
56.0	45.1	55.6	6 600 *	48.2	55.1	6 700*	51.0	53.5	5 200*	56.0
60.0	40.6	51.2	6 000	43.6	50.6	6 200	46.3	48.9	4 900*	60.0
64.0	35.7	46.0	5 000	38.6	45.3	5 300	41.0	43.4	4 700*	64.0
68.0	30.0	39.6	4 200	32.8	38.8	4 400				68.0
72.0	23.1	31.3	3 500							72.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
54.5m Boom										
15.2	80.9	80.2	10 100 *							15.2
16.0	80.3	80.1	10 100 *							16.0
18.0	78.8	79.7	9 900 *							18.0
20.0	77.3	79.3	9 700 *	80.5	78.8	9 400 *				20.0
22.0	75.8	78.8	9 500 *	79.0	78.3	9 200 *				22.0
24.0	74.3	78.2	9 300 *	77.5	77.8	9 100 *				24.0
26.0	72.8	77.6	9 100 *	76.0	77.2	8 900 *	79.2	76.0	8 400 *	26.0
28.0	71.3	76.9	8 900 *	74.4	76.5	8 700 *	77.6	75.3	8 300 *	28.0
30.0	69.7	76.2	8 700 *	72.9	75.7	8 500 *	76.0	74.6	8 200 *	30.0
32.0	68.2	75.4	8 500 *	71.3	74.9	8 400 *	74.4	73.8	7 900 *	32.0
34.0	66.6	74.5	8 300 *	69.7	74.1	8 200 *	72.8	72.9	7 600 *	34.0
36.0	65.0	73.6	8 200 *	68.1	73.1	8 100 *	71.2	72.0	7 300 *	36.0
38.0	63.4	72.6	8 000 *	66.5	72.1	7 900 *	69.5	70.9	7 000 *	38.0
40.0	61.7	71.5	7 900 *	64.8	71.1	7 800 *	67.8	69.8	6 800 *	40.0
44.0	58.3	69.2	7 500 *	61.4	68.7	7 500 *	64.4	67.4	6 300 *	44.0
48.0	54.8	66.4	7 200 *	57.9	65.9	7 300 *	60.8	64.6	5 900 *	48.0
52.0	51.2	63.4	6 900 *	54.2	62.8	7 000 *	57.0	61.4	5 600 *	52.0
56.0	47.3	59.8	6 700 *	50.3	59.3	6 800 *	53.0	57.8	5 300 *	56.0
60.0	43.2	55.8	5 700	46.1	55.2	6 100	48.7	53.6	5 000 *	60.0
64.0	38.7	51.0	4 800	41.5	50.4	5 100	43.9	48.6	4 800 *	64.0
68.0	33.6	45.4	4 000	36.4	44.7	4 200				68.0
72.0	27.8	38.5	3 200	30.5	37.6	3 400				72.0
76.0	20.6	29.3	2 600							76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
57.5m Boom										
16.8	80.1	83.0	10 000 *							16.8
18.0	79.2	82.8	9 900 *							18.0
20.0	77.8	82.3	9 700 *	80.9	81.9	9 400*				20.0
22.0	76.4	81.9	9 500 *	79.4	81.4	9 200*				22.0
24.0	74.9	81.3	9 300 *	78.0	80.9	9 000*				24.0
26.0	73.5	80.7	9 100 *	76.5	80.3	8 800*	79.6	79.2	8 400*	26.0
28.0	72.0	80.1	8 900 *	75.0	79.6	8 700*	78.1	78.5	8 300*	28.0
30.0	70.5	79.4	8 700 *	73.5	78.9	8 500*	76.6	77.8	8 200*	30.0
32.0	69.0	78.6	8 600 *	72.0	78.2	8 400*	75.1	77.0	8 100*	32.0
34.0	67.5	77.8	8 400 *	70.5	77.3	8 200*	73.5	76.2	7 700*	34.0
36.0	66.0	76.9	8 200 *	69.0	76.5	8 100*	71.9	75.3	7 400*	36.0
38.0	64.4	75.9	8 000 *	67.4	75.5	7 900*	70.4	74.3	7 200*	38.0
40.0	62.9	74.9	7 900 *	65.8	74.5	7 800*	68.8	73.2	6 900*	40.0
44.0	59.6	72.7	7 600 *	62.6	72.2	7 600*	65.5	70.9	6 500*	44.0
48.0	56.3	70.1	7 300 *	59.2	69.6	7 300*	62.0	68.3	6 000*	48.0
52.0	52.9	67.2	7 000 *	55.7	66.7	7 100*	58.5	65.3	5 700*	52.0
56.0	49.2	63.9	6 500	52.1	63.3	6 800*	54.7	61.9	5 400*	56.0
60.0	45.4	60.1	5 400	48.2	59.5	5 800	50.7	58.0	5 100*	60.0
64.0	41.2	55.8	4 500	44.0	55.1	4 800	46.4	53.4	4 900*	64.0
68.0	36.7	50.7	3 700	39.4	50.0	3 900	41.7	48.1	4 200	68.0
72.0	31.7	44.7	2 900	34.3	43.9	3 100				72.0
76.0	25.7	37.2	2 200	28.2	36.2	2 400				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
60.5m Boom										
16.8	80.5	86.1	9 900 *							16.8
18.0	79.6	85.8	9 900 *							18.0
20.0	78.3	85.4	9 700 *							20.0
22.0	76.9	84.9	9 600 *	79.8	84.5	9 200*				22.0
24.0	75.5	84.4	9 300 *	78.4	84.0	9 000*				24.0
26.0	74.1	83.9	9 100 *	77.0	83.4	8 800*	80.0	82.3	8 400*	26.0
28.0	72.7	83.2	9 000 *	75.6	82.8	8 700*	78.5	81.6	8 300*	28.0
30.0	71.2	82.6	8 800 *	74.1	82.1	8 500*	77.1	81.0	8 200*	30.0
32.0	69.8	81.8	8 600 *	72.7	81.4	8 400*	75.6	80.2	8 100*	32.0
34.0	68.3	81.0	8 400 *	71.2	80.6	8 300*	74.1	79.4	7 900*	34.0
36.0	66.9	80.2	8 300 *	69.8	79.7	8 100*	72.6	78.5	7 600*	36.0
38.0	65.4	79.3	8 100 *	68.3	78.8	8 000*	71.1	77.6	7 300*	38.0
40.0	63.9	78.3	7 900 *	66.8	77.8	7 900*	69.6	76.6	7 000*	40.0
44.0	60.8	76.2	7 600 *	63.7	75.7	7 600*	66.5	74.4	6 600*	44.0
48.0	57.7	73.7	7 300 *	60.5	73.2	7 300*	63.2	71.9	6 200*	48.0
52.0	54.4	71.0	7 100 *	57.2	70.4	7 100*	59.8	69.1	5 800*	52.0
56.0	51.0	67.8	6 200	53.7	67.3	6 700	56.3	65.8	5 500*	56.0
60.0	47.4	64.3	5 200	50.1	63.7	5 600	52.6	62.2	5 300*	60.0
64.0	43.5	60.3	4 200	46.2	59.7	4 600	48.6	58.0	4 900	64.0
68.0	39.4	55.6	3 400	42.1	55.0	3 700	44.3	53.2	4 000	68.0
72.0	34.9	50.2	2 700	37.4	49.5	2 900				72.0
76.0	29.7	43.7	2 000	32.2	42.9	2 200				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating


European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
63.5m Boom										
16.8	80.8	89.1	9 900 *							16.8
18.0	80.0	88.9	9 800 *							18.0
20.0	78.7	88.5	9 700 *							20.0
22.0	77.3	88.0	9 500 *	80.2	87.6	9 100*				22.0
24.0	76.0	87.5	9 300 *	78.8	87.1	9 000*				24.0
26.0	74.6	87.0	9 100 *	77.5	86.5	8 800*	80.3	85.4	8 300*	26.0
28.0	73.3	86.4	9 000 *	76.1	85.9	8 700*	79.0	84.8	8 300*	28.0
30.0	71.9	85.7	8 800 *	74.7	85.3	8 500*	77.6	84.1	8 100*	30.0
32.0	70.5	85.0	8 600 *	73.3	84.6	8 400*	76.2	83.4	8 000*	32.0
34.0	69.1	84.3	8 400 *	71.9	83.8	8 200*	74.7	82.6	7 900*	34.0
36.0	67.7	83.5	8 300 *	70.5	83.0	8 100*	73.3	81.8	7 700*	36.0
38.0	66.3	82.6	8 100 *	69.1	82.1	8 000*	71.8	80.9	7 400*	38.0
40.0	64.9	81.6	7 900 *	67.6	81.2	7 900*	70.4	79.9	7 200*	40.0
44.0	61.9	79.6	7 600 *	64.7	79.1	7 600*	67.4	77.8	6 700*	44.0
48.0	58.9	77.3	7 300 *	61.6	76.8	7 400*	64.3	75.4	6 300*	48.0
52.0	55.8	74.6	7 100	58.5	74.1	7 200*	61.1	72.8	6 000*	52.0
56.0	52.5	71.7	6 000	55.2	71.1	6 500	57.7	69.7	5 600*	56.0
60.0	49.1	68.4	4 900	51.8	67.8	5 400	54.3	66.3	5 400*	60.0
64.0	45.6	64.6	4 000	48.2	64.0	4 400	50.5	62.4	4 700	64.0
68.0	41.7	60.3	3 200	44.3	59.7	3 500	46.6	57.9	3 800	68.0
72.0	37.6	55.4	2 400	40.1	54.7	2 700	42.2	52.8	3 000	72.0
76.0				35.5	48.8	2 000				76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
66.5m Boom										
18.3	80.1	91.9	9 700 *							18.3
20.0	79.0	91.5	9 600 *							20.0
22.0	77.8	91.1	9 500 *	80.5	90.7	9 400*				22.0
24.0	76.5	90.6	9 300 *	79.2	90.2	9 200*				24.0
26.0	75.2	90.1	9 100 *	77.9	89.7	9 100*	80.7	88.5	8 600*	26.0
28.0	73.8	89.5	9 000 *	76.6	89.1	8 900*	79.3	87.9	8 400*	28.0
30.0	72.5	88.9	8 800 *	75.2	88.5	8 700*	78.0	87.3	8 300*	30.0
32.0	71.2	88.2	8 700 *	73.9	87.8	8 600*	76.6	86.6	8 200*	32.0
34.0	69.8	87.5	8 500 *	72.6	87.0	8 400*	75.3	85.8	8 100*	34.0
36.0	68.5	86.7	8 300 *	71.2	86.2	8 300*	73.9	85.0	7 800*	36.0
38.0	67.1	85.9	8 100 *	69.8	85.4	8 100*	72.5	84.2	7 500*	38.0
40.0	65.7	85.0	8 000 *	68.4	84.5	8 000*	71.1	83.2	7 300*	40.0
44.0	62.9	83.0	7 700 *	65.6	82.5	7 700*	68.2	81.2	6 800*	44.0
48.0	60.0	80.8	7 400 *	62.7	80.3	7 500*	65.3	79.0	6 400*	48.0
52.0	57.1	78.3	7 000	59.7	77.8	7 200	62.2	76.4	6 100*	52.0
56.0	54.0	75.5	5 700	56.6	74.9	6 300	59.1	73.5	5 800*	56.0
60.0	50.8	72.3	4 700	53.4	71.8	5 200	55.8	70.3	5 500	60.0
64.0	47.4	68.8	3 700	50.0	68.2	4 100	52.3	66.6	4 500	64.0
68.0	43.8	64.8	2 900	46.4	64.2	3 300	48.6	62.5	3 600	68.0
72.0	40.0	60.2	2 200	42.5	59.6	2 500	44.6	57.8	2 800	72.0
76.0				38.3	54.3	1 800	40.3	52.3	2 000	76.0



Liftcrane Jib Capacities

Jib No. 134 With 3 810 mm Strut On
Boom No. 57
83 870 kg Crane Counterweight
19 960 kg Carbody Counterweight
360 Degree Rating

European Standards
14 m/s Maximum Wind thru 54.5m Boom
12 m/s with 57.5m and 60.5m Boom
10 m/s with 63.5m thru 75.5m Boom

15000 SERIES 2

Capacities based on
structural competence are
denoted by an asterisk (*).

24.4m Fixed Jib

Jib Oper. Rad. Meters	5 Degree Offset			15 Degree Offset			25 Degree Offset			Jib Oper. Rad. Meters
	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	Boom Ang. Deg.	Jib Point Elev. Meters	Jib Capacity Kilograms	
69.5m Boom										
18.3	80.5	94.9	9 700 *							18.3
20.0	79.4	94.6	9 600 *							20.0
22.0	78.2	94.2	9 500 *							22.0
24.0	76.9	93.7	9 300 *	79.6	93.3	9 200*				24.0
26.0	75.6	93.2	9 100 *	78.3	92.8	9 100*				26.0
28.0	74.4	92.7	9 000 *	77.0	92.2	8 900*	79.7	91.0	8 400*	28.0
30.0	73.1	92.0	8 800 *	75.7	91.6	8 700*	78.4	90.4	8 300*	30.0
32.0	71.8	91.4	8 700 *	74.4	90.9	8 600*	77.1	89.7	8 200*	32.0
34.0	70.5	90.7	8 500 *	73.1	90.2	8 400*	75.8	89.0	8 100*	34.0
36.0	69.2	89.9	8 300 *	71.8	89.5	8 300*	74.5	88.2	7 900*	36.0
38.0	67.9	89.1	8 200 *	70.5	88.7	8 200*	73.1	87.4	7 700*	38.0
40.0	66.6	88.3	8 000 *	69.2	87.8	8 000*	71.8	86.5	7 400*	40.0
44.0	63.9	86.4	7 700 *	66.5	85.9	7 800*	69.0	84.6	7 000*	44.0
48.0	61.1	84.2	7 400 *	63.7	83.7	7 500*	66.2	82.4	6 600*	48.0
52.0	58.3	81.8	6 700	60.8	81.3	7 200	63.3	80.0	6 200*	52.0
56.0	55.3	79.2	5 400	57.8	78.6	6 000	60.2	77.2	5 900*	56.0
60.0	52.3	76.2	4 300	54.8	75.6	4 800	57.1	74.2	5 300	60.0
64.0	49.1	72.8	3 400	51.6	72.3	3 900	53.8	70.7	4 300	64.0
68.0	45.7	69.1	2 600	48.2	68.5	3 000	50.4	66.8	3 300	68.0
72.0				44.6	64.2	2 200	46.7	62.5	2 500	72.0