



Drum And Lagging Chart

15000 SERIES 1, 2, 3, 4

| TANDEM DRUMS | | | | | | | | | | |
|--------------------------|---------------|------------------|--------------|------------------------|--------------------|--------------------------------------|------------------------|------------------------|---|-------------------------------------|
| Application | Drum Location | Drum Part Number | Type Of Drum | Drum Diameter | Drum Width | Optional Grooved Lagging Part Number | Lagging Diameter | Nominal Wire Rope Size | Drum or Lagging Groove Pitch ¹ | Minimum Wire Rope Size ² |
| LIFTCRANE - BASIC | | | | | | | | | | |
| Hoist | Rear | 195434 | Grooved | 21-1/4 in. (540 mm) | 37 in. (940 mm) | | | 26 mm | 1.057 in. (26.85 mm) | 1.025 in. (26.03 mm) |
| Whip | Front | 195434 | Grooved | 21-1/4 in. (540 mm) | 37 in. (940 mm) | | | 26 mm | 1.057 in. (26.85 mm) | 1.025 in. (26.03 mm) |
| Auxiliary | Boom Butt | 177379 | Bare | 19-1/2 in. (495 mm) | 37 in. (940 mm) | 502372 | 21-1/4 in. (540 mm) | 26 mm | 1.057 in. (26.85 mm) | 1.025 in. (26.03 mm) |
| | | | | | | 502382 | 21-1/4 in. (540 mm) | 1 in. | 1.042 in. (26.47 mm) | 1.010 in. (25.65 mm) |
| LIFTCRANE - LUFFING JIB | | | | | | | | | | |
| Hoist | Front | 195434 | Grooved | 21-1/4 in. (540 mm) | 37 in. (940 mm) | | | 26 mm | 1.057 in. (26.85 mm) | 1.025 in. (26.03 mm) |
| Hoist (Auxiliary) | Boom Butt | 177379 | Bare | 19-1/2 in. (495 mm) | 37 in. (940 mm) | 502372 | 21-1/4 in. (540 mm) | 26 mm | 1.057 in. (26.85 mm) | 1.025 in. (26.03 mm) |
| | | | | | | 502382 | 21-1/4 in. (540 mm) | 1 in. | 1.042 in. (26.47 mm) | 1.010 in. (25.65 mm) |
| CLAMSHELL - LIMITED DUTY | | | | | | | | | | |
| Closing | Front | 195434 | Grooved | 21-1/4 in. (540 mm) | 37 in. (940 mm) | | | 1 in. | 1.057 in. (26.85 mm) | |
| Holding | Rear | 195434 | Grooved | 21-1/4 in. (540 mm) | 37 in. (940 mm) | | | 1 in. | 1.057 in. (26.85 mm) | |

¹ Maximum wire rope diameter and width as wound on drum must not exceed drum or lagging groove pitch.

² Minimum recommended wire rope size for proper spooling.

When equipped with luffing jib, rear drum is used as luffing jib hoist.

NOTE: When optional laggings are used for liftcrane application, the recommended lagging for specific wire rope dia. must be used.