


Liftcrane Boom Capacities

18000

Boom No. 55-79A with 30,5 m Mast No. 56
239 500 kg Crane Counterweight
145 150 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds

14 m/s with 36,6 m thru 91,4 m Boom
10 m/s with 97,5 m thru 103,6 m Boom
7 m/s with 109,7 m thru 121,9 m Boom



LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and are calculated to comply with EN 13000, ISO 4305 and include factors based on a 4,0 degree tipping angle. Capacities based on structural competence are denoted by an asterisk (*).

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom point sheaves is considered part of main boom load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with mast up. Refer to boom rigging **No. A05379**, Wire Rope Specification chart **No. 8652-A or 8652-B** and Counterweight Arrangement chart **No. 8577-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to Operator's Manual for operating guidelines.

WIND CONDITIONS: Machine may be operated in winds stated in Maximum Operating Wind Speed table provided crane operator judgment is used to allow for wind effect on lifted load and other considerations noted on capacity chart are followed. Wind will have a considerable effect on load with a large "sail area" and must be compensated for accordingly by reducing load ratings, reducing operating speeds, or by a combination of both. Wind speed to be measured at boom point elevation. **Operation is not permitted when wind is above conditions stated in Maximum Operating Wind Speed table.** Park crane (upper inline with crawlers) with load block on ground or secured and position boom at 70 degrees. Lower boom onto blocking at ground level and haul in boom hoist wire rope just wire enough to tension mast straps when wind is above 22 m/s. Lower mast to ground when wind is above 34 m/s.

MACHINE TRAVEL: Machine to travel on a firm, level [up to 1 percent (0,5 degrees) grade] and uniformly supporting surface. *Travel with 100 percent of rated load prohibited.* Travel restricted to 90 percent of rated capacity with speed not to exceed 0,4 m/s. Boom must be within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specification chart **No. 8653-A** for travel on grade.

MAX PERMISSIBLE SLEWING SPEED: Slew operation with working load shall not exceed 0,4 m/s as measured at the operating radius. The amount of time to brake or start slewing a working load shall not be less than 2,5 seconds.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 11 811 mm crawlers, 1 524 mm treads, 9,1 m live mast, 30,5 m mast, 16 part boom hoist reeving, boom support straps, 239 500 kg crane counterweight and 145 150 kg carbody counterweight.

Maximum Boom Length Lifted Unassisted

Over End of Blocked Crawlers	Over Side of Crawlers
Boom Length	Boom Length
121,9 m	109,7 m
Load block, hook and weight ball on ground at start.	

Upper Boom Point Deduct


Deduct 270 kg from capacities when upper boom point No. A08516 is attached.

Boom Catwalks Deduct

Deduct 400 kg from capacities when boom catwalks are attached.

Liftcrane Boom Capacities

18000

Boom No. 55-79A with 30,5 m Mast No. 56
239 500 kg Crane Counterweight
145 150 kg Carbody Counterweight
360 Degree Rating
Maximum Operating Wind Speeds
14 m/s with 36,6 m thru 91,4 m Boom
10 m/s with 97,5 m thru 103,6 m Boom
7 m/s with 109,7 m thru 121,9 m Boom


Upper Boom Point Capacity For Liftcrane Service - Whip Line		
28 mm		32 mm
Drum 2	Drum 3	Drum 2
Single Part Line		
16 240 kg	13 610 kg	22 140 kg
Two Part Line		
Upper Boom Point No. 170419		
27 220 kg	27 220 kg	27 220 kg
Upper Boom Point No. A08516		
32 480 kg	27 220 kg	44 270 kg
In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.		


Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
36,6 m (120 Ft.) Boom			
7,9	82,2	39,5	452 100 *
8,0	82,1	39,5	452 100 *
10,0	78,9	39,1	419 400 *
12,0	75,7	38,5	349 500 *
14,0	72,4	37,9	297 200 *
16,0	69,0	37,1	255 800 *
18,0	65,5	36,2	224 100 *
20,0	62,0	35,1	199 000 *
22,0	58,3	33,8	178 400 *
24,0	54,4	32,3	161 500 *
26,0	50,3	30,7	147 200 *
28,0	46,0	28,7	134 900 *
30,0	41,2	26,5	124 300 *
32,0	35,9	23,7	115 000 *
34,0	29,8	20,4	106 000 *
36,0	21,9	15,8	91 800 *

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
42,7 m (140 Ft.) Boom			
8,5	82,5	45,6	452 100 *
10,0	80,5	45,3	417 900 *
12,0	77,8	44,8	348 200 *
14,0	75,0	44,3	296 200 *
16,0	72,2	43,6	254 800 *
18,0	69,3	42,8	223 100 *
20,0	66,3	42,0	198 000 *
22,0	63,3	40,9	177 500 *
24,0	60,2	39,8	160 600 *
26,0	57,0	38,5	146 300 *
28,0	53,6	37,0	134 000 *
30,0	50,1	35,3	123 500 *
32,0	46,4	33,4	114 200 *
34,0	42,5	31,2	106 000 *
36,0	38,1	28,6	97 900 *
38,0	33,3	25,6	90 600 *
40,0	27,7	22,0	84 100 *
42,0	20,5	17,0	77 000 *

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
48,8 m (160 Ft.) Boom			
9,1	82,7	51,7	426 000 *
10,0	81,7	51,5	416 000 *
12,0	79,3	51,1	346 600 *
14,0	76,9	50,6	294 800 *
16,0	74,5	50,0	253 400 *
18,0	72,0	49,4	221 800 *
20,0	69,5	48,6	196 600 *
22,0	66,9	47,7	176 200 *
24,0	64,3	46,8	159 300 *
26,0	61,6	45,7	144 900 *
28,0	58,9	44,4	132 700 *
30,0	56,0	43,1	122 200 *
32,0	53,1	41,6	113 000 *
34,0	50,0	39,9	104 800 *
36,0	46,8	38,0	96 900 *
38,0	43,3	35,9	89 500 *
40,0	39,7	33,5	83 100 *
42,0	35,7	30,7	77 200 *
44,0	31,2	27,5	72 000 *
46,0	26,0	23,5	67 200 *
48,0	19,4	18,3	62 800 *

Liftcrane Boom Capacities

18000

Boom No. 55-79A with 30,5 m Mast No. 56
239 500 kg Crane Counterweight
145 150 kg Carbody Counterweight
360 Degree Rating
Maximum Operating Wind Speeds
14 m/s with 36,6 m thru 91,4 m Boom
10 m/s with 97,5 m thru 103,6 m Boom
7 m/s with 109,7 m thru 121,9 m Boom



Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
54,9 m (180 Ft.) Boom			
9,8	82,9	57,7	372 200 *
10,0	82,6	57,7	372 200 *
12,0	80,5	57,3	346 500 *
14,0	78,4	56,9	294 300 *
16,0	76,2	56,4	252 900 *
18,0	74,1	55,8	221 300 *
20,0	71,9	55,1	196 200 *
22,0	69,6	54,4	175 700 *
24,0	67,4	53,5	158 700 *
26,0	65,0	52,6	144 400 *
28,0	62,7	51,5	132 200 *
30,0	60,3	50,4	121 700 *
32,0	57,8	49,1	112 500 *
34,0	55,3	47,7	104 300
36,0	52,6	46,2	96 600
38,0	49,9	44,5	89 200
40,0	47,0	42,6	82 700
42,0	44,0	40,5	76 900
44,0	40,8	38,2	71 700
46,0	37,4	35,6	66 900
48,0	33,7	32,7	62 600
50,0	29,5	29,2	58 600
52,0	24,7	25,0	55 000
54,0	18,6	19,5	51 600

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
61,0 m (200 Ft.) Boom			
11,0	82,5	63,7	342 000 *
12,0	81,5	63,5	340 700 *
14,0	79,6	63,2	294 200 *
16,0	77,6	62,7	252 800 *
18,0	75,7	62,2	221 200 *
20,0	73,7	61,6	196 100 *
22,0	71,8	60,9	175 600 *
24,0	69,7	60,1	158 700 *
26,0	67,7	59,3	144 400 *
28,0	65,6	58,4	132 100 *
30,0	63,5	57,4	121 600 *
32,0	61,4	56,3	112 400 *
34,0	59,2	55,1	104 300 *
36,0	56,9	53,8	96 700
38,0	54,6	52,3	89 400
40,0	52,3	50,8	82 900
42,0	49,8	49,1	77 100
44,0	47,2	47,2	71 900
46,0	44,5	45,2	67 100
48,0	41,7	42,9	62 800
50,0	38,7	40,5	58 900
52,0	35,5	37,7	55 200
54,0	32,0	34,5	51 900
56,0	28,1	30,9	48 800
58,0	23,5	26,5	45 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
67,1 m (220 Ft.) Boom			
11,6	82,6	69,8	309 800 *
12,0	82,3	69,7	309 800 *
14,0	80,5	69,4	287 100 *
16,0	78,8	68,9	251 400 *
18,0	77,0	68,5	220 600 *
20,0	75,3	67,9	195 300 *
22,0	73,5	67,3	174 800 *
24,0	71,7	66,7	157 900 *
26,0	69,9	65,9	143 600 *
28,0	68,0	65,1	131 400 *
30,0	66,1	64,2	120 800 *
32,0	64,2	63,2	111 600 *
34,0	62,3	62,2	103 500 *
36,0	60,3	61,0	96 000
38,0	58,3	59,7	88 700
40,0	56,2	58,4	82 200
42,0	54,1	56,9	76 400
44,0	52,0	55,4	71 200
46,0	49,7	53,7	66 500
48,0	47,4	51,8	62 100
50,0	45,0	49,8	58 200
52,0	42,4	47,6	54 600
54,0	39,8	45,2	51 300
56,0	36,9	42,6	48 200
58,0	33,9	39,6	45 400
60,0	30,6	36,3	42 700
62,0	26,9	32,5	40 200
64,0	22,6	27,9	37 800

Liftcrane Boom Capacities

18000

Boom No. 55-79A with 30,5 m Mast No. 56
239 500 kg Crane Counterweight
145 150 kg Carbody Counterweight
360 Degree Rating
Maximum Operating Wind Speeds
14 m/s with 36,6 m thru 91,4 m Boom
10 m/s with 97,5 m thru 103,6 m Boom
7 m/s with 109,7 m thru 121,9 m Boom



Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
73,2 m (240 Ft.) Boom			
12,2	82,8	75,8	287 400 *
14,0	81,3	75,6	268 000 *
16,0	79,7	75,2	235 800 *
18,0	78,1	74,7	211 800 *
20,0	76,5	74,3	192 500
22,0	74,9	73,7	174 700
24,0	73,3	73,1	157 500 *
26,0	71,6	72,4	143 200 *
28,0	69,9	71,7	131 000 *
30,0	68,2	70,9	120 500 *
32,0	66,5	70,0	111 300 *
34,0	64,8	69,0	103 200 *
36,0	63,0	68,0	95 800
38,0	61,2	66,9	88 500
40,0	59,4	65,7	82 000
42,0	57,6	64,4	76 200
44,0	55,7	63,0	71 000
46,0	53,7	61,6	66 300
48,0	51,7	60,0	62 000
50,0	49,7	58,3	58 000
52,0	47,5	56,4	54 400
54,0	45,3	54,5	51 100
56,0	43,0	52,3	48 000
58,0	40,6	50,0	45 200
60,0	38,1	47,4	42 500
62,0	35,4	44,6	40 000
64,0	32,5	41,5	37 700
66,0	29,4	38,0	35 600
68,0	25,8	34,0	33 500
70,0	21,8	29,2	31 600

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
79,2 m (260 Ft.) Boom			
13,7	82,2	81,8	255 100 *
14,0	82,0	81,7	250 700 *
16,0	80,5	81,4	220 800 *
18,0	79,1	81,0	198 200 *
20,0	77,6	80,5	180 100 *
22,0	76,1	80,0	165 300 *
24,0	74,6	79,5	152 800 *
26,0	73,1	78,8	140 900
28,0	71,5	78,2	129 300
30,0	70,0	77,4	119 200
32,0	68,4	76,6	110 300
34,0	66,9	75,8	102 300 *
36,0	65,3	74,8	94 900
38,0	63,7	73,8	87 700
40,0	62,0	72,8	81 200
42,0	60,4	71,6	75 400
44,0	58,7	70,4	70 200
46,0	56,9	69,1	65 400
48,0	55,2	67,7	61 100
50,0	53,4	66,2	57 200
52,0	51,5	64,6	53 600
54,0	49,6	62,9	50 200
56,0	47,6	61,0	47 200
58,0	45,6	59,1	44 300
60,0	43,5	57,0	41 700
62,0	41,3	54,7	39 200
64,0	39,0	52,2	36 900
66,0	36,6	49,6	34 700
68,0	34,1	46,6	32 700
70,0	31,3	43,4	30 800
72,0	28,3	39,7	29 000
74,0	24,9	35,5	27 300
76,0	21,1	30,6	25 600

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
85,3 m (280 Ft.) Boom			
13,7	82,8	87,9	221 300 *
14,0	82,6	87,9	220 700 *
16,0	81,2	87,6	210 900 *
18,0	79,9	87,2	186 800 *
20,0	78,5	86,8	169 700 *
22,0	77,1	86,3	155 600 *
24,0	75,7	85,8	143 800 *
26,0	74,3	85,2	133 700 *
28,0	72,9	84,6	125 000 *
30,0	71,5	83,9	116 600
32,0	70,1	83,2	107 800
34,0	68,6	82,4	100 100
36,0	67,2	81,5	93 200
38,0	65,7	80,6	87 000
40,0	64,2	79,7	80 800
42,0	62,7	78,6	74 900
44,0	61,1	77,5	69 700
46,0	59,6	76,3	64 900
48,0	58,0	75,1	60 600
50,0	56,4	73,7	56 700
52,0	54,7	72,3	53 100
54,0	53,0	70,8	49 800
56,0	51,3	69,2	46 700
58,0	49,6	67,5	43 900
60,0	47,7	65,6	41 200
62,0	45,9	63,7	38 800
64,0	43,9	61,6	36 500
66,0	41,9	59,4	34 300
68,0	39,8	57,0	32 300
70,0	37,6	54,4	30 400
72,0	35,3	51,6	28 600
74,0	32,9	48,5	26 900
76,0	30,2	45,2	25 300
78,0	27,4	41,4	23 700
80,0	24,1	37,0	22 300
82,0	20,5	31,9	20 900

Liftcrane Boom Capacities

18000

Boom No. 55-79A with 30,5 m Mast No. 56
239 500 kg Crane Counterweight
145 150 kg Carbody Counterweight
360 Degree Rating
Maximum Operating Wind Speeds
14 m/s with 36,6 m thru 91,4 m Boom
10 m/s with 97,5 m thru 103,6 m Boom
7 m/s with 109,7 m thru 121,9 m Boom


Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
91,4 m (300 Ft.) Boom			
15,2	82,3	93,9	195 200 *
16,0	81,8	93,8	192 000 *
18,0	80,5	93,4	177 300 *
20,0	79,3	93,0	159 900 *
22,0	78,0	92,6	146 400 *
24,0	76,7	92,1	135 200 *
26,0	75,4	91,6	125 600 *
28,0	74,1	91,0	117 300 *
30,0	72,8	90,4	110 000 *
32,0	71,5	89,7	103 600 *
34,0	70,1	88,9	97 400
36,0	68,8	88,2	90 600
38,0	67,4	87,3	84 500
40,0	66,0	86,4	79 000
42,0	64,6	85,5	73 900
44,0	63,2	84,4	68 800
46,0	61,8	83,4	64 000
48,0	60,4	82,2	59 700
50,0	58,9	81,0	55 700
52,0	57,4	79,7	52 200
54,0	55,9	78,4	48 800
56,0	54,4	76,9	45 800
58,0	52,8	75,4	42 900
60,0	51,2	73,8	40 300
62,0	49,5	72,1	37 800
64,0	47,8	70,2	35 500
66,0	46,1	68,3	33 400
68,0	44,3	66,3	31 400
70,0	42,4	64,1	29 400
72,0	40,5	61,7	27 700
74,0	38,5	59,2	26 000
76,0	36,4	56,5	24 400
78,0	34,2	53,6	22 800
80,0	31,8	50,4	21 400
82,0	29,3	46,9	20 000
84,0	26,5	43,0	18 700
86,0	23,4	38,5	17 400
88,0	19,9	33,2	16 200

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
97,5 m (320 Ft.) Boom			
15,2	82,8	100,0	180 300 *
16,0	82,3	99,9	177 400 *
18,0	81,1	99,6	167 300 *
20,0	79,9	99,2	151 700 *
22,0	78,7	98,8	138 700 *
24,0	77,5	98,4	127 800 *
26,0	76,3	97,9	118 700 *
28,0	75,1	97,3	110 700 *
30,0	73,9	96,8	103 800 *
32,0	72,7	96,1	97 600 *
34,0	71,4	95,4	92 100 *
36,0	70,2	94,7	87 200 *
38,0	68,9	93,9	82 400
40,0	67,6	93,1	77 000
42,0	66,3	92,2	72 100
44,0	65,0	91,3	67 600
46,0	63,7	90,3	63 400
48,0	62,4	89,2	59 100
50,0	61,1	88,1	55 100
52,0	59,7	86,9	51 500
54,0	58,3	85,7	48 200
56,0	56,9	84,4	45 100
58,0	55,5	83,0	42 300
60,0	54,0	81,5	39 700
62,0	52,5	80,0	37 200
64,0	51,0	78,4	34 900
66,0	49,5	76,7	32 800
68,0	47,9	74,8	30 800
70,0	46,3	72,9	28 900
72,0	44,6	70,9	27 100
74,0	42,9	68,7	25 400
76,0	41,1	66,5	23 800
78,0	39,2	64,0	22 200
80,0	37,3	61,4	20 800
82,0	35,3	58,6	19 500
84,0	33,1	55,5	18 200
86,0	30,9	52,2	16 900
88,0	28,4	48,6	15 700
90,0	25,8	44,5	14 600
92,0	22,8	39,9	13 500
96,0	15,3	27,7	10 900 *

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
103,6 m (340 Ft.) Boom			
16,8	82,4	106,0	142 200 *
18,0	81,7	105,8	141 500 *
20,0	80,5	105,4	139 900 *
22,0	79,4	105,1	132 000 *
24,0	78,3	104,6	120 800 *
26,0	77,2	104,2	111 900 *
28,0	76,0	103,7	104 200 *
30,0	74,9	103,1	97 500 *
32,0	73,7	102,5	91 700 *
34,0	72,6	101,9	86 400 *
36,0	71,4	101,2	81 700 *
38,0	70,2	100,5	77 400 *
40,0	69,0	99,7	73 500 *
42,0	67,8	98,9	69 700
44,0	66,6	98,0	65 400
46,0	65,4	97,1	61 400
48,0	64,2	96,1	57 600
50,0	62,9	95,1	54 100
52,0	61,7	94,0	50 500
54,0	60,4	92,8	47 200
56,0	59,1	91,6	44 100
58,0	57,8	90,4	41 300
60,0	56,5	89,0	38 600
62,0	55,1	87,6	36 200
64,0	53,7	86,2	33 900
66,0	52,3	84,6	31 800
68,0	50,9	83,0	29 700
70,0	49,5	81,3	27 800
72,0	48,0	79,4	26 000
74,0	46,4	77,6	24 300
76,0	44,9	75,5	22 700
78,0	43,3	73,4	21 200
80,0	41,6	71,2	19 800
82,0	39,9	68,8	18 400
84,0	38,1	66,2	17 200
86,0	36,2	63,5	15 900
88,0	34,3	60,6	14 700
90,0	32,2	57,4	13 600
92,0	30,0	54,0	12 500
96,0	25,1	46,1	8 600 *


Liftcrane Boom Capacities

18000

Boom No. 55-79A with 30,5 m Mast No. 56
239 500 kg Crane Counterweight
145 150 kg Carbody Counterweight
360 Degree Rating

Maximum Operating Wind Speeds

14 m/s with 36,6 m thru 91,4 m Boom
10 m/s with 97,5 m thru 103,6 m Boom
7 m/s with 109,7 m thru 121,9 m Boom



Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
109,7 m (360 Ft.) Boom			
16,8	82,8	112,1	135 400 *
18,0	82,1	111,9	135 300 *
20,0	81,1	111,6	133 700 *
22,0	80,0	111,3	125 000 *
24,0	78,9	110,9	114 700 *
26,0	77,9	110,4	106 000 *
28,0	76,8	110,0	98 500 *
30,0	75,7	109,4	92 100 *
32,0	74,6	108,9	86 300 *
34,0	73,6	108,3	81 300 *
36,0	72,5	107,6	76 700 *
38,0	71,4	107,0	72 600 *
40,0	70,2	106,2	68 900 *
42,0	69,1	105,5	65 400 *
44,0	68,0	104,6	62 200 *
46,0	66,9	103,8	59 200
48,0	65,7	102,9	55 800
50,0	64,6	101,9	52 300
52,0	63,4	100,9	49 200
54,0	62,2	99,8	46 200
56,0	61,0	98,7	43 300
58,0	59,8	97,6	40 400
60,0	58,6	96,3	37 800
62,0	57,3	95,0	35 300
64,0	56,1	93,7	33 000
66,0	54,8	92,3	30 900
68,0	53,5	90,8	28 900
70,0	52,2	89,2	26 900
72,0	50,8	87,6	25 200
74,0	49,4	85,9	23 500
76,0	48,0	84,1	21 900
78,0	46,6	82,2	20 400
80,0	45,1	80,2	18 900
82,0	43,6	78,1	17 600
84,0	42,0	75,8	16 300
86,0	40,4	73,5	15 100
88,0	38,8	71,0	13 900
90,0	37,0	68,4	12 700
92,0	35,2	65,6	11 700
96,0	31,3	59,3	9 300 *
100,0	27,0	51,9	7 100 *

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
115,8 m (380 Ft.) Boom			
18,3	82,4	118,1	116 700 *
20,0	81,5	117,8	116 000 *
22,0	80,5	117,5	115 000 *
24,0	79,5	117,1	109 500 *
26,0	78,5	116,7	100 300 *
28,0	77,5	116,2	93 100 *
30,0	76,5	115,7	86 800 *
32,0	75,5	115,2	81 200 *
34,0	74,4	114,7	76 300 *
36,0	73,4	114,0	71 900 *
38,0	72,4	113,4	67 900 *
40,0	71,3	112,7	64 200 *
42,0	70,3	112,0	60 900 *
44,0	69,2	111,2	57 900 *
46,0	68,1	110,4	55 000 *
48,0	67,1	109,6	52 400 *
50,0	66,0	108,7	50 000 *
52,0	64,9	107,7	47 200
54,0	63,8	106,7	44 300
56,0	62,7	105,7	41 600
58,0	61,5	104,6	39 000
60,0	60,4	103,4	36 600
62,0	59,3	102,2	34 200
64,0	58,1	101,0	31 900
66,0	56,9	99,7	29 800
68,0	55,7	98,3	27 800
70,0	54,5	96,9	25 900
72,0	53,3	95,4	24 100
74,0	52,0	93,8	22 400
76,0	50,7	92,2	20 800
78,0	49,4	90,5	19 300
80,0	48,1	88,7	17 800
82,0	46,7	86,8	16 500
84,0	45,3	84,8	15 200
86,0	43,9	82,7	14 000
88,0	42,4	80,5	12 800
90,0	40,9	78,2	11 700
92,0	39,4	75,8	10 500 *
96,0	36,1	70,5	8 200 *

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
121,9 m (400 Ft.) Boom			
18,3	82,8	124,2	99 800 *
20,0	82,0	124,0	99 800 *
22,0	81,0	123,7	99 800 *
24,0	80,1	123,3	99 500 *
26,0	79,1	122,9	95 600 *
28,0	78,1	122,5	88 300 *
30,0	77,2	122,0	82 100 *
32,0	76,2	121,5	76 800 *
34,0	75,2	121,0	71 900 *
36,0	74,3	120,4	67 600 *
38,0	73,3	119,8	63 800 *
40,0	72,3	119,2	60 200 *
42,0	71,3	118,5	57 000 *
44,0	70,3	117,7	54 100 *
46,0	69,3	117,0	51 400 *
48,0	68,3	116,2	48 900 *
50,0	67,3	115,3	46 500 *
52,0	66,2	114,4	44 300 *
54,0	65,2	113,5	42 200 *
56,0	64,2	112,5	40 000
58,0	63,1	111,5	37 500
60,0	62,0	110,4	35 100
62,0	61,0	109,3	32 900
64,0	59,9	108,2	30 800
66,0	58,8	106,9	28 900
68,0	57,7	105,7	27 000
70,0	56,5	104,3	25 100
72,0	55,4	103,0	23 300
74,0	54,2	101,5	21 600
76,0	53,0	100,0	20 000
78,0	51,8	98,4	18 500
80,0	50,6	96,8	17 100
82,0	49,4	95,1	15 700
84,0	48,1	93,3	14 400
86,0	46,8	91,4	13 200
88,0	45,5	89,4	12 000
90,0	44,2	87,4	10 900
92,0	42,8	85,2	9 700 *
96,0	39,9	80,5	7 400 *