

Drum and Lagging Chart

MLC90A-1

Application	Drum Number and Location	Drum Part Number	Type Of Drum	Drum Diameter	Drum Width	Wire Rope Size
LIFTCRANE						
Hoist	Drum 2 (Rear)	84054285 (with free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm
		84054279 (without free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm
Whip or Auxiliary	Drum 1 (Front)	84054282 (with free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm
		84054276 (without free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm
Auxiliary (Optional)	Drum 3 (Rotating Bed)	84054290	Grooved	454 mm (17-7/8 in.)	520 mm (20-1/2 in.)	22 mm
CLAMSHELL - LIMITED DUTY						
Closing	Drum 1 (Front)	84054282 (with free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm
		84054276 (without free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm
Holding	Drum 2 (Rear)	84054285 (with free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm
		84054279 (without free-fall)	Grooved	709 mm (27-15/16 in.)	559 mm (22 in.)	26 mm