

Liftcrane Boom Capacities

Boom No. B10:290

45,400 lb Crane Counterweight

0 lb Carbody Counterweight

360 Degree Rating

MLC90A-1 SERIES 1



LIFTING CAPACITIES: Lifting capacities for various boom lengths and operating radii are for freely suspended loads and may be based on percent of static tipping or strength of structural components. Capacities must be reduced by applicable deducts.

Upper boom point capacity for liftcrane service with single part whip line from Drum 3 is 20,000 lb. When Drum 1 or Drum 2 is used, capacity with single part whip line is 27,600 lb. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom point sheaves, is considered part of load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate on a firm, level, and uniformly supporting surface. Refer to Boom Rigging **No. 80121887**, Wire Rope Specifications chart **No. 9751-A**, Counterweight Arrangements chart **No. 9745-A**, and Wind Conditions chart **No. 9750-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, travel, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.

MACHINE TRAVEL: Machine to travel on a firm, level, and uniformly supporting surface. Boom must be within boom angle range shown in capacity chart. Refer to Maximum Allowable Travel Specifications chart **No. 9749-A**.



OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block.



BOOM ANGLE: Boom angle in degrees (°) is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.



BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 21 ft 3 in. crawlers, 35 in. treads, 14 ft 5 in. gantry, 8 part boom hoist reeving, two 32 mm boom pendants, 45,400 lb crane counterweight, and 0 lb carbody counterweight.

Consult chart **No. 9753-A** when Jib No. 117 is attached.

Upper Boom Point Deduct

Deduct 600 lb from capacities when upper boom point is attached. Deduct does not apply to 62.3 ft boom length.

Third Line Deduct

Deduct 300 lb from capacities when boom top is equipped with optional 3rd sheave wire rope guide.

Deduct From Capacities When Jib No. 117 Is Attached

Jib Length (ft)	Deduct (lb)
30.0	4,500
40.0	5,300
50.0	6,200
60.0	7,400

Weight of jib and 700 lb suspended beneath jib point have been included in determination of deduct.


Refer to Table 1 for raising ability with the maximum weight of all load blocks, hooks, weight ball, slings, and hoist lines beneath boom point sheaves. For block weights shown with #, load blocks, hooks, weight ball, and slings must remain on ground until combined weights are within rated capacity of chart. Raising is not permitted in shaded areas of table.

Combined weight beneath boom point sheaves must not exceed block weight shown.

Table 1

Boom Length (ft)	Over End or Side of Crawlers	Over End of Blocked Crawlers
	Block Weight (lb)	
62.3 - 131.2	3,800	3,800
141.1	2,650	2,650
150.9 - 160.8	700	700
170.6		700
180.4		#
Warning: Crane must remain in-line with crawlers when raising over end of blocked crawlers until operating radius is within 360 degree chart. <i>Crane tipping or structural damage can occur.</i>		

Explanation of Symbols



Boom No. B10:290



Crane Counterweight
+
Carbody Counterweight



360 Degree Rating




Boom Length



Operating Radius
(see page 1)



Boom Angle
(see page 1)




Boom Point Elevation
(see page 1)



Lifting Capacities
(see page 1)

B10



45,400 lb
+
0 lb




360°

62.3 ft				72.2 ft				82.0 ft			
ft	°	ft	lb	ft	°	ft	lb	ft	°	ft	lb
15	80.3	68.3	155,600	16	80.8	78.1	137,400	18	80.5	87.7	110,700
16	79.3	68.1	137,000	17	80.0	77.9	122,700	19	79.8	87.5	100,800
17	78.4	67.8	122,300	18	79.2	77.7	110,700	20	79.1	87.3	92,400
18	77.4	67.6	110,300	19	78.4	77.5	100,800	22	77.6	86.9	79,100
19	76.5	67.4	100,400	20	77.6	77.3	92,500	24	76.2	86.4	69,000
20	75.5	67.1	92,100	22	75.9	76.8	79,200	26	74.8	85.9	61,100
22	73.6	66.5	78,800	24	74.3	76.2	69,100	28	73.3	85.3	54,700
24	71.7	65.9	68,800	26	72.6	75.6	61,200	30	71.8	84.6	49,500
26	69.7	65.2	60,900	28	70.9	74.9	54,800	32	70.4	83.9	45,000
28	67.8	64.4	54,500	30	69.2	74.2	49,600	34	68.9	83.2	41,300
30	65.8	63.5	49,200	32	67.5	73.3	45,200	36	67.3	82.3	38,100
32	63.7	62.5	44,800	34	65.8	72.5	41,400	38	65.8	81.4	35,300
34	61.6	61.4	41,100	36	64.0	71.5	38,200	40	64.3	80.5	32,800
36	59.5	60.3	37,900	38	62.2	70.5	35,400	42	62.7	79.5	30,600
38	57.3	59.0	35,100	40	60.4	69.3	32,900	44	61.1	78.4	28,700
40	55.1	57.6	32,600	42	58.6	68.1	30,800	46	59.5	77.2	26,900
42	52.8	56.1	30,500	44	56.7	66.8	28,800	48	57.8	76.0	25,400
44	50.4	54.5	28,500	46	54.7	65.4	27,100	50	56.2	74.6	23,900
46	48.0	52.7	26,800	48	52.7	63.9	25,500	55	51.8	70.9	20,900
48	45.4	50.8	25,200	50	50.7	62.3	24,100	60	47.2	66.6	18,400
50	42.7	48.7	23,800	55	45.3	57.7	21,100	65	42.2	61.4	16,400
55	35.3	42.4	20,700	60	39.3	52.1	18,600	70	36.6	55.2	14,700
60	26.1	33.7	18,300	65	32.5	45.0	16,600	75	30.2	47.5	13,200
				70	23.9	35.5	14,800	80	22.1	37.0	11,900

MLC90A-1 S-1

ASME B30.5



45,400 lb
+
0 lb




91.9 ft			
ft	°	ft	lb
19	80.9	97.5	100,800
20	80.3	97.4	92,400
22	79.0	97.0	79,100
24	77.7	96.5	69,000
26	76.4	96.1	61,100
28	75.1	95.5	54,700
30	73.8	95.0	49,400
32	72.5	94.3	45,000
34	71.2	93.7	41,200
36	69.9	92.9	38,000
38	68.6	92.2	35,200
40	67.2	91.3	32,700
42	65.8	90.4	30,600
44	64.5	89.5	28,600
46	63.1	88.5	26,900
48	61.6	87.4	25,300
50	60.2	86.3	23,900
55	56.5	83.1	20,900
60	52.7	79.5	18,400
65	48.6	75.4	16,300
70	44.3	70.5	14,600
75	39.6	64.9	13,200
80	34.3	58.1	11,900
85	28.2	49.7	10,800
90	20.5	38.4	9,800

101.7 ft			
ft	°	ft	lb
22	80.1	107.0	79,000
24	78.9	106.6	68,900
26	77.8	106.2	61,000
28	76.6	105.7	54,500
30	75.4	105.2	49,300
32	74.3	104.6	44,800
34	73.1	104.0	41,100
36	71.9	103.4	37,900
38	70.7	102.7	35,000
40	69.5	102.0	32,600
42	68.3	101.2	30,400
44	67.1	100.3	28,400
46	65.9	99.4	26,700
48	64.6	98.5	25,100
50	63.4	97.5	23,700
55	60.1	94.8	20,700
60	56.8	91.6	18,200
65	53.4	88.1	16,100
70	49.8	84.1	14,400
75	45.9	79.5	13,000
80	41.8	74.2	11,700
85	37.4	68.0	10,600
90	32.4	60.8	9,600
95	26.6	51.7	8,700

111.5 ft			
ft	°	ft	lb
22	81.0	117.0	78,900
24	79.9	116.6	68,800
26	78.9	116.2	60,800
28	77.8	115.8	54,400
30	76.8	115.3	49,100
32	75.7	114.8	44,700
34	74.6	114.3	40,900
36	73.6	113.7	37,700
38	72.5	113.1	34,900
40	71.4	112.4	32,400
42	70.3	111.7	30,200
44	69.2	111.0	28,300
46	68.1	110.2	26,500
48	67.0	109.3	25,000
50	65.9	108.4	23,500
55	63.0	106.0	20,500
60	60.1	103.2	18,000
65	57.1	100.1	16,000
70	53.9	96.6	14,300
75	50.7	92.7	12,800
80	47.2	88.3	11,500
85	43.6	83.3	10,400
90	39.7	77.6	9,500
95	35.5	71.0	8,600
100	30.7	63.2	7,800
105	25.1	53.6	7,100

B10




45,400 lb
+
0 lb



360°

121.4 ft				131.2 ft				141.1 ft			
ft	°	ft	lb	ft	°	ft	lb	ft	°	ft	lb
24	80.7	126.6	68,700	26	80.6	136.3	60,500	28	80.4	145.9	54,000
26	79.8	126.3	60,700	28	79.7	135.9	54,100	30	79.6	145.5	48,700
28	78.8	125.9	54,300	30	78.8	135.5	48,800	32	78.7	145.2	44,200
30	77.9	125.5	49,000	32	77.9	135.1	44,400	34	77.9	144.7	40,400
32	76.9	125.0	44,500	34	77.0	134.6	40,600	36	77.1	144.3	37,200
34	75.9	124.5	40,800	36	76.1	134.1	37,400	38	76.2	143.8	34,400
36	74.9	124.0	37,500	38	75.2	133.6	34,500	40	75.4	143.3	31,900
38	74.0	123.4	34,700	40	74.3	133.1	32,100	42	74.6	142.7	29,700
40	73.0	122.8	32,200	42	73.4	132.5	29,900	44	73.7	142.1	27,700
42	72.0	122.1	30,000	44	72.5	131.8	27,900	46	72.9	141.5	26,000
44	71.0	121.5	28,100	46	71.5	131.2	26,200	48	72.0	140.9	24,400
46	70.0	120.7	26,300	48	70.6	130.5	24,600	50	71.2	140.2	23,000
48	69.0	120.0	24,800	50	69.7	129.7	23,200	55	69.0	138.4	19,900
50	67.9	119.2	23,300	55	67.3	127.7	20,100	60	66.8	136.3	17,400
55	65.4	117.0	20,300	60	64.9	125.5	17,700	65	64.6	134.0	15,400
60	62.7	114.5	17,800	65	62.5	123.0	15,600	70	62.3	131.5	13,700
65	60.0	111.7	15,800	70	60.0	120.2	13,900	75	60.0	128.7	12,200
70	57.3	108.6	14,000	75	57.4	117.1	12,400	80	57.6	125.6	10,900
75	54.4	105.2	12,600	80	54.8	113.7	11,200	85	55.1	122.2	9,800
80	51.4	101.4	11,300	85	52.1	110.0	10,100	90	52.6	118.5	8,900
85	48.3	97.1	10,200	90	49.2	105.8	9,100	95	50.0	114.5	8,000
90	45.1	92.3	9,200	95	46.3	101.2	8,200	100	47.3	110.0	7,200
95	41.6	86.9	8,400	100	43.1	96.1	7,500	105	44.4	105.1	6,500
100	37.9	80.8	7,600	105	39.8	90.4	6,800	110	41.4	99.7	5,900
105	33.8	73.8	6,900	110	36.2	83.9	6,100	115	38.2	93.6	5,300
110	29.2	65.6	6,300	115	32.3	76.5	5,600	120	34.8	86.8	4,800
115	23.9	55.4	5,700	120	27.9	67.7	5,000	125	31.0	79.0	4,300
				125	22.8	57.0	4,600	130	26.8	69.8	3,900



150.9 ft			
ft	°	ft	lb
30	80.3	155.6	48,500
32	79.5	155.2	44,000
34	78.7	154.8	40,300
36	77.9	154.4	37,000
38	77.2	153.9	34,200
40	76.4	153.4	31,700
42	75.6	152.9	29,500
44	74.8	152.4	27,500
46	74.0	151.8	25,800
48	73.2	151.2	24,200
50	72.4	150.6	22,800
55	70.4	148.9	19,700
60	68.4	147.0	17,200
65	66.3	144.9	15,200
70	64.2	142.5	13,500
75	62.1	140.0	12,000
80	59.9	137.2	10,700
85	57.7	134.1	9,600
90	55.4	130.8	8,600
95	53.1	127.1	7,800
100	50.6	123.1	7,000
105	48.1	118.8	6,300
110	45.5	114.1	5,700
115	42.8	108.9	5,100
120	39.9	103.1	4,600
125	36.8	96.7	4,100

160.8 ft			
ft	°	ft	lb
30	80.9	165.5	48,300
32	80.1	165.2	43,900
34	79.4	164.8	40,100
36	78.7	164.4	36,800
38	78.0	164.0	34,000
40	77.2	163.6	31,500
42	76.5	163.1	29,300
44	75.8	162.6	27,300
46	75.0	162.0	25,600
48	74.3	161.5	24,000
50	73.5	160.9	22,600
55	71.7	159.3	19,500
60	69.8	157.5	17,000
65	67.9	155.6	15,000
70	65.9	153.4	13,200
75	63.9	151.0	11,800
80	61.9	148.4	10,500
85	59.9	145.6	9,400
90	57.8	142.6	8,400
95	55.7	139.3	7,500
100	53.5	135.7	6,800
105	51.2	131.8	6,100
110	48.9	127.5	5,400
115	46.5	122.9	4,900
120	43.9	117.9	4,400
125	41.3	112.4	3,900


170.6 ft			
ft	°	ft	lb
32	80.7	175.2	43,700
34	80.0	174.8	39,900
36	79.3	174.5	36,600
38	78.7	174.1	33,800
40	78.0	173.6	31,300
42	77.3	173.2	29,100
44	76.6	172.7	27,100
46	75.9	172.2	25,400
48	75.2	171.7	23,800
50	74.5	171.1	22,400
55	72.8	169.7	19,300
60	71.0	168.0	16,800
65	69.2	166.2	14,800
70	67.4	164.1	13,000
75	65.6	161.9	11,600
80	63.7	159.5	10,300
85	61.8	156.9	9,200
90	59.9	154.1	8,200
95	57.9	151.1	7,400
100	55.9	147.8	6,600
105	53.8	144.2	5,900
110	51.7	140.4	5,300
115	49.5	136.2	4,700
120	47.3	131.8	4,200

MLC90A-1 S-1

ASME B30.5





B10



45,400 lb
+
0 lb



180.4 ft

			
 ft	 °	 ft	 lb
34	80.6	184.8	39,700
36	79.9	184.5	36,500
38	79.3	184.1	33,600
40	78.6	183.7	31,100
42	78.0	183.3	28,900
44	77.3	182.8	26,900
46	76.7	182.4	25,200
48	76.0	181.9	23,600
50	75.4	181.3	22,200
55	73.7	179.9	19,100
60	72.1	178.4	16,600
65	70.4	176.7	14,500
70	68.7	174.8	12,800
75	67.0	172.7	11,300
80	65.2	170.5	10,100
85	63.5	168.0	9,000
90	61.7	165.4	8,000
95	59.9	162.6	7,100
100	58.0	159.5	6,300
105	56.1	156.3	5,700
110	54.2	152.8	5,000
115	52.2	149.0	4,500
120	50.1	144.9	3,900

REFERENCE ONLY!