



DRUM AND LAGGING CHART

888 SERIES 1
888 SERIES 2

TANDEM DRUMS								
BOOM NO. 22E WITH OPEN THROAT TOP								
APPLI CATION	DRUM LOCATI ON	DRUM PART NUMBER	TYPE OF DRUM	DRUM DI AMETER	DRUM WI DTH	OPTI ONAL GROOVED LAGGI NG PART NUMBER	LAGGI NG DI AMETER	WI RE ROPE SI ZE
LI FT CRANE								
HOI ST	FRONT	176516	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
WHI P	REAR	176516	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
						502373	27" (686 mm)	26 mm
						502383	27" (686 mm)	1"
HOI ST (AUXI LI ARY)	BOOM BUTT	177379	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
CLAMSHELL								
CLOSI NG	FRONT	176516			37" (940 mm)	502374	21-1/4" (540 mm)	1" OR 26 mm
HOLDI NG	REAR	176516			37" (940 mm)	502374	21-1/4" (540 mm)	1" OR 26 mm
BOOM NO. 22E WITH LIGHT TAPERED TOP								
LI FT CRANE								
HOI ST	FRONT	176516	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
WHI P	REAR	176516	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
						502373	27" (686 mm)	26 mm
						502383	27" (686 mm)	1"

NOTE: WHEN OPTIONAL LAGGINGS ARE USED FOR LI FT CRANE APPLI CATION, THE RECOMMENDE D LAGGI NG FOR SPECI FIC WI RE ROPE DI A. MUST BE USED.



DRUM AND LAGGING CHART

888 SERIES 1
888 SERIES 2

TANDEM DRUMS								
BOOM NO. 22EL								
APPLI CATION	DRUM LOCATI ON	DRUM PART NUMBER	TYPE OF DRUM	DRUM DI AMETER	DRUM WI DTH	OPTI ONAL GROOVED LAGGI NG PART NUMBER	LAGGI NG DI AMETER	WI RE ROPE SI ZE
LI FT CRANE - BASI C								
HOI ST	REAR	176516	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
WHI P	FRONT	176516	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
						502373	27" (686 mm)	26 mm
						502383	27" (686 mm)	1"
AUXI LI ARY	BOOM BUTT	177379	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
CLAM SHELL								
CLOS I NG	FRONT	176516			37" (940 mm)	502374	21-1/4" (540 mm)	1" OR 26 mm
HOLD I NG	REAR	176516			37" (940 mm)	502374	21-1/4" (540 mm)	1" OR 26 mm
LI FT CRANE - LUFFI NG JI B								
HOI ST	FRONT	176516	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"
HOI ST (AUXI LI ARY)	BOOM BUTT	177379	BARE	19-1/2" (495 mm)	37" (940 mm)	502372	21-1/4" (540 mm)	26 mm
						502382	21-1/4" (540 mm)	1"

REAR DRUM EQUIPPED WITH LAGGING NO. 502372 OR NO. 502382 IS REQUIRED FOR USE AS LUFFING JIB HOIST. RECOMMENDED LAGGING FOR SPECIFIC WIRE ROPE DIA. MUST BE USED.

NOTE: WHEN OPTIONAL LAGGINGS ARE USED FOR LI FT CRANE APPLI CATION, THE RECOMMENDED LAGGING FOR SPECIFIC WIRE ROPE DIA. MUST BE USED.