

## **Drum and Lagging Chart**

## MLC150-1

Application	Drum Number and Location	Drum Part Number	Type Of Drum	Drum Diameter	Drum Width	Wire Rope Size
LIFTCRANE						
Hoist	Drum 1 (Front)	80115483 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
		80115477 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
Whip or Luffing	Drum 2 (Rear)	80115488 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
		80115486 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
Auxiliary (Optional)	Drum 3 (Rotating Bed)	80115492	Grooved	454 mm (17-7/8 in.)	724 mm (20-1/2 in.)	22 mm
CLAMSHELL - LIMITED DUTY						
Closing	Drum 1 (Front)	80115483 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
	<b>/</b> -	80115477 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
Holding	Drum 2 (Rear)	80115488 (with free fall)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm
		80115486 (full power)	Grooved	709 mm (27-15/16 in.)	750 mm (29-1/2 in.)	26 mm