

# Hup M 28-22

### The crane for all your projects

**Height Under Hook:** 19,6 m - 31,1 m (raised jib at 30°)

Jib radius: 28 m Maximum load: 2,2 t

Max. load at jib end: 700 kg or 850 kg\*

Transport axle: 80 km/h on road (depends on the local regulations)



## Hup M 28-22

### The crane for all your projects



#### M for Mobile: ready for the road

- Integrated transport axle 80 km/h to transport the crane direct on the road from one jobsite to another one whatever the distance or 25 km/h transport axle
- EBS braking system
- One single package with permanent ballast
- Fith wheel or tow bar
- Compact dimensions: the only self-erecting crane with 28 m jib in such a compact transport format



- Easy moving thanks to the double steering axle, controled from the remote control
- Maximum steering radius +20°/-20° in order to reach the most confined areas



dual steering axle +20°/-20°

- Dual wheels to face any terrain type
- Hydraulic leveling controled from the remote control
- Integrated battery pack to ensure the steering axle movements and the hydraulic leveling is easily achieved



## High performance, versatile and ergonomic crane

- Lastest mechanims generation: LVF Optima DVF optima, HPS High Performance Slewing
- 16 jib configurations, 2 footprint options
- Crane erection and folding by one operator only thanks to the remote control
- Smart Set-up: simple and reactive interface and always the operator driving customisation, high precision speed

#### **New Smart Set-up**



steering axle control



hydraulic leveling control



#### Hup M 28-22: return on investment

- Maximum mobility for a self-erecting crane
- A real tower crane productivity on site
- Potain CONNECT solution
- The Smart Set-up advanced operating software
- An environment friendly crane on the jobsite