

## Special applications

National Crane boom trucks offer special application configurations including Wireline, for oil field applications. National Crane also offers more models, boom lengths, jib options and capacities than other manufacturers of tractor mount cranes.

### ➤ Wireline



### ➤ Tractor mount



## Truck Mod Center™

### Unique truck configurations

- Tool boxes
- Pintle-hitches
- Outrigger cribbing and stowage
- Wheelbase rolls
- Lift axles
- Truck backup cameras

## Lift Solutions™

### Options and Lift Solutions

- Hydraulic hose reels
- Wireless anti-two-block
- Bulkhead and flat-bed options
- Camera systems
- Wireless radio remotes

## The Manitowoc Company, Inc.

### Regional headquarters

#### Americas

Manitowoc,  
Wisconsin, USA  
Tel: +1 920 684 6621

Shady Grove,  
Pennsylvania, USA  
Tel: +1 717 597 8121

#### Europe, Middle East, Africa

Dardilly, France -  
TOWERS  
Tel: +33 472 18 20 20

Wilhelmshaven,  
Germany - MOBILE  
Tel: +49 (0) 4421 294 01

#### China

Shanghai, China  
Tel: +86 21 6457 0066

#### Greater Asia-Pacific

Singapore  
Tel: +65 6264 1188

Dubai, UAE  
Tel: +971 4 8862677

## National Crane range

### Pocket guide



This document is non-contractual. Constant improvement and engineering progress make it necessary that we reserve the right to make specification, equipment, and price changes without notice. Illustrations shown may include optional equipment and accessories and may not include all standard equipment.



## Telescoping crane - stand up controls

Model				
<b>400B</b>	10 USt (9,1 t)	56 ft (17,1 m)	N/A (N/A)	66 ft (20,1 m)
<b>500E2</b>	18 USt (16,3 t)	71 ft (21,6 m)	23 - 41 ft (7,0 - 12,5 m)	121 ft (36,9 m)
<b>600E2</b>	20 USt (18,1 t)	90 ft (27,4 m)	25 - 45 ft (7,6 - 13,7 m)	144 ft (43,9 m)
<b>800D</b>	23 USt (20,9 t)	100 ft (30,5 m)	25 - 44 ft (7,6 - 13,4 m)	152 ft (46,3 m)
<b>900A</b>	26 USt (23,6 t)	103 ft (31,4 m)	25 - 44 ft (7,6 - 13,4 m)	155 ft (47,2 m)



National Crane offers the broadest range of telescoping cranes with stand up controls. Capacities range from 10 USt – 33 USt (9,1 t – 29,9 t), and National Crane boom trucks have the most available options and mounting configurations on the market.



## Telescoping crane - stand up controls

H-Series Model				
<b>600H</b>	20 USt (18,1 t)	90 ft (27,4 m)	25 - 45 ft (7,6 - 13,7 m)	144 ft (43,9 m)
<b>NBT30H-2</b>	30 USt (27,2 t)	110 ft (33,5 m)	25 - 44 ft (7,6 - 13,4 m)	163 ft (49,7 m)
<b>1400H</b>	33 USt (29,9 t)	127 ft (38,7 m)	30 ft (9,1 m)	164 ft (50,0 m)



The H Series models have multi-position outriggers that offer excellent setup flexibility for job site conditions. The Rated Capacity Limiter (RCL) displays the actual outrigger setup, crane configuration and diagnostic information.



## Telescoping crane - swing cab controls

Model				
<b>1300A*</b>	30 USt (27,2 t)	110 ft (33,5 m)	25 - 44 ft (7,6 - 13,4 m)	163 ft (49,7 m)
<b>1400A*</b>	33 USt (29,9 t)	127 ft (38,7 m)	30 ft (9,1 m)	164 ft (50,0 m)
<b>NBT40-2 Series</b>	40-45 USt (36,3 - 40,8 t)	142 ft (43,3 m)	31 - 55 ft (9,4 - 16,8 m)	204 ft (62,2m)
<b>NBT50 Series</b>	50-55 USt (45,4 t)	128 ft (39,0 m)	26 - 45 ft (7,9 - 13,7 m)	179 ft (54,6 m)
<b>NTC55</b>	55 USt (49,9 t)	128 ft (39,0 m)	26 - 45 ft (7,9 - 13,7 m)	179 ft (54,6 m)
<b>NBT50L/ NTC50L</b>	50 USt (45,4 t)	151 ft (45,7 m)	26 - 45 ft (7,9 - 13,7 m)	204 ft (62,2 m)
<b>NBT55L/ NTC55L</b>	55 USt (49,9 t)	151 ft (45,7 m)	26 - 45 ft (7,9 - 13,7 m)	204 ft (62,2 m)
<b>NBT60</b>	60 USt (54,4 t)	128 ft (39,0 m)	26 - 45 ft (7,9 - 13,7 m)	179 ft (54,6 m)
<b>NBT60L/ NTC60L</b>	60 USt (54,4 t)	151 ft (45,7 m)	26 - 45 ft (7,9 - 13,7 m)	204 ft (62,2 m)
<b>NBT60XL/ NTC60XL</b>	60 USt (54,4 t)	151 ft (45,7 m)	26 - 45 ft (7,9 - 13,7 m)	204 ft (62,2 m)

\* Also available with open seat controls



National Crane takes the boom truck into the next generation with advanced features such as tilting cabs, hydraulically removable counterweight and unmatched capacities.