

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Jobsite Travel

MLC300 SERIES 1 must be equipped with 135 200 kg (298,100 lb) VPC (Variable Position Counterweight); MLC300 SERIES 2 must be equipped with 175 200 kg (386,200 lb) VPC; MLC300 Series 3 must be equipped with 215 200 kg (474,400 lb) VPC. Refer to Wind Conditions chart for maximum wind speed for various boom lengths and capacity charts for maximum boom lengths lifted unassisted. Travel slowly and smoothly to avoid shock loading boom and rigging.

Warning: Maintain adequate clearance between boom and load blocks, hooks, or weight ball while traveling. The boom can buckle and collapse if load blocks, hooks or weight ball contact the boom.

1. Machine Travel With Load

- A. Machine can swing and travel with 360 degree rating.
- B. Grade in any direction must not exceed 1 percent (0.5 degrees).
- C. Travel surface must be firm, level and uniformly supporting. Capacity charts are based on static conditions; therefore judgment must be used to allow for dynamic effects of traveling with load. Carry load as close to ground as possible. Stabilize load with taglines.

2. Machine Travel Without Load - Without Boom Angle Adjustment on Grade

- A. Load blocks, hooks, weight ball, slings, hoist lines, etc., may be suspended beneath points or tied off to machine. Total combined suspended weight beneath points must not exceed 5 400 kg (12,000 lb).
- B. Machine to travel on a firm and uniformly supporting surface. Travel allowed with 360 degree swing up to 1 percent (0.5 degrees) grade; crane upperworks must be in-line with crawlers and grade when grade exceeds 1 percent. Side-to-side grade must not exceed 2 percent (1.1 degrees) measured at boom hinge pins.
- C. Refer to Tables 2 thru 4 for boom angle, boom length, and direction for various grades.
Before traveling onto grade:
 - Position machine **on a level surface** with grade in any direction not to exceed 1 percent (0.5 degrees).
 - Unlock the VPC.
 - **Adjust boom** within boom angle range shown in table.
 - Lock the VPC.VPC must be locked before traveling onto grade. **Do not adjust boom angle after crane has been traveled onto grade.** Boom angle is angle between horizontal and centerline of boom butt and inserts. Refer to Table 1 for grade vs. angle when traveling.
- D. Do not exceed 2 percent (1.1 degrees) side-to-side grade at boom hinge pins when cutting (turning on grade).
- E. **Warning:** Refer to Section 3 of the Operator Manual for setting of VPC Lockout Key Switch prior to traveling onto grade. *Crane could tip.*
- F. **Warning:** Travel prohibited for boom angle range not shown in Tables 2 thru 4. *Crane could tip.*

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

3. Machine Travel Without Load - With Boom Angle Adjustment on Grade

- A. Load blocks, hooks, weight ball, slings, hoist lines, etc., may be suspended beneath points or tied off to machine. Total combined suspended weight beneath points must not exceed 5 400 kg (12,000 lb).
- B. Machine to travel on a firm and uniformly supporting surface. Travel allowed with 360 degree swing up to 1 percent (0.5 degrees) grade; crane upperworks must be in-line with crawlers and grade when grade exceeds 1 percent. Side-to-side grade must not exceed 2 percent (1.1 degrees) measured at boom hinge pins.
- C. Refer to Tables 5 thru 7 for boom angle, boom length, and direction for various grades.

Before traveling onto grade:

- Position machine **on a level surface** with grade in any direction not to exceed 1 percent (0.5 degrees).
- Unlock the VPC.
- **Adjust boom** within boom angle range shown in table.
- Lock the VPC in the optimized travel position.

VPC must be locked in the optimized travel position before traveling onto grade. **Adjust boom** to remain within boom angle range shown in table **while traveling on grade**. Boom angle is angle between horizontal and centerline of boom butt and inserts. Refer to Table 1 for grade vs. angle when traveling.

- D. Do not exceed 2 percent (1.1 degrees) side-to-side grade at boom hinge pins when cutting (turning on grade).
- E. **Warning:** Refer to Folio F2327 for setting VPC into optimized travel position. *Crane could tip.*
- F. **Warning:** Travel prohibited for boom angle range not shown in Tables 5 thru 7. *Crane could tip.*

Table 1

Percent Grade Vs. Angle In Degrees	
Percent Grade	Angle
5	2.9
10	5.7
20	11.3
30	16.7

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 2a - Without Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
35,0	114.8	42 - 73	46 - 73	49 - 73	52 - 73
41,0	134.5	42 - 73	45 - 73	48 - 73	52 - 73
47,0	154.2	40 - 73	42 - 73	47 - 73	52 - 73
53,0	173.9	40 - 73	42 - 73	47 - 73	52 - 73
59,0	193.6	42 - 73	44 - 73	48 - 73	55 - 73
65,0	213.3	42 - 73	45 - 73	54 - 73	64 - 73
71,0	232.9	48 - 73	52 - 73	60 - 73	—
77,0	252.6	55 - 73	58 - 73	66 - 73	—
83,0	272.3	59 - 73	62 - 73	70 - 73	—

Table 2b - Without Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
35,0	114.8	40 - 70	40 - 67	40 - 61	—
41,0	134.5	40 - 70	40 - 67	40 - 61	—
47,0	154.2	40 - 70	40 - 67	40 - 61	—
53,0	173.9	40 - 70	40 - 67	40 - 56	—
59,0	193.6	40 - 70	40 - 67	40 - 54	40 - 45
65,0	213.3	40 - 70	40 - 67	40 - 58	40 - 50
71,0	232.9	43 - 70	43 - 67	43 - 61	43 - 52
77,0	252.6	51 - 70	51 - 67	51 - 61	51 - 55
83,0	272.3	54 - 70	54 - 67	54 - 61	54 - 56

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 3a - Without Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
35,0	114.8	42 - 73	46 - 73	49 - 73	52 - 73
38,0	124.7	42 - 73	44 - 73	47 - 73	52 - 73
41,0	134.5	42 - 73	45 - 73	48 - 73	52 - 73
44,0	144.4	42 - 73	43 - 73	46 - 73	52 - 73
47,0	154.2	40 - 73	42 - 73	47 - 73	52 - 73
50,0	164.0	41 - 73	43 - 73	48 - 73	52 - 73
53,0	173.9	40 - 73	42 - 73	46 - 73	52 - 73
56,0	183.7	41 - 73	41 - 73	46 - 73	52 - 73
59,0	193.6	42 - 73	44 - 73	46 - 73	52 - 73
62,0	203.4	41 - 73	43 - 73	46 - 73	52 - 73
65,0	213.3	42 - 73	44 - 73	47 - 73	52 - 73
68,0	223.1	41 - 73	43 - 73	48 - 73	54 - 73
71,0	232.9	40 - 73	42 - 73	48 - 73	64 - 73
74,0	242.8	41 - 73	44 - 73	53 - 73	71 - 73
77,0	252.6	43 - 73	46 - 73	56 - 73	—
80,0	262.5	47 - 73	51 - 73	60 - 73	—
83,0	272.3	49 - 73	53 - 73	61 - 73	—
86,0	282.2	52 - 73	55 - 73	64 - 73	—
89,0	292.0	54 - 73	58 - 73	66 - 73	—

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 3b - Without Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
35,0	114.8	40 - 70	40 - 67	40 - 61	—
38,0	124.7	40 - 70	40 - 67	40 - 61	—
41,0	134.5	40 - 70	40 - 67	40 - 61	—
44,0	144.4	40 - 70	40 - 67	40 - 61	—
47,0	154.2	40 - 70	40 - 67	40 - 61	—
50,0	164.0	40 - 70	40 - 67	40 - 61	—
53,0	173.9	40 - 70	40 - 67	40 - 61	—
56,0	183.7	40 - 70	40 - 67	40 - 52	—
59,0	193.6	40 - 70	40 - 67	40 - 47	—
62,0	203.4	40 - 70	40 - 67	40 - 46	—
65,0	213.3	40 - 70	40 - 67	40 - 48	—
68,0	223.1	40 - 70	40 - 67	40 - 50	40 - 42
71,0	232.9	40 - 70	40 - 67	40 - 51	40 - 42
74,0	242.8	40 - 70	40 - 67	40 - 54	40 - 46
77,0	252.6	40 - 70	40 - 67	40 - 55	40 - 47
80,0	262.5	44 - 70	44 - 67	44 - 58	44 - 50
83,0	272.3	45 - 70	45 - 67	45 - 58	45 - 51
86,0	282.2	48 - 70	48 - 67	48 - 59	48 - 52
89,0	292.0	50 - 70	50 - 67	50 - 60	50 - 54

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 4a - Without Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING DOWNHILL			
35,0	114.8	42 - 73	46 - 73
38,0	124.7	40 - 73	44 - 73
41,0	134.5	42 - 73	45 - 73
44,0	144.4	41 - 73	43 - 73
47,0	154.2	40 - 73	42 - 73
50,0	164.0	41 - 73	43 - 73
53,0	173.9	40 - 73	42 - 73
56,0	183.7	41 - 73	41 - 73
59,0	193.6	42 - 73	44 - 73
62,0	203.4	41 - 73	43 - 73
65,0	213.3	42 - 73	44 - 73
68,0	223.1	41 - 73	43 - 73
71,0	232.9	40 - 73	42 - 73
74,0	242.8	41 - 73	42 - 73
77,0	252.6	40 - 73	42 - 73
80,0	262.5	42 - 73	45 - 73
83,0	272.3	45 - 73	47 - 73
86,0	282.2	48 - 73	50 - 73
89,0	292.0	51 - 73	53 - 73

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 4b - Without Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING UPHILL			
35,0	114.8	40 - 70	40 - 67
38,0	124.7	40 - 70	40 - 67
41,0	134.5	40 - 70	40 - 67
44,0	144.4	40 - 70	40 - 67
47,0	154.2	40 - 70	40 - 67
50,0	164.0	40 - 70	40 - 67
53,0	173.9	40 - 70	40 - 67
56,0	183.7	40 - 70	40 - 67
59,0	193.6	40 - 70	40 - 67
62,0	203.4	40 - 70	40 - 67
65,0	213.3	40 - 70	40 - 67
68,0	223.1	40 - 70	40 - 67
71,0	232.9	40 - 70	40 - 67
74,0	242.8	40 - 70	40 - 67
77,0	252.6	40 - 70	40 - 67
80,0	262.5	40 - 70	40 - 67
83,0	272.3	41 - 70	41 - 67
86,0	282.2	45 - 70	45 - 67
89,0	292.0	47 - 70	47 - 67

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 5a - With Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
35,0	114.8	38 - 80	38 - 77	38 - 71	38 - 66
41,0	134.5	38 - 80	38 - 77	38 - 72	38 - 66
47,0	154.2	36 - 80	36 - 77	36 - 71	39 - 66
53,0	173.9	36 - 80	38 - 77	41 - 72	46 - 66
59,0	193.6	43 - 80	44 - 77	48 - 72	51 - 66
65,0	213.3	47 - 80	49 - 77	53 - 72	55 - 66
71,0	232.9	53 - 80	54 - 77	56 - 72	59 - 66
77,0	252.6	57 - 80	58 - 77	59 - 71	61 - 66
83,0	272.3	59 - 80	60 - 77	61 - 72	—

Table 5b - With Boom Angle Adjustment: SERIES 1

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
35,0	114.8	41 - 83	44 - 83	49 - 83	55 - 79
41,0	134.5	41 - 83	44 - 83	50 - 83	55 - 81
47,0	154.2	39 - 83	41 - 83	47 - 83	52 - 78
53,0	173.9	39 - 83	42 - 83	47 - 83	53 - 78
59,0	193.6	40 - 83	42 - 83	48 - 82	53 - 78
65,0	213.3	40 - 83	43 - 83	48 - 81	54 - 78
71,0	232.9	38 - 83	41 - 83	47 - 81	52 - 79
77,0	252.6	43 - 83	46 - 83	51 - 80	57 - 79
83,0	272.3	48 - 83	51 - 83	57 - 81	62 - 80

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 6a - With Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING DOWNHILL					
35,0	114.8	38 - 80	38 - 77	38 - 71	38 - 66
38,0	124.7	36 - 80	36 - 77	36 - 71	36 - 66
41,0	134.5	38 - 80	38 - 77	38 - 72	38 - 66
44,0	144.4	37 - 80	37 - 77	37 - 72	37 - 66
47,0	154.2	36 - 80	36 - 77	36 - 71	36 - 66
50,0	164.0	37 - 80	37 - 77	37 - 71	37 - 66
53,0	173.9	36 - 80	36 - 77	36 - 72	37 - 66
56,0	183.7	35 - 80	35 - 77	35 - 72	43 - 66
59,0	193.6	37 - 80	37 - 77	40 - 72	45 - 66
62,0	203.4	37 - 80	39 - 77	44 - 71	47 - 66
65,0	213.3	40 - 80	41 - 77	45 - 72	50 - 66
68,0	223.1	43 - 80	45 - 77	48 - 72	52 - 66
71,0	232.9	45 - 80	47 - 77	50 - 72	53 - 66
74,0	242.8	49 - 80	49 - 77	52 - 72	55 - 66
77,0	252.6	50 - 80	51 - 77	53 - 71	57 - 66
80,0	262.5	52 - 80	54 - 77	56 - 72	59 - 66
83,0	272.3	53 - 80	54 - 77	57 - 72	59 - 66
86,0	282.2	54 - 80	56 - 77	58 - 72	61 - 66
89,0	292.0	57 - 80	57 - 77	60 - 72	62 - 66

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 6b - With Boom Angle Adjustment: SERIES 2

MACHINE TRAVEL WITHOUT LOAD					
Boom Length		Boom Angle Range in Degrees			
		Maximum Percent Grade			
Meters	Feet	5%	10%	20%	30%
BOOM FACING UPHILL					
35,0	114.8	41 - 83	44 - 83	49 - 76	55 - 68
38,0	124.7	39 - 83	42 - 83	48 - 78	53 - 71
41,0	134.5	41 - 83	44 - 83	50 - 80	55 - 74
44,0	144.4	40 - 83	43 - 83	48 - 81	54 - 74
47,0	154.2	39 - 83	41 - 83	47 - 80	52 - 76
50,0	164.0	40 - 83	43 - 83	49 - 82	54 - 76
53,0	173.9	39 - 83	42 - 83	47 - 81	53 - 76
56,0	183.7	38 - 83	41 - 83	46 - 81	52 - 76
59,0	193.6	40 - 83	42 - 83	48 - 80	53 - 76
62,0	203.4	39 - 83	41 - 82	47 - 80	52 - 76
65,0	213.3	40 - 83	43 - 83	48 - 79	54 - 76
68,0	223.1	39 - 83	42 - 82	47 - 79	53 - 76
71,0	232.9	38 - 82	41 - 82	47 - 79	52 - 75
74,0	242.8	39 - 83	42 - 81	48 - 78	53 - 76
77,0	252.6	39 - 82	41 - 80	47 - 78	52 - 76
80,0	262.5	40 - 82	42 - 81	48 - 79	53 - 76
83,0	272.3	39 - 82	42 - 81	47 - 79	53 - 76
86,0	282.2	40 - 82	42 - 81	48 - 79	53 - 76
89,0	292.0	43 - 83	45 - 82	51 - 79	56 - 77

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 7a - With Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING DOWNHILL			
35,0	114.8	38 - 80	38 - 77
38,0	124.7	36 - 80	36 - 77
41,0	134.5	38 - 80	38 - 77
44,0	144.4	37 - 80	37 - 77
47,0	154.2	36 - 80	36 - 77
50,0	164.0	37 - 80	37 - 77
53,0	173.9	36 - 80	36 - 77
56,0	183.7	35 - 80	35 - 77
59,0	193.6	37 - 80	37 - 77
62,0	203.4	36 - 80	36 - 77
65,0	213.3	37 - 80	37 - 77
68,0	223.1	36 - 80	38 - 77
71,0	232.9	38 - 80	41 - 77
74,0	242.8	41 - 80	43 - 77
77,0	252.6	43 - 80	45 - 77
80,0	262.5	46 - 80	48 - 77
83,0	272.3	47 - 80	49 - 77
86,0	282.2	50 - 80	50 - 77
89,0	292.0	51 - 80	53 - 77

Maximum Allowable Travel Specifications

MLC300

Boom No. B45:505-500
with 7,0 m (23.0 ft) Extended Upper Boom Point

Table 7b - With Boom Angle Adjustment: SERIES 3

MACHINE TRAVEL WITHOUT LOAD			
Boom Length		Boom Angle Range in Degrees	
		Maximum Percent Grade	
Meters	Feet	5%	10%
BOOM FACING UPHILL			
35,0	114.8	41 - 83	44 - 78
38,0	124.7	39 - 83	42 - 81
41,0	134.5	41 - 83	44 - 82
44,0	144.4	40 - 83	43 - 83
47,0	154.2	39 - 83	41 - 83
50,0	164.0	40 - 83	43 - 83
53,0	173.9	39 - 83	42 - 83
56,0	183.7	38 - 83	41 - 83
59,0	193.6	40 - 83	42 - 83
62,0	203.4	39 - 83	41 - 82
65,0	213.3	40 - 83	43 - 82
68,0	223.1	39 - 83	42 - 81
71,0	232.9	38 - 82	41 - 80
74,0	242.8	39 - 82	42 - 80
77,0	252.6	39 - 81	41 - 79
80,0	262.5	40 - 81	42 - 80
83,0	272.3	39 - 81	42 - 79
86,0	282.2	38 - 80	41 - 79
89,0	292.0	41 - 81	44 - 80