

Liftcrane Boom Capacities

Boom No. 22EL
65 360 kg Counterweight
8 585 mm Crawlers Extended
Rating Over Front Of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements

888 SERIES 1

LIFTING CAPACITIES: Capacities for various boom lengths and operating radii are for freely suspended loads and do not exceed 75% of a static tipping load over front of machine with crawlers extended and blocked. Capacities based on structural competence are denoted by an asterisk (*). Capacities indicated by (b) require 5 670 kg minimum weight.

Upper boom point capacity for liftcrane service with single part whip line is 13 380 kg or 26 760 kg with two part whip line. When boom butt mounted auxiliary drum is used, capacity with single part whip line is 9 070 kg or 18 140 kg with two part whip line. In all cases, upper boom point capacities cannot exceed those listed for main boom capacity.

76.2m boom length requires only the middle two sheaves in lower boom point. All other sheaves must be removed from lower boom point.

Weight of jib, all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves, is considered part of main boom load. Boom is not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate in a level position on a firm uniformly supporting surface with gantry up, crawlers fully extended, and front tumbler properly blocked so that centerline of idler tumbler becomes tipping

fulcrum. Drive motors must be to rear of machine. Swing is limited to that sector shown on Operating Range Diagram **No. 7770-A**. Refer to boom rigging **No. 177156** or **No. 177353** and Wire Rope Specification chart **No. 7810-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to operators manual for operating guidelines.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation to center of vertical hoist line or load block. Boom angle is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

BOOM POINT ELEVATION: Boom point elevation is vertical distance from ground level to centerline of boom point shaft.

MACHINE EQUIPMENT: Machine equipped with 8 585 mm extendible crawlers, 1 219 mm treads, 3 124 mm retractable gantry, 9 144 mm live mast, 20 part boom hoist reeving, four 35 mm boom pendants and 65 360 kg counterweight.

Maximum Boom and Jib Lengths Lifted Unassisted Over Front of Blocked Crawlers	
Boom Length	Jib No. 134
(a) 76.2m	—
73.2m	—
70.1m	—
67.1m	18.3m
64.0m	24.4m
Load block, hook and weight ball on ground at start. (a) Upper boom point cannot be used on 76.2m boom.	

Deduct From Capacities When Jib Is Attached	
Jib Length	Jib No. 134
9.1m	1 220 kg
12.2m	1 590 kg
15.2m	1 950 kg
18.3m	2 310 kg
21.3m	2 770 kg
24.4m	3 220 kg

Consult jib chart for jib capacities. Upper boom point cannot be used when jib is attached.

Liftcrane Boom Capacities

888 SERIES 1

Meets
ANSI B30.5
Requirements

Boom No. 22EL
65 360 kg Counterweight
8 585 mm Crawlers Extended
Rating Over Front Of Blocked Crawlers
No Travel - Limited Swing

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
21.3m (70 Ft.) Boom			
4.9	82.8	23.5	184 300 *b
5.0	82.5	23.5	180 200 *b
5.5	81.1	23.4	164 600 *b
6.0	79.7	23.3	151 400 *b
7.0	77.0	23.1	130 300 *b
8.0	74.2	22.8	114 200 *
9.0	71.3	22.5	101 400 *
10.0	68.4	22.1	91 000 *
11.0	65.5	21.6	82 400
12.0	62.5	21.1	73 700
13.0	59.3	20.5	64 800
14.0	56.1	19.8	57 800
15.0	52.7	19.0	52 100
16.0	49.1	18.1	47 300
18.0	41.3	16.0	39 700
20.0	31.9	13.2	33 900
24.4m (80 Ft.) Boom			
5.2	83.0	26.6	173 800 *b
5.5	82.2	26.5	164 200 *b
6.0	81.0	26.4	151 100 *b
7.0	78.6	26.2	130 000 *b
8.0	76.2	26.0	113 800 *
9.0	73.8	25.7	101 100 *
10.0	71.3	25.3	90 700 *
11.0	68.8	24.9	82 100 *
12.0	66.2	24.5	73 800
13.0	63.5	24.0	64 900
14.0	60.9	23.4	57 900
15.0	58.1	22.8	52 200
16.0	55.2	22.1	47 300
18.0	49.1	20.4	39 700
20.0	42.4	18.4	34 000
22.0	34.5	15.7	29 500
24.0	24.5	11.9	25 800
27.4m (90 Ft.) Boom			
5.8	82.5	29.6	156 100 *b
6.0	82.0	29.5	150 900 *b
7.0	79.9	29.3	129 800 *b
8.0	77.8	29.1	113 600 *
9.0	75.6	28.9	100 900 *
10.0	73.4	28.6	90 500 *
11.0	71.2	28.2	81 900 *
12.0	69.0	27.8	73 800
13.0	66.7	27.4	65 000
14.0	64.4	26.9	58 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
27.4m (90 Ft.) Boom			
15.0	62.0	26.4	52 200
16.0	59.6	25.8	47 400
18.0	54.5	24.4	39 800
20.0	49.1	22.7	34 000
22.0	43.2	20.7	29 500
24.0	36.4	18.2	25 900
26.0	28.3	14.9	22 900
30.5m (100 Ft.) Boom			
6.1	82.7	32.6	148 400 *b
7.0	80.9	32.5	129 600 *b
8.0	79.0	32.3	113 500 *
9.0	77.1	32.0	100 700 *
10.0	75.1	31.7	90 400 *
11.0	73.2	31.4	81 800 *
12.0	71.2	31.1	73 800
13.0	69.2	30.7	65 100
14.0	67.1	30.3	58 100
15.0	65.1	29.8	52 300
16.0	62.9	29.3	47 400
18.0	58.6	28.1	39 900
20.0	54.0	26.7	34 100
22.0	49.1	25.0	29 600
24.0	43.8	23.1	26 000
26.0	37.9	20.6	23 000
28.0	31.0	17.6	20 500
30.0	22.2	13.4	18 300
33.5m (110 Ft.) Boom			
6.7	82.3	35.6	135 000 *
7.0	81.8	35.5	129 600 *
8.0	80.0	35.4	113 200 *
9.0	78.3	35.2	100 400 *
10.0	76.5	34.9	90 100 *
11.0	74.8	34.6	81 500 *
12.0	73.0	34.3	73 700
13.0	71.2	34.0	65 100
14.0	69.3	33.6	58 100
15.0	67.5	33.2	52 300
16.0	65.6	32.7	47 400
18.0	61.7	31.7	39 800
20.0	57.7	30.4	34 100
22.0	53.5	29.0	29 500
24.0	49.1	27.3	25 900
26.0	44.3	25.4	22 900
28.0	39.0	23.0	20 400
30.0	33.1	20.2	18 300
32.0	25.8	16.5	16 400

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
36.6m (120 Ft.) Boom			
6.7	82.9	38.7	134 800 *
7.0	82.5	38.6	129 400 *
8.0	80.9	38.5	113 000 *
9.0	79.3	38.3	100 300 *
10.0	77.7	38.0	89 900 *
11.0	76.1	37.8	81 300 *
12.0	74.4	37.5	73 600
13.0	72.8	37.2	65 100
14.0	71.1	36.8	58 100
15.0	69.5	36.5	52 300
16.0	67.8	36.1	47 500
18.0	64.3	35.1	39 800
20.0	60.7	34.0	34 000
22.0	57.0	32.8	29 500
24.0	53.2	31.3	25 900
26.0	49.1	29.6	22 900
28.0	44.7	27.7	20 400
30.0	40.0	25.4	18 300
32.0	34.7	22.7	16 400
34.0	28.5	19.3	14 800
36.0	20.6	14.7	13 400
39.6m (130 Ft.) Boom			
7.3	82.6	41.7	123 500 *
8.0	81.6	41.6	112 900 *
9.0	80.1	41.4	100 100 *
10.0	78.6	41.2	89 800 *
11.0	77.2	40.9	81 200 *
12.0	75.7	40.7	73 600
13.0	74.2	40.4	65 200
14.0	72.6	40.1	58 100
15.0	71.1	39.7	52 300
16.0	69.6	39.4	47 400
18.0	66.4	38.5	39 800
20.0	63.2	37.5	34 000
22.0	59.9	36.4	29 500
24.0	56.4	35.1	25 900
26.0	52.8	33.6	22 900
28.0	49.1	31.9	20 400
30.0	45.1	30.0	18 300
32.0	40.7	27.8	16 500
34.0	36.0	25.2	14 900
36.0	30.5	22.0	13 500
38.0	24.0	18.0	12 200

Liftcrane Boom Capacities

888 SERIES 1

Boom No. 22EL
65 360 kg Counterweight
8 585 mm Crawlers Extended
Rating Over Front Of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
42.7m (140 Ft.) Boom			
7.9	82.3	44.7	113 800 *
8.0	82.2	44.6	112 700 *
9.0	80.8	44.5	99 900 *
10.0	79.5	44.3	89 600 *
11.0	78.1	44.1	81 000 *
12.0	76.7	43.8	73 500
13.0	75.3	43.6	65 100
14.0	73.9	43.3	58 100
15.0	72.5	43.0	52 300
16.0	71.1	42.6	47 400
18.0	68.2	41.8	39 700
20.0	65.3	40.9	33 900
22.0	62.2	39.9	29 400
24.0	59.1	38.7	25 800
26.0	55.9	37.4	22 800
28.0	52.6	35.9	20 300
30.0	49.1	34.2	18 200
32.0	45.4	32.3	16 400
34.0	41.4	30.1	14 800
36.0	37.0	27.6	13 400
38.0	32.2	24.6	12 200
40.0	26.6	20.9	11 000
42.0	19.4	16.0	10 000
45.7m (150 Ft.) Boom			
7.9	82.8	47.7	110 700 *
8.0	82.7	47.7	110 000 *
9.0	81.4	47.6	99 800 *
10.0	80.2	47.4	89 200 *
11.0	78.9	47.2	80 700 *
12.0	77.6	47.0	73 400
13.0	76.3	46.7	65 100
14.0	75.0	46.4	58 000
15.0	73.7	46.2	52 200
16.0	72.4	45.8	47 300
18.0	69.7	45.1	39 600
20.0	67.0	44.3	33 800
22.0	64.3	43.3	29 300
24.0	61.4	42.3	25 600
26.0	58.5	41.1	22 700
28.0	55.5	39.7	20 100
30.0	52.3	38.2	18 000
32.0	49.1	36.5	16 200
34.0	45.6	34.6	14 600
36.0	41.9	32.5	13 200
38.0	37.9	30.0	12 000
40.0	33.6	27.2	10 900
42.0	28.6	23.7	9 900
44.0	22.6	19.4	9 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
48.8m (160 Ft.) Boom			
8.5	82.5	50.7	103 800 *
9.0	82.0	50.7	99 100 *
10.0	80.8	50.5	89 000 *
11.0	79.6	50.3	80 400 *
12.0	78.4	50.1	73 200
13.0	77.2	49.9	65 000
14.0	76.0	49.6	57 900
15.0	74.8	49.3	52 100
16.0	73.5	49.0	47 200
18.0	71.1	48.4	39 500
20.0	68.5	47.6	33 700
22.0	66.0	46.7	29 200
24.0	63.4	45.7	25 500
26.0	60.7	44.6	22 500
28.0	57.9	43.4	20 100
30.0	55.1	42.1	17 900
32.0	52.1	40.5	16 100
34.0	49.1	38.8	14 500
36.0	45.8	37.0	13 100
38.0	42.4	34.8	11 900
40.0	38.7	32.4	10 800
42.0	34.7	29.7	9 800
44.0	30.2	26.4	8 900
46.0	25.0	22.5	8 000
48.0	18.5	17.3	7 300
51.8m (170 Ft.) Boom			
8.5	83.0	53.8	96 800 *
9.0	82.5	53.7	95 400 *
10.0	81.3	53.6	89 100 *
11.0	80.2	53.4	80 200 *
12.0	79.1	53.2	73 100 *
13.0	78.0	53.0	65 000
14.0	76.8	52.8	57 900
15.0	75.7	52.5	52 000
16.0	74.5	52.2	47 100
18.0	72.2	51.6	39 400
20.0	69.9	50.9	33 700
22.0	67.5	50.1	29 100
24.0	65.1	49.2	25 500
26.0	62.6	48.1	22 500
28.0	60.0	47.0	20 000
30.0	57.4	45.8	17 800
32.0	54.7	44.4	16 000

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
51.8m (170 Ft.) Boom			
34.0	52.0	42.8	14 400
36.0	49.1	41.1	13 000
38.0	46.0	39.3	11 800
40.0	42.8	37.2	10 700
42.0	39.4	34.8	9 700
44.0	35.7	32.1	8 800
46.0	31.6	29.1	8 000
48.0	27.0	25.4	7 200
50.0	21.5	20.8	6 600
54.9m (180 Ft.) Boom			
9.1	82.7	56.8	90 300 *
10.0	81.8	56.7	87 500 *
11.0	80.8	56.5	80 000 *
12.0	79.7	56.3	72 800 *
13.0	78.6	56.1	64 900
14.0	77.6	55.9	57 800
15.0	76.5	55.6	51 900
16.0	75.4	55.4	47 000
18.0	73.2	54.8	39 300
20.0	71.0	54.1	33 500
22.0	68.8	53.4	29 000
24.0	66.5	52.5	25 300
26.0	64.2	51.6	22 300
28.0	61.9	50.5	19 800
30.0	59.5	49.4	17 700
32.0	57.0	48.1	15 900
34.0	54.4	46.7	14 300
36.0	51.8	45.1	12 900
38.0	49.0	43.4	11 700
40.0	46.2	41.6	10 500
42.0	43.2	39.5	9 600
44.0	40.0	37.2	8 700
46.0	36.6	34.6	7 900
48.0	32.8	31.6	7 200
50.0	28.6	28.2	6 400
52.0	23.8	24.0	5 800



Liftcrane Boom Capacities

888 SERIES 1

Boom No. 22EL
65 360 kg Counterweight
8 585 mm Crawlers Extended
Rating Over Front Of Blocked Crawlers
No Travel - Limited Swing

Meets
ANSI B30.5
Requirements

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
57.9m (190 Ft.) Boom			
9.8	82.5	59.8	82 100 *
10.0	82.3	59.8	81 500 *
11.0	81.3	59.6	79 200 *
12.0	80.3	59.4	72 500 *
13.0	79.2	59.2	64 900
14.0	78.2	59.0	57 700
15.0	77.2	58.8	51 900
16.0	76.2	58.5	47 000
18.0	74.2	58.0	39 200
20.0	72.1	57.3	33 400
22.0	70.0	56.6	28 800
24.0	67.8	55.8	25 200
26.0	65.7	54.9	22 100
28.0	63.5	54.0	19 600
30.0	61.2	52.9	17 500
32.0	58.9	51.7	15 700
34.0	56.6	50.4	14 100
36.0	54.1	49.0	12 700
38.0	51.6	47.4	11 500
40.0	49.0	45.7	10 400
42.0	46.3	43.9	9 400
44.0	43.5	41.8	8 500
46.0	40.5	39.6	7 700
48.0	37.3	37.0	6 900
50.0	33.9	34.2	6 300
52.0	30.0	30.9	5 700
54.0	25.7	27.0	5 100
56.0	20.5	22.1	4 500
61.0m (200 Ft.) Boom			
9.8	82.9	62.9	77 500 *
10.0	82.7	62.8	77 000 *
11.0	81.7	62.7	74 900 *
12.0	80.7	62.5	71 900 *
13.0	79.8	62.3	64 800
14.0	78.8	62.1	57 600
15.0	77.9	61.9	51 700
16.0	76.9	61.7	46 800
18.0	75.0	61.2	39 100
20.0	73.0	60.6	33 200
22.0	71.0	59.9	28 700
24.0	69.0	59.1	25 000
26.0	67.0	58.3	22 000
28.0	64.9	57.4	19 500
30.0	62.8	56.4	17 300
32.0	60.7	55.3	15 500
34.0	58.5	54.1	13 900
36.0	56.2	52.7	12 500
38.0	53.9	51.3	11 300
40.0	51.5	49.7	10 200

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
61.0m (200 Ft.) Boom			
42.0	49.0	48.0	9 200
44.0	46.5	46.2	8 300
46.0	43.8	44.2	7 500
48.0	41.0	41.9	6 800
50.0	38.0	39.4	6 100
52.0	34.8	36.6	5 500
54.0	31.2	33.5	4 900
56.0	27.3	29.8	4 400
58.0	22.8	25.4	3 900
64.0m (210 Ft.) Boom			
10.4	82.7	65.9	71 900 *
11.0	82.1	65.8	70 800 *
12.0	81.2	65.6	69 100 *
13.0	80.3	65.4	65 000
14.0	79.4	65.2	57 500
15.0	78.5	65.0	51 600
16.0	77.5	64.8	46 700
18.0	75.7	64.3	38 900
20.0	73.8	63.7	33 100
22.0	72.0	63.1	28 500
24.0	70.1	62.4	24 900
26.0	68.1	61.6	21 900
28.0	66.2	60.7	19 400
30.0	64.2	59.8	17 200
32.0	62.2	58.8	15 400
34.0	60.1	57.6	13 800
36.0	58.0	56.4	12 400
38.0	55.9	55.1	11 200
40.0	53.7	53.6	10 100
42.0	51.4	52.0	9 100
44.0	49.0	50.3	8 200
46.0	46.6	48.5	7 400
48.0	44.1	46.5	6 700
50.0	41.4	44.3	6 000
52.0	38.6	41.8	5 400
54.0	35.6	39.1	4 800
56.0	32.3	36.1	4 300
58.0	28.7	32.6	3 800
60.0	24.6	28.5	3 300
62.0	19.7	23.4	2 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
67.1m (220 Ft.) Boom			
10.4	83.0	68.9	66 900 *
11.0	82.5	68.8	66 400 *
12.0	81.6	68.7	64 800 *
13.0	80.7	68.5	63 000
14.0	79.9	68.3	57 400
15.0	79.0	68.2	51 500
16.0	78.1	67.9	46 600
18.0	76.4	67.5	38 800
20.0	74.6	66.9	33 000
22.0	72.8	66.3	28 400
24.0	71.0	65.6	24 700
26.0	69.2	64.9	21 700
28.0	67.3	64.1	19 200
30.0	65.5	63.2	17 100
32.0	63.6	62.2	15 200
34.0	61.6	61.1	13 700
36.0	59.6	60.0	12 200
38.0	57.6	58.7	11 000
40.0	55.6	57.4	9 900
42.0	53.5	55.9	8 900
44.0	51.3	54.4	8 000
46.0	49.0	52.6	7 200
48.0	46.7	50.8	6 500
50.0	44.3	48.8	5 800
52.0	41.8	46.6	5 200
54.0	39.1	44.2	4 600
56.0	36.3	41.6	4 100
58.0	33.2	38.6	3 600
60.0	29.9	35.3	3 100
62.0	26.2	31.4	2 700
64.0	21.9	26.8	2 300



Liftcrane Boom Capacities

888 SERIES 1

Boom No. 22EL
65 360 kg Counterweight
8 585 mm Crawlers Extended
Rating Over Front Of Blocked Crawlers
No Travel - Limited Swing

 Meets
ANSI B30.5
Requirements

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
70.1m (230 Ft.) Boom			
11.0	82.8	71.9	60 500 *
12.0	82.0	71.8	60 300 *
13.0	81.1	71.6	59 400 *
14.0	80.3	71.4	57 300
15.0	79.5	71.3	51 400
16.0	78.6	71.1	46 500
18.0	77.0	70.6	38 700
20.0	75.3	70.1	32 800
22.0	73.6	69.5	28 200
24.0	71.9	68.9	24 600
26.0	70.1	68.2	21 500
28.0	68.4	67.4	19 000
30.0	66.6	66.5	16 900
32.0	64.8	65.6	15 100
34.0	63.0	64.6	13 400
36.0	61.1	63.5	12 000
38.0	59.2	62.3	10 800
40.0	57.3	61.1	9 700
42.0	55.3	59.7	8 700
44.0	53.3	58.2	7 800
46.0	51.2	56.7	7 000
48.0	49.0	54.9	6 300
50.0	46.8	53.1	5 600
52.0	44.5	51.1	5 000
54.0	42.1	48.9	4 400
56.0	39.6	46.6	3 900
58.0	36.9	44.0	3 400
60.0	34.0	41.1	2 900
62.0	30.9	37.9	2 500
64.0	27.5	34.3	2 100

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
73.2m (240 Ft.) Boom			
11.6	82.6	74.9	55 000 *
12.0	82.3	74.9	54 900 *
13.0	81.5	74.7	54 600 *
14.0	80.7	74.5	54 400 *
15.0	79.9	74.4	51 600
16.0	79.1	74.2	46 300
18.0	77.5	73.7	38 500
20.0	75.9	73.2	32 700
22.0	74.3	72.7	28 100
24.0	72.6	72.1	24 400
26.0	71.0	71.4	21 400
28.0	69.3	70.7	18 800
30.0	67.6	69.8	16 700
32.0	65.9	69.0	14 800
34.0	64.2	68.0	13 300
36.0	62.4	67.0	11 900
38.0	60.6	65.9	10 600
40.0	58.8	64.7	9 500
42.0	56.9	63.4	8 500
44.0	55.0	62.0	7 600
46.0	53.1	60.5	6 800
48.0	51.1	59.0	6 100
50.0	49.0	57.2	5 400
52.0	46.9	55.4	4 800
54.0	44.7	53.4	4 200
56.0	42.4	51.3	3 700
58.0	40.0	49.0	3 200
60.0	37.5	46.4	2 800
62.0	34.8	43.6	2 300
64.0	31.9	40.5	1 900

Oper. Rad. Meters	Boom Ang. Deg.	Boom Point Elev. Meters	Boom Capacity Kilograms
76.2m (250 Ft.) Boom			
11.6	82.9	78.0	49 900 *
12.0	82.6	77.9	49 800 *
13.0	81.9	77.8	49 600 *
14.0	81.1	77.6	49 400 *
15.0	80.3	77.5	49 100 *
16.0	79.6	77.3	47 100
18.0	78.0	76.9	38 700
20.0	76.5	76.4	32 700
22.0	74.9	75.9	28 200
24.0	73.4	75.3	24 500
26.0	71.8	74.6	21 500
28.0	70.2	73.9	18 900
30.0	68.6	73.1	16 800
32.0	66.9	72.3	14 900
34.0	65.3	71.4	13 300
36.0	63.6	70.4	12 000
38.0	61.9	69.4	10 700
40.0	60.2	68.2	9 600
42.0	58.4	67.0	8 600
44.0	56.6	65.7	7 700
46.0	54.8	64.3	6 900
48.0	52.9	62.8	6 200
50.0	51.0	61.3	5 500
52.0	49.0	59.5	4 900
54.0	47.0	57.7	4 300
56.0	44.9	55.7	3 800
58.0	42.7	53.6	3 300
60.0	40.4	51.3	2 900
62.0	38.0	48.8	2 400
64.0	35.4	46.1	2 000