



Wire Rope Specifications 15000 SERIES 1, 2, 3, 4

Liftcrane - Boom No. 57

European
Standards

Wire Rope Lengths								
Boom or Boom and Jib Length		Whip Line Front or Auxiliary Drum				Hoist Line Rear Drum		Maximum Required Parts of Line
		1 Part		2 Part				
Ft.	Meters	Ft.	Meters	Ft.	Meters	Ft.	Meters	
70.5	21.5	180	55	270	82	1325	404	16
80.4	24.5	200	61	300	91	1500	457	16
90.2	27.5	220	67	330	101	1575	480	15
100.1	30.5	240	73	360	110	1625	495	14
109.9	33.5	260	79	390	119	1650	503	13
119.8	36.5	280	85	420	128	1800	549	13
129.6	39.5	300	91	450	137	1800	549	12
139.4	42.5	320	98	480	146	1800	549	11
149.3	45.5	340	104	500	152	1800	549	10
159.1	48.5	360	110	530	162	1825	556	10
169.0	51.5	380	116	560	171	1825	556	9
178.8	54.5	400	122	590	180	1825	556	8
188.7	57.5	420	128	620	189	1825	556	8
198.5	60.5	440	134	650	198	1825	556	7
208.3	63.5	460	140	680	207	1825	556	7
218.2	66.5	480	146	710	216	1825	556	6
228.0	69.5	500	152	740	226	1825	556	6
237.9	72.5	520	158	770	235	1825	556	5
247.7	75.5	540	165	800	244	1825	556	4
257.6	78.5	560	171	830	253	1825	556	4
267.4	81.5	580	177	860	262	1825	556	4
277.2	84.5	600	183	890	271	1825	556	4
287.1	87.5	620	189	920	280	1825	556	3
297.0	90.5	640	195	950	290			
306.8	93.5	660	201	980	299			
316.6	96.5	680	207	1010	308			
326.4	99.5	700	213	1040	317			
336.3	102.5	720	219					

Note: Hoist line and whip line lengths given in table will allow hook to touch ground. When block travel below ground is required, add additional rope equal to parts of line times added travel distance. Hoisting distance or line pull may be limited when block travel below ground is required.



Wire Rope Specifications 15000 SERIES 1, 2, 3, 4

Liftcrane - Boom No. 57

European
Standards

Hoist Reeving for Main Load Block								
No. Parts of Line	1	2	3	4	5	6	7	8
Maximum Load Lbs.	29,500	59,000	88,500	118,000	147,500	177,000	206,500	236,000
Maximum Load kg	13 380	26 760	40 140	53 520	66 900	80 290	93 670	107 050
No. Parts of Line	9	10	11	12	13	14	15	16
Maximum Load Lbs.	265,500	295,000	324,500	354,000	383,500	413,000	442,500	500,000
Maximum Load kg	120 430	133 810	147 190	160 570	173 950	187 330	200 720	226 700

Maximum Spooling Capacities	
Rear Drum: (Hoist Line)	26 mm Wire Rope - 7 Layers - 1,727 Ft. (526m)
Front Drum: (Whip Line)	26 mm Wire Rope - 7 Layers - 1,727 Ft. (526m)
Auxiliary Drum: (Whip Line)	26 mm Wire Rope - 6 Layers - 1,323 Ft. (403m) 6 Layers - 1,415 Ft. (431m) with 21-1/4 in. (540 mm) Dia. Lagging
17 Ft. (5m) is deducted from maximum spooling capacities for 3 dead wraps per drum or lagging.	

Note: When optional laggings are used, the recommended lagging for specific wire rope dia. must be used.

Refer to drum and lagging chart **No. 8613-A**.

Wire Rope Specifications 15000 SERIES 1, 2, 3, 4

Liftcrane - Boom No. 57

European
Standards

Wire Rope Specifications

Rotation Resistant Wire Rope

Hoist Line: 26 mm - 2 160 N/mm² Wire Rope With Pad Eye (MCC Part No. 719430)
Right Hand Regular Lay
Minimum Breaking Strength = 161,200 Lbs. (717.0 kN)
Approx. Weight = 2.13 Lbs Per Ft. (3.17 kg/m)
No Load Dia. = 1.033 in. (26.24 mm) to 1.045 in. (26.54 mm)

Or

26 mm - Wire Rope With Pad Eye (MCC Part No. 719432)
Right Hand Lang Lay
Minimum Breaking Strength = 156,400 Lbs. (695.7 kN)
Approx. Weight = 2.39 Lbs Per Ft. (3.56 kg/m)
No Load Dia. = 1.034 in. (26.26 mm) to 1.054 in. (26.77 mm)

Whip Line: 26 mm - 2 160 N/mm² Wire Rope With Pad Eye (MCC Part No. 719430)
Right Hand Regular Lay
Minimum Breaking Strength Required = 147,500 Lbs. (656.1 kN)
Maximum Load = 29,500 Lbs. (13 380 kg) Per Line
Approx. Weight = 2.13 Lbs Per Ft. (3.17 kg/m)
No Load Dia. = 1.033 in. (26.24 mm) to 1.045 in. (26.54 mm)

Or

26 mm - Wire Rope With Pad Eye (MCC Part No. 719432)
Right Hand Lang Lay
Minimum Breaking Strength Required = 147,500 Lbs. (656.1 kN)
Maximum Load = 29,500 Lbs. (13 380 kg) Per Line
Approx. Weight = 2.39 Lbs Per Ft. (3.56 kg/m)
No Load Dia. = 1.034 in. (26.26 mm) to 1.054 in. (26.77 mm)

Auxiliary Line: 26 mm - 1 960 N/mm² Wire Rope (MCC Part No. 719378)
Right Hand Regular Lay
Minimum Breaking Strength Required = 100,000 Lbs. (445.0 kN)
Maximum Load = 20,000 Lbs. (9 070 kg) Per Line
Approx. Weight = 2.13 Lbs. Per Ft. (3.17 kg/m)
No Load Dia. (required for lagging) = 1.033 in. (26.24 mm) to 1.045 in. (26.54 mm)

Or

26 mm - Wire Rope With Pad Eye (MCC Part No. 719432)
Right Hand Lang Lay
Minimum Breaking Strength Required = 100,000 Lbs. (445.0 kN)
Maximum Load = 20,000 Lbs. (9 070 kg) Per Line
Approx. Weight = 2.39 Lbs. Per Ft. (3.56 kg/m)
No Load Dia. (required for lagging) = 1.034 in. (26.26 mm) to 1.054 in. (26.77 mm)